

## Power reduction mechanism verification

According to the May 2017 TCBC Workshop, Demonstration of proper functioning of the detection and triggering mechanisms is required to support the corresponding RF exposure conditions. The verification is through a base station simulator is used to establish a conducted RF connection and monitor output power under different operating conditions related to the power reduction mechanisms. Detail of power reduction mechanisms referring to Operational Description

### 1. Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

#### General Note:

1. This device uses different Exposure Condition Index (ECI) to configure different time averaged power levels based on certain exposure scenarios is , as the following table:

Exposure Condition	ECI	Ant	Trigger conditions
Head SAR	ECI2	All Ant	Earpiece On
Hotspot SAR	ECI7	All Ant	Hotspot On
Body worn/ Extremity SAR	ECI4	Ant 2/7/8	receiver off
Body worn/ Extremity SAR	ECI4	Ant 0/1/4/5	Sensor Off
Body worn SAR	ECI3	All Ant	Sensor On
Extremity SAR	ECI10	Ant 0	Sensor On
Extremity SAR	ECI11	Ant 1	Sensor On
Extremity SAR	ECI12	Ant 4	Sensor On
Extremity SAR	ECI13	Ant 5	Sensor On

2. Select the bands with the largest power reduction for power verification :
  - a. Establish voice call and audio routed through the earpiece to monitor output power under head power states.
    - Tradition voice call for GSM/WCDMA, voice over IP CMRS operations for LTE/5G FR1
    - GSM1900 is set to GPRS 4TX slot, LTE Band 25 is set at 'highest BW, 1RB, RB Offset = 0, QPSK', WCDMA IV is set AMR 12.2Kbps, 5G FR1 n25 is set at highest BW, 1RB, RB offset = 1.
  - b. Establish data connection monitor hotspot power state.
    - GSM1900 is set to GPRS 4TX slot, LTE Band 25 is set at 'highest BW, 1RB, RB Offset = 0, QPSK', WCDMA IV is set RMC 12.2Kbps, 5G FR1 n25 is set at highest BW, 1RB, RB offset = 1.
  - c. Establish data connection monitor body worn power state.
    - GSM1900 is set to GPRS 4TX slot, LTE Band 25 is set at 'highest BW, 1RB, RB Offset = 0, QPSK' WCDMA IV is set RMC 12.2Kbps, 5G FR1 n25 is set at highest BW, 1RB, RB offset = 1.
    - Body Detect mechanism was performed for the in-hand and on a stationary object (placed on a table)
  - d. Establish data connection monitor extremity power state.
    - GSM1900 is set to GPRS 4TX slot, LTE Band 25 is set at 'highest BW, 1RB, RB Offset = 0, QPSK' WCDMA IVI is set RMC 12.2Kbps. 5G FR1 n25 is set at highest BW, 1RB, RB offset = 1.
    - Body Detect mechanism was performed for the in-hand and on a stationary object (placed on a table).
2. In this power validation purpose is to demonstrate of proper functioning of the detection and triggering mechanisms to support the corresponding RF exposure conditions.
3. Verification performed for one technology/Band to demonstrate that the power reduction applies for same technology/band and call origination.

## 2. Verification output Power Results

### Head exposure conditions

Ear acoustic output Status:		OFF		ON	
Power state		WWAN ECI4		WWAN ECI2	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (GPRS 4 TX slots)	Ant 0	26.12	26.5	25.88	26.5
WCDMA IV	Ant 0	23.28	24	23.31	24
LTE Band 25	Ant 4	23.29	24	15.85	16.5
FR1 n25	Ant 4	23.19	24	14.21	15

### Hotspot exposure condition

Hotspot output Status:		OFF		ON	
Power state		WWAN ECI4		WWAN ECI7	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (GPRS 4 TX slots)	Ant 0	26.12	26.5	20.68	21.5
WCDMA IV	Ant 0	23.28	24	17.35	18.5
LTE Band 25	Ant 4	23.29	24	13.18	14
FR1 n25	Ant 4	23.19	24	15.23	16

### Body worn exposure condition

Sensor output Status:		OFF		ON	
Power state		WWAN ECI4		WWAN ECI3	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (GPRS 4 TX slots)	Ant 0	26.12	26.5	22.07	23
WCDMA IV	Ant 0	23.28	24	18.46	19.5
LTE Band 25	Ant 4	23.29	24	16.03	17
FR1 n25	Ant 4	23.19	24	18.15	19

### Extremity exposure condition

Sensor output Status:		OFF		ON	
Power state		WWAN ECI4		WWAN ECI10	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (GPRS 4 TX slots)	Ant 0	26.12	26.5	24.67	25.5
WCDMA IV	Ant 0	23.28	24	21.47	22.5

Sensor output Status:		OFF		ON	
Power state		WWAN ECI4		WWAN ECI12	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
LTE Band 25	Ant 4	23.29	24	19.1	20
FR1 n25	Ant 4	23.19	24	20.76	21.5