




**MOTOROLA**

**Exhibit 11: Class II Permissive Change SAR Test Report**

**Test Report #:** 21549-2F  
**Date of Report:** 21-Mar-2008  
**Date of Test:** 22-Feb-2008 ~ 20-Mar-2008  
**FCC ID #:** **IHDT56HP1**  
**Generic Name:** **MUQ6-34411D11**  
**Laboratory:** Motorola Mobile Devices Business Product Safety & Compliance Laboratory  
 11th Floor, Hibrand Living Hall,  
 215, Yanjae-Dong, Seocho-Gu, Seoul, South Korea, 137-130

**Report Author:** Brian Lee  
 RF Engineer  


This laboratory is accredited to ISO/IEC 17025-2005 to perform the following tests:

**Accreditation:**



TESTING CERT #2518-03

|  |   |
|--|---|
| <u>Tests:</u>                            | <u>Procedures:</u>                                    |
| Electromagnetic Specific Absorption Rate | IEC 62209-1   |
|  | RSS-102   |
|  | IEEE 1528 - 2003                                      |
|  | FCC OET Bulletin 65 ( <i>including Supplement C</i> ) |
|  | Australian Communications Authority Radio             |
|  | Communications (Electromagnetic Radiation – Human     |
|  | Exposure) Standard 2003                               |
|  | CENELEC EN 50360 (2001)                               |
|  | CENELEC EN 50361 (2001)                               |
|  | ARIB Std. T-56 (2002)                                 |

On the following products or types of products:

On the following products or types of products: Wireless Communications Devices (Examples): Two Way Radios; Portable Phones (including Cellular, Licensed Non-Broadcast and PCS); Low Frequency Readers; and Pagers

**Statement of Compliance:**

Motorola declares under its sole responsibility that the portable cellular telephone model to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines (FCC 47 CFR §2.1093) as well as with CENELEC en50360:2001 and ANSI / IEEE C95.1. It also declares that the product was tested in accordance with IEEE 1528 / CENELEC EN62209-1 (2006), as well as other appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below:

(none)

©Motorola, Inc. 2007

This test report shall not be reproduced except in full, without written approval of the laboratory.

The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report.

Motorola encourages all feedback, both positive and negative, on this test report.

## Table of Contents

|   |           |
|---|-----------|
| <b>1. Introduction</b>  | <b>2</b>  |
| <b>2. Description of the Device Under Test</b>                                  | <b>3</b>  |
| <i>2.1 Antenna description</i>  | 3         |
| <i>2.2 Device description</i>   | 3         |
| <b>3. Test Equipment Used</b>   | <b>4</b>  |
| <i>3.1 Dosimetric System</i>  | 4         |
| <i>3.2 Additional Equipment</i>   | 4         |
| <b>4. Electrical parameters of the tissue simulating liquid</b>                 | <b>5</b>  |
| <b>5. System Accuracy Verification</b>  | <b>6</b>  |
| <b>6. Test Results</b>  | <b>7</b>  |
| <i>6.1 Head Adjacent Test Results</i>   | 7         |
| <i>6.2 Body Worn Test Results</i>   | 16        |
| <b>References</b>   | <b>21</b> |
| <b>Appendix 1: SAR distribution comparison for system accuracy verification</b> | <b>22</b> |
| <b>Appendix 2: SAR distribution plots for Phantom Head Adjacent Use</b>         | <b>23</b> |
| <b>Appendix 3: SAR distribution plots for Body Worn Configuration</b>           | <b>24</b> |
| <b>Appendix 4: Probe Calibration Certificate</b>                                | <b>25</b> |
| <b>Appendix 5: Measurement Uncertainty Budget</b>                               | <b>26</b> |
| <b>Appendix 6: Photographs of the device under test</b>                         | <b>28</b> |
| <b>Appendix 7: Dipole Characterization Certificate</b>                          | <b>33</b> |

## **1. Introduction**

The Motorola Mobile Devices Business Product Safety Laboratory has performed measurements of the maximum potential exposure to the user of the portable cellular phone covered by this test report. The Specific Absorption Rate (SAR) of this product was measured. The portable cellular phone was tested in accordance with [1], [4] and [5]. The SAR values measured for the portable cellular phone are below the maximum recommended levels of 1.6 W/kg in a 1g average set in [3] and 2.0W/kg in a 10g average set in [2].

For ANSI / IEEE C95.1 (1g), the final SAR reading for this phone is 1.39 W/kg for head adjacent use and 0.62 W/kg for body worn use. These measurements were performed using a Dasy4™ v4.7 system manufactured by Schmid & Partner Engineering AG (SPEAG), of Zurich Switzerland.

**2. Description of the Device Under Test**

**2.1 Antenna description**

|                      |                       |         |
|----------------------|-----------------------|---------|
| <b>Type</b>          | Internal Antenna      |         |
| <b>Location</b>      | Bottom of transceiver |         |
| <b>Dimensions</b>    | Length                | 32.0 mm |
|                      | Width                 | 7.0 mm  |
| <b>Configuration</b> | FJA                   |         |

**2.2 Device description**

|   |                                   |                   |                     |                     |                     |                     |
|---|-----------------------------------|-------------------|---------------------|---------------------|---------------------|---------------------|
| <b>Serial Number</b>  | <b>TA10005LZ</b>                  |                   |                     |                     |                     |                     |
| <b>Mode(s) of Operation</b>                                   | GSM 850                           | GSM 900           | GSM 1800            | GSM 1900            | UMTS 2100           | Bluetooth           |
| <b>Modulation Mode(s)</b>                                     | GMSK                              | GMSK              | GMSK                | GMSK                | QPSK                | GFSK                |
| <b>Maximum Output Power Setting</b>                           | 32.50 dBm                         | 33.00 dBm         | 30.00 dBm           | 29.50 dBm           | 24.00 dBm           | 4.0 dBm             |
| <b>Duty Cycle</b>   | 1:8                               | 1:8               | 1:8                 | 1:8                 | 1:1                 | 1:1                 |
| <b>Transmitting Frequency Range(s)</b>                        | 824.2 - 848.8 MHz                 | 880.2 - 914.8 MHz | 1710.2 - 1784.8 MHz | 1850.2 - 1909.8 MHz | 1922.4 - 1977.6 MHz | 2400.0 - 2483.5 MHz |
| <b>Production Unit or Identical Prototype (47 CFR §2.908)</b> | Identical Prototype               |                   |                     |                     |                     |                     |
| <b>Device Category</b>  | Portable                          |                   |                     |                     |                     |                     |
| <b>RF Exposure Limits</b>                                     | General Population / Uncontrolled |                   |                     |                     |                     |                     |

|  |                   |                  |           |           |                   |                  |           |           |                     |                  |           |           |                     |                 |           |           |
|--|-------------------|------------------|-----------|-----------|-------------------|------------------|-----------|-----------|---------------------|------------------|-----------|-----------|---------------------|-----------------|-----------|-----------|
| <b>Mode(s) of Operation</b>            | GPRS 850          |                  |           |           | GPRS 900          |                  |           |           | GPRS 1800           |                  |           |           | GPRS 1900           |                 |           |           |
| <b>Modulation Mode(s)</b>              | GMSK              |                  |           |           | GMSK              |                  |           |           | GMSK                |                  |           |           | GMSK                |                 |           |           |
| <b>Maximum Output Power Setting</b>    | 32.50 dBm         | <b>30.60 dBm</b> | 28.60 dBm | 26.70 dBm | 33.00 dBm         | <b>31.07 dBm</b> | 29.14 dBm | 27.21 dBm | 30.00 dBm           | <b>28.27 dBm</b> | 26.53 dBm | 24.80 dBm | 29.50 dBm           | <b>27.6 dBm</b> | 25.60 dBm | 23.70 dBm |
| <b>Duty Cycle</b>                      | 1:8               | <b>2:8</b>       | 3:8       | 4:8       | 1:8               | <b>2:8</b>       | 3:8       | 4:8       | 1:8                 | <b>2:8</b>       | 3:8       | 4:8       | 1:8                 | <b>2:8</b>      | 3:8       | 4:8       |
| <b>Transmitting Frequency Range(s)</b> | 824.2 - 848.8 MHz |                  |           |           | 880.2 - 914.8 MHz |                  |           |           | 1710.2 - 1784.8 MHz |                  |           |           | 1850.2 - 1909.8 MHz |                 |           |           |

|  |                   |                  |           |           |                   |                  |           |           |                     |                  |           |           |                     |                  |           |           |
|--|-------------------|------------------|-----------|-----------|-------------------|------------------|-----------|-----------|---------------------|------------------|-----------|-----------|---------------------|------------------|-----------|-----------|
| <b>Mode(s) of Operation</b>            | EDGE 850          |                  |           |           | EDGE 900          |                  |           |           | EDGE 1800           |                  |           |           | EDGE 1900           |                  |           |           |
| <b>Modulation Mode(s)</b>              | 8PSK              |                  |           |           | 8PSK              |                  |           |           | 8PSK                |                  |           |           | 8PSK                |                  |           |           |
| <b>Maximum Output Power Setting</b>    | 27.50 dBm         | <b>25.70 dBm</b> | 23.90 dBm | 22.00 dBm | 27.50 dBm         | <b>25.59 dBm</b> | 23.68 dBm | 21.77 dBm | 26.50 dBm           | <b>24.73 dBm</b> | 22.96 dBm | 21.19 dBm | 26.50 dBm           | <b>24.50 dBm</b> | 22.50 dBm | 20.50 dBm |
| <b>Duty Cycle</b>                      | 1:8               | <b>2:8</b>       | 3:8       | 4:8       | 1:8               | <b>2:8</b>       | 3:8       | 4:8       | 1:8                 | <b>2:8</b>       | 3:8       | 4:8       | 1:8                 | <b>2:8</b>       | 3:8       | 4:8       |
| <b>Transmitting Frequency Range(s)</b> | 824.2 - 848.8 MHz |                  |           |           | 880.2 - 914.8 MHz |                  |           |           | 1710.2 - 1784.8 MHz |                  |           |           | 1850.2 - 1909.8 MHz |                  |           |           |

**Note: Bolded entries indicate data mode of highest time-average power per band and data mode type.**

### 3. Test Equipment Used

#### 3.1 Dosimetric System

The Motorola Mobile Devices Business Product Safety & Compliance Laboratory utilizes a Dosimetric Assessment System (Dasy4™ v4.7) manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. All the SAR measurements are taken within a shielded enclosure. The overall 10g RSS uncertainty of the measurement system is ±10.8% (K=1) with an expanded uncertainty of ±21.6% (K=2). The overall 1g RSS uncertainty of the measurement system is ±11.1% (K=1) with an expanded uncertainty of ±22.2% (K=2). The measurement uncertainty budget is given in Appendix 6. Per IEEE 1528, this uncertainty budget is applicable to the SAR range of 0.4W/kg to 10W/kg.

The list of calibrated equipment used for the measurements is shown in the following table.

| Description                               | Serial Number | Cal Due Date |
|---|---------------|--------------|
| DASY4™ DAE V1                             | SN365         | 18-Sep-2008  |
| E-Field Probe ETDV6R                      | SN1391        | 24-Sep-2008  |
| Dipole Validation Kit, DV900V2            | 77            | 01-May-2008  |
| S.A.M. Phantom used for 800/900MHz        | TP-1155       |              |
| Dipole Validation Kit, DV1800V2           | 280tr         | 01-May-2008  |
| S.A.M. Phantom used for 1800/1900MHz      | TP-1086       |              |
| DASY4™ DAE V1                             | SN383         | 24-Aug-2008  |
| E-Field Probe ETDV6R                      | SN1515        | 28-Aug-2008  |
| S.A.M. Phantom used for 800/900MHz        | TP-1129       |              |
| S.A.M. Phantom used for 1800/1900/2450MHz | TP-1134       |              |
| Dipole Validation Kit, DV900V2            | 97            | 01-May-2008  |
| Dipole Validation Kit, DV1800V2           | 277tr         | 01-May-2008  |
| Dipole Validation Kit, D2450V2            | 767           | 01-May-2008  |

#### 3.2 Additional Equipment

| Description                   | Serial Number | Cal Due Date |
|-------------------------------|---------------|--------------|
| Signal Generator HP8648C      | 3847A04630    | 28-Jan-2009  |
| Power Meter E4419B            | US39250623    | 28-Jan-2009  |
| Power Sensor #1 - 8481A       | US37296472    | 29-Jan-2009  |
| Power Sensor #2 - 8481A       | 3318A86935    | 29-Jan-2009  |
| Network Analyzer HP8753ES     | US39172714    | 28-Jan-2009  |
| Dielectric Probe Kit HP85070B | US99360207    |              |
| Signal Generator HP8648C      | 3847A04840    | 28-Jan-2009  |
| Power Meter E4419B            | GB39511085    | 28-Jan-2009  |
| Power Sensor #1 - 8481A       | MY41095450    | 28-Jan-2009  |
| Power Sensor #2 - 8481A       | 2702A82671    | 28-Jan-2009  |

**4. Electrical parameters of the tissue simulating liquid**

Prior to conducting SAR measurements, the relative permittivity,  $\epsilon_r$ , and the conductivity,  $\sigma$ , of the tissue simulating liquids were measured with a HP85070 Dielectric Probe Kit. These values, along with the temperature of the simulated tissue are shown in the table below. The recommended limits for permittivity and conductivity are also shown. A mass density of  $\rho=1\text{g/cm}^3$  was entered into the system in all the cases. It can be seen that the measured parameters are within tolerance of the recommended limits specified in [1] and [5].

| f (MHz) | Tissue type | Limits / Measured     | Dielectric Parameters |                |           |
|---------|-------------|-----------------------|-----------------------|----------------|-----------|
|         |             |                       | $\epsilon_r$          | $\sigma$ (S/m) | Temp (°C) |
| 835     | Head        | Measured, 22-Feb-2008 | 41.7                  | 0.9            | 21.1      |
|         |             | Measured, 25-Feb-2008 | 41.3                  | 0.9            | 20.5      |
|         |             | Measured, 29-Feb-2008 | 42.6                  | 0.92           | 21.5      |
|         |             | Recommended Limits    | 41.5 ±5%              | 0.90 ±5%       | 18-25     |
|         | Body        | Measured, 25-Feb-2008 | 55.3                  | 0.98           | 20.5      |
|         |             | Recommended Limits    | 55.2 ±5%              | 0.97 ±5%       | 18-25     |
| 1880    | Head        | Measured, 22-Feb-2008 | 39.5                  | 1.45           | 20.8      |
|         |             | Measured, 25-Feb-2008 | 39.3                  | 1.46           | 20.6      |
|         |             | Measured, 26-Feb-2008 | 39.3                  | 1.46           | 20.7      |
|         |             | Recommended Limits    | 40.0 ±5%              | 1.40 ±5%       | 18-25     |
|         | Body        | Measured, 22-Feb-2008 | 53.7                  | 1.57           | 21.2      |
|         |             | Recommended Limits    | 53.3 ±5%              | 1.52 ±5%       | 18-25     |
| 2450    | Body        | Measured, 20-Mar-2008 | 51.6                  | 2.04           | 20.8      |
|         |             | Recommended Limits    | 52.7 ±10%             | 1.95 ±5%       | 18-25     |

The list of ingredients and the percent composition used for the tissue simulates are indicated in the table below.

| Ingredient | 835MHz / 900 MHz | 835MHz / 900 MHz | 1800MHz / 1900 MHz | 1800 MHz / 1900 MHz | 2450MHz | 2450 MHz |
|------------|------------------|------------------|--------------------|---------------------|---------|----------|
|            | Head             | Body             | Head               | Body                | Head    | Body     |
| Sugar      | 57               | 44.9             | --                 | --                  | --      | --       |
| DGBE       | --               | --               | 47                 | 30.8                | --      | 30       |
| Diacetin   | --               | --               | --                 | --                  | 51      | --       |
| Water      | 40.45            | 53.06            | 52.62              | 68.8                | 48.75   | 70       |
| Salt       | 1.45             | 0.94             | 0.38               | 0.4                 | 0.15    | --       |
| HEC        | 1                | 1                | --                 | --                  | --      | --       |
| Bact.      | 0.1              | 0.1              | --                 | --                  | 0.1     | --       |

**5. System Accuracy Verification**

A system accuracy verification of the DASY4™ was performed using the measurement equipment listed in Section 3.1. The daily system accuracy verification occurs within the flat section of the SAM phantom.

A SAR measurement was performed to verify the measured SAR was within ±10% from the target SAR indicated in Section 8.3.7 Reference SAR Values in [5] or Appendix 7 for the 900 MHz and 1800MHz target reference SAR value. These tests were done at 900MHz and 1800MHz. These frequencies are within ±10% of the compliance test mid-band frequency as required in [1] and [5]. The test was conducted on the same days as the measurement of the DUT. Recommended limits for permittivity and conductivity, specified in [5], are shown in the table below. The obtained results from the system accuracy verification are also displayed in the table below. SAR values are normalized to 1W forward power delivered to the dipole. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values. The distributions of SAR compare well with those of the reference measurements (see Appendix 1). The tissue stimulant depth was verified to be 15.0cm ±0.5cm. Z-axis scans showing the SAR penetration are also included in Appendix 1.

| f (MHz) | Description           | SAR (W/kg), 1gram | Dielectric Parameters |                | Ambient Temp (°C) | Tissue Temp (°C) |
|---------|-----------------------|-------------------|-----------------------|----------------|-------------------|------------------|
|         |                       |                   | $\epsilon_r$          | $\sigma$ (S/m) |                   |                  |
| 900     | Measured, 22-Feb-2008 | 11.78             | 41.0                  | 0.97           | 20.7              | 21.1             |
|         | Measured, 25-Feb-2008 | 11.45             | 40.5                  | 0.97           | 21.0              | 20.9             |
|         | Measured, 29-Feb-2008 | 11.58             | 41.9                  | 0.98           | 20.8              | 20.9             |
|         | Recommended Limits    | 11.24             | 41.5 ±5%              | 0.97 ±5%       | 18-25             | 18-25            |
| 1800    | Measured, 21-Feb-2008 | 36.93             | 39.8                  | 1.36           | 21.3              | 21.1             |
|         | Measured, 22-Feb-2008 | 37.95             | 39.6                  | 1.38           | 20.6              | 20.8             |
|         | Measured, 25-Feb-2008 | 37.30             | 39.6                  | 1.38           | 20.6              | 21.1             |
|         | Measured, 26-Feb-2008 | 37.58             | 39.5                  | 1.38           | 21.3              | 21.0             |
|         | Recommended Limits    | 37.5              | 40.0 ±5%              | 1.4 ±5%        | 18-25             | 18-25            |
| 2450    | Measured, 20-Mar-2008 | 53.75             | 37.2                  | 1.85           | 21.5              | 22.1             |
|         | Recommended Limits    | 58.0              | 39.2 ±10%             | 1.80 ±5%       | 18-25             | 18-25            |

The following probe conversion factors were used on the E-Field probe(s) used for the system accuracy verification measurements:

| Description           | Serial Number | f (MHz) | Conversion Factor | Cal Cert pg # |
|-----------------------|---------------|---------|-------------------|---------------|
| E-Field Probe ET3DV6R | SN1391        | 900     | 5.97              | 8 of 9        |
|                       |               | 1810    | 4.96              | 8 of 9        |
| E-Field Probe ET3DV6  | SN1515        | 900     | 6.50              | 8 of 9        |
|                       |               | 1810    | 5.21              | 8 of 9        |
|                       |               | 2450    | 4.64              | 8 of 9        |

## 6. Test Results

The test sample was operated using an actual transmission through a base station simulator. The base station simulator was setup to the proper channel, transmitter power level and transmit mode of operation. The phone was tested in the configurations stipulated in [1], [4] and [5]. The phone was positioned into these configurations using the device holder supplied with the DASY4™ SAR measurement system. The measured dielectric constant of the material used for the device holder is less than 2.9 and the loss tangent is less than 0.02 ( $\pm 30\%$ ) at 850MHz. The default settings for the “coarse” and “cube” scans were chosen and used for measurements. The grid spacing of the course scan was set to 15cm as shown in the SAR plots included in Appendix 2 and 3. Please refer to the DASY4™ manual for additional information on SAR scanning procedures and algorithms used.

The Cellular Phone model covered by this report has the following battery options:

SNN5792A - 1100 mAH Battery

SNN5784A - 880 mAH Battery

SNN5779B - 750 mAH Battery

The battery with the highest capacity is the SNN5792A. This battery was used to do most of the SAR testing. The phone was placed in the SAR measurement system with a fully charged battery. The configuration that resulted in the highest SAR values were tested using the other batteries listed above.

### 6.1 Head Adjacent Test Results

The SAR results shown in tables 1 through 16 are maximum SAR values averaged over 1 gram of phantom tissue, to demonstrate compliance to [3] and also over 10 grams of phantom tissue, to demonstrate compliance to the [6]. Also shown are the measured conducted output power levels, the temperature of the simulated tissue after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is  $\text{New SAR} = \text{Old SAR} * 10^{(-\text{drift}/10)}$ . The SAR reported at the end of the measurement process by the DASY4™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test.

The left head and right head SAR contour distributions are similar. Because of this similarity, the cheek/touch and 15° tilt test conditions with the highest SAR values in each band are indicated as bold numbers in the following tables and are included in Appendix 2. All other test conditions measured lower SAR values than those included in Appendix 2.

The SAR measurements were performed using the SAM phantoms listed in section 3.1. Since the same phantoms and simulated tissue were used for the system accuracy verification and the device SAR measurements, the Z-axis scans included in Appendix 1 are applicable for verification of simulated tissue depth to be 15.0cm  $\pm$ 0.5cm.

The following probe conversion factors were used on the E-Field probe(s) used for the head adjacent measurements:

| Description              | Serial Number | f (MHz) | Conversion Factor | Cal Cert pg # |
|--------------------------|---------------|---------|-------------------|---------------|
| E-Field Probe<br>ET3DV6R | SN1391        | 900     | 5.97              | 8 of 9        |
|                          |               | 1810    | 4.96              | 8 of 9        |



| Left Head Cheek Position (Slider Closed) |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                        | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                            | Channel 128 | 32.63                                 | 21.3         | -0.02         | 0.788                | 0.79                   | 1.15                | 1.16                   |
|  | Channel 190 | 32.52                                 | 21.5         | 0.00          | 0.854                | 0.85                   | 1.26                | 1.26                   |
|  | Channel 251 | 32.60                                 | <b>21.1</b>  | <b>0.03</b>   | <b>0.92</b>          | <b>0.92</b>            | <b>1.39</b>         | <b>1.39</b>            |
| GSM<br>1900MHz                           | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | 21.8         | -0.02         | 0.365                | 0.37                   | 0.647               | 0.65                   |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

**Table 1: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.**

| Right Head Cheek Position (Slider Closed) |             |                                       |              |               |                      |                        |                     |                        |
|---|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                         | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|   |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                             | Channel 128 | 32.63                                 | 20.4         | -0.04         | 0.761                | 0.77                   | 1.07                | 1.08                   |
|   | Channel 190 | 32.52                                 | 20.4         | -0.03         | 0.834                | 0.84                   | 1.18                | 1.19                   |
|   | Channel 251 | 32.60                                 | 20.4         | 0.01          | 0.891                | 0.89                   | 1.26                | 1.26                   |
| GSM<br>1900MHz                            | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|   | Channel 661 | 29.56                                 | 20.8         | -0.04         | 0.299                | 0.30                   | 0.497               | 0.50                   |
|   | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

**Table 2: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.**

| Highest Head Cheek (Slider Closed) with SNN5784A |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                                | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                                    | Channel 128 | 32.63                                 |              |               |                      |                        |                     |                        |
|  | Channel 190 | 32.52                                 |              |               |                      |                        |                     |                        |
|  | Channel 251 | 32.60                                 | 20.7         | -0.01         | 0.838                | 0.84                   | 1.23                | 1.23                   |
| GSM<br>1900MHz                                   | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | 21.0         | 0.01          | 0.363                | 0.36                   | 0.652               | 0.65                   |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

**Table 3: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.**

| Highest Head Cheek (Slider Closed) with SNN5779B |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                                | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                                    | Channel 128 | 32.63                                 |              |               |                      |                        |                     |                        |
|  | Channel 190 | 32.52                                 |              |               |                      |                        |                     |                        |
|  | Channel 251 | 32.60                                 | 20.5         | -0.01         | 0.896                | 0.90                   | 1.32                | 0.32                   |
| GSM<br>1900MHz                                   | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | <b>20.6</b>  | <b>0.01</b>   | <b>0.369</b>         | <b>0.37</b>            | <b>0.663</b>        | <b>0.66</b>            |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

**Table 4: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.**

| Left Head Cheek Position (Slider Open) |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                      | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                          | Channel 128 | 32.63                                 | 20.6         | -0.02         | 0.651                | 0.65                   | 0.902               | 0.91                   |
|  | Channel 190 | 32.52                                 | 20.7         | -0.02         | 0.692                | 0.70                   | 0.966               | 0.97                   |
|  | Channel 251 | 32.60                                 | <b>20.6</b>  | <b>-0.02</b>  | <b>0.766</b>         | <b>0.77</b>            | <b>1.07</b>         | <b>1.07</b>            |
| GSM<br>1900MHz                         | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | <b>20.8</b>  | <b>0.05</b>   | <b>0.184</b>         | <b>0.18</b>            | <b>0.296</b>        | <b>0.30</b>            |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

Table 5: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

| Right Head Cheek Position (Slider Open) |             |                                       |              |               |                      |                        |                     |                        |
|---|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                       | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|   |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                           | Channel 128 | 32.63                                 | 20.5         | 0.06          | 0.622                | 0.62                   | 0.869               | 0.87                   |
|   | Channel 190 | 32.52                                 | 20.6         | 0.00          | 0.687                | 0.69                   | 0.96                | 0.96                   |
|   | Channel 251 | 32.60                                 | 20.4         | 0.06          | 0.765                | 0.77                   | 1.07                | 1.07                   |
| GSM<br>1900MHz                          | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|   | Channel 661 | 29.56                                 | 20.9         | 0.01          | 0.179                | 0.18                   | 0.281               | 0.28                   |
|   | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

Table 6: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

| Highest Head Cheek (Slider Open) with SNN5784A |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                              | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                                  | Channel 128 | 32.63                                 |              |               |                      |                        |                     |                        |
|  | Channel 190 | 32.52                                 |              |               |                      |                        |                     |                        |
|  | Channel 251 | 32.60                                 | 20.7         | -0.02         | 0.639                | 0.64                   | 0.883               | 0.89                   |
| GSM<br>1900MHz                                 | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | 20.8         | 0.00          | 0.178                | 0.18                   | 0.285               | 0.29                   |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

**Table 7: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.**

| Highest Head Cheek (Slider Open) with SNN5779B |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                              | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                                  | Channel 128 | 32.63                                 |              |               |                      |                        |                     |                        |
|  | Channel 190 | 32.52                                 |              |               |                      |                        |                     |                        |
|  | Channel 251 | 32.60                                 | 20.3         | -0.03         | 0.708                | 0.71                   | 0.983               | 0.99                   |
| GSM<br>1900MHz                                 | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | 20.4         | -0.01         | 0.176                | 0.18                   | 0.282               | 0.28                   |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

**Table 8: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.**

| Left Head 15° Tilt Position (Slider Closed) |             |                              |           |            |                      |                     |                     |                     |
|---|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)                           | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|   |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GSM 850MHz                                  | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|   | Channel 190 | 32.52                        | 20.9      | 0.08       | 0.427                | 0.43                | 0.597               | 0.58                |
|   | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GSM 1900MHz                                 | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|   | Channel 661 | 29.56                        | 21.5      | 0.04       | 0.133                | 0.13                | 0.219               | 0.22                |
|   | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

**Table 9: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.**

| Right Head 15° Tilt Position (Slider Closed) |             |                              |           |            |                      |                     |                     |                     |
|--|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)                            | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|  |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GSM 850MHz                                   | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|  | Channel 190 | 32.52                        | 20.8      | -0.06      | 0.402                | 0.41                | 0.54                | 0.55                |
|  | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GSM 1900MHz                                  | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|  | Channel 661 | 29.56                        | 20.9      | 0.01       | 0.128                | 0.13                | 0.219               | 0.22                |
|  | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

**Table 10: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.**

| Highest Head 15° Tilt Position (Slider Closed) with SNN5784A |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)  | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz  | Channel 128 | 32.63                                 |              |               |                      |                        |                     |                        |
|  | Channel 190 | 32.52                                 | 21.5         | -0.01         | 0.437                | 0.44                   | 0.596               | 0.60                   |
|  | Channel 251 | 32.60                                 |              |               |                      |                        |                     |                        |
| GSM<br>1900MHz   | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | 20.8         | 0.03          | 0.141                | 0.14                   | 0.231               | 0.23                   |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

Table 11: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

| Highest Head 15° Tilt Position (Slider Closed) with SNN5779B |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)  | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz  | Channel 128 | 32.63                                 |              |               |                      |                        |                     |                        |
|  | Channel 190 | 32.52                                 | 20.3         | -0.02         | 0.431                | 0.43                   | 0.585               | 0.59                   |
|  | Channel 251 | 32.60                                 |              |               |                      |                        |                     |                        |
| GSM<br>1900MHz   | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | 20.7         | -0.01         | 0.145                | 0.15                   | 0.236               | 0.24                   |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

Table 12: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

| Left Head 15° Tilt Position (Slider Open) |             |                                       |              |               |                      |                        |                     |                        |
|---|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                         | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|   |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                             | Channel 128 | 32.63                                 |              |               |                      |                        |                     |                        |
|   | Channel 190 | 32.52                                 | 20.6         | -0.02         | 0.356                | 0.36                   | 0.48                | 0.48                   |
|   | Channel 251 | 32.60                                 |              |               |                      |                        |                     |                        |
| GSM<br>1900MHz                            | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|   | Channel 661 | 29.56                                 | 20.8         | 0.19          | 0.0764               | 0.08                   | 0.125               | 0.13                   |
|   | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

Table 13: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

| Right Head 15° Tilt Position (Slider Open) |             |                                       |              |               |                      |                        |                     |                        |
|--|-------------|---------------------------------------|--------------|---------------|----------------------|------------------------|---------------------|------------------------|
| <i>f</i><br>(MHz)                          | Description | Conducted<br>Output<br>Power<br>(dBm) | Temp<br>(°C) | Drift<br>(dB) | <i>10g SAR value</i> |                        | <i>1g SAR value</i> |                        |
|  |             |                                       |              |               | Measured<br>(W/kg)   | Extrapolated<br>(W/kg) | Measured<br>(W/kg)  | Extrapolated<br>(W/kg) |
| GSM<br>850MHz                              | Channel 128 | 32.63                                 |              |               |                      |                        |                     |                        |
|  | Channel 190 | 32.52                                 | 20.4         | 0.00          | 0.335                | 0.34                   | 0.45                | 0.45                   |
|  | Channel 251 | 32.60                                 |              |               |                      |                        |                     |                        |
| GSM<br>1900MHz                             | Channel 512 | 29.54                                 |              |               |                      |                        |                     |                        |
|  | Channel 661 | 29.56                                 | 20.8         | -0.05         | 0.0591               | 0.06                   | 0.102               | 0.10                   |
|  | Channel 810 | 29.43                                 |              |               |                      |                        |                     |                        |

Table 14: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

| Highest Head 15° Tilt Position (Slider Open) with SNN5784A |             |                              |           |            |                      |                     |                     |                     |
|--|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)  | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|  |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GSM 850MHz   | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|  | Channel 190 | 32.52                        | 20.5      | -0.15      | 0.347                | 0.36                | 0.469               | 0.49                |
|  | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GSM 1900MHz  | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|  | Channel 661 | 29.56                        | 20.8      | 0.00       | 0.0773               | 0.08                | 0.126               | 0.13                |
|  | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

Table 15: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

| Highest Head 15° Tilt Position (Slider Open) with SNN5779B |             |                              |           |            |                      |                     |                     |                     |
|--|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)  | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|  |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GSM 850MHz   | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|  | Channel 190 | 32.52                        | 20.3      | -0.06      | 0.337                | 0.34                | 0.454               | 0.46                |
|  | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GSM 1900MHz  | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|  | Channel 661 | 29.56                        | 20.7      | 0.06       | 0.0783               | 0.08                | 0.127               | 0.13                |
|  | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

Table 16: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.



## 6.2 Body Worn Test Results

The SAR results shown in tables 17 through 24 are maximum SAR values averaged over 1 gram of phantom tissue, to demonstrate compliance to [3] and also over 10 grams of phantom tissue, to demonstrate compliance to the [6]. Also shown are the measured conducted output power levels, the temperature of the test facility during the test, the temperature of the tissue simulate after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is  $\text{New SAR} = \text{Old SAR} * 10^{(-\text{drift}/10)}$ . The SAR reported at the end of the measurement process by the DASY4™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test.

The test conditions that produced the highest SAR values in each band are indicated as bold numbers in the following tables and are included in Appendix 3. All other test conditions measured lower SAR values than those included in Appendix 3.

A “flat” phantom was for the body-worn tests. This “flat” phantom is made out of 1” thick natural High Density Polyethylene with a thickness at the bottom equal to 2.0mm. It measures 52.7cm(long) x 26.7cm(wide) x 21.2cm(tall). The measured dielectric constant of the material used is less than 2.3 and the loss tangent is less than 0.0046 all the way up to 2.184GHz.

The tissue stimulant depth was verified to be 15.0cm ±0.5cm. The same device holder described in section 6 was used for positioning the phone. The functional accessories were divided into two categories, the ones with metal components and the ones with non-metal components. For non-metallic component accessories, testing was performed on the accessory that displayed the closest proximity to the flat phantom. Each metallic component accessory, if any, was checked for uniqueness of metal component so that each is tested with the device. If multiple accessories shared an identical metal component, only the accessory that dictates the closest spacing to the body was tested. In addition to accessory testing, the cellular phone was tested with the front and back of the phone facing the phantom. For voice mode operation, the phone was placed as a distance of 15mm from the phantom. For data mode operation, the phone was placed as a distance of 25mm from the phantom. The cellular phone was tested with a headset connected to the device for all body-worn SAR measurements.

There are no Body-Worn Accessories available for this phone at the time of testing hence the device was tested per the supplement C testing guidelines for devices that do not have body worn accessories. The phone was placed a maximum of 15mm away from a flat phantom per the supplement C standard guidelines to perform SAR measurement.

The DUT is multislot Class 10 (2 timeslots in uplink), Class 11 (3 timeslots in uplink), and Class 12 (4 timeslots in uplink) capable in GPRS and EDGE (8PSK) modes. The software within the phone has been designed to reduce the peak power of the pulse when these multislot classes are being used. The peak power values for each mode and class are given in the tables in section 2.2. The worst-case configuration is found in Class 10 on GPRS 850/1900, EDGE850/1900, when comparing the average power increases (due to additional timeslots) and power reductions for each multislot class. For this reason, multislot Class 10 was used to perform SAR tests in GPRS 850/1900 and EDGE 850/1900 modes.

MOTOROLA, INC. Portable Cellular Phone SAR Test Report Number: **21549-2F**

The following probe conversion factors were used on the E-Field probe(s) used for the body worn measurements:

| <b>Description</b>       | <b>Serial Number</b> | <b>f (MHz)</b> | <b>Conversion Factor</b> | <b>Cal Cert pg #</b> |
|--------------------------|----------------------|----------------|--------------------------|----------------------|
| E-Field Probe<br>ET3DV6R | SN1391               | 900            | 5.75                     | 8 of 9               |
|                          |                      | 1810           | 4.48                     | 8 of 9               |
| E-Field Probe<br>ET3DV6R | SN1515               | 900            | 6.09                     | 8 of 9               |
|                          |                      | 1810           | 4.73                     | 8 of 9               |
|                          |                      | 2450           | 4.06                     | 8 of 9               |

| Body-Worn; Front of Phone 15mm from Phantom |             |                              |           |            |                      |                     |                     |                     |
|---|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)                           | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|   |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GSM 850MHz                                  | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|   | Channel 190 | 32.52                        | 20.5      | -0.03      | 0.433                | 0.44                | 0.598               | 0.60                |
|   | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GSM 1900MHz                                 | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|   | Channel 661 | 29.56                        | 21.2      | -0.02      | 0.11                 | 0.11                | 0.18                | 0.18                |
|   | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

Table 17: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| Body-Worn; Back of Phone 15mm from Phantom |             |                              |           |            |                      |                     |                     |                     |
|--|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)                          | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|  |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GSM 850MHz                                 | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|  | Channel 190 | 32.52                        | 20.5      | 0.00       | 0.439                | 0.44                | 0.621               | 0.62                |
|  | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GSM 1900MHz                                | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|  | Channel 661 | 29.56                        | 21.2      | -0.01      | 0.166                | 0.17                | 0.274               | 0.27                |
|  | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

Table 18: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| Body-Worn; Highest Position (Back or Front) 25mm from Phantom with GPRS Class 10 Mode |             |                              |           |            |                      |                     |                     |                     |
|---|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)   | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|   |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GPRS 850MHz   | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|   | Channel 190 | 32.52                        | 20.4      | -0.03      | 0.233                | 0.23                | 0.32                | 0.32                |
|   | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GPRS 1900MHz  | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|   | Channel 661 | 29.56                        | 20.8      | -0.04      | 0.0928               | 0.09                | 0.145               | 0.15                |
|   | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

Table 19: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| Body-Worn; Highest Position (Back or Front) 25mm from Phantom with EDGE Class 10 Mode |             |                              |           |            |                      |                     |                     |                     |
|---|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)   | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|   |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| EDGE 850MHz   | Channel 128 | 27.54                        |           |            |                      |                     |                     |                     |
|   | Channel 190 | 27.46                        | 20.4      | -0.01      | 0.0611               | 0.06                | 0.0836              | 0.08                |
|   | Channel 251 | 27.54                        |           |            |                      |                     |                     |                     |
| EDGE 1900MHz  | Channel 512 | 26.66                        |           |            |                      |                     |                     |                     |
|   | Channel 661 | 26.65                        | 20.8      | -0.04      | 0.0387               | 0.04                | 0.0607              | 0.06                |
|   | Channel 810 | 26.45                        |           |            |                      |                     |                     |                     |

Table 20: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| Highest Body-Worn with SNN5784A |             |                              |           |            |                      |                     |                     |                     |
|---------------------------------|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)               | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|                                 |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GSM 850MHz                      | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|                                 | Channel 190 | 32.52                        | 21.1      | -0.05      | 0.424                | 0.43                | 0.583               | 0.59                |
|                                 | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GSM 1900MHz                     | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|                                 | Channel 661 | 29.56                        | 20.9      | 0.02       | 0.136                | 0.14                | 0.22                | 0.22                |
|                                 | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

Table 21: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| Highest Body-Worn with SNN5779B |             |                              |           |            |                      |                     |                     |                     |
|---------------------------------|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)               | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|                                 |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| GSM 850MHz                      | Channel 128 | 32.63                        |           |            |                      |                     |                     |                     |
|                                 | Channel 190 | 32.52                        | 20.9      | -0.03      | 0.422                | 0.42                | 0.583               | 0.59                |
|                                 | Channel 251 | 32.60                        |           |            |                      |                     |                     |                     |
| GSM 1900MHz                     | Channel 512 | 29.54                        |           |            |                      |                     |                     |                     |
|                                 | Channel 661 | 29.56                        | 20.8      | 0.03       | 0.126                | 0.13                | 0.202               | 0.20                |
|                                 | Channel 810 | 29.43                        |           |            |                      |                     |                     |                     |

Table 22: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| Bluetooth Stand-alone : Highest Body-Worn Position on each band 15mm from Phantom |             |                              |           |            |                      |                     |                     |                     |
|---|-------------|------------------------------|-----------|------------|----------------------|---------------------|---------------------|---------------------|
| <i>f</i><br>(MHz)   | Description | Conducted Output Power (dBm) | Temp (°C) | Drift (dB) | <i>10g SAR value</i> |                     | <i>1g SAR value</i> |                     |
|   |             |                              |           |            | Measured (W/kg)      | Extrapolated (W/kg) | Measured (W/kg)     | Extrapolated (W/kg) |
| 2450MHz<br>Back<br>SNN5792A   | Channel 0   |                              |           |            |                      |                     |                     |                     |
|   | Channel 39  |                              | 20.8      | 0.66       | 0.000411             | 0.00                | 0.000936            | 0.00                |
|   | Channel 78  |                              |           |            |                      |                     |                     |                     |

Table 23: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| Highest Extrapolated Body-Worn SAR values summation with Bluetooth Stand-alone |   |                      |                              |                     |                     |                              |                     |
|--|---|----------------------|------------------------------|---------------------|---------------------|------------------------------|---------------------|
| <i>f</i><br>(MHz)  | Description   | <i>10g SAR value</i> |                              |                     | <i>1g SAR value</i> |                              |                     |
|  |   | Measured (W/kg)      | Bluetooth Measurement (W/Kg) | Extrapolated (W/kg) | Measured (W/kg)     | Bluetooth Measurement (W/Kg) | Extrapolated (W/kg) |
| 850MHz   | Body-Worn: <b>Back</b> of phone 15mm away from phantom with <b>SNN5792A</b> battery | 0.44                 | 0.00                         | 0.44                | 0.62                | 0.00                         | 0.62                |
| 1900MHz  | Body-Worn: <b>Back</b> of phone 15mm away from phantom with <b>SNN5792A</b> battery | 0.17                 | 0.00                         | 0.17                | 0.27                | 0.00                         | 0.27                |

Table 24: SAR measurement results at the highest possible output power, calculated in a body-worn position against the ICNIRP and ANSI SAR Limit.

## References

- [1] CENELEC, en62209-1:2006 “Human Exposure to Radio Frequency Fields From Hand - Held and Body - Mounted Wireless Communication Devices – Human Models, Instrumentation, and Procedures”
- [2] CENELEC, en50360:2001 “Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300MHz – 3GHz)”.
- [3] ANSI / IEEE, C95.1 1999 Edition “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz”
- [4] FCC OET Bulletin 65 Supplement C 01-01
- [5] IEEE 1528 2003 Edition “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”
- [6] ICNIRP Guidelines “Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz)”

**Appendix 1**

**SAR distribution comparison for the system accuracy verification**

## Test Laboratory: Motorola 20080222 900Mhz Good +4.8

Procedure Notes: 900 MHz System Performance Check / Dipole Sn# 077 PM1 Power = 200mW

Sim.Temp@meas = 21.55C Sim.Temp@SPC = 21.1C Room Temp @ SPC =20.7C

Communication System: CW - Dipole; Frequency: 900 MHz; Channel Number: 4; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used:  $f = 900$  MHz;  $\sigma = 0.97$  mho/m;  $\epsilon_r = 41$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(5.97, 5.97, 5.97); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

**Daily SPC Check/Dipole Area Scan (4x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.25 mW/g

**Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 53.0 V/m; Power Drift = 0.070 dB

Peak SAR (extrapolated) = 3.63 W/kg

**SAR(1 g) = 2.38 mW/g; SAR(10 g) = 1.51 mW/g**

Maximum value of SAR (measured) = 2.58 mW/g

**Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 53.0 V/m; Power Drift = 0.070 dB



Peak SAR (extrapolated) = 3.56 W/kg

**SAR(1 g) = 2.33 mW/g; SAR(10 g) = 1.48 mW/g**


Maximum value of SAR (measured) = 2.53 mW/g

**Daily SPC Check/Z-Axis Retraction (1x1x31):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 2.59 mW/g







## Test Laboratory: Motorola 20080225 900Mhz Good +1.9

Procedure Notes: 900 MHz System Performance Check / Dipole Sn# 077 PM1 Power = 200mW

Sim.Temp@meas = 21.35C Sim.Temp@SPC = 20.9C Room Temp @ SPC =21.0C

Communication System: CW - Dipole; Frequency: 900 MHz; Channel Number: 4; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used:  $f = 900$  MHz;  $\sigma = 0.97$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(5.97, 5.97, 5.97); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

**Daily SPC Check/Dipole Area Scan (4x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.26 mW/g

**Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 52.7 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 3.47 W/kg

**SAR(1 g) = 2.3 mW/g; SAR(10 g) = 1.48 mW/g**

Maximum value of SAR (measured) = 2.48 mW/g

**Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm



Reference Value = 52.7 V/m; Power Drift = 0.026 dB


Peak SAR (extrapolated) = 3.46 W/kg

**SAR(1 g) = 2.28 mW/g; SAR(10 g) = 1.45 mW/g**

**Daily SPC Check/Z-Axis Retraction (1x1x31):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 2.52 mW/g





## Test Laboratory: Motorola 20080229 900Mhz Good +3.0

Procedure Notes: 900 MHz System Performance Check / Dipole Sn# 077 PM1 Power = 200 mW

Sim.Temp@meas = 21.62C Sim.Temp@SPC = 20.9C Room Temp @ SPC = 20.8C

Communication System: CW - Dipole; Frequency: 900 MHz; Channel Number: 4; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used:  $f = 900$  MHz;  $\sigma = 0.98$  mho/m;  $\epsilon_r = 41.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(5.97, 5.97, 5.97); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

**Daily SPC Check/Dipole Area Scan (4x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.25 mW/g

**Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 52.1 V/m; Power Drift = 0.054 dB

Peak SAR (extrapolated) = 3.51 W/kg

**SAR(1 g) = 2.31 mW/g; SAR(10 g) = 1.48 mW/g**

Maximum value of SAR (measured) = 2.50 mW/g

**Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 52.1 V/m; Power Drift = 0.054 dB



Peak SAR (extrapolated) = 3.52 W/kg


**SAR(1 g) = 2.32 mW/g; SAR(10 g) = 1.48 mW/g**

Maximum value of SAR (measured) = 2.51 mW/g

**Daily SPC Check/Z-Axis Retraction (1x1x31):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 2.53 mW/g





## Test Laboratory: Motorola 20080221 1800Mhz Good -1.5

Procedure Notes: 1800 MHz System Performance Check / Dipole Sn# 280tr PM1 Power = 200 mW

Sim.Temp@meas = 21.79C Sim.Temp@SPC = 21.1C Room Temp @ SPC = 21.3C

Communication System: CW - Dipole; Frequency: 1800 MHz; Channel Number: 8; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.36$  mho/m;  $\epsilon_r = 39.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.96, 4.96, 4.96); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

**Daily SPC Check/Dipole Area Scan (4x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 6.01 mW/g

**Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 82.0 V/m; Power Drift = 0.001 dB

Peak SAR (extrapolated) = 12.9 W/kg

**SAR(1 g) = 7.43 mW/g; SAR(10 g) = 3.93 mW/g**

Maximum value of SAR (measured) = 8.28 mW/g

**Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 82.0 V/m; Power Drift = 0.001 dB


Peak SAR (extrapolated) = 12.8 W/kg


**SAR(1 g) = 7.34 mW/g; SAR(10 g) = 3.85 mW/g**

Maximum value of SAR (measured) = 7.99 mW/g

**Daily SPC Check/Z-Axis Retraction (1x1x31):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 8.34 mW/g





## Test Laboratory: Motorola 20080222 1800Mhz Good +1.2

Procedure Notes: 1800 MHz System Performance Check / Dipole Sn# 280tr PM1 Power = 200 mW

Sim.Temp@meas = 21.70C Sim.Temp@SPC = 20.8C Room Temp @ SPC = 20.6C

Communication System: CW - Dipole; Frequency: 1800 MHz; Channel Number: 8; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 39.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.96, 4.96, 4.96); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

**Daily SPC Check/Dipole Area Scan (4x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 6.18 mW/g

**Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 81.9 V/m; Power Drift = -0.002 dB

Peak SAR (extrapolated) = 13.4 W/kg

**SAR(1 g) = 7.65 mW/g; SAR(10 g) = 4.04 mW/g**

Maximum value of SAR (measured) = 8.61 mW/g

**Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 81.9 V/m; Power Drift = -0.002 dB


Peak SAR (extrapolated) = 13.1 W/kg

**SAR(1 g) = 7.53 mW/g; SAR(10 g) = 3.96 mW/g**


Maximum value of SAR (measured) = 8.18 mW/g

**Daily SPC Check/Z-Axis Retraction (1x1x31):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 8.52 mW/g







## Test Laboratory: Motorola 20080225 1800Mhz Good -0.5

Procedure Notes: 1800 MHz System Performance Check / Dipole Sn# 280tr PM1 Power = 200 mW

Sim.Temp@meas = 21.35C Sim.Temp@SPC = 21.1C Room Temp @ SPC = 20.6C

Communication System: CW - Dipole; Frequency: 1800 MHz; Channel Number: 8; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 39.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.96, 4.96, 4.96); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

**Daily SPC Check/Dipole Area Scan (4x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 6.45 mW/g

**Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 81.3 V/m; Power Drift = -0.010 dB

Peak SAR (extrapolated) = 12.8 W/kg

**SAR(1 g) = 7.5 mW/g; SAR(10 g) = 4.03 mW/g**

Maximum value of SAR (measured) = 8.45 mW/g

**Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 81.3 V/m; Power Drift = -0.010 dB


Peak SAR (extrapolated) = 12.7 W/kg


**SAR(1 g) = 7.42 mW/g; SAR(10 g) = 3.95 mW/g**

Maximum value of SAR (measured) = 8.27 mW/g

**Daily SPC Check/Z-Axis Retraction (1x1x31):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 8.50 mW/g





## Test Laboratory: Motorola 20080226 1800Mhz Good +0.2

Procedure Notes: 1800 MHz System Performance Check / Dipole Sn# 280tr PM1 Power = 200 mW

Sim.Temp@meas = 21.59C Sim.Temp@SPC = 21.0C Room Temp @ SPC = 21.3C

Communication System: CW - Dipole; Frequency: 1800 MHz; Channel Number: 8; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 39.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.96, 4.96, 4.96); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

**Daily SPC Check/Dipole Area Scan (4x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 6.57 mW/g

**Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 81.6 V/m; Power Drift = 0.005 dB

Peak SAR (extrapolated) = 13.1 W/kg

**SAR(1 g) = 7.6 mW/g; SAR(10 g) = 4.04 mW/g**

Maximum value of SAR (measured) = 8.56 mW/g

**Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 81.6 V/m; Power Drift = 0.005 dB


Peak SAR (extrapolated) = 12.8 W/kg


**SAR(1 g) = 7.43 mW/g; SAR(10 g) = 3.95 mW/g**

Maximum value of SAR (measured) = 8.20 mW/g

**Daily SPC Check/Z-Axis Retraction (1x1x31):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 8.31 mW/g





## Test Laboratory: Motorola 0320'2008\_2450MHz\_Good -7.3%

Procedure Notes: 2450 MHz System Performance Check / Dipole Sn# 767 PM1 Power = 200 mW

Sim.Temp@meas = 22.32C Sim.Temp@SPC = 22.1C Room Temp @ SPC = 21.5C

Communication System: CW - Dipole; Frequency: 2450 MHz; Channel Number: 11; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.85$  mho/m;  $\epsilon_r = 37.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6 - SN1515; ConvF(4.64, 4.64, 4.64); Calibrated: 8/28/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn383; Calibrated: 8/24/2007
- Phantom: PCS-9 Glycol SAM; Type: SAM; Serial: TP-1134;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

**Daily SPC Check/Dipole Area Scan (4x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 8.19 mW/g

**Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 83.0 V/m; Power Drift = 0.018 dB

Peak SAR (extrapolated) = 24.9 W/kg

**SAR(1 g) = 10.8 mW/g; SAR(10 g) = 4.92 mW/g**

Maximum value of SAR (measured) = 12.1 mW/g

**Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 83.0 V/m; Power Drift = 0.018 dB


Peak SAR (extrapolated) = 24.0 W/kg


**SAR(1 g) = 10.7 mW/g; SAR(10 g) = 4.92 mW/g**

Maximum value of SAR (measured) = 11.9 mW/g

**Daily SPC Check/Z-Axis Retraction (1x1x31):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 12.0 mW/g





**Appendix 2**

**SAR distribution plots for Phantom Head Adjacent Use**



## Test Laboratory: Motorola GSM850 Cheek Slider Closed

### TA100005LZ ;

Procedure Notes: Pwr Step: 05(OTA) Antenna Position: internal

Battery Model #: SNN5792A; DEVICE POSITION (cheek or rotated): cheek

Communication System: GSM 850; Frequency: 848.8 MHz; Channel Number: 251; Duty Cycle: 1:8

Medium: Low Freq Head; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.9$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(5.97, 5.97, 5.97); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.40 mW/g

### Left Head Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 41.4 V/m; Power Drift = 0.031 dB

Peak SAR (extrapolated) = 2.07 W/kg

**SAR(1 g) = 1.39 mW/g; SAR(10 g) = 0.920 mW/g**

Maximum value of SAR (measured) = 1.46 mW/g



## Test Laboratory: Motorola GSM850 Cheek Slider Open

### TA100005LZ ;

Procedure Notes: Pwr Step: 05(OTA) Antenna Position: internal

Battery Model #: SNN5792A; DEVICE POSITION (cheek or rotated): cheek

Communication System: GSM 850; Frequency: 848.8 MHz; Channel Number: 251; Duty Cycle: 1:8

Medium: Low Freq Head; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.9$  mho/m;  $\epsilon_r = 41.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(5.97, 5.97, 5.97); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.08 mW/g

### Left Head Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 35.3 V/m; Power Drift = -0.020 dB

Peak SAR (extrapolated) = 1.41 W/kg

**SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.766 mW/g**

Maximum value of SAR (measured) = 1.12 mW/g



## Test Laboratory: Motorola GSM850 Tilt Slider Closed

### TA100005LZ ;

Procedure Notes: Pwr Step: 05(OTA) Antenna Position: internal

Battery Model #: SNN5784A; DEVICE POSITION (cheek or rotated): Rotated

Communication System: GSM 850; Frequency: 836.6 MHz; Channel Number: 190; Duty Cycle: 1:8

Medium: Low Freq Head; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.92$  mho/m;  $\epsilon_r = 42.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(5.97, 5.97, 5.97); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.609 mW/g

### Left Head Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.1 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 0.758 W/kg

**SAR(1 g) = 0.596 mW/g; SAR(10 g) = 0.437 mW/g**

Maximum value of SAR (measured) = 0.629 mW/g



## Test Laboratory: Motorola GSM850 Tilt Slider Open

### TA100005LZ ;

Procedure Notes: Pwr Step: 05(OTA) Antenna Position: internal

Battery Model #: SNN5784A; DEVICE POSITION (cheek or rotated): rotated

Communication System: GSM 850; Frequency: 836.6 MHz; Channel Number: 190; Duty Cycle: 1:8

Medium: Low Freq Head; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.9$  mho/m;  $\epsilon_r = 41.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(5.97, 5.97, 5.97); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.485 mW/g

### Left Head Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.0 V/m; Power Drift = -0.150 dB

Peak SAR (extrapolated) = 0.595 W/kg

**SAR(1 g) = 0.469 mW/g; SAR(10 g) = 0.347 mW/g**

Maximum value of SAR (measured) = 0.492 mW/g



## Test Laboratory: Motorola GSM1900 Cheek Slider Closed

### TA100005LZ ;

Procedure Notes: Pwr Step: 00(OTA) Antenna Position: internal

Battery Model #: SNN5779B; DEVICE POSITION (cheek or rotated): cheek

Communication System: GSM 1900; Frequency: 1880 MHz; Channel Number: 661; Duty Cycle: 1:8

Medium: Regular Glycol Head 1750/1880; Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.46$  mho/m;  $\epsilon_r = 39.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.96, 4.96, 4.96); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.748 mW/g

### Left Head Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.2 V/m; Power Drift = 0.007 dB

Peak SAR (extrapolated) = 1.08 W/kg

**SAR(1 g) = 0.663 mW/g; SAR(10 g) = 0.369 mW/g**

Maximum value of SAR (measured) = 0.741 mW/g



## Test Laboratory: Motorola GSM1900 Cheek Slider Open

### TA100005LZ ;

Procedure Notes: Pwr Step: 00(OTA) Antenna Position: internal

Battery Model #: SNN5792A; DEVICE POSITION (cheek or rotated): cheek

Communication System: GSM 1900; Frequency: 1880 MHz; Channel Number: 661; Duty Cycle: 1:8

Medium: Regular Glycol Head 1750/1880; Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 39.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.96, 4.96, 4.96); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.309 mW/g

### Left Head Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.8 V/m; Power Drift = 0.045 dB

Peak SAR (extrapolated) = 0.449 W/kg

**SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.184 mW/g**

Maximum value of SAR (measured) = 0.320 mW/g



## Test Laboratory: Motorola GSM1900 Tilt Slider Closed

### TA100005LZ ;

Procedure Notes: Pwr Step: 00(OTA) Antenna Position: internal

Battery Model #: SNN5779B; DEVICE POSITION (cheek or rotated): Rotated

Communication System: GSM 1900; Frequency: 1880 MHz; Channel Number: 661; Duty Cycle: 1:8

Medium: Regular Glycol Head 1750/1880; Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.46$  mho/m;  $\epsilon_r = 39.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.96, 4.96, 4.96); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.248 mW/g

### Left Head Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.5 V/m; Power Drift = -0.011 dB

Peak SAR (extrapolated) = 0.366 W/kg

**SAR(1 g) = 0.236 mW/g; SAR(10 g) = 0.145 mW/g**

Maximum value of SAR (measured) = 0.252 mW/g



## Test Laboratory: Motorola GSM1900 Tilt Slider Open

### TA100005LZ ;

Procedure Notes: Pwr Step: 00(OTA) Antenna Position: internal

Battery Model #: SNN5779B; DEVICE POSITION (cheek or rotated): Rotated

Communication System: GSM 1900; Frequency: 1880 MHz; Channel Number: 661; Duty Cycle: 1:8

Medium: Regular Glycol Head 1750/1880; Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.46$  mho/m;  $\epsilon_r = 39.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.96, 4.96, 4.96); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10 Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.138 mW/g

### Left Head Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.44 V/m; Power Drift = 0.062 dB

Peak SAR (extrapolated) = 0.192 W/kg

**SAR(1 g) = 0.127 mW/g; SAR(10 g) = 0.078 mW/g**

Maximum value of SAR (measured) = 0.136 mW/g





**Appendix 3**

**SAR distribution plots for Body Worn Configuration**

## Test Laboratory: Motorola GSM850 BodyWorn

### TA100005LZ ;

Procedure Notes: Pwr Step: 05(OTA) Antenna Position: Internal

Battery Model #: SNN5792A; Device Position: Back of phone 15mm away from the flat phantom

Communication System: GSM 850; Frequency: 836.6 MHz; Channel Number: 190; Duty Cycle: 1:8

Medium: Low Freq Body; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.98$  mho/m;  $\epsilon_r = 55.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(5.75, 5.75, 5.75); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10\_Section 1, Amy Twin, Rev2 (23-June-04); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.645 mW/g

### Amy Twin Phone Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.4 V/m; Power Drift = 0.005 dB

Peak SAR (extrapolated) = 0.830 W/kg

**SAR(1 g) = 0.621 mW/g; SAR(10 g) = 0.439 mW/g**

Maximum value of SAR (measured) = 0.664 mW/g



## Test Laboratory: Motorola GSM1900 BodyWorn

### TA100005LZ ;

Procedure Notes: Pwr Step: 00(OTA) Antenna Position: Internal

Battery Model #: SNN5792A; Device Position: Back of phone 15mm away from the flat phantom

Communication System: GSM 1900; Frequency: 1880 MHz; Channel Number: 661; Duty Cycle: 1:8

Medium: Regular Glycol Body 1750/1880; Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.57$  mho/m;  $\epsilon_r = 53.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

### DASY4 Configuration:

- Probe: ET3DV6R - SN1391; ConvF(4.48, 4.48, 4.48); Calibrated: 9/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn365; Calibrated: 9/18/2007
- Phantom: PCS-10\_Section 2, Amy Twin, Rev2 (23-June-04); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.302 mW/g

### Amy Twin Phone Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.3 V/m; Power Drift = -0.009 dB

Peak SAR (extrapolated) = 0.424 W/kg

**SAR(1 g) = 0.274 mW/g; SAR(10 g) = 0.166 mW/g**

Maximum value of SAR (measured) = 0.298 mW/g



## Test Laboratory: Motorola Bluetooth 2450

### TA100005LZ ;

Procedure Notes: Pwr Step: BT Antenna Position: Internal

Battery Model #:SNN5792A; Device Position: Back of phone 15mm away from the flat phantom

Communication System: Bluetooth; Frequency: 2441 MHz; Channel Number: 39; Duty Cycle: 1:1

Medium: 2450 Glycol Body; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.04$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY4 Configuration:

- Probe: ET3DV6 - SN1515; ConvF(4.06, 4.06, 4.06); Calibrated: 8/28/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn383; Calibrated: 8/24/2007
- Phantom: R#9\_ Section 2, Amy Twin, Rev2 (23-June-04); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

### Amy Twin Phone Template/Area Scan - Normal Body (10mm) (19x10x1):

Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.001 mW/g

### Amy Twin Phone Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.450 V/m; Power Drift = 0.660 dB

Peak SAR (extrapolated) = 0.004 W/kg

**SAR(1 g) = 0.000936 mW/g; SAR(10 g) = 0.000411 mW/g**

Maximum value of SAR (measured) = 0.002 mW/g



**Appendix 4**

**Probe Calibration Certificate**



Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola Korea**

Certificate No. **ET3-1391\_Sep07**

## CALIBRATION CERTIFICATE

Object **ET3DV6R - SN: 1391**

Calibration procedure(s) **QA-CAL-01-v6  
Calibration procedure for dosimetric E-field probes**

Calibration date: **September 24, 2007**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID #            | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration |
|----------------------------|-----------------|---|-----------------------|
| Power meter E4419B         | GB41293874      | 29-Mar-07 (METAS, No. 217-00670)          | Mar-08                |
| Power sensor E4412A        | MY41495277      | 29-Mar-07 (METAS, No. 217-00670)          | Mar-08                |
| Power sensor E4412A        | MY41498087      | 29-Mar-07 (METAS, No. 217-00670)          | Mar-08                |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 8-Aug-07 (METAS, No. 217-00719)           | Aug-08                |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 29-Mar-07 (METAS, No. 217-00671)          | Mar-08                |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 8-Aug-07 (METAS, No. 217-00720)           | Aug-08                |
| Reference Probe ES3DV2     | SN: 3013        | 4-Jan-07 (SPEAG, No. ES3-3013_Jan07)      | Jan-08                |
| DAE4                       | SN: 654         | 20-Apr-07 (SPEAG, No. DAE4-654_Apr07)     | Apr-08                |

| Secondary Standards       | ID #         | Check Date (in house)                    | Scheduled Check        |
|---------------------------|--------------|--|------------------------|
| RF generator HP 8648C     | US3642U01700 | 4-Aug-99 (SPEAG, in house check Nov-05)  | In house check: Nov-07 |
| Network Analyzer HP 8753E | US37390585   | 18-Oct-01 (SPEAG, in house check Oct-06) | In house check: Oct-07 |

|                | Name          | Function          | Signature |
|----------------|---------------|-------------------|-----------|
| Calibrated by: | Katja Pokovic | Technical Manager |           |
| Approved by:   | Fin Bomholt   | R&D Director      |           |

Issued: September 24, 2007

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

|                          |  |
|--------------------------|--|
| TSL                      | tissue simulating liquid   |
| NORM <sub>x,y,z</sub>    | sensitivity in free space  |
| ConF                     | sensitivity in TSL / NORM <sub>x,y,z</sub>   |
| DCP                      | diode compression point  |
| Polarization $\varphi$   | $\varphi$ rotation around probe axis   |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* *frequency\_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe ET3DV6R

## SN:1391

|                  |                    |
|------------------|--------------------|
| Manufactured:    | October 1, 1999    |
| Last calibrated: | November 21, 2006  |
| Recalibrated:    | September 24, 2007 |

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)



**DASY - Parameters of Probe: ET3DV6R SN:1391**

| Sensitivity in Free Space <sup>A</sup> |              |                                     | Diode Compression <sup>B</sup> |       |
|--|--------------|-------------------------------------|--------------------------------|-------|
| NormX                                  | 1.81 ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ | DCP X                          | 90 mV |
| NormY                                  | 1.87 ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ | DCP Y                          | 90 mV |
| NormZ                                  | 1.87 ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ | DCP Z                          | 91 mV |

**Sensitivity in Tissue Simulating Liquid (Conversion Factors)**

Please see Page 8.

**Boundary Effect**

| TSL | 900 MHz                                   | Typical SAR gradient: 5 % per mm  |        |        |
|-----|---|-----------------------------------|--------|--------|
|     | Sensor Center to Phantom Surface Distance |                                   | 3.7 mm | 4.7 mm |
|     | SAR <sub>be</sub> [%]                     | Without Correction Algorithm      | 5.9    | 2.6    |
|     | SAR <sub>be</sub> [%]                     | With Correction Algorithm         | 0.0    | 0.1    |
| TSL | 1810 MHz                                  | Typical SAR gradient: 10 % per mm |        |        |
|     | Sensor Center to Phantom Surface Distance |                                   | 3.7 mm | 4.7 mm |
|     | SAR <sub>be</sub> [%]                     | Without Correction Algorithm      | 14.1   | 9.2    |
|     | SAR <sub>be</sub> [%]                     | With Correction Algorithm         | 0.1    | 0.2    |

**Sensor Offset**

|                            |        |
|----------------------------|--------|
| Probe Tip to Sensor Center | 2.7 mm |
|----------------------------|--------|


**The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.**

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Page 8).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.




# Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

### Receiving Pattern ( $\phi$ ), $\vartheta = 0^\circ$





Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

### Dynamic Range f(SAR<sub>head</sub>) (Waveguide R22, f = 1800 MHz)



Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)

## Conversion Factor Assessment




| f [MHz] | Validity [MHz] <sup>c</sup> | TSL  | Permittivity | Conductivity | Alpha | Depth | ConvF Uncertainty  |
|---------|-----------------------------|------|--------------|--------------|-------|-------|--------------------|
| 900     | ± 50 / ± 100                | Head | 41.5 ± 5%    | 0.97 ± 5%    | 0.33  | 2.64  | 5.97 ± 11.0% (k=2) |
| 1810    | ± 50 / ± 100                | Head | 40.0 ± 5%    | 1.40 ± 5%    | 0.60  | 2.36  | 4.96 ± 11.0% (k=2) |
| 1950    | ± 50 / ± 100                | Head | 40.0 ± 5%    | 1.40 ± 5%    | 0.67  | 2.31  | 4.72 ± 11.0% (k=2) |
| 900     | ± 50 / ± 100                | Body | 55.0 ± 5%    | 1.05 ± 5%    | 0.38  | 2.61  | 5.75 ± 11.0% (k=2) |
| 1810    | ± 50 / ± 100                | Body | 53.3 ± 5%    | 1.52 ± 5%    | 0.70  | 2.49  | 4.48 ± 11.0% (k=2) |
| 1950    | ± 50 / ± 100                | Body | 53.3 ± 5%    | 1.52 ± 5%    | 0.90  | 2.08  | 4.30 ± 11.0% (k=2) |

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

### Deviation from Isotropy in HSL

Error ( $\phi, \vartheta$ ),  $f = 900$  MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  ( $k=2$ )



Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola Korea**

Certificate No. **ET3-1515-Aug07**

## CALIBRATION CERTIFICATE

Object **ET3DV6 - SN:1515**

Calibration procedure(s) **QA-CAL-01-v6  
Calibration procedure for dosimetric E-field probes**

Calibration date: **August 28, 2007**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID #            | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration  |
|----------------------------|-----------------|---|------------------------|
| Power meter E4419B         | GB41293874      | 29-Mar-07 (METAS, No. 217-00670)          | Mar-08                 |
| Power sensor E4412A        | MY41495277      | 29-Mar-07 (METAS, No. 217-00670)          | Mar-08                 |
| Power sensor E4412A        | MY41498087      | 29-Mar-07 (METAS, No. 217-00670)          | Mar-08                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 8-Aug-07 (METAS, No. 217-00719)           | Aug-08                 |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 29-Mar-07 (METAS, No. 217-00671)          | Mar-08                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 8-Aug-07 (METAS, No. 217-00720)           | Aug-08                 |
| Reference Probe ES3DV2     | SN: 3013        | 4-Jan-07 (SPEAG, No. ES3-3013_Jan07)      | Jan-08                 |
| DAE4                       | SN: 654         | 20-Apr-07 (SPEAG, No. DAE4-654_Apr07)     | Apr-08                 |
| Secondary Standards        | ID #            | Check Date (in house)                     | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (SPEAG, in house check Nov-05)   | In house check: Nov-07 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (SPEAG, in house check Oct-06)  | In house check: Oct-07 |

|                | Name          | Function          | Signature |
|----------------|---------------|-------------------|-----------|
| Calibrated by: | Katja Pokovic | Technical Manager |           |
| Approved by:   | Niels Kuster  | Quality Manager   |           |

Issued: August 28, 2007

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

|                          |  |
|--------------------------|--|
| TSL                      | tissue simulating liquid   |
| NORM <sub>x,y,z</sub>    | sensitivity in free space  |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>   |
| DCP                      | diode compression point  |
| Polarization $\phi$      | $\phi$ rotation around probe axis  |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.



# Probe ET3DV6

## SN:1515

|                  |                  |
|------------------|------------------|
| Manufactured:    | February 1, 2000 |
| Last calibrated: | August 24, 2006  |
| Modified:        | August 22, 2007  |
| Recalibrated:    | August 28, 2007  |


Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)






# Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

### Receiving Pattern ( $\phi$ ), $\vartheta = 0^\circ$





Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

### Dynamic Range $f(\text{SAR}_{\text{head}})$ (Waveguide R22, $f = 1800 \text{ MHz}$ )



Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment




| f [MHz] | Validity [MHz] <sup>c</sup> | TSL  | Permittivity | Conductivity | Alpha | Depth | ConvF Uncertainty  |
|---------|-----------------------------|------|--------------|--------------|-------|-------|--------------------|
| 900     | ± 50 / ± 100                | Head | 41.5 ± 5%    | 0.97 ± 5%    | 0.31  | 2.72  | 6.50 ± 11.0% (k=2) |
| 1810    | ± 50 / ± 100                | Head | 40.0 ± 5%    | 1.40 ± 5%    | 0.61  | 2.40  | 5.21 ± 11.0% (k=2) |
| 1950    | ± 50 / ± 100                | Head | 40.0 ± 5%    | 1.40 ± 5%    | 0.63  | 2.47  | 4.98 ± 11.0% (k=2) |
| 2450    | ± 50 / ± 100                | Head | 39.2 ± 5%    | 1.80 ± 5%    | 0.70  | 1.84  | 4.64 ± 11.8% (k=2) |
| 900     | ± 50 / ± 100                | Body | 55.0 ± 5%    | 1.05 ± 5%    | 0.34  | 2.89  | 6.09 ± 11.0% (k=2) |
| 1810    | ± 50 / ± 100                | Body | 53.3 ± 5%    | 1.52 ± 5%    | 0.65  | 2.62  | 4.73 ± 11.0% (k=2) |
| 1950    | ± 50 / ± 100                | Body | 53.3 ± 5%    | 1.52 ± 5%    | 0.78  | 2.28  | 4.45 ± 11.0% (k=2) |
| 2450    | ± 50 / ± 100                | Body | 52.7 ± 5%    | 1.95 ± 5%    | 0.66  | 2.16  | 4.06 ± 11.8% (k=2) |

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

# Deviation from Isotropy in HSL

Error ( $\phi, \vartheta$ ),  $f = 900$  MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  ( $k=2$ )

**Appendix 5**

**Measurement Uncertainty Budget**



MOTOROLA, INC. Portable Cellular Phone SAR Test Report Number: 21549-2F

| <i>a</i>   | <i>b</i>                | <i>c</i>      | <i>d</i>         | <i>e =<br/>f(d,k)</i> | <i>f</i>                      | <i>g</i>                          | <i>h =<br/>c x f<br/>/ e</i>            | <i>i =<br/>c x g<br/>/ e</i>             | <i>k</i>             |
|--|-------------------------|---------------|------------------|-----------------------|-------------------------------|-----------------------------------|---|--|----------------------|
| Uncertainty Component                              | IEEE<br>1528<br>section | Tol.<br>(± %) | Prob<br><br>Dist | Div.                  | <i>c<sub>i</sub></i><br>(1 g) | <i>c<sub>i</sub></i><br>(10<br>g) | 1 g<br><br><i>u<sub>i</sub></i><br>(±%) | 10 g<br><br><i>u<sub>i</sub></i><br>(±%) | <i>v<sub>i</sub></i> |
| <b>Measurement System</b>                          |                         |               |                  |                       |                               |                                   |   |  |                      |
| Probe Calibration                                  | E.2.1                   | 5.9           | N                | 1.00                  | 1                             | 1                                 | 5.9                                     | 5.9                                      | ∞                    |
| Axial Isotropy                                     | E.2.2                   | 4.7           | R                | 1.73                  | 0.707                         | 0.707                             | 1.9                                     | 1.9                                      | ∞                    |
| Hemispherical Isotropy                             | E.2.2                   | 9.6           | R                | 1.73                  | 0.707                         | 0.707                             | 3.9                                     | 3.9                                      | ∞                    |
| Boundary Effect                                    | E.2.3                   | 1.0           | R                | 1.73                  | 1                             | 1                                 | 0.6                                     | 0.6                                      | ∞                    |
| Linearity  | E.2.4                   | 4.7           | R                | 1.73                  | 1                             | 1                                 | 2.7                                     | 2.7                                      | ∞                    |
| System Detection Limits                            | E.2.5                   | 1.0           | R                | 1.73                  | 1                             | 1                                 | 0.6                                     | 0.6                                      | ∞                    |
| Readout Electronics                                | E.2.6                   | 0.3           | N                | 1.00                  | 1                             | 1                                 | 0.3                                     | 0.3                                      | ∞                    |
| Response Time                                      | E.2.7                   | 1.1           | R                | 1.73                  | 1                             | 1                                 | 0.6                                     | 0.6                                      | ∞                    |
| Integration Time                                   | E.2.8                   | 1.1           | R                | 1.73                  | 1                             | 1                                 | 0.6                                     | 0.6                                      | ∞                    |
| RF Ambient Conditions - Noise                      | E.6.1                   | 3.0           | R                | 1.73                  | 1                             | 1                                 | 1.7                                     | 1.7                                      | ∞                    |
| RF Ambient Conditions - Reflections                | E.6.1                   | 0.0           | R                | 1.73                  | 1                             | 1                                 | 0.0                                     | 0.0                                      | ∞                    |
| Probe Positioner Mech. Tolerance                   | E.6.2                   | 0.4           | R                | 1.73                  | 1                             | 1                                 | 0.2                                     | 0.2                                      | ∞                    |
| Probe Positioning w.r.t Phantom                    | E.6.3                   | 1.4           | R                | 1.73                  | 1                             | 1                                 | 0.8                                     | 0.8                                      | ∞                    |
| Max. SAR Evaluation (ext., int., avg.)             | E.5                     | 3.4           | R                | 1.73                  | 1                             | 1                                 | 2.0                                     | 2.0                                      | ∞                    |
| <b>Test sample Related</b>                         |                         |               |                  |                       |                               |                                   |   |  |                      |
| Test Sample Positioning                            | E.4.2                   | 3.2           | N                | 1.00                  | 1                             | 1                                 | 3.2                                     | 3.2                                      | 29                   |
| Device Holder Uncertainty                          | E.4.1                   | 4.0           | N                | 1.00                  | 1                             | 1                                 | 4.0                                     | 4.0                                      | 8                    |
| SAR drift  | 6.6.2                   | 5.0           | R                | 1.73                  | 1                             | 1                                 | 2.9                                     | 2.9                                      | ∞                    |
| <b>Phantom and Tissue Parameters</b>               |                         |               |                  |                       |                               |                                   |   |  |                      |
| Phantom Uncertainty                                | E.3.1                   | 4.0           | R                | 1.73                  | 1                             | 1                                 | 2.3                                     | 2.3                                      | ∞                    |
| Liquid Conductivity (target)                       | E.3.2                   | 5.0           | R                | 1.73                  | 0.64                          | 0.43                              | 1.8                                     | 1.2                                      | ∞                    |
| Liquid Conductivity (measurement)                  | E.3.3                   | 3.3           | N                | 1.00                  | 0.64                          | 0.43                              | 2.1                                     | 1.4                                      | ∞                    |
| Liquid Permittivity (target)                       | E.3.2                   | 5.0           | R                | 1.73                  | 0.6                           | 0.49                              | 1.7                                     | 1.4                                      | ∞                    |
| Liquid Permittivity (measurement)                  | E.3.3                   | 1.9           | N                | 1.00                  | 0.6                           | 0.49                              | 1.1                                     | 0.9                                      | ∞                    |
| <b>Combined Standard Uncertainty</b>               |                         |               | RSS              |                       |                               |                                   | 11.1                                    | 10.8                                     | 411                  |
| <b>Expanded Uncertainty (95% CONFIDENCE LEVEL)</b> |                         |               | <i>k</i> =2      |                       |                               |                                   | 22.2                                    | 21.6                                     |                      |

**Appendix 6**

**Photographs of the device under test**



**Figure1: Front of Phone Close**




**Figure2: Back of Phone**




**Figure3: Front of Phone Open**



**Figure4: Phone Against the Head Phantom (Cheek Touch - Phone Close)**



**Figure5: Phone Against the Head Phantom (15° Tilt - Phone Close)**



**Figure6: Phone Against the Head Phantom (Cheek Touch - Phone Open)**



**Figure7: Phone Against the Head Phantom (15° Tilt - Phone Open)**



**Figure8: Phone Against the Flat Phantom**

**Appendix 7**

**Dipole Characterization Certificate**

# Certification of System Performance Check Targets

Based on WI-0396

-Historical Data-

| 900MHz   |                          |
|--|--------------------------|
| IEEE/IEC Target:   | 10.8 (W/kg)              |
| Measurement Uncertainty (k=1):   | 9.0%                     |
| Measurement Period:  | 10-May-06 to 18-April-07 |
| # of tests performed:  | 1,562                    |
| Grand Average:   | 11.24 (W/kg)             |
| % Delta (Average - IEEE1528 Target)  | 4.1%                     |
| Is % Delta <= Expanded Measurement Uncertainty (k=2)?  | Yes                      |
| Accept/Reject <u>Average</u> as new system performance check target?                                     | ACCEPT                   |
| <b>Applies to Dipole SN's:</b><br>55, 69, 77, 78, 79,<br>80, 91, 92, 93, 94,<br>95, 96, 97, 1d034, 1d035 |                          |


-New System Performance Check Targets- per WI-0396

(based on analysis of historical data)

| Frequency | SAR Target (W/kg) | Permittivity | Conductivity (S/m) |
|-----------|-------------------|--------------|--------------------|
| 900MHz    | 11.24             | 41.5 ± 5%    | 0.97 ± 5%          |

-Approvals-

Submitted by:  Date:

Signed: 

Comments:

Approved by:  Date:

Signed: 

Comments:



# Certification of System Performance Check Targets

## Based on WI-0396

-Historical Data-


| <b>1800MHz</b>   |                          |
|--|--------------------------|
| IEEE1528 Target:   | 38.1 (W/kg)              |
| Measurement Uncertainty (k=1):   | 9.0%                     |
| Measurement Period:  | 10-May-06 to 18-April-07 |
| # of tests performed:  | 1314                     |
| Grand Average:   | 37.5 (W/kg)              |
| % Delta<br>(Average - IEEE1528 Target)   | -1.6%                    |
| Is % Delta <= Expanded Measurement Uncertainty (k=2)?  | <b>Yes</b>               |
| Accept/Reject <u>Average</u> as new system performance check target?   | <b>ACCEPT</b>            |
| <u>Applies to Dipole SN's:</u><br>246tr, 250tr, 251tr, 259tr, 263tr, 271tr, 272tr, 276tr, 277tr, 279tr, 280tr, 281tr, 283tr, 284tr, 2d128, 2d129 |                          |

-New System Performance Check Targets- per WI-0396  
 (based on analysis of historical data)

| Frequency      | SAR Target (W/kg) | Permittivity | Conductivity (S/m) |
|----------------|-------------------|--------------|--------------------|
| <b>1800MHz</b> | <b>37.5</b>       | 40.0 ± 5%    | 1.40 ± 5%          |

-Approvals-

Submitted by:  Date:

Signed: 

Comments:

Approved by:  Date:

Signed: 

Comments:

# Certification of System Performance Check Targets

Based on WI-0396

-Historical Data-

| 2450MHz  |                          |
|--|--------------------------|
| IEEE1528 Target:   | 52.4 (W/kg)              |
| Measurement Uncertainty (k=1):                                       | 9.0%                     |
| Measurement Period:  | 10-May-06 to 18-April-07 |
| # of tests performed:  | 32                       |
| Grand Average:   | 58.0 (W/kg)              |
| % Delta (Average - IEEE1528 Target)                                  | 10.6%                    |
| Is % Delta <= Expanded Measurement Uncertainty (k=2)?                | Yes                      |
| Accept/Reject <u>Average</u> as new system performance check target? | ACCEPT                   |
| <u>Applies to Dipole SN's:</u><br>740, 766, 767, 788, 789            |                          |


-New System Performance Check Targets- per WI-0396

(based on analysis of historical data)

| Frequency | SAR Target (W/kg) | Permittivity | Conductivity (S/m) |
|-----------|-------------------|--------------|--------------------|
| 2450MHz   | 58.0              | 39.2 ± 5%    | 1.80 ± 5%          |

-Approvals-

Submitted by:  Date:

Signed: 

Comments:

Approved by:  Date:

Signed: 

Comments: