



## PRODUCT SAFETY AND COMPLIANCE EMC LABORATORY

### EMC TEST REPORT - Addendum

Test Report Number –24965-1

Report Date – 2012-04-13

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

Signature:

Name: Lei Yang

Title: EMC Project Engineer

Test: 2012-03-20 to 2012-04-13

As the responsible test lab manager, I hereby declare that the model tested as specified in this report conforms to the requirements indicated.

Signature:

Name: Yilin Zhao

Title: Test Lab Manager

Date: 2012-04-17

This report must not be reproduced, except in full, without written approval from this laboratory.

FCC Registration Number: 177885  
IC Registration Number: 109AW-1

ADR Testing Service location ADR BJ  
ISO/IEC-17025:2005 accredited by UKAS



## Table of Contents

<u>Test Report Details</u> .....	3
<u>Summary of Testing</u> .....	4
<u>General and Special Conditions</u> .....	4
<u>Equipment and Cable Configurations</u> .....	5
<u>Measurement Procedures and Data</u> .....	5
<u>RF POWER OUTPUT</u> .....	8
<u>RADIATED POWER (EIRP AND ERP)</u> .....	9
<u>OCCUPIED BANDWIDTH</u> .....	11
<u>SPURIOUS EMISSIONS AT ANTENNA TERMINALS</u> .....	20
<u>FIELD STRENGTH OF SPURIOUS EMISSIONS</u> .....	23
<u>FREQUENCY STABILITY</u> .....	26

## Test Report Details

Tests Performed By: Motorola (Beijing) Mobility Technologies Co., Ltd.

Asia Global Compliance Labs

No.1 Wang Jing East Road

Chao Yang District

Beijing, 100102, P. R. China

Phone: +86 10 8473 2610

FCC Registration Number: 177885

IC Registration Number: 109AW-1

Tests Requested By: Motorola Mobility Inc.  
No. 1 Wang Jing East Road  
Chao Yang District  
Beijing, 100102, P. R. China

Product Type: Cell phone

Signaling Capability: GSM850/1900, EDGE850/1900, CDMA 850/1900,  
EVDO, Bluetooth, 802.11b/802.11g/802.11n

HEX: A000002C98F7E8

FCC ID: IHDT56NH2

Project number: 24965-1

Testing Complete Date: 2012-04-13

**Applicable Standards**

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 2  
 Part 22 Subpart H – Public Mobilie Services  
 Part 24 Subpart E – Personal Communications Services

Applicable Standards: ANSI C63.4-2003, ANSI/TIA-603-C-2004, RSS-Gen Issue 3, RSS132 Issue 2, RSS-133 Issue 5.

## **Summary of Testing**

Test #	Test Name	Pass/Fail
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	Pass
3	EIRP (Effective Isotropic Radiated Power)	Pass
4	Occupied Bandwidth	Pass
5	Spurious Emissions at Antenna Terminal	Pass
6	Field Strength of Spurious Emissions	Pass
7	Frequency Stability	Pass

Test #	Test Name	Margin with respect to the Limit
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	See results
3	EIRP (Effective Isotropic Radiated Power)	See results
4	Occupied Bandwidth	See Plots
5	Spurious Emissions at Antenna Terminal	See results
6	Field Strength of Spurious Emissions	See results
7	Frequency Stability	See results

The margin with respect to the limit is the minimum margin for all modes and bands.

## **General and Special Conditions**

The EUT was tested using a fully charged embedded battery when applicable. Where a battery could not be used due to the need for a controlled variation of input voltage, an external power supply was utilized.

All testing was done in an indoor controlled environment. The temperature and the relative humidity were maintained within the ANSI C63.4-2003 Standard requirements during the entire duration of testing.

## **Equipment and Cable Configurations**

The EUT was tested in a stand-alone configuration that is representative of typical use.

Equipment	Model/type	Serial number	Operational range	Date of calibration
EMI analyzers	ESU 40	100036	20 Hz – 40 GHz	11.11.2011
Pre Amplifiers	PA-02-0001:	2007343	(10 kHz – 3 GHz)	07.04.2011
	PA-02-218	2007344	3 GHz – 18 GHz	07.04.2011
	PA-02-5	2007345	18 GHz – 40 GHz	07.04.2011
Radio com. Tester	CMU 200	112790	GSM 850/900/1800/1900 UMTS, CDMA, Bluetooth	N/A
Band Reject Filter	WRCD	N/A	GSM 850/900/1800/1900 UMTS, CDMA	N/A
	4N45-24241/3/6	N/A	WLAN	N/A
EMI analyzers	R&S ESCI	100650	9 kHz – 3 GHz	03.13.2012
LISN	ENV216	100375	9 kHz – 30 MHz	12.19.2010
Environment Chamber	Votsch VT4004	3546270300000 20	-50 <sup>0</sup> C -150 <sup>0</sup> C	10.27.2011
DC Power Supply	Agilent E3632A	My40021519	15V/7A	07.20.2011
Power meter	Agilent E4416A	MY451000906	NA	03.03.2011
Power sensor	Agilent E9323A	MY44420783	50MHz-6GHz	03.03.2011

The antennas used in the various tests are listed in the below table.

Antenna	Type	Serial number	Operational range	Date of calibration
Hybrid-log periodic	TDK HLP 3003C	130361	30 MHz – 3 GHz	11.14.2011
Double ridged Horn	TDK HRN0118	130303	1 GHz – 18 GHz	01.22.2011
Double ridged Horn	ETS HRN3116	00071938	18 GHz – 40 GHz	07.13.2011
Active Loop Antenna	FMZB1513	1513-105	9 kHz – 30 MHz	04.01.2012

All test equipments was within their calibration date during the time of testing. When equipment went out of calibration during testing it was replaced using a similar piece of calibrated equipment. All these equipments are listed in the equipment list.

Note that the Agilent power meter, power sensor and the preamplifier are on two-year calibration cycle. Antennas are on three-year calibration cycle. All other equipments are on a one-year calibration cycle.

**Measurement Procedures and Data****RF POWER OUTPUT****Measurement Procedure**

The RF output port of the equipment under test is directly coupled to the input of an Agilent power meter through a 30dB passive attenuator, adaptor (if needed), and specialized RF connector.

**Measurement Results****GSM 850**

Frequency (MHz)	Power (dBm)
824.2	33.45
836.6	33.55
848.8	33.69

**Edge 850**

Frequency (MHz)	Power (dBm)
824.2	28.55
836.6	28.46
848.8	28.58

**GSM 1900**

Frequency (MHz)	Power (dBm)
1850.2	30.64
1880	30.43
1909.8	30.27

**Edge 1900**

Frequency (MHz)	Power (dBm)
1850.2	27.88
1880	27.79
1909.8	27.56

**CDMA800**

Frequency (MHz)	Power (dBm)
824.7	25.19
836.52	24.96
848.31	25.03

APPLICANT: MOTOROLA MOBILITY, INC

FCC ID: IHDT56NH2

**CDMA1900**

Frequency (MHz)	Power (dBm)
1851.25	25.05
1880	25.10
1908.75	24.55

## CDMA Power Measurement Data

Band	Channel	Measured Conducted Power (dBm) for CDMA modes									
		Loopback				Data		EVDO Rev O	EVDO Rev A		
		RC3		RC1		TDSO SO32					
		SO55	SO2	SO55	SO2	+FCH-SCH	+SCH				
CDMA 800	1013	25.19	25.17	25.16	25.2	25.15	25.18	25.15	25.16		
	384	25.02	24.99	24.98	24.96	24.95	24.97	24.99	24.99		
	777	25.03	25.02	25.01	24.98	25.04	25.04	25.07	25.09		
CDMA 1900	25	25.06	25	25.1	25.03	25.08	25.1	25.05	25.08		
	600	25.12	25.1	25.1	25.06	25.06	25.08	25.05	25.11		
	1175	24.58	24.56	24.55	24.55	24.53	24.6	24.62	24.59		

## **RADIATED POWER (EIRP AND ERP)**

### **Measurement Procedure**

The phone was tested in a 16' anechoic chamber with a 2-axis position system that permits taking complete spherical scans of the EUT's radiation patterns. For all tests, the phone was supported in a free space type environment, vertically oriented in the chamber.

All measurements were made with the phone placed in a call using a mobile station test set. The phone was weakly coupled to the test set and configured to transmit in full data rate mode. Radiated power was measured at each 15 degree step. The radiated power was measured using a Peak detector for all bands in the Spectrum Analyzers. From these measurements, the software calculates the angle at which maximum radiated power occurs for each case, and the radiated power at this angle was extracted from the data. To get ERP (effective radiated power referenced to a half-wave dipole), subtract 2.1 dB from these

A Peak detector was used for measurements in the GSM850, GSM1900, CDMA800, CDMA1900.

### **Measurement Results**

<b>Band</b>	<b>EIRP dBm</b>	<b>ERP dBm</b>
GSM850	30.2	<b>28.1</b>
Edge850	31.4	<b>29.3</b>
GSM1900	<b>30.7</b>	28.6
Edge1900	<b>32.9</b>	30.8
CDMA800	26	<b>23.9</b>
CDMA1900	<b>30.5</b>	28.4

## **OCCUPIED BANDWIDTH**

CFR Part 2.1049, 22.917, 24.238

### **Measurement Procedure**

The RF output port of the equipment under test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 20dB passive attenuator for all bands. The amplitude of the spectrum analyzer is corrected for the attenuator and any other applicable losses. The analyzer is set for Peak Detector and each trace is set for Max Hold. A fully charged battery was used for the supply voltage.


The middle channel within the designated frequency block was measured. For digital modulation, the lower and upper band edge plots are displayed.

### **Measurement Results**

Attached


## Measurement Results – GSM 850

### GSM 850 – Reference Level Plot – Channel 190 (836.6 MHz)




Date: 10.APR.2012 15:17:36


### GSM 850 – Channel 190 (836.6 MHz)– Occupied Bandwidth



Date: 10.APR.2012 15:18:54

**GSM 850 – Lower Band Edge – Channel 128 (824.2 MHz)**


Date: 10.APR.2012 15:21:06

**GSM 850 – Upper Band Edge – Channel 251 (848.8 MHz)**

Date: 10.APR.2012 15:22:41

## Measurement Results – Edge 850

### GSM 850 – Channel 190 (836.6 MHz)– Occupied Bandwidth




Date: 10.APR.2012 14:51:47

APPLICANT: MOTOROLA MOBILITY, INC


FCC ID: IHDT56NH2

**GSM 850 – Lower Band Edge – Channel 128 (824.2 MHz)**



Date: 10.APR.2012 14:55:04


**GSM 850 – Upper Band Edge – Channel 251 (848.8 MHz)**



Date: 10.APR.2012 14:57:35


## Measurement Results – PCS 1900

### GSM 1900(PCS) – Reference Level Plot – Channel 661 (1880.00 MHz)




Date: 10.APR.2012 15:24:45


### GSM 1900(PCS) – Channel 661 (1880.00 MHz) – Occupied Bandwidth



Date: 10.APR.2012 15:25:59

**GSM 1900(PCS) – Lower Band Edge – Channel 512 (1850.2 MHz)**


Date: 10.APR.2012 15:27:51

**GSM 1900(PCS) – Upper Band Edge – Channel 810 (1909.8 MHz)**


Date: 10.APR.2012 15:29:17

## **Measurement Results – Edge 1900**


## Edge 1900(PCS) – Channel 661 (1880.00 MHz) – Occupied Bandwidth



Date: 10.APR.2012 15:09:11

**Edge 1900(PCS) – Lower Band Edge – Channel 512 (1850.2 MHz)**


Date: 10.APR.2012 15:11:23

**Edge 1900(PCS) – Upper Band Edge – Channel 810 (1909.8 MHz)**

Date: 10.APR.2012 15:13:09


## Measurement Results – CDMA 1900

### CDMA 1900 – Reference Level Plot – Channel 600 (1880.00 MHz)



Date: 10.APR.2012 14:16:40

### CDMA 1900 – Channel 600 (1880.00 MHz) – Occupied Bandwidth




Date: 10.APR.2012 14:20:15

APPLICANT: MOTOROLA MOBILITY, INC


FCC ID: IHDT56NH2

**CDMA 1900 – Lower Band Edge – Channel 25 (1851.25 MHz)**



Date: 10.APR.2012 14:23:17


**CDMA 1900 – Upper Band Edge – Channel 1175 (1908.75 MHz)**



Date: 10.APR.2012 14:26:27


## Measurement Results – CDMA 800

### CDMA 800 – Reference Level Plot – Channel 384 (836.52 MHz)




Date: 10.APR.2012 14:28:55


### CDMA 800 – Channel 384 (836.52 MHz) – Occupied Bandwidth



Date: 10.APR.2012 14:31:17

**CDMA 800 – Lower Band Edge – Channel 1013 (824.7 MHz)**

Date: 10.APR.2012 14:39:58

**CDMA 800 – Upper Band Edge – Channel 777 (848.31 MHz)**

Date: 10.APR.2012 14:43:14

**SPURIOUS EMISSIONS AT ANTENNA TERMINALS****Measurement Procedure**

The RF output port of the Equipment Under Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 20dB passive attenuator. For all testing the EUT was powered through the computer's USB.

The spectrum was investigated from the lowest frequency signal generated, without going below 9 kHz, up to at least the tenth harmonic of the fundamental or 40 GHz, whichever is lower.

The spectrum analyzer settings were as follows:


Units	dBm
Divisions	10 dB
Detector	Peak Detector
Resolution Bandwidth	1 MHz
Video Bandwidth (AVG)	Auto
Sweep Time	Auto

**Measurement Results**

Attached

**Measurement Results – GSM 850****Conducted Spurious and Harmonic Emissions**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-22.34
3rd harmonic	-13	-24.14
4th harmonic	-13	-36.60
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*




## Notes:

1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – Edge 850****Conducted Spurious and Harmonic Emissions**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-25.06
3rd harmonic	-13	-29.51
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*


**Notes:**

1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – GSM 1900****Conducted Spurious and Harmonic Emissions**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	*
3rd harmonic	-13	-31.79
4th harmonic	-13	-30.86
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*


**Notes:**

1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – Edge 1900****Conducted Spurious and Harmonic Emissions**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-35.83
3rd harmonic	-13	-35.05
4th harmonic	-13	-30.06
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*


**Notes:**

1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – CDMA 800****Conducted Spurious and Harmonic Emissions**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-30.83
3rd harmonic	-13	-30.65
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*


**Notes:**

1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – CDMA 1900****Conducted Spurious and Harmonic Emissions**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-34.56
3rd harmonic	-13	-29.53
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*

**Notes:**

1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

The margin with respect to the limit is the minimum margin for all modes and bands.

**FIELD STRENGTH OF SPURIOUS EMISSIONS****Measurement Procedure**

The equipment under test is placed inside the semi-anechoic chamber on a wooden table at the turntable center. For each spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum reading on the spectrum analyzer. This is repeated for both horizontal and vertical polarizations of the receive antenna.

The equipment under test is then replaced with a substitution antenna fed by a signal generator. With the signal generator tuned to a particular spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters to obtain a maximum reading at the spectrum analyzer. The output of the signal generator is then adjusted until a reading identical to that obtained with the actual transmitter is achieved.

The power in dBm of each spurious emission is calculated by correcting the signal generator level for cable loss and gain of the substitution antenna referenced to a dipole. A fully charged battery was used for the supply voltage.

The settings of the receiver were as follows:


Units	dBm
Divisions	5 dB
Detector	Peak Detector
Resolution Bandwidth	1 MHz
Video Bandwidth (AVG)	Auto
Sweep Time	Auto

**Measurement Results**

Attached

**Measurement Results – GSM 850****Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	-19.2	-24.6
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*




Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – EDGE 850****Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	-28.1	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*



## Notes:


- \* Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm.
- Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
- The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – GSM 1900****Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	*	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*



## Notes:


- \* Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm.
- Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
- The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – EDGE 1900****Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	*	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*



## Notes:


- \* Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm.
- Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
- The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – CDMA 800****Radiated Spurious and Harmonic Emissions**  
Submission # 24965-1      800 CDMA

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	*	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*



## Notes:


- \* Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dB.
- Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
- The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

**Measurement Results – CDMA 1900****Radiated Spurious and Harmonic Emissions**  
Submission # 24965-1 1900 CDMA

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	*	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*



Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

**FREQUENCY STABILITY****Measurement Procedure**

The equipment under test is placed in an environmental chamber. The antenna port of the Equipment Under Test is directly coupled to the input of the measurement equipment through a specialized RF connector. A power supply is attached as the primary voltage supply.

Frequency measurements are made at the extremes of the temperature range -30° C to +60° C and at intervals of 10° C with the primary supply voltage set to the nominal battery operating voltage. A period of time sufficient to stabilize all components of the equipment is allowed at each frequency measurement. The maximum variation of frequency is measured.

At room temperature, the primary supply voltage is reduced to the battery operating endpoint of the equipment under test. The maximum variation of frequency is measured. A battery eliminator was used for the input supply voltage.


**Measurement Results**

Attached

**Measurement Results – GSM 850****Frequency Stability**

Mode: GSM 850      Operating Frequency: 836.6 MHz  
 Channel: 190      Deviation Limit (PPM): 0.1 ppm


Temperature	Frequency Error	Frequency Error	Voltage	Voltage
C	Hz	(PPM)	(%)	(VDC)
-30 C	51.00	0.061	100%	
-20 C	-11.00	-0.013	100%	
-10 C	-17.00	-0.020	100%	
0 C	38.00	0.045	100%	
10 C	29.00	0.035	100%	
20 C	-23.00	-0.027	100%	
30 C	-26.00	-0.031	100%	
40 C	-29.00	-0.035	100%	
50 C	49.00	0.059	100%	
60 C	47.00	0.056	100%	
20 C	-16.00	-0.019	Battery Endpoint	3.50



**Measurement Results – Edge 850****Frequency Stability**

Mode: Edge 850      Operating Frequency: 836.6 MHz  
 Channel: 190      Deviation Limit (PPM): 0.1 ppm


Temperature	Frequency Error	Frequency Error	Voltage	Voltage
C	HZ	(PPM)	(%)	(VDC)
-30 C	52.00	0.062	100%	
-20 C	49.00	0.059	100%	
-10 C	40.00	0.048	100%	
0 C	-28.00	-0.033	100%	
10 C	-39.00	-0.047	100%	
20 C	-21.00	-0.025	100%	
30 C	-43.00	-0.051	100%	
40 C	-35.00	-0.042	100%	
50 C	-49.00	-0.059	100%	
60 C	-38.00	-0.045	100%	
20 C	-45.00	-0.054	Battery Endpoint	3.50



**Measurement Results – GSM 1900****Frequency Stability**

Mode: GSM 1900      Operating Frequency: 1880.0 MHz  
 Channel: 661      Deviation Limit (PPM): 0.1ppm


Temperature	Frequency Error	Frequency Error	Voltage	Voltage
C	HZ	(PPM)	(%)	(VDC)
-30 C	44.00	0.023	100%	
-20 C	30.00	0.016	100%	
-10 C	50.00	0.027	100%	
0 C	61.00	0.032	100%	
10 C	56.00	0.030	100%	
20 C	22.00	0.012	100%	
30 C	-44.00	-0.023	100%	
40 C	-23.00	-0.012	100%	
50 C	99.00	0.053	100%	
60 C	-28.00	-0.015	100%	
20 C	34.00	0.018	Battery Endpoint	3.50



**Measurement Results – Edge 1900****Frequency Stability**


Mode: Edge 1900      Operating Frequency: 1880.0 MHz  
 Channel: 661      Deviation Limit (PPM): 0.1ppm

Temperature	Frequency Error	Frequency Error	Voltage	Voltage
C	HZ	(PPM)	(%)	(VDC)
-30 C	84.00	0.045	100%	
-20 C	-18.00	-0.010	100%	
-10 C	16.00	0.009	100%	
0 C	67.00	0.036	100%	
10 C	98.00	0.052	100%	
20 C	49.00	0.026	100%	
30 C	125.00	0.066	100%	
40 C	-20.00	-0.011	100%	
50 C	-31.00	-0.016	100%	
60 C	42.00	0.022	100%	
20 C	55.00	0.029	Battery Endpoint	3.50




**Measurement Results – CDMA 800****Frequency Stability**Mode: CDMA 800  
Channel: 384Operating Frequency: 836.52 MHz  
Deviation Limit (PPM): 0.359ppm (+/-300 Hz)

Temperature	Frequency Error	Frequency Error	Voltage	Voltage
C	HZ	(PPM)	(%)	(VDC)
-30 C	15.00	0.018	100%	
-20 C	-15.00	-0.018	100%	
-10 C	-12.00	-0.014	100%	
0 C	-13.00	-0.016	100%	
10 C	9.00	0.011	100%	
20 C	-15.00	-0.018	100%	
30 C	11.00	0.013	100%	
40 C	15.00	0.018	100%	
50 C	13.00	0.016	100%	
60 C	17.00	0.020	100%	
20 C	14.00	0.017	Battery Endpoint	3.50



**Measurement Results – CDMA 1900****Frequency Stability**Mode: CDMA 1900  
Channel: 600Operating Frequency: 1880.0 MHz  
Deviation Limit (PPM): 0.08ppm (+/-150Hz)

Temperature	Frequency Error	Frequency Error	Voltage	Voltage
C	HZ	(PPM)	(%)	(VDC)
-30 C	16.00	0.009	100%	
-20 C	18.00	0.010	100%	
-10 C	20.00	0.011	100%	
0 C	14.00	0.007	100%	
10 C	16.00	0.009	100%	
20 C	18.00	0.010	100%	
30 C	12.00	0.006	100%	
40 C	-14.00	-0.007	100%	
50 C	14.00	0.007	100%	
60 C	15.00	0.008	100%	
20 C	12.00	0.006	Battery Endpoint	3.50

**End of Test Report**