


# FCC SAR Test Report

APPLICANT : Motorola Mobility, LLC  
EQUIPMENT : Mobile Cellular Phone  
BRAND NAME : Motorola  
MODEL NAME : 4059  
FCC ID : IHDT56QC1  
STANDARD : FCC 47 CFR Part 2 (2.1093)  
ANSI/IEEE C95.1-1992  
IEEE 1528-2003

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



## SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



# Table of Contents

- 1. Statement of Compliance ..... 4**
- 2. Administration Data ..... 5**
- 3. Guidance Standard ..... 5**
- 4. Equipment Under Test (EUT) ..... 6**
  - 4.1 General Information ..... 6
  - 4.2 Maximum Tune-up Limit..... 7
  - 4.3 General LTE SAR Test and Reporting Considerations ..... 8
- 5. RF Exposure Limits.....10**
  - 5.1 Uncontrolled Environment.....10
  - 5.2 Controlled Environment.....10
- 6. Specific Absorption Rate (SAR).....11**
  - 6.1 Introduction ..... 11
  - 6.2 SAR Definition..... 11
- 7. System Description and Setup .....12**
- 8. Measurement Procedures .....13**
  - 8.1 Spatial Peak SAR Evaluation.....13
  - 8.2 Power Reference Measurement.....14
  - 8.3 Area Scan .....14
  - 8.4 Zoom Scan.....15
  - 8.5 Volume Scan Procedures.....15
  - 8.6 Power Drift Monitoring.....15
- 9. Test Equipment List .....16**
- 10. System Verification .....17**
  - 10.1 Tissue Verification .....17
  - 10.2 System Performance Check Results.....18
- 11. RF Exposure Positions .....19**
  - 11.1 Ear and handset reference point .....19
  - 11.2 Definition of the cheek position.....20
  - 11.3 Definition of the tilt position.....21
  - 11.4 Body Worn Accessory .....22
  - 11.5 Wireless Router.....22
- 12. Conducted RF Output Power (Unit: dBm).....23**
- 13. Antenna Location .....40**
- 14. SAR Test Results .....41**
  - 14.1 Head SAR .....42
  - 14.2 Hotspot SAR .....44
  - 14.3 Body Worn Accessory SAR.....47
  - 14.4 Repeated SAR Measurement .....48
- 15. Simultaneous Transmission Analysis.....49**
  - 15.1 Head Exposure Conditions .....50
  - 15.2 Hotspot Exposure Conditions.....51
  - 15.3 Body-Worn Accessory Exposure Conditions .....53
  - 15.4 SPLSR Evaluation and Analysis.....54
- 16. Uncertainty Assessment .....57**
- 17. References.....59**
- Appendix A. Plots of System Performance Check**
- Appendix B. Plots of High SAR Measurement**
- Appendix C. DASY Calibration Certificate**
- Appendix D. BT/WiFi Reference Report**





**1. Statement of Compliance**

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility, LLC, Mobile Cellular Phone, 4059**, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary			
		Head (Separation 0mm) 1g SAR (W/kg)	Body-worn (Separation 15mm) 1g SAR (W/kg)	Wireless Router (Separation 10mm) 1g SAR (W/kg)	Highest Simultaneous Transmission 1g SAR (W/kg)
PCE	GSM850	0.43	0.45	0.55	1.57
	GSM1900	0.26	0.22	0.53	
	WCDMA Band V	0.68	0.64	0.98	
	WCDMA Band IV	1.08	0.66	<b>1.46</b>	
	WCDMA Band II	0.73	0.77	1.32	
	LTE Band 12	0.56	0.45	0.65	
	LTE Band 17	0.79	0.40	0.64	
	LTE Band 5	0.59	0.76	0.89	
	LTE Band 4	0.83	0.59	1.08	
	LTE Band 2	0.72	0.65	1.37	
	LTE Band 7	<b>1.20</b>	<b>0.98</b>	1.26	
DTS	2.4GHz WLAN	0.89	0.09	0.15	1.57
DSSS	Bluetooth	0.15	0.01	0.02	1.49
Date of Testing:		11/19/2014 ~ 11/30/2014			

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.



## 2. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Motorola Mobility, LLC
Address	222 W. Merchandise Mart Plaza, Chicago IL 60654 USA

Manufacturer	
Company Name	Motorola Mobility, LLC
Address	222 W. Merchandise Mart Plaza, Chicago IL 60654 USA

## 3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03
- FCC KDB 941225 D05 SAR for LTE Devices v02r03
- FCC KDB 941225 D06 Hotspot Mode SAR v02



### 4. Equipment Under Test (EUT)

#### 4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
Model Name	4059
FCC ID	IHDT56QC1
IMEI Code	353333060012612
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	<ul style="list-style-type: none"> <li>• GSM/GPRS/EGPRS</li> <li>• RMC/AMR 12.2Kbps</li> <li>• HSDPA</li> <li>• HSUPA</li> <li>• DC-HSDPA</li> <li>• LTE: QPSK, 16QAM</li> <li>• 802.11b/g/n HT20</li> <li>• Bluetooth v3.0+EDR , Bluetooth v4.0-LE</li> </ul>
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
<b>Remark:</b> <ol style="list-style-type: none"> <li>1. This device supported VoIP in EGPRS, WCDMA, LTE (e.g. 3rd party VoIP).</li> <li>2. The 2.4GHz WLAN and Bluetooth conducted power and SAR testing results were referred to Sporton FCC SAR Test Report, Brand Name: Motorola, Model Name: 4060, FCC ID: IHDT56QC4, Report No: FA4N1482-01 or Appendix D and also used perform transmission simultaneous analysis.</li> <li>3. While operating in body-adjacent exposure configurations during a mobile hotspot session, reduced power limits are enforced on the WCDMA B2 and LTE B2 / B7 transmitter. More detailed information which can be referred to “operational description”.</li> </ol>	



**4.2 Maximum Tune-up Limit**

Mode	Burst average power(dBm)	
	GSM 850	GSM 1900
GSM (GMSK, 1 Tx slot)	33.50	30.50
GPRS (GMSK, 1 Tx slot)	33.50	30.50
GPRS (GMSK, 2 Tx slots)	30.50	27.50
GPRS (GMSK, 3 Tx slots)	28.75	25.75
GPRS (GMSK, 4 Tx slots)	27.50	24.50
EDGE (8PSK, 1 Tx slot)	28.00	27.00
EDGE (8PSK, 2 Tx slots)	25.50	24.50
EDGE (8PSK, 3 Tx slots)	23.25	22.25
EDGE (8PSK, 4 Tx slots)	22.00	21.00

Band / Mode			Average power(dBm)
WCDMA	Band V / IV / II	AMR / RMC 12.2Kbps	24.0
		HSDPA Subtest-1	23.0
		DC-HSDPA Subtest-1	23.0
		HSUPA Subtest-5	23.0
LTE		Band 12	24.0
		Band 17	24.0
		Band 5	24.0
		Band 4	24.0
		Band 2	24.0
		Band 7	24.0

Mode			Average Power (dBm)	
2.4GHz WLAN	802.11b		18.00	
	802.11g	CH 1	16.00	
		CH 6	16.00	
		CH 11	14.00	
	802.11n-HT20	CH 1	16.00	
		CH 6	16.00	
		CH 11	14.00	
Bluetooth	v3.0+EDR	1Mbps	Low	13.00
			Middle	12.00
			High	10.00
		2Mbps	Low	10.00
			Middle	10.00
			High	8.00
	v4.0+LE	3Mbps	Low	10.00
			Middle	10.00
			High	8.00
			Low	10.50
			Middle	12.00
			High	9.00



**4.3 General LTE SAR Test and Reporting Considerations**

Summarized necessary items addressed in KDB 941225 D05 v02r03																																																						
FCC ID	IHDT56QC1																																																					
Equipment Name	Mobile Cellular Phone																																																					
Operating Frequency Range of each LTE transmission band	LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 05: 824.7 MHz ~ 848.3 MHz LTE Band 04: 1710.7 MHz ~ 1754.3 MHz LTE Band 02: 1850.7 MHz ~ 1909.3 MHz LTE Band 07: 2502.5 MHz ~ 2567.5 MHz																																																					
Channel Bandwidth	LTE Band 12: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz LTE Band 05: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 04: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 02: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 07: 5MHz, 10MHz, 15MHz, 20MHz																																																					
Release and Category	Rel8, Cat4																																																					
uplink modulations used	QPSK, and 16QAM																																																					
LTE Voice / Data requirements	Data only																																																					
LTE MPR permanently built-in by design	<table border="1"> <thead> <tr> <th colspan="8">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</th> </tr> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 2</td> </tr> </tbody> </table>								Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3								Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3																																																						
Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)																																															
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																															
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																															
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																															
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																					
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																					
Power reduction applied to satisfy SAR compliance	Yes, When operating in hotspot mode that LTE B2 / B7 power reduction applied to satisfy SAR compliance.																																																					
Transmission (H, M, L) channel numbers and frequencies in each LTE band																																																						
LTE Band 12																																																						
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz																																															
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)																																														
L	23017	699.7	23025	700.5	23035	701.5	23060	704																																														
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5																																														
H	23173	715.3	23165	714.5	23155	713.5	23130	711																																														
LTE Band 17																																																						
	Bandwidth 5 MHz				Bandwidth 10 MHz																																																	
	Channel #		Freq.(MHz)		Channel #		Freq. (MHz)																																															
L	23755		706.5		23780		709																																															
M	23790		710		23790		710																																															
H	23825		713.5		23800		711																																															
LTE Band 5																																																						
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz																																															
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)																																														
L	20407	824.7	20415	825.5	20425	826.5	20450	829																																														
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5																																														
H	20643	848.3	20635	847.5	20625	846.5	20600	844																																														



LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510				
M	21100	2535	21100	2535	21100	2535	21100	2535				
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				



### 5. RF Exposure Limits

#### 5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

#### 5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Limits for Occupational/Controlled Exposure (W/kg)**

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

**Limits for General Population/Uncontrolled Exposure (W/kg)**

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

## **6. Specific Absorption Rate (SAR)**

### **6.1 Introduction**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### **6.2 SAR Definition**

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

## 7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

## **8. Measurement Procedures**

The measurement procedures are as follows:

### <Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### **8.1 Spatial Peak SAR Evaluation**

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

**8.2 Power Reference Measurement**

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

**8.3 Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

### 8.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm*	3 – 4 GHz: $\leq 5$ mm* 4 – 6 GHz: $\leq 4$ mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm	
	graded grid	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm	
Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

### 8.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASYS measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



### 9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1078	Jun. 23, 2014	Jun. 22, 2015
SPEAG	835MHz System Validation Kit	D835V2	4d092	Jun. 23, 2014	Jun. 22, 2015
SPEAG	1750MHz System Validation Kit	D1750V2	1008	Aug. 28, 2014	Aug. 27, 2015
SPEAG	1900MHz System Validation Kit	D1900V2	5d018	Jun. 18, 2014	Jun. 17, 2015
SPEAG	2600MHz System Validation Kit	D2600V2	1058	Jun. 23, 2014	Jun. 22, 2015
SPEAG	Data Acquisition Electronics	DAE4	778	Aug. 21, 2014	Aug. 20, 2015
SPEAG	Data Acquisition Electronics	DAE4	1388	Sep. 24, 2014	Sep. 23, 2015
SPEAG	Data Acquisition Electronics	DAE3	495	May. 19, 2014	May. 18, 2015
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 26, 2014	Sep. 25, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3697	Sep. 29, 2014	Sep. 28, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3925	May. 22, 2014	May. 21, 2015
Wisewind	Thermometer	ETP-101	TM560	Oct. 21, 2014	Oct. 20, 2015
Wisewind	Thermometer	ETP-101	TM685	Oct. 21, 2014	Oct. 20, 2015
Wisewind	Thermometer	HTC-1	TM642	Oct. 21, 2014	Oct. 20, 2015
Wisewind	Thermometer	HTC-1	TM281	Oct. 21, 2014	Oct. 20, 2015
Anritsu	Radio Communication Analyzer	MT8820C	6201074414	Feb. 11, 2014	Feb. 10, 2015
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 27, 2014	May. 26, 2015
SPEAG	Device Holder	N/A	N/A	NCR	NCR
R&S	Signal Generator	SMU200A	102502	Jul. 07, 2014	Jul. 06, 2015
SPEAG	Dielectric Probe Kit	DAKS-3.5	0004	Mar. 04, 2014	Mar. 03, 2015
Agilent	ENA Network Analyzer	E5071C	MY46101588	May. 31, 2014	May. 30, 2015
Anritsu	Power Meter	ML2495A	1036004	Aug. 09, 2014	Aug. 08, 2015
Anritsu	Power Sensor	MA2411B	1027253	Aug. 11, 2014	Aug. 10, 2015
R&S	Spectrum Analyzer	FSP 7	101131	Jul. 10, 2014	Jul. 09, 2015
Agilent	Dual Directional Coupler	778D	50422		Note1
Woken	Attenuator 1	WK0602-XX	N/A		Note1
PE	Attenuator 2	PE7005-10	N/A		Note1
PE	Attenuator 3	PE7005-3	N/A		Note1
AR	Power Amplifier	5S1G4M2	0328767		Note1
Mini-Circuits	Power Amplifier	ZVE-3W	162601250		Note1
Mini-Circuits	Power Amplifier	ZHL-42W+	13440021344		Note1

**General Note:**

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.



## 10. System Verification

### 10.1 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )
<b>For Head</b>								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
<b>For Body</b>								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

#### Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%


#### <Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )	Conductivity Target ( $\sigma$ )	Permittivity Target ( $\epsilon_r$ )	Delta ( $\sigma$ ) (%)	Delta ( $\epsilon_r$ ) (%)	Limit (%)	Date
750	HSL	22.5	0.880	40.752	0.89	41.90	-1.12	-2.74	±5	2014/11/22
750	MSL	22.5	0.965	54.349	0.96	55.50	0.52	-2.07	±5	2014/11/23
835	HSL	22.5	0.886	41.237	0.90	41.50	-1.56	-0.63	±5	2014/11/23
835	MSL	22.4	0.963	54.544	0.97	55.20	-0.72	-1.19	±5	2014/11/24
1750	HSL	22.2	1.394	40.060	1.37	40.10	1.75	-0.10	±5	2014/11/21
1750	HSL	22.5	1.404	39.373	1.37	40.10	2.48	-1.81	±5	2014/11/22
1750	MSL	22.3	1.504	51.589	1.49	53.40	0.94	-3.39	±5	2014/11/21
1750	MSL	22.2	1.527	51.825	1.49	53.40	2.48	-2.95	±5	2014/11/22
1900	HSL	22.3	1.438	39.210	1.40	40.00	2.71	-1.98	±5	2014/11/20
1900	HSL	22.4	1.440	40.631	1.40	40.00	2.86	1.58	±5	2014/11/21
1900	MSL	22.3	1.521	53.218	1.52	53.30	0.07	-0.15	±5	2014/11/20
1900	MSL	22.4	1.553	51.068	1.52	53.30	2.17	-4.19	±5	2014/11/21
2600	HSL	22.4	1.981	38.254	1.96	39.00	1.07	-1.91	±5	2014/11/19
2600	MSL	22.4	2.165	53.823	2.16	52.50	0.23	2.52	±5	2014/11/19
2600	MSL	22.6	2.209	51.123	2.16	52.50	2.27	-2.62	±5	2014/11/26

### 10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2014/11/22	750	HSL	250	D750V3-1078	ES3DV3 - SN3270	DAE4 Sn778	2.07	8.34	8.28	-0.72
2014/11/23	750	MSL	250	D750V3-1078	ES3DV3 - SN3270	DAE4 Sn778	2.19	8.63	8.76	1.51
2014/11/23	835	HSL	250	D835V2-4d092	ES3DV3 - SN3270	DAE4 Sn778	2.37	9.25	9.48	2.49
2014/11/24	835	MSL	250	D835V2-4d092	ES3DV3 - SN3270	DAE4 Sn778	2.28	9.47	9.12	-3.70
2014/11/21	1750	HSL	250	D1750V2-1008	EX3DV4 - SN3697	DAE4 Sn1388	9.07	36.90	36.28	-1.68
2014/11/22	1750	HSL	250	D1750V2-1008	EX3DV4 - SN3697	DAE4 Sn1388	9.13	36.90	36.52	-1.03
2014/11/21	1750	MSL	250	D1750V2-1008	EX3DV4 - SN3697	DAE4 Sn1388	9.44	37.50	37.76	0.69
2014/11/22	1750	MSL	250	D1750V2-1008	EX3DV4 - SN3697	DAE4 Sn1388	9.59	37.50	38.36	2.29
2014/11/20	1900	HSL	250	D1900V2-5d018	EX3DV4 - SN3697	DAE4 Sn1388	9.65	40.10	38.60	-3.74
2014/11/21	1900	HSL	250	D1900V2-5d018	EX3DV4 - SN3697	DAE4 Sn1388	9.43	40.10	37.72	-5.94
2014/11/20	1900	MSL	250	D1900V2-5d018	EX3DV4 - SN3697	DAE4 Sn1388	10.50	39.80	42.00	5.53
2014/11/21	1900	MSL	250	D1900V2-5d018	EX3DV4 - SN3697	DAE4 Sn1388	9.97	39.80	39.88	0.20
2014/11/19	2600	HSL	250	D2600V2_1058	EX3DV4 - SN3697	DAE4 Sn1388	14.50	57.90	58.00	0.17
2014/11/19	2600	MSL	250	D2600V2_1058	EX3DV4 - SN3697	DAE4 Sn1388	15.00	56.80	60.00	5.63
2014/11/26	2600	MSL	250	D2600V2_1058	EX3DV4 - SN3925	DAE3 Sn495	14.20	56.80	56.80	0.00



**Fig 8.3.1 System Performance Check Setup**



**Fig 8.3.2 Setup Photo**

## 11. RF Exposure Positions

### 11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.






Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

**11.2 Definition of the cheek position**


1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width  $w_t$  of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width  $w_b$  of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.



**Fig 9.2.1 Handset vertical and horizontal reference lines—“fixed case”**




**Fig 9.2.2 Handset vertical and horizontal reference lines—“clam-shell case”**



**Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.**

**11.3 Definition of the tilt position**

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




**Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.**

**11.4 Body Worn Accessory**

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB 648474 D04v01r02, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v05r02 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is < 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.



**Fig 9.4 Body Worn Position**

**11.5 Wireless Router**

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC HDB Publication 941225 D06 v02 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05r02 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

## 12. Conducted RF Output Power (Unit: dBm)

### <GSM Conducted Power>

**General Note:**

1. Per KDB 447498 D01v05r02, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.
3. Per KDB 941225 D01v03, for Hotspot SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.

Band GSM850 TX Channel	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM (GMSK, 1 Tx slot)	32.50	32.55	32.65	33.50	23.50	23.55	23.65	24.50
GPRS (GMSK, 1 Tx slot)	32.57	32.62	32.72	33.50	23.57	23.62	23.72	24.50
GPRS (GMSK, 2 Tx slots)	29.41	29.62	29.77	30.50	23.41	23.62	23.77	24.50
GPRS (GMSK, 3 Tx slots)	27.41	27.61	27.76	28.75	23.15	23.35	23.50	24.49
GPRS (GMSK, 4 Tx slots)	26.06	26.25	26.35	27.50	23.06	23.25	23.35	24.50
EDGE (8PSK, 1 Tx slot)	26.54	26.64	26.82	28.00	17.54	17.64	17.82	19.00
EDGE (8PSK, 2 Tx slots)	23.97	24.05	24.25	25.50	17.97	18.05	18.25	19.50
EDGE (8PSK, 3 Tx slots)	22.52	22.61	22.79	23.25	18.26	18.35	18.53	18.99
EDGE (8PSK, 4 Tx slots)	21.19	21.36	21.44	22.00	18.19	18.36	18.44	19.00

Band GSM1900 TX Channel	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
	512	661	810		512	661	810	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM (GMSK, 1 Tx slot)	29.19	29.40	29.48	30.50	20.19	20.40	20.48	21.50
GPRS (GMSK, 1 Tx slot)	29.20	29.41	29.49	30.50	20.20	20.41	20.49	21.50
GPRS (GMSK, 2 Tx slots)	26.21	26.24	26.25	27.50	20.21	20.24	20.25	21.50
GPRS (GMSK, 3 Tx slots)	24.46	24.44	24.57	25.75	20.20	20.18	20.31	21.49
GPRS (GMSK, 4 Tx slots)	23.24	23.22	23.23	24.50	20.24	20.22	20.23	21.50
EDGE (8PSK, 1 Tx slot)	25.54	25.54	25.53	27.00	16.54	16.54	16.53	18.00
EDGE (8PSK, 2 Tx slots)	23.03	23.01	23.00	24.50	17.03	17.01	17.00	18.50
EDGE (8PSK, 3 Tx slots)	21.25	21.21	21.20	22.25	16.99	16.95	16.94	17.99
EDGE (8PSK, 4 Tx slots)	19.96	19.93	19.89	21.00	16.96	16.93	16.89	18.00

**<WCDMA Conducted Power>**

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

**HSDPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each
  - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
  - iii. Set RMC 12.2Kbps + HSDPA mode.
  - iv. Set Cell Power = -86 dBm
  - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
  - vi. Select HSDPA Uplink Parameters
  - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
  - viii. Set Ack-Nack Repetition Factor to 3
  - ix. Set CQI Feedback Cycle (k) to 4 ms
  - x. Set CQI Repetition Factor to 2
  - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

**Table C.10.1.4:  $\beta$  values for transmitter characteristics tests with HS-DPCCH**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta_{ACK}$  and  $\Delta_{NACK} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ , and  $\Delta_{CQI} = 24/15$  with  $\beta_{HS} = 24/15 * \beta_c$ .

Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15, \beta_{HS}/\beta_c = 24/15$ . For all other combinations of DPCCH, DPDCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

**Setup Configuration**

**HSUPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting \* :
  - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
  - ii. Set the Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
  - iii. Set Cell Power = -86 dBm
  - iv. Set Channel Type = 12.2k + HSPA
  - v. Set UE Target Power
  - vi. Power Ctrl Mode= Alternating bits
  - vii. Set and observe the E-TFCl
  - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

**Table C.11.1.3:  $\beta$  values for transmitter characteristics tests with HS-DPCCH and E-DCH**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note 1)	$\beta_{ec}$	$\beta_{ed}$ (Note 5) (Note 6)	$\beta_{ed}$ (SF)	$\beta_{ed}$ (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCl
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/225	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}$ : 47/15 $\beta_{ed2}$ : 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15, \beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6:  $\beta_{ed}$  can not be set directly, it is set by Absolute Grant Value.

**Setup Configuration**

**DC-HSDPA 3GPP release 8 Setup Configuration:**


- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set RMC 12.2Kbps + HSDPA mode.
  - ii. Set Cell Power = -25 dBm
  - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
  - iv. Select HSDPA Uplink Parameters
  - v. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
    - a). Subtest 1:  $\beta_c/\beta_d=2/15$
    - b). Subtest 2:  $\beta_c/\beta_d=12/15$
    - c). Subtest 3:  $\beta_c/\beta_d=15/8$
    - d). Subtest 4:  $\beta_c/\beta_d=15/4$
  - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
  - vii. Set Ack-Nack Repetition Factor to 3
  - viii. Set CQI Feedback Cycle (k) to 4 ms
  - ix. Set CQI Repetition Factor to 2
  - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

**C.8.1.12 Fixed Reference Channel Definition H-Set 12**

**Table C.8.1.12: Fixed Reference Channel H-Set 12**

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload ( $N_{INF}$ )	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		



**Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)**

**Setup Configuration**



**<WCDMA Conducted Power>**

**General Note:**

1. Per KDB 941225 D01v03, SAR for Head / Hotspot / Body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq \frac{1}{4}$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

Band		WCDMA V			WCDMA II			WCDMA IV			
TX Channel		4132	4182	4233	9262	9400	9538	1312	1413	1513	
Frequency (MHz)		826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6	
MPR (dB)	3GPP Rel 99	AMR 12.2Kbps	23.10	23.08	23.00	23.09	22.94	23.02	23.11	23.08	22.97
	3GPP Rel 99	RMC 12.2Kbps	23.11	23.09	23.02	23.11	22.96	23.03	23.12	23.10	22.99
0	3GPP Rel 6	HSDPA Subtest-1	21.92	21.87	21.78	21.79	21.79	21.81	22.13	22.02	21.92
0	3GPP Rel 6	HSDPA Subtest-2	22.02	22.03	21.87	21.86	21.97	21.85	22.17	22.16	22.11
0.5	3GPP Rel 6	HSDPA Subtest-3	21.53	21.47	21.39	21.38	21.48	21.35	21.67	21.65	21.63
0.5	3GPP Rel 6	HSDPA Subtest-4	21.53	21.50	21.41	21.39	21.40	21.36	21.67	21.66	21.58
0	3GPP Rel 8	DC-HSDPA Subtest-1	21.91	21.79	21.72	21.78	21.72	21.79	22.13	21.94	21.83
0	3GPP Rel 8	DC-HSDPA Subtest-2	21.96	21.98	21.82	21.78	21.94	21.77	22.09	22.16	22.05
0.5	3GPP Rel 8	DC-HSDPA Subtest-3	21.45	21.47	21.32	21.33	21.40	21.34	21.62	21.62	21.63
0.5	3GPP Rel 8	DC-HSDPA Subtest-4	21.45	21.42	21.41	21.33	21.39	21.35	21.65	21.61	21.58
0	3GPP Rel 6	HSUPA Subtest-1	21.65	21.78	21.37	21.62	21.64	21.62	22.09	22.06	21.97
2	3GPP Rel 6	HSUPA Subtest-2	20.94	20.58	20.44	20.89	20.32	20.82	20.81	20.79	20.76
1	3GPP Rel 6	HSUPA Subtest-3	20.52	20.50	20.45	20.49	20.41	20.76	20.62	20.62	20.58
2	3GPP Rel 6	HSUPA Subtest-4	21.00	20.75	20.98	21.00	20.99	20.71	20.89	20.85	20.84
0	3GPP Rel 6	HSUPA Subtest-5	21.80	21.80	21.70	21.80	21.80	21.80	22.00	21.96	21.87



**<LTE Conducted Power>**

**General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r03, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r03, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r03, Smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune up Limit (dBm)	MPR (dB)
Channel				23060	23095	23130		
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	23.66	23.56	23.52	24	0
10	QPSK	1	24	23.52	23.45	23.49		
10	QPSK	1	49	23.28	23.25	23.46		
10	QPSK	25	0	22.45	22.35	22.40	23	1
10	QPSK	25	12	22.30	22.18	22.27		
10	QPSK	25	24	22.36	22.26	22.39		
10	QPSK	50	0	22.37	22.30	22.31	23	1
10	16QAM	1	0	22.97	22.98	22.59		
10	16QAM	1	24	22.56	22.91	22.52		
10	16QAM	1	49	22.47	22.14	22.41	22	2
10	16QAM	25	0	21.29	21.30	21.37		
10	16QAM	25	12	21.20	21.13	21.29		
10	16QAM	25	24	21.11	21.25	21.34	22	2
10	16QAM	25	0	21.30	21.18	21.25		
10	16QAM	50	0	21.30	21.18	21.25		
Channel				23035	23095	23155		
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	23.57	23.59	23.48	24	0
5	QPSK	1	12	23.53	23.49	23.46		
5	QPSK	1	24	23.27	23.00	23.35		
5	QPSK	12	0	22.40	22.28	22.17	23	1
5	QPSK	12	6	22.39	22.36	22.35		
5	QPSK	12	11	22.38	22.21	22.36		
5	QPSK	25	0	22.30	22.26	22.37	23	1
5	16QAM	1	0	22.93	22.49	22.72		
5	16QAM	1	12	22.83	22.46	22.70		
5	16QAM	1	24	22.72	22.27	22.49	22	2
5	16QAM	12	0	21.29	21.27	21.13		
5	16QAM	12	6	21.27	21.24	21.27		
5	16QAM	12	11	21.28	21.19	21.24	22	2
5	16QAM	12	0	21.53	21.25	21.37		
5	16QAM	25	0	21.53	21.25	21.37		
Channel				23025	23095	23165		
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	23.56	23.61	23.52	24	0
3	QPSK	1	7	23.47	23.51	23.48		
3	QPSK	1	14	23.24	23.21	23.36		
3	QPSK	8	0	22.38	22.39	22.46	23	1
3	QPSK	8	4	22.40	22.30	22.45		
3	QPSK	8	7	22.42	22.32	22.42		
3	QPSK	15	0	22.37	22.34	22.45	23	1
3	16QAM	1	0	22.45	22.55	22.75		
3	16QAM	1	7	22.39	22.36	22.45		
3	16QAM	1	14	22.29	22.15	22.33	22	2
3	16QAM	8	0	21.35	21.49	21.26		
3	16QAM	8	4	21.35	21.06	21.16		
3	16QAM	8	7	21.48	21.10	21.39	22	2
3	16QAM	8	0	21.34	21.13	21.26		



Channel				23017	23095	23173	Tune up Limit (dBm)	Target MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	23.64	23.40	23.48	24	0
1.4	QPSK	1	2	23.40	23.28	23.37		
1.4	QPSK	1	5	23.37	23.26	23.11		
1.4	QPSK	3	0	23.31	23.16	23.40		
1.4	QPSK	3	1	23.23	23.10	23.43		
1.4	QPSK	3	2	23.18	23.09	23.26		
1.4	QPSK	6	0	22.52	22.26	22.44	23	1
1.4	16QAM	1	0	22.99	22.71	22.66	23	1
1.4	16QAM	1	2	22.91	22.69	22.64		
1.4	16QAM	1	5	22.54	22.52	22.51		
1.4	16QAM	3	0	22.36	22.33	22.46		
1.4	16QAM	3	1	22.22	22.35	22.37		
1.4	16QAM	3	2	22.20	22.24	22.32		
1.4	16QAM	6	0	21.30	20.87	21.31	22	2



<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune up Limit (dBm)	MPR (dB)
Channel				23780	23790	23800		
Frequency (MHz)				709	710	711		
10	QPSK	1	0	23.50	23.53	23.66	24	0
10	QPSK	1	24	23.44	23.49	23.64		
10	QPSK	1	49	23.23	23.35	23.51		
10	QPSK	25	0	22.35	22.40	22.45	23	1
10	QPSK	25	12	22.26	22.25	22.22		
10	QPSK	25	24	22.16	22.25	22.14		
10	QPSK	50	0	22.35	22.31	22.37		
10	16QAM	1	0	22.41	22.32	22.45	23	1
10	16QAM	1	24	22.34	22.24	22.34		
10	16QAM	1	49	22.29	22.19	22.28		
10	16QAM	25	0	21.48	21.28	21.43	22	2
10	16QAM	25	12	21.39	21.43	21.33		
10	16QAM	25	24	21.37	21.40	21.21		
10	16QAM	50	0	21.07	21.14	21.27		
Channel				23755	23790	23825	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				706.5	710	713.5		
5	QPSK	1	0	23.65	23.54	23.45	24	0
5	QPSK	1	12	23.59	23.44	23.40		
5	QPSK	1	24	23.44	23.11	23.18		
5	QPSK	12	0	22.47	22.24	22.16	23	1
5	QPSK	12	6	22.46	22.20	22.42		
5	QPSK	12	11	22.32	22.20	22.36		
5	QPSK	25	0	22.34	22.17	22.27		
5	16QAM	1	0	22.28	22.56	22.42	23	1
5	16QAM	1	12	22.16	22.39	22.04		
5	16QAM	1	24	22.14	22.22	22.18		
5	16QAM	12	0	21.27	21.09	21.12	22	2
5	16QAM	12	6	21.20	21.10	21.18		
5	16QAM	12	11	21.21	21.22	21.31		
5	16QAM	12	11	21.21	21.22	21.31		
5	16QAM	25	0	21.48	21.07	21.13		



<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune up Limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	23.62	23.43	23.55	24	0
10	QPSK	1	24	23.52	23.33	23.53		
10	QPSK	1	49	23.46	23.23	23.47		
10	QPSK	25	0	22.45	22.33	22.38	23	1
10	QPSK	25	12	22.35	22.29	22.32		
10	QPSK	25	24	22.33	22.15	22.31		
10	QPSK	50	0	22.35	22.11	22.32		
10	16QAM	1	0	22.89	22.70	22.89	23	1
10	16QAM	1	24	22.64	22.58	22.81		
10	16QAM	1	49	22.45	22.52	22.72		
10	16QAM	25	0	21.66	21.28	21.45	22	2
10	16QAM	25	12	21.39	21.37	21.38		
10	16QAM	25	24	21.39	21.54	21.27		
10	16QAM	50	0	21.40	21.09	21.22		
Channel				20425	20525	20625	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	23.54	23.55	23.24	24	0
5	QPSK	1	12	23.53	23.52	23.23		
5	QPSK	1	24	23.29	23.11	23.20		
5	QPSK	12	0	22.25	22.35	22.22	23	1
5	QPSK	12	6	22.19	22.30	22.13		
5	QPSK	12	11	22.16	22.30	22.24		
5	QPSK	25	0	22.09	22.21	22.17		
5	16QAM	1	0	22.94	22.77	22.89	23	1
5	16QAM	1	12	22.88	22.69	22.85		
5	16QAM	1	24	22.87	22.54	22.64		
5	16QAM	12	0	21.45	21.21	21.17	22	2
5	16QAM	12	6	21.42	21.31	21.44		
5	16QAM	12	11	21.33	21.12	20.92		
5	16QAM	25	0	21.59	21.29	21.14		
Channel				20415	20525	20635	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	23.60	23.48	23.22	24	0
3	QPSK	1	7	23.39	23.41	23.10		
3	QPSK	1	14	23.29	23.33	23.12		
3	QPSK	8	0	22.55	22.29	22.29	23	1
3	QPSK	8	4	22.57	22.28	22.32		
3	QPSK	8	7	22.45	22.34	22.34		
3	QPSK	15	0	22.51	22.38	22.19		
3	16QAM	1	0	22.85	22.98	22.67	23	1
3	16QAM	1	7	22.75	22.94	22.61		
3	16QAM	1	14	22.69	22.78	22.52		
3	16QAM	8	0	21.49	21.44	21.24	22	2
3	16QAM	8	4	21.42	21.51	21.42		
3	16QAM	8	7	21.38	21.38	21.47		
3	16QAM	15	0	21.32	21.49	21.29		



Channel				20407	20525	20643	Tune up Limit (dBm)	Target MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	23.40	23.49	23.39	24	0
1.4	QPSK	1	2	23.39	23.44	23.34		
1.4	QPSK	1	5	23.37	23.25	23.28		
1.4	QPSK	3	0	23.25	23.24	23.21		
1.4	QPSK	3	1	23.15	23.17	23.20		
1.4	QPSK	3	2	23.11	23.11	23.19		
1.4	QPSK	6	0	22.54	22.35	22.37	23	1
1.4	16QAM	1	0	22.88	22.63	22.98	23	1
1.4	16QAM	1	2	22.81	22.49	22.88		
1.4	16QAM	1	5	22.56	22.45	22.64		
1.4	16QAM	3	0	22.61	22.42	22.54		
1.4	16QAM	3	1	22.51	22.33	22.34		
1.4	16QAM	3	2	22.49	22.30	22.22		
1.4	16QAM	6	0	21.18	21.24	21.21	22	2



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune up Limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	23.81	23.79	23.71	24	0
20	QPSK	1	49	23.68	23.59	23.66		
20	QPSK	1	99	23.59	23.52	23.54		
20	QPSK	50	0	22.79	22.56	22.49	23	1
20	QPSK	50	24	22.63	22.53	22.44		
20	QPSK	50	49	22.45	22.37	22.34		
20	QPSK	100	0	22.58	22.54	22.44		
20	16QAM	1	0	22.94	22.98	22.91	23	1
20	16QAM	1	49	22.88	22.78	22.82		
20	16QAM	1	99	22.79	22.68	22.75		
20	16QAM	50	0	21.61	21.54	21.43	22	2
20	16QAM	50	24	21.44	21.48	21.43		
20	16QAM	50	49	21.40	21.39	21.29		
20	16QAM	100	0	21.50	21.47	21.47		
Channel				20025	20175	20325		
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	23.64	23.80	23.78	24	0
15	QPSK	1	37	23.60	23.77	23.77		
15	QPSK	1	74	23.50	23.66	23.59		
15	QPSK	36	0	22.72	22.60	22.59	23	1
15	QPSK	36	18	22.71	22.58	22.42		
15	QPSK	36	37	22.59	22.49	22.38		
15	QPSK	75	0	22.67	22.41	22.41	23	1
15	16QAM	1	0	22.75	22.76	22.85		
15	16QAM	1	37	22.74	22.52	22.66		
15	16QAM	1	74	22.56	22.35	22.61		
15	16QAM	36	0	21.54	21.65	21.49	22	2
15	16QAM	36	18	21.51	21.67	21.35		
15	16QAM	36	37	21.34	21.42	21.32		
15	16QAM	75	0	21.61	21.31	21.40		
Channel				20000	20175	20350		
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	23.66	23.67	23.47	24	0
10	QPSK	1	24	23.41	23.38	23.23		
10	QPSK	1	49	23.40	23.27	23.44		
10	QPSK	25	0	22.68	22.62	22.48	23	1
10	QPSK	25	12	22.70	22.60	22.46		
10	QPSK	25	24	22.63	22.46	22.39		
10	QPSK	50	0	22.65	22.59	22.44		
10	16QAM	1	0	22.80	22.98	22.88	23	1
10	16QAM	1	24	22.70	22.89	22.77		
10	16QAM	1	49	22.71	22.77	22.51		
10	16QAM	25	0	21.62	21.58	21.51	22	2
10	16QAM	25	12	21.54	21.59	21.36		
10	16QAM	25	24	21.58	21.53	21.40		
10	16QAM	50	0	21.62	21.48	21.36		



Channel				19975	20175	20375	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	23.72	23.55	23.57	24	0
5	QPSK	1	12	23.69	23.49	23.52		
5	QPSK	1	24	23.43	23.08	23.44		
5	QPSK	12	0	22.54	22.50	22.34	23	1
5	QPSK	12	6	22.71	22.54	22.32		
5	QPSK	12	11	22.57	22.44	22.27		
5	QPSK	25	0	22.58	22.54	22.29	23	1
5	16QAM	1	0	22.84	22.56	22.63		
5	16QAM	1	12	22.74	22.47	22.55		
5	16QAM	1	24	22.70	22.39	22.51	22	2
5	16QAM	12	0	21.46	21.46	21.28		
5	16QAM	12	6	21.45	21.50	21.33		
5	16QAM	12	11	21.43	21.29	21.24	22	2
5	16QAM	25	0	21.50	21.57	21.42		
Channel				19965	20175	20385		
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	23.62	23.59	23.51	24	0
3	QPSK	1	7	23.52	23.34	23.49		
3	QPSK	1	14	23.48	23.32	23.36		
3	QPSK	8	0	22.64	22.57	22.42	23	1
3	QPSK	8	4	22.67	22.52	22.31		
3	QPSK	8	7	22.60	22.49	22.30		
3	QPSK	15	0	22.65	22.54	22.32	23	1
3	16QAM	1	0	22.79	22.71	22.66		
3	16QAM	1	7	22.73	22.64	22.58		
3	16QAM	1	14	22.66	22.54	22.23	22	2
3	16QAM	8	0	21.49	21.45	21.63		
3	16QAM	8	4	21.61	21.71	21.52		
3	16QAM	8	7	21.78	21.68	21.49	22	2
3	16QAM	15	0	21.73	21.70	21.38		
Channel				19957	20175	20393		
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	23.56	23.61	23.52	24	0
1.4	QPSK	1	2	23.46	23.53	23.45		
1.4	QPSK	1	5	23.42	23.43	23.39		
1.4	QPSK	3	0	23.36	23.39	23.33		
1.4	QPSK	3	1	23.33	23.32	23.28		
1.4	QPSK	3	2	23.31	23.25	23.21		
1.4	QPSK	6	0	22.53	22.46	22.43	23	1
1.4	16QAM	1	0	22.99	22.85	22.73	23	1
1.4	16QAM	1	2	22.98	22.64	22.59		
1.4	16QAM	1	5	22.82	22.59	22.49		
1.4	16QAM	3	0	22.79	22.53	22.41		
1.4	16QAM	3	1	22.72	22.43	22.39		
1.4	16QAM	3	2	22.66	22.41	22.31		
1.4	16QAM	6	0	21.40	21.49	21.22	22	2



<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune up Limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	23.60	23.51	23.75	24	0
20	QPSK	1	49	23.51	23.49	23.65		
20	QPSK	1	99	23.44	23.38	23.56		
20	QPSK	50	0	22.56	22.55	22.59	23	1
20	QPSK	50	24	22.53	22.51	22.52		
20	QPSK	50	49	22.45	22.39	22.39		
20	QPSK	100	0	22.39	22.38	22.41		
20	16QAM	1	0	22.95	22.86	22.79	23	1
20	16QAM	1	49	22.91	22.54	22.74		
20	16QAM	1	99	22.84	22.57	22.68		
20	16QAM	50	0	21.59	21.57	21.60	22	2
20	16QAM	50	24	21.64	21.49	21.47		
20	16QAM	50	49	21.66	21.39	21.45		
20	16QAM	100	0	21.42	21.32	21.35		
Channel				18675	18900	19125	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	23.74	23.64	23.68	24	0
15	QPSK	1	37	23.71	23.58	23.55		
15	QPSK	1	74	23.63	23.55	23.42		
15	QPSK	36	0	22.71	22.47	22.49	23	1
15	QPSK	36	18	22.66	22.36	22.39		
15	QPSK	36	37	22.65	22.22	22.31		
15	QPSK	75	0	22.43	22.20	22.45	23	1
15	16QAM	1	0	22.43	22.58	22.65		
15	16QAM	1	37	22.28	22.53	22.58		
15	16QAM	1	74	22.19	22.42	22.54		
15	16QAM	36	0	21.58	21.35	21.56	22	2
15	16QAM	36	18	21.60	21.27	21.43		
15	16QAM	36	37	21.70	21.23	21.37		
15	16QAM	75	0	21.44	21.42	21.44		
Channel				18650	18900	19150	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	23.68	23.57	23.39	24	0
10	QPSK	1	24	23.58	23.44	23.25		
10	QPSK	1	49	23.52	23.42	23.21		
10	QPSK	25	0	22.69	22.45	22.43	23	1
10	QPSK	25	12	22.61	22.36	22.38		
10	QPSK	25	24	22.57	22.32	22.35		
10	QPSK	50	0	22.52	22.35	22.39	23	1
10	16QAM	1	0	22.99	22.90	22.88		
10	16QAM	1	24	22.89	22.83	22.70		
10	16QAM	1	49	22.78	22.77	22.60		
10	16QAM	25	0	21.75	21.38	21.37	22	2
10	16QAM	25	12	21.44	21.32	21.48		
10	16QAM	25	24	21.39	21.27	21.51		
10	16QAM	50	0	21.35	21.41	21.26		



Channel				18625	18900	19175	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	23.59	23.41	23.55	24	0
5	QPSK	1	12	23.54	23.31	23.47		
5	QPSK	1	24	23.33	23.25	23.32		
5	QPSK	12	0	22.59	22.36	22.40	23	1
5	QPSK	12	6	22.55	22.36	22.36		
5	QPSK	12	11	22.38	22.32	22.35		
5	QPSK	25	0	22.54	22.26	22.32	23	1
5	16QAM	1	0	22.99	22.87	22.74		
5	16QAM	1	12	22.94	22.75	22.69		
5	16QAM	1	24	22.91	22.69	22.58	22	2
5	16QAM	12	0	21.53	21.32	21.30		
5	16QAM	12	6	21.43	21.32	21.14		
5	16QAM	12	11	21.36	21.27	21.30	22	2
5	16QAM	25	0	21.82	21.32	21.52		
Channel				18615	18900	19185	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	23.64	23.46	23.44	24	0
3	QPSK	1	7	23.59	23.36	23.42		
3	QPSK	1	14	23.45	23.20	23.41		
3	QPSK	8	0	22.54	22.42	22.39	23	1
3	QPSK	8	4	22.52	22.41	22.44		
3	QPSK	8	7	22.49	22.37	22.41		
3	QPSK	15	0	22.43	22.44	22.36	23	1
3	16QAM	1	0	22.95	22.47	22.85		
3	16QAM	1	7	22.89	22.46	22.76		
3	16QAM	1	14	22.80	22.31	22.71	22	2
3	16QAM	8	0	21.82	21.61	21.60		
3	16QAM	8	4	21.59	21.17	21.45		
3	16QAM	8	7	21.56	21.37	21.52	22	2
3	16QAM	15	0	21.61	21.52	21.64		
Channel				18607	18900	19193	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	23.72	23.49	23.55	24	0
1.4	QPSK	1	2	23.62	23.39	23.52		
1.4	QPSK	1	5	23.60	23.38	23.41		
1.4	QPSK	3	0	23.56	23.30	23.38		
1.4	QPSK	3	1	23.52	23.28	23.27		
1.4	QPSK	3	2	23.49	23.17	23.21		
1.4	QPSK	6	0	22.72	22.55	22.80	23	1
1.4	16QAM	1	0	22.69	22.50	22.74	23	1
1.4	16QAM	1	2	22.64	22.48	22.69		
1.4	16QAM	1	5	22.56	22.44	22.64		
1.4	16QAM	3	0	22.50	22.41	22.59		
1.4	16QAM	3	1	22.44	22.35	22.47		
1.4	16QAM	3	2	22.33	22.32	22.43		
1.4	16QAM	6	0	21.15	21.29	21.35	22	2



<LTE Band 7>


BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune up Limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	23.15	23.11	23.14	24	0
20	QPSK	1	49	23.00	23.05	23.06		
20	QPSK	1	99	22.93	22.98	22.96		
20	QPSK	50	0	22.15	21.98	22.10	23	1
20	QPSK	50	24	22.13	21.94	22.08		
20	QPSK	50	49	22.09	21.88	22.03		
20	QPSK	100	0	22.07	22.04	22.01		
20	16QAM	1	0	22.41	22.44	22.32	23	1
20	16QAM	1	49	22.35	22.27	22.30		
20	16QAM	1	99	22.29	22.19	22.23		
20	16QAM	50	0	21.16	21.16	21.26	22	2
20	16QAM	50	24	21.10	21.00	21.16		
20	16QAM	50	49	21.08	21.04	21.16		
20	16QAM	100	0	21.03	20.99	21.18		
Channel				20825	21100	21375	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	23.14	22.94	22.90	24	0
15	QPSK	1	37	23.09	22.84	22.85		
15	QPSK	1	74	22.91	22.78	22.81		
15	QPSK	36	0	22.07	21.75	22.04	23	1
15	QPSK	36	18	21.94	21.73	21.91		
15	QPSK	36	37	21.93	21.78	21.90		
15	QPSK	75	0	22.01	21.74	21.92		
15	16QAM	1	0	21.97	21.77	21.76	23	1
15	16QAM	1	37	21.89	21.57	21.64		
15	16QAM	1	74	21.85	21.70	21.67		
15	16QAM	36	0	21.01	20.88	21.10	22	2
15	16QAM	36	18	20.92	20.78	21.06		
15	16QAM	36	37	20.90	20.77	20.94		
15	16QAM	75	0	20.97	20.59	20.86		
Channel				20800	21100	21400	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	23.11	23.05	23.11	24	0
10	QPSK	1	24	23.06	22.99	23.04		
10	QPSK	1	49	23.04	22.86	22.99		
10	QPSK	25	0	22.17	22.03	22.14	23	1
10	QPSK	25	12	22.10	21.90	22.08		
10	QPSK	25	24	22.14	21.96	22.10		
10	QPSK	50	0	22.16	21.92	22.08		
10	16QAM	1	0	22.29	22.21	22.15	23	1
10	16QAM	1	24	22.13	22.01	22.09		
10	16QAM	1	49	21.80	21.95	22.04		
10	16QAM	25	0	21.24	21.29	21.09	22	2
10	16QAM	25	12	21.18	21.15	21.14		
10	16QAM	25	24	21.14	21.01	21.11		
10	16QAM	50	0	21.05	20.80	21.01		



Channel				20775	21100	21425	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	23.09	22.88	23.13	24	0
5	QPSK	1	12	23.05	22.85	23.05		
5	QPSK	1	24	22.94	22.83	23.02		
5	QPSK	12	0	22.15	21.89	22.17	23	1
5	QPSK	12	6	22.13	21.87	22.21		
5	QPSK	12	11	22.07	21.86	22.15		
5	QPSK	25	0	22.09	21.89	22.16		
5	16QAM	1	0	22.45	21.99	22.37	23	1
5	16QAM	1	12	22.39	21.94	22.35		
5	16QAM	1	24	22.31	21.90	22.25		
5	16QAM	12	0	21.30	21.09	20.85	22	2
5	16QAM	12	6	21.07	20.84	21.06		
5	16QAM	12	11	20.95	20.93	20.98		
5	16QAM	25	0	21.00	20.74	21.13		

### 13. Antenna Location

<Mobile Phone>



Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	≤ 25mm	≤ 25mm
Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes

**General Note:**

- Referring to KDB 941225 D06 v02, when the overall device length and width are ≥ 9cm\*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.



## 14. SAR Test Results

### General Note:

1. Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - b. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)\*Tune-up Scaling Factor
2. Per KDB 447498 D01v05r02, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
  - $\leq 0.6$  W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - $\leq 0.4$  W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz
3. Per KDB 941225 D01v03, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.
4. Per KDB 941225 D01v03, for Hotspot SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.
5. Per KDB 941225 D01v03, SAR for head / Hotspot / Body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
6. Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq \frac{1}{4}$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.
7. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
8. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
9. Per KDB 941225 D05v02r03, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
10. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is  $> \text{not } \frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
11. Per KDB 941225 D05v02r03, Smaller bandwidth output power for each RB allocation configuration is  $> \text{not } \frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.
12. Pre KDB648474 D04v01r02, when the reported SAR for a body-worn accessory, measured without a headset connected to the handset is  $> 1.2$  W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset, if reported SAR  $< 1.2$  W/kg connected to the headset is not required.



14.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Right Cheek	251	848.8	26.35	27.50	1.303	-0.07	0.263	0.343
	GSM850	GPRS (4 Tx slots)	Right Tilted	251	848.8	26.35	27.50	1.303	0.01	0.192	0.250
1	GSM850	GPRS (4 Tx slots)	Left Cheek	251	848.8	26.35	27.50	1.303	0	0.327	0.426
	GSM850	GPRS (4 Tx slots)	Left Cheek	128	824.2	26.06	27.50	1.393	0.08	0.205	0.286
	GSM850	GPRS (4 Tx slots)	Left Cheek	189	836.4	26.25	27.50	1.334	-0.01	0.238	0.317
	GSM850	GPRS (4 Tx slots)	Left Tilted	251	848.8	26.35	27.50	1.303	0.02	0.198	0.258
	GSM1900	GPRS (4 Tx slots)	Right Cheek	512	1850.2	23.24	24.50	1.337	-0.07	0.101	0.135
	GSM1900	GPRS (4 Tx slots)	Right Tilted	512	1850.2	23.24	24.50	1.337	0.07	0.078	0.104
2	GSM1900	GPRS (4 Tx slots)	Left Cheek	512	1850.2	23.24	24.50	1.337	0.19	0.196	0.262
	GSM1900	GPRS (4 Tx slots)	Left Cheek	661	1880	23.22	24.50	1.343	-0.13	0.179	0.240
	GSM1900	GPRS (4 Tx slots)	Left Cheek	810	1909.8	23.23	24.50	1.340	-0.12	0.151	0.202
	GSM1900	GPRS (4 Tx slots)	Left Tilted	512	1850.2	23.24	24.50	1.337	0.04	0.039	0.052

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Right Cheek	4132	826.4	23.11	24.00	1.227	0.04	0.347	0.426
	WCDMA V	RMC 12.2Kbps	Right Tilted	4132	826.4	23.11	24.00	1.227	0.01	0.232	0.285
	WCDMA V	RMC 12.2Kbps	Left Cheek	4132	826.4	23.11	24.00	1.227	0.05	0.446	0.547
	WCDMA V	RMC 12.2Kbps	Left Cheek	4182	836.4	23.09	24.00	1.233	-0.03	0.464	0.572
3	WCDMA V	RMC 12.2Kbps	Left Cheek	4233	846.6	23.02	24.00	1.253	-0.01	0.541	0.678
	WCDMA V	RMC 12.2Kbps	Left Tilted	4132	826.4	23.11	24.00	1.227	0.02	0.263	0.323
	WCDMA IV	RMC 12.2Kbps	Right Cheek	1312	1712.4	23.12	24.00	1.225	-0.01	0.425	0.520
	WCDMA IV	RMC 12.2Kbps	Right Tilted	1312	1712.4	23.12	24.00	1.225	0.06	0.219	0.268
	WCDMA IV	RMC 12.2Kbps	Left Cheek	1312	1712.4	23.12	24.00	1.225	-0.09	0.814	0.997
	WCDMA IV	RMC 12.2Kbps	Left Cheek	1413	1732.6	23.10	24.00	1.230	-0.03	0.847	1.042
4	WCDMA IV	RMC 12.2Kbps	Left Cheek	1513	1752.6	22.99	24.00	1.262	0.07	0.855	1.079
	WCDMA IV	RMC 12.2Kbps	Left Tilted	1312	1712.4	23.12	24.00	1.225	0.08	0.221	0.271
	WCDMA II	RMC 12.2Kbps	Right Cheek	9262	1852.4	23.11	24.00	1.227	-0.04	0.374	0.459
	WCDMA II	RMC 12.2Kbps	Right Tilted	9262	1852.4	23.11	24.00	1.227	0.03	0.196	0.241
	WCDMA II	RMC 12.2Kbps	Left Cheek	9262	1852.4	23.11	24.00	1.227	0.05	0.547	0.671
5	WCDMA II	RMC 12.2Kbps	Left Cheek	9400	1880	22.96	24.00	1.271	0.07	0.573	0.728
	WCDMA II	RMC 12.2Kbps	Left Cheek	9538	1907.6	23.03	24.00	1.250	0.04	0.514	0.643
	WCDMA II	RMC 12.2Kbps	Left Tilted	9262	1852.4	23.11	24.00	1.227	0.06	0.165	0.203

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
6	LTE Band 12	10M	QPSK	1RB	0offset	Right Cheek	23060	704	23.66	24.00	1.081	-0.05	0.514	0.556
	LTE Band 12	10M	QPSK	25RB	0offset	Right Cheek	23060	704	22.45	23.00	1.135	0.01	0.365	0.414
	LTE Band 12	10M	QPSK	1RB	0offset	Right Tilted	23060	704	23.66	24.00	1.081	0.08	0.175	0.189
	LTE Band 12	10M	QPSK	25RB	0offset	Right Tilted	23060	704	22.45	23.00	1.135	-0.02	0.117	0.133
	LTE Band 12	10M	QPSK	1RB	0offset	Left Cheek	23060	704	23.66	24.00	1.081	0.07	0.335	0.362
	LTE Band 12	10M	QPSK	25RB	0offset	Left Cheek	23060	704	22.45	23.00	1.135	0.05	0.220	0.250
	LTE Band 12	10M	QPSK	1RB	0offset	Left Tilted	23060	704	23.66	24.00	1.081	0.01	0.157	0.170
	LTE Band 12	10M	QPSK	25RB	0offset	Left Tilted	23060	704	22.45	23.00	1.135	-0.01	0.106	0.120



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	
7	LTE Band 17	10M	QPSK	1RB	Ooffset	Right Cheek	23800	711	23.66	24.00	1.081	0.11	0.732	<b>0.792</b>	
	LTE Band 17	10M	QPSK	25RB	Ooffset	Right Cheek	23800	711	22.45	23.00	1.135	0.01	0.451	0.512	
	LTE Band 17	10M	QPSK	1RB	Ooffset	Right Tilted	23800	711	23.66	24.00	1.081	0.08	0.243	0.263	
	LTE Band 17	10M	QPSK	25RB	Ooffset	Right Tilted	23800	711	22.45	23.00	1.135	-0.01	0.156	0.177	
	LTE Band 17	10M	QPSK	1RB	Ooffset	Left Cheek	23800	711	23.66	24.00	1.081	0.02	0.461	0.499	
	LTE Band 17	10M	QPSK	25RB	Ooffset	Left Cheek	23800	711	22.45	23.00	1.135	0.03	0.295	0.335	
	LTE Band 17	10M	QPSK	1RB	Ooffset	Left Tilted	23800	711	23.66	24.00	1.081	0.09	0.199	0.215	
	LTE Band 17	10M	QPSK	25RB	Ooffset	Left Tilted	23800	711	22.45	23.00	1.135	0.07	0.127	0.144	
	LTE Band 5	10M	QPSK	1RB	Ooffset	Right Cheek	20450	829	23.62	24.00	1.091	0.14	0.311	0.339	
	LTE Band 5	10M	QPSK	25RB	Ooffset	Right Cheek	20450	829	22.45	23.00	1.135	0.02	0.204	0.232	
	LTE Band 5	10M	QPSK	1RB	Ooffset	Right Tilted	20450	829	23.62	24.00	1.091	0.05	0.236	0.258	
	LTE Band 5	10M	QPSK	25RB	Ooffset	Right Tilted	20450	829	22.45	23.00	1.135	0.04	0.152	0.173	
	LTE Band 5	10M	QPSK	1RB	Ooffset	Left Cheek	20450	829	23.62	24.00	1.091	0	0.432	0.472	
	LTE Band 5	10M	QPSK	1RB	Ooffset	Left Cheek	20525	836.5	23.43	24.00	1.140	-0.05	0.468	0.534	
	8	LTE Band 5	10M	QPSK	1RB	Ooffset	Left Cheek	20600	844	23.55	24.00	1.109	0.08	0.535	<b>0.593</b>
		LTE Band 5	10M	QPSK	25RB	Ooffset	Left Cheek	20450	829	22.45	23.00	1.135	0.06	0.280	0.318
LTE Band 5		10M	QPSK	1RB	Ooffset	Left Tilted	20450	829	23.62	24.00	1.091	0.12	0.251	0.274	
LTE Band 5		10M	QPSK	25RB	Ooffset	Left Tilted	20450	829	22.45	23.00	1.135	-0.01	0.167	0.190	
LTE Band 4		20M	QPSK	1RB	Ooffset	Right Cheek	20050	1720	23.81	24.00	1.045	-0.07	0.480	0.501	
LTE Band 4		20M	QPSK	50RB	Ooffset	Right Cheek	20050	1720	22.79	23.00	1.050	-0.17	0.296	0.311	
LTE Band 4		20M	QPSK	1RB	Ooffset	Right Tilted	20050	1720	23.81	24.00	1.045	0.02	0.228	0.238	
LTE Band 4		20M	QPSK	50RB	Ooffset	Right Tilted	20050	1720	22.79	23.00	1.050	0.02	0.148	0.155	
	LTE Band 4	20M	QPSK	1RB	Ooffset	Left Cheek	20050	1720	23.81	24.00	1.045	0.1	0.605	0.632	
	LTE Band 4	20M	QPSK	1RB	Ooffset	Left Cheek	20175	1732.5	23.79	24.00	1.050	0.14	0.686	0.720	
	9	LTE Band 4	20M	QPSK	1RB	Ooffset	Left Cheek	20300	1745	23.71	24.00	1.069	0.1	0.778	<b>0.832</b>
		LTE Band 4	20M	QPSK	50RB	Ooffset	Left Cheek	20050	1720	22.79	23.00	1.050	0.03	0.450	0.472
		LTE Band 4	20M	QPSK	100RB	Ooffset	Left Cheek	20050	1720	22.58	23.00	1.102	-0.03	0.419	0.462
		LTE Band 4	20M	QPSK	1RB	Ooffset	Left Tilted	20050	1720	23.81	24.00	1.045	0.16	0.211	0.220
		LTE Band 4	20M	QPSK	50RB	Ooffset	Left Tilted	20050	1720	22.79	23.00	1.050	-0.02	0.133	0.140
	LTE Band 2	20M	QPSK	1RB	Ooffset	Right Cheek	19100	1900	23.75	24.00	1.059	-0.08	0.399	0.423	
LTE Band 2	20M	QPSK	50RB	Ooffset	Right Cheek	19100	1900	22.59	23.00	1.099	-0.02	0.251	0.276		
LTE Band 2	20M	QPSK	1RB	Ooffset	Right Tilted	19100	1900	23.75	24.00	1.059	0	0.244	0.258		
	LTE Band 2	20M	QPSK	50RB	Ooffset	Right Tilted	19100	1900	22.59	23.00	1.099	0.04	0.162	0.178	
	LTE Band 2	20M	QPSK	1RB	Ooffset	Left Cheek	19100	1900	23.75	24.00	1.059	-0.03	0.615	0.651	
	LTE Band 2	20M	QPSK	1RB	Ooffset	Left Cheek	18700	1860	23.60	24.00	1.096	-0.04	0.623	0.683	
	10	LTE Band 2	20M	QPSK	1RB	Ooffset	Left Cheek	18900	1880	23.51	24.00	1.119	0.03	0.647	<b>0.724</b>
		LTE Band 2	20M	QPSK	50RB	Ooffset	Left Cheek	19100	1900	22.59	23.00	1.099	-0.01	0.388	0.426
		LTE Band 2	20M	QPSK	1RB	Ooffset	Left Tilted	19100	1900	23.75	24.00	1.059	0.04	0.182	0.193
		LTE Band 2	20M	QPSK	50RB	Ooffset	Left Tilted	19100	1900	22.59	23.00	1.099	0.02	0.111	0.122
	LTE Band 7	20M	QPSK	1RB	Ooffset	Right Cheek	20850	2510	23.15	24.00	1.216	-0.05	0.753	0.916	
LTE Band 7	20M	QPSK	1RB	Ooffset	Right Cheek	21100	2535	23.11	24.00	1.227	-0.07	0.873	1.072		
11	LTE Band 7	20M	QPSK	1RB	Ooffset	Right Cheek	21350	2560	23.14	24.00	1.219	-0.01	0.986	<b>1.202</b>	
	LTE Band 7	20M	QPSK	50RB	Ooffset	Right Cheek	20850	2510	22.15	23.00	1.216	-0.03	0.688	0.837	
	LTE Band 7	20M	QPSK	50RB	Ooffset	Right Cheek	21100	2535	21.98	23.00	1.265	-0.05	0.717	0.907	
	LTE Band 7	20M	QPSK	50RB	Ooffset	Right Cheek	21350	2560	22.10	23.00	1.230	-0.01	0.878	1.080	
	LTE Band 7	20M	QPSK	100RB	Ooffset	Right Cheek	20850	2510	22.07	23.00	1.239	-0.01	0.673	0.834	
	LTE Band 7	20M	QPSK	1RB	Ooffset	Right Tilted	20850	2510	23.15	24.00	1.216	-0.06	0.142	0.173	
	LTE Band 7	20M	QPSK	50RB	Ooffset	Right Tilted	20850	2510	22.15	23.00	1.216	0.04	0.139	0.169	
	LTE Band 7	20M	QPSK	1RB	Ooffset	Left Cheek	20850	2510	23.15	24.00	1.216	-0.03	0.535	0.651	
	LTE Band 7	20M	QPSK	50RB	Ooffset	Left Cheek	20850	2510	22.15	23.00	1.216	0.03	0.483	0.587	
	LTE Band 7	20M	QPSK	1RB	Ooffset	Left Tilted	20850	2510	23.15	24.00	1.216	0.04	0.139	0.169	
LTE Band 7	20M	QPSK	50RB	Ooffset	Left Tilted	20850	2510	22.15	23.00	1.216	0.016	0.114	0.139		



**14.2 Hotspot SAR**

**<GSM SAR>**

Plot No.	Band	Mode	Test Position	Gap (cm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	1cm	OFF	251	848.8	26.35	27.50	1.303	0.01	0.357	0.465
12	GSM850	GPRS (4 Tx slots)	Back	1cm	OFF	251	848.8	26.35	27.50	1.303	0.05	0.421	0.549
	GSM850	GPRS (4 Tx slots)	Back	1cm	OFF	128	824.2	26.06	27.50	1.393	0.01	0.321	0.447
	GSM850	GPRS (4 Tx slots)	Back	1cm	OFF	189	836.4	26.25	27.50	1.334	0.02	0.369	0.492
	GSM850	GPRS (4 Tx slots)	Left Side	1cm	OFF	251	848.8	26.35	27.50	1.303	-0.12	0.406	0.529
	GSM850	GPRS (4 Tx slots)	Right Side	1cm	OFF	251	848.8	26.35	27.50	1.303	-0.05	0.293	0.382
	GSM850	GPRS (4 Tx slots)	Bottom Side	1cm	OFF	251	848.8	26.35	27.50	1.303	0.06	0.082	0.107
	GSM1900	GPRS (4 Tx slots)	Front	1cm	OFF	512	1850.2	23.24	24.50	1.337	-0.04	0.349	0.466
	GSM1900	GPRS (4 Tx slots)	Back	1cm	OFF	512	1850.2	23.24	24.50	1.337	0.03	0.262	0.350
	GSM1900	GPRS (4 Tx slots)	Left Side	1cm	OFF	512	1850.2	23.24	24.50	1.337	-0.11	0.157	0.210
	GSM1900	GPRS (4 Tx slots)	Right Side	1cm	OFF	512	1850.2	23.24	24.50	1.337	-0.1	0.040	0.053
	GSM1900	GPRS (4 Tx slots)	Bottom Side	1cm	OFF	512	1850.2	23.24	24.50	1.337	-0.15	0.354	0.473
	GSM1900	GPRS (4 Tx slots)	Bottom Side	1cm	OFF	661	1880	23.22	24.50	1.343	-0.12	0.364	0.489
13	GSM1900	GPRS (4 Tx slots)	Bottom Side	1cm	OFF	810	1909.8	23.23	24.50	1.340	-0.07	0.398	0.533

**<WCDMA SAR>**

Plot No.	Band	Mode	Test Position	Gap (cm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	1cm	OFF	4132	826.4	23.11	24.00	1.227	-0.02	0.656	0.805
	WCDMA V	RMC 12.2Kbps	Front	1cm	OFF	4182	836.4	23.09	24.00	1.233	0.07	0.468	0.577
	WCDMA V	RMC 12.2Kbps	Front	1cm	OFF	4233	846.6	23.02	24.00	1.253	-0.04	0.554	0.694
14	WCDMA V	RMC 12.2Kbps	Back	1cm	OFF	4132	826.4	23.11	24.00	1.227	0.08	0.794	0.975
	WCDMA V	RMC 12.2Kbps	Back	1cm	OFF	4182	836.4	23.09	24.00	1.233	0	0.582	0.718
	WCDMA V	RMC 12.2Kbps	Back	1cm	OFF	4233	846.6	23.02	24.00	1.253	0.1	0.678	0.850
	WCDMA V	RMC 12.2Kbps	Left Side	1cm	OFF	4132	826.4	23.11	24.00	1.227	0.02	0.755	0.927
	WCDMA V	RMC 12.2Kbps	Left Side	1cm	OFF	4182	836.4	23.09	24.00	1.233	0.13	0.411	0.507
	WCDMA V	RMC 12.2Kbps	Left Side	1cm	OFF	4233	846.6	23.02	24.00	1.253	0.1	0.542	0.679
	WCDMA V	RMC 12.2Kbps	Right Side	1cm	OFF	4132	826.4	23.11	24.00	1.227	0.07	0.308	0.378
	WCDMA V	RMC 12.2Kbps	Bottom Side	1cm	OFF	4132	826.4	23.11	24.00	1.227	0.14	0.134	0.164
	WCDMA IV	RMC 12.2Kbps	Front	1cm	OFF	1312	1712.4	23.12	24.00	1.225	-0.03	0.922	1.129
	WCDMA IV	RMC 12.2Kbps	Front	1cm	OFF	1413	1732.6	23.10	24.00	1.230	0.02	1.120	1.378
15	WCDMA IV	RMC 12.2Kbps	Front	1cm	OFF	1513	1752.6	22.99	24.00	1.262	0.01	1.160	1.464
	WCDMA IV	RMC 12.2Kbps	Back	1cm	OFF	1312	1712.4	23.12	24.00	1.225	-0.05	0.751	0.920
	WCDMA IV	RMC 12.2Kbps	Back	1cm	OFF	1413	1732.6	23.10	24.00	1.230	-0.03	0.880	1.083
	WCDMA IV	RMC 12.2Kbps	Back	1cm	OFF	1513	1752.6	22.99	24.00	1.262	-0.04	0.690	0.871
	WCDMA IV	RMC 12.2Kbps	Left Side	1cm	OFF	1312	1712.4	23.12	24.00	1.225	0.02	0.311	0.381
	WCDMA IV	RMC 12.2Kbps	Right Side	1cm	OFF	1312	1712.4	23.12	24.00	1.225	-0.07	0.068	0.083
	WCDMA IV	RMC 12.2Kbps	Bottom Side	1cm	OFF	1312	1712.4	23.12	24.00	1.225	-0.1	0.549	0.672
	WCDMA II	RMC 12.2Kbps	Front	1cm	ON	9262	1852.4		21.50	1.000	0.05	0.906	0.906
	WCDMA II	RMC 12.2Kbps	Front	1cm	ON	9400	1880		21.50	1.000	-0.07	1.090	1.090
	WCDMA II	RMC 12.2Kbps	Front	1cm	ON	9538	1907.6		21.50	1.000	-0.07	1.110	1.110
	WCDMA II	RMC 12.2Kbps	Back	1cm	ON	9262	1852.4		21.50	1.000	0.03	0.753	0.753
	WCDMA II	RMC 12.2Kbps	Left Side	1cm	ON	9262	1852.4		21.50	1.000	-0.11	0.387	0.387
	WCDMA II	RMC 12.2Kbps	Right Side	1cm	ON	9262	1852.4		21.50	1.000	-0.1	0.077	0.077
	WCDMA II	RMC 12.2Kbps	Bottom Side	1cm	ON	9262	1852.4		21.50	1.000	-0.12	0.934	0.934
	WCDMA II	RMC 12.2Kbps	Bottom Side	1cm	ON	9400	1880		21.50	1.000	-0.12	1.280	1.280
16	WCDMA II	RMC 12.2Kbps	Bottom Side	1cm	ON	9538	1907.6		21.50	1.000	-0.09	1.320	1.320



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (cm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 12	10M	QPSK	1RB	0offset	Front	1cm	OFF	23060	704	23.66	24.00	1.081	-0.05	0.515	0.557
	LTE Band 12	10M	QPSK	25RB	0offset	Front	1cm	OFF	23060	704	22.45	23.00	1.135	-0.03	0.347	0.394
17	LTE Band 12	10M	QPSK	1RB	0offset	Back	1cm	OFF	23060	704	23.66	24.00	1.081	0	0.602	0.651
	LTE Band 12	10M	QPSK	25RB	0offset	Back	1cm	OFF	23060	704	22.45	23.00	1.135	-0.01	0.409	0.464
	LTE Band 12	10M	QPSK	1RB	0offset	Left Side	1cm	OFF	23060	704	23.66	24.00	1.081	0.06	0.128	0.138
	LTE Band 12	10M	QPSK	25RB	0offset	Left Side	1cm	OFF	23060	704	22.45	23.00	1.135	0.09	0.076	0.086
	LTE Band 12	10M	QPSK	1RB	0offset	Right Side	1cm	OFF	23060	704	23.66	24.00	1.081	0.03	0.470	0.508
	LTE Band 12	10M	QPSK	25RB	0offset	Right Side	1cm	OFF	23060	704	22.45	23.00	1.135	0	0.317	0.360
	LTE Band 12	10M	QPSK	1RB	0offset	Bottom Side	1cm	OFF	23060	704	23.66	24.00	1.081	0.08	0.188	0.203
	LTE Band 12	10M	QPSK	25RB	0offset	Bottom Side	1cm	OFF	23060	704	22.45	23.00	1.135	-0.02	0.130	0.148
	LTE Band 17	10M	QPSK	1RB	0offset	Front	1cm	OFF	23800	711	23.66	24.00	1.081	-0.07	0.522	0.565
	LTE Band 17	10M	QPSK	25RB	0offset	Front	1cm	OFF	23800	711	22.45	23.00	1.135	0.02	0.326	0.370
	LTE Band 17	10M	QPSK	1RB	0offset	Back	1cm	OFF	23800	711	23.66	24.00	1.081	0.07	0.546	0.590
	LTE Band 17	10M	QPSK	25RB	0offset	Back	1cm	OFF	23800	711	22.45	23.00	1.135	-0.07	0.340	0.386
	LTE Band 17	10M	QPSK	1RB	0offset	Left Side	1cm	OFF	23800	711	23.66	24.00	1.081	0.04	0.085	0.092
	LTE Band 17	10M	QPSK	25RB	0offset	Left Side	1cm	OFF	23800	711	22.45	23.00	1.135	0.02	0.055	0.062
18	LTE Band 17	10M	QPSK	1RB	0offset	Right Side	1cm	OFF	23800	711	23.66	24.00	1.081	0.04	0.588	0.636
	LTE Band 17	10M	QPSK	25RB	0offset	Right Side	1cm	OFF	23800	711	22.45	23.00	1.135	-0.03	0.373	0.423
	LTE Band 17	10M	QPSK	1RB	0offset	Bottom Side	1cm	OFF	23800	711	23.66	24.00	1.081	0.09	0.257	0.278
	LTE Band 17	10M	QPSK	25RB	0offset	Bottom Side	1cm	OFF	23800	711	22.45	23.00	1.135	-0.12	0.162	0.184
	LTE Band 5	10M	QPSK	1RB	0offset	Front	1cm	OFF	20450	829	23.62	24.00	1.091	0.14	0.577	0.630
	LTE Band 5	10M	QPSK	25RB	0offset	Front	1cm	OFF	20450	829	22.45	23.00	1.135	0.05	0.382	0.434
	LTE Band 5	10M	QPSK	1RB	0offset	Back	1cm	OFF	20450	829	23.62	24.00	1.091	0.1	0.738	0.805
	LTE Band 5	10M	QPSK	1RB	0offset	Back	1cm	OFF	20525	836.5	23.43	24.00	1.140	0.02	0.752	0.857
19	LTE Band 5	10M	QPSK	1RB	0offset	Back	1cm	OFF	20600	844	23.55	24.00	1.109	0.03	0.801	0.888
	LTE Band 5	10M	QPSK	25RB	0offset	Back	1cm	OFF	20450	829	22.45	23.00	1.135	-0.07	0.469	0.532
	LTE Band 5	10M	QPSK	50RB	0offset	Back	1cm	OFF	20450	829	22.35	23.00	1.161	-0.08	0.473	0.549
	LTE Band 5	10M	QPSK	1RB	0offset	Left Side	1cm	OFF	20450	829	23.62	24.00	1.091	-0.04	0.782	0.854
	LTE Band 5	10M	QPSK	1RB	0offset	Left Side	1cm	OFF	20525	836.5	23.43	24.00	1.140	0.11	0.759	0.865
	LTE Band 5	10M	QPSK	1RB	0offset	Left Side	1cm	OFF	20600	844	23.55	24.00	1.109	0.01	0.751	0.833
	LTE Band 5	10M	QPSK	25RB	0offset	Left Side	1cm	OFF	20450	829	22.45	23.00	1.135	-0.12	0.513	0.582
	LTE Band 5	10M	QPSK	50RB	0offset	Left Side	1cm	OFF	20450	829	22.35	23.00	1.161	0	0.500	0.581
	LTE Band 5	10M	QPSK	1RB	0offset	Right Side	1cm	OFF	20450	829	23.62	24.00	1.091	0.15	0.521	0.569
	LTE Band 5	10M	QPSK	25RB	0offset	Right Side	1cm	OFF	20450	829	22.45	23.00	1.135	-0.05	0.365	0.414
	LTE Band 5	10M	QPSK	1RB	0offset	Bottom Side	1cm	OFF	20450	829	23.62	24.00	1.091	0.03	0.112	0.122
	LTE Band 5	10M	QPSK	25RB	0offset	Bottom Side	1cm	OFF	20450	829	22.45	23.00	1.135	0.01	0.077	0.087
	LTE Band 4	20M	QPSK	1RB	0offset	Front	1cm	OFF	20050	1720	23.81	24.00	1.045	0.15	0.811	0.847
	LTE Band 4	20M	QPSK	1RB	0offset	Front	1cm	OFF	20175	1732.5	23.79	24.00	1.050	0.09	0.982	1.031
20	LTE Band 4	20M	QPSK	1RB	0offset	Front	1cm	OFF	20300	1745	23.71	24.00	1.069	0.04	1.010	1.080
	LTE Band 4	20M	QPSK	50RB	0offset	Front	1cm	OFF	20050	1720	22.79	23.00	1.050	0.01	0.583	0.612
	LTE Band 4	20M	QPSK	100RB	0offset	Front	1cm	OFF	20050	1720	22.58	23.00	1.102	0.05	0.604	0.665
	LTE Band 4	20M	QPSK	1RB	0offset	Back	1cm	OFF	20050	1720	23.81	24.00	1.045	-0.03	0.784	0.819
	LTE Band 4	20M	QPSK	1RB	0offset	Back	1cm	OFF	20175	1732.5	23.79	24.00	1.050	-0.06	0.878	0.921
	LTE Band 4	20M	QPSK	1RB	0offset	Back	1cm	OFF	20300	1745	23.71	24.00	1.069	0.07	0.904	0.966
	LTE Band 4	20M	QPSK	50RB	0offset	Back	1cm	OFF	20050	1720	22.79	23.00	1.050	-0.02	0.498	0.523
	LTE Band 4	20M	QPSK	100RB	0offset	Back	1cm	OFF	20050	1720	22.58	23.00	1.102	0.1	0.511	0.563
	LTE Band 4	20M	QPSK	1RB	0offset	Left Side	1cm	OFF	20050	1720	23.81	24.00	1.045	-0.1	0.384	0.401
	LTE Band 4	20M	QPSK	50RB	0offset	Left Side	1cm	OFF	20050	1720	22.79	23.00	1.050	0.06	0.238	0.250
	LTE Band 4	20M	QPSK	1RB	0offset	Right Side	1cm	OFF	20050	1720	23.81	24.00	1.045	0.16	0.080	0.084
	LTE Band 4	20M	QPSK	50RB	0offset	Right Side	1cm	OFF	20050	1720	22.79	23.00	1.050	0.02	0.051	0.054
	LTE Band 4	20M	QPSK	1RB	0offset	Bottom Side	1cm	OFF	20050	1720	23.81	24.00	1.045	-0.07	0.540	0.564
	LTE Band 4	20M	QPSK	50RB	0offset	Bottom Side	1cm	OFF	20050	1720	22.79	23.00	1.050	-0.02	0.359	0.377



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (cm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1RB	0offset	Front	1cm	ON	19100	1900		22.50	1.000	0.07	0.988	0.988
	LTE Band 2	20M	QPSK	1RB	0offset	Front	1cm	ON	18700	1860		22.50	1.000	0.11	0.855	0.855
	LTE Band 2	20M	QPSK	1RB	0offset	Front	1cm	ON	18900	1880		22.50	1.000	-0.1	0.947	0.947
	LTE Band 2	20M	QPSK	50RB	0offset	Front	1cm	ON	19100	1900		22.50	1.000	-0.05	0.827	0.827
	LTE Band 2	20M	QPSK	50RB	0offset	Front	1cm	ON	18700	1860		22.50	1.000	0.04	0.684	0.684
	LTE Band 2	20M	QPSK	50RB	0offset	Front	1cm	ON	18900	1880		22.50	1.000	-0.02	0.769	0.769
	LTE Band 2	20M	QPSK	100RB	0offset	Front	1cm	ON	19100	1900		22.50	1.000	0.01	0.826	0.826
	LTE Band 2	20M	QPSK	1RB	0offset	Back	1cm	ON	19100	1900		22.50	1.000	0.11	0.835	0.835
	LTE Band 2	20M	QPSK	1RB	0offset	Back	1cm	ON	18700	1860		22.50	1.000	-0.18	0.655	0.655
	LTE Band 2	20M	QPSK	1RB	0offset	Back	1cm	ON	18900	1880		22.50	1.000	0.06	0.744	0.744
	LTE Band 2	20M	QPSK	50RB	0offset	Back	1cm	ON	19100	1900		22.50	1.000	0.01	0.679	0.679
	LTE Band 2	20M	QPSK	100RB	0offset	Back	1cm	ON	19100	1900		22.50	1.000	0.04	0.674	0.674
	LTE Band 2	20M	QPSK	1RB	0offset	Left Side	1cm	ON	19100	1900		22.50	1.000	0.09	0.369	0.369
	LTE Band 2	20M	QPSK	50RB	0offset	Left Side	1cm	ON	19100	1900		22.50	1.000	0.01	0.293	0.293
	LTE Band 2	20M	QPSK	1RB	0offset	Right Side	1cm	ON	19100	1900		22.50	1.000	0.04	0.075	0.075
	LTE Band 2	20M	QPSK	50RB	0offset	Right Side	1cm	ON	19100	1900		22.50	1.000	0.1	0.053	0.053
21	LTE Band 2	20M	QPSK	1RB	0offset	Bottom Side	1cm	ON	19100	1900		22.50	1.000	-0.1	1.370	1.370
	LTE Band 2	20M	QPSK	1RB	0offset	Bottom Side	1cm	ON	18700	1860		22.50	1.000	0.07	0.923	0.923
	LTE Band 2	20M	QPSK	1RB	0offset	Bottom Side	1cm	ON	18900	1880		22.50	1.000	-0.09	1.150	1.150
	LTE Band 2	20M	QPSK	50RB	0offset	Bottom Side	1cm	ON	19100	1900		22.50	1.000	-0.13	1.090	1.090
	LTE Band 2	20M	QPSK	50RB	0offset	Bottom Side	1cm	ON	18700	1860		22.50	1.000	-0.05	0.737	0.737
	LTE Band 2	20M	QPSK	50RB	0offset	Bottom Side	1cm	ON	18900	1880		22.50	1.000	-0.03	1.010	1.010
	LTE Band 2	20M	QPSK	100RB	0offset	Bottom Side	1cm	ON	19100	1900		22.50	1.000	-0.01	1.120	1.120
	LTE Band 7	20M	QPSK	1RB	0offset	Front	1cm	ON	20850	2510		21.00	1.000	-0.01	0.773	0.773
	LTE Band 7	20M	QPSK	50RB	0offset	Front	1cm	ON	20850	2510		21.00	1.000	-0.08	0.767	0.767
	LTE Band 7	20M	QPSK	1RB	0offset	Back	1cm	ON	20850	2510		21.00	1.000	-0.02	0.505	0.505
	LTE Band 7	20M	QPSK	50RB	0offset	Back	1cm	ON	20850	2510		21.00	1.000	0.05	0.527	0.527
	LTE Band 7	20M	QPSK	1RB	0offset	Left Side	1cm	ON	20850	2510		21.00	1.000	-0.07	0.134	0.134
	LTE Band 7	20M	QPSK	50RB	0offset	Left Side	1cm	ON	20850	2510		21.00	1.000	0.01	0.130	0.130
	LTE Band 7	20M	QPSK	1RB	0offset	Right Side	1cm	ON	20850	2510		21.00	1.000	0.01	0.819	0.819
	LTE Band 7	20M	QPSK	1RB	0offset	Right Side	1cm	ON	21100	2535		21.00	1.000	0.15	1.020	1.020
	LTE Band 7	20M	QPSK	1RB	0offset	Right Side	1cm	ON	21350	2560		21.00	1.000	-0.07	1.220	1.220
	LTE Band 7	20M	QPSK	50RB	0offset	Right Side	1cm	ON	20850	2510		21.00	1.000	-0.02	0.817	0.817
	LTE Band 7	20M	QPSK	50RB	0offset	Right Side	1cm	ON	21100	2535		21.00	1.000	-0.03	1.020	1.020
22	LTE Band 7	20M	QPSK	50RB	0offset	Right Side	1cm	ON	21350	2560		21.00	1.000	-0.04	1.260	1.260
	LTE Band 7	20M	QPSK	100RB	0offset	Right Side	1cm	ON	20850	2510		21.00	1.000	0.05	0.840	0.840
	LTE Band 7	20M	QPSK	1RB	0offset	Bottom Side	1cm	ON	20850	2510		21.00	1.000	-0.1	0.594	0.594
	LTE Band 7	20M	QPSK	50RB	0offset	Bottom Side	1cm	ON	20850	2510		21.00	1.000	-0.08	0.604	0.604



**14.3 Body Worn Accessory SAR**

**<GSM SAR>**

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	1.5cm	251	848.8	26.35	27.50	1.303	-0.06	0.317	0.413
23	GSM850	GPRS (4 Tx slots)	Back	1.5cm	251	848.8	26.35	27.50	1.303	0.02	0.348	<b>0.454</b>
	GSM850	GPRS (4 Tx slots)	Back	1.5cm	128	824.2	26.06	27.50	1.393	-0.03	0.267	0.372
	GSM850	GPRS (4 Tx slots)	Back	1.5cm	189	836.4	26.25	27.50	1.334	-0.01	0.311	0.415
24	GSM1900	GPRS (4 Tx slots)	Front	1.5cm	512	1850.2	23.24	24.50	1.337	0.01	0.164	<b>0.219</b>
	GSM1900	GPRS (4 Tx slots)	Front	1.5cm	661	1880	23.22	24.50	1.343	-0.01	0.155	0.208
	GSM1900	GPRS (4 Tx slots)	Front	1.5cm	810	1909.8	23.23	24.50	1.340	0.08	0.154	0.206
	GSM1900	GPRS (4 Tx slots)	Back	1.5cm	512	1850.2	23.24	24.50	1.337	-0.03	0.125	0.167

**<WCDMA SAR>**

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	1.5cm	4132	826.4	23.11	24.00	1.227	0	0.297	0.365
	WCDMA V	RMC 12.2Kbps	Back	1.5cm	4132	826.4	23.11	24.00	1.227	-0.07	0.364	0.447
	WCDMA V	RMC 12.2Kbps	Back	1.5cm	4182	836.4	23.09	24.00	1.233	0.01	0.426	0.525
25	WCDMA V	RMC 12.2Kbps	Back	1.5cm	4233	846.6	23.02	24.00	1.253	-0.03	0.510	<b>0.639</b>
	WCDMA IV	RMC 12.2Kbps	Front	1.5cm	1312	1712.4	23.12	24.00	1.225	0.08	0.475	0.582
26	WCDMA IV	RMC 12.2Kbps	Front	1.5cm	1413	1732.6	23.10	24.00	1.230	0.03	0.540	<b>0.664</b>
	WCDMA IV	RMC 12.2Kbps	Front	1.5cm	1513	1752.6	22.99	24.00	1.262	-0.05	0.481	0.607
	WCDMA IV	RMC 12.2Kbps	Back	1.5cm	1312	1712.4	23.12	24.00	1.225	0.02	0.401	0.491
	WCDMA II	RMC 12.2Kbps	Front	1.5cm	9262	1852.4	23.11	24.00	1.227	-0.02	0.493	0.605
	WCDMA II	RMC 12.2Kbps	Front	1.5cm	9400	1880	22.96	24.00	1.271	0.02	0.580	0.737
27	WCDMA II	RMC 12.2Kbps	Front	1.5cm	9538	1907.6	23.03	24.00	1.250	0	0.614	<b>0.768</b>
	WCDMA II	RMC 12.2Kbps	Back	1.5cm	9262	1852.4	23.11	24.00	1.227	-0.1	0.431	0.529

**<LTE SAR>**

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 12	10M	QPSK	1RB	0offset	Front	1.5cm	23060	704	23.66	24.00	1.081	-0.09	0.397	0.429
	LTE Band 12	10M	QPSK	25RB	0offset	Front	1.5cm	23060	704	22.45	23.00	1.135	0.01	0.277	0.314
28	LTE Band 12	10M	QPSK	1RB	0offset	Back	1.5cm	23060	704	23.66	24.00	1.081	-0.03	0.418	<b>0.452</b>
	LTE Band 12	10M	QPSK	25RB	0offset	Back	1.5cm	23060	704	22.45	23.00	1.135	0.01	0.292	0.331
	LTE Band 17	10M	QPSK	1RB	0offset	Front	1.5cm	23800	711	23.66	24.00	1.081	0.1	0.357	0.386
	LTE Band 17	10M	QPSK	25RB	0offset	Front	1.5cm	23800	711	22.45	23.00	1.135	0.04	0.228	0.259
29	LTE Band 17	10M	QPSK	1RB	0offset	Back	1.5cm	23800	711	23.66	24.00	1.081	-0.04	0.366	<b>0.396</b>
	LTE Band 17	10M	QPSK	25RB	0offset	Back	1.5cm	23800	711	22.45	23.00	1.135	0.01	0.231	0.262
	LTE Band 5	10M	QPSK	1RB	0offset	Front	1.5cm	20450	829	23.62	24.00	1.091	-0.18	0.520	0.568
	LTE Band 5	10M	QPSK	25RB	0offset	Front	1.5cm	20450	829	22.45	23.00	1.135	-0.08	0.344	0.390
	LTE Band 5	10M	QPSK	1RB	0offset	Back	1.5cm	20450	829	23.62	24.00	1.091	-0.14	0.600	0.655
	LTE Band 5	10M	QPSK	1RB	0offset	Back	1.5cm	20525	836.5	23.43	24.00	1.140	-0.17	0.637	0.726
30	LTE Band 5	10M	QPSK	1RB	0offset	Back	1.5cm	20600	844	23.55	24.00	1.109	-0.15	0.684	<b>0.759</b>
	LTE Band 5	10M	QPSK	25RB	0offset	Back	1.5cm	20450	829	22.45	23.00	1.135	0.03	0.406	0.461

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 4	20M	QPSK	1RB	0offset	Front	1.5cm	20050	1720	23.81	24.00	1.045	0.09	0.452	0.472
	LTE Band 4	20M	QPSK	1RB	0offset	Front	1.5cm	20175	1732.5	23.79	24.00	1.050	0.14	0.509	0.534
31	LTE Band 4	20M	QPSK	1RB	0offset	Front	1.5cm	20300	1745	23.71	24.00	1.069	0.06	0.549	0.587
	LTE Band 4	20M	QPSK	50RB	0offset	Front	1.5cm	20050	1720	22.79	23.00	1.050	0.03	0.305	0.320
	LTE Band 4	20M	QPSK	1RB	0offset	Back	1.5cm	20050	1720	23.81	24.00	1.045	0.06	0.428	0.447
	LTE Band 4	20M	QPSK	50RB	0offset	Back	1.5cm	20050	1720	22.79	23.00	1.050	-0.01	0.275	0.289
32	LTE Band 2	20M	QPSK	1RB	0offset	Front	1.5cm	19100	1900	23.75	24.00	1.059	0.07	0.615	0.651
	LTE Band 2	20M	QPSK	1RB	0offset	Front	1.5cm	18700	1860	23.60	24.00	1.096	0.02	0.507	0.556
	LTE Band 2	20M	QPSK	1RB	0offset	Front	1.5cm	18900	1880	23.51	24.00	1.119	-0.05	0.559	0.626
	LTE Band 2	20M	QPSK	50RB	0offset	Front	1.5cm	19100	1900	22.59	23.00	1.099	0	0.417	0.458
	LTE Band 2	20M	QPSK	1RB	0offset	Back	1.5cm	19100	1900	23.75	24.00	1.059	-0.18	0.520	0.551
	LTE Band 2	20M	QPSK	50RB	0offset	Back	1.5cm	19100	1900	22.59	23.00	1.099	-0.02	0.328	0.360
	LTE Band 7	20M	QPSK	1RB	0offset	Front	1.5cm	20850	2510	23.15	24.00	1.216	0.01	0.665	0.809
	LTE Band 7	20M	QPSK	1RB	0offset	Front	1.5cm	21100	2535	23.11	24.00	1.227	0.07	0.750	0.921
33	LTE Band 7	20M	QPSK	1RB	0offset	Front	1.5cm	21350	2560	23.14	24.00	1.219	0.06	0.801	0.976
	LTE Band 7	20M	QPSK	50RB	0offset	Front	1.5cm	20850	2510	22.15	23.00	1.216	-0.01	0.582	0.708
	LTE Band 7	20M	QPSK	100RB	0offset	Front	1.5cm	20850	2510	22.07	23.00	1.239	-0.01	0.541	0.670
	LTE Band 7	20M	QPSK	1RB	0offset	Back	1.5cm	20850	2510	23.15	24.00	1.216	-0.06	0.491	0.597
	LTE Band 7	20M	QPSK	50RB	0offset	Back	1.5cm	20850	2510	22.15	23.00	1.216	-0.07	0.438	0.533

### 14.4 Repeated SAR Measurement

No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (cm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Front	1cm	OFF	1513	1752.6	22.99	24.00	1.262	0.01	1.160	-	1.464
2nd	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Front	1cm	OFF	1513	1752.6	22.99	24.00	1.262	0.02	1.020	1.14	1.287
1st	LTE Band 5	10M	QPSK	1RB	0offset	-	Back	1cm	OFF	20600	844	23.55	24.00	1.109	0.03	0.801	-	0.888
2nd	LTE Band 5	10M	QPSK	1RB	0offset	-	Back	1cm	OFF	20600	844	23.55	24.00	1.109	0.04	0.714	1.12	0.792
1st	LTE Band 2	20M	QPSK	1RB	0offset	-	Bottom Side	1cm	ON	19100	1900		22.50	1.000	-0.1	1.370	-	1.370
2nd	LTE Band 2	20M	QPSK	1RB	0offset	-	Bottom Side	1cm	ON	19100	1900		22.50	1.000	-0.08	1.310	1.05	1.310
1st	LTE Band 7	20M	QPSK	50RB	0offset	-	Right Side	1cm	ON	21350	2560		21.00	1.000	-0.04	1.260	-	1.260
2nd	LTE Band 7	20M	QPSK	50RB	0offset	-	Right Side	1cm	ON	21350	2560		21.00	1.000	-0.01	1.220	1.03	1.220

**General Note:**

1. Per KDB 865664 D01v01r03, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8W/kg$
2. Per KDB 865664 D01v01r03, if the ratio among the repeated measurement is  $\leq 1.2$  and the measured SAR  $< 1.45W/kg$ , only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured* SAR.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

## 15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			Note
		Head	Body-worn	Hotspot	
1.	GSM(Voice) + WLAN2.4GHz(data)	Yes	Yes		
2.	WCDMA(Voice) + WLAN2.4GHz(data)	Yes	Yes		
3.	GSM(Voice) + Bluetooth(data)	Yes	Yes		
4.	WCDMA((Voice) + Bluetooth(data)	Yes	Yes		
5.	GPRS/EDGE(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
6.	WCDMA(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
7.	LTE(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
8.	GPRS/EDGE(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
9.	WCDMA(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
10.	LTE(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering

### General Note:

1. The 2.4GHz WLAN and Bluetooth conducted power and SAR testing results were referred to Sporton FCC SAR Test Report, Brand Name: Motorola, Model Name: 4060, FCC ID: IHDT56QC4, Report No: FA4N1482-01 or Appendix D and also used perform transmission simultaneous analysis.
2. This device supported VoIP in EGPRS, WCDMA, LTE (e.g. 3rd party VoIP).
3. The Scaled SAR summation is calculated based on the same configuration and test position.
4. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
5. Per KDB 447498 D01v05r02, simultaneous transmission SAR is compliant if,
  - i) Scalar SAR summation < 1.6W/kg.
  - ii)  $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$ , and the peak separation distance is determined from the square root of  $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$ , where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
  - iii) If  $SPLSR \leq 0.04$ , simultaneously transmission SAR measurement is not necessary.
  - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
  - v) The SPLSR calculated results please refer to section 15.4.



15.1 Head Exposure Conditions

WWAN Band	Exposure Position	1	2	3	1+2 Summed SAR (W/kg)	1+3 Summed SAR (W/kg)	SPLSR	Case No	
		WWAN	2.4GHz WLAN	2.4GHz Bluetooth					
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)					
GSM	GSM850	Right Cheek	0.343	0.535	0.086	0.88	0.43		
		Right Tilted	0.250	0.504	0.081	0.75	0.33		
		Left Cheek	0.426	0.891	0.153	1.32	0.58		
		Left Tilted	0.258	0.589	0.101	0.85	0.36		
	GSM1900	Right Cheek	0.135	0.535	0.086	0.67	0.22		
		Right Tilted	0.104	0.504	0.081	0.61	0.19		
		Left Cheek	0.262	0.891	0.153	1.15	0.42		
		Left Tilted	0.052	0.589	0.101	0.64	0.15		
WCDMA	Band V	Right Cheek	0.426	0.535	0.086	0.96	0.51		
		Right Tilted	0.285	0.504	0.081	0.79	0.37		
		Left Cheek	0.678	0.891	0.153	1.57	0.83		
		Left Tilted	0.323	0.589	0.101	0.91	0.42		
	Band IV	Right Cheek	0.520	0.535	0.086	1.06	0.61		
		Right Tilted	0.268	0.504	0.081	0.77	0.35		
		Left Cheek	1.079	0.891	0.153	1.97	1.23	0.04	Case 1
		Left Tilted	0.271	0.589	0.101	0.86	0.37		
	Band II	Right Cheek	0.459	0.535	0.086	0.99	0.55		
		Right Tilted	0.241	0.504	0.081	0.75	0.32		
		Left Cheek	0.728	0.891	0.153	1.62	0.88	0.03	Case 2
		Left Tilted	0.203	0.589	0.101	0.79	0.30		
LTE	Band 12	Right Cheek	0.556	0.535	0.086	1.09	0.64		
		Right Tilted	0.189	0.504	0.081	0.69	0.27		
		Left Cheek	0.362	0.891	0.153	1.25	0.52		
		Left Tilted	0.170	0.589	0.101	0.76	0.27		
	Band 17	Right Cheek	0.792	0.535	0.086	1.33	0.88		
		Right Tilted	0.263	0.504	0.081	0.77	0.34		
		Left Cheek	0.499	0.891	0.153	1.39	0.65		
		Left Tilted	0.215	0.589	0.101	0.80	0.32		
	Band 5	Right Cheek	0.339	0.535	0.086	0.87	0.43		
		Right Tilted	0.258	0.504	0.081	0.76	0.34		
		Left Cheek	0.593	0.891	0.153	1.48	0.75		
		Left Tilted	0.274	0.589	0.101	0.86	0.38		
	Band 4	Right Cheek	0.501	0.535	0.086	1.04	0.59		
		Right Tilted	0.238	0.504	0.081	0.74	0.32		
		Left Cheek	0.832	0.891	0.153	1.72	0.99	0.03	Case 3
		Left Tilted	0.220	0.589	0.101	0.81	0.32		
	Band 2	Right Cheek	0.423	0.535	0.086	0.96	0.51		
		Right Tilted	0.258	0.504	0.081	0.76	0.34		
		Left Cheek	0.724	0.891	0.153	1.62	0.88	0.03	Case 4
		Left Tilted	0.193	0.589	0.101	0.78	0.29		
	Band 7	Right Cheek	1.202	0.535	0.086	1.74	1.29	0.03	Case 5
		Right Tilted	0.173	0.504	0.081	0.68	0.25		
		Left Cheek	0.651	0.891	0.153	1.54	0.80		
		Left Tilted	0.169	0.589	0.101	0.76	0.27		



**15.2 Hotspot Exposure Conditions**

WWAN Band	Exposure Position	1	2	3	1+2 Summed SAR (W/kg)	1+3 Summed SAR (W/kg)	SPLSR	Case No	
		WWAN	2.4GHz WLAN	2.4GHz Bluetooth					
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)					
GSM	GSM850	Front	0.465	0.150	0.022	0.62	0.49		
		Back	0.549	0.110	0.017	0.66	0.57		
		Left side	0.529			0.53	0.53		
		Right side	0.382	0.064	0.010	0.45	0.39		
		Top side		0.113	0.014	0.11	0.01		
		Bottom side	0.107			0.11	0.11		
	GSM1900	Front	0.466	0.150	0.022	0.62	0.49		
		Back	0.350	0.110	0.017	0.46	0.37		
		Left side	0.210			0.21	0.21		
		Right side	0.053	0.064	0.010	0.12	0.06		
		Top side		0.113	0.014	0.11	0.01		
		Bottom side	0.533			0.53	0.53		
WCDMA	Band V	Front	0.805	0.150	0.022	0.96	0.83		
		Back	0.975	0.110	0.017	1.09	0.99		
		Left side	0.927			0.93	0.93		
		Right side	0.378	0.064	0.010	0.44	0.39		
		Top side		0.113	0.014	0.11	0.01		
		Bottom side	0.164			0.16	0.16		
	Band IV	Front	1.464	0.150	0.022	1.61	1.49	0.02	Case 6
		Back	1.083	0.110	0.017	1.19	1.10		
		Left side	0.381			0.38	0.38		
		Right side	0.083	0.064	0.010	0.15	0.09		
		Top side		0.113	0.014	0.11	0.01		
		Bottom side	0.672			0.67	0.67		
	Band II	Front	1.110	0.150	0.022	1.26	1.13		
		Back	0.753	0.110	0.017	0.86	0.77		
		Left side	0.387			0.39	0.39		
		Right side	0.077	0.064	0.010	0.14	0.09		
		Top side		0.113	0.014	0.11	0.01		
		Bottom side	1.320			1.32	1.32		



WWAN Band	Exposure Position	1	2	3	1+2 Summed SAR (W/kg)	1+3 Summed SAR (W/kg)	SPLSR	Case No	
		WWAN	2.4GHz WLAN	2.4GHz Bluetooth					
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)					
LTE	Band 12	Front	0.557	0.150	0.022	<b>0.71</b>	<b>0.58</b>		
		Back	0.651	0.110	0.017	<b>0.76</b>	<b>0.67</b>		
		Left side	0.138			<b>0.14</b>	<b>0.14</b>		
		Right side	0.508	0.064	0.010	<b>0.57</b>	<b>0.52</b>		
		Top side		0.113	0.014	<b>0.11</b>	<b>0.01</b>		
		Bottom side	0.203			<b>0.20</b>	<b>0.20</b>		
	Band 17	Front	0.565	0.150	0.022	<b>0.72</b>	<b>0.59</b>		
		Back	0.590	0.110	0.017	<b>0.70</b>	<b>0.61</b>		
		Left side	0.092			<b>0.09</b>	<b>0.09</b>		
		Right side	0.636	0.064	0.010	<b>0.70</b>	<b>0.65</b>		
		Top side		0.113	0.014	<b>0.11</b>	<b>0.01</b>		
		Bottom side	0.278			<b>0.28</b>	<b>0.28</b>		
	Band 5	Front	0.630	0.150	0.022	<b>0.78</b>	<b>0.65</b>		
		Back	0.888	0.110	0.017	<b>1.00</b>	<b>0.91</b>		
		Left side	0.865			<b>0.87</b>	<b>0.87</b>		
		Right side	0.569	0.064	0.010	<b>0.63</b>	<b>0.58</b>		
		Top side		0.113	0.014	<b>0.11</b>	<b>0.01</b>		
		Bottom side	0.122			<b>0.12</b>	<b>0.12</b>		
	Band 4	Front	1.080	0.150	0.022	<b>1.23</b>	<b>1.10</b>		
		Back	0.966	0.110	0.017	<b>1.08</b>	<b>0.98</b>		
		Left side	0.401			<b>0.40</b>	<b>0.40</b>		
		Right side	0.084	0.064	0.010	<b>0.15</b>	<b>0.09</b>		
		Top side		0.113	0.014	<b>0.11</b>	<b>0.01</b>		
		Bottom side	0.564			<b>0.56</b>	<b>0.56</b>		
	Band 2	Front	0.988	0.150	0.022	<b>1.14</b>	<b>1.01</b>		
		Back	0.835	0.110	0.017	<b>0.95</b>	<b>0.85</b>		
		Left side	0.369			<b>0.37</b>	<b>0.37</b>		
		Right side	0.075	0.064	0.010	<b>0.14</b>	<b>0.09</b>		
		Top side		0.113	0.014	<b>0.11</b>	<b>0.01</b>		
		Bottom side	1.370			<b>1.37</b>	<b>1.37</b>		
Band 7	Front	0.773	0.150	0.022	<b>0.92</b>	<b>0.80</b>			
	Back	0.527	0.110	0.017	<b>0.64</b>	<b>0.54</b>			
	Left side	0.134			<b>0.13</b>	<b>0.13</b>			
	Right side	1.260	0.064	0.010	<b>1.32</b>	<b>1.27</b>			
	Top side		0.113	0.014	<b>0.11</b>	<b>0.01</b>			
	Bottom side	0.604			<b>0.60</b>	<b>0.60</b>			



**15.3 Body-Worn Accessory Exposure Conditions**


WWAN Band		Exposure Position	1	2	3	1+2 Summed SAR (W/kg)	1+3 Summed SAR (W/kg)	SPLSR	Case No
			WWAN	2.4GHz WLAN	2.4GHz Bluetooth				
			SAR (W/kg)	SAR (W/kg)	SAR (W/kg)				
GSM	GSM850	Front	0.413	0.087	0.011	<b>0.50</b>	<b>0.42</b>		
		Back	0.454	0.060	0.007	<b>0.51</b>	<b>0.46</b>		
	GSM1900	Front	0.219	0.087	0.011	<b>0.31</b>	<b>0.23</b>		
		Back	0.167	0.060	0.007	<b>0.23</b>	<b>0.17</b>		
WCDMA	Band V	Front	0.365	0.087	0.011	<b>0.45</b>	<b>0.38</b>		
		Back	0.639	0.060	0.007	<b>0.70</b>	<b>0.65</b>		
	Band IV	Front	0.664	0.087	0.011	<b>0.75</b>	<b>0.68</b>		
		Back	0.491	0.060	0.007	<b>0.55</b>	<b>0.50</b>		
	Band II	Front	0.768	0.087	0.011	<b>0.86</b>	<b>0.78</b>		
		Back	0.529	0.060	0.007	<b>0.59</b>	<b>0.54</b>		
LTE	Band 12	Front	0.429	0.087	0.011	<b>0.52</b>	<b>0.44</b>		
		Back	0.452	0.060	0.007	<b>0.51</b>	<b>0.46</b>		
	Band 17	Front	0.386	0.087	0.011	<b>0.47</b>	<b>0.40</b>		
		Back	0.396	0.060	0.007	<b>0.46</b>	<b>0.40</b>		
	Band 5	Front	0.568	0.087	0.011	<b>0.66</b>	<b>0.58</b>		
		Back	0.759	0.060	0.007	<b>0.82</b>	<b>0.77</b>		
	Band 4	Front	0.587	0.087	0.011	<b>0.67</b>	<b>0.60</b>		
		Back	0.447	0.060	0.007	<b>0.51</b>	<b>0.45</b>		
	Band 2	Front	0.651	0.087	0.011	<b>0.74</b>	<b>0.66</b>		
		Back	0.551	0.060	0.007	<b>0.61</b>	<b>0.56</b>		
	Band 7	Front	0.976	0.087	0.011	<b>1.06</b>	<b>0.99</b>		
		Back	0.597	0.060	0.007	<b>0.66</b>	<b>0.60</b>		

### 15.4 SPLSR Evaluation and Analysis


**General Note:**

- SPLSR =  $(SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$ . If  $SPLSR \leq 0.04$ , simultaneously transmission SAR measurement is not necessary


Case 1	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA IV				X	Y	Z				
	2.4GHz WLAN	Left Cheek	1.079	-	0.0604	0.258	-0.174	73.2	1.97	0.04	Not required
			0.891	-	0.0267	0.323	-0.172				




Case 2	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II				X	Y	Z				
	2.4GHz WLAN	Left Cheek	0.728	-	0.0619	0.264	-0.173	68.7	1.62	0.03	Not required
			0.891	-	0.0267	0.323	-0.172				




Case 3	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 4	Left Cheek	0.832	-	0.0636	0.254	-0.174	78.3	1.72	0.03	Not required
	2.4GHz WLAN		0.891	-	0.0267	0.323	-0.172				




Case 4	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 2	Left Cheek	0.724	-	0.0601	0.258	-0.172	73.1	1.62	0.03	Not required
	2.4GHz WLAN		0.891	-	0.0267	0.323	-0.172				



Case 5	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 7	Right Cheek	1.202	-	0.067	-0.258	-0.172	66.3	1.74	0.03	Not required
	2.4GHz WLAN		0.535	-	0.0175	-0.302	-0.17				



Case 6	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Front	1.464	1	-0.033	-0.0675	-0.204	113.8	1.64	0.02	Not required
	2.4GHz WLAN		0.172	1	-0.0206	0.0456	-0.205				



**Test Engineer :** Aaron Chen, Vic Yang, Steven Chang, Poa Pan, Kurt Liu, Jerry Hu, Lawrence Chen,  
and Iran Wang

## 16. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture’s specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor <sup>(a)</sup>	1/k <sup>(b)</sup>	1/√3	1/√6	1/√2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b)  $\kappa$  is the coverage factor

**Table 16.1. Standard Uncertainty for Assumed Distribution**

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual “root-sum-squares” (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
<b>Measurement System</b>							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
<b>Test Sample Related</b>							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
<b>Phantom and Setup</b>							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
<b>Combined Standard Uncertainty</b>						± 11.0 %	± 10.8 %
<b>Coverage Factor for 95 %</b>						K=2	
<b>Expanded Uncertainty</b>						± 22.0 %	± 21.5 %

Table 16.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz



## **17. References**

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 447498 D01 v05r02, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Feb 2014
- [6] FCC KDB 648474 D03 v01r02, "Evaluation and Approval Considerations for Handsets with Specific Wireless Charging Battery Covers" May 2013.
- [7] FCC KDB 941225 D01 v03, "3G SAR MEAUREMENT PROCEDURES", Oct 2014
- [8] FCC KDB 941225 D05 v02r03, "SAR Evaluation Considerations for LTE Devices", Dec 2013
- [9] FCC KDB 941225 D06 v02, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2014.
- [10] FCC KDB 865664 D01 v01r03, "SAR Measurement Requirements for 100 MHz to 6 GHz", Feb 2014.
- [11] FCC KDB 865664 D02 v01r01, "RF Exposure Compliance Reporting and Documentation Considerations" May 2013.



---

**Appendix A. Plots of System Performance Check**

The plots are shown as follows.



---

**Appendix B. Plots of SAR Measurement**

The plots are shown as follows.



---

**Appendix C.    *DASY Calibration Certificate***

The DASY calibration certificates are shown as follows.