



FCC RF Test Report

APPLICANT : Motorola Mobility, LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : 3600
FCC ID : IHDT56QD2
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Sep. 11, 2014 and testing was completed on Sep. 26, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	7
1.8 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	11
3 TEST RESULT	12
3.1 Conducted Output Power Measurement.....	12
3.2 Peak-to-Average Ratio	14
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	30
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	36
3.5 Band Edge Measurement.....	60
3.6 Conducted Spurious Emission Measurement.....	68
3.7 Field Strength of Spurious Radiation Measurement	123
3.8 Frequency Stability Measurement.....	146
4 LIST OF MEASURING EQUIPMENT	151
5 UNCERTAINTY OF EVALUATION	152



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG491144A	Rev. 01	Initial issue of report	Oct. 10, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b) §27.53(h)(3)	Occupied Bandwidth	Reporting Only	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 16.32 dB at 2544.000 MHz
3.8	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-
	§2.1055 §24.235 §27.54		within authorized band		



1 General Description

1.1 Applicant

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.2 Manufacturer

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	3600
IMEI	359320050014850
FCC ID	IHDT56QD2
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/NFC 2.4GHz WLAN 11b/g/n HT20 WLAN 11ac VHT20 5 GHz WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth v3.0 EDR Bluetooth v4.0 - LE
HW Version	P2
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Accessory List	
AC Adapter	Brand Name : Motorola
	Model Name : SPN5864A
Earphone	Brand Name : Motorola
	Model Name : SJYN1305A
Battery	Brand Name : LG
	Model Name : SNN5953A
USB Cable	Brand Name : Motorola
	Model Name : SKN6466A

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.74 dBm GSM1900 : 29.69 dBm WCDMA Band V : 23.25 dBm WCDMA Band IV : 22.92 dBm WCDMA Band II : 23.02 dBm
99% Occupied Bandwidth	GSM850: 0.252MHz GSM1900: 0.246MHz WCDMA Band V: 4.20MHz WCDMA Band IV: 4.20MHz WCDMA Band II: 4.18MHz
Antenna Type	Fixed Internal Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.582	0.005 ppm	250KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.109	0.007 ppm	252KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.106	0.013 ppm	4M20F9W
Part 24	GSM1900 GPRS class 8	GMSK	1.365	0.004 ppm	244KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.589	0.003 ppm	246KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.260	0.006 ppm	4M18F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.235	0.002 ppm	4M20F9W

1.7 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	03CH07-HY



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01
- ♦ KDB 648474 D03 Handset Wireless Chargers Battery Covers v01r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.
3. 30 MHz to 18000 MHz for WCDMA Band IV

All modes and data rates and positions were investigated, and the wireless charger configuration was evaluated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link ■ EDGE class 8 Link	■ GPRS class 8 Link ■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link ■ EDGE class 8 Link	■ GPRS class 8 Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Note: The maximum power levels are chosen to test as the worst case configuration as follows:

GPRS multi-slot class 8 mode for GMSK modulation,

EDGE multi-slot class 8 mode for 8PSK modulation,

RMC 12.2Kbps mode for WCDMA band V,

RMC 12.2Kbps mode for WCDMA band II,

RMC 12.2Kbps mode for WCDMA band IV, only these modes were used for all tests.

only these modes were used for all tests. In addition to above worst-case test, below investigating on all data rates, and all modes are compliance with each FCC test case which has specific test limits. For spurious emissions at antenna port, the EUT was investigated the band edges on low and high channels, and the unwanted spurious emissions on middle channel for all modes, the results are pass, then only the worst-results were reported in the test report. The Radiated Spurious emissions for GSM/GPRS/EGPRS/HSDPA/CDMA modes were investigated on the middle channel and the passed results were not worse than those data tested from the highest power channels.




Conducted Power Measurement Results:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.65	32.71	32.72	29.68	29.60	29.65
GPRS class 8	32.67	32.74	32.73	29.69	29.61	29.68
GPRS class 10	29.35	29.48	29.62	26.65	26.56	26.61
GPRS class 11	27.45	27.61	27.73	24.78	24.67	24.73
GPRS class 12	26.08	26.23	26.33	23.29	23.27	23.32
EGPRS class 8	26.52	26.55	26.68	25.58	25.54	25.65
EGPRS class 10	23.55	23.65	23.77	22.78	22.75	22.88
EGPRS class 11	22.55	22.35	22.51	21.62	21.54	21.65
EGPRS class 12	20.84	20.97	21.17	20.43	20.24	20.27

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2K	23.10	23.18	23.25	22.82	23.02	22.80	22.83	22.84	22.92
HSDPA Subtest-1	22.27	22.23	22.29	21.80	22.13	21.85	21.55	21.84	21.89
HSDPA Subtest-2	22.13	22.24	22.28	21.83	22.17	21.88	21.58	21.85	21.93
HSDPA Subtest-3	21.70	21.74	21.81	21.32	21.56	21.46	21.31	21.40	21.60
HSDPA Subtest-4	21.72	21.73	21.85	21.35	21.59	21.49	21.33	21.44	21.62
HSUPA Subtest-1	21.85	21.72	21.99	21.28	21.52	21.41	21.54	21.63	21.61
HSUPA Subtest-2	20.56	20.45	20.75	20.69	20.99	20.81	20.77	20.88	20.83
HSUPA Subtest-3	20.49	20.50	20.70	20.28	20.57	20.43	20.64	20.79	20.72
HSUPA Subtest-4	21.62	21.57	21.69	21.01	21.20	21.10	20.75	20.92	20.79
HSUPA Subtest-5	22.17	22.16	22.31	21.88	22.08	21.80	21.83	21.86	21.93

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	WPC	Samsung	A3LEPP00IJWU	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.67	32.74	32.73	26.52	26.55	26.68	23.10	23.18	23.25

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.69	29.61	29.68	25.58	25.54	25.65	22.82	23.02	22.80

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	22.83	22.84	22.92

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.2.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. For GSM/EGPRS operating modes, signal gating is implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.

Record the maximum PAPR level associated with a probability of 0.1%.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Peak-to-Average Ratio (dB)	0.20	0.20	0.24	3.08	3.08	3.24	3.12	3.16	3.24


PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.32	0.28	0.32	3.20	3.16	3.20	3.04	3.20	3.16

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Peak-to-Average Ratio (dB)	3.12	3.12	3.16

3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
---------------	---------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)



Date: 24.SEP.2014 14:41:16


Peak-to-Average Ratio on Channel 189 (836.4 MHz)



Date: 24.SEP.2014 14:42:14



Peak-to-Average Ratio on Channel 251 (848.8 MHz)




Date: 24.SEP.2014 14:42:44




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)



Date: 24.SEP.2014 15:24:55


Peak-to-Average Ratio on Channel 189 (836.4 MHz)



Date: 24.SEP.2014 15:26:44



Peak-to-Average Ratio on Channel 251 (848.8 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1
Mean 26.72 dBm
Peak 29.96 dBm
Crest 3.24 dB


10 %	2.68 dB
1 %	3.16 dB
.1 %	3.24 dB
.01 %	3.28 dB

Date: 24.SEP.2014 15:27:11




Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 16:40:50


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 24.SEP.2014 16:41:24



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 24.SEP.2014 16:41:58




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 17:40:49


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 24.SEP.2014 17:41:20



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1
Mean 24.70 dBm
Peak 27.99 dBm
Crest 3.29 dB


10 % 2.60 dB
1 % 3.12 dB
.1 % 3.20 dB
.01 % 3.28 dB

Date: 24.SEP.2014 17:41:56




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 4132 (826.4 MHz)



Date: 25.SEP.2014 16:13:12


Peak-to-Average Ratio on Channel 4182 (836.4 MHz)



Date: 25.SEP.2014 16:13:38



Peak-to-Average Ratio on Channel 4233 (846.6 MHz)




Date: 25.SEP.2014 16:14:17




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 1312 (1712.4 MHz)



Date: 26.SEP.2014 10:24:28


Peak-to-Average Ratio on Channel 1413 (1732.6 MHz)



Date: 26.SEP.2014 10:25:02



Peak-to-Average Ratio on Channel 1513 (1752.6 MHz)




Date: 26.SEP.2014 10:25:30




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 25.SEP.2014 14:11:31


Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 25.SEP.2014 14:12:09



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 25.SEP.2014 14:12:49



3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band) and 1 Watts (AWS Band).


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by dipole antenna (substitution antenna) at the same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-17.26	37.45	18.04	0.064
836.4	-17.22	37.65	18.28	0.067
848.8	-16.75	37.95	19.05	0.080
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-9.59	38.84	27.10	0.513
836.4	-9.04	38.43	27.24	0.530
848.8	-9.18	38.98	27.65	0.582

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

GSM850 (EDGE class 8) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-24.50	37.45	10.80	0.012
836.4	-24.57	37.65	10.93	0.012
848.8	-24.23	37.95	11.57	0.014
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-16.89	38.84	19.80	0.095
836.4	-16.00	38.43	20.28	0.107
848.8	-16.44	38.98	20.39	0.109

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
826.4	-23.47	37.3	11.68	0.015
836.4	-24.17	37.65	11.33	0.014
846.6	-24.75	38.02	11.12	0.013
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
826.4	-16.23	38.64	20.26	0.106
836.4	-16.58	38.43	19.70	0.093
846.6	-17.00	38.79	19.64	0.092

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

3.3.6 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-18.97	44.62	25.65	0.367
1880.0	-19.45	45.32	25.87	0.386
1909.8	-19.23	44.90	25.67	0.369
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-17.16	48.50	31.34	1.361
1880.0	-18.38	49.73	31.35	1.365
1909.8	-16.92	48.09	31.17	1.309

* EIRP = LVL (dBm) + Correction Factor (dB)

GSM1900 (EDGE class 8) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-23.19	44.62	21.43	0.139
1880.0	-23.27	45.32	22.05	0.160
1909.8	-23.43	44.90	21.47	0.140
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-20.80	48.50	27.70	0.589
1880.0	-22.46	49.73	27.27	0.533
1909.8	-21.21	48.09	26.88	0.488

* EIRP = LVL (dBm) + Correction Factor (dB)

WCDMA Band IV (RMC 12.2Kbps) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1712.4	-27.07	42.79	15.72	0.037
1732.6	-26.28	43.00	16.72	0.047
1752.6	-25.57	42.92	17.35	0.054
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1712.4	-24.09	46.10	22.01	0.159
1732.6	-22.74	45.94	23.20	0.209
1752.6	-23.72	47.43	23.71	0.235

* EIRP = LVL (dBm) + Correction Factor (dB)

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1852.4	-26.19	44.64	18.45	0.070
1880.0	-26.51	45.32	18.81	0.076
1907.6	-26.74	44.96	18.22	0.066
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1852.4	-24.53	48.50	23.97	0.249
1880.0	-25.58	49.73	24.15	0.260
1907.6	-24.46	48.13	23.67	0.233

* EIRP = LVL (dBm) + Correction Factor (dB)

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	246.00	246.00	250.00	246.00	252.00	252.00
26dB BW (kHz)	314.00	314.00	314.00	314.00	310.00	308.00

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	244.00	242.00	242.00	246.00	242.00	242.00
26dB BW (kHz)	318.00	310.00	314.00	314.00	304.00	302.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.20	4.18	4.20
26dB BW (MHz)	4.68	4.68	4.68

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
99% OBW (MHz)	4.20	4.18	4.18
26dB BW (MHz)	4.68	4.68	4.68




PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.18	4.18	4.18
26dB BW (MHz)	4.68	4.68	4.68



3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 24.SEP.2014 15:04:37


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 24.SEP.2014 14:57:18




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 24.SEP.2014 15:05:12


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 24.SEP.2014 14:57:56




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 24.SEP.2014 15:05:46

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 24.SEP.2014 14:58:31




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 24.SEP.2014 16:00:43


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 24.SEP.2014 15:48:47




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 24.SEP.2014 15:52:10


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 24.SEP.2014 15:49:35




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 24.SEP.2014 15:53:06

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 24.SEP.2014 15:50:12




Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 16:55:54


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 16:51:18




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 24.SEP.2014 16:56:29


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 24.SEP.2014 16:51:58




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 24.SEP.2014 16:57:05

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 24.SEP.2014 16:52:44




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 18:10:03


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 17:50:22




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 24.SEP.2014 18:10:36


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 24.SEP.2014 17:50:58




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 24.SEP.2014 18:11:31

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 24.SEP.2014 17:51:33




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 25.SEP.2014 16:48:55


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 25.SEP.2014 16:25:08




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 25.SEP.2014 16:49:24


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 25.SEP.2014 16:25:37




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 25.SEP.2014 16:49:53

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 25.SEP.2014 16:26:05




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 26.SEP.2014 11:10:42


26dB Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 26.SEP.2014 10:55:03




99% Occupied Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 26.SEP.2014 11:11:10


26dB Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 26.SEP.2014 10:55:31




99% Occupied Bandwidth Plot on Channel 1513 (1752.6 MHz)



Date: 26.SEP.2014 11:11:39

26dB Bandwidth Plot on Channel 1513 (1752.6 MHz)




Date: 26.SEP.2014 10:59:25




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 25.SEP.2014 15:56:41


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 25.SEP.2014 15:30:24




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 25.SEP.2014 15:57:10


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 25.SEP.2014 15:33:29




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 25.SEP.2014 15:57:38

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 25.SEP.2014 15:31:22

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 24.SEP.2014 14:50:21

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 24.SEP.2014 14:47:30




Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 24.SEP.2014 15:37:41

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 24.SEP.2014 15:33:40




Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 16:48:45

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 24.SEP.2014 16:45:59




Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 24.SEP.2014 17:48:30

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 24.SEP.2014 17:46:10




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Lower Band Edge Plot on Channel 4132 (826.4 MHz)



Date: 25.SEP.2014 16:23:08

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 25.SEP.2014 16:18:11




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 1312 (1712.4 MHz)



Date: 26.SEP.2014 10:51:50

Higher Band Edge Plot on Channel 1513 (1752.6 MHz)




Date: 26.SEP.2014 10:29:06




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Date: 25.SEP.2014 14:38:24

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 25.SEP.2014 14:15:46

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.6.4 Test Setup




3.6.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GSM850	Channel :	CH128
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 15:06:52

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 24.SEP.2014 15:07:03

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 15:07:11

Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 24.SEP.2014 15:07:20


Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 15:09:22


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 15:08:28




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 15:08:36

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 24.SEP.2014 15:08:44




Band :	GSM850	Channel :	CH251
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 15:13:27


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 15:13:38




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 15:13:46

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 24.SEP.2014 15:13:54




Band :	GSM850	Channel :	CH128
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 16:11:28


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 16:11:39




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 16:11:47


Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 24.SEP.2014 16:11:56


Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 16:14:03


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 16:14:15




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 16:14:23


Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 24.SEP.2014 16:14:32


Band :	GSM850	Channel :	CH251
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 24.SEP.2014 16:16:03


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 16:16:14

Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 24.SEP.2014 16:16:22


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 24.SEP.2014 16:16:30




Band :	GSM1900	Channel :	CH512
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1850.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 17:05:53


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 17:06:01




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 17:06:12


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2014 17:06:20



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 24.SEP.2014 17:06:29




Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 17:28:34


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 17:28:42




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 17:28:53


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2014 17:29:02




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 24.SEP.2014 17:29:10


Band :	GSM1900	Channel :	CH810
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1909.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 17:29:57


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 17:30:05




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 17:30:17


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2014 17:30:26



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 24.SEP.2014 17:30:34




Band :	GSM1900	Channel :	CH512
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1850.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 24.SEP.2014 18:13:43


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 18:13:51

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 18:14:01

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 24.SEP.2014 18:14:10




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 24.SEP.2014 18:14:18


Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2014 18:16:09


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2014 18:16:18




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 18:16:28


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2014 18:16:36



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 24.SEP.2014 18:16:45




Band :	GSM1900	Channel :	CH810
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1909.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 24.SEP.2014 18:17:26

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 24.SEP.2014 18:17:35

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2014 18:17:45


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2014 18:17:54



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 24.SEP.2014 18:18:02




Band :	WCDMA Band V	Channel :	CH4132
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	826.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 26.SEP.2014 11:33:34


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 26.SEP.2014 11:33:44




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 26.SEP.2014 11:33:52

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 26.SEP.2014 11:34:01




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 26.SEP.2014 11:33:03


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 26.SEP.2014 11:32:42




Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 26.SEP.2014 11:32:51

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 26.SEP.2014 11:32:59


Band :	WCDMA Band V	Channel :	CH4233
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	846.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 26.SEP.2014 11:34:42

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 26.SEP.2014 11:34:52

Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 26.SEP.2014 11:35:00


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 26.SEP.2014 11:35:09




Band :	WCDMA Band IV	Channel :	CH1312
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1712.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 26.SEP.2014 11:14:04


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 26.SEP.2014 11:14:13




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 26.SEP.2014 11:14:23


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 26.SEP.2014 11:14:31




Conducted Spurious Emission Plot between 13.6GHz ~ 18GHz




Date: 26.SEP.2014 11:14:40



Band :	WCDMA Band IV	Channel :	CH1413
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1732.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 26.SEP.2014 11:12:47

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 26.SEP.2014 11:12:55




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 26.SEP.2014 11:13:05


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 26.SEP.2014 11:13:14



Conducted Spurious Emission Plot between 13.6GHz ~ 18GHz




Date: 26.SEP.2014 11:13:22




Band :	WCDMA Band IV	Channel :	CH1513
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1752.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 26.SEP.2014 11:15:42


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 26.SEP.2014 11:15:51




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 26.SEP.2014 11:16:01


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 26.SEP.2014 11:16:10



Conducted Spurious Emission Plot between 13.6GHz ~ 18GHz




Date: 26.SEP.2014 11:16:18




Band :	WCDMA Band II	Channel :	CH9262
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1852.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 25.SEP.2014 16:00:06


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 25.SEP.2014 16:00:14

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 25.SEP.2014 16:00:55

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 25.SEP.2014 16:01:03



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 25.SEP.2014 16:01:12




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 25.SEP.2014 15:58:31


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 25.SEP.2014 15:58:39




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 25.SEP.2014 15:58:52


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 25.SEP.2014 15:59:00



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 25.SEP.2014 15:59:09




Band :	WCDMA Band II	Channel :	CH9538
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1907.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 25.SEP.2014 16:04:01


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 25.SEP.2014 16:04:10

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 25.SEP.2014 16:04:21

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 25.SEP.2014 16:04:29



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 25.SEP.2014 16:04:38



3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

Note: Wireless charger configuration was evaluated.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r01 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated

<Low Channel>

Band :	GSM850	Temperature :	23~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648	-43.14	-13	-30.14	-52.39	-44.9	0.98	4.89	H	Pass
2472	-35.32	-13	-22.32	-48.87	-37.2	1.28	5.32	H	Pass
3297	-51.38	-13	-38.38	-65.08	-54.8	1.54	7.11	H	Pass

Band :	GSM850	Temperature :	23~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648	-43.34	-13	-30.34	-54.42	-45.1	0.98	4.89	V	Pass
2472	-37.42	-13	-24.42	-51.46	-39.3	1.28	5.32	V	Pass
3297	-49.68	-13	-36.68	-65.25	-53.1	1.54	7.11	V	Pass



<Middle Channel>

Band :	GSM850	Temperature :	23~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-44.22	-13	-31.22	-53.45	-45.9	0.99	4.82	H	Pass
2512	-34.13	-13	-21.13	-47.88	-36.1	1.29	5.41	H	Pass
3345	-51.09	-13	-38.09	-65.14	-54.7	1.56	7.32	H	Pass

Band :	GSM850	Temperature :	23~24℃						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-46.92	-13	-33.92	-58.27	-48.6	0.99	4.82	V	Pass
2512	-38.73	-13	-25.73	-52.54	-40.7	1.29	5.41	V	Pass
3345	-49.09	-13	-36.09	-64.84	-52.7	1.56	7.32	V	Pass



<High Channel>

Band :	GSM850					Temperature :	23~24°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1696	-35.70	-13	-22.70	-45.03	-37.3	1.00	4.75	H	Pass
2544	-29.32	-13	-16.32	-42.94	-31.3	1.30	5.44	H	Pass
3393	-51.29	-13	-38.29	-65.52	-55.1	1.57	7.53	H	Pass

Band :	GSM850	Temperature :	23~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)	(dB)	(dB)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1696	-41.10	-13	-28.10	-52.78	-42.7	1.00	4.75	V	Pass
2544	-33.42	-13	-20.42	-47.71	-35.4	1.30	5.44	V	Pass
3393	-49.79	-13	-36.79	-65.33	-53.6	1.57	7.53	V	Pass

**<Low Channel>**

Band :	GSM850				Temperature :	23~24°C			
Test Mode :	EDGE class 8 Link (8PSK)				Relative Humidity :	46~48%			
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu				Polarization :	Horizontal			
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1648	-53.54	-13	-40.54	-62.46	-55.3	0.98	4.89	H	Pass
2472	-47.52	-13	-34.52	-61.03	-49.4	1.28	5.32	H	Pass
3297	-50.98	-13	-37.98	-64.95	-54.4	1.54	7.11	H	Pass

Band :	GSM850	Temperature :	23~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1648	-52.14	-13	-39.14	-63.67	-53.9	0.98	4.89	V	Pass
2472	-48.52	-13	-35.52	-62.57	-50.4	1.28	5.32	V	Pass
3297	-49.48	-13	-36.48	-65.58	-52.9	1.54	7.11	V	Pass

**<Middle Channel>**

Band :	GSM850					Temperature :	23~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-54.62	-13	-41.62	-63.69	-56.3	0.99	4.82	H	Pass
2512	-42.13	-13	-29.13	-56.23	-44.1	1.29	5.41	H	Pass
3345	-51.99	-13	-38.99	-65.98	-55.6	1.56	7.32	H	Pass

Band :	GSM850	Temperature :	23~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-53.52	-13	-40.52	-64.63	-55.2	0.99	4.82	V	Pass
2509	-48.94	-13	-35.94	-63.19	-50.9	1.29	5.41	V	Pass
3345	-49.59	-13	-36.59	-64.76	-53.2	1.56	7.32	V	Pass



<High Channel>

Band :	GSM850	Temperature :	23~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1696	-51.70	-13	-38.70	-60.94	-53.3	1.00	4.75	H	Pass
2544	-41.52	-13	-28.52	-55.09	-43.5	1.30	5.44	H	Pass
3393	-50.79	-13	-37.79	-65.19	-54.6	1.57	7.53	H	Pass

Band :	GSM850					Temperature :	23~24℃		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1696	-51.70	-13	-38.70	-63.16	-53.3	1.00	4.75	V	Pass
2544	-46.47	-13	-33.47	-60.56	-50.6	1.30	5.44	V	Pass
3393	-48.84	-13	-35.84	-64.89	-54.8	1.57	7.53	V	Pass



<Low Channel>

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	loss	Gain	(H/V)	
3700	-50.93	-13	-37.93	-66.03	-57.5	1.67	8.24	H	Pass
5551	-46.03	-13	-33.03	-66.4	-53.1	2.65	9.72	H	Pass
7401	-40.56	-13	-27.56	-67.69	-49.7	2.46	11.60	H	Pass

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	loss	Gain	(H/V)	
3700	-49.73	-13	-36.73	-66.31	-56.3	1.67	8.24	V	Pass
5551	-47.13	-13	-34.13	-67.52	-54.2	2.65	9.72	V	Pass
7401	-40.96	-13	-27.96	-67.72	-50.1	2.46	11.60	V	Pass



<Middle Channel>

Band :	GSM1900				Temperature :	23~24°C			
Test Mode :	GPRS class 8 Link (GMSK)				Relative Humidity :	46~48%			
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu				Polarization :	Horizontal			
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3763	-51.37	-13	-38.37	-66.72	-58	1.69	8.32	H	Pass
5640	-46.75	-13	-33.75	-66.96	-53.8	2.71	9.76	H	Pass
7520	-40.81	-13	-27.81	-67.94	-50.2	2.42	11.81	H	Pass

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	loss	Gain	(H/V)	
3763	-49.27	-13	-36.27	-66.2	-55.9	1.69	8.32	V	Pass
5640	-45.45	-13	-32.45	-65.95	-52.5	2.71	9.76	V	Pass
7520	-41.11	-13	-28.11	-67.83	-50.5	2.42	11.81	V	Pass

**<High Channel>**

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3819	-51.42	-13	-38.42	-67.1	-58.1	1.70	8.38	H	Pass
5729	-46.47	-13	-33.47	-67.57	-53.5	2.76	9.79	H	Pass
7639	-40.60	-13	-27.60	-67.03	-50.1	2.38	11.88	H	Pass

Band :	GSM1900					Temperature :	23~24℃		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3820	-47.92	-13	-34.92	-64.41	-54.6	1.70	8.38	V	Pass
5730	-41.07	-13	-28.07	-62.02	-48.1	2.76	9.79	V	Pass
7639	-40.10	-13	-27.10	-66.41	-49.6	2.38	11.88	V	Pass

**<Low Channel>**

Band :	GSM1900					Temperature :	23~24°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	loss	Gain	(H/V)	
3700	-50.53	-13	-37.53	-65.43	-57.1	1.67	8.24	H	Pass
5551	-46.13	-13	-33.13	-66.35	-53.2	2.65	9.72	H	Pass
7401	-40.46	-13	-27.46	-67.3	-49.6	2.46	11.60	H	Pass

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3700	-48.93	-13	-35.93	-65.57	-55.5	1.67	8.24	V	Pass
5551	-47.13	-13	-34.13	-67.58	-54.2	2.65	9.72	V	Pass
7401	-40.56	-13	-27.56	-67.34	-49.7	2.46	11.60	V	Pass

**<Middle Channel>**

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3763	-51.07	-13	-38.07	-66.41	-57.7	1.69	8.32	H	Pass
5640	-46.45	-13	-33.45	-67.1	-53.5	2.71	9.76	H	Pass
7520	-40.21	-13	-27.21	-67.14	-49.6	2.42	11.81	H	Pass

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3763	-50.17	-13	-37.17	-66.57	-56.8	1.69	8.32	V	Pass
5640	-46.15	-13	-33.15	-66.72	-53.2	2.71	9.76	V	Pass
7520	-40.81	-13	-27.81	-67.24	-50.2	2.42	11.81	V	Pass

**<High Channel>**

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3819	-51.22	-13	-38.22	-66.77	-57.9	1.70	8.38	H	Pass
5729	-46.27	-13	-33.27	-67.37	-53.3	2.76	9.79	H	Pass
7639	-40.10	-13	-27.10	-66.3	-49.6	2.38	11.88	H	Pass

Band :	GSM1900	Temperature :	23~24°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3819	-50.42	-13	-37.42	-66.64	-57.1	1.70	8.38	V	Pass
5730	-46.17	-13	-33.17	-66.88	-53.2	2.76	9.79	V	Pass
7639	-40.50	-13	-27.50	-66.42	-50	2.38	11.88	V	Pass

**<Low Channel>**

Band :	WCDMA Band V				Temperature :	23~24°C			
Test Mode :	RMC 12.2Kbps Link (QPSK)				Relative Humidity :	46~48%			
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu				Polarization :	Horizontal			
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1656	-55.17	-13	-42.17	-64.43	-56.9	0.98	4.86	H	Pass
2479	-49.70	-13	-36.70	-63.04	-51.6	1.28	5.34	H	Pass
3306	-51.75	-13	-38.75	-65.83	-55.2	1.54	7.15	H	Pass

Band :	WCDMA Band V	Temperature :	23~24℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1656	-53.37	-13	-40.37	-63.97	-55.1	0.98	4.86	V	Pass
2479	-50.30	-13	-37.30	-64.04	-52.2	1.28	5.34	V	Pass
3306	-49.55	-13	-36.55	-64.89	-53	1.54	7.15	V	Pass



<Middle Channel>

Band :	WCDMA Band V	Temperature :	23~24℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-55.22	-13	-42.22	-64.09	-56.9	0.99	4.82	H	Pass
2509	-50.04	-13	-37.04	-63.41	-52	1.29	5.41	H	Pass
3345	-52.49	-13	-39.49	-66.1	-56.1	1.56	7.32	H	Pass

Band :	WCDMA Band V				Temperature :	23~24°C			
Test Mode :	RMC 12.2Kbps Link (QPSK)				Relative Humidity :	46~48%			
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu				Polarization :	Vertical			
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-52.62	-13	-39.62	-64.02	-54.3	0.99	4.82	V	Pass
2509	-50.34	-13	-37.34	-64.16	-52.3	1.29	5.41	V	Pass
3345	-50.49	-13	-37.49	-65.76	-54.1	1.56	7.32	V	Pass

**<High Channel>**

Band :	WCDMA Band V					Temperature :	23~24°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1688	-48.47	-13	-35.47	-57.5	-50.1	1.00	4.77	H	Pass
2544	-45.52	-13	-32.52	-59.15	-47.5	1.30	5.44	H	Pass
3386	-51.32	-13	-38.32	-65.56	-55.1	1.57	7.50	H	Pass

Band :	WCDMA Band V					Temperature :	23~24°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading	Power	loss	Gain	(H/V)	
(dBm)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1696	-52.50	-13	-39.50	-63.36	-54.1	1.00	4.75	V	Pass
2540	-50.72	-13	-37.72	-64.5	-52.7	1.30	5.43	V	Pass
3386	-49.32	-13	-36.32	-65.17	-53.1	1.57	7.50	V	Pass



<Low Channel>

Band :	WCDMA Band IV					Temperature :	23~24℃		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3427	-51.20	-13	-38.20	-65.49	-57.3	1.58	7.68	H	Pass
5137	-48.52	-13	-35.52	-66.71	-55.8	2.42	9.70	H	Pass
6850	-40.72	-13	-27.72	-66.4	-48.7	2.64	10.62	H	Pass

Band :	WCDMA Band IV	Temperature :	23~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3725	-50.00	-13	-37.00	-65.75	-56.6	1.67	8.27	V	Pass
5137	-48.82	-13	-35.82	-67.19	-56.1	2.42	9.70	V	Pass
6850	-42.22	-13	-29.22	-66.95	-50.2	2.64	10.62	V	Pass

**<Middle Channel>**

Band :	WCDMA Band IV				Temperature :	23~24°C			
Test Mode :	RMC 12.2Kbps Link (QPSK)				Relative Humidity :	46~48%			
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu				Polarization :	Horizontal			
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3465	-52.25	-13	-39.25	-66.38	-58.5	1.59	7.85	H	Pass
5198	-48.05	-13	-35.05	-66.62	-55.3	2.45	9.70	H	Pass
6930	-40.90	-13	-27.90	-66.74	-49	2.61	10.72	H	Pass

Band :	WCDMA Band IV	Temperature :	23~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3462	-52.86	-13	-39.86	-68.48	-59.1	1.59	7.83	V	Pass
5198	-50.35	-13	-37.35	-69.27	-57.6	2.45	9.70	V	Pass
6930	-45.50	-13	-32.50	-70.47	-53.6	2.61	10.72	V	Pass

**<High Channel>**

Band :	WCDMA Band IV	Temperature :	23~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3504	-50.80	-13	-37.80	-65.31	-57.2	1.61	8.00	H	Pass
5258	-47.69	-13	-34.69	-66.63	-54.9	2.49	9.70	H	Pass
7010	-41.57	-13	-28.57	-67.76	-49.8	2.59	10.82	H	Pass

Band :	WCDMA Band IV	Temperature :	23~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3505	-50.80	-13	-37.80	-65.74	-57.2	1.61	8.01	V	Pass
5258	-48.89	-13	-35.89	-67.57	-56.1	2.49	9.70	V	Pass
7010	-41.97	-13	-28.97	-67.18	-50.2	2.59	10.82	V	Pass

**<Low Channel>**

Band :	WCDMA Band II					Temperature :	23~24°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3707	-50.92	-13	-37.92	-66.07	-57.5	1.67	8.25	H	Pass
5557	-46.44	-13	-33.44	-66.77	-53.5	2.66	9.72	H	Pass
7410	-38.94	-13	-25.94	-65.98	-48.1	2.46	11.62	H	Pass

Band :	WCDMA Band II	Temperature :	23~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3707	-50.52	-13	-37.52	-66.43	-57.1	1.67	8.25	V	Pass
5557	-45.04	-13	-32.04	-65.05	-52.1	2.66	9.72	V	Pass
7410	-40.44	-13	-27.44	-67.4	-49.6	2.46	11.62	V	Pass

**<Middle Channel>**

Band :	WCDMA Band II					Temperature :	23~24°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	46~48%		
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3763	-50.57	-13	-37.57	-66.11	-57.2	1.69	8.32	H	Pass
5640	-46.05	-13	-33.05	-66.79	-53.1	2.71	9.76	H	Pass
7520	-40.81	-13	-27.81	-68	-50.2	2.42	11.81	H	Pass

Band :	WCDMA Band II				Temperature :	23~24°C			
Test Mode :	RMC 12.2Kbps Link (QPSK)				Relative Humidity :	46~48%			
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu				Polarization :	Vertical			
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading	Power	loss	Gain	(H/V)	
3763	-49.57	-13	-36.57	-66.03	-56.2	1.69	8.32	V	Pass
5640	-43.15	-13	-30.15	-63.75	-50.2	2.71	9.76	V	Pass
7520	-41.31	-13	-28.31	-68.07	-50.7	2.42	11.81	V	Pass

**<High Channel>**

Band :	WCDMA Band II	Temperature :	23~24℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3815	-50.43	-13	-37.43	-65.87	-57.1	1.70	8.38	H	Pass
5716	-41.36	-13	-28.36	-62.59	-48.4	2.75	9.79	H	Pass
7630	-40.71	-13	-27.71	-66.85	-50.2	2.39	11.88	H	Pass

Band :	WCDMA Band II	Temperature :	23~24°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	46~48%						
Test Engineer :	Derreck Chen, Nick Yu and Ken Wu	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3815	-50.43	-13	-37.43	-66.84	-57.1	1.70	8.38	V	Pass
5726	-46.46	-13	-33.46	-67.09	-53.5	2.76	9.79	V	Pass
7630	-41.41	-13	-28.41	-67.75	-50.9	2.39	11.88	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r01 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r01 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0036	0.0060	PASS
40	0.0012	0.0012	
30	0.0024	0.0036	
20(Ref.)	0.0000	0.0000	
10	0.0024	0.0024	
0	0.0012	0.0012	
-10	0.0012	0.0036	
-20	0.0024	0.0048	
-30	0.0048	0.0072	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0032	0.0027	PASS
40	0.0027	0.0011	
30	0.0011	0.0005	
20(Ref.)	0.0000	0.0000	
10	0.0021	0.0032	
0	0.0011	0.0021	
-10	0.0016	0.0011	
-20	0.0027	0.0016	
-30	0.0043	0.0005	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0048	PASS
40	0.0024	
30	0.0012	
20(Ref.)	0.0000	
10	0.0132	
0	0.0120	
-10	0.0024	
-20	0.0000	
-30	0.0036	

Band :	WCDMA Band IV	Channel :	1413
Limit (ppm) :	within authorized band	Frequency :	1732.6 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0017	PASS
40	0.0023	
30	0.0006	
20(Ref.)	0.0000	
10	0.0012	
0	0.0012	
-10	0.0006	
-20	0.0017	
-30	0.0006	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0037	PASS
40	0.0021	
30	0.0011	
20(Ref.)	0.0000	
10	0.0005	
0	0.0016	
-10	0.0021	
-20	0.0064	
-30	0.0016	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	4.35	0.0024	2.5	PASS
		3.80	0.0000		
		BEP	0.0012		
	EDGE class 8	4.35	0.0012		
		3.80	0.0024		
		BEP	0.0048		
GSM 1900 CH661	GPRS class 8	4.35	0.0037	(Note 3.)	
		3.80	0.0011		
		BEP	0.0032		
	EDGE class 8	4.35	0.0011		
		3.80	0.0000		
		BEP	0.0005		
WCDMA Band V CH4182	RMC 12.2Kbps	4.35	0.0132	2.5	
		3.80	0.0000		
		BEP	0.0012		
WCDMA Band IV CH1413	RMC 12.2Kbps	4.35	0.0000	(Note 3.)	
		3.80	0.0012		
		BEP	0.0006		
WCDMA Band II CH9400	RMC 12.2Kbps	4.35	0.0021	(Note 3.)	
		3.80	0.0011		
		BEP	0.0016		

Note:

1. Normal Voltage = 3.80V.
2. Battery End Point (BEP) = 3.40 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator	Rohde & Schwarz	CMU200	117995	N/A	Jul. 29, 2014	Sep. 24, 2014~ Sep. 26, 2014	Jul. 28, 2015	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Sep. 24, 2014~ Sep. 26, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D3SP	TBN-930701	N/A	Jul. 17, 2014	Sep. 24, 2014~ Sep. 26, 2014	Jul. 16, 2015	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	101749	10Hz ~ 30GHz	Feb. 10, 2014	Sep. 19, 2014	Feb. 09, 2015	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Oct. 10, 2013	Sep. 19, 2014	Oct. 09, 2014	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1GHz~18GHz	Aug. 19, 2014	Sep. 19, 2014	Aug. 18, 2015	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10 MHz ~ 1000MHz	Mar. 17, 2014	Sep. 19, 2014	Mar. 16, 2015	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1 GHz~26.5 GHz	Nov. 29, 2013	Sep. 19, 2014	Nov. 28, 2014	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Sep. 19, 2014	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	M-400-0	114/8000604/L	N/A	N/A	Sep. 19, 2014	N/A	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 03, 2013	Sep. 19, 2014	Oct. 02, 2014	Radiation (03CH07-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 23, 2014	Sep. 19, 2014	May 22, 2015	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00066583	1GHz~18GHz	Jul. 24, 2014	Sep. 19, 2014	Jul. 23, 2015	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.50
---	------