



# FCC Test Report

**APPLICANT** : Motorola Mobility, LLC  
**EQUIPMENT** : Mobile Cellular Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : 7383  
**FCC ID** : IHDT56VD4  
**STANDARD** : FCC 47 CFR FCC Part 15 Subpart B  
**CLASSIFICATION** : Certification

The product was received on May 10, 2016 and testing was completed on May 21, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Louis Wu / Manager

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL INC.**  
No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1. Applicant.....	5
1.2. Manufacturer .....	5
1.3. Product Feature of Equipment Under Test .....	5
1.4. Product Specification of Equipment Under Test .....	6
1.5. Modification of EUT .....	7
1.6. Test Location .....	8
1.7. Applicable Standards .....	8
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>9</b>
2.1. Test Mode .....	9
2.2. Connection Diagram of Test System .....	10
2.3. Support Unit used in test configuration and system.....	11
2.4. EUT Operation Test Setup .....	11
<b>3. TEST RESULT.....</b>	<b>12</b>
3.1. Test of AC Conducted Emission Measurement .....	12
3.2. Test of Radiated Emission Measurement .....	16
<b>4. LIST OF MEASURING EQUIPMENT.....</b>	<b>20</b>
<b>5. UNCERTAINTY OF EVALUATION.....</b>	<b>21</b>



## REVISION HISTORY



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 8.40 dB at 0.190 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 8.74 dB at 174.180 MHz



## 1. General Description

### 1.1. Applicant

**Motorola Mobility, LLC**

222 W. Merchandise Mart Plaza, Chicago IL 60654 USA

### 1.2. Manufacturer

**Motorola Mobility, LLC**

222 W. Merchandise Mart Plaza, Chicago IL 60654 USA

### 1.3. Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Mobile Cellular Phone
<b>Brand Name</b>	Motorola
<b>Model Name</b>	7383
<b>FCC ID</b>	IHDT56VD4
<b>IMEI Code</b>	354140070005315
<b>EUT supports Radios application</b>	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/FM WLAN 11b/g/n HT20 Bluetooth v3.0 EDR Bluetooth v4.1 LE
<b>HW Version</b>	DVT2-A
<b>SW Version</b>	fastboot_harpia_oem_userdebug_6.0.1_MPI24.223_2173_intcfg-test-keys_oem.tar.gz
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Accessory List	
<b>Earphone</b>	Brand Name : Motorola Model Name : SJYN1181B
<b>USB Cable</b>	Brand Name : Motorola Model Name : SKN6462A
<b>Battery 1</b>	Brand Name : Motorola Model Name : SNN5976A
<b>Battery 2</b>	Brand Name : Motorola Model Name : SNN5977A



## 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz LTE Band 25 : 1850.7 MHz ~ 1914.3 MHz LTE Band 26 : 814.7 MHz ~ 848.3 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 13 : 748.5 MHz ~ 753.5 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz LTE Band 25 : 1930.7 MHz ~ 1994.3 MHz LTE Band 26 : 859.7 MHz ~ 893.3 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz Glonass : 1602 MHz + n× 0.5625MHz (n=-7,-6,-5,...0,...,6) FM : 88 MHz ~ 108 MHz



Standards-related Product Specification	
<b>Antenna Type</b>	WWAN: PIFA Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS/Glonass: Fixed Internal Antenna FM: External headset Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA: QPSK (Uplink) HSDPA: 64QAM (Downlink) HSUPA: QPSK (Uplink) LTE: QPSK / 16QAM / 64QAM (Downlink Only) CDMA2000 : QPSK CDMA2000 1xEV-DO : 8PSK 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS/ Glonass : BPSK FM : FM

## 1.5. Modification of EUT

No modifications are made to the EUT during all test items.



## 1.6. Test Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	CO05-HY	03CH06-HY

## 1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2014

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. For FCC 15 Subpart B - Unintentional Radiators, device supporting USB interface or similar peripherals (defined as the Section 15.3 (r) Peripheral device) acting as a peripheral for personal computers shall be authorized as "The Class B personal computers and peripherals" per the Section 15.101 (a) Equipment authorization of unintentional radiators.
3. For other Unintentional Radiators features of this EUT, test reports are be issued separately.

Per the Note of the Section 15.101, when device supports features (USB, FM Radio, digital devices...etc) more than one category of authorization, type of authorization shall be appropriately chosen for FCC 15B compliance rule, and the Section 15.101 (b), only those receivers that operate (tune) within the frequency range of 30-960 MHz, CB receivers and radar detectors are subject to the authorizations shown in paragraph (a) of the Section 15.101. However, receivers indicated as being subject to Declaration of Conformity that are contained within a transceiver, the transmitter portion of which is subject to certification, shall be authorized under the verification procedure.



## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Data application transferred mode (EUT with notebook)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

#### Abbreviations:


- EMI AC: AC conducted emissions
- EMI RE  $\geq$  1G: EUT radiated emissions  $\geq$  1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1	Mode 1: GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 1 + USB Cable (Data Link with Notebook) Mode 2: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook)
Radiated Emissions < 1GHz	1	Mode 1: GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 1 + USB Cable (Data Link with Notebook) Mode 2: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook)
Radiated Emissions $\geq$ 1GHz	1	Mode 1: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook)

#### Remark:

1. The worst case of AC is mode 2; only the test data of this mode was reported.
2. The worst case of RE < 1G is mode 2; only the test data of this mode was reported.
3. Data Link with Notebook means data application transferred mode between EUT and Notebook.

## 2.2. Connection Diagram of Test System



Conduction and Radiation Test Setup								
No.	Wireless Station	Connection Type	Test Mode					
			1	2	-	-	-	-
A1	BT Earphone	Bluetooth	X	X				
A2	System Simulator	GSM/UMTS/CDMA/ WCDMA/LTE	X	X				
A3	AP router	WiFi	X	X				
No.	Setup Peripherals	Connection Type	1	2	-	-	-	-
C1	Notebook	USB cable	X	X				
C1-1	iPod	USB Cable to C1	X	X				
C1-2	WLAN AP	RJ-45 Cable to C1	X	X				
C2	Earphone	Earphone jack	X	X				
C3	SD card	SD I/O interface without cable	X	X				



## 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
5.	iPod	Apple	A1199	FCC DoC	Shielded, 1.0 m	N/A
6.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
7.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
8.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

## 2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

The EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Laptop and EUT via USB cable.



### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test Setup



### 3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	22~23°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	51~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook)		




#### Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	43.6	Off	L1	19.6	22.4	66.0
0.190000	55.6	Off	L1	19.6	8.4	64.0
0.246000	45.1	Off	L1	19.6	16.8	61.9
0.326000	40.4	Off	L1	19.6	19.2	59.6
0.462000	32.8	Off	L1	19.6	23.9	56.7
4.654000	27.9	Off	L1	19.7	28.1	56.0
5.294000	23.8	Off	L1	19.7	36.2	60.0
16.742000	26.8	Off	L1	19.8	33.2	60.0

#### Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	24.8	Off	L1	19.6	31.2	56.0
0.190000	39.0	Off	L1	19.6	15.0	54.0
0.246000	26.5	Off	L1	19.6	25.4	51.9
0.326000	25.5	Off	L1	19.6	24.1	49.6
0.462000	22.7	Off	L1	19.6	24.0	46.7
4.654000	18.0	Off	L1	19.7	28.0	46.0
5.294000	16.1	Off	L1	19.7	33.9	50.0
16.742000	18.1	Off	L1	19.8	31.9	50.0

<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	22~23°C
<b>Test Engineer :</b>	Arthur Hsieh	<b>Relative Humidity :</b>	51~52%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook)		

**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	42.5	Off	N	19.6	23.5	66.0
0.182000	51.2	Off	N	19.6	13.2	64.4
0.254000	43.7	Off	N	19.6	17.9	61.6
0.326000	37.7	Off	N	19.6	21.9	59.6
0.438000	31.7	Off	N	19.6	25.4	57.1
3.422000	28.8	Off	N	19.6	27.2	56.0
5.110000	23.9	Off	N	19.6	36.1	60.0
16.622000	28.5	Off	N	19.9	31.5	60.0
18.366000	27.0	Off	N	19.9	33.0	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	24.6	Off	N	19.6	31.4	56.0
0.182000	29.8	Off	N	19.6	24.6	54.4
0.254000	28.7	Off	N	19.6	22.9	51.6
0.326000	24.8	Off	N	19.6	24.8	49.6
0.438000	25.4	Off	N	19.6	21.7	47.1
3.422000	20.0	Off	N	19.6	26.0	46.0
5.110000	15.8	Off	N	19.6	34.2	50.0
16.622000	20.7	Off	N	19.9	29.3	50.0
18.366000	18.8	Off	N	19.9	31.2	50.0



## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





## 3.2.5. Test Result of Radiated Emission

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	20~23°C							
<b>Test Engineer :</b>	Daniel Lee	<b>Relative Humidity :</b>	50~53%							
<b>Test Distance :</b>	3m	<b>Polarization :</b>	Horizontal							
<b>Function Type :</b>	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook)									
<b>Remark :</b>	#6 is system simulator signal which can be ignored.									
 <p>Level (dBuV/m)      Date: 2016-05-21</p> <p>Frequency (MHz)</p>										
<b>Site</b>	: 03CH06-HY									
<b>Condition</b>	: FCC CLASS-B 3m 9120D_1156_150827 HORIZONTAL									
<b>Power</b>	: From System									
<b>Memo</b>	: Mode 2									
	Freq	Over Level	Limit	Read	Antenna Line Factor	Cable Factor	Preamp Loss Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	30.00	23.05	-16.95	40.00	27.25	25.70	1.90	31.80	---	--- Peak
2	83.46	26.34	-13.66	40.00	42.21	13.86	2.00	31.73	---	--- Peak
3	174.18	34.76	-8.74	43.50	48.92	15.53	2.03	31.72	100	325 Peak
4	449.80	32.59	-13.41	46.00	38.52	23.10	2.79	31.82	---	--- Peak
5	850.20	33.02	-12.98	46.00	32.33	29.11	3.31	31.73	---	--- Peak
6 *	881.70	50.35		49.30	29.29	3.36	31.60		---	--- Peak
7	899.90	33.18	-12.82	46.00	31.92	29.40	3.39	31.53	---	--- Peak
8	1826.00	45.23	-28.77	74.00	73.67	26.07	5.99	60.50	---	--- Peak
9	3892.00	44.91	-29.09	74.00	66.77	29.49	10.11	61.46	---	--- Peak
10	6760.00	42.93	-31.07	74.00	56.70	34.72	11.86	60.35	---	--- Peak
11	8522.00	44.01	-29.99	74.00	52.58	36.93	13.93	59.43	---	--- Peak
12	10982.00	46.87	-27.13	74.00	50.46	40.49	15.07	59.15	---	--- Peak
13	11646.00	47.41	-26.59	74.00	49.80	39.87	16.22	58.48	100	0 Peak



<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	20~23°C							
<b>Test Engineer :</b>	Daniel Lee	<b>Relative Humidity :</b>	50~53%							
<b>Test Distance :</b>	3m	<b>Polarization :</b>	Vertical							
<b>Function Type :</b>	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook)									
<b>Remark :</b>	#5 is system simulator signal which can be ignored.									
<p>Level (dBuV/m)</p> <p>Date: 2016-05-21</p> <p>FCC CLASS-B</p> <p>FCC CLASS-B (AVG)</p> <p>Frequency (MHz)</p>										
<b>Site</b>	: 03CH06-HY									
<b>Condition</b>	: FCC CLASS-B 3m 9120D_1156_150827 VERTICAL									
<b>Power</b>	: From System									
<b>Memo</b>	: Mode 2									
	Freq	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm deg	
1	31.89	25.59	-14.41	40.00	30.90	24.58	1.91	31.80	---	--- Peak
2	147.45	30.95	-12.55	43.50	43.00	17.54	2.12	31.71	---	--- Peak
3	169.59	33.78	-9.72	43.50	47.64	15.80	2.06	31.72	100	205 Peak
4	850.20	35.71	-10.29	46.00	35.02	29.11	3.31	31.73	---	--- Peak
5 *	881.70	50.50			49.45	29.29	3.36	31.60	---	--- Peak
6	899.90	35.86	-10.14	46.00	34.60	29.40	3.39	31.53	---	--- Peak
7	950.30	35.69	-10.31	46.00	33.00	30.70	3.05	31.06	---	--- Peak
8	1892.00	50.99	-23.01	74.00	79.20	26.14	6.15	60.50	100	311 Peak
9	3886.00	49.11	-24.89	74.00	70.97	29.49	10.11	61.46	---	--- Peak
10	6528.00	42.84	-31.16	74.00	56.83	34.14	12.27	60.40	---	--- Peak
11	8034.00	44.66	-29.34	74.00	54.36	37.18	12.71	59.59	---	--- Peak
12	10852.00	46.82	-27.18	74.00	51.07	40.39	14.87	59.51	---	--- Peak
13	11010.00	46.81	-27.19	74.00	50.26	40.49	15.14	59.08	---	--- Peak



## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 19, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	May 19, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	May 19, 2016	Dec. 01, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 14, 2015	May 21, 2016	Dec. 13, 2016	Conduction (CO05-HY)
Bilog Antenna	Schaffner	CBL6111C	2725	30MHz~1GHz	Nov. 17, 2015	May 21, 2016	Nov. 16, 2016	Radiation (03CH06-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Jan. 07, 2016	May 21, 2016	Jan. 06, 2017	Radiation (03CH06-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1156	1GHz~18GHz	Aug. 21, 2015	May 21, 2016	Aug. 20, 2016	Radiation (03CH06-HY)
Preamplifier	SONOMA	310N	186713	9kHz~1GHz	Apr. 19, 2016	May 21, 2016	Apr. 18, 2017	Radiation (03CH06-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1850117	1GHz ~ 18GHz	Jul. 01, 2015	May 21, 2016	Jun. 30, 2016	Radiation (03CH06-HY)
Controller	INN-CO	EM1000	060782	Control Turn table & Ant Mast	N/A	May 21, 2016	N/A	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF78020821 2	1m~4m	N/A	May 21, 2016	N/A	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0-360 degree	N/A	May 21, 2016	N/A	Radiation (03CH06-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	May 21, 2016	Sep. 01, 2016	Radiation (03CH06-HY)



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.26
---	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.00
---	------