



FCC Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : 10874, 12665
FCC ID : IHDT56WK3
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jun. 17, 2017 and testing was completed on Jul. 24, 2017. We, Sporton International (KunShan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.

***No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China***



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Product Feature of Equipment Under Test	5
1.4. Product Specification of Equipment Under Test	6
1.5. Specification of Accessory	8
1.6. Modification of EUT	8
1.7. Test Location	8
1.8. Applicable Standards	9
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1. Test Mode	10
2.2. Connection Diagram of Test System	11
2.3. Support Unit used in test configuration and system.....	12
2.4. EUT Operation Test Setup	12
3. TEST RESULT	13
3.1. Test of AC Conducted Emission Measurement	13
3.2. Test of Radiated Emission Measurement	17
4. LIST OF MEASURING EQUIPMENT	21
5. UNCERTAINTY OF EVALUATION	22
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC761702-02	Rev. 01	Initial issue of report	Aug. 09, 2017



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 11.33 dB at 0.449 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.04 dB at 165.81 MHz for Quasi-Peak



1. General Description

1.1. Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2. Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	10874, 12665
FCC ID	IHDT56WK3
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/ HSPA+ (16QAM uplink is not supported)/LTE/NFC WLAN 2.4G 802.11b/g/n HT20/HT40/ WLAN 5G 802.11a/n HT20/HT40/ WLAN 5G 802.11ac VHT20/VHT40/VHT80/ Bluetooth V3.0 + EDR/ Bluetooth V4.0 LE/ Bluetooth v4.1 LE / Bluetooth v4.2 LE / Bluetooth v5.0 LE
IMEI Code	Conduction: 356516080008035/356516080008043 Radiation: 356516080008050/356516080008068
HW Version	DVT2
SW Version	NPW26.75
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, the differences between two samples are only for SIM slot: sample 1(Model name: 12665) is dual SIM slot, sample 2(Model name: 10874) is single SIM slot. We only choose sample 1 to perform full tests.

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500MHz ~ 5700 MHz ; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7: 2622.5 MHz ~ 2687.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500MHz ~ 5700 MHz ; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz Glonass: 1602 MHz + $n \times 0.5625\text{MHz}$ ($n=-7,-6,-5,...,0,...,6$) FM : 88 MHz ~ 108 MHz NFC : 13.56 MHz
Antenna Type	WWAN : Fixed Internal Antenna WLAN : Loop Antenna Bluetooth : Loop Antenna GPS/Glonass : Internal Loop Antenna NFC : Frame Loop Antenna FM: External headset Antenna



Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (uplink is not supported) DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM (Uplink) 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS/Glonass : BPSK FM NFC: ASK
---------------------------	---

Note: WLAN operation in 5600 MHz ~ 5650 MHz is notched.

1.5. Specification of Accessory

Specification of Accessory			
AC Adapter 1 (US)	Brand Name	Motorola (Salom)	Model Name SC-22
	Power Rating	I/P: 100 – 240 Vac, 500 mA, O/P: 5/9/12 Vdc, 3000/1600/1200 mA	
AC Adapter 2 (US)	Brand Name	Motorola (Chenyang)	Model Name SC-22
	Power Rating	I/P: 100 – 240 Vac, 500 mA, O/P: 5/9/12 Vdc, 3000/1600/1200 mA	
AC Adapter 3 (US)	Brand Name	Motorola (LiteOn)	Model Name SC-22
	Power Rating	I/P: 100 – 240 Vac, 500 mA, O/P: 5/9/12 Vdc, 3000/1600/1200 mA	
Battery	Brand Name	Motorola (Sunwoda)	Model Name HX40
	Power Rating	3.8Vdc, 2810mAh	Type Li-ion
Earphone	Brand Name	Motorola (Cosonic)	Model Name SH38C16617
	Signal Line Type	1.10 meter, non-shielded cable, with w/o ferrite core	
USB Cable 1	Brand Name	Motorola (Saibao)	Model Name SKN6473A
	Signal Line Type	1.10 meter, shielded cable, with w/o ferrite core	
USB Cable 2	Brand Name	Motorola (Foxlink)	Model Name SKN6473A
	Signal Line Type	1.10 meter, shielded cable, with w/o ferrite core	
USB Cable 3	Brand Name	Motorola (Cabletech)	Model Name SKN6473A
	Signal Line Type	1.10 meter, shielded cable, with w/o ferrite core	

1.6. Modification of EUT

No modifications are made to the EUT during all test items.

1.7. Test Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No is CN5013.

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.		FCC Test Firm Registration No.
	CO01-KS	03CH02-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. For FCC 15 Subpart B - Unintentional Radiators, device supporting USB interface or similar peripherals (defined as the Section 15.3 (r) Peripheral device) acting as a peripheral for personal computers shall be authorized as "The Class B personal computers and peripherals" per the Section 15.101 (a) Equipment authorization of unintentional radiators.
3. For other Unintentional Radiators features of this EUT, test reports are be issued separately.
Per the Note of the Section 15.101, when device supports features (USB, FM Radio, digital devices...etc) more than one category of authorization, type of authorization shall be appropriately chosen for FCC 15B compliance rule, and the Section 15.101 (b), only those receivers that operate (tune) within the frequency range of 30-960 MHz, CB receivers and radar detectors are subject to the authorizations shown in paragraph (a) of the Section 15.101. However, receivers indicated as being subject to Declaration of Conformity that are contained within a transceiver, the transmitter portion of which is subject to certification, shall be authorized under the verification procedure.

2. Test Configuration of Equipment Under Test


2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Earphone + USB Cable 1(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1 Mode 2: LTE Band 5 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable 2(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1 Mode 3: LTE Band 5 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable 3(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1
Radiated Emissions < 1GHz	Mode 1: LTE Band 5 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable 1(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1 Mode 2: LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Earphone + USB Cable 2(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1 Mode 3: LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Earphone + USB Cable 3(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1
Radiated Emissions $\geq$ 1GHz	Mode 1: LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Earphone + USB Cable 3(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1
Remark: 1. The worst case of AC is mode 2; only the test data of this mode was reported. 2. The worst case of RE < 1G is mode 3; only the test data of this mode was reported.	

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritus	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	ADIVIE	MP9000	N/A	N/A	Unshielded, 1.8m
3.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
4.	WLAN AP	TP-LINK	TL-WDR5600	N/A	N/A	N/A
5.	Notebook	Dell	Latitude3440	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
7.	Bluetooth Earphone	Lenovo	LBH301	QTLBH-106	N/A	N/A
8.	Bluetooth Earphone	Lenovo	LBH308	QTLBH-106	N/A	N/A
9.	Hard Disk	Lenovo	F310	FCC DoC	Shielded, 1.2 m	N/A
10.	SD Card	Kingston	8GB	N/A	N/A	N/A
11.	SD Card	SanDisk	Ultra	N/A	N/A	N/A

2.4. EUT Operation Test Setup

The EUT was in LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on GPS function to make the EUT receive continuous signals from GPS station.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 5 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable 2(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1		




Site : CO01-KS
 Condition : FCC CLASS-B LISN-L-161017-060103 LINE
 Project : (FC) 761702-02
 mode : Mode 2
 : 356516080008035/356516080008043 #4

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV		dB	dBuV	dB	dB	
1	0.158	38.49	-27.07	65.56	27.61	0.50	10.38	QP
2	0.158	23.49	-32.07	55.56	12.61	0.50	10.38	Average
3	0.167	37.42	-27.70	65.12	26.60	0.45	10.37	QP
4	0.167	25.12	-30.00	55.12	14.30	0.45	10.37	Average
5	0.189	34.26	-29.80	64.06	23.60	0.32	10.34	QP
6	0.189	21.96	-32.10	54.06	11.30	0.32	10.34	Average
7	0.198	33.21	-30.50	63.71	22.60	0.28	10.33	QP
8	0.198	21.91	-31.80	53.71	11.30	0.28	10.33	Average
9	0.449	36.66	-20.23	56.89	26.20	0.27	10.19	QP
10 *	0.449	35.56	-11.33	46.89	25.10	0.27	10.19	Average
11	0.471	35.06	-21.43	56.49	24.60	0.27	10.19	QP
12	0.471	32.26	-14.23	46.49	21.80	0.27	10.19	Average



Test Mode :	Mode 2	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 5 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable 2(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1		



Site : CO01-KS
 Condition : FCC CLASS-B LISN-N-161017-060103 NEUTRAL
 Project : (FC) 761702-02
 mode : Mode 2
 : 356516080008035/356516080008043 #4

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.152	43.33	-22.58	65.91	32.60	0.34	10.39	QP
2	0.152	32.33	-23.58	55.91	21.60	0.34	10.39	Average
3	0.169	41.90	-23.09	64.99	31.19	0.34	10.37	QP
4	0.169	31.30	-23.69	54.99	20.59	0.34	10.37	Average
5	0.183	35.18	-29.15	64.33	24.50	0.33	10.35	QP
6	0.183	26.98	-27.35	54.33	16.30	0.33	10.35	Average
7	0.197	38.17	-25.59	63.76	27.50	0.33	10.34	QP
8	0.197	26.97	-26.79	53.76	16.30	0.33	10.34	Average
9	0.205	36.26	-27.14	63.40	25.60	0.33	10.33	QP
10	0.205	26.96	-26.44	53.40	16.30	0.33	10.33	Average
11	0.474	36.07	-20.38	56.45	25.50	0.38	10.19	QP
12 *	0.474	33.87	-12.58	46.45	23.30	0.38	10.19	Average

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz



3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 3	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Earphone + USB Cable 3(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1		
Remark :	#7 is system simulator signal which can be ignored.		




Condition : FCC CLASS-B 3m 02 LF ANT HORIZONTAL
 Project : (FC) 761702-02
 Mode : 3
 IMEI : 356516080008050 356516080008068 #3

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	96.15	24.42	-19.08	43.50	38.65	17.50	0.23	31.96	---	Peak
2 !	165.81	40.46	-3.04	43.50	54.90	16.96	0.35	31.75	200	0 QP
3 !	170.40	39.73	-3.77	43.50	54.28	16.82	0.36	31.73	---	Peak
4	254.37	33.67	-12.33	46.00	47.59	17.00	0.50	31.42	---	Peak
5	345.50	36.02	-9.98	46.00	46.60	19.67	0.71	30.96	---	Peak
6	615.00	33.10	-12.90	46.00	36.72	24.85	0.94	29.41	---	Peak
7 *	876.80	51.52			50.30	27.32	1.55	27.65	---	Peak
8	1388.00	44.74	-29.26	74.00	47.90	28.48	3.35	34.99	---	Peak
9	2014.00	46.71	-27.29	74.00	44.60	30.25	4.61	32.75	---	Peak
10	2864.00	45.83	-28.17	74.00	40.88	32.00	2.85	29.90	---	Peak
11	3111.00	47.07	-26.93	74.00	39.55	32.78	4.76	30.02	---	Peak
12	3804.00	47.07	-26.93	74.00	36.02	34.68	6.59	30.22	---	Peak
13	4236.00	47.13	-26.87	74.00	36.67	35.35	6.17	31.06	---	Peak



Test Mode :	Mode 3	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Function Type :	LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Earphone + USB Cable 3(Data Link with Notebook) + Battery + GPS Rx + SIM1 for Sample 1		
Remark :	#7 is system simulator signal which can be ignored.		



Condition : FCC CLASS-B 3m 02 LF ANT VERTICAL
 Project : (FC) 761702-02
 Mode : 3
 IMEI : 356516080008050 356516080008068 #3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	42.96	25.95	-14.05	40.00	37.31	20.57	0.13	32.06	---	---	Peak
2 !	165.27	39.84	-3.66	43.50	54.28	16.96	0.35	31.75	100	0	Peak
3	170.67	34.88	-8.62	43.50	49.43	16.82	0.36	31.73	---	---	Peak
4	174.72	35.94	-7.56	43.50	50.61	16.68	0.37	31.72	---	---	Peak
5	615.00	37.70	-8.30	46.00	41.32	24.85	0.94	29.41	---	---	Peak
6	705.30	32.61	-13.39	46.00	33.79	26.44	1.20	28.82	---	---	Peak
7 !	883.10	42.49			41.14	27.36	1.59	27.60	---	---	Peak
8	1966.00	45.81	-28.19	74.00	44.24	29.94	4.47	32.84	---	---	Peak
9	2144.00	44.92	-29.08	74.00	42.24	30.60	5.50	33.42	---	---	Peak
10	2966.00	45.53	-28.47	74.00	39.23	32.30	3.04	29.04	---	---	Peak
11	3399.00	47.00	-27.00	74.00	38.10	33.28	5.93	30.31	---	---	Peak
12	3756.00	46.64	-27.36	74.00	35.72	34.60	6.44	30.12	---	---	Peak
13	4167.00	45.89	-28.11	74.00	34.96	35.27	6.60	30.94	---	---	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 20, 2017	Jul. 24, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Jul. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Jul. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Jul. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Aug. 09, 2016	Jul. 16, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44G,MAX 30dB	Apr. 18, 2017	Jul. 16, 2017	Apr. 17, 2018	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Aug. 20, 2016	Jul. 16, 2017	Aug. 19, 2017	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 22, 2016	Jul. 16, 2017	Oct. 21, 2017	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz ~40GHz	Feb. 15, 2017	Jul. 16, 2017	Feb. 14, 2018	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-H G	1887435	18~40GHz	Oct. 13, 2016	Jul. 16, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 09, 2016	Jul. 16, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1~26.5GHz Gain 30dB	Oct. 13, 2016	Jul. 16, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Jul. 16, 2017	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jul. 16, 2017	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jul. 16, 2017	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.3dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.2dB
--	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.7dB
--	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.3dB
--	-------