



# FCC Test Report

**APPLICANT** : Motorola Mobility LLC  
**EQUIPMENT** : Mobile Cellular Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT1926-6, XT1926-7  
**FCC ID** : IHDT56WL4  
**STANDARD** : FCC 47 CFR FCC Part 15 Subpart B  
**CLASSIFICATION** : Certification

The product was received on Dec. 27, 2017 and testing was completed on Jan. 22, 2018. We, Sporton International (KunShan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

**Sporton International (Kunshan) Inc.**  
**No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335**  
**China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1. GENERAL DESCRIPTION ..... 5**

    1.1. Applicant..... 5

    1.2. Manufacturer ..... 5

    1.3. Product Feature of Equipment Under Test ..... 5

    1.4. Product Specification of Equipment Under Test ..... 6

    1.5. Modification of EUT ..... 7

    1.6. Accessory List ..... 8

    1.7. Test Location ..... 9

    1.8. Applicable Standards ..... 9

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 10**

    2.1. Test Mode ..... 10

    2.2. Connection Diagram of Test System ..... 12

    2.3. Support Unit used in test configuration and system ..... 14

    2.4. EUT Operation Test Setup ..... 14

**3. TEST RESULT ..... 15**

    3.1. Test of AC Conducted Emission Measurement ..... 15

    3.2. Test of Radiated Emission Measurement ..... 21

**4. LIST OF MEASURING EQUIPMENT ..... 27**

**5. UNCERTAINTY OF EVALUATION ..... 28**

**APPENDIX A. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 9.21 dB at 0.224 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 4.25 dB at 44.580 MHz for Quasi-Peak



# 1. General Description

## 1.1. Applicant

Motorola Mobility LLC  
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2. Manufacturer

Motorola Mobility LLC  
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1926-6, XT1926-7
FCC ID	IHDT56WL4
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth v3.0+ EDR / Bluetooth v4.0 LE/ Bluetooth v4.1 LE / Bluetooth v4.2 LE / Bluetooth v5.0 LE
SN/IMEI Code	Conduction: NTEL1B0009 for Sample 1 351881090004332 for Sample 2 Radiation: 351853090016038/351853090016046
HW Version	DVT1B
SW Version	evert_n-userdebug 8.0.0 OPW27.88 1825 intcfg,test-keys
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT: sample 1 (XT1926-7) is dual SIM card, sample 2 (XT1926-6) is single SIM card. Except the SIM card slot, all the others are the same. According to the difference, we choose sample 1 to perform full test, sample 2 to verify worst case.



### 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz; 5745 MHz ~ 5825 MHz; Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz; 5745 MHz ~ 5825 MHz; Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz FM : 88 MHz ~ 108 MHz NFC : 13.56 MHz
<b>Antenna Type</b>	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna NFC: Loop Antenna FM: External headset Antenna



<p><b>Type of Modulation</b></p>	<p>GSM: GMSK  GPRS: GMSK  EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK  WCDMA : BPSK (Uplink)  HSDPA/DC-HSDPA : QPSK (Uplink)  HSUPA : QPSK (Uplink)  HSPA+ : 16QAM (Uplink)  DC-HSDPA : 64QAM  LTE: QPSK / 16QAM / 64QAM  802.11b : DSSS (DBPSK / DQPSK / CCK)  802.11a/g/n/ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)  Bluetooth LE : GFSK  Bluetooth (1Mbps) : GFSK  Bluetooth (2Mbps) : <math>\pi/4</math>-DQPSK  Bluetooth (3Mbps) : 8-DPSK  GNSS : BPSK  NFC : ASK  FM</p>
----------------------------------	---

Note: GNSS Rx = GPS Rx + Glonass Rx

### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.



### 1.6. Accessory List

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola (Salom)	Model Name	SC-22
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(EU)	Brand Name	Motorola (Salom)	Model Name	SC-23
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(UK)	Brand Name	Motorola (Salom)	Model Name	SC-24
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(IN)	Brand Name	Motorola (Salom)	Model Name	SC-25
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(AU)	Brand Name	Motorola (Salom)	Model Name	SC-26
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(AR)	Brand Name	Motorola (Salom)	Model Name	SC-27
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(US)	Brand Name	Motorola (Chenyang)	Model Name	SC-22
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(EU)	Brand Name	Motorola (Chenyang)	Model Name	SC-23
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(UK)	Brand Name	Motorola (Chenyang)	Model Name	SC-24
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(IN)	Brand Name	Motorola (Chenyang)	Model Name	SC-25
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(AU)	Brand Name	Motorola (Chenyang)	Model Name	SC-26
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(AR)	Brand Name	Motorola (chenyang)	Model Name	SC-27
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
Battery	Brand Name	Motorola (ATL)	Model Name	JT40
	Power Rating	3.8Vdc,3200mAh	Type	Li-ion Polymer
Earphone 1	Brand Name	Motorola (Jiahe)	Model Name	LS-118M-12
	Signal Line Type	1.2 meter, non-shielded cable, without ferrite core		
Earphone 2	Brand Name	Motorola (Lianyun)	Model Name	TS910A-38AMS01WHR-M
	Signal Line Type	1.2 meter, non-shielded cable, without ferrite core		
USB Cable	Brand Name	Motorola (Liqi)	Model Name	L32B-053000100-ALL
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		



### 1.7. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No is CN5013.

<b>Test Site</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Test Firm Registration No.</b>
	CO01-KS	03CH02-KS	630927

**Note:** The test site complies with ANSI C63.4 2014 requirement.

### 1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + Camera (Rear) + SIM 1 for Sample 1<fig.1>
	Mode 2: PCS 1900 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + Camera (Front) + SIM 2 for Sample 1<fig.1>
	Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + MPEG4 + SIM 1 for Sample 1<fig.1>
	Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + GNSS Rx + SIM 2 for Sample 1<fig.2>
	Mode 5: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + NFC On + SIM 2 for Sample 1<fig.1>
	Mode 6: GSM 850 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter2) + Earphone 2 + Battery + Camera (Rear) + SIM 1 for Sample 1<fig.1>
	Mode 7: GSM 850 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + Camera (Rear) + SIM 1 for Sample 2<fig.1>
	Mode 8: LTE Band 7 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone 1 + Battery + GNSS Rx + SIM 1 for Sample 1<fig.3>
	Mode 9: USB Cable (Charging from Adapter 1) + Earphone 1 + Battery + FM Rx (88MHz) for Sample 1<fig.4>
	Mode 10 : USB Cable (Charging from Adapter 1) + Earphone 1 + Battery + FM Rx (98MHz) for Sample 1<fig.4>
	Mode 11 : USB Cable (Charging from Adapter 1) + Earphone 1 + Battery + FM Rx (108MHz) for Sample 1<fig.4>
	Mode 12 : USB Cable (Charging from Adapter 2) + Earphone 2 + Battery + FM Rx (88MHz) for Sample 1<fig.4>




Radiated Emissions	Mode 1: GSM 850 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + Camera (Rear) + SIM 1 for Sample 1<fig.1>
	Mode 2: PCS 1900 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + Camera (Front) + SIM 2 for Sample 1<fig.1>
	Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + MPEG4 + SIM 1 for Sample 1<fig.1>
	Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + GNSS Rx + SIM 2 for Sample 1<fig.2>
	Mode 5: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + NFC On + SIM 2 for Sample 1<fig.1>
	Mode 6: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter2) + Earphone 2 + Battery + MPEG4 + SIM 1 for Sample 1<fig.1>
	Mode 7: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + MPEG4 + SIM 1 for Sample 2<fig.1>
	Mode 8: LTE Band 7 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone 1 + Battery + GNSS Rx + SIM 1 for Sample 1<fig.3>
	Mode 1: USB Cable (Charging from Adapter 1) + Earphone 1 + Battery + FM Rx (88MHz) for Sample 1<fig.4>
	Mode 2: USB Cable (Charging from Adapter 1) + Earphone 1 + Battery + FM Rx (98MHz) for Sample 1<fig.4>
	Mode 3: USB Cable (Charging from Adapter 1) + Earphone 1 + Battery + FM Rx (108MHz) for Sample 1<fig.4>
	Mode 9: USB Cable (Charging from Adapter 2) + Earphone 2 + Battery + FM Rx (108MHz) for Sample 1<fig.4>


**Remark:**

1. The worst case of AC is mode 1; and USB Link is mode 8, the test data of these modes were reported.
2. The worst case of RE < 1G is mode 3; and USB Link is mode 8, the test data of these modes were reported.
3. Data Link with Notebook means data application transferred mode between EUT and Notebook


## 2.2. Connection Diagram of Test System




<Fig.1>



<Fig.2>



<Fig.3>



<Fig.4>

### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	GNSS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8m
3.	FM Generator	R&S	SMBV100A	N/A	N/A	Unshielded, 1.8 m
4.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
5.	WLAN AP	TP-LINK	TL-WDR5600	N/A	N/A	Unshielded, 1.8 m
6.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
7.	Notebook	Dell	Latitude3440	NA	NA	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
8.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
9.	SD Card	Kingston	8GB	N/A	N/A	N/A
10.	SD Card	SanDisk	Uitra	N/A	N/A	N/A
11.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A

### 2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator’s paging reorganization.

During test, the EUT was turned to Radio frequency channels, FM88 MHz, FM98 MHz, and FM108 MHz, from FM Generator. At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Execute “Video player” to play MPEG4 files.
4. Turn on camera to capture images.
5. Turn on NFC function.



### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Eko Guan	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM 850 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + Camera (Rear) + SIM 1 for Sample 1		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-L-171013-060103 LINE

mode : Mode 1  
 : NTEL1B0009 #10

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.170	54.43	-10.51	64.94	43.70	0.18	10.55	QP
2	0.170	36.93	-18.01	54.94	26.20	0.18	10.55	Average
3	0.191	52.98	-11.00	63.98	42.31	0.19	10.48	QP
4	0.191	39.28	-14.70	53.98	28.61	0.19	10.48	Average
5	0.202	50.96	-12.58	63.54	40.31	0.20	10.45	QP
6	0.202	38.46	-15.08	53.54	27.81	0.20	10.45	Average
7 *	0.224	53.45	-9.21	62.66	42.79	0.21	10.45	QP
8	0.224	37.95	-14.71	52.66	27.29	0.21	10.45	Average
9	0.259	37.45	-24.02	61.47	26.79	0.22	10.44	QP
10	0.259	25.85	-25.62	51.47	15.19	0.22	10.44	Average
11	0.398	31.95	-25.95	57.90	21.29	0.25	10.41	QP
12	0.398	20.85	-27.05	47.90	10.19	0.25	10.41	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Eko Guan	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM 850 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + Camera (Rear) + SIM 1 for Sample 1		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-N-171013-060103 NEUTRAL

mode : Mode 1  
 : NTEL1B0009 #10

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.170	43.73	-21.21	64.94	32.90	0.28	10.55	QP
2	0.170	33.03	-21.91	54.94	22.20	0.28	10.55	Average
3	0.191	40.66	-23.32	63.98	29.90	0.28	10.48	QP
4	0.191	26.66	-27.32	53.98	15.90	0.28	10.48	Average
5	0.221	37.03	-25.76	62.79	26.30	0.28	10.45	QP
6	0.221	25.53	-27.26	52.79	14.80	0.28	10.45	Average
7	0.244	40.22	-21.73	61.95	29.50	0.28	10.44	QP
8	0.244	29.12	-22.83	51.95	18.40	0.28	10.44	Average
9 *	0.604	34.92	-21.08	56.00	24.39	0.30	10.23	QP
10	0.604	22.12	-23.88	46.00	11.59	0.30	10.23	Average
11	0.651	33.79	-22.21	56.00	23.30	0.30	10.19	QP
12	0.651	23.89	-22.11	46.00	13.40	0.30	10.19	Average



Test Mode :	Mode 8	Temperature :	22~24°C
Test Engineer :	Eko Guan	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 7 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone 1 + Battery + GNSS Rx + SIM 1 for Sample 1		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-L-171013-060103 LINE  
 Project : (FC) 7D2702

: NTEL1B0009 #10

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.163	37.04	-28.26	65.30	26.30	0.17	10.57	QP
2	0.163	25.54	-29.76	55.30	14.80	0.17	10.57	Average
3	0.444	36.11	-20.87	56.98	25.50	0.25	10.36	QP
4 *	0.444	33.91	-13.07	46.98	23.30	0.25	10.36	Average
5	0.471	35.89	-20.60	56.49	25.30	0.26	10.33	QP
6	0.471	27.89	-18.60	46.49	17.30	0.26	10.33	Average
7	2.309	34.10	-21.90	56.00	23.61	0.29	10.20	QP
8	2.309	25.00	-21.00	46.00	14.51	0.29	10.20	Average
9	2.707	32.30	-23.70	56.00	21.80	0.31	10.19	QP
10	2.707	24.10	-21.90	46.00	13.60	0.31	10.19	Average
11	4.978	31.40	-24.60	56.00	20.80	0.37	10.23	QP
12	4.978	27.40	-18.60	46.00	16.80	0.37	10.23	Average



Test Mode :	Mode 8	Temperature :	22~24°C
Test Engineer :	Eko Guan	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 7 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone 1 + Battery + GNSS Rx + SIM 1 for Sample 1		



Site : CO01-KS  
 Condition : FCC CLASS-B LISN-N-171013-060103 NEUTRAL  
 Project : (FC) 7D2702

: NTEL1B0009 #10

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.153	41.29	-24.53	65.82	30.40	0.28	10.61	QP
2	0.153	31.59	-24.23	55.82	20.70	0.28	10.61	Average
3	0.161	37.46	-27.97	65.43	26.60	0.28	10.58	QP
4	0.161	29.06	-26.37	55.43	18.20	0.28	10.58	Average
5	0.179	33.60	-30.95	64.55	22.80	0.28	10.52	QP
6	0.179	27.50	-27.05	54.55	16.70	0.28	10.52	Average
7	0.391	32.50	-25.53	58.03	21.80	0.29	10.41	QP
8	0.391	31.20	-16.83	48.03	20.50	0.29	10.41	Average
9	0.486	37.11	-19.12	56.23	26.50	0.29	10.32	QP
10 *	0.486	33.81	-12.42	46.23	23.20	0.29	10.32	Average
11	5.005	30.87	-29.13	60.00	20.30	0.34	10.23	QP
12	5.005	25.27	-24.73	50.00	14.70	0.34	10.23	Average



### 3.2. Test of Radiated Emission Measurement

#### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

#### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 3	Temperature :	21~22°C
Test Engineer :	Leo Li	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + MPEG4 + SIM 1 for Sample 1		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m LF 47610 HORIZONTAL  
 Mode : 3  
 IMEI : 351853090016038 351853090016046 #9

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	32.43	23.45	-16.55	40.00	31.56	23.32	0.61	32.04	---	---	Peak
2	44.31	22.79	-17.21	40.00	37.94	16.30	0.66	32.11	---	---	Peak
3	166.35	21.69	-21.81	43.50	36.33	15.82	1.32	31.78	---	---	Peak
4	206.31	28.37	-15.13	43.50	43.20	15.34	1.48	31.65	---	---	Peak
5	386.10	35.00	-11.00	46.00	42.41	21.32	2.03	30.76	---	---	Peak
6	423.90	37.20	-8.80	46.00	43.48	22.23	2.12	30.63	100	0	Peak
7 *	882.40	51.30			49.37	26.50	3.08	27.65	---	---	Peak
8	2038.00	46.12	-27.88	74.00	44.06	30.42	4.67	33.03	---	---	Peak
9	2660.00	45.44	-28.56	74.00	38.62	31.76	5.48	30.42	---	---	Peak
10	2962.00	45.97	-28.03	74.00	37.55	32.45	5.94	29.97	---	---	Peak
11	3315.00	44.73	-29.27	74.00	35.18	33.26	6.25	29.96	---	---	Peak
12	3708.00	45.54	-28.46	74.00	34.55	34.37	6.55	29.93	---	---	Peak
13	4098.00	44.69	-29.31	74.00	32.53	35.26	7.01	30.11	---	---	Peak



Test Mode :	Mode 3	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter1) + Earphone 1 + Battery + MPEG4 + SIM 1 for Sample 1		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m LF 47610 VERTICAL  
 Mode : 3  
 IMEI : 351853090016038 351853090016046 #9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	31.61	-8.39	40.00	38.07	25.00	0.57	32.03	---	---	Peak
2	39.99	33.31	-6.69	40.00	45.51	19.20	0.64	32.04	---	---	Peak
3 !	44.58	35.75	-4.25	40.00	50.90	16.30	0.66	32.11	100	290	QP
4	200.10	30.56	-12.94	43.50	45.38	15.40	1.45	31.67	---	---	Peak
5	383.30	30.78	-15.22	46.00	38.30	21.23	2.02	30.77	---	---	Peak
6	450.50	30.35	-15.65	46.00	35.90	22.81	2.18	30.54	---	---	Peak
7 !	881.70	43.44			41.53	26.49	3.08	27.66	---	---	Peak
8	1974.00	45.01	-28.99	74.00	43.77	30.07	4.61	33.44	---	---	Peak
9	2758.00	45.71	-28.29	74.00	38.20	31.91	5.72	30.12	---	---	Peak
10	2948.00	46.81	-27.19	74.00	38.41	32.45	5.92	29.97	---	---	Peak
11	3309.00	45.63	-28.37	74.00	36.08	33.26	6.25	29.96	---	---	Peak
12	3594.00	45.73	-28.27	74.00	35.15	33.70	6.45	29.57	---	---	Peak
13	3978.00	46.15	-27.85	74.00	34.50	35.06	6.70	30.11	---	---	Peak



Test Mode :	Mode 8	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	LTE Band 7 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone 1 + Battery + GNSS Rx + SIM 1 for Sample 1		
Remark :	#8 is system simulator signal which can be ignored.		




Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m LF 47610 HORIZONTAL  
 Project : (FC)7D2702  
 IMEI : 351853090016038 351853090016046 #9

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	22.27	-17.73	40.00	28.73	25.00	0.57	32.03	---	---	Peak
2	166.08	24.08	-19.42	43.50	38.69	15.86	1.32	31.79	---	---	Peak
3	200.10	26.83	-16.67	43.50	41.65	15.40	1.45	31.67	---	---	Peak
4	229.80	24.35	-21.65	46.00	38.02	16.30	1.63	31.60	---	---	Peak
5	468.70	28.24	-17.76	46.00	33.39	23.06	2.25	30.46	---	---	Peak
6	848.80	35.28	-10.72	46.00	33.88	26.29	3.04	27.93	100	0	Peak
7	2208.00	45.13	-28.87	74.00	41.13	31.00	4.94	31.94	---	---	Peak
8	2566.00	44.48			38.28	31.59	5.31	30.70	---	---	Peak
9	2766.00	44.86	-29.14	74.00	37.26	31.94	5.78	30.12	---	---	Peak
10	4230.00	46.49	-27.51	74.00	33.86	35.48	7.27	30.12	---	---	Peak
11	4389.00	46.92	-27.08	74.00	34.19	35.72	7.15	30.14	---	---	Peak
12	4716.00	47.33	-26.67	74.00	35.72	35.73	7.68	31.80	---	---	Peak



Test Mode :	Mode 8	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Function Type :	LTE Band 7 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone 1 + Battery + GNSS Rx + SIM 1 for Sample 1		
Remark :	#8 is system simulator signal which can be ignored.		



Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m LF 47610 VERTICAL  
 Project : (FC)7D2702  
 IMEI : 351853090016038 351853090016046 #9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	42.96	24.36	-15.64	40.00	38.33	17.46	0.65	32.08	---	---	Peak
2	114.78	21.54	-21.96	43.50	34.36	17.99	1.09	31.90	---	---	Peak
3	153.12	28.70	-14.80	43.50	42.88	16.38	1.27	31.83	---	---	Peak
4	229.80	23.60	-22.40	46.00	37.27	16.30	1.63	31.60	---	---	Peak
5	382.60	28.18	-17.82	46.00	35.70	21.23	2.02	30.77	---	---	Peak
6	598.90	32.00	-14.00	46.00	34.44	24.61	2.62	29.67	100	0	Peak
7	2302.00	45.10	-28.90	74.00	40.60	31.16	5.04	31.70	---	---	Peak
8	2686.00	44.89			37.90	31.79	5.54	30.34	---	---	Peak
9	2770.00	44.87	-29.13	74.00	37.27	31.94	5.78	30.12	---	---	Peak
10	4293.00	47.60	-26.40	74.00	34.91	35.58	7.23	30.12	---	---	Peak
11	4710.00	47.87	-26.13	74.00	36.06	35.74	7.68	31.61	---	---	Peak
12	4917.00	47.40	-26.60	74.00	37.29	35.58	7.79	33.26	---	---	Peak



### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 20, 2017	Jan. 22, 2018	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2017	Jan. 22, 2018	Oct. 12, 2018	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2017	Jan. 22, 2018	Oct. 12, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000 811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2017	Jan. 22, 2018	Oct. 11, 2018	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Aug. 08, 2017	Jan. 20, 2018	Aug. 07, 2018	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 08	10Hz~44GHz, MAX 30dB	Apr. 18, 2017	Jan. 20, 2018	Apr. 17, 2018	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz~2GHz	Jan. 22, 2017	Jan. 20, 2018	Jan. 21, 2018	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 21, 2017	Jan. 20, 2018	Oct. 20, 2018	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Feb. 15, 2017	Jan. 20, 2018	Feb. 14, 2018	Radiation (03CH01-KS)
Amplifier	SONOMA	310N	187289	9kHz~1GHz	Aug. 07, 2017	Jan. 20, 2018	Aug. 06, 2018	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A0238 4	1-26.5GHz Gain 30dB	Oct. 12, 2017	Jan. 20, 2018	Oct. 11, 2018	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18GHz~40GHz	Oct. 12, 2017	Jan. 20, 2018	Oct. 11, 2018	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Jan. 20, 2018	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jan. 20, 2018	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jan. 20, 2018	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5dB
---	-------

### Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.2dB
---	-------

### Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.7dB
---	-------