



# FCC RF Test Report

**APPLICANT** : Motorola Mobility LLC  
**EQUIPMENT** : Mobile Cellular Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT1980-3  
**FCC ID** : IHDT56XS2  
**STANDARD** : FCC Part 15 Subpart C §15.225  
**CLASSIFICATION** : (DXX) Low Power Communication Device Transmitter

The product was received on Dec. 28, 2018 and testing was completed on Jan. 22, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang /  
Manager



**Sporton International (Kunshan) Inc.**  
**No. 1098, Pengxi North Road, Kunshan Economic Development Zone,**  
**Jiangsu Province 215335, China**



# TABLE OF CONTENTS

**TABLE OF CONTENTS .....2**  
**REVISION HISTORY .....3**  
**SUMMARY OF THE TEST RESULT .....4**  
**1. GENERAL DESCRIPTION .....5**  
    1.1 Applicant..... 5  
    1.2 Manufacturer ..... 5  
    1.3 Product Feature of Equipment Under Test ..... 5  
    1.4 Product Specification of Equipment Under Test ..... 6  
    1.5 Specification of Accessory..... 6  
    1.6 Modification of EUT ..... 6  
    1.7 Testing Location ..... 7  
    1.8 Applicable Standards..... 7  
**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....8**  
    2.1 Descriptions of Test Mode ..... 8  
    2.2 Connection Diagram of Test System ..... 9  
    2.3 Table for Supporting Units ..... 9  
    2.4 EUT Operation Test Setup ..... 9  
**3. TEST RESULTS.....10**  
    3.1 AC Power Line Conducted Emissions Measurement ..... 10  
    3.2 20dB and 99% OBW Spectrum Bandwidth Measurement..... 12  
    3.3 Frequency Stability Measurement ..... 13  
    3.4 Field Strength of Fundamental Emissions and Mask Measurement..... 14  
    3.5 Radiated Emissions Measurement ..... 16  
    3.6 Antenna Requirements..... 19  
**4. LIST OF MEASURING EQUIPMENT .....20**  
**5. UNCERTAINTY OF EVALUATION .....21**  
**APPENDIX A. TEST RESULTS OF CONDUCTED EMISSION TEST**  
**APPENDIX B. TEST RESULTS OF CONDUCTED TEST ITEMS**  
    B1. Test Result of 20dB Spectrum Bandwidth  
    B2. Test Result of Frequency Stability  
**APPENDIX C. TEST RESULTS OF RADIATED TEST ITEMS**  
    C1. Test Result of Field Strength of Fundamental Emissions  
    C2. Results of Radiated Emissions (9 kHz~30MHz)  
    C3. Results of Radiated Emissions (30MHz~1GHz)  
**APPENDIX D. SETUP PHOTOGRAPHS**





### SUMMARY OF THE TEST RESULT

Report Section	FCC Rule	Description of Test	Result	Remark
3.1	15.207	AC Power Line Conducted Emissions	Complies	Under limit 6.80 dB at 0.199MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Complies	-
	-	99% OBW Spectrum Bandwidth	Complies	-
3.3	15.225(e)	Frequency Stability	Complies	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	Max level 66.03 dB $\mu$ V/m at 13.56 MHz
3.5	15.225(d) & 15.209	Radiated Spurious Emissions	Complies	Under limit 7.28 dB at 41.64MHz
3.6	15.203	Antenna Requirements	Complies	-



# 1. General Description

## 1.1 Applicant

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2 Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1980-3
FCC ID	IHDT56XS2
EUT supports Radios application	CDMA/EVDO/GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+(16QAM is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR / EDR / LE NFC/GNSS/FM Receiver
IMEI Code	Conducted: 352156100008097 Conduction: 352156100009624 Radiation: 352156100008246/352156100008201
HW Version	DVT2
SW Version	PPF29.58
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	13.553 ~ 13.567MHz
Channel Number	1
20dBW	2.50 KHz
99%OBW	2.11 KHz
Antenna Type	Loop Antenna
Type of Modulation	ASK

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.5 Specification of Accessory

Specification of Accessory			
AC Adapter 1(US)	Brand Name	Motorola (Salom)	Model Name SC-51
	Power Rating	I/P: 100-240 Vac, 0.6A O/P: 5Vdc,3A or 9Vdc,2A or 12Vdc,1.5A	
AC Adapter 2(US)	Brand Name	Motorola (Chenyang)	Model Name SC-51
	Power Rating	I/P: 100-240 Vac, 0.6A O/P: 5Vdc,3A or 9Vdc,2A or 12Vdc,1.5A	
Battery	Brand Name	Amperex (Motorola)	Model Name KZ40
	Power Rating	3.8Vdc,3600mAh	Type Li-ion Polymer
USB Cable 1	Brand Name	Motorola (Cabletech)	Model Name SC18C49697
	Signal Line Type	1.0 meter, shielded cable, without ferrite core	
USB Cable 2	Brand Name	Motorola (Saibao)	Model Name SC18C24367
	Signal Line Type	1.0 meter, shielded cable, without ferrite core	
USB Cable 3	Brand Name	Motorola (Luxshare)	Model Name SC18C24368
	Signal Line Type	1.0 meter, shielded cable, without ferrite core	

### 1.6 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

<b>Test Site</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC designation No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-KS CO01-KS 03CH06-KS	CN5013	630927

**Note:** The test site complies with ANSI C63.4 2014 requirement.

### 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2013



## 2. Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.


Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report. Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

Test Cases	
AC Conducted Emission	Mode 1: GSM 850 Idle + Bluetooth Link + WLAN 2.4 Link + NFC Tx + Earphone + USB Cable 2 (Charging from Adapter 2)



## 2.2 Connection Diagram of Test System



## 2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
3.	WLAN AP	D-link	DIR-855	KA2DIR855A2		Unshielded,1.8m
4.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8 m
5.	NFC Card	N/A	N/A	N/A	N/A	N/A
6.	SD Card	Kingston	8GB	N/A	N/A	N/A

## 2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.

### 3. Test Results

#### 3.1 AC Power Line Conducted Emissions Measurement

##### 3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test setup



### 3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

## 3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

### 3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

### 3.3 Frequency Stability Measurement

#### 3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The  $f_c$  is declaring of channel frequency. Then the frequency error formula is  $(f_c - f) / f_c \times 10^6$  ppm and the limit is less than  $\pm 100$ ppm.
6. Extreme temperature rule is -20°C~50°C.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.



### 3.4 Field Strength of Fundamental Emissions and Mask Measurement

#### 3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

#### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.

Note: Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).

### 3.4.4 Test Setup

For radiated emissions below 30MHz



### 3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

### 3.5 Radiated Emissions Measurement

#### 3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.5.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

**Note:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.






### **3.5.4 Test Procedures**


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

### 3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



### 3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

**Remark:** There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.



## **3.6 Antenna Requirements**

### **3.6.1 Standard Applicable**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.6.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.



### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY564000 23	3Hz~8.5GHz;M ax 30dBm	Oct. 12. 2018	Jan. 22, 2019	Oct. 11.2019	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Jan. 22, 2019	Oct. 18, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Jan. 29, 2018	Jan. 22, 2019	Jan. 28, 2019	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 6, 2018	Jan. 22, 2019	Aug. 5, 2019	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Jan. 22, 2019	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 22, 2019	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 22, 2019	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Dec. 25, 2018	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Dec. 25, 2018	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Dec. 25, 2018	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Dec. 25, 2018	Oct. 11, 2019	Conduction (CO01-KS)
RF Cable	WOKEN	Y5T	00100N1Q 3N1	150kHz~30MHz	Aug. 24 2018	Dec. 25, 2018	Aug. 23, 2019	Conduction (CO01-KS)
Transient limiter	COM-POWER	LIT-153	531040	150kHz~30MHz	Aug. 24, 2018	Dec. 25, 2018	Aug. 23, 2019	Conduction (CO01-KS)
Power bar	SP101EA	CN02		150kHz~30MHz	Apr. 16, 2018	Dec. 25, 2018	Apr. 15, 2019	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	Jan. 22, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-9605 02	-40~+150°C	Nov. 19, 2018	Jan. 22, 2019	Nov. 18, 2019	Conducted (TH01-KS)



## 5. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.9 dB
---	--------


### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------



## Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Amos Zhang	Temperature :	23.3~24.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Site : CO01-KS  
 Condition : FCC PART 15C LISN-L-181013-060103 LINE  
 Project : (FR) 8D2801  
 mode : Mode 2  
 : 352156100009624 #4

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.170	48.15	-16.79	64.94	37.49	0.23	10.43	QP
2	0.170	27.85	-27.09	54.94	17.19	0.23	10.43	Average
3	0.191	51.10	-12.88	63.98	40.50	0.22	10.38	QP
4	0.191	30.80	-23.18	53.98	20.20	0.22	10.38	Average
5	0.205	54.88	-8.52	63.40	44.30	0.22	10.36	QP
6	0.205	37.18	-16.22	53.40	26.60	0.22	10.36	Average
7	0.228	44.47	-18.05	62.52	33.90	0.22	10.35	QP
8	0.228	23.17	-29.35	52.52	12.60	0.22	10.35	Average
9	0.243	43.76	-18.24	62.00	33.20	0.22	10.34	QP
10	0.243	23.16	-28.84	52.00	12.60	0.22	10.34	Average
11	0.260	45.75	-15.67	61.42	35.20	0.22	10.33	QP
12	0.260	25.75	-25.67	51.42	15.20	0.22	10.33	Average
13	0.277	44.74	-16.16	60.90	34.20	0.22	10.32	QP
14	0.277	25.74	-25.16	50.90	15.20	0.22	10.32	Average
15	0.329	41.32	-18.17	59.49	30.80	0.23	10.29	QP
16	0.329	22.72	-26.77	49.49	12.20	0.23	10.29	Average
17	0.389	39.30	-18.78	58.08	28.80	0.23	10.27	QP



Test Engineer :	Amos Zhang	Temperature :	23.3~24.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line



Site : CO01-KS  
 Condition : FCC PART 15C LISN-L-181013-060103 LINE  
 Project : (FR) 8D2801  
 mode : Mode 2  
 : 352156100009624 #4


Freq	Level	Over	Limit	Read	LISN	Cable	Remark
MHz	dBuV	Limit	Line	Level	Factor	Loss	
		dB	dBuV	dBuV	dB	dB	
18	0.389	24.40	-23.68	48.08	13.90	0.23	10.27 Average
19 *	13.560	67.01	7.01	60.00	56.30	0.33	10.38 QP
20 *	13.560	63.81	13.81	50.00	53.10	0.33	10.38 Average

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	Amos Zhang	Temperature :	23.3~24.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral




Site : CO01-KS  
 Condition : FCC PART 15C LISN-N-181013-060103 NEUTRAL  
 Project : (FR) 8D2801  
 mode : Mode 2  
 : 352156100009624 #4

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.153	55.58	-10.24	65.82	44.90	0.21	10.47	QP
2	0.153	36.98	-18.84	55.82	26.30	0.21	10.47	Average
3	0.162	51.86	-13.52	65.38	41.20	0.21	10.45	QP
4	0.162	30.96	-24.42	55.38	20.30	0.21	10.45	Average
5	0.173	51.73	-13.08	64.81	41.10	0.21	10.42	QP
6	0.173	30.23	-24.58	54.81	19.60	0.21	10.42	Average
7	0.199	56.87	-6.80	63.67	46.30	0.20	10.37	QP
8	0.199	38.87	-14.80	53.67	28.30	0.20	10.37	Average
9	0.207	56.06	-7.26	63.32	45.50	0.20	10.36	QP
10	0.207	37.16	-16.16	53.32	26.60	0.20	10.36	Average
11	0.223	48.35	-14.35	62.70	37.80	0.20	10.35	QP
12	0.223	26.45	-26.25	52.70	15.90	0.20	10.35	Average
13	0.244	47.13	-14.82	61.95	36.59	0.20	10.34	QP
14	0.244	25.03	-26.92	51.95	14.49	0.20	10.34	Average
15	0.273	47.82	-13.21	61.03	37.30	0.20	10.32	QP
16	0.273	30.82	-20.21	51.03	20.30	0.20	10.32	Average
17	0.294	42.11	-18.30	60.41	31.60	0.20	10.31	QP





Test Engineer :	Amos Zhang	Temperature :	23.3~24.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS  
 Condition : FCC PART 15C LISN-N-181013-060103 NEUTRAL  
 Project : (FR) 8D2801  
 mode : Mode 2  
 : 352156100009624 #4


Freq	Level	Over	Limit	Read	LISN	Cable	Loss	Remark
MHz	dBuV	Limit	Line	Level	Factor	Loss	dB	
18	0.294	21.71	-28.70	50.41	11.20	0.20	10.31	Average
19	0.330	42.69	-16.75	59.44	32.21	0.19	10.29	QP
20	0.330	24.29	-25.15	49.44	13.81	0.19	10.29	Average
21	0.389	41.06	-17.02	58.08	30.60	0.19	10.27	QP
22	0.389	22.66	-25.42	48.08	12.20	0.19	10.27	Average
23	0.440	41.64	-15.43	57.07	31.20	0.19	10.25	QP
24	0.440	23.94	-23.13	47.07	13.50	0.19	10.25	Average
25	0.524	38.63	-17.37	56.00	28.20	0.19	10.24	QP
26	0.524	21.73	-24.27	46.00	11.30	0.19	10.24	Average
27	0.595	36.73	-19.27	56.00	26.29	0.20	10.24	QP
28	0.595	22.03	-23.97	46.00	11.59	0.20	10.24	Average
29 *	13.560	67.84	7.84	60.00	57.20	0.26	10.38	QP
30 *	13.560	63.24	13.24	50.00	52.60	0.26	10.38	Average

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	Amos Zhang	Temperature :	23.3~24.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line



Site : CO01-KS  
 Condition : FCC PART 15C LISN-L-181013-060103 LINE  
 Project : (FR) 8D2801  
 mode : Mode 2  
 : 352156100009624 #4


	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	13.560	52.21	-7.79	60.00	41.50	0.33	10.38	QP
2 *	13.560	46.31	-3.69	50.00	35.60	0.33	10.38	Average

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.



Test Engineer :	Amos Zhang	Temperature :	23.3~24.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS  
 Condition : FCC PART 15C LISN-N-181013-060103 NEUTRAL  
 Project : (FR) 8D2801  
 mode : Mode 2  
 : 352156100009624 #4

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	13.560	52.24	-7.76	60.00	41.60	0.26	10.38	QP
2 *	13.560	45.24	-4.76	50.00	34.60	0.26	10.38	Average

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.



## Appendix B. Test Results of Conducted Test Items

### B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56																																																																
<table border="1"> <thead> <tr> <th>Marker</th> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td></td> <td>13.559711 MHz</td> <td>-21.08 dBm</td> <td>ndB down</td> <td>2.504 kHz</td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td></td> <td>13.558466 MHz</td> <td>-41.17 dBm</td> <td>ndB</td> <td>20.00 dB</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td></td> <td>13.56097 MHz</td> <td>-41.32 dBm</td> <td>Q factor</td> <td>5416.0</td> </tr> </tbody> </table>		Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1			13.559711 MHz	-21.08 dBm	ndB down	2.504 kHz	T1	1			13.558466 MHz	-41.17 dBm	ndB	20.00 dB	T2	1			13.56097 MHz	-41.32 dBm	Q factor	5416.0	<table border="1"> <thead> <tr> <th>Marker</th> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td></td> <td>13.559711 MHz</td> <td>-24.06 dBm</td> <td></td> <td></td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td></td> <td>13.5586541 MHz</td> <td>-38.04 dBm</td> <td>Occ Bw</td> <td>2.112879884 kHz</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td></td> <td>13.560767 MHz</td> <td>-37.89 dBm</td> <td></td> <td></td> </tr> </tbody> </table>		Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1			13.559711 MHz	-24.06 dBm			T1	1			13.5586541 MHz	-38.04 dBm	Occ Bw	2.112879884 kHz	T2	1			13.560767 MHz	-37.89 dBm		
Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																												
M1	1			13.559711 MHz	-21.08 dBm	ndB down	2.504 kHz																																																												
T1	1			13.558466 MHz	-41.17 dBm	ndB	20.00 dB																																																												
T2	1			13.56097 MHz	-41.32 dBm	Q factor	5416.0																																																												
Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																												
M1	1			13.559711 MHz	-24.06 dBm																																																														
T1	1			13.5586541 MHz	-38.04 dBm	Occ Bw	2.112879884 kHz																																																												
T2	1			13.560767 MHz	-37.89 dBm																																																														
<b>20dB Bandwidth (kHz)</b>	2.504	<b>99% OccupiedBW(kHz)</b>	2.113																																																																
<b>Frequency range (MHz)</b>	$f_L > 13.553$	13.55847	<b>Test Result</b>																																																																
	$f_H < 13.567$	13.56097	<b>Complies</b>																																																																

**Remark:** Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.




**B2. Test Result of Frequency Stability**

<b>B3. Voltage vs. Frequency Stability</b>		<b>Temperature vs. Frequency Stability</b>	
<b>Voltage (Vac)</b>	<b>Measurement Frequency (MHz)</b>	<b>Temperature (°C)</b>	<b>Measurement Frequency (MHz)</b>
120	13.559704	-20	13.559711
102	13.559704	-10	13.559711
138	13.559704	0	13.559704
		10	13.559704
		20	13.559704
		30	13.559711
		40	13.559718
		50	13.559711
<b>Max.Deviation (MHz)</b>	-0.000296	<b>Max.Deviation (MHz)</b>	-0.000296
<b>Max.Deviation (ppm)</b>	-21.8658	<b>Max.Deviation (ppm)</b>	-21.8658
<b>Limit</b>	<b>FS &lt; ±100 ppm</b>	<b>Limit</b>	<b>FS &lt; ±100 ppm</b>
<b>Test Result</b>	<b>PASS</b>	<b>Test Result</b>	<b>PASS</b>



# Appendix C. Test Results of Radiated Test Items

## C1. Test Result of Field Strength of Fundamental Emissions





C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :		NFC Tx			Polarization :		Horizontal		
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.01915	58.56	-63.4	121.96	37.95	20.6	0.01	-	-	Average
0.05003	50.1	-63.51	113.61	29.69	20.4	0.01	-	-	Average
0.0716	54.07	-56.43	110.5	33.71	20.35	0.01	-	-	Average
1.484	50.06	-14.11	64.17	30.28	19.75	0.03	-	-	QP
1.815	55.73	-13.81	69.54	35.92	19.78	0.03	-	-	QP
2.726	55.83	-13.71	69.54	35.99	19.8	0.04	-	-	QP

Test Mode :		NFC Tx			Polarization :		Vertical		
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.01915	59.88	-62.08	121.96	39.27	20.6	0.01	-	-	Average
0.05003	48.17	-65.44	113.61	27.76	20.4	0.01	-	-	Average
0.0716	54.55	-55.95	110.5	34.19	20.35	0.01	-	-	Average
1.501	50.24	-13.83	64.07	30.46	19.75	0.03	-	-	QP
1.819	57.63	-11.91	69.54	37.82	19.78	0.03	-	-	QP
2.738	57.46	-12.08	69.54	37.62	19.8	0.04	-	-	QP

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
3. Limit line = specific limits (dBμV) + distance extrapolation factor.



C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :		NFC Tx			Polarization :		Horizontal			
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
30.97	22.39	-17.61	40	30.89	23.52	0.58	32.6	-	-	Peak
104.69	21.08	-22.42	43.5	35.02	17.21	1.04	32.19	-	-	Peak
330.7	24.18	-21.82	46	34.07	19.98	1.91	31.78	-	-	Peak
646.92	24.99	-21.01	46	29.23	24.74	2.73	31.71	-	-	Peak
742.95	27.24	-18.76	46	30.7	25.41	2.93	31.8	-	-	Peak
898.15	28.71	-17.29	46	30.59	26.49	3.23	31.6	100	0	Peak

Test Mode :		NFC Tx			Polarization :		Vertical			
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
41.64	32.72	-7.28	40	47.06	17.5	0.62	32.46	100	0	Peak
75.59	25.92	-14.08	40	44.67	12.7	0.87	32.32	-	-	Peak
130.88	23.29	-20.21	43.5	36.56	17.7	1.17	32.14	-	-	Peak
551.86	25	-21	46	30.12	24.07	2.51	31.7	-	-	Peak
705.12	26.33	-19.67	46	30.35	24.96	2.82	31.8	-	-	Peak
854.5	27.45	-18.55	46	29.71	26.32	3.11	31.69	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.