



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT1970-3
FCC ID : IHDT56XT2
STANDARD : 47 CFR Part 2, 22(H), 27(M)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Dec. 20, 2018 and completely tested on Mar. 18, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China



TABLE OF CONTENTS

REVISION HISTORY.....3
SUMMARY OF TEST RESULT4
1 GENERAL DESCRIPTION5
1.1 Applicant5
1.2 Manufacturer5
1.3 Product Feature of Equipment Under Test.....5
1.4 Product Specification of Equipment Under Test.....6
1.5 Modification of EUT6
1.6 Re-use of Measured Data6
1.7 Specification of Accessory.....7
1.8 Maximum EIRP Power, Frequency Tolerance, and Emission Designator9
1.9 Testing Location 10
1.10 Applicable Standards..... 10
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 11
2.1 Test Mode 11
2.2 Connection Diagram of Test System..... 12
2.3 Support Unit used in test configuration and system 12
2.4 Measurement Results Explanation Example..... 12
2.5 Frequency List of Low/Middle/High Channels 13
3 CONDUCTED TEST ITEMS 14
3.1 Measuring Instruments 14
3.2 Test Setup 14
3.3 Test Result of Conducted Test 14
3.4 Conducted Output Power and EIRP 15
3.5 Peak-to-Average Ratio 16
3.6 Occupied Bandwidth..... 17
3.7 Conducted Band Edge 18
3.8 Conducted Spurious Emission 19
3.9 Frequency Stability 20
4 RADIATED TEST ITEMS 21
4.1 Measuring Instruments 21
4.2 Test Setup 21
4.3 Test Result of Radiated Test 21
4.4 Radiated Spurious Emission 22
5 LIST OF MEASURING EQUIPMENT 23
6 UNCERTAINTY OF EVALUATION 24
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS
APPENDIX D. REFERENCE REPORT



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG8D2002-01B	Rev. 01	Initial issue of report	Mar. 18, 2019



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 38) (Band 41)	EIRP < 2Watt	PASS	-
3.5	N/A	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§27.53(m)(4)	Conducted Band Edge Measurement (Band 38) (Band 41)	§27.53(m)(4)	PASS	-
3.8	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 38) (Band 41)	< 55+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 38) (Band 41)	< 55+10log ₁₀ (P[Watts])	PASS	Under limit 27.29 dB at 7760.000 MHz



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1970-3
FCC ID	IHDT56XT2
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR / EDR / LE NFC/GNSS/FM Receiver
IMEI Code	Conducted: 352172100009431/352172100009449 Radiation: 352172100008615/352172100008601
HW Version	DVT2
SW Version	PSA29.76
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT sample 1 and sample 2, the differences between two samples are only for SIM slot, According to the difference, we only choose dual SIM sample to perform full tests.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz LTE Band 41 : 2537.5 MHz ~ 2652.5 MHz
Rx Frequency	LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz LTE Band 41 : 2537.5 MHz ~ 2652.5 MHz
Bandwidth	LTE Band 38 : 5MHz / 10MHz / 15MHz / 20MHz LTE Band 41 : 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 38 : 22.98 dBm LTE Band 41 : 23.20 dBm
Antenna Gain	LTE Band 38 : -1.44 dBi LTE Band 41 : -1.44 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Re-use of Measured Data

1.6.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: XT1970-3, FCC ID: IHDT56XT2) is electrically identical to the reference device (Model: XT1970-1, XT1970-2, FCC ID: IHDT56XT1) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 484596 D01.

1.6.2 Difference Section

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., please refer to the Product Equality Declaration.

The re-used RF data includes the following bands provided in Appendix D (Sporton RF Report No. FG8D2002B for the reference device Model: XT1970-1, XT1970-2, FCC ID: IHDT56XT1).

1.6.3 Reference detail Section:

Equipment Class	Reference FCC ID	Folder Test	Report Title/Section
PCE (2G/3G)	IHDT56XT1	Part22H.24E.27L(FG8D2002A)	All sections applicable for GSM850/1900 and WCDMA Band V
PCE (LTE)	IHDT56XT1	Part22H.24E.27L.27M (FG8D2002B)	All sections applicable for LTE Band 5/7



1.6.4 Spot Check Verification Data Section

In order to confirm hardware similarity of the subject device with the reference device, spot check measurements were performed on the subject device for the radiated spurious emission, the test result were consistent with FCC ID: IHDT56XT1 and LTE Band 41 to full test, LTE Band 38 is covered by the Band 41.

Assertions concerning the similarity of these devices are based on representations by the applicant. The applicant accepts full responsibility for the validity of the similarity claim, and for the determination that verification test data are sufficient to support it.

Test Item	Mode	IHDT56XT1 Worst Result	IHDT56XT2 Worst Result	Difference (dB)
Radiated Spurious Emission (Harmonic) (dBm)	GSM 850	-41.72	-45.05	3.33
	PCS 1900	-42.54	-44.05	1.51
	LTE Band 7 - BW 20M	-56.71	-54.99	1.72

1.7 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola (Salom)	Model Name	SC-51
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 1(EU)	Brand Name	Motorola (Salom)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 1(UK)	Brand Name	Motorola (Salom)	Model Name	SC-53
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 1(IN)	Brand Name	Motorola (Salom)	Model Name	SC-54
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 1(AU)	Brand Name	Motorola (Salom)	Model Name	SC-55
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 1(AR)	Brand Name	Motorola (Salom)	Model Name	SC-56
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 1(BR)	Brand Name	Motorola (Salom)	Model Name	SC-57
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 1(PRC)	Brand Name	Motorola (Salom)	Model Name	SC-58
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 1 (Chile)	Brand Name	Motorola (Salom)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 2(US)	Brand Name	Motorola (Chenyang)	Model Name	SC-51
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		



AC Adapter 2(EU)	Brand Name	Motorola (Chenyang)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 2(UK)	Brand Name	Motorola (Chenyang)	Model Name	SC-53
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 2(AU)	Brand Name	Motorola (Chenyang)	Model Name	SC-55
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 2(AR)	Brand Name	Motorola (Chenyang)	Model Name	SC-56
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
AC Adapter 2(PRC)	Brand Name	Motorola (Chenyang)	Model Name	SC-58
	Power Rating	I/P: 100-240 Vac, 600mA O/P: 5Vdc,3000mA; 9Vdc,2000mA; 12Vdc,1500mA		
Battery	Brand Name	Motorola (ATL)	Model Name	KR40
	Power Rating	3.8Vdc,3500mAh	Type	Li-ion, Polymer
Earphone 1	Brand Name	Motorola (Lyand)	Model Name	SH38C37773
	Signal Line Type	1.1 meter, non-shielded cable, without ferrite core		
Earphone 2	Brand Name	Motorola (jiahe)	Model Name	SH38C44959
	Signal Line Type	1.1 meter, non-shielded cable, without ferrite core		
USB Cable 1	Brand Name	Motorola (LiQi)	Model Name	L32B-053000100/L32B-053000100L
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 2	Brand Name	Motorola (Saibao)	Model Name	S32B-053000100/S32B-053000100L
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		



1.8 Maximum EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 38		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2572.5 ~ 2617.5	4M56G7D	-	0.1472	4M53W7D	-	0.1233
10	2575.0 ~ 2615.0	9M11G7D	0.0020	0.1472	9M03W7D	-	0.1265
15	2577.5 ~ 2612.5	13M5G7D	-	0.1486	13M7W7D	-	0.1230
20	2580.0 ~ 2610.0	18M6G7D	-	0.1500	18M5W7D	-	0.1222
LTE Band 38		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)	Maximum EIRP(W)		
5	2572.5 ~ 2617.5	4M51W7D		-	0.0995		
10	2575.0 ~ 2615.0	9M07W7D		-	0.0989		
15	2577.5 ~ 2612.5	13M5W7D		-	0.0971		
20	2580.0 ~ 2610.0	18M4W7D		-	0.0964		
LTE Band 41		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2537.5 ~ 2652.5	4M56G7D	-	0.1472	4M53W7D	-	0.1233
10	2540.0 ~ 2650.0	9M11G7D	0.0020	0.1472	9M03W7D	-	0.1265
15	2542.5 ~ 2647.5	13M5G7D	-	0.1486	13M7W7D	-	0.1230
20	2545.0 ~ 2645.0	18M6G7D	-	0.1500	18M5W7D	-	0.1222
LTE Band 41		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)	Maximum EIRP(W)		
5	2537.5 ~ 2652.5	4M51W7D		-	0.0995		
10	2540.0 ~ 2650.0	9M07W7D		-	0.0989		
15	2542.5 ~ 2647.5	13M5W7D		-	0.0971		
20	2545.0 ~ 2645.0	18M4W7D		-	0.0964		

Note: LTE Band 41 overlaps the entire frequency range of LTE Band 38. Therefore, the test results provided in this report covers Band 41 as well as Band 38.



1.9 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	TH01-KS 03CH06-KS	CN5013	630927

1.10 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 27(M)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel			
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H	
Max. Output Power	38	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v	
	41	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v	
Peak-to-Average Ratio	41	-	-				v	v	v	v	v		v	v	v	v	
26dB and 99% Bandwidth	41	-	-	v	v	v	v	v	v	v			v	v	v	v	
Conducted Band Edge	41	-	-	v	v	v	v	v	v	v	v		v	v		v	
Conducted Spurious Emission	41	-	-	v	v	v	v	v	v	v	v			v	v	v	
Frequency Stability	41	-	-		v			v					v		v		
E.I.R.P	41	-	-	v	v	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	41	Worst Case												v			
Note	<ol style="list-style-type: none"> The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.7 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 5.7 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 38 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	37850	38000	38150
	Frequency	2580	2595	2610
15	Channel	37825	38000	38175
	Frequency	2577.5	2595	2612.5
10	Channel	37800	38000	38200
	Frequency	2575	2595	2615
5	Channel	37775	38000	38225
	Frequency	2572.5	2595	2617.5

LTE Band 41 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	40140	40640	41140
	Frequency	2545	2595	2645
15	Channel	40115	40640	41165
	Frequency	2542.5	2595	2647.5
10	Channel	40090	40640	41190
	Frequency	2540	2595	2650
5	Channel	40065	40640	41215
	Frequency	2537.5	2595	2652.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and EIRP

3.4.1 Description of the Conducted Output Power Measurement and EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 41.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. Offset has included the duty factor for LTE Band 41. Duty factor $= 10 \log (1/x)$, where x is the measured duty cycle.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10 \log (P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10 \log (P)]$ (dB)
 $= [30 + 10 \log (P)]$ (dBm) - $[43 + 10 \log (P)]$ (dB) = -13dBm.

10. For LTE Band 41, the other 40 dB, and 55 dB have additionally applied same calculation above.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 41:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. Offset has included the duty factor for LTE Band 41. Duty factor = $10 \log (1/x)$, where x is the measured duty cycle
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. For Band 41

The limit line is derived from $55 + 10 \log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [55 + 10 \log(P)]$ (dB)
= $[30 + 10 \log(P)]$ (dBm) - $[55 + 10 \log(P)]$ (dB)
= -25dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 41

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
11. $ERP (dBm) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] (dB)$
 $= [30 + 10\log(P)] (dBm) - [43 + 10\log(P)] (dB)$
 $= -13dBm.$

13. For Band 41:

The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	100319	9kHz~40GHz	Oct. 11, 2018	Mar. 15, 2019~ Mar. 18, 2019	Oct. 10, 2019	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jun. 27, 2018	Mar. 15, 2019~ Mar. 18, 2019	Jun. 26, 2019	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471084	10Hz-44GHz	Oct. 09, 2018	Feb. 24, 2019	Oct. 08, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Apr. 19, 2018	Feb. 24, 2019	Apr. 18, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 20, 2018	Feb. 24, 2019	Oct. 19, 2019	Radiation (03CH06-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Jan. 05, 2019	Feb. 24, 2019	Jan. 04, 2020	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2018	Feb. 24, 2019	Aug. 05, 2019	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jan. 14, 2019	Feb. 24, 2019	Jan. 13, 2020	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Apr. 17, 2018	Feb. 24, 2019	Apr. 16, 2019	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 18, 2018	Feb. 24, 2019	Apr. 17, 2019	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 24, 2019	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 24, 2019	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 24, 2019	NCR	Radiation (03CH06-KS)

NCR: No Calibration Required



6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.0dB
---	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.88	22.98	22.91
20	1	49		22.90	22.92	22.93
20	1	99		22.80	22.97	22.93
20	50	0		21.77	21.84	21.86
20	50	24		21.76	21.84	21.86
20	50	50		21.80	21.86	21.86
20	100	0		21.77	21.85	21.85
20	1	0	16-QAM	21.66	21.92	21.89
20	1	49		21.69	21.93	21.88
20	1	99		21.66	21.98	21.86
20	50	0		20.85	20.89	20.87
20	50	24		20.85	20.88	20.88
20	50	50		20.88	20.91	20.89
20	100	0		20.87	20.92	20.91
20	1	0	64QAM	20.78	20.76	20.75
20	1	49		20.80	20.77	20.73
20	1	99		20.89	20.78	20.75
20	50	0		20.00	20.04	20.04
20	50	24		20.02	20.05	20.07
20	50	50		20.03	20.08	20.03
20	100	0		20.05	20.09	20.02
15	1	0	QPSK	22.88	22.88	22.84
15	1	37		22.84	22.87	22.84
15	1	74		22.89	22.94	22.83
15	36	0		21.83	21.81	21.82
15	36	20		21.83	21.83	21.80
15	36	39		21.85	21.84	21.79
15	75	0		21.83	21.82	21.80
15	1	0	16-QAM	21.73	21.74	21.88



15	1	37		21.75	21.74	21.86
15	1	74		21.78	21.77	21.87
15	36	0		20.84	20.86	20.81
15	36	20		20.85	20.87	20.82
15	36	39		20.85	20.86	20.82
15	75	0		20.92	20.91	20.89
15	1	0	64QAM	20.86	20.84	20.87
15	1	37		20.81	20.83	20.73
15	1	74		20.88	20.80	20.98
15	36	0		20.03	19.94	20.01
15	36	20		20.04	20.00	20.00
15	36	39		20.03	20.06	19.94
15	75	0		20.05	20.03	19.95



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.84	22.91	22.93
10	1	25		22.84	22.90	22.93
10	1	49		22.84	22.97	22.92
10	25	0		21.77	21.81	21.83
10	25	12		21.77	21.81	21.82
10	25	25		21.76	21.82	21.83
10	50	0		21.76	21.82	21.83
10	1	0	16-QAM	21.85	21.86	21.80
10	1	25		21.84	21.84	21.82
10	1	49		21.85	21.83	21.76
10	25	0		20.91	20.91	20.93
10	25	12		20.90	20.92	20.92
10	25	25		20.89	20.93	20.94
10	50	0		20.84	20.88	20.89
10	1	0	64QAM	20.76	20.76	20.82
10	1	25		20.75	20.75	20.83
10	1	49		20.74	20.80	20.80
10	25	0		19.98	20.01	20.01
10	25	12		19.97	20.03	20.03
10	25	25		19.98	20.03	20.01
10	50	0		20.04	20.06	20.04
5	1	0	QPSK	22.88	22.92	22.89
5	1	12		22.89	22.91	22.93
5	1	24		22.85	22.91	22.91
5	12	0		21.78	21.82	21.82
5	12	7		21.80	21.82	21.85
5	12	13		21.77	21.83	21.83
5	25	0		21.79	21.83	21.83
5	1	0	16-QAM	21.68	21.86	21.77
5	1	12		21.70	21.90	21.80
5	1	24		21.70	21.92	21.81
5	12	0		20.80	20.86	20.83
5	12	7		20.83	20.85	20.82



5	12	13		20.82	20.85	20.84
5	25	0		20.94	20.95	20.94
5	1	0	64QAM	20.82	20.85	20.85
5	1	12		20.87	20.82	20.87
5	1	24		20.83	20.86	20.89
5	12	0		19.95	19.98	19.96
5	12	7		19.94	19.97	19.96
5	12	13		19.94	19.97	19.94
5	25	0		19.99	20.01	20.02



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.64	22.97	23.20
20	1	49		22.68	23.17	22.96
20	1	99		22.72	23.02	22.98
20	50	0		21.59	22.17	22.00
20	50	24		21.58	22.25	21.91
20	50	50		21.60	22.19	21.92
20	100	0		21.61	22.16	21.92
20	1	0	16-QAM	21.70	22.31	22.14
20	1	49		21.73	22.31	22.13
20	1	99		21.73	22.29	22.14
20	50	0		20.66	21.16	20.98
20	50	24		20.64	21.23	20.97
20	50	50		20.65	21.20	20.96
20	100	0		20.71	21.15	20.98
20	1	0	64QAM	20.80	21.18	21.23
20	1	49		20.80	21.28	21.21
20	1	99		20.82	21.23	21.22
20	50	0		20.04	20.15	20.34
20	50	24		20.11	20.25	20.34
20	50	50		19.93	20.19	20.31
20	100	0		20.03	20.14	20.33
15	1	0	QPSK	22.61	22.93	23.02
15	1	37		22.59	23.16	22.97
15	1	74		22.62	22.91	22.97
15	36	0		21.59	22.09	21.98
15	36	20		21.59	22.22	21.97
15	36	39		21.58	22.20	21.95
15	75	0		21.59	22.13	21.96
15	1	0	16-QAM	21.62	22.11	22.29
15	1	37		21.63	22.34	22.23
15	1	74		21.69	22.18	22.26
15	36	0		20.64	21.08	21.00
15	36	20		20.64	21.22	20.99



15	36	39	64QAM	20.65	21.20	20.98
15	75	0		20.68	21.12	21.02
15	1	0		20.91	21.07	21.09
15	1	37		20.92	21.31	21.12
15	1	74		20.89	21.10	21.07
15	36	0		20.02	20.12	20.35
15	36	20		20.01	20.23	20.38
15	36	39		20.01	20.24	20.37
15	75	0		19.98	20.13	20.38



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.79	22.88	23.12
10	1	25		22.81	23.10	23.10
10	1	49		22.90	23.01	23.04
10	25	0		21.73	22.08	22.09
10	25	12		21.71	22.21	22.08
10	25	25		21.71	22.21	22.07
10	50	0		21.72	22.16	22.08
10	1	0	16-QAM	21.95	22.10	22.29
10	1	25		21.96	22.46	22.29
10	1	49		22.05	22.25	22.26
10	25	0		20.85	21.12	21.17
10	25	12		20.84	21.26	21.17
10	25	25		20.83	21.24	21.16
10	50	0		20.79	21.14	21.07
10	1	0	64QAM	20.95	21.09	21.35
10	1	25		21.01	21.39	21.32
10	1	49		20.96	21.20	21.33
10	25	0		20.13	20.11	20.45
10	25	12		20.10	20.23	20.44
10	25	25		20.13	20.22	20.45
10	50	0		20.14	20.17	20.47
5	1	0	QPSK	22.80	22.91	23.12
5	1	12		22.81	23.12	23.11
5	1	24		22.77	23.09	22.73
5	12	0		21.75	22.95	21.90
5	12	7		21.69	23.05	22.09
5	12	13		21.73	23.11	22.11
5	25	0		21.73	22.18	22.10
5	1	0	16-QAM	21.61	22.14	22.21
5	1	12		21.61	22.35	22.23
5	1	24		21.62	22.29	22.20
5	12	0		20.75	22.02	21.10
5	12	7		20.76	22.06	21.10



5	12	13	64QAM	20.74	22.11	21.08
5	25	0		20.87	21.23	21.17
5	1	0		21.00	21.08	21.42
5	1	12		21.06	21.27	21.38
5	1	24		21.01	21.23	21.39
5	12	0		20.05	21.13	20.40
5	12	7		20.07	21.21	20.40
5	12	13		20.06	21.28	20.40
5	25	0		20.12	20.18	20.45



EIRP

LTE Band 41 (G _T - L _C = -1.44 dB) QPSK									
Bandwidth	5M			10M			15M		
Channel	40065	40640	41215	40090	40640	41190	40115	40640	41165
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	2537.5	2595	2652.5	2540	2595	2650	2542.5	2595	2647.5
Conducted Power (dBm)	22.81	23.12	23.11	22.79	22.88	23.12	22.59	23.16	22.97
Conducted Power (Watts)	0.1910	0.2051	0.2046	0.1901	0.1941	0.2051	0.1816	0.2070	0.1982
EIRP(dBm)	21.37	21.68	21.67	21.35	21.44	21.68	21.15	21.72	21.53
EIRP(Watts)	0.1371	0.1472	0.1469	0.1365	0.1393	0.1472	0.1303	0.1486	0.1422

LTE Band 41 (G _T - L _C = -1.44 dB) QPSK			
Bandwidth	20M		
Channel	40140	40640	41140
	(Low)	(Mid)	(High)
Frequency (MHz)	2545	2595	2645
Conducted Power (dBm)	22.64	22.97	23.20
Conducted Power (Watts)	0.1837	0.1982	0.2089
EIRP(dBm)	21.20	21.53	21.76
EIRP(Watts)	0.1318	0.1422	0.1500



LTE Band 41 (G _T - L _C = -1.44 dB) 16QAM									
Bandwidth	5M			10M			15M		
Channel	40065	40640	41215	40090	40640	41190	40115	40640	41165
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	2537.5	2595	2652.5	2540	2595	2650	2542.5	2595	2647.5
Conducted Power (dBm)	21.61	22.35	22.23	21.96	22.46	22.29	21.63	22.34	22.23
Conducted Power (Watts)	0.1449	0.1718	0.1671	0.1570	0.1762	0.1694	0.1455	0.1714	0.1671
EIRP(dBm)	20.17	20.91	20.79	20.52	21.02	20.85	20.19	20.90	20.79
EIRP(Watts)	0.1040	0.1233	0.1199	0.1127	0.1265	0.1216	0.1045	0.1230	0.1199

LTE Band 41 (G _T - L _C = -1.44dB) 16QAM			
Bandwidth	20M		
Channel	40140	40640	41140
	(Low)	(Mid)	(High)
Frequency (MHz)	2545	2595	2645
Conducted Power (dBm)	21.73	22.31	22.13
Conducted Power (Watts)	0.1489	0.1702	0.1633
EIRP(dBm)	20.29	20.87	20.69
EIRP(Watts)	0.1069	0.1222	0.1172



LTE Band 41 (G _T - L _C = -1.44 dB) 64QAM									
Bandwidth	5M			10M			15M		
Channel	40065	40640	41215	40090	40640	41190	40115	40640	41165
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	2537.5	2595	2652.5	2540	2595	2650	2542.5	2595	2647.5
Conducted Power (dBm)	21.00	21.08	21.42	21.01	21.39	21.32	20.92	21.31	21.12
Conducted Power (Watts)	0.1259	0.1282	0.1387	0.1262	0.1377	0.1355	0.1236	0.1352	0.1294
EIRP(dBm)	19.56	19.64	19.98	19.57	19.95	19.88	19.48	19.87	19.68
EIRP(Watts)	0.0904	0.0920	0.0995	0.0906	0.0989	0.0973	0.0887	0.0971	0.0929

LTE Band 41 (G _T - L _C = -1.44 dB) 64QAM			
Bandwidth	20M		
Channel	40140	40640	41140
	(Low)	(Mid)	(High)
Frequency (MHz)	2545	2595	2645
Conducted Power (dBm)	20.80	21.28	21.21
Conducted Power (Watts)	0.1202	0.1343	0.1321
EIRP(dBm)	19.36	19.84	19.77
EIRP(Watts)	0.0863	0.0964	0.0948



Peak-to-Average Ratio

Mode	LTE Band 41 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	6.64	6.67	6.55	6.78	PASS
Middle CH	6.61	5.65	6.78	6.64	
Highest CH	6.9	6.75	6.72	6.61	
Mode	LTE Band 41 / 20MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	6.23	6.78			PASS
Middle CH	6.67	6.84			
Highest CH	6.81	6.9			




LTE Band 41 / 20MHz / QPSK

Lowest Channel / 1RB




Date: 16 MAR 2019 02:07:34

Lowest Channel / Full RB




Date: 16 MAR 2019 02:09:41

Middle Channel / 1RB



Date: 16 MAR 2019 02:12:08

Middle Channel / Full RB




Date: 16 MAR 2019 02:10:05

Highest Channel / 1RB



Date: 16 MAR 2019 02:12:35

Highest Channel / Full RB




Date: 16 MAR 2019 02:16:31




LTE Band 41 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 16 MAR 2019 02:08:12

Lowest Channel / Full RB



Date: 16 MAR 2019 02:09:28

Middle Channel / 1RB




Date: 16 MAR 2019 02:11:53

Middle Channel / Full RB



Date: 16 MAR 2019 02:10:27

Highest Channel / 1RB



Date: 16 MAR 2019 02:12:48

Highest Channel / Full RB




Date: 16 MAR 2019 02:20:44




LTE Band 41 / 20MHz / 64QAM

Lowest Channel / 1RB




Date: 16 MAR 2019 02:08:25

Lowest Channel / Full RB




Date: 16 MAR 2019 02:08:53

Middle Channel / 1RB



Date: 16 MAR 2019 02:11:31

Middle Channel / Full RB



Date: 16 MAR 2019 02:10:42

Highest Channel / 1RB



Date: 16 MAR 2019 02:21:32

Highest Channel / Full RB



Date: 16 MAR 2019 02:20:19




26dB Bandwidth

Mode	LTE Band 41 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	5.355	5.195	9.95	10.33	14.296	14.565	20.14	20.539
Middle CH	-	-	-	-	4.895	4.705	9.65	9.73	14.655	14.146	20.18	20.02
Highest CH	-	-	-	-	5.225	5.155	9.63	9.85	14.416	14.416	20.14	20.18
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH					4.845		10.05		14.266		19.94	
Middle CH					5.125		10.11		14.476		20.18	
Highest CH					4.975		9.93		14.836		19.9	




LTE Band 41

Lowest Channel / 5MHz / QPSK




Date: 15 MAR 2019 23:29:54

Lowest Channel / 5MHz / 16QAM




Date: 15 MAR 2019 23:32:06

Middle Channel / 5MHz / QPSK




Date: 15 MAR 2019 22:18:12

Middle Channel / 5MHz / 16QAM




Date: 15 MAR 2019 22:19:39

Highest Channel / 5MHz / QPSK



Date: 15 MAR 2019 22:36:19

Highest Channel / 5MHz / 16QAM




Date: 15 MAR 2019 22:36:45




LTE Band 41

Lowest Channel / 10MHz / QPSK




Date: 15 MAR 2019 23:33:52

Lowest Channel / 10MHz / 16QAM




Date: 15 MAR 2019 23:34:39

Middle Channel / 10MHz / QPSK




Date: 15 MAR 2019 22:23:13

Middle Channel / 10MHz / 16QAM




Date: 15 MAR 2019 22:22:45

Highest Channel / 10MHz / QPSK



Date: 15 MAR 2019 22:35:04

Highest Channel / 10MHz / 16QAM




Date: 15 MAR 2019 22:34:40




LTE Band 41

Lowest Channel / 15MHz / QPSK




Date: 15 MAR 2019 23:36:17

Lowest Channel / 15MHz / 16QAM




Date: 15 MAR 2019 23:37:00

Middle Channel / 15MHz / QPSK




Date: 15 MAR 2019 22:24:12

Middle Channel / 15MHz / 16QAM




Date: 15 MAR 2019 22:24:34

Highest Channel / 15MHz / QPSK



Date: 15 MAR 2019 22:30:36

Highest Channel / 15MHz / 16QAM




Date: 15 MAR 2019 22:31:05




LTE Band 41

Lowest Channel / 20MHz / QPSK




Date: 15 MAR 2019 23:38:40

Lowest Channel / 20MHz / 16QAM




Date: 15 MAR 2019 23:39:23

Middle Channel / 20MHz / QPSK




Date: 15 MAR 2019 22:25:44

Middle Channel / 20MHz / 16QAM




Date: 15 MAR 2019 22:26:07

Highest Channel / 20MHz / QPSK



Date: 15 MAR 2019 22:27:51

Highest Channel / 20MHz / 16QAM




Date: 15 MAR 2019 22:28:16




LTE Band 41

Lowest Channel / 5MHz / 64QAM




Date: 15 MAR 2019 23:32:18

Lowest Channel / 10MHz / 64QAM




Date: 15 MAR 2019 23:34:53

Middle Channel / 5MHz / 64QAM




Date: 15 MAR 2019 22:20:20

Middle Channel / 10MHz / 64QAM




Date: 15 MAR 2019 22:22:13

Highest Channel / 5MHz / 64QAM



Date: 15 MAR 2019 22:37:19

Highest Channel / 10MHz / 64QAM




Date: 15 MAR 2019 22:33:59




LTE Band 41

Lowest Channel / 15MHz / 64QAM




Date: 15 MAR 2019 23:37:13

Lowest Channel / 20MHz / 64QAM




Date: 15 MAR 2019 23:39:36

Middle Channel / 15MHz / 64QAM




Date: 15 MAR 2019 22:24:55

Middle Channel / 20MHz / 64QAM




Date: 15 MAR 2019 22:28:29

Highest Channel / 15MHz / 64QAM



Date: 15 MAR 2019 22:32:11

Highest Channel / 20MHz / 64QAM



Date: 15 MAR 2019 22:28:45




Occupied Bandwidth

Mode	LTE Band 41 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.56	4.5	9.11	8.99	13.43	13.52	18.58	18.38
Middle CH	-	-	-	-	4.55	4.53	9.05	9.03	13.49	13.46	18.42	18.46
Highest CH	-	-	-	-	4.51	4.49	9.05	9.01	13.43	13.7	18.38	18.38
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH					4.48		9.07		13.46		18.34	
Middle CH					4.51		9.03		13.46		18.22	
Highest CH					4.51		9.03		13.49		18.42	




LTE Band 41

Lowest Channel / 5MHz / QPSK




Date: 15 MAR 2019 23:30:33

Lowest Channel / 5MHz / 16QAM




Date: 15 MAR 2019 23:31:53

Middle Channel / 5MHz / QPSK




Date: 15 MAR 2019 22:18:55

Middle Channel / 5MHz / 16QAM




Date: 15 MAR 2019 22:19:25

Highest Channel / 5MHz / QPSK



Date: 15 MAR 2019 22:36:09

Highest Channel / 5MHz / 16QAM




Date: 15 MAR 2019 22:36:32




LTE Band 41

Lowest Channel / 10MHz / QPSK




Date: 15 MAR 2019 23:34:11

Lowest Channel / 10MHz / 16QAM




Date: 15 MAR 2019 23:34:25

Middle Channel / 10MHz / QPSK




Date: 15 MAR 2019 22:23:03

Middle Channel / 10MHz / 16QAM




Date: 15 MAR 2019 22:23:30

Highest Channel / 10MHz / QPSK



Date: 15 MAR 2019 22:34:53

Highest Channel / 10MHz / 16QAM



Date: 15 MAR 2019 22:34:26