



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2027-1
FCC ID : IHDT56YH1
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Aug. 15, 2019 and testing was completed on Sep. 29, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China***



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards.....	7
1.8 Specification of Accessory.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Carrier Frequency and Channel	10
2.2 Test Mode.....	11
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	13
2.6 Measurement Results Explanation Example.....	13
3 TEST RESULT	14
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	14
3.2 Maximum Conducted Output Power Measurement	17
3.3 Power Spectral Density Measurement	18
3.4 Unwanted Emissions Measurement.....	20
3.5 AC Conducted Emission Measurement.....	24
3.6 Automatically Discontinue Transmission	26
3.7 Antenna Requirements.....	27
4 LIST OF MEASURING EQUIPMENT	28
5 UNCERTAINTY OF EVALUATION.....	29
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR981517F	Rev. 01	Initial issue of report	Oct. 22, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 6.50 dB at 48.430 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 4.26 dB at 0.202 MHz
3.6	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.7	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2027-1
FCC ID	IHDT56YH1
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+(16QAM uplink is not supported) /LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR / EDR/ LE FM Receiver and GNSS
IMEI Code	Conducted: 35722510002959600 Conduction: 357226100002971 Radiation: 35722510028838/35722510028846
HW Version	DVT2
SW Version	QPF30.71
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power	<5745 MHz ~ 5825 MHz> 802.11a : 16.35 dBm / 0.0432 W 802.11n HT20 : 16.22 dBm / 0.0419 W 802.11n HT40 : 15.70 dBm / 0.0372 W 802.11ac VHT20: 16.16 dBm / 0.0413 W 802.11ac VHT40: 15.69 dBm / 0.0371 W 802.11ac VHT80: 14.43 dBm / 0.0277 W
99% Occupied Bandwidth	802.11a : 17.98 MHz 802.11n HT20 : 18.88 MHz 802.11ac VHT40 : 36.86 MHz 802.11ac VHT80 : 75.76 MHz
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Antenna Type / Gain	Loop Antenna with gain -2.30 dBi

Note: For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11n HT20/HT40 by referring to their maximum conducted power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH05-KS TH01-KS	CN1257	314309



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.8 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(Salom)	Model Name	SC-51
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(EU)	Brand Name	Motorola(Salom)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(UK)	Brand Name	Motorola(Salom)	Model Name	SC-53
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(AU)	Brand Name	Motorola(Salom)	Model Name	SC-55
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(AR)	Brand Name	Motorola(Salom)	Model Name	SC-56
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(BR)	Brand Name	Motorola(Salom)	Model Name	SC-57
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(Chile)	Brand Name	Motorola(Salom)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(BR) Local Build	Brand Name	Motorola(Flex)	Model Name	SC-57
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(US)	Brand Name	Motorola(Chenyang)	Model Name	SC-51
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(EU)	Brand Name	Motorola(Chenyang)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(UK)	Brand Name	Motorola(Chenyang)	Model Name	SC-53
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(AU)	Brand Name	Motorola(Chenyang)	Model Name	SC-55
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(AR)	Brand Name	Motorola(Chenyang)	Model Name	SC-56
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 3(BR) Cliptech Local Build	Brand Name	Motorola(Cliptech)	Model Name	SC-57
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 4(US)	Brand Name	Motorola(Chenyang)	Model Name	SC-81
	Power Rating	I/P: 100-240 Vac , 1.2A; O/P: 5/9/15/20Vdc, 4000/4000/3000/2250mA		
AC Adapter 4(EU)	Brand Name	Motorola(Chenyang)	Model Name	SC-82
	Power Rating	I/P: 100-240 Vac , 1.2A; O/P: 5/9/15/20Vdc, 4000/4000/3000/2250mA		
AC Adapter 4(BR)	Brand Name	Motorola(Chenyang)	Model Name	SC-87
	Power Rating	I/P: 100-240 Vac , 1.2A; O/P: 5/9/15/20Vdc, 4000/4000/3000/2250mA		
AC Adapter 5(AR)	Brand Name	Motorola(Salom)	Model Name	SC-36
	Power Rating	I/P: 100-240 Vac , 800mA; O/P: 5/9Vdc, 3000/3000mA		
AC Adapter 6(AR)	Brand Name	Motorola(Acbel)	Model Name	SC-36
	Power Rating	I/P: 100-240 Vac , 800mA; O/P: 5/9Vdc, 3000/3000mA		



Battery	Brand Name	Motorola(ATL)	Model Name	KG50
	Power Rating	3.8Vdc, 3790/4000mAh	Type	Li-ion; Polymer
Earphone 1	Brand Name	Motorola(Lianyun)	Model Name	SH38C37773
	Signal Line Type	1.11 meter, non-shielded cable, without ferrite core		
Earphone 2	Brand Name	Motorola (Cosonic)	Model Name	SH38C44959
	Signal Line Type	1.11 meter, non-shielded cable, without ferrite core		
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18C24367
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 2	Brand Name	Motorola(Luxshare)	Model Name	SC18C24368
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 3	Brand Name	Motorola(I SHENG)	Model Name	SC18C28955
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 4	Brand Name	Motorola(Saibao)	Model Name	SC18C57604
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link(5G) + Earphone 2 + USB Cable 2(Charging from Adapter 2)
--------------------------------------	---

Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 7.0 dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 7.0 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW \geq 1 MHz.
 - Number of points in sweep \geq 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
-
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Note: Average Power Density (dBm/500kHz) = Measured value+ Duty Factor+ 10log(500kHz/RBW) Factor

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

3.4.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW \geq 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2019	Sep. 21, 2019	Aug. 06, 2020	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 14, 2019	Sep. 21, 2019	Jan. 13, 2020	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 14, 2019	Sep. 21, 2019	Jan. 13, 2020	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 12, 2018	Sep. 29, 2019	Oct. 11, 2019	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz~44GHz	Oct. 09, 2018	Sep. 29, 2019	Oct. 08, 2019	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Sep. 29, 2019	Oct. 18, 2019	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Dec. 28, 2018	Sep. 29, 2019	Dec. 27, 2019	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 27, 2019	Sep. 29, 2019	Jan. 26, 2020	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Sep. 29, 2019	Jan. 04, 2020	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	187289	9KHz~1GHz	Aug. 06, 2019	Sep. 29, 2019	Aug. 05, 2020	Radiation (03CH05-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jan. 14, 2019	Sep. 29, 2019	Jan. 13, 2020	Radiation (03CH05-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz~18Ghz	Aug. 17, 2019	Sep. 29, 2019	Aug. 16, 2020	Radiation (03CH05-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5GHz	Dec. 22, 2018	Sep. 29, 2019	Dec. 21, 2019	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Sep. 29, 2019	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Sep. 29, 2019	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Sep. 29, 2019	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2019	Sep. 26, 2019	Apr. 15, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Sep. 26, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Sep. 26, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Sep. 26, 2019	Oct. 11, 2019	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------



Appendix A. Conducted Test Results

Test Engineer:	Lion Ran	Temperature:	21~25	°C
Test Date:	2019/9/21	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	17.98	24.48	16.02	0.5	Pass
11a	6Mbps	1	157	5785	17.83	24.28	15.46	0.5	Pass
11a	6Mbps	1	165	5825	17.53	23.83	15.78	0.5	Pass
HT20	MCS 0	1	149	5745	18.88	25.03	16.82	0.5	Pass
HT20	MCS 0	1	157	5785	18.73	24.88	16.68	0.5	Pass
HT20	MCS 0	1	165	5825	18.78	25.08	16.56	0.5	Pass
HT40	MCS 0	1	151	5755	36.86	42.17	36.16	0.5	Pass
HT40	MCS 0	1	159	5795	36.56	41.81	35.48	0.5	Pass
VHT80	MCS 0	1	155	5775	75.76	83.44	75.12	0.5	Pass

TEST RESULTS DATA
Average Power Table


Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.08	16.11	30.00	-2.30		Pass
11a	6Mbps	1	157	5785	0.08	16.35	30.00	-2.30		Pass
11a	6Mbps	1	165	5825	0.08	16.12	30.00	-2.30		Pass
HT20	MCS 0	1	149	5745	0.08	15.93	30.00	-2.30		Pass
HT20	MCS 0	1	157	5785	0.08	16.22	30.00	-2.30		Pass
HT20	MCS 0	1	165	5825	0.08	15.96	30.00	-2.30		Pass
HT40	MCS 0	1	151	5755	0.16	15.65	30.00	-2.30		Pass
HT40	MCS 0	1	159	5795	0.16	15.70	30.00	-2.30		Pass
VHT20	MCS 0	1	149	5745	0.08	15.91	30.00	-2.30		Pass
VHT20	MCS 0	1	157	5785	0.08	16.16	30.00	-2.30		Pass
VHT20	MCS 0	1	165	5825	0.08	15.97	30.00	-2.30		Pass
VHT40	MCS 0	1	151	5755	0.16	15.62	30.00	-2.30		Pass
VHT40	MCS 0	1	159	5795	0.16	15.69	30.00	-2.30		Pass
VHT80	MCS 0	1	155	5775	0.30	14.43	30.00	-2.30		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.08	2.22	2.55	30.00	-2.30	Pass
11a	6Mbps	1	157	5785	0.08	2.22	3.23	30.00	-2.30	Pass
11a	6Mbps	1	165	5825	0.08	2.22	3.30	30.00	-2.30	Pass
HT20	MCS 0	1	149	5745	0.08	2.22	2.18	30.00	-2.30	Pass
HT20	MCS 0	1	157	5785	0.08	2.22	2.74	30.00	-2.30	Pass
HT20	MCS 0	1	165	5825	0.08	2.22	2.90	30.00	-2.30	Pass
HT40	MCS 0	1	151	5755	0.16	2.22	2.38	30.00	-2.30	Pass
HT40	MCS 0	1	159	5795	0.16	2.22	2.38	30.00	-2.30	Pass
VHT80	MCS 0	1	155	5775	0.30	2.22	-4.76	30.00	-2.30	Pass




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Amos Zhang	Temperature :	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15E LISN-N-181119-060105 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.152	53.26	-12.65	65.91	42.60	0.18	10.48	QP
2	0.152	39.96	-15.95	55.91	29.30	0.18	10.48	Average
3	0.187	48.77	-15.38	64.15	38.21	0.17	10.39	QP
4	0.187	28.07	-26.08	54.15	17.51	0.17	10.39	Average
5 *	0.201	54.74	-8.84	63.58	44.21	0.17	10.36	QP
6	0.201	36.84	-16.74	53.58	26.31	0.17	10.36	Average
7	0.214	49.03	-14.02	63.05	38.51	0.17	10.35	QP
8	0.214	28.03	-25.02	53.05	17.51	0.17	10.35	Average
9	0.272	47.39	-13.68	61.07	36.91	0.16	10.32	QP
10	0.272	29.09	-21.98	51.07	18.61	0.16	10.32	Average
11	0.334	42.75	-16.60	59.35	32.30	0.16	10.29	QP
12	0.334	25.55	-23.80	49.35	15.10	0.16	10.29	Average
13	17.661	40.77	-19.23	60.00	30.21	0.11	10.45	QP
14	17.661	29.87	-20.13	50.00	19.31	0.11	10.45	Average



Appendix C. Radiated Spurious Emission

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5639.6	54.38	-13.92	68.3	41.47	35.3	8.55	30.94	113	117	P	H
		5689.6	61.57	-36.06	97.63	48.75	35.25	8.58	31.01	113	117	P	H
		5715.6	69.59	-40.08	109.67	56.77	35.24	8.61	31.03	113	117	P	H
		5724	73.53	-46.49	120.02	60.75	35.22	8.61	31.05	113	117	P	H
		5746	114.14	-	-	101.36	35.21	8.64	31.07	113	117	P	H
		5746	104.94	-	-	92.16	35.21	8.64	31.07	113	117	A	H
		5636	53.67	-14.63	68.3	40.76	35.3	8.55	30.94	282	95	P	V
		5699.6	55.09	-49.92	105.01	42.24	35.25	8.61	31.01	282	95	P	V
		5717.2	60.64	-49.48	110.12	47.82	35.24	8.61	31.03	282	95	P	V
		5724.4	67.15	-53.78	120.93	54.37	35.22	8.61	31.05	282	95	P	V
		5746	105.24	-	-	92.46	35.21	8.64	31.07	282	95	P	V
		5746	98.04	-	-	85.26	35.21	8.64	31.07	282	95	A	V
802.11a CH 165 5825MHz		5824	114.97	-	-	102.32	35.13	8.72	31.2	100	117	P	H
		5824	107.43	-	-	94.78	35.13	8.72	31.2	100	117	A	H
		5852.4	67.88	-48.95	116.83	55.3	35.12	8.72	31.26	100	117	P	H
		5855.6	64.49	-46.24	110.73	51.89	35.1	8.77	31.27	100	117	P	H
		5883.2	60.27	-38.94	99.21	47.68	35.1	8.77	31.28	100	117	P	H
		5932	55.09	-13.21	68.3	42.48	35.09	8.82	31.3	100	117	P	H
		5830	106.09	-	-	93.44	35.13	8.72	31.2	301	93	P	V
		5830	98.98	-	-	86.33	35.13	8.72	31.2	301	93	A	V
		5853.6	60.52	-53.57	114.09	47.96	35.1	8.72	31.26	301	93	P	V
		5855.6	57.65	-53.08	110.73	45.05	35.1	8.77	31.27	301	93	P	V
		5881.2	54.27	-46.42	100.69	41.68	35.1	8.77	31.28	301	93	P	V
		5925.2	54.2	-14.1	68.3	41.58	35.09	8.82	31.29	301	93	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												


Band 4 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	43.87	-30.13	74	55.97	37.99	12.74	62.83	100	360	P	H
		11490	42.42	-31.58	74	54.52	37.99	12.74	62.83	100	360	P	V
802.11a CH 157 5785MHz		11570	44.43	-29.57	74	56.4	38.06	12.79	62.82	100	360	P	H
		11570	43.29	-30.71	74	55.26	38.06	12.79	62.82	100	360	P	V
802.11a CH 165 5825MHz		11650	43.27	-30.73	74	55.12	38.11	12.85	62.81	100	360	P	H
		11650	42.77	-31.23	74	54.62	38.11	12.85	62.81	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5615.6	53.97	-14.33	68.3	41.1	35.29	8.52	30.94	100	295	P	H
		5693.2	58.08	-42.21	100.29	45.26	35.25	8.58	31.01	100	295	P	H
		5718	64.73	-45.61	110.34	51.93	35.22	8.61	31.03	100	295	P	H
		5724.8	71.35	-50.49	121.84	58.57	35.22	8.61	31.05	100	295	P	H
		5746	110.51	-	-	97.73	35.21	8.64	31.07	100	295	P	H
		5746	103.06	-	-	90.28	35.21	8.64	31.07	100	295	A	H
		5647.2	52.97	-15.33	68.3	40.08	35.3	8.55	30.96	258	247	P	V
		5689.2	54.29	-43.05	97.34	41.47	35.25	8.58	31.01	258	247	P	V
		5716	57.62	-52.16	109.78	44.8	35.24	8.61	31.03	258	247	P	V
		5724.4	63.99	-56.94	120.93	51.21	35.22	8.61	31.05	258	247	P	V
		5746	105.19	-	-	92.41	35.21	8.64	31.07	258	247	P	V
		5746	97.98	-	-	85.2	35.21	8.64	31.07	258	247	A	V
802.11n HT20 CH 165 5825MHz		5824	112.01	-	-	99.36	35.13	8.72	31.2	101	295	P	H
		5824	112.01	-	-	99.36	35.13	8.72	31.2	101	295	A	H
		5852.8	64.56	-51.36	115.92	51.98	35.12	8.72	31.26	101	295	P	H
		5855.2	61.47	-49.37	110.84	48.92	35.1	8.72	31.27	101	295	P	H
		5880.4	57.54	-43.75	101.29	44.95	35.1	8.77	31.28	101	295	P	H
		5944	53.86	-14.44	68.3	41.19	35.09	8.88	31.3	101	295	P	H
		5824	106.07	-	-	93.42	35.13	8.72	31.2	256	246	P	V
		5824	106.07	-	-	93.42	35.13	8.72	31.2	256	246	A	V
		5850.1	58.86	-63.21	122.07	46.28	35.12	8.72	31.26	256	246	P	V
		5856.4	55.62	-54.89	110.51	43.02	35.1	8.77	31.27	256	246	P	V
		5876.8	56.44	-47.52	103.96	43.85	35.1	8.77	31.28	256	246	P	V
		5933.2	53.72	-14.58	68.3	41.11	35.09	8.82	31.3	256	246	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20		11490	43.56	-30.44	74	55.66	37.99	12.74	62.83	100	360	P	H
CH 149 5745MHz		11490	42.62	-31.38	74	54.72	37.99	12.74	62.83	100	360	P	V
802.11n HT20		11570	44.23	-29.77	74	56.2	38.06	12.79	62.82	100	360	P	H
CH 157 5785MHz		11570	43.15	-30.85	74	55.12	38.06	12.79	62.82	100	360	P	V
802.11n HT20		11650	44.22	-29.78	74	56.07	38.11	12.85	62.81	100	360	P	H
CH 165 5825MHz		11650	43.42	-30.58	74	55.27	38.11	12.85	62.81	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5641.6	53.94	-14.36	68.3	41.03	35.3	8.55	30.94	111	293	P	H
		5699.2	61.05	-43.66	104.71	48.23	35.25	8.58	31.01	111	293	P	H
		5719.6	72.64	-38.15	110.79	59.84	35.22	8.61	31.03	111	293	P	H
		5724.4	72.7	-48.23	120.93	59.92	35.22	8.61	31.05	111	293	P	H
		5758	108.8	-	-	96.04	35.19	8.64	31.07	111	293	P	H
		5758	101.34	-	-	88.58	35.19	8.64	31.07	111	293	A	H
		5852	57.71	-60.03	117.74	45.13	35.12	8.72	31.26	111	293	P	H
		5855.6	55.65	-55.08	110.73	43.05	35.1	8.77	31.27	111	293	P	H
		5910.4	53.52	-25.55	79.07	40.89	35.09	8.82	31.28	111	293	P	H
		5925.2	53.17	-15.13	68.3	40.55	35.09	8.82	31.29	111	293	P	H
		5646	52.85	-15.45	68.3	39.96	35.3	8.55	30.96	272	249	P	V
		5699.98	54.94	-50.35	105.29	42.09	35.25	8.61	31.01	272	249	P	V
		5719.2	65	-45.68	110.68	52.2	35.22	8.61	31.03	272	249	P	V
		5724.4	65.04	-55.89	120.93	52.26	35.22	8.61	31.05	272	249	P	V
		5758	102.93	-	-	90.17	35.19	8.64	31.07	272	249	P	V
		5758	94.96	-	-	82.2	35.19	8.64	31.07	272	249	A	V
		5852.8	52.27	-63.65	115.92	39.69	35.12	8.72	31.26	272	249	P	V
		5866.8	53.59	-54	107.59	40.99	35.1	8.77	31.27	272	249	P	V
		5889.6	54.41	-40.05	94.46	41.82	35.1	8.77	31.28	272	249	P	V
		5969.6	53.74	-14.56	68.3	41.08	35.09	8.88	31.31	272	249	P	V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.		(MHz)	(dBμV/m)	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1				(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 159 5795MHz		5602.8	53.43	-14.87	68.3	40.57	35.28	8.52	30.94	102	292	P	H
		5698.4	55.08	-49.04	104.12	42.26	35.25	8.58	31.01	102	292	P	H
		5719.6	56.79	-54	110.79	43.99	35.22	8.61	31.03	102	292	P	H
		5724.4	57.57	-63.36	120.93	44.79	35.22	8.61	31.05	102	292	P	H
		5794	108.98	-	-	96.27	35.16	8.67	31.12	102	292	P	H
		5794	101.11	-	-	88.4	35.16	8.67	31.12	102	292	A	H
		5852.8	60.53	-55.39	115.92	47.95	35.12	8.72	31.26	102	292	P	H
		5855.2	58.56	-52.28	110.84	46.01	35.1	8.72	31.27	102	292	P	H
		5879.6	55.92	-45.96	101.88	43.33	35.1	8.77	31.28	102	292	P	H
		5933.6	53.55	-14.75	68.3	40.88	35.09	8.88	31.3	102	292	P	H
		5620.8	52.93	-15.37	68.3	40.06	35.29	8.52	30.94	257	250	P	V
		5654	54.59	-16.68	71.27	41.72	35.28	8.55	30.96	257	250	P	V
		5701.6	54.73	-51.02	105.75	41.89	35.24	8.61	31.01	257	250	P	V
		5723.6	53.15	-65.96	119.11	40.37	35.22	8.61	31.05	257	250	P	V
		5788	101.63	-	-	88.92	35.16	8.67	31.12	257	250	P	V
		5788	95.07	-	-	82.36	35.16	8.67	31.12	257	250	A	V
		5852	56.75	-60.99	117.74	44.17	35.12	8.72	31.26	257	250	P	V
		5867.2	54.4	-53.08	107.48	41.8	35.1	8.77	31.27	257	250	P	V
		5882.8	54.48	-45.03	99.51	41.89	35.1	8.77	31.28	257	250	P	V
		5949.2	53.21	-15.09	68.3	40.54	35.09	8.88	31.3	257	250	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40		11510	44.02	-29.98	74	56.11	38	12.74	62.83	100	360	P	H
CH 151 5755MHz		11510	43.06	-30.94	74	55.15	38	12.74	62.83	100	360	P	V
802.11n HT40		11590	42.65	-31.35	74	54.57	38.07	12.82	62.81	100	360	P	H
CH 159 5795MHz		11590	43.17	-30.83	74	55.09	38.07	12.82	62.81	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5631.6	54.63	-13.67	68.3	41.73	35.29	8.55	30.94	100	292	P	H
		5694.8	68.6	-32.87	101.47	55.78	35.25	8.58	31.01	100	292	P	H
		5710.4	70.79	-37.42	108.21	57.97	35.24	8.61	31.03	100	292	P	H
		5720.4	70.79	-41.02	111.81	57.99	35.22	8.61	31.03	100	292	P	H
		5782	104.67	-	-	91.94	35.18	8.67	31.12	100	292	P	H
		5782	97.39	-	-	84.66	35.18	8.67	31.12	100	292	A	H
		5852.8	67.73	-48.19	115.92	55.15	35.12	8.72	31.26	100	292	P	H
		5858	65.99	-44.07	110.06	53.39	35.1	8.77	31.27	100	292	P	H
		5875.2	62.43	-42.72	105.15	49.84	35.1	8.77	31.28	100	292	P	H
		5938.8	53.62	-14.68	68.3	40.95	35.09	8.88	31.3	100	292	P	H
		5628.8	53.88	-14.42	68.3	40.98	35.29	8.55	30.94	246	250	P	V
		5690.4	60.45	-37.77	98.22	47.63	35.25	8.58	31.01	246	250	P	V
		5719.98	63.12	-47.77	110.89	50.32	35.22	8.61	31.03	246	250	P	V
		5720.2	63.12	-48.24	111.36	50.32	35.22	8.61	31.03	246	250	P	V
		5782	98.38	-	-	85.65	35.18	8.67	31.12	246	250	P	V
		5782	91.31	-	-	78.58	35.18	8.67	31.12	246	250	A	V
		5851.6	61.02	-57.63	118.65	48.44	35.12	8.72	31.26	246	250	P	V
		5860.8	62.14	-47.13	109.27	49.54	35.1	8.77	31.27	246	250	P	V
		5880	55.56	-46.03	101.59	42.97	35.1	8.77	31.28	246	250	P	V
		5959.2	53.91	-14.39	68.3	41.25	35.09	8.88	31.31	246	250	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80		11550	44.3	-29.7	74	56.29	38.04	12.79	62.82	100	360	P	H
CH 155 5775MHz		11550	44.41	-29.59	74	56.4	38.04	12.79	62.82	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		48.43	25.11	-14.89	40	41.84	15.43	0.8	32.96	-	-	P	H
		89.17	27.93	-15.57	43.5	45.02	14.77	1.06	32.92	-	-	P	H
		167.74	35.36	-8.14	43.5	50.99	15.88	1.43	32.94	100	39	P	H
		252.13	27.6	-18.4	46	39.75	19.08	1.76	32.99	-	-	P	H
		344.28	28.84	-17.16	46	39.41	20.46	2.05	33.08	-	-	P	H
		453.89	29.81	-16.19	46	37.33	23.37	2.34	33.23	-	-	P	H
		48.43	33.5	-6.5	40	50.23	15.43	0.8	32.96	100	30	P	V
		120.21	27.14	-16.36	43.5	41.17	17.7	1.21	32.94	-	-	P	V
		167.74	36.24	-7.26	43.5	51.87	15.88	1.43	32.94	-	-	P	V
		196.84	34.03	-9.47	43.5	50.37	15.01	1.56	32.91	-	-	P	V
		343.31	31.17	-14.83	46	41.76	20.44	2.05	33.08	-	-	P	V
		463.59	32.89	-13.11	46	40.21	23.54	2.37	33.23	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	98.28	-	-	10Hz
802.11n HT20	98.15	-	-	10Hz
802.11n HT40	96.32	0.949	1.053	1.1kHz
802.11ac VHT80	93.30	0.464	2.156	2.2kHz

802.11a




Date: 19.SEP.2019 00:05:10



802.11n HT40



802.11ac VHT80



Date: 19.SEP.2019 00:32:32