# **FCC RF Test Report**

APPLICANT : Motorola Mobility LLC EQUIPMENT : Mobile Cellular Phone

BRAND NAME : Motorola

MODEL NAME : XT2041-4, XT2041-6, XT2041-7, XT2041DL

FCC ID : IHDT56YL1

STANDARD : 47 CFR Part 2, and 90(S)

**CLASSIFICATION**: PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Sep. 19, 2019 and completely tested on Oct. 29, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Reviewed by: Jason Jia / Supervisor

JasonJia

Approved by: James Huang / Manager

### Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 1 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

### **TABLE OF CONTENTS**

RE	VISIO	N HISTORY	3
SU	MMAF	RY OF TEST RESULT	4
1	GENI	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	
	1.3	Feature of Equipment Under Test	
	1.4	Product Specification of Equipment Under Test	
	1.5	Specification of Accessory	
	1.6	Modification of EUT	
	1.7	Maximum Conducted Power, Frequency Tolerance and Emission Designator	7
	1.8	Testing Site	
	1.9	Test Software	
	1.10	Applied Standards	8
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	9
	2.1	Test Mode	9
	2.2	Connection Diagram of Test System	10
	2.3	Support Unit used in test configuration and system	10
	2.4	Measurement Results Explanation Example	11
	2.5	Frequency List of Low/Middle/High Channels	11
3	TEST	RESULT	12
	3.1	Conducted Output Power Measurement	12
	3.2	99% Occupied Bandwidth and 26dB Bandwidth Measurement	13
	3.3	Emissions Mask Measurement	
	3.4	Emissions Mask – Out Of Band Emissions Measurement	16
	3.5	Field Strength of Spurious Radiation Measurement	17
	3.6	Frequency Stability Measurement	19
4	LIST	OF MEASURING EQUIPMENT	21
5	UNCI	ERTAINTY OF EVALUATION	22
ΔΡ	DENID	IX A. TEST RESULTS OF CONDUCTED TEST	
<b>~</b> F	LIND	IX A. IEST RESSETS OF CONDUCTED TEST	
ΑP	<b>PEND</b>	IX B. TEST RESULTS OF RADIATED TEST	

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 2 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

# **REVISION HISTORY**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FW992001B	Rev. 01	Initial issue of report	Dec. 10, 2019

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 3 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

### **SUMMARY OF TEST RESULT**

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< 50+10log <sub>10</sub> (P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious  Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 40.26 dB at 2444.00 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

#### **Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

#### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 4 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

### 1 General Description

### 1.1 Applicant

#### **Motorola Mobility LLC**

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

### 1.2 Manufacturer

#### **Motorola Mobility LLC**

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

### 1.3 Feature of Equipment Under Test

	Product Feature
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2041-4, XT2041-6, XT2041-7, XT2041DL
FCC ID	IHDT56YL1
	CDMA/GSM/WCDMA/LTE
	WLAN 2.4GHz 802.11b/g/n HT20
ELIT cumparta Badica application	WLAN 5GHz 802.11a/n HT20/HT40
EUT supports Radios application	WLAN 5GHz 802.11ac VHT20/VHT40/VHT80
	Bluetooth BR/EDR/LE
	FM Receiver and GNSS
IMELCOA	Conducted: 357244100011546/357244100011501
IMEI Code	Radiation: 357244100020935/357244100020901
HW Version	DVT2
SW Version	QPM30.55
EUT Stage	Identical Prototype

Report No.: FW992001B

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard							
Tx Frequency	814.7 ~ 823.3 MHz						
Rx Frequency	859.7 ~ 868.3 MHz						
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz						
Maximum Output Power to Antenna	23.21 dBm						
Antenna Type	PIFA Antenna						
Type of Modulation	QPSK / 16QAM						

 Sporton International (Kunshan) Inc.
 Page Number
 : 5 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Dec. 10, 2019

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

 FCC ID: IHDT56YL1
 Report Template No.: BU5-FWLTE Version 2.0

### 1.5 Specification of Accessory

		Specification of Accessor	у			
AC Adoptor 1	Brand Name	Motorola(Acbel)	Model Name	SC-41		
AC Adapter 1	Power Rating	I/P: 100-240 Vac, 300mA, O/F	P: 5Vdc, 2000mA			
AC Adoptor 2	Brand Name	Motorola(Chenyang)	Model Name	SC-41		
AC Adapter 2	Power Rating	I/P: 100-240 Vac, 300mA, O/F				
Pottory	Brand Name	Motorola ( Amperex )	Model Name	KZ50		
Battery	Power Rating	3.8Vdc, 4700mAh	Туре	Li-ion polymer		
USB Cable 1	Brand Name	Motorola (Saibao)	Model Name	SC18C24367		
USB Cable 1	Signal Line Type	1.0 meter, shielded cable, with				
USB Cable 2	Brand Name	Motorola (Luxshare)	Model Name	SC18C24368		
USB Cable 2	Signal Line Type	1.0 meter, shielded cable, without ferrite core				

### 1.6 Modification of EUT

No modifications are made to the EUT during all test items.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 6 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

# 1.7 Maximum Conducted Power, Frequency Tolerance and Emission Designator

FCC Rule	System	Type of Modulation	BW	Frequency Tolerance (ppm)	Emission Designator	Maximum Conducted power(W)
Part 90S	LTE Band 26	QPSK	1.4 MHz	-	1M09G7D	0.2080
Part 90S	LTE Band 26	16QAM	1.4 MHz	-	1M09W7D	0.1811
Part 90S	LTE Band 26	64QAM	1.4 MHz	-	1M09W7D	0.1459
Part 90S	LTE Band 26	QPSK	3 MHz	-	2M72G7D	0.2042
Part 90S	LTE Band 26	16QAM	3 MHz	-	2M73W7D	0.1730
Part 90S	LTE Band 26	64QAM	3 MHz	-	2M74W7D	0.1416
Part 90S	LTE Band 26	QPSK	5 MHz	-	4M51G7D	0.2094
Part 90S	LTE Band 26	16QAM	5 MHz	-	4M51W7D	0.1807
Part 90S	LTE Band 26	64QAM	5 MHz	-	4M49W7D	0.1472
Part 90S	LTE Band 26	QPSK	10 MHz	0.0077	9M09G7D	0.2075
Part 90S	LTE Band 26	16QAM	10 MHz	-	9M01W7D	0.1770
Part 90S	LTE Band 26	64QAM	10 MHz	-	8M99W7D	0.1462
Part 90S	LTE Band 26	QPSK	15 MHz	-	13M4G7D	0.2042
Part 90S	LTE Band 26	16QAM	15 MHz	-	13M5W7D	0.1778
Part 90S	LTE Band 26	64QAM	15 MHz	-	13M4W7D	0.1426

## 1.8 Testing Site

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (F	Sporton International (Kunshan) Inc.							
	No. 1098, Pengxi North Road, Kunshan Economic Development Zone								
Test Site Location	Jiangsu Province 215300 People's Republic of China								
rest one Location	TEL: +86-512-57900158								
	FAX: +86-512-57900958								
	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.						
Test Site No.	03CH06-KS TH01-KS	CN1257	314309						

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 7 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

#### 1.9 Test Software

Item	Site	Manufacture	Name	Version	
1.	03CH06-KS	AUDIX	E3	6.2009-8-24al	

### 1.10 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

#### Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 8 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

#### **Test Configuration of Equipment Under Test** 2

#### **Test Mode** 2.1

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

	Donal	Bandwidth (MHz)				Modulation		RB#			Test Channel					
Test Items	Band	1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	М	Н
Max. Output Power	26	٧	٧	٧	v	٧	-	v	v	v	>	v	v	٧	٧	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v	v			v	v	v	v
Emission masks In-band emissions	26	٧	٧	٧	v	٧	-	v	v	v	٧		v	v		v
Emission masks – Out of band emissions	26	٧	٧	٧	v	٧	-	v	v	v	٧			v	v	v
Frequency Stability	26				v	٧	-	v					v		v	
Radiated Spurious Emission	26	v	v	٧	v	٧	-	v			v				v	
Note	<ol> <li>The mark "v" means that this configuration is chosen for testing</li> <li>The mark "-" means that this bandwidth is not supported.</li> <li>LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies.</li> </ol>															


falls within part 22 also complies.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1

: 9 of 21 Page Number Report Issued Date: Dec. 10, 2019 Report Version : Rev. 01

Report No.: FW992001B

### 2.2 Connection Diagram of Test System



# 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord	
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m	
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m	
3.	Earphone	N/A	N/A	N/A	N/A	N/A	

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 10 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

### 2.4 Measurement Results Explanation Example

#### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.6 dB.

Example:

 $Offset(dB) = RF \ cable \ loss(dB).$ = 4.6 (dB)

### 2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List									
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest					
15	Channel	26765	-	-					
15	Frequency	821.5	-	-					
10	Channel	-	26740	-					
10	Frequency	-	819	-					
5	Channel	26715	26740	26765					
5	Frequency	816.5	819	821.5					
3	Channel	26705	26740	26775					
3	Frequency	815.5	819	822.5					
1.4	Channel	26697	26740	26783					
1.4	Frequency	814.7	819	823.3					

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 11 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

#### 3 Test Result

### 3.1 Conducted Output Power Measurement

#### 3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


#### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.1.3 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through the system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

#### 3.1.4 Test Setup



#### 3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

Report No.: FW992001B

### 3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.2.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

#### 3.2.4 Test Setup



#### 3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 13 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

#### 3.3 Emissions Mask Measurement

#### 3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

- (a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:
- (1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log<sub>10</sub>(f/6.1) decibels or 50 + 10 Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.
- (2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- 2. The emissions mask of low and high channels for the highest RF powers were measured.
- The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
- 4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

### 3.3.4 Test Setup



### 3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 15 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

#### 3.4 Emissions Mask - Out Of Band Emissions Measurement

#### 3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
   The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

#### 3.4.4 Test Setup



### 3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 16 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

### 3.5 Field Strength of Spurious Radiation Measurement

#### **Description of Field Strength of Spurious Radiated Measurement** 3.5.1

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43+10log<sub>10</sub>(P[Watts]) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 **Test Procedures**


- The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 5. 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

: 17 of 21 Page Number Report Issued Date: Dec. 10, 2019 Report Version : Rev. 01


Report No.: FW992001B

#### 3.5.4 Test Setup

#### For radiated test from 30MHz to 1GHz



#### For radiated test above 1GHz



### 3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 18 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

### 3.6 Frequency Stability Measurement

#### **Description of Frequency Stability Measurement** 3.6.1

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

#### 3.6.2 **Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 **Test Procedures for Temperature Variation**

- 1. The EUT was set up in the thermal chamber and connected with the base station.
- 2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
- With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized 3. at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.


#### 3.6.4 **Test Procedures for Voltage Variation**

- 1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
- 2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
- 3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
- 4. battery operating end point, which shall be specified by the manufacturer.
- 5. The variation in frequency was measured for the worst case.

: 19 of 21 Page Number Report Issued Date: Dec. 10, 2019 Report Version : Rev. 01

Report No.: FW992001B

### 3.6.5 Test Setup



#### 3.6.6 **Test Result of Temperature Variation**

Please refer to Appendix A.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1

Page Number : 20 of 21 Report Issued Date: Dec. 10, 2019 Report Version : Rev. 01

Report No.: FW992001B

# 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2019	Oct. 13, 2019~ Oct. 17, 2019	Aug. 06, 2020	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 04, 2019	Oct. 13, 2019~ Oct. 17, 2019	Jul. 03, 2020	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44GHz	Apr. 16, 2019	Oct. 29, 2019	Apr. 18, 2020	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 28, 2018	Oct. 29, 2019	Dec. 27, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 27, 2019	Oct. 29, 2019	Jan. 26, 2020	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug, 06, 2019	Oct. 29, 2019	Aug, 05, 2020	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Apr.17. 2019	Oct. 29, 2019	Apr.16, 2020	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 29, 2019	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 29, 2019	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 29, 2019	NCR	Radiation (03CH06-KS)

NCR: No Calibration Required

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 21 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

### 5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

#### <u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

-		
	Measuring Uncertainty for a Level of	3 E4D
ı	Confidence of 95% (U = 2Uc(y))	2.5dB

#### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of	2.1dB
Confidence of 95% (U = 2Uc(y))	2.105

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : 22 of 21
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

Report No.: FW992001B

# **Appendix A. Test Results of Conducted Test**

# **Conducted Output Power (Average power)**

	LTE Band 26 Maximum Average Power [dBm]										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest					
15	1	0		23.10							
15	1	37		23.04							
15	1	74		23.02							
15	36	0	QPSK	22.16							
15	36	20		22.20							
15	36	39		22.17							
15	75	0		22.20		_					
15	1	0		22.50	-	-					
15	1	37		22.23							
15	1	74		22.09							
15	36	0	16-QAM	21.20							
15	36	20		21.35							
15	36	39		21.25							
15	75	0		21.25							
15	1	0		21.38							
15	1	37		21.12							
15	1	74		21.54							
15	36	0	64-QAM	20.38							
15	36	20		20.43							
15	36	39		20.36							
15	75	0		20.41							

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : A1 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

			LTE Ban	d 26 Maximum Average F	Power [dBm]	
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0			23.05	
10	1	25			23.09	
10	1	49			23.17	
10	25	0	QPSK		22.18	
10	25	12			22.24	
10	25	25			22.13	
10	50	0		_	22.20	_
10	1	0		-	22.20	-
10	1	25			22.12	
10	1	49			22.48	
10	25	0	16-QAM		21.27	
10	25	12			21.32	
10	25	25			21.32	
10	50	0			21.27	
10	1	0			21.65	
10	1	25			21.53	
10	1	49			21.21	
10	25	0	64-QAM		20.36	
10	25	12			20.52	
10	25	25			20.44	
10	50	0			20.43	

Page Number : A2 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

	LTE Band 26 Maximum Average Power [dBm]										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest					
5	1	0		23.21	23.20	23.12					
5	1	12		23.03	23.06	23.08					
5	1	24		23.10	23.11	22.99					
5	12	0	QPSK	22.07	22.12	22.11					
5	12	7		22.15	22.27	22.17					
5	12	13		22.08	22.15	22.12					
5	25	0		22.02	22.18	22.02					
5	1	0		22.27	22.15	22.40					
5	1	12		22.23	22.32	22.57					
5	1	24	16-QAM	22.14	22.50	22.30					
5	12	0		21.18	21.29	21.26					
5	12	7		21.18	21.31	21.35					
5	12	13		21.17	21.26	21.19					
5	25	0		21.16	21.25	21.20					
5	1	0		21.47	21.68	21.27					
5	1	12		21.38	21.19	21.67					
5	1	24		21.67	21.49	21.38					
5	12	0	64-QAM	20.36	20.41	20.40					
5	12	7		20.46	20.54	20.46					
5	12	13		20.16	20.41	20.29					
5	25	0		20.33	20.37	20.25					

Page Number : A3 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

	LTE Band 26 Maximum Average Power [dBm]										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest					
	LTE Band 26 Maximum Average Power [dBm]										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest					
3	1	0		23.03	23.10	22.91					
3	1	8		23.02	23.10	23.07					
3	1	14		22.97	23.09	22.93					
3	8	0	QPSK	22.41	22.40	22.27					
3	8	4		22.39	22.49	22.38					
3	8	7		22.34	22.37	22.21					
3	15	0		22.35	22.46	22.27					
3	1	0		22.33	22.38	22.25					
3	1	8		22.35	22.38	22.32					
3	1	14		22.34	22.35	22.25					
3	8	0	16-QAM	21.29	21.36	21.23					
3	8	4		21.28	21.36	21.34					
3	8	7		21.22	21.34	21.26					
3	15	0		21.30	21.30	21.09					
3	1	0		21.44	21.44	21.41					
3	1	8		21.33	21.42	21.44					
3	1	14		21.34	21.51	21.31					
3	8	0	64-QAM	20.45	20.52	20.37					
3	8	4		20.43	20.51	20.37					
3	8	7		20.38	20.50	20.33					
3	15	0		20.30	20.40	20.29					

Page Number : A4 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

	LTE Band 26 Maximum Average Power [dBm]										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest					
1.4	1	0		23.15	23.09	22.99					
1.4	1	3		23.18	23.05	23.09					
1.4	1	5		23.15	23.04	22.98					
1.4	3	0	QPSK	23.07	23.15	22.94					
1.4	3	1		23.17	23.18	23.08					
1.4	3	3		23.11	23.14	23.06					
1.4	6	0		22.26	22.37	22.26					
1.4	1	0		22.51	22.50	22.39					
1.4	1	3		22.54	22.58	22.50					
1.4	1	5		22.42	22.52	22.44					
1.4	3	0	16-QAM	22.21	22.18	22.13					
1.4	3	1		22.18	22.22	22.09					
1.4	3	3		22.15	22.15	22.05					
1.4	6	0		21.39	21.39	21.32					
1.4	1	0		21.43	21.39	21.37					
1.4	1	3		21.16	21.58	21.48					
1.4	1	5		21.38	21.48	21.28					
1.4	3	0	64-QAM	21.53	21.50	21.45					
1.4	3	1		21.59	21.64	21.51					
1.4	3	3		21.46	21.57	21.46					
1.4	6	0		20.31	20.39	20.32					

Page Number : A5 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

# Peak-to-Average Ratio


Mode					
Mod.	QP	SK	16C	Limit: 13dB	
RB Size	1RB Full RB		1RB	Full RB	Result
Lowest CH	3.28	4.49	4.84	5.74	
Middle CH	-	-	-	-	PASS
Highest CH	-	-	-	-	
Mod.	64C	AM	Limit: 13dB		
RB Size	1RB	Full RB	Result		
Lowest CH	4.58	5.77			
Middle CH	-	-	PASS		
Highest CH	-	-			

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1

: A6 of A48 Page Number Report Issued Date: Dec. 10, 2019 : Rev. 01

Report No.: FW992001B

Report Version



Page Number : A7 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

# 26dB Bandwidth


Mode		LTE Band 26 : 26dB BW(MHz)										
BW	1.4	ИНz	3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.242	1.242	3.0569	2.985	4.925	4.885			14.386	14.356	-	-
Middle CH	1.2308	1.2252	3.039	3.021	4.885	4.915	9.65	9.73			-	-
Highest CH	1.2252	1.2252	3.021	3.039	4.895	4.905					-	-
Mode					LTE Ba	and 26 : :	26dB BV	V(MHz)				
BW	1.4	ИНz	3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM			
Lowest CH	1.2196		2.985		4.945				14.146		-	-
Middle CH	1.2336		2.991		4.905		9.91				-	-
Highest CH	1.2112		2.991		4.885						-	-

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1


: A8 of A48 Page Number Report Issued Date: Dec. 10, 2019

Report No.: FW992001B


Report Version : Rev. 01




Page Number : A9 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




Page Number : A10 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




Page Number : A11 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




Page Number : A12 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01



Page Number : A13 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01



Page Number : A14 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01



Page Number : A15 of A48 Report Issued Date: Dec. 10, 2019 : Rev. 01

Report No.: FW992001B

Report Version

## **Occupied Bandwidth**

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.09	2.71	2.73	4.51	4.51			13.43	13.46	-	-
Middle CH	1.09	1.09	2.71	2.73	4.50	4.51	9.09	9.01			-	-
Highest CH	1.09	1.09	2.72	2.73	4.51	4.49					-	-
Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM			
Lowest CH	1.09		2.73		4.49				13.43		-	-
Middle CH	1.09		2.74		4.49		8.99				-	-
Highest CH	1.09		2.72		4.48						-	-


Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1


: A16 of A48 Page Number Report Issued Date: Dec. 10, 2019

Report No.: FW992001B


Report Version : Rev. 01




Page Number : A17 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




Page Number : A18 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




Page Number : A19 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




Page Number : A20 of A48 Report Issued Date: Dec. 10, 2019 Report Version : Rev. 01



Page Number : A21 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : A22 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




Page Number : A23 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01

## **Conducted Band Edge**




Sporton International (Kunshan) Inc.


TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : A24 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : A25 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : A26 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : A27 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : A28 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56YL1 Page Number : A29 of A48
Report Issued Date : Dec. 10, 2019
Report Version : Rev. 01