
Branch



FCC TEST REPORT

Application No:	ZR/2020/50007
Applicant:	Motorola Mobility LLC
Address of Applicant	222 W Merchandise Mart Plaza, Suite 1800, Chicago IL 60654, USA
Manufacturer:	Company Name: Motorola Mobility LLC
Address of Manufacturer:	222 W Merchandise Mart Plaza, Suite 1800, Chicago IL 60654, USA
EUT Name:	Mobile Cellular Phone
Model No.:	XT2081-2
Type Name:	MC367
Trade mark:	Motorola
FCC ID:	IHDT56ZD2
Standards:	47 CFR Part 2
	47 CFR Part 22 subpart H
	47 CFR Part 24 subpart E
	47 CFR Part 27 subpart C
Test Method:	FCC KDB 971168 D01 Power Meas License Digital Systems V03r01
	C63.26 (2015)
Date of Receipt:	2020/5/9
Date of Test:	2020/5/10 to 2020/6/12
Date of Issue:	2020/8/7
Test Result:	PASS *

In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Derde yang

Derek Yang Wireless Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions/Terms-enDocument.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exconserate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755)83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 •深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



> Report No.: ZR/2020/5000701 Page: 2 of 26

1 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020/8/7		Original

Authorized for issue by:		
Tested By	Mike Mu (Mike Hu) /Project Engineer	
Checked By	David Chen (David Chen) /Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation on liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: (N_Doccheck@gss.com)

or email: <u>CN_Doccheck@ags.com</u> No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



Report No.: ZR/2020/5000701 Page: 3 of 26

Content

1 VERSION	2
2 TEST SUMMARY	5
2.1 GSM850/UMTS BAND 5 & LTE BAND 5	
2.2 GSM 1900/UMTS BAND 2	5
2.3 LTE BAND 7/38/41	6
3 GENERAL INFORMATION	7
3.1 CLIENT INFORMATION	7
3.2 TEST LOCATION	7
3.3 TEST FACILITY	7
3.4 GENERAL DESCRIPTION OF EUT	
3.5 Test Mode	8
3.6 TEST ENVIRONMENT	9
3.7 TECHNICAL SPECIFICATION	9
3.8 TEST FREQUENCIES	11
4 DESCRIPTION OF TESTS	14
4.1 CONDUCTED OUTPUT POWER	14
4.2 EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER	14
4.3 Occupied Bandwidth	14
4.4 BAND EDGE AT ANTENNA TERMINALS	
4.5 Spurious And Harmonic Emissions at Antenna Terminal	
4.6 PEAK-AVERAGE RATIO	16
4.7 FIELD STRENGTH OF SPURIOUS RADIATION	17
4.8 FREQUENCY STABILITY / TEMPERATURE VARIATION	
4.9 TEST SETUPS	
4.9.1 Test Setup 1	
4.9.2 Test Setup 2	
4.9.3 Test Setup 3	20
4.9.4 Test Setup 4	21
4.10 TEST CONDITIONS	22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Tormat documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cloes not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this teres theort neft only to the sample(s) are relatined for 30 days only. Altention: To back the authenticity of testing /inspection report's certificate, please contact us at telephone: (86-755) 8307 1443, or email. CM.Deched.esge.com on back the authent for the fullest contact for a contact us at telephone: (86-755) 8307 1443, or email. CM.Deched.esge.com on back the authent for the full the full the full the full telephone for the full telephone full the full telephone full the contact us at telephone for the full telephone full the full telephone full the state the telephone full the full telephone full tele

or email: <u>CN_Doccheck@ags.com</u> No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



Report No.: ZR/2020/5000701 Page: 4 of 26

5 MAIN TEST INSTRUMENTS	24
6 MEASUREMENT UNCERTAINTY	
7 APPENDIXES	26



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation on liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: (N_Doccheck@gss.com)

or email: <u>CN_Deccheck@ssg.com</u> No.1Workshop.M-10.Midde Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 · 深圳 · 科技因中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



> Report No.: ZR/2020/5000701 Page: 5 of 26

2 Test Summary

2.1 GSM850/UMTS Band 5 & LTE Band 5

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §22.913	FCC: ERP ≤ 7 W	Section 1 of Appendix B	Pass
Peak-Average Ratio		Limit≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §22.917	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13 dBm/100 kHz.	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Section 8 of Appendix B	Pass
Remark: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

2.2 GSM 1900/UMTS Band 2

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §24.232	EIRP ≤ 2 W	Section 1 of Appendix B	Pass
Peak-Average Ratio	§2.1046, §24.232	Limit≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §24.238	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	 ≤ -13 dBm/1 MHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges. 	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13 dBm/1 MHz.	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055,	≤ ±2.5 ppm.	Section 8 of	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, a subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document inges otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing linspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@sgs.com

or email: <u>CN_Doccheck@sgs.com</u> No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



Report No.: ZR/2020/5000701 Page: 6 of 26

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
	§24.235		Appendix B	
Remark: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

2.3 LTE Band 7/38/41

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	EIRP ≤ 2W	Section 1 of Appendix B	Pass
Peak-Average Ratio	§27.50(a)	≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §27.53(m4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	Channel Edge -25 dBm/ 1 MHz 9 kHz 9.5 MHz XMHz 10th harmonics X=Max {6MHz, EBW}	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	Channel Edge -25 dBm/ 1 MHz 9 kHz 9 kHz X=Max {6MHz, EBW}	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	Section 8 of Appendix B	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available or request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is dream to the linking of t

 Of Ball: CN. Doccheck@sgs.com
 Workshop, M-10, Midde Section, Science & Technology Park, Shenzhen, China 518057
 t (86–755) 26012053
 f (86–755) 26710594
 www.sgsgroup.com.cn

 中国・深圳・科技园中区M-10栋一号厂房
 邮编: 518057
 t (86–755) 26012053
 f (86–755) 26710594
 sgs.china@sgs.com



Report No.: ZR/2020/5000701 Page: 7 of 26

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Remark: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

3 General Information

3.1 Client Information

Applicant:	Motorola Mobility LLC
Address of Applicant:	222 W Merchandise Mart Plaza, Suite 1800, Chicago IL 60654, USA
Manufacturer:	Company Name: Motorola Mobility LLC
Address of Manufacturer:	222 W Merchandise Mart Plaza, Suite 1800, Chicago IL 60654, USA

3.2 Test Location

Company:	SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch	
Address:	No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China	
Post code:	518057	
Telephone:	+86 (0) 755 2601 2053	
Fax:	+86 (0) 755 2671 0594	
E-mail:	ee.shenzhen@sgs.com	

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. ĆNAS LŽ929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.





Report No.: ZR/2020/5000701 Page: 8 of 26

3.4 General Description of EUT

EUT Description::	Mobile Cellular Phone				
Model No.:	XT2081-2				
Type Name:	MC367				
Trade Mark:	Motorola				
Hardware Version:	DVT2-2				
Software Version:	QPZ30.30-Q3				
Sample Type:	☑ Portable Device, ☐ Module				
Antenna Type:	External, Integrated				
	GSM850: -3.6dBi;				
	GSM1900:-2.1dBi				
	WCDMA Band II:-2.1dBi				
Antenna Gain:	WCDMA Band V:-3.6dBi				
Antenna Gain.	LTE Band 5:-3.6dBi;				
	LTE Band 7: -1.4dBi				
	LTE Band 38:-1.4dBi;				
	LTE Band 41: -1.4dBi				
	AC Aadpte:Model No.:SC-41;SC-42;SC-43;SC-46;SC-47;MC-101;MC-102;MC-103;MC-106;MC-107				
Accsessories	I/P:100-240 300mA				
	O/P:5V,2000mA;				
	Battery: Model No.:JK50,3.8V				

3.5 Test Mode

Test Mode	Test Modes Description
GSM/TM1	GSM system, GSM/GPRS, GMSK modulation
GSM/TM2	GSM system, EGPRS, 8PSK modulation
UMTS/TM1	UMTS system, WCDMA, QPSK modulation
LTE/TM1	LTE system, QPSK modulation
LTE/TM2	LTE system, 16QAM modulation
LTE/TM3	LTE system, 64QAM modulation

Remark: The test mode(s) are selected according to relevant radio technology specifications.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: **CN_Doccheck@ass.com**

No. Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



> Report No.: ZR/2020/5000701 Page: 9 of 26

3.6 Test Environment

Environment Parameter	Selected Values During Tests			
Relative Humidity	52%			
Atmospheric Pressure:	101.32 KPa			
Temperature	NT 25 °C			
	LV 3.6V			
Voltage:	NV	3.8V		
	HV	4.4V		

Remark: LV= lower extreme test voltage; NV= nominal voltage

HV= upper extreme test voltage; NT= normal temperature

3.7 Technical Specification

Characteristics	Description					
	⊠ GSM					
Radio System Type	🖂 UMTS					
	🖂 LTE					
	Band	ТХ	RX			
	GSM850	824 to 849 MHz	869 to 894 MHz			
	GSM1900	1850 to 1910 MHz	1930 to 1990 MHz			
	UMTS Band II	1850 to 1910 MHz	1930 to 1990 MHz			
Supported Frequency Range	UMTS Band V	824 to 849 MHz	869 to 894 MHz			
lango	LTE Band 5	824 to 849 MHz	869 to 894 MHz			
	LTE Band 7	2500 to 2570 MHz	2620 to 2690 MHz			
	LTE Band 38	2570 to 2620 MHz	2570 to 2620 MHz			
	LTE Band 41	2535 to 2655MHz	2535 to 2655MHz			
Target TX Output Power	GSM850:33.5 dBm GSM1900: 30.5dBm UMTS Band II: 24dBm UMTS Band V: 24dBm LTE Band 5: 24dBm LTE Band 7: 24dBm LTE Band 38: 24dBm LTE Band 41: 24dBm					
	GSM system: UMTS system:	⊠ 0.2 MHz ⊠ 5 MHz				
Supported Channel	LTE Band 5	\boxtimes 1.4 MHz; \boxtimes 3 MHz; \boxtimes 5	i MHz; ⊠ 10 MHz			
Bandwidth	LTE Band 7	🛛 5 MHz; 🖂 10 MHz; 🖂 1	5 MHz, 🛛 20 MHz			
	LTE Band38	🛛 5 MHz; 🖂 10 MHz; 🖂 1				
	LTE Band41	│ 🖾 5 MHz; 🖾 10 MHz; 🖾 1	5 MHz, 🛛 20 MHz			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are relatined for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@ags.com

中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: ZR/2020/5000701 Page: 10 of 26

Characteristics	Description	
	GSM850	246KGXW; 249KG7W
	GSM1900	246KGXW; 249KG7W
	UMTS Band II	4M15F9W;
	UMTS Band V	4M14F9W;
Designation of		1M09G7D;1M09W7D; 1M10W7D
Emissions	LTE Band 5	2M70G7D;2M69W7D; 2M69W7D
		4M48G7D;4M49W7D; 4M48W7D
(Remark: the necessary		8M93G7D;8M93W7D; 8M93W7D
bandwidth of which is	LTE Band 7	4M48G7D;4M49W7D; 4M48W7D
the worst value from		8M93G7D;8M93W7D; 8M93W7D
the measured occupied		13M5G7D;13M5W7D; 13M5W7D
bandwidths for each		17M9G7D;17M9W7D; 17M9W7D
type of channel	LTE Band 38	4M48G7D;4M50W7D; 4M49W7D
bandwidth		8M91G7D;8M91W7D; 8M93W7D
		13M5G7D;13M5W7D; 13M5W7D
configuration.)		17M9G7D;17M9W7D; 17M9W7D
		4M48G7D;4M50W7D; 4M49W7D
	LTE Band 41	8M91G7D;8M91W7D; 8M93W7D
	LIE Dallu 41	13M5G7D;13M5W7D; 13M5W7D
		17M9G7D;17M9W7D; 17M9W7D



of email: <u>CN_DeceneeKeesga.com</u> No.1Workshop,M-10.Midd escloin, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 · 深圳 · 科技因中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.com



> Report No.: ZR/2020/5000701 Page: 11 of 26

3.8 Test Frequencies

Test Mode	est Mode TX / RX	RF Channel			
Test Mode		Low (L)	Middle (M)	High (H)	
	ТХ	Channel 128	Channel 190	Channel 251	
GSM850		824.2MHz	836.6 MHz	848.8 MHz	
GSIM650		Channel 128	Channel 190	Channel 251	
	RX	869.2 MHz	881.6 MHz	893.8 MHz	

Test Mode		est Mode TX / RX RF Channel				
Test Mode		Low (L)	Middle (M)	High (H)		
	ТХ	Channel 512	Channel 661	Channel 810		
CSM1000		1850.2MHz	1880.0 MHz	1909.8 MHz		
GSM1900	DV	Channel 512	Channel 661	Channel 810		
	RX	1930.2 MHz	1960.0 MHz	1989.8 MHz		

Test Mode	Mode TX / RX	RF Channel			
Test Mode		Low (L)	Middle (M)	High (H)	
	ТХ	Channel 9262	Channel 9400	Channel 9538	
WCDMA		1852.4 MHz	1880.0 MHz	1907.6 MHz	
Band II	RX	Channel 9662	Channel 9800	Channel 9938	
	π۸	1932.4 MHz	1960.0 MHz	1987.6 MHz	

Test Mode	TX / RX	TX / PX RF Channel				
Test Mode		Low (L)	Middle (M)	High (H)		
	тх	Channel 4132	Channel 4182	Channel 4233		
WCDMA		826.4MHz	836.4 MHz	846.6 MHz		
Band V	ΒV	Channel 4357	Channel 4407	Channel 4458		
	RX	871.4 MHz	881.4 MHz	891.6 MHz		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not excore a transaction from exercising all their rights and obligations under the transaction documents. This document is unawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this tercept re only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ags.com

or email: <u>CN_Doccheck@sgs.com</u> No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



> Report No.: ZR/2020/5000701 Page: 12 of 26

Test Mode	Bandwidth	TX / RX		RF Channel	
Test Mode			Low (L)	Middle (M)	High (H)
		ΤХ	Channel 20407	Channel 20525	Channel 20643
	1.4MHz		824.7 MHz	836.5 MHz	848.3 MHz
	1.411112	RX	Channel 2407	Channel 2525	Channel 2643
		КЛ	869.7 MHz	881.5 MHz	893.3 MHz
		ТХ	Channel 20415	Channel 20525	Channel 20635
	3MHz		825.5 MHz	836.5 MHz	847.5 MHz
	SIVILIZ	RX	Channel 2415	Channel 2525	Channel 2635
LTE Band 5			870.5 MHz	881.5 MHz	892.5 MHz
LIE Dallu 5		5MHz	Channel 20425	Channel 20525	Channel 20625
			826.5 MHz	836.5 MHz	846.5 MHz
		RX -	Channel 2425	Channel 2525	Channel 2625
			871.5 MHz	881.5 MHz	891.5 MHz
		ТХ	Channel 20450	Channel 20525	Channel 20600
	10MHz		829 MHz	836.5 MHz	844 MHz
	TOMHZ	RX	Channel 2450	Channel 2525	Channel 2600
		ΓΛ	874 MHz	881.5 MHz	889 MHz

Test Mede	Bandwidth	TV / DV	RF Channel		
Test Mode		Bandwidth TX / RX	Low (L)	Middle (M)	High (H)
		ΤХ	Channel 20775	Channel 21100	Channel 21425
	5MHz		2502.5 MHz	2535 MHz	2567.5 MHz
	SIVILIZ	RX	Channel 2775	Channel 3100	Channel 5825
		ΓA	2622.5 MHz	2655 MHz	2687.5 MHz
		ТХ	Channel 20800	Channel 21100	Channel 21400
	10MHz		2505 MHz	2535 MHz	2565 MHz
	TOWITZ	RX	Channel 2800	Channel 3100	Channel 3400
LTE Band 7			2625 MHz	2655 MHz	2685 MHz
LIE Dallu I		ТХ	Channel 20825	Channel 21100	Channel 21375
	15MHz		2507.5 MHz	2535 MHz	2562.5 MHz
	TOIVITIZ	RX	Channel 2825	Channel 3100	Channel 3375
			2627.5 MHz	2655 MHz	2682.5 MHz
		ТХ	Channel 20850	Channel 21100	Channel 21350
	20MHz		2510 MHz	2535 MHz	2560 MHz
		PY	Channel 2850	Channel 3100	Channel 3350
		RX	INA	2630 MHz	2655 MHz

Test Mode	Bandwidth	Bandwidth TX / RX	RF Channel		
Test Mode	Danuwiuth		Low (L)	Middle (M)	High (H)
	5MHz	TX/RX	Channel 37775	Channel38000	Channel 38225
			2572.5 MHz	2595 MHz	2617.5 MHz
	10MHz	TX/RX	Channel 37800	Channel38000	Channel 38200
	TOIVINZ		2575 MHz	2595 MHz	2615 MHz
LTE Band 38		15MHz TX/RX	Channel 37825	Channel38000	Channel 38175
			2577.5 MHz	2595 MHz	2612.5 MHz
	2014	20MHz TX/RX	Channel 37850	Channel38000	Channel 38150
	2010112		2580 MHz	2595 MHz	2610 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation on liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excore a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: (N_Doccheck@egs.com)

or email: <u>CN_Doccheck@segs.com</u> No.1Workshop.M10, Middle Section, Science & Technology Park, Shenzhen, China 518057 tt (86–755) 26012053 ft (86–755) 26710594 www.sgsgroup.com.cn 中国 •深圳 • 科技因中区M-10栋一号厂房 邮编: 518057 tt (86–755) 26012053 ft (86–755) 26710594 sgs.com



> Report No.: ZR/2020/5000701 Page: 13 of 26

Test Mode	Bandwidth	TX / RX	RF Channel			
Test Mode			Low (L)	Middle (M)	High (H)	
	5MHz	TX/RX	Channel 40065	Channel40640	Channel 41215	
LTE Band 41			2537.5 MHz	2595 MHz	2652.5 MHz	
	10MHz	TX/RX	Channel 40090	Channel40640	Channel 41190	
			2540 MHz	2595 MHz	2650 MHz	
	15MHz	TX/RX	Channel 40115	Channel40640	Channel 41165	
			2542.5 MHz	2595 MHz	2647.5 MHz	
	20MHz T		Channel 40140	Channel40640	Channel 41140	
		TX/RX	2545 MHz	2595 MHz	2645 MHz	



or email: CN_DocCheck@ssg.com No.1Workshop.M-10,Midde Section,Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com SGS s

SGS-CSTC Standards Technical Services Co., Ltd.Shenzhen

Report No.: ZR/2020/5000701 Page: 14 of 26

4 Description of Tests

4.1 Conducted Output Power

Measurement Procedure: FCC KDB 971168 D01 V03r01

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

Remark: Reference test setup 1

4.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure: FCC KDB 971168 D01 V03r01 ; C63.26 (2015) Calculate power in dBm by the following formula: ERP (dBm) = Conducted Power (dBm) + antenna gain (dBd) EIRP(dBm) = Conducted Power (dBm) + antenna gain (dBi) EIRP=ERP+2.15dB

4.3 Occupied Bandwidth

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 4.2

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

Remark: Reference test setup 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exoncerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report a certificate, please contact us at telephone: (86-755) 8307 1443, or email: <u>CN.Doccheck@ags.com</u>] (Mo.1Wickbon, Milo, Midde Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 260710594 www.sgsgroup.com.cn

中国・深圳・科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: ZR/2020/5000701 Page: 15 of 26

Test Settings

- The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- 3. VBW ≥ 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2 7 were repeated after changing the RBW such that it would be within

1 - 5% of the 99% occupied bandwidth observed in Step 7

4.4 Band Edge at Antenna Terminals

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold power.

Remark: Reference test setup 1

Test Settings

- 1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW ≥ 1% of the emission bandwidth
- 4. VBW > 3 x RBW
- 5. Detector = RMS
- 6. Number of sweep points ≥ 2 x Span/RBW
- 7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
- 8. Sweep time = auto couple
- 9. The trace was allowed to stabilize

4.5 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure: FCC KDB 971168 D01 V03r01



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excore the company. Sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification on the sample(s) test report reformed on the sample(s) test repartients on the sample(s) test reparties to a test report reformed test ing imspection report & certificate, please contact us at telephone: (86-755)83071443, or email: (SN.Doccheck@egs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: ZR/2020/5000701 Page: 16 of 26

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Remark: Reference test setup 1

Test Settings

- Start frequency was set to 30MHz and stop frequency was set to at least 10 * the fundamental frequency (separated into at least two plots per channel)
- 2. Detector = RMS
- 3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
- 4. Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings

4.6 Peak-Average Ratio

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.7.1

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Remark: Reference test setup 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not excore a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this ter report refer only to the sample(s) ters retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755)8307 1443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳•科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: ZR/2020/5000701 Page: 17 of 26

Test Settings

- 1. The signal analyzer's CCDF measurement profile is enabled
- Frequency = carrier center frequency
- Measurement BW > Emission bandwidth of signal
- 4. The signal analyzer was set to collect one million samples to generate the CCDF curve
- 5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

4.7 Field Strength of Spurious Radiation

Measurement Procedure: FCC KDB 971168 D01 V03r01

Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8) Calculate power in dBm by the following formula:

ERP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBd)

Where:

Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] - cable loss [dB]. The calculated Pd levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of 43 + 10log10(Power [Watts]).

Above 1GHz test procedure as below:

1) Different between above is the test site, change from Semi- Anechoic

中国·深圳·科技园中区M-10栋一号厂房

Chamber to fully Anechoic Chamber



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and <u>urisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,</u> No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn sgs.china@sgs.com

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594

Member of the SGS Group (SGS SA)

SGS SG

SGS-CSTC Standards Technical Services Co., Ltd.Shenzhen Branch

Report No.: ZR/2020/5000701 Page: 18 of 26

2) Calculate power in dBm by the following formula:

```
EIRP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBi)
```

```
EIRP=ERP+2.15dB
```

Where:

Pg is the generator output power into the substitution antenna.

- 3. Test the EUT in the lowest channel, the middle channel the Highest channel
- 4. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5. Repeat above procedures until all frequencies measured was complete
- Remark: Reference test setup 3

4.8 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of FCC KDB 971168 D01 V03r01; ANSI/C63.26 (2015)

- . The frequency stability of the transmitter is measured by:
- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Remark: Reference test setup 4



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳•科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



> Report No.: ZR/2020/5000701 Page: 19 of 26

4.9 Test Setups

4.9.1 Test Setup 1



Ground Reference Plane

4.9.2 Test Setup 2





Figure 1. 30MHz to 1GHz





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document to content be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or or and : CN. Doccheck@ass.com

 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057
 t (86-755) 26012053 f (86-755) 26710594
 www.sgsgroup.com.cn

 中国・深圳・科技図中区M-10栋一号厂房
 邮编: 518057
 t (86-755) 26012053 f (86-755) 26710594
 sgs.china@sgs.com



> Report No.: ZR/2020/5000701 Page: 20 of 26

4.9.3 Test Setup 3




Figure 1. Below 30MHz





Figure 2. 30MHz to 1GHz






Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-enD-conditions/T

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 •深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



> Report No.: ZR/2020/5000701 Page: 21 of 26

4.9.4 Test Setup 4



Ground Reference Plane



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation on liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excore a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: (N_Doccheck@egs.com)

No. Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技國中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



> Report No.: ZR/2020/5000701 Page: 22 of 26

4.10 Test Conditions

Test Case		Test Conditions			
		Test Environment	Ambient Climate & Rated Voltage		
	Average	Test Setup	Test Setup 1		
	Power, Total	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
Transmit Output		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2		
Power Data	Average	Test Environment	Ambient Climate & Rated Voltage		
	Power,	Test Setup	Test Setup 1		
	Spectral Density (if	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
	required)	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
		Test Mode	UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Peak-to-Ave	erane Ratio	Test Setup	Test Setup 1		
Peak-to-Average Ratio (if required)	•	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
		Test Mode	UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Madulation		Test Setup	Test Setup 1		
Modulation Characteristics		RF Channels (TX)	M (M= middle channel)		
		Test Mede	GSM/TM1;GSM/TM2;UMTS/TM1;		
		Test Mode	UMTS/TM2; LTE/TM1;LTE/TM2		
Bandwidth	Occupied Bandwidth	Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 1		
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unavful and offenders may be prosecuted to the fulles extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of lesting inspection report & certificate, please contact us at telephone: (86-755)80071443, or email: CN_Doccheck@sgs.com

or email: <u>CN_Doccheck@ags.com</u> No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



Report No.: ZR/2020/5000701 Page: 23 of 26

			UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
	Emission Bandwidth	Test Setup	Test Setup 1		
(if		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Dond Edgo	-	Test Setup	Test Setup 1		
Band Edges Compliance		RF Channels (TX)	L, H (L= low channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
		Test Mode	UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Spurious Er	mission at	Test Setup	Test Setup 1		
Antenna Te	erminals	RF Channels	L,M, H		
		(TX)	(L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;UMTS/TM1; LTE/TM1		
		Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 2		
Field Streng Spurious Ra	-	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;UMTS/TM2; LTE/TM1;LTE/TM2;		
			Remark: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.		
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage;		
Frequency Stability		Environment	(2) VL, VN and VH of Rated Voltage at Ambient Climate.		
		Test Setup	Test Setup 4		
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parilies to a transaction from exercising all their rights and obligations under the transaction documents. This document to exonerate parilies to a except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) is test and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report a certificate, please contact us at teephone: (86-755) 83071443, or email: CN_Doccheck@ags.com

or email: <u>CN_Deccheck@ssg.com</u> No.1Workshop.M-10.Midde Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 · 深圳 · 科技因中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



> Report No.: ZR/2020/5000701 Page: 24 of 26

5 Main Test Instruments

RE in Chamber						
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm- dd)	Cal.Due date (yyyy-mm- dd)	
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018/3/13	2021/3/12	
Spectrum Analyzer (20Hz-43GHz)	Rohde & Schwarz	FSU43	SEM004-08	2020/4/16	2021/4/15	
BiConiLog Antenna (26- 3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017/6/27	2020/6/26	
Horn Antenna (800MHz- 18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/4/13	2021/4/12	
Horn Antenna (15-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017/10/17	2020/10/16	
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2019/7/14	2020/7/14	
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA- 0118- 352810	SEM005-05	2019/7/14	2020/7/14	
Pre-Amplifier (0.1- 26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	EMC2063	2019/9/20	2020/9/19	
Pre-amplifier (26-40GHz)	Compliance Directions Systems Inc.	PAP-2640- 50	SEM005-08	2020/4/16	2021/4/15	
Band filter	N/A	N/A	N/A	N/A	N/A	
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A	
Coaxial Cable	SGS	N/A	SEM026-01	2019/7/12	2020/7/11	
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2020/4/16	2021/4/15	
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2020/1/13	2021/1/2	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation on liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excore a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: (N_Doccheck@egs.com)

or email: <u>CN_Deccheck@ssg.com</u> No.1Workshop.M-10.Midde Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 · 深圳 · 科技因中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



> Report No.: ZR/2020/5000701 Page: 25 of 26

RF conducted test						
Test Equipment	Manufacturer	Model No.	Inventory	Cal. date	Cal.Due date	
			No.	(yyyy-mm- dd)	(yyyy-mm- dd)	
Dual Output Mobile Communication DC Source	Agilent Technologies Inc	66311B	W009-09	2019/10/22	2020/10/21	
Signal Analyzer	Rohde & Schwarz	FSV	W005-02	2020/4/16	2021/4/15	
Coaxial Cable	SGS	N/A	SEM031-01	2019/7/12	2020/7/11	
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A	
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019/10/22	2020/10/21	
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	HTC-1	W006-17	2019/10/22	2020/10/21	
Temperature Chamber	GIANT FORCE	ICT-150- 40-CP-AR	W027-03	2019/10/22	2020/10/21	
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2020/4/16	2021/4/15	
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2019/10/22	2020/10/21	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation on liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excore a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: (N_Doccheck@egs.com)

of email: <u>CN_DeceneeKeesgs.com</u> No.1Workshop,M-10, Midd escloin, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 · 深圳 · 科技园中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.com



Report No.: ZR/2020/5000701 Page: 26 of 26

6 Measurement Uncertainty

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item	Extended Uncertainty	Data	
Transmit Output Power Data	Power [dBm]	U =±0.37 dB	
Bandwidth	Magnitude [%]	U =± 0.2%	
Band Edge Compliance	Disturbance Power [dBm]	U = ±2.0 dB	
Spurious Emissions, Conducted	Disturbance Power [dBm]	U = ±2.0 dB	
		For 3 m Chamber:	
		$U = \pm 4.5 \text{ dB}$ (30 MHz to 1GHz)	
Field Strength of Spurious	ERP[dBm]/EIRP [dBm]	$U = \pm 3.3 \text{ dB}$ (above 1 GHz)	
Radiation		For 10 m Chamber:	
		$U = \pm 4.5 \text{ dB}$ (30 MHz to 1GHz)	
		$U = \pm 3.2 \text{ dB}$ (above 1 GHz)	
Frequency Stability	Frequency Accuracy [ppm]	U = ±0.24 ppm	

7 Appendixes

Appendix A	Photographs of Set-Up for ZR/2020/50007	
Appendix B.1	GSM 850 & 1900	
Appendix B.2	WCDMA Band II & V	
Appendix B.3	LTE Band 5	
Appendix B.4	LTE Band 7	
Appendix B.5	LTE Band 38	
Appendix B.6	LTE Band 41	

The End



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content to enter or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) lessed and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)83071443,

No. Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com