FCC RF Test Report

APPLICANT : Motorola Mobility LLC EQUIPMENT : Mobile Cellular Phone

BRAND NAME : Motorola

MODEL NAME : XT2093-3, XT2093DL, XT2093-4, XT2093-2,

XT2093-2PP

FCC ID : IHDT56ZD4

STANDARD : 47 CFR Part 2, and 90(S)

CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Aug. 07, 2020 and completely tested on Aug. 15, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Reviewed by: Jason Jia / Supervisor

JasonJia

Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 1 of 21 Report Issued Date : Sep. 16, 2020

Report No.: FW080709B

Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMAF	RY OF TEST RESULT	4
1	GENI	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	
	1.3	Feature of Equipment Under Test	
	1.4	Product Specification of Equipment Under Test	
	1.5	Modification of EUT	
	1.6	Specification of Accessory	6
	1.7	Maximum Conducted Power, Frequency Tolerance and Emission Designator	7
	1.8	Testing Site	
	1.9	Test Software	
	1.10	Applied Standards	8
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	9
	2.1	Test Mode	9
	2.2	Connection Diagram of Test System	10
	2.3	Support Unit used in test configuration and system	10
	2.4	Measurement Results Explanation Example	11
	2.5	Frequency List of Low/Middle/High Channels	11
3	TEST	RESULT	12
	3.1	Conducted Output Power Measurement	12
	3.2	99% Occupied Bandwidth and 26dB Bandwidth Measurement	
	3.3	Emissions Mask Measurement	
	3.4	Emissions Mask – Out Of Band Emissions Measurement	
	3.5	Field Strength of Spurious Radiation Measurement	
	3.6	Frequency Stability Measurement	19
4	LIST	OF MEASURING EQUIPMENT	21
5	UNCI	ERTAINTY OF EVALUATION	22
A P		IV A TEST DESULTS OF CONDUCTED TEST	
AΡ	PEND	IX A. TEST RESULTS OF CONDUCTED TEST	
ΑP	PEND	IX B. TEST RESULTS OF RADIATED TEST	

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 2 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FW080709B	Rev. 01	Initial issue of report	Sep. 16, 2020

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4

: 3 of 21 Page Number Report Issued Date: Sep. 16, 2020 Report Version : Rev. 01

Report No.: FW080709B

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< 50+10log ₁₀ (P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 51.28 dB at 3258.000 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 4 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Feature of Equipment Under Test

	Product Feature
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2093-3, XT2093DL, XT2093-4, XT2093-2, XT2093-2PP
FCC ID	IHDT56ZD4
	CDMA/GSM/WCDMA/LTE
	WLAN 2.4GHz 802.11b/g/n HT20
EUT cumports Padias application	WLAN 5GHz 802.11a/n HT20/HT40
EUT supports Radios application	WLAN 5GHz 802.11ac VHT20/VHT40/VHT80
	Bluetooth BR/EDR/LE
	FM Receiver and GNSS
IMEI Code	Conducted: 355567110012068/355567110012001
IIWEI Code	Radiation: 355567110009700
HW Version	DVT2
SW Version	QZA30.32
EUT Stage	Identical Prototype

Report No.: FW080709B

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard							
Tx Frequency	814.7 ~ 823.3 MHz						
Rx Frequency	859.7 ~ 868.3 MHz						
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz						
Maximum Output Power to Antenna	23.24 dBm						
Antenna Gain	-2.50 dBi						
Type of Modulation	QPSK / 16QAM / 64QAM						

 Sporton International (Kunshan) Inc.
 Page Number
 : 5 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Sep. 16, 2020

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

 FCC ID: IHDT56ZD4
 Report Template No.: BU5-FWLTE Version 2.0

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory								
AC Adapter 1	Brand Name	Motorola (Salcomp)	Model Name	MC-101				
AC Adapter 2	Brand Name	Motorola (Chenyang)	Model Name	MC-101				
Battery	Brand Name	Motorola (ATL)	Model Name	JK50				
USB Cable 1	Brand Name	Motorola (saibao)	Model Name	SC18C24367				
USB Cable 2	Brand Name	Motorola (BSC)	Model Name	SC18C24368				

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 6 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

1.7 Maximum Conducted Power, Frequency Tolerance and Emission Designator

FCC Rule	System	Type of Modulation	BW	Frequency Tolerance (ppm)	Emission Designator	Maximum Conducted power(W)
Part 90S	LTE Band 26	QPSK	1.4 MHz	-	1M09G7D	0.2109
Part 90S	LTE Band 26	16QAM	1.4 MHz	-	1M10W7D	0.1879
Part 90S	LTE Band 26	64QAM	1.4 MHz	-	1M10W7D	0.1361
Part 90S	LTE Band 26	QPSK	3 MHz	-	2M72G7D	0.2080
Part 90S	LTE Band 26	16QAM	3 MHz	-	2M73W7D	0.1770
Part 90S	LTE Band 26	64QAM	3 MHz	-	2M73W7D	0.1377
Part 90S	LTE Band 26	QPSK	5 MHz	-	4M50G7D	0.2070
Part 90S	LTE Band 26	16QAM	5 MHz	-	4M52W7D	0.1762
Part 90S	LTE Band 26	64QAM	5 MHz	-	4M50W7D	0.1371
Part 90S	LTE Band 26	QPSK	10 MHz	0.0040	9M03G7D	0.2094
Part 90S	LTE Band 26	16QAM	10 MHz	-	9M05W7D	0.1837
Part 90S	LTE Band 26	64QAM	10 MHz	-	9M03W7D	0.1368
Part 90S	LTE Band 26	QPSK	15 MHz	-	13M5G7D	0.2056
Part 90S	LTE Band 26	16QAM	15 MHz	-	13M4W7D	0.1905
Part 90S	LTE Band 26	64QAM	15 MHz	-	13M5W7D	0.1330

1.8 Testing Site

<FCC>-KS

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.							
	No. 1098, Pengxi North Road, Kunshan Economic Development Zone							
Test Site Location	Jiangsu Province 215300 People's Republic of China							
rest one Location	TEL: +86-512-57900158							
	FAX: +86-512-57900958							
	Sporton Site No.	FCC Designation No.	FCC Test Firm					
Test Site No.	Sporton Site No.	i CC Designation No.	Registration No.					
	03CH04-KS TH01-KS	CN1257	314309					

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 7 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

1.9 Test Software

Item	Site	Manufacture	Name	Version	
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a	

1.10 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 8 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.


		Bandwidth (MHz)			Modulation			RB#			Test Channel					
Test Items	Band	1.4	3	5	10	15	20	QPSK	16QAM	64QA M	1	Half	Full	L	М	Н
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	٧	٧	v	v	٧	-	v	v	v			٧	v	v	v
Emission masks In-band emissions	26	>	٧	v	v	٧	-	v	v	v	v		٧	٧		v
Emission masks – Out of band	26	٧	٧	٧	v	٧		v	v	v	v			٧	v	v
emissions																
Frequency Stability	26				v	v	-	v					٧		v	
Radiated Spurious Emission	26		Worst Case							v						
Note	2. The 3. LTE 15M	The mark "-" means that this bandwidth is not supported.														

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 9 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment Trade Name		Model No.	FCC ID	Data Cable	Power Cord	
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m	

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 10 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example:

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 4.2 + 10 = 14.2 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List								
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest				
45	Channel	26765	-	-				
15	Frequency	821.5	-	-				
10	Channel	-	26740	-				
10	Frequency	-	819	-				
5	Channel	26715	26740	26765				
5	Frequency	816.5	819	821.5				
3	Channel	26705	26740	26775				
3	Frequency	815.5	819	822.5				
1.4	Channel	26697	26740	26783				
1.4	Frequency	814.7	819	823.3				

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 11 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through the system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

Page Number : 12 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 13 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

- (a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:
- (1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log₁₀(f/6.1) decibels or 50 + 10 Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.
- (2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.3.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- 2. The emissions mask of low and high channels for the highest RF powers were measured.
- The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
- 4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

Report No.: FW080709B

Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 15 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

3.4 Emissions Mask - Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
 The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 16 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[Watts])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

- The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)


Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 17 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01


Report No.: FW080709B

3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 18 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation

- 1. The EUT was set up in the thermal chamber and connected with the base station.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three
 hours. Power was applied and the maximum change in frequency was recorded within one
 minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.


3.6.4 Test Procedures for Voltage Variation

- 1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
- The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
- 3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
- 4. battery operating end point, which shall be specified by the manufacturer.
- 5. The variation in frequency was measured for the worst case.

Page Number : 19 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

3.6.5 Test Setup



3.6.6 **Test Result of Temperature Variation**

Please refer to Appendix A.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4

Page Number : 20 of 21 Report Issued Date: Sep. 16, 2020 Report Version : Rev. 01

Report No.: FW080709B

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 02, 2019	Aug. 13, 2020	Nov. 01, 2020	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Nov. 18, 2019	Aug. 13, 2020	Nov. 17, 2020	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 15, 2020	Aug. 15, 2020	Apr. 14, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jan. 03, 2020	Aug. 15, 2020	Jan. 02, 2021	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 20, 2020	Aug. 15, 2020	Apr. 19, 2021	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2019	Aug. 15, 2020	Nov. 09, 2020	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 03, 2020 Aug. 15, 2020		Jan. 02, 2021	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 08, 2020 Aug. 15, 202		Jan. 07, 2021	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Jan. 03, 2020	Aug. 15, 2020	Jan. 02, 2021	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct.15, 2019	Aug. 15, 2020	Oct.14, 2020	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 15, 2020	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 15, 2020	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 15, 2020	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 21 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of	3.3dB
Confidence of 95% (U = 2Uc(y))	3.305

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of	2.8dB
Confidence of 95% (U = 2Uc(y))	2.0UB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of	2.8dB
Confidence of 95% (U = 2Uc(y))	Z.OUD

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : 22 of 21
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

Report No.: FW080709B

Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power)

LTE Band 26

LIE Ballu 2				Power	Power	Power
BW [MHz]	Modulation	RB Size	RB Offset	Low	Middle	High
				Ch. / Freq.	Ch. / Freq.	Ch. / Freq.
	Cha	nnel	26765			
	Frequen	cy (MHz)	821.5			
15	QPSK	1	0	23.09		
15	QPSK	1	37	23.13		
15	QPSK	1	74	23.12		
15	QPSK	36	0	22.40		
15	QPSK	36	20	22.11		
15	QPSK	36	39	21.99		
15	QPSK	75	0	22.22		
15	16QAM	1	0	22.76		
15	16QAM	1	37	22.45		
15	16QAM	1	74	22.80		
15	16QAM	36	0	21.37		
15	16QAM	36	20	20.99		
15	16QAM	36	39	21.31		
15	16QAM	75	0	21.03		
15	64QAM	1	0	20.93		
15	64QAM	1	37	20.95		
15	64QAM	1	74	21.24		
15	64QAM	36	0	20.12		
15	64QAM	36	20	19.79		
15	64QAM	36	39	19.95		
15	64QAM	75	0	19.81		

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4

Page Number : A1 of A51 Report Issued Date: Sep. 16, 2020 Report Version

Report No.: FW080709B

: Rev. 01

	Cha	nnel	26740		
	Frequen	cy (MHz)	819		
10	QPSK	1	0	23.21	
10	QPSK	1	25	23.01	
10	QPSK	1	49	23.12	
10	QPSK	25	0	22.21	
10	QPSK	25	12	22.09	
10	QPSK	25	25	22.17	
10	QPSK	50	0	22.04	
10	16QAM	1	0	22.48	
10	16QAM	1	25	22.49	
10	16QAM	1	49	22.64	
10	16QAM	25	0	21.11	
10	16QAM	25	12	21.10	
10	16QAM	25	25	21.25	
10	16QAM	50	0	21.14	
10	64QAM	1	0	21.29	
10	64QAM	1	25	21.33	
10	64QAM	1	49	21.36	
10	64QAM	25	0	19.95	
10	64QAM	25	12	19.86	
10	64QAM	25	25	20.04	
10	64QAM	50	0	19.93	

Page Number : A2 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



	Cha	nnel	26715	26740	26765		
	Frequen	cy (MHz)	816.5	819	821.5		
5	QPSK	1	0	22.83	23.10	23.09	
5	QPSK	1	12	22.92	23.01	23.09	
5	QPSK	1	24	23.06	23.16	22.88	
5	QPSK	12	0	22.09	22.14	22.16	
5	QPSK	12	7	21.97	22.20	22.06	
5	QPSK	12	13	21.98	22.13	22.09	
5	QPSK	25	0	21.98	22.12	22.17	
5	16QAM	1	0	22.26	22.46	22.46	
5	16QAM	1	12	22.04	22.18	22.25	
5	16QAM	1	24	22.45	22.46	22.13	
5	16QAM	12	0	21.08	21.13	21.14	
5	16QAM	12	7	21.06	21.19	21.08	
5	16QAM	12	13	20.98	21.14	21.13	
5	16QAM	25	0	20.98	21.13	21.04	
5	64QAM	1	0	21.23	21.22	21.34	
5	64QAM	1	12	21.13	20.95	21.37	
5	64QAM	1	24	21.09	21.23	21.00	
5	64QAM	12	0	19.85	19.93	19.87	
5	64QAM	12	7	19.75	19.91	19.92	
5	64QAM	12	13	19.79	19.95	19.82	
5	64QAM	25	0	19.75	19.84	19.89	

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A3 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



	Cha	nnel	26705	26740	26775	
	Frequen	cy (MHz)	815.5	819	822.5	
3	QPSK	1	0	23.11	23.09	23.10
3	QPSK	1	8	23.08	23.18	23.06
3	QPSK	1	14	22.88	23.16	22.87
3	QPSK	8	0	22.01	22.08	22.02
3	QPSK	8	4	22.05	22.20	22.02
3	QPSK	8	7	21.97	22.11	22.04
3	QPSK	15	0	22.08	22.06	22.04
3	16QAM	1	0	22.37	22.30	22.31
3	16QAM	1	8	22.34	22.47	22.43
3	16QAM	1	14	22.16	22.48	22.45
3	16QAM	8	0	21.14	21.14	21.08
3	16QAM	8	4	21.18	21.22	20.99
3	16QAM	8	7	20.93	21.14	21.08
3	16QAM	15	0	21.01	21.07	21.04
3	64QAM	1	0	21.02	21.13	21.39
3	64QAM	1	8	21.23	21.29	21.14
3	64QAM	1	14	21.20	21.05	21.07
3	64QAM	8	0	19.80	19.79	19.80
3	64QAM	8	4	19.84	19.97	19.84
3	64QAM	8	7	19.68	19.91	19.79
3	64QAM	15	0	19.78	19.84	19.82

Page Number : A4 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



	Cha	nnol -	26607	26740	26792	
		nnel	26697	26740	26783	
	Frequen	cy (MHz)	814.7	819	823.3	
1.4	QPSK	1	0	23.03	23.06	23.08
1.4	QPSK	1	3	<mark>23.24</mark>	23.11	23.10
1.4	QPSK	1	5	23.09	23.23	23.06
1.4	QPSK	3	0	23.09	<mark>23.24</mark>	23.22
1.4	QPSK	3	1	23.15	23.21	23.20
1.4	QPSK	3	3	23.17	23.09	22.96
1.4	QPSK	QPSK 6		22.11	22.16	22.10
1.4	16QAM	1	0	22.46	22.43	22.35
1.4	16QAM	1	3	22.44	22.61	22.40
1.4	16QAM	1	5	22.44	22.74	22.32
1.4	16QAM	3	0	22.07	22.14	22.22
1.4	16QAM	3	1	22.20	22.31	22.23
1.4	16QAM	3	3	22.12	22.28	22.15
1.4	16QAM	6	0	21.14	21.24	21.19
1.4	64QAM	1	0	21.22	21.29	21.06
1.4	64QAM	1	3	21.13	21.01	21.03
1.4	64QAM	1	5	21.29	21.34	21.13
1.4	64QAM	3	0	21.01	20.90	21.06
1.4	64QAM	3	1	21.15	21.33	21.07
1.4	64QAM	3	3	21.07	21.25	20.95
1.4	64QAM	6	0	19.97	19.79	19.75


Page Number : A5 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01

LTE Band 26_Part 90S


Peak-to-Average Ratio

Mode									
Mod.	QP	SK	160	QAM	Limit: 13dB				
RB Size	1RB Full RB		1RB	Full RB	Result				
Lowest CH			-	-					
Middle CH	5.25	5.68	6.06	6.38	PASS				
Highest CH	-	-	-	-					
Mode		LTE Band 26 / 10MHz							
Mod.	64C	AM			Limit: 13dB				
RB Size	1RB	Full RB			Result				
Lowest CH	-	-	-	-					
Middle CH	6.12	6.78	-	-	PASS				
Highest CH	-	-	-	-					

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A6 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



Page Number : A7 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




Page Number : A8 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01


26dB Bandwidth

Mode		LTE Band 26 : 26dB BW(MHz)										
BW	1.4	ИHz	3M	3MHz 5MHz		Hz	10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.28	1.28	2.97	3.00	4.98	4.96	-	-	14.48	14.27	-	-
Middle CH	1.29	1.26	3.07	2.99	4.98	4.88	9.67	9.75	-	-	-	-
Highest CH	1.26	1.26	3.05	2.99	4.89	4.92	-	-	-	-	-	-
Mode					LTE Ba	and 26 :	26dB BV	V(MHz)				
BW	1.4	ИHz	3MHz		5MHz		101	ЛHz	15N	ЛHz	201	ИHz
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.26	-	3.00	-	4.94	-	-	-	14.27	-	-	-
Middle CH	1.26	-	3.03	-	4.88	-	9.79	-	-	-	-	-
Highest CH	1.30	-	3.02	-	4.91	-	-	-	-	-	-	-


TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A9 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




Page Number : A10 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




Page Number : A11 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




Page Number : A12 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




Page Number : A13 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



Page Number : A14 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



Page Number : A15 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



Page Number : A16 of A51 Report Issued Date: Sep. 16, 2020

Report No.: FW080709B

Report Version : Rev. 01

Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.10	2.72	2.70	4.50	4.48	-	-	13.46	13.43	-	-
Middle CH	1.09	1.09	2.72	2.70	4.50	4.48	9.03	9.05	-	-	-	-
Highest CH	1.08	1.08	2.71	2.73	4.49	4.52	-	-	-	-	-	-
Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.10	-	2.73	-	4.48	-	-	-	13.46	-	-	-
Middle CH	1.09	-	2.73	-	4.50	-	9.03	-	-	-	-	-
Highest CH	1.10	-	2.72	-	4.49	-	-	-	-	-	-	-


Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4


: A17 of A51 Page Number Report Issued Date: Sep. 16, 2020

Report No.: FW080709B


Report Version : Rev. 01




Page Number : A18 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




Page Number : A19 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




Page Number : A20 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




Page Number : A21 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



Page Number : A22 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A23 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



Page Number : A24 of A51 Report Issued Date: Sep. 16, 2020

Report No.: FW080709B

Report Version : Rev. 01


Conducted Band Edge

Sporton International (Kunshan) Inc.


TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A25 of A51
Report Issued Date : Sep. 16, 2020

Report No.: FW080709B


Report Version : Rev. 01




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A26 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A27 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A28 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A29 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A30 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A31 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: IHDT56ZD4 Page Number : A32 of A51
Report Issued Date : Sep. 16, 2020
Report Version : Rev. 01