



# FCC RF Test Report

**APPLICANT** : Motorola Mobility LLC  
**EQUIPMENT** : Mobile Cellular Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT2093-3, XT2093DL, XT2093-4,  
XT2093-2, XT2093-2PP  
**FCC ID** : IHDT56ZD4  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The product was received on Aug. 07, 2020 and testing was completed on Sep. 03, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International (ShenZhen) Inc.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



**Sporton International (Kunshan) Inc.**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 5

    1.5 Modification of EUT ..... 6

    1.6 Specification of Accessory..... 6

    1.7 Testing Location ..... 7

    1.8 Test Software..... 8

    1.9 Applicable Standards..... 8

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 9**

    2.1 Carrier Frequency and Channel ..... 9

    2.2 Test Mode ..... 10

    2.3 Connection Diagram of Test System ..... 11

    2.4 Support Unit used in test configuration and system ..... 12

    2.5 EUT Operation Test Setup ..... 12

    2.6 Measurement Results Explanation Example..... 12

**3 TEST RESULT ..... 13**

    3.1 6dB and 99% Bandwidth Measurement ..... 13

    3.2 Output Power Measurement..... 15

    3.3 Power Spectral Density Measurement ..... 16

    3.4 Conducted Band Edges and Spurious Emission Measurement ..... 18

    3.5 Radiated Band Edges and Spurious Emission Measurement ..... 28

    3.6 AC Conducted Emission Measurement..... 32

    3.7 Antenna Requirements ..... 34

**4 LIST OF MEASURING EQUIPMENT ..... 35**

**5 UNCERTAINTY OF EVALUATION ..... 36**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX C. RADIATED SPURIOUS EMISSION**

**APPENDIX D. DUTY CYCLE PLOTS**

**APPENDIX E. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 30dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.07 dB at 4926.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.61 dB at 0.668 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

Motorola Mobility LLC  
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2 Manufacturer

Motorola Mobility LLC  
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2093-3, XT2093DL, XT2093-4, XT2093-2, XT2093-2PP
FCC ID	IHDT56ZD4
EUT supports Radios application	CDMA/GSM/WCDMA/LTE WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE FM Receiver and GNSS
IMEI Code	Conducted: 355567110011052 Conduction: 355567110009700 Radiation: 35556711000994
HW Version	DVT2
SW Version	QZA30.32
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum Output Power to antenna	802.11b : 18.70 dBm (0.0741 W) 802.11g : 18.80 dBm (0.0759 W) 802.11n HT20 : 17.90 dBm (0.0617 W)
99% Occupied Bandwidth	802.11b : 13.99MHz 802.11g : 16.78MHz 802.11n HT20 : 17.93MHz
Antenna Type / Gain	Loop Antenna with gain -3.01 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola (Salcomp)	Model Name	MC-101
AC Adapter 2	Brand Name	Motorola (Chenyang)	Model Name	MC-101
Battery	Brand Name	Motorola (ATL)	Model Name	JK50
USB Cable 1	Brand Name	Motorola (saibao)	Model Name	SC18C24367
USB Cable 2	Brand Name	Motorola (BSC)	Model Name	SC18C24368



### 1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH05-KS	CN1257	314309

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

<b>Test Firm</b>	Sporton International (Shenzhen) Inc.		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-SZ	CN1256	421272

Test data subcontracted: Conducted test items in section 3.1~3.4 of this report.



### 1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH05-KS	AUDIX	E3	6.2009-8-24al
2.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.





## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z, X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		



## 2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0


Test Cases	
<b>AC Conducted Emission</b>	Mode 1 :GSM850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable 1(Charging from Adapter 2) + Earphone
<b>Remark:</b> For Radiated Test Cases, The tests were performance with Adapter 1, Earphone and USB Cable 1.	

### 2.3 Connection Diagram of Test System

For Radiated Emission:



For Conducted Emission:





## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded, 1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
5.	SD Card	Kingston	8GB	N/A	N/A	N/A
6.	Earphone	N/A	N/A	N/A	N/A	N/A

## 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 1.2 dB and 20dB attenuator.

$$Offset(dB) = RF\ cable\ loss(dB) + attenuator\ factor(dB).$$

$$= 1.2 + 20 = 21.2\ (dB)$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


##### 3.1.4 Test Setup





### 3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.2.3.2 Method AVGPM-G method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Average output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

#### 3.3.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.




### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.4.4 Test Setup







### 3.4.5 Test Result of Conducted Band Edges and Spurious Emission




Test Engineer : ZengMengHui	Temperature :	24~26°C
	Relative Humidity :	50~53%

Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----







Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----







Test Mode : 802.11b Test Channel : 11






Test Mode : 802.11g Test Channel : 01






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----


**100kHz PSD reference Level**



**Spurious Emission 30MHz~3GHz**





**Spurious Emission 2GHz~25GHz**







Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----










Test Mode : 802.11n HT20 Test Channel : 01







Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----





Test Mode :	802.11n HT20	Test Channel :	11
-------------	--------------	----------------	----





### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





### **3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### **3.5.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix C.

### **3.5.7 Duty Cycle**

Please refer to Appendix D.

### **3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix C.



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

#### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.



### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 17, 2020	Sep. 02, 2020~ Sep. 03, 2020	Apr. 16, 2021	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 26, 2019	Sep. 02, 2020~ Sep. 03, 2020	Dec. 25, 2020	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 26, 2019	Sep. 02, 2020~ Sep. 03, 2020	Dec. 25, 2020	Conducted (TH01-SZ)
EMI Test Receiver	Keysight	N9038A	MY572901 51	3Hz~8.5GHz;M ax 30dBm	Jul. 17, 2020	Aug. 27, 2020~ Sep. 02, 2020	Jul. 16, 2021	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 44	10Hz-44G,MAX 30dB	Apr. 15, 2020	Aug. 27, 2020~ Sep. 02, 2020	Apr. 14, 2021	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 10, 2019	Aug. 27, 2020~ Sep. 02, 2020	Nov. 09, 2020	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jun. 08, 2020	Aug. 27, 2020~ Sep. 02, 2020	Jun. 07, 2021	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 26, 2020	Aug. 27, 2020~ Sep. 02, 2020	Apr. 25, 2021	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2019	Aug. 27, 2020~ Sep. 02, 2020	Nov. 09, 2020	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Apr. 14, 2020	Aug. 27, 2020~ Sep. 02, 2020	Apr. 13, 2021	Radiation (03CH05-KS)
Amplifier	MITEQ	EM18G40GG A	060728	18~40GHz	Jan. 08, 2020	Aug. 27, 2020~ Sep. 02, 2020	Jan. 07, 2021	Radiation (03CH05-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2012228	1Ghz-18Ghz	Oct. 18, 2019	Aug. 27, 2020~ Sep. 02, 2020	Oct. 17, 2020	Radiation (03CH05-KS)
Amplifier	Keysight	83017A	MY532703 16	500MHz~26.5G Hz	Oct. 18, 2019	Aug. 27, 2020~ Sep. 02, 2020	Oct. 17, 2020	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Aug. 27, 2020~ Sep. 02, 2020	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 27, 2020~ Sep. 02, 2020	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 27, 2020~ Sep. 02, 2020	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 14, 2020	Aug. 26, 2020	Apr. 13, 2021	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 18, 2019	Aug. 26, 2020	Oct. 17, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Oct. 28, 2019	Aug. 26, 2020	Oct. 27, 2020	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 18, 2019	Aug. 26, 2020	Oct. 17, 2020	Conduction (CO01-KS)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------



## Appendix A. Conducted Test Results

Test Engineer:	Liu Qiu Qiu	Temperature:	21~25	°C
Test Date:	2020/9/2~2020/9/3	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 1		
11b	1Mbps	1	1	2412	13.99	8.07	0.50	Pass
11b	1Mbps	1	6	2437	14.04	8.07	0.50	Pass
11b	1Mbps	1	11	2462	13.89	8.05	0.50	Pass
11g	6Mbps	1	1	2412	16.73	15.34	0.50	Pass
11g	6Mbps	1	6	2437	16.78	15.52	0.50	Pass
11g	6Mbps	1	11	2462	16.68	15.50	0.50	Pass
HT20	MCS0	1	1	2412	17.88	15.94	0.50	Pass
HT20	MCS0	1	6	2437	17.93	15.12	0.50	Pass
HT20	MCS0	1	11	2462	17.88	15.46	0.50	Pass

**TEST RESULTS DATA**  
**Average Output Power**

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
					Ant 1	Ant 1	Ant 1	Ant 1	Ant 1	
11b	1Mbps	1	1	2412	18.30	30.00	-3.01	15.29	36.00	Pass
11b	1Mbps	1	6	2437	18.60	30.00	-3.01	15.59	36.00	Pass
11b	1Mbps	1	11	2462	18.70	30.00	-3.01	15.69	36.00	Pass
11g	6Mbps	1	1	2412	15.70	30.00	-3.01	12.69	36.00	Pass
11g	6Mbps	1	2	2417	18.20	30.00	-3.01	15.19	36.00	Pass
11g	6Mbps	1	6	2437	18.80	30.00	-3.01	15.79	36.00	Pass
11g	6Mbps	1	10	2457	17.90	30.00	-3.01	14.89	36.00	Pass
11g	6Mbps	1	11	2462	15.40	30.00	-3.01	12.39	36.00	Pass
HT20	MCS0	1	1	2412	15.00	30.00	-3.01	11.99	36.00	Pass
HT20	MCS0	1	2	2417	17.60	30.00	-3.01	14.59	36.00	Pass
HT20	MCS0	1	6	2437	17.90	30.00	-3.01	14.89	36.00	Pass
HT20	MCS0	1	10	2457	17.80	30.00	-3.01	14.79	36.00	Pass
HT20	MCS0	1	11	2462	15.00	30.00	-3.01	11.99	36.00	Pass

Note: Measured power (dBm) has offset with cable loss.




**TEST RESULTS DATA**  
**Average Power Spectral Density**

2.4GHz Band									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average PSD (dBm/3kHz)	DG (dBi)	Average PSD Limit (dBm/3kHz)	Pass/Fail
					Ant 1	Ant 1	Ant 1	Ant 1	
11b	1Mbps	1	1	2412	0.08	-8.11	-3.01	8.00	Pass
11b	1Mbps	1	6	2437	0.08	-7.53	-3.01	8.00	Pass
11b	1Mbps	1	11	2462	0.08	-7.29	-3.01	8.00	Pass
11g	6Mbps	1	1	2412	0.08	-11.47	-3.01	8.00	Pass
11g	6Mbps	1	6	2437	0.08	-7.05	-3.01	8.00	Pass
11g	6Mbps	1	11	2462	0.08	-10.99	-3.01	8.00	Pass
HT20	MCS0	1	1	2412	0.08	-11.59	-3.01	8.00	Pass
HT20	MCS0	1	6	2437	0.08	-8.44	-3.01	8.00	Pass
HT20	MCS0	1	11	2462	0.08	-11.29	-3.01	8.00	Pass

Measured power density (dBm) has offset with cable loss.




## Appendix B. AC Conducted Emission Test Results





Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS  
 Condition : 15C RSS247-QP LISN-N-191028-CN02 NEUTRAL

mode : Mode 1  
 : 355567110009700 #10

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.570	45.08	-10.92	56.00	34.60	0.24	10.24	QP
2	0.570	32.38	-13.62	46.00	21.90	0.24	10.24	Average
3 *	0.668	49.39	-6.61	56.00	38.90	0.25	10.24	QP
4	0.668	34.39	-11.61	46.00	23.90	0.25	10.24	Average
5	1.388	44.83	-11.17	56.00	34.20	0.40	10.23	QP
6	1.388	29.53	-16.47	46.00	18.90	0.40	10.23	Average
7	1.560	43.57	-12.43	56.00	32.90	0.44	10.23	QP
8	1.560	30.87	-15.13	46.00	20.20	0.44	10.23	Average
9	1.810	44.02	-11.98	56.00	33.30	0.49	10.23	QP
10	1.810	31.02	-14.98	46.00	20.30	0.49	10.23	Average
11	2.023	45.66	-10.34	56.00	34.90	0.53	10.23	QP
12	2.023	29.06	-16.94	46.00	18.30	0.53	10.23	Average
13	3.364	43.24	-12.76	56.00	32.30	0.69	10.25	QP
14	3.364	27.54	-18.46	46.00	16.60	0.69	10.25	Average
15	3.901	43.10	-12.90	56.00	32.11	0.74	10.25	QP
16	3.901	27.90	-18.10	46.00	16.91	0.74	10.25	Average
17	14.288	47.44	-12.56	60.00	35.20	1.85	10.39	QP
18	14.288	35.14	-14.86	50.00	22.90	1.85	10.39	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



## Appendix C. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b CH 01 2412MHz		2363.82	55.38	-18.62	74	48.42	31.18	7.44	31.66	295	322	P	H
		2389.95	44.33	-9.67	54	37.28	31.2	7.5	31.65	295	322	A	H
	*	2412	107.19	-	-	100	31.31	7.53	31.65	295	322	P	H
	*	2414	104.04	-	-	96.85	31.31	7.53	31.65	295	322	A	H
		2358.36	55.41	-18.59	74	48.46	31.18	7.44	31.67	111	246	P	V
		2389.95	44.49	-9.51	54	37.44	31.2	7.5	31.65	111	246	A	V
	*	2412	109.34	-	-	102.15	31.31	7.53	31.65	111	246	P	V
	*	2410	106.02	-	-	98.83	31.31	7.53	31.65	111	246	A	V
802.11b CH 11 2462MHz	*	2462	109.57	-	-	101.9	31.66	7.61	31.6	294	322	P	H
	*	2464	106.26	-	-	98.59	31.66	7.61	31.6	294	322	A	H
		2486.14	57.55	-16.45	74	49.72	31.77	7.64	31.58	294	322	P	H
		2483.5	46.8	-7.2	54	38.97	31.77	7.64	31.58	294	322	A	H
	*	2462	109.92	-	-	102.25	31.66	7.61	31.6	102	245	P	V
	*	2464	106.63	-	-	98.96	31.66	7.61	31.6	102	245	A	V
		2484.4	56.92	-17.08	74	49.09	31.77	7.64	31.58	102	245	P	V
		2483.5	46.71	-7.29	54	38.88	31.77	7.64	31.58	102	245	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz  
WIFI 802.11b (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11b CH 01 2412MHz		4824	52.5	-21.5	74	68.02	33.72	10.8	60.04	224	178	P	H
		4824	50.33	-3.67	54	65.85	33.72	10.8	60.04	224	178	A	H
		4824	47.85	-26.15	74	63.37	33.72	10.8	60.04	300	360	P	V
		4824	47.85	-26.15	74	63.37	33.72	10.8	60.04	300	360	P	V
802.11b CH 06 2437MHz		4872	52.56	-21.44	74	67.95	33.77	10.87	60.03	169	178	P	H
		4872	50.44	-3.56	54	65.83	33.77	10.87	60.03	169	178	A	H
		7308	42.83	-31.17	74	54.1	35.86	13.38	60.51	300	0	P	H
		4872	48.64	-25.36	74	64.03	33.77	10.87	60.03	174	164	P	V
		4872	46.67	-7.33	54	62.06	33.77	10.87	60.03	174	164	A	V
		7308	43.06	-30.94	74	54.33	35.86	13.38	60.51	300	360	P	V
802.11b CH 11 2462MHz		4926	52.84	-21.16	74	68.1	33.82	10.94	60.02	215	174	P	H
		4926	50.93	-3.07	54	66.19	33.82	10.94	60.02	215	174	A	H
		7386	43.12	-30.88	74	54.18	36.01	13.46	60.53	300	0	P	H
		4926	48.75	-25.25	74	64.01	33.82	10.94	60.02	300	360	P	V
		7386	42.66	-31.34	74	53.72	36.01	13.46	60.53	300	360	P	V
		4926	48.75	-25.25	74	64.01	33.82	10.94	60.02	300	360	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Path Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include data for 802.11g CH 01 (2412MHz) and 802.11g CH 02 (2417MHz).



802.11g CH 10 2457MHz	*	2483.8	61.99	-12.01	74	54.16	31.77	7.64	31.58	116	129	P	H
	*	2483.5	49.77	-4.23	54	41.94	31.77	7.64	31.58	116	129	A	H
		2456	110.52	-	-	102.85	31.66	7.61	31.6	116	129	P	H
	!	2458	102.39	-	-	94.72	31.66	7.61	31.6	116	129	A	H
	*	2483.98	61.36	-12.64	74	53.53	31.77	7.64	31.58	207	219	P	V
	*	2483.5	49.48	-4.52	54	41.65	31.77	7.64	31.58	207	219	A	V
		2458	110.88	-	-	103.21	31.66	7.61	31.6	207	219	P	V
	!	2458	102.5	-	-	94.83	31.66	7.61	31.6	207	219	A	V
802.11g CH 11 2462MHz	*	2464	108.05	-	-	100.38	31.66	7.61	31.6	294	324	P	H
	*	2464	99.8	-	-	92.13	31.66	7.61	31.6	294	324	A	H
		2483.98	62.06	-11.94	74	54.23	31.77	7.64	31.58	294	324	P	H
	!	2483.5	49.63	-4.37	54	41.8	31.77	7.64	31.58	294	324	A	H
	*	2462	108.95	-	-	101.28	31.66	7.61	31.6	100	246	P	V
	*	2464	100.45	-	-	92.78	31.66	7.61	31.6	100	246	A	V
		2483.68	64.6	-9.4	74	56.77	31.77	7.64	31.58	100	246	P	V
!	2483.5	50.89	-3.11	54	43.06	31.77	7.64	31.58	100	246	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz  
WIFI 802.11g (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11g CH 01 2412MHz		4824	44.28	-29.72	74	59.8	33.72	10.8	60.04	300	0	P	H
		4824	41.9	-32.1	74	57.42	33.72	10.8	60.04	300	360	P	V
802.11g CH 02 2417MHz		4836	48.42	-25.58	74	63.9	33.73	10.82	60.03	100	360	P	H
		7251	42.21	-31.79	74	53.61	35.77	13.33	60.5	100	360	P	H
		4836	46.14	-27.86	74	61.62	33.73	10.82	60.03	100	360	P	V
		7251	43.32	-30.68	74	54.72	35.77	13.33	60.5	100	360	P	V
802.11g CH 06 2437MHz		4872	52.04	-21.96	74	67.43	33.77	10.87	60.03	198	175	P	H
		4872	41.29	-12.71	54	56.68	33.77	10.87	60.03	198	175	P	H
		7308	43.22	-30.78	74	54.49	35.86	13.38	60.51	300	0	P	H
		4872	47.24	-26.76	74	62.63	33.77	10.87	60.03	300	360	P	V
		7308	43.02	-30.98	74	54.29	35.86	13.38	60.51	300	360	P	V
802.11g CH 10 2457MHz		4914	50.81	-23.19	74	66.12	33.8	10.91	60.02	100	360	P	H
		7368	41.99	-32.01	74	53.09	35.98	13.45	60.53	100	360	P	H
		4914	47	-27	74	62.31	33.8	10.91	60.02	100	360	P	V
		7368	42.57	-31.43	74	53.67	35.98	13.45	60.53	100	360	P	V
802.11g CH 11 2462MHz		4926	45.98	-28.02	74	61.24	33.82	10.94	60.02	300	0	P	H
		7386	42.23	-31.77	74	53.29	36.01	13.46	60.53	300	0	P	H
		4926	43.01	-30.99	74	58.27	33.82	10.94	60.02	300	360	P	V
		7386	43.16	-30.84	74	54.22	36.01	13.46	60.53	300	360	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 01 2412MHz		2389.56	60.67	-13.33	74	53.62	31.2	7.5	31.65	294	325	P	H
	!	2389.95	49.13	-4.87	54	42.08	31.2	7.5	31.65	294	325	A	H
	*	2418	106.33	-	-	99.12	31.31	7.53	31.63	294	325	P	H
	*	2414	98.02	-	-	90.83	31.31	7.53	31.65	294	325	A	H
		2389.04	63.02	-10.98	74	55.97	31.2	7.5	31.65	113	244	P	V
	!	2389.95	50.4	-3.6	54	43.35	31.2	7.5	31.65	113	244	A	V
	*	2414	108.98	-	-	101.79	31.31	7.53	31.65	113	244	P	V
802.11n HT20 CH 02 2417MHz	*	2389.95	61.68	-12.32	74	54.63	31.2	7.5	31.65	100	127	P	H
	*	2389.95	49	-5	54	41.95	31.2	7.5	31.65	100	127	A	H
		2420	110.15	-	-	102.79	31.43	7.56	31.63	100	127	P	H
	!	2418	101.82	-	-	94.61	31.31	7.53	31.63	100	127	A	H
	*	2389.82	58.13	-15.87	74	51.08	31.2	7.5	31.65	109	245	P	V
	*	2389.95	46.39	-7.61	54	39.34	31.2	7.5	31.65	109	245	A	V
		2416	109.07	-	-	101.86	31.31	7.53	31.63	109	245	P	V
!	2416	100.54	-	-	93.33	31.31	7.53	31.63	109	245	A	V	



802.11n HT20 CH 10 2457MHz	*	2483.86	59.78	-14.22	74	51.95	31.77	7.64	31.58	117	129	P	H
	*	2483.5	48.23	-5.77	54	40.4	31.77	7.64	31.58	117	129	A	H
		2460	109.07	-	-	101.4	31.66	7.61	31.6	117	129	P	H
	!	2458	100.71	-	-	93.04	31.66	7.61	31.6	117	129	A	H
	*	2483.98	57.83	-16.17	74	50	31.77	7.64	31.58	185	220	P	V
	*	2483.5	46.73	-7.27	54	38.9	31.77	7.64	31.58	185	220	A	V
		2458	109.56	-	-	101.89	31.66	7.61	31.6	185	220	P	V
	!	2458	100.58	-	-	92.91	31.66	7.61	31.6	185	220	A	V
802.11n HT20 CH 11 2462MHz	*	2464	106.49	-	-	98.82	31.66	7.61	31.6	280	2	P	H
	*	2460	98.18	-	-	90.51	31.66	7.61	31.6	280	2	A	H
		2484.16	59.15	-14.85	74	51.32	31.77	7.64	31.58	280	2	P	H
	!	2483.5	48.39	-5.61	54	40.56	31.77	7.64	31.58	280	2	A	H
	*	2464	107.5	-	-	99.83	31.66	7.61	31.6	100	245	P	V
	*	2460	99.19	-	-	91.52	31.66	7.61	31.6	100	245	A	V
		2483.86	62.62	-11.38	74	54.79	31.77	7.64	31.58	100	245	P	V
!	2483.5	50.49	-3.51	54	42.66	31.77	7.64	31.58	100	245	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 01 2412MHz		4824	43.87	-30.13	74	59.39	33.72	10.8	60.04	300	0	P	H
		4824	41.82	-32.18	74	57.34	33.72	10.8	60.04	300	360	P	V
802.11n HT20 CH 02 2417MHz		4836	47.39	-26.61	74	62.87	33.73	10.82	60.03	100	360	P	H
		7251	41.59	-32.41	74	52.99	35.77	13.33	60.5	100	360	P	H
		4836	45.17	-28.83	74	60.65	33.73	10.82	60.03	100	360	P	V
		7251	41.97	-32.03	74	53.37	35.77	13.33	60.5	100	360	P	V
802.11n HT20 CH 06 2437MHz		4872	49.75	-24.25	74	65.14	33.77	10.87	60.03	300	0	P	H
		7308	43.68	-30.32	74	54.95	35.86	13.38	60.51	300	0	P	H
		4872	45.82	-28.18	74	61.21	33.77	10.87	60.03	300	360	P	V
		7308	43.05	-30.95	74	54.32	35.86	13.38	60.51	300	360	P	V
802.11n HT20 CH 10 2457MHz		4914	49.34	-24.66	74	64.65	33.8	10.91	60.02	100	360	P	H
		7368	42.72	-31.28	74	53.82	35.98	13.45	60.53	100	360	P	H
		4914	46.75	-27.25	74	62.06	33.8	10.91	60.02	100	360	P	V
		7368	42.58	-31.42	74	53.68	35.98	13.45	60.53	100	360	P	V
802.11n HT20 CH 11 2462MHz		4926	43.46	-30.54	74	58.72	33.82	10.94	60.02	300	0	P	H
		7386	42.67	-31.33	74	53.73	36.01	13.46	60.53	300	0	P	H
		4926	41.9	-32.1	74	57.16	33.82	10.94	60.02	300	360	P	V
		7386	42.7	-31.3	74	53.76	36.01	13.46	60.53	300	360	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz  
2.4GHz WIFI 802.11b (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz 802.11b LF		30.97	18.66	-21.34	40	26.11	24.57	1.26	33.28	-	-	P	H
		95.96	20.44	-23.06	43.5	35.67	15.58	2.21	33.02	-	-	P	H
		152.22	22.16	-21.34	43.5	35.6	16.98	2.78	33.2	-	-	P	H
		276.38	28.31	-17.69	46	38.44	19.27	3.75	33.15	-	-	P	H
		868.08	28.52	-17.48	46	24.83	29.23	6.62	32.16	100	0	P	H
		972.84	29.48	-24.52	54	23.71	30.82	7	32.05	-	-	P	H
		30.97	23.54	-16.46	40	30.99	24.57	1.26	33.28	-	-	P	V
		52.31	25.26	-14.74	40	42.89	13.9	1.63	33.16	100	0	P	V
		95.96	19.66	-23.84	43.5	34.89	15.58	2.21	33.02	-	-	P	V
		273.47	20.83	-25.17	46	30.78	19.47	3.73	33.15	-	-	P	V
		861.29	27.91	-18.09	46	24.25	29.25	6.59	32.18	-	-	P	V
		967.02	29.03	-24.97	54	23.22	30.86	6.98	32.03	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



For co-location:

**2.4GHz 2400~2483.5MHz  
WIFI 802.11b (Band Edge @ 3m)**

WIFI Ant.	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11b CH 06 2437MHz& LTE13-BW5 M-MCH		2386.7	55.44	-18.56	74	48.39	31.2	7.5	31.65	100	276	P	H
	!	2389.95	43.99	-10.01	54	36.94	31.2	7.5	31.65	100	276	A	H
	*	2436	109.49	-	-	102.11	31.43	7.56	31.61	100	276	P	H
	*	2436	106.02	-	-	98.64	31.43	7.56	31.61	100	276	A	H
		2498.32	56.39	-17.61	74	48.39	31.89	7.67	31.56	100	276	P	H
		2484.16	44.93	-9.07	54	37.1	31.77	7.64	31.58	100	276	A	H
		2353.42	55.27	-18.73	74	48.32	31.18	7.44	31.67	373	307	P	V
		2389.3	43.81	-10.19	54	36.76	31.2	7.5	31.65	373	307	A	V
	*	2436	106.43	-	-	99.05	31.43	7.56	31.61	373	307	P	V
	*	2436	103.08	-	-	95.7	31.43	7.56	31.61	373	307	A	V
		2494	56	-18	74	48	31.89	7.67	31.56	373	307	P	V
	2484.04	44.81	-9.19	54	36.98	31.77	7.64	31.58	373	307	A	V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**2.4GHz 2400~2483.5MHz  
WIFI 802.11b (Harmonic @ 3m)**

WIFI Ant.	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11b CH 06 2437MHz& LTE13-BW5 M-MCH		4872	48.39	-25.61	74	63.78	33.77	10.87	60.03	300	0	P	H
		7308	42.63	-31.37	74	53.9	35.86	13.38	60.51	300	0	P	H
		4872	48.91	-25.09	74	64.3	33.77	10.87	60.03	300	360	P	V
		7308	42.61	-31.39	74	53.88	35.86	13.38	60.51	300	360	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Note symbol

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.



## Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	98.28	-	-	10Hz
802.11g	98.28	-	-	10Hz
802.11n HT20	98.16	-	-	10Hz


### 802.11b







802.11g



802.11n HT20

