



# FCC Test Report

**APPLICANT** : Motorola Mobility LLC  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT2095-1  
**FCC ID** : IHDT56ZJ4  
**STANDARD** : 47 CFR Part 15 Subpart B  
**CLASSIFICATION** : Certification

The product was received on Aug. 03, 2020 and testing was completed on Aug. 27, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Reviewed by: Jason Jia / Supervisor

Approved by: James Huang / Manager



**Sporton International (Kunshan) Inc.**

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1. GENERAL DESCRIPTION ..... 5**

    1.1. Applicant..... 5

    1.2. Manufacturer ..... 5

    1.3. Product Feature of Equipment Under Test ..... 5

    1.4. Product Specification of Equipment Under Test ..... 6

    1.5. Modification of EUT ..... 7

    1.6. Test Location ..... 7

    1.7. Test Software ..... 7

    1.8. Applicable Standards ..... 7

    1.9. Specification of Accessory ..... 8

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 9**

    2.1. Test Mode ..... 9

    2.2. Connection Diagram of Test System ..... 11

    2.3. Support Unit used in test configuration and system ..... 12

    2.4. EUT Operation Test Setup ..... 12

**3. TEST RESULT ..... 13**

    3.1. Test of AC Conducted Emission Measurement ..... 13

    3.2. Test of Radiated Emission Measurement ..... 17

**4. LIST OF MEASURING EQUIPMENT ..... 22**

**5. UNCERTAINTY OF EVALUATION ..... 23**

**APPENDIX A. SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC080310	Rev. 01	Initial issue of report	Sep. 21, 2020



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 4.23 dB at 0.151 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 7.95 dB at 31.940 MHz

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1. General Description

## 1.1. Applicant

Motorola Mobility LLC  
222 W, Merchandise Mart Plaza,Chicago,IL60654 USA

## 1.2. Manufacturer

Motorola Mobility LLC  
222 W, Merchandise Mart Plaza,Chicago,IL60654 USA

## 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Motorola
Model Name	XT2095-1
FCC ID	IHDT56ZJ4
EUT supports Radios application	GSM/WCDMA/LTE WLAN 802.11b/g/n HT20 Bluetooth BR/EDR/LE FM Receiver, and GNSS
IMEI Code	Conduction: 356916110016174/356916110016182 for Sample 1 356916110022578/356916110022586 for Sample3 Radiation: 356916110016174/356916110016182 for Sample 1 356916110022578/356916110022586 for Sample 3 356916110024939/356916110024947 for Sample 4
HW Version	DVT2
SW Version	QOF30.396
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are four types of EUT, for change note, please refer the product equality declaration exhibit submitted. According to the difference, we choose the sample 1 to full test and the sample 3/4 is verified.



### 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 66 : 2110.7 MHz~ 2179.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz FM : 88 MHz ~ 108 MHz
<b>Antenna Type</b>	WWAN : Fixed Internal Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna FM : External Earphone Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) :π/4-DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK FM

GNSS=Galileo + GLONASS + GPS



### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH02-KS	CN1257	314309

### 1.7. Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

### 1.9 Specification of Accessory

Specification of Accessory			
AC Adapter 1(US)	Brand Name	Motorola(Chenyang)	Model Name SC-61
AC Adapter 1(EU)	Brand Name	Motorola(Chenyang)	Model Name SC-62
AC Adapter 1(UK)	Brand Name	Motorola(Chenyang)	Model Name SC-63UK
AC Adapter 1(AR)	Brand Name	Motorola(Chenyang)	Model Name SC-64
AC Adapter 1(EU)	Brand Name	Motorola(Chenyang)	Model Name SC-62
AC Adapter 1(UK)	Brand Name	Motorola(Chenyang)	Model Name SC-63UK
AC Adapter 2(US)	Brand Name	Motorola(Acbel)	Model Name SC-61
AC Adapter 2(EU)	Brand Name	Motorola(Acbel)	Model Name SC-62
AC Adapter 2(AR)	Brand Name	Motorola(Acbel)	Model Name SC-64
AC Adapter 2(Chile)	Brand Name	Motorola(Acbel)	Model Name SC-62
AC Adapter 3(AU)	Brand Name	Motorola(Chenyang)	Model Name MC-105
AC Adapter 3(BR)	Brand Name	Motorola(Chenyang)	Model Name MC-107
AC Adapter 4(BR)	Brand Name	Motorola(Flex)	Model Name SC-47
AC Adapter 5(BR)	Brand Name	Motorola(Cliptech)	Model Name SC-47
AC Adapter 6(BR)	Brand Name	Motorola(Flex)	Model Name MC-107
AC Adapter 7(BR)	Brand Name	Motorola(Salcomp)	Model Name MC-107
Battery 1	Brand Name	Motorola(ATL)	Model Name KG40
Battery 2	Brand Name	Motorola(SCUD)	Model Name KG40
Earphone	Brand Name	Motorola(NEW LEADER)	Model Name NLD-EM301K-01SF
USB Cable 1	Brand Name	Motorola(Washin)	Model Name HX-ZN-04
USB Cable 2	Brand Name	Motorola(Ju wei)	Model Name JWUB1472-ZN01H
USB Cable 3	Brand Name	Motorola(I SHENG)	Model Name SC18C28955





## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 Rx (Middle) + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 1(Charging from Adapter 1) + Battery 1 for Sample 1
	Mode 2: WCDMA FDD II Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 2) + Battery 1 for Sample 1
	Mode 3: LTE Band 2 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + MP4 + USB Cable 3(Charging from Adapter 3) + Battery 1 for Sample 1
	Mode 4: LTE Band 4 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + FM Rx(98MHz) + USB Cable 3(Charging from Adapter 4) + Battery 1 for Sample 1
	Mode 5: LTE Band 5 Rx(High) + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 3(Charging from Adapter 5) + Battery 1 for Sample 1
	Mode 6: LTE Band 7 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 3(Charging from Adapter 6) + Battery 1 for Sample 1
	Mode 7: LTE Band 66 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 3(Charging from Adapter 7) + Battery 1 for Sample 1
	Mode 8: WCDMA FDD V Rx(Low) + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 for Sample 1
	Mode 9: GSM 1900 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 1 for Sample 1
	Mode 10 : WCDMA FDD IV Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 3(Data Link with Notebook) + Battery 1 for Sample 1
	Mode 11 : LTE Band 66 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Front) + USB Cable 3(Charging from Adapter 7) + Battery 1 for Sample 3
	Mode 12 : WCDMA FDD IV Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 3(Data Link with Notebook) + Battery 2 for Sample 3




Radiated Emissions	Mode 1: GSM850 Rx (Middle) + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 1(Charging from Adapter 1) + Battery 1 for Sample 1
	Mode 2: WCDMA FDD II Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 2) + Battery 1 for Sample 1
	Mode 3: LTE Band 2 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + MP4 + USB Cable 3(Charging from Adapter 3) + Battery 1 for Sample 1
	Mode 4: LTE Band 4 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + FM Rx(88MHz) + USB Cable 2(Charging from Adapter 4) + Battery 1 for Sample 1
	Mode 5: LTE Band 5 Rx(High) + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Charging from Adapter 5) + Battery 1 for Sample 1
	Mode 6: LTE Band 7 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 6) + Battery 1 for Sample 1
	Mode 7: LTE Band 66 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 7) + Battery 1 for Sample 1
	Mode 8: WCDMA 850 Rx(Low) + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 for Sample 1
	Mode 9: GSM 1900 Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 1 for Sample 1
	Mode 10 : WCDMA FDD IV Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 3(Data Link with Notebook) + Battery 1 for Sample 1
	Mode 11 : WCDMA FDD II Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 2) + Battery 2 for Sample 3
	Mode 12 : WCDMA 850 Rx(Low) + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 for Sample 3
	Mode 13 : WCDMA FDD II Rx + Bluetooth Idle + Earphone + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 2) + Battery 1 for Sample 4

**Remark:**

1. The worst case of AC is mode 7; only the test data of this mode is reported.
2. The worst case of RE is mode 2; only the test data of this mode is reported.
3. Data Link with Notebook means data application transferred mode between EUT and Notebook
4. Pre-scanned Low/Middle/High channel, the worst channel was recorded in this report.

## 2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded,1.8m
3.	Base Station	R&S	CMU 200	N/A	N/A	Unshielded,1.8m
4.	Signal Generator	R&S	SMBV100A	N/A	N/A	Unshielded,1.8m
5.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded,1.8m
6.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
7.	Notebook	Dell	Latitude3440	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
8.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
9.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
10.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
11.	Hard disk	KINGSHARE	KSP6120G	Fcc DoC	Shielded, 1.2m	N/A
12.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
13.	SD Card	Kingston	8GB	N/A	N/A	N/A

### 2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator’s paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on FM receiver function to make the EUT receive continuous signals from FM station.
4. Turn on camera to capture images.
5. Turn on MPEG4 function.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-L-191028-CN02 LINE  
 Project : (FC) 080310

: 356916110016174/356916110016182 #8

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.158	58.33	-7.23	65.56	47.80	0.07	10.46	QP
2	0.158	44.13	-11.43	55.56	33.60	0.07	10.46	Average
3	0.202	55.05	-8.49	63.54	44.60	0.09	10.36	QP
4	0.202	42.05	-11.49	53.54	31.60	0.09	10.36	Average
5	0.248	47.23	-14.59	61.82	36.80	0.10	10.33	QP
6	0.248	35.33	-16.49	51.82	24.90	0.10	10.33	Average
7	0.303	44.01	-16.14	60.15	33.59	0.11	10.31	QP
8	0.303	30.71	-19.44	50.15	20.29	0.11	10.31	Average
9	0.360	40.90	-17.84	58.74	30.51	0.11	10.28	QP
10	0.360	29.00	-19.74	48.74	18.61	0.11	10.28	Average
11	18.920	41.31	-18.69	60.00	28.81	2.03	10.47	QP
12	18.920	31.11	-18.89	50.00	18.61	2.03	10.47	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS  
 Condition : FCC CLASS-B LISN-N-191028-CN02 NEUTRAL  
 Project : (FC) 080310

: 356916110016174/356916110016182 #8

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
		dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.151	61.73	-4.23	65.96	51.10	0.15	10.48	QP
2	0.151	50.83	-5.13	55.96	40.20	0.15	10.48	Average
3	0.156	59.82	-5.83	65.65	49.21	0.15	10.46	QP
4	0.156	47.22	-8.43	55.65	36.61	0.15	10.46	Average
5	0.200	52.13	-11.49	63.62	41.60	0.17	10.36	QP
6	0.200	38.73	-14.89	53.62	28.20	0.17	10.36	Average
7	0.251	47.12	-14.61	61.73	36.61	0.18	10.33	QP
8	0.251	35.12	-16.61	51.73	24.61	0.18	10.33	Average
9	0.300	42.40	-17.84	60.24	31.90	0.19	10.31	QP
10	0.300	31.10	-19.14	50.24	20.60	0.19	10.31	Average
11	0.360	41.99	-16.75	58.74	31.50	0.21	10.28	QP
12	0.360	31.69	-17.05	48.74	21.20	0.21	10.28	Average
13	16.398	40.83	-19.17	60.00	28.20	2.20	10.43	QP
14	16.398	31.93	-18.07	50.00	19.30	2.20	10.43	Average

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)





### 3.2. Test of Radiated Emission Measurement

#### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



### **3.2.3. Test Procedures**


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Winter Zhang	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal




Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m LF 6111D SN44483 HORIZONTAL  
 Project : (FC) 080310

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	58.13	21.34	-18.66	40.00	40.38	12.40	1.72	33.16	---	---	Peak
2	97.90	28.43	-15.07	43.50	43.41	15.84	2.24	33.06	100	0	Peak
3	105.66	26.81	-16.69	43.50	40.96	16.64	2.32	33.11	---	---	Peak
4	153.19	23.09	-20.41	43.50	36.58	16.92	2.79	33.20	---	---	Peak
5	771.08	27.70	-18.30	46.00	25.62	28.20	6.24	32.36	---	---	Peak
6	881.66	29.84	-16.16	46.00	26.14	29.17	6.67	32.14	---	---	Peak
7	3896.00	39.78	-34.22	74.00	20.13	35.07	11.98	27.40	---	---	Peak
8	6240.00	42.61	-31.39	74.00	18.39	36.30	15.27	27.35	---	---	Peak
9	7720.00	43.38	-30.62	74.00	15.97	37.81	17.07	27.47	---	---	Peak
10	11115.00	45.01	-28.99	74.00	11.30	39.52	20.82	26.63	---	---	Peak
11	16056.00	45.41	-28.59	74.00	4.94	42.45	25.49	27.47	---	---	Peak
12	17604.00	46.17	-27.83	74.00	2.87	43.44	27.02	27.16	---	---	Peak



Test Engineer :	Winter Zhang	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical



Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m LF 6111D SN44483 VERTICAL  
 Project : (FC) 080310

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	31.94	32.05	-7.95	40.00	39.99	24.04	1.28	33.26	100	0 Peak	
2	58.13	30.53	-9.47	40.00	49.57	12.40	1.72	33.16	---	---	Peak
3	107.60	29.92	-13.58	43.50	43.87	16.82	2.34	33.11	---	---	Peak
4	647.89	24.58	-21.42	46.00	24.98	26.47	5.73	32.60	---	---	Peak
5	763.32	27.57	-18.43	46.00	25.54	28.20	6.20	32.37	---	---	Peak
6	881.66	29.61	-16.39	46.00	25.91	29.17	6.67	32.14	---	---	Peak
7	4336.00	40.24	-33.76	74.00	19.64	35.40	12.60	27.40	---	---	Peak
8	6672.00	41.63	-32.37	74.00	16.46	36.61	15.90	27.34	---	---	Peak
9	8880.00	43.19	-30.81	74.00	13.69	38.57	18.38	27.45	---	---	Peak
10	10728.00	45.35	-28.65	74.00	12.43	39.39	20.38	26.85	---	---	Peak
11	14976.00	46.17	-27.83	74.00	6.38	41.16	24.53	25.90	---	---	Peak
12	17829.00	46.83	-27.17	74.00	3.35	43.30	27.25	27.07	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Oct. 18, 2019	Aug. 26, 2020	Oct. 17, 2020	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 18, 2019	Aug. 26, 2020	Oct. 17, 2020	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 30, 2019	Aug. 26, 2020	Dec. 29, 2020	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 10, 2019	Aug. 26, 2020	Nov. 09, 2020	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2019	Aug. 26, 2020	Nov. 09, 2020	Radiation (03CH02-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 08, 2020	Aug. 26, 2020	Jan. 07, 2021	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 02, 2020	Aug. 26, 2020	Jan. 01, 2021	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5GHz	Oct. 18, 2019	Aug. 26, 2020	Oct. 17, 2020	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Aug. 26, 2020	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Aug. 26, 2020	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Aug. 26, 2020	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 14, 2020	Aug. 27, 2020	Apr. 13, 2021	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 18, 2019	Aug. 27, 2020	Oct. 17, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Oct. 28, 2019	Aug. 27, 2020	Oct. 27, 2020	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 18, 2019	Aug. 27, 2020	Oct. 17, 2020	Conduction (CO01-KS)

NCR: No Calibration Required



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.9dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.9dB
---	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0dB
---	-------