# **FCC RF Test Report**

APPLICANT : Motorola Mobility LLC EQUIPMENT : Mobile Cellular Phone

BRAND NAME : Motorola

MODEL NAME : XT2131-1, XT2131-4, XT2131-3, XT2131DL

FCC ID : IHDT56ZL1

STANDARD : 47 CFR Part 2, and 90(S)

**CLASSIFICATION**: PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jan. 29, 2021 and completely tested on Feb. 27, 2021. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Frie Shih

Donale Chen

Approved by: Eric Shih / Manager

Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 1 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report No.: FW112907B

### **TABLE OF CONTENTS**

RE	visio	N HISTORY	3
SU	MMA	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	5
	1.5	Modification of EUT	
	1.6	Maximum Conducted Power, Frequency Tolerance and Emission Designator	
	1.7	Testing Site	
	1.8	Test Software	
	1.9	Applied Standards	7
2	TES	CONFIGURATION OF EQUIPMENT UNDER TEST	9
	2.1	Test Mode	9
	2.2	Connection Diagram of Test System	10
	2.3	Support Unit used in test configuration and system	10
	2.4	Measurement Results Explanation Example	10
	2.5	Frequency List of Low/Middle/High Channels	11
3	TES	「RESULT	12
	3.1	Conducted Output Power Measurement	12
	3.2	99% Occupied Bandwidth and 26dB Bandwidth Measurement	
	3.3	Emissions Mask Measurement	14
	3.4	Emissions Mask – Out Of Band Emissions Measurement	
	3.5	Field Strength of Spurious Radiation Measurement	17
	3.6	Frequency Stability Measurement	19
4	LIST	OF MEASURING EQUIPMENT	21
5	UNC	ERTAINTY OF EVALUATION	22
ΔΕ	PEND	DIX A. TEST RESULTS OF CONDUCTED TEST	
AF	PEND	DIX B. TEST RESULTS OF RADIATED TEST	

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 2 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

## **REVISION HISTORY**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FW112907B	Rev. 01	Initial issue of report	Mar. 25, 2021

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 3 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

### **SUMMARY OF TEST RESULT**

Report Section	FCC Rule Description		Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< 50+10log <sub>10</sub> (P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious  Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 47.60 dB at 3267.000 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

#### **Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### **Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 4 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

## 1 General Description

## 1.1 Applicant

**Motorola Mobility LLC** 

222 W, Merchandise Mart Plaza, Chicago, IL60654 USA

#### 1.2 Manufacturer

**Motorola Mobility LLC** 

222 W, Merchandise Mart Plaza, Chicago, IL60654 USA

### 1.3 Feature of Equipment Under Test

	Product Feature
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2131-1, XT2131-4, XT2131-3, XT2131DL
FCC ID	IHDT56ZL1
	CDMA/GSM/WCDMA/LTE/5G NR
	WLAN 2.4GHz 802.11b/g/n HT20
FLIT supports Padios application	WLAN 5GHz 802.11a/n HT20/HT40
Lor supports Radios application	WLAN 5GHz 802.11ac VHT20/VHT40/VHT80
	Bluetooth BR / EDR / LE
	FM Receiver / GNSS
IMEL Code	Conducted: 356611280012398
rand Name odel Name CC ID  JT supports Radios application  EI Code  W Version  W Version	Radiation: 356611280016803
HW Version	DVT
SW Version	RRE31.37
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard					
Tx Frequency	814 ~ 824 MHz				
Rx Frequency	859 ~ 869 MHz				
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz				
Maximum Output Power to Antenna	Top Antenna: 23.26 dBm				
Maximum Output Fower to Antenna	Bottom Antenna: 22.54 dBm				
Antenna Gain	Top Antenna: -7.1 dBi				
Antenna Gain	Bottom Antenna: -7.7 dBi				
Type of Modulation	QPSK / 16QAM / 64QAM				

Note: The Maximum ERP/EIRP is calculated from Max Output power and Max antenna gain, only the maximum ERP/EIRP is shown on the report

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 5 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

# 1.6 Maximum Conducted Power, Frequency Tolerance and Emission Designator

L	TE Band 26		QPSK		16QAM			
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW) Frequency Tolerance (ppm)		Tolerance Conducted		Frequency Tolerance (ppm)	Maximum Conducted power (W)	
1.4	814.7 ~ 823.3	1M09G7D	-	0.2109	1M09W7D	-	0.1811	
3	815.5 ~ 822.5	2M72G7D	-	0.2113	2M73W7D	-	0.1919	
5	816.5 ~ 821.5	4M50G7D -	-	0.2099	4M52W7D	-	0.1854	
10	819.0	9M09G7D	0.0048	0.2099	8M99W7D	-	0.1837	
15	821.5	13M5G7D	-	0.2118	13M4W7D	-	0.1820	
L	TE Band 26			64Q	QAM			
BW (MHz)	Frequency Range (MHz)		Designator OBW)	•	/ Tolerance om)	Maximum Conducted power (W)		
1.4	814.7 ~ 823.3	1M09	W7D		-	0.1452		
3	815.5 ~ 822.5	2M73	BW7D		-	0.1476		
5	816.5 ~ 821.5	4M50	)W7D		-	0.1462		
10	819.0	9M01	W7D	-		0.1393		
15	821.5	13M4	₽W7D		-	0.1387		

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 6 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

### 1.7 Testing Site

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.								
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nansh Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595								
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.						
	TH01-SZ	CN1256	421272						

Test Firm	Sporton International (Sh	Sporton International (Shenzhen) Inc.							
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398								
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.						
	03CH04-SZ	CN1256	421272						

### 1.8 Test Software

Ite	em Site		Manufacturer	Name	Version	
1		03CH04-SZ	AUDIX	E3	6.2009-8-24	

## 1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

#### Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 7 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report No.: FW112907B

## 1.10 Specification of Accessory

	Specification of Accessory								
AC Adapter 1(US)	Brand Name	Motorola (Chenyang)	Model Name	MC-101					
AC Adapter 2(US)	Brand Name	Motorola (Salcomp)	Model Name	MC-101					
Battery	Brand Name	Motorola (ATL)	Model Name	MD50					
USB Cable 1	Brand Name	Motorola (Saibao)	Model Name	SC18C24367					
USB Cable 2	Brand Name	Motorola (Luxshare)	Model Name	SC18C24368					

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 8 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.


Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

			Ban	dwid	lth (M	Hz)		Modulation			RB#			Test Channel		
Test Items	Band	1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	М	Н
Max. Output Power	26	v	v	v	v	v	-	٧	v	v	v	v	v	v	٧	v
26dB and 99% Bandwidth	26	v	v	v	v	v	•	>	v	v			v	v	>	v
Emission masks In-band emissions	26	v	v	v	v	v	-	٧	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v	v	v	v			v	٧	v
Frequency Stability	26				v	v	-	v					v		٧	
Radiated Spurious Emission	26			v	v	v		v			v			v	v	
Note	<ol> <li>The</li> <li>LTE</li> <li>over</li> </ol>	mark "- Band26 15MHz	" mea 6 tran 2 band	ans th smit f dwidtl	at this reque	bandy ncy for plies th	width i r part2 ne ER	s not supp 2 rule is 8	24MHz-849	ng 9MHz, for p rule, therefo						Р

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 9 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report No.: FW112907B

### 2.2 Connection Diagram of Test System



### 2.3 Support Unit used in test configuration and system

Item		Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord	
	1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m	

## 2.4 Measurement Results Explanation Example

#### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

### Example:

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ 

$$= 4.0 + 10 = 14.0 (dB)$$

Report No.: FW112907B

## 2.5 Frequency List of Low/Middle/High Channels

	LTE Band 26 Channel and Frequency List											
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest								
15	Channel	26765	-	-								
15	Frequency	821.5	-	-								
10	Channel	-	26740	-								
	Frequency	-	819	-								
5	Channel	26715	26740	26765								
5	Frequency	816.5	819	821.5								
3	Channel	26705	26740	26775								
3	Frequency	815.5	819	822.5								
1.4	Channel	26697	26740	26783								
1.4	Frequency	814.7	819	823.3								

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 11 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

### 3 Test Result

### 3.1 Conducted Output Power Measurement

### 3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.1.3 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through the system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

### 3.1.4 Test Setup



### 3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 12 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report No.: FW112907B

### 3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

### 3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.2.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

#### 3.2.4 Test Setup



#### 3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 13 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report No.: FW112907B

### 3.3 Emissions Mask Measurement

#### 3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

- (a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:
- (1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log<sub>10</sub>(f/6.1) decibels or 50 + 10 Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.
- (2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


#### 3.3.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- 2. The emissions mask of low and high channels for the highest RF powers were measured.
- The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
- 4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 14 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report No.: FW112907B

### 3.3.4 Test Setup



### 3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 15 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

#### 3.4 Emissions Mask - Out Of Band Emissions Measurement

### 3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
   The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

#### 3.4.4 Test Setup



### 3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 16 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

### 3.5 Field Strength of Spurious Radiation Measurement

### 3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43+10log<sub>10</sub>(P[Watts]) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures


- The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 17 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01


Report Template No.: BU5-FWLTE Version 2.0

### 3.5.4 Test Setup

#### For radiated test from 30MHz to 1GHz



#### For radiated test above 1GHz



### 3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 18 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report No.: FW112907B

### 3.6 Frequency Stability Measurement

### 3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures for Temperature Variation

- 1. The EUT was set up in the thermal chamber and connected with the base station.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three
  hours. Power was applied and the maximum change in frequency was recorded within one
  minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.6.4 Test Procedures for Voltage Variation

- 1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
- The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
- 3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
- 4. battery operating end point, which shall be specified by the manufacturer.
- 5. The variation in frequency was measured for the worst case.


Report Issued Date: Mar. 25, 2021 Report Version: Rev. 01

Page Number

Report Template No.: BU5-FWLTE Version 2.0

: 19 of 21

### 3.6.5 Test Setup



### 3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 20 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report No.: FW112907B

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 17, 2020	Feb. 11, 2021	Apr. 16, 2021	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 22, 2020	Feb. 11, 2021	Jul. 21, 2021	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 16, 2020	Feb. 27, 2021	Oct. 15, 2021	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 21, 2020	Feb. 27, 2021	Jul. 20, 2021	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	Nov. 07, 2020	Feb. 27, 2021	Nov. 06, 2021	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1474	1GHz~18GHz	May 23, 2020	Feb. 27, 2021	May 22, 2021	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 26, 2020	Feb. 27, 2021	Jul. 25, 2021	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 16, 2020	Feb. 27, 2021	Oct. 15, 2021	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P-R	1943528	1GHz~18GHz	Oct. 17, 2020	Feb. 27, 2021	Oct. 16, 2021	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 21, 2020	Feb. 27, 2021	Jul. 20, 2021	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY53270156	500MHz~26.5GHz	Oct. 17, 2020	Feb. 27, 2021	Oct. 16, 2021	Radiation (03CH04-SZ)
AC Power Source	Chroma	61601	N/A	N/A	NCR	Feb. 27, 2021	NCR	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Feb. 27, 2021	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Feb. 27, 2021	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 21 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

### 5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

#### <u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of	2.8dB
Confidence of 95% (U = 2Uc(y))	2.005

#### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of	3.1dB
Confidence of 95% (U = 2Uc(y))	3.1ub

#### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of	3.9dB
Confidence of 95% (U = 2Uc(y))	3.905

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : 22 of 21
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

## **Appendix A. Test Results of Conducted Test**

## **Conducted Output Power (Average power)**

#### Top Antenna:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.
	Cha	nnel		26765		
	Frequenc	cy (MHz)	821.5			
15	QPSK	1	0	23.26		
15	QPSK	1	37	23.23		
15	QPSK	1	74	23.12		
15	QPSK	36	0	22.38		
15	QPSK	36	20	22.27		
15	QPSK	36	39	22.40		
15	QPSK	75	0	22.31		
15	16QAM	1	0	22.60		
15	16QAM	1	37	22.41		
15	16QAM	1	74	22.44		
15	16QAM	36	0	21.35		
15	16QAM	36	20	21.38		
15	16QAM	36	39	21.30		
15	16QAM	75	0	21.42		
15	64QAM	1	0	21.40		
15	64QAM	1	37	21.42		
15	64QAM	1	74	21.35		
15	64QAM	36	0	20.42		
15	64QAM	36	20	20.40		
15	64QAM	36	39	20.39		
15	64QAM	75	0	20.43		
	Cha	nnel			26740	
	Frequenc	cy (MHz)			819	
10	QPSK	1	0		23.22	
10	QPSK	1	25		23.01	
10	QPSK	1	49		23.03	
10	QPSK	25	0		22.24	
10	QPSK	25	12		22.17	
10	QPSK	25	25		22.25	
10	QPSK	50	0		22.17	
10	16QAM	1	0		22.64	
10	16QAM	1	25		22.39	
10	16QAM	1	49		22.40	
10	16QAM	25	0		21.26	
10	16QAM	25	12		21.31	
10	16QAM	25	25		21.26	
10	16QAM	50	0		21.30	
10	64QAM	1	0		21.37	

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : A1 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



## FCC RF Test Report

40	040414	4	05		04.44	
10	64QAM	1	25		21.44	
10	64QAM	1	49		21.27	
10	64QAM	25	0		20.29	
10	64QAM	25	12		20.27	
10	64QAM	25	25		20.26	
10	64QAM	50	0		20.29	
	Cha -		26715	26740	26765	
	Frequen		816.5	819	821.5	
5	QPSK	1	0	23.10	23.17	23.05
5	QPSK	1	12	23.08	23.22	22.95
5	QPSK	1	24	23.07	23.18	22.90
5	QPSK	12	0	22.55	22.18	22.11
5	QPSK	12	7	22.55	22.34	22.08
5	QPSK	12	13	22.58	22.28	22.09
5	QPSK	25	0	22.56	22.18	22.10
5	16QAM	1	0	22.68	22.20	22.49
5	16QAM	1	12	22.66	22.22	22.49
5	16QAM	1	24	22.40	22.34	22.41
5	16QAM	12	0	21.55	21.18	21.08
5	16QAM	12	7	21.54	21.26	21.06
5	16QAM	12	13	21.56	21.33	21.08
5	16QAM	25	0	21.48	21.25	21.07
5	64QAM	1	0	21.65	21.29	21.41
5	64QAM	1	12	21.50	21.33	21.44
5	64QAM	1	24	21.49	21.37	21.17
5	64QAM	12	0	20.66	20.27	20.30
5	64QAM	12	7	20.64	20.23	20.26
5	64QAM	12	13	20.59	20.27	20.24
5	64QAM	25	0	20.56	20.23	20.23
	Cha	nnel		26705	26740	26775
	Frequen	cy (MHz)		815.5	819	822.5
3	QPSK	1	0	23.25	23.08	23.01
3	QPSK	1	8	23.13	23.12	23.04
3	QPSK	1	14	23.11	23.15	22.89
3	QPSK	8	0	22.47	22.19	22.07
3	QPSK	8	4	22.51	22.25	22.07
3	QPSK	8	7	22.50	22.23	22.03
3	QPSK	15	0	22.50	22.19	22.05
3	16QAM	1	0	22.74	22.48	22.50
3	16QAM	1	8	22.83	22.55	22.51
3	16QAM	1	14	22.68	22.41	22.42
3	16QAM	8	0	21.60	21.25	21.18
3	16QAM	8	4	21.63	21.34	21.18
3	16QAM	8	7	21.59	21.16	21.14
3	16QAM	15	0	21.55	21.20	21.10
3	64QAM	1	0	21.64	21.50	21.22
3	64QAM	1	8	21.69	21.44	21.30
3	64QAM	1	14	21.58	21.65	21.24
3	64QAM	8	0	20.57	20.26	20.11
3	64QAM	8	4	20.59	20.31	20.29

Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : A2 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



## FCC RF Test Report

3	64QAM	8	7	20.50	20.30	20.10
3	64QAM	15	0	20.54	20.26	20.13
	Cha	nnel	26697	26740	26783	
	Frequen	cy (MHz)	814.7	819	823.3	
1.4	QPSK	1	0	22.98	22.99	22.93
1.4	QPSK	1	3	23.24	23.04	22.93
1.4	QPSK	1	5	23.04	23.01	22.94
1.4	QPSK	3	0	23.04	23.04	23.07
1.4	QPSK	3	1	23.15	23.15	23.05
1.4	QPSK	3	3	23.17	23.14	23.01
1.4	QPSK	6	0	22.49	22.24	22.05
1.4	16QAM	1	0	22.35	22.16	22.18
1.4	16QAM	1	3	22.38	22.16	22.22
1.4	16QAM	1	5	22.58	22.10	22.13
1.4	16QAM	3	0	22.34	22.14	21.95
1.4	16QAM	3	1	22.38	22.31	22.04
1.4	16QAM	3	3	22.31	22.17	21.94
1.4	16QAM	6	0	21.44	21.04	21.00
1.4	64QAM	1	0	21.60	21.44	21.13
1.4	64QAM	1	3	21.53	21.62	21.16
1.4	64QAM	1	5	21.47	21.39	21.19
1.4	64QAM	3	0	21.42	21.32	21.31
1.4	64QAM	3	1	21.48	21.53	21.26
1.4	64QAM	3	3	21.53	21.20	21.20
1.4	64QAM	6	0	20.52	20.12	20.14

**Sporton International (ShenZhen) Inc.** TEL: 86-755-8637-9589

FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : A3 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01

## 26dB Bandwidth

Mode		LTE Band 26 : 26dB BW(MHz)										
BW	1.4	ИНz	3M	3MHz		5MHz		10MHz		ИHz	20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.23	1.22	3.03	3.01	4.90	4.86	-	-	14.39	14.30	-	-
Middle CH	1.23	1.22	3.04	3.00	4.93	4.90	9.69	9.87	-	-	-	-
Highest CH	1.23	1.23	3.02	3.06	4.95	4.90	-	-	-	-	-	-
Mode					LTE Ba	and 26 :	26dB BV	V(MHz)				
BW	1.4	ИНz	3M	lHz	5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.23	-	2.99	-	4.93	-	-	-	14.69	-	-	-
Middle CH	1.22	-	3.03	-	4.86	-	9.89	-	-	-	-	-
Highest CH	1.22	-	2.95	-	4.92	-	-	-	-	-	-	-


Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1


: A4 of A44 Page Number Report Issued Date: Mar. 25, 2021

Report No.: FW112907B


Report Version : Rev. 01




Page Number : A5 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Page Number : A6 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Page Number : A7 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Page Number : A8 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



Page Number : A9 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



Page Number : A10 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



Page Number : A11 of A44 Report Issued Date: Mar. 25, 2021

Report No.: FW112907B

Report Version : Rev. 01

## **Occupied Bandwidth**


Mode		LTE Band 26 : 99%OBW(MHz)										
BW	1.4	ИНz	3MHz		5M	5MHz		10MHz		ЛHz	20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.08	2.70	2.73	4.48	4.52	-	-	13.46	13.37	-	-
Middle CH	1.09	1.09	2.72	2.72	4.48	4.50	9.09	8.99	-	-	-	-
Highest CH	1.09	1.09	2.72	2.72	4.50	4.49	-	-	-	-	-	-
Mode					LTE Ba	and 26 :	99%OBV	V(MHz)				
BW	1.4	ИHz	3M	3MHz		5MHz		10MHz		ИHz	20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.09	-	2.71	-	4.50	-	-	-	13.40	-	-	-
Middle CH	1.09	-	2.73	-	4.49	-	9.01	-	-	-	-	-
Highest CH	1.09	-	2.70	-	4.49	-	-	-	-	-	-	-

Sporton International (ShenZhen) Inc.


TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : A12 of A44
Report Issued Date : Mar. 25, 2021

Report No.: FW112907B


Report Version : Rev. 01




Page Number : A13 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Page Number : A14 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Page Number : A15 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Page Number : A16 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



Page Number : A17 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



Page Number : A18 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Page Number : A19 of A44 Report Issued Date: Mar. 25, 2021 Report Version

Report No.: FW112907B


: Rev. 01

## **Conducted Band Edge**




Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : A20 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Page Number : A21 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01




Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : A22 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : A23 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01



Sporton International (ShenZhen) Inc.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: IHDT56ZL1 Page Number : A24 of A44
Report Issued Date : Mar. 25, 2021
Report Version : Rev. 01