



# FCC SAR Test Report

APPLICANT : Motorola Mobility LLC  
EQUIPMENT : Mobile Cellular Phone  
BRAND NAME : Motorola  
MODEL NAME : XT2127-2  
FCC ID : IHDT56ZM2  
STANDARD : FCC 47 CFR Part 2 (2.1093)

The product was received on Oct. 20, 2020 and testing was started from Nov. 12, 2020 and completed on Nov. 20, 2020. We, Sporton International (ShenZhen) Inc, would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Hank Huang / Supervisor

Approved by: Johnny Chen / Manager



**Sporton International (ShenZhen) Inc.**  
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055  
People's Republic of China



Table of Contents

1. Statement of Compliance ..... 4
2. Administration Data ..... 5
3. Guidance Applied ..... 5
4. Equipment Under Test (EUT) Information ..... 6
4.1 General Information ..... 6
4.2 General LTE SAR Test and Reporting Considerations ..... 7
5. Proximity Sensor Triggering Test ..... 9
5.1 Proximity sensor triggering distances(Per KDB616217§6.2) ..... 9
6. RF Exposure Limits ..... 15
6.1 Uncontrolled Environment ..... 15
6.2 Controlled Environment ..... 15
7. Specific Absorption Rate (SAR) ..... 16
7.1 Introduction ..... 16
7.2 SAR Definition ..... 16
8. System Description and Setup ..... 17
8.1 E-Field Probe ..... 18
8.2 Data Acquisition Electronics (DAE) ..... 18
8.3 Phantom ..... 19
8.4 Device Holder ..... 20
9. Measurement Procedures ..... 21
9.1 Spatial Peak SAR Evaluation ..... 21
9.2 Power Reference Measurement ..... 22
9.3 Area Scan ..... 22
9.4 Zoom Scan ..... 23
9.5 Volume Scan Procedures ..... 23
9.6 Power Drift Monitoring ..... 23
10. Test Equipment List ..... 24
11. System Verification ..... 25
11.1 Tissue Simulating Liquids ..... 25
11.2 Tissue Verification ..... 26
11.3 System Performance Check Results ..... 27
12. RF Exposure Positions ..... 28
12.1 Ear and handset reference point ..... 28
12.2 Definition of the cheek position ..... 29
12.3 Definition of the tilt position ..... 30
12.4 Body Worn Accessory ..... 31
12.5 Product Specific 10g SAR Exposure ..... 32
12.6 Wireless Router ..... 32
13. Conducted RF Output Power (Unit: dBm) ..... 33
14. Antenna Location ..... 43
15. SAR Test Results ..... 44
15.1 Head SAR ..... 47
15.2 Hotspot SAR ..... 50
15.3 Body Worn Accessory SAR ..... 55
15.4 Product specific 10g SAR ..... 59
15.5 Repeated SAR Measurement ..... 62
16. Simultaneous Transmission Analysis ..... 63
16.1 Head Exposure Conditions ..... 64
16.2 Hotspot Exposure Conditions ..... 65
16.3 Body-Worn Accessory Exposure Conditions ..... 66
16.4 Product specific 10g SAR Exposure Conditions ..... 67
16.5 SPLSR Evaluation and Analysis ..... 68
17. Uncertainty Assessment ..... 74
18. References ..... 75
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASY Calibration Certificate
Appendix D. Test Setup Photos
Appendix E. Conducted RF Output Power Table





### 1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility LLC, Mobile Cellular Phone, XT2127-2**, are as follows.

Highest 1g SAR Summary						
Equipment Class	Frequency Band		Head (Separation 0mm)	Hotspot (Separation 5mm)	Body-worn (Separation 5mm)	Highest Simultaneous Transmission 1g SAR (W/kg)
			1g SAR (W/kg)			
Licensed	GSM	GSM850	0.54	1.27	1.27	1.54
		GSM1900	0.24	1.40	1.11	
	WCDMA	Band V	0.44	1.26	1.28	
		Band II	0.33	1.36	<b>1.36</b>	
	LTE	Band 5	0.39	1.19	1.19	
		Band 26	0.41	1.21	1.21	
		Band 2	0.27	1.37	1.35	
		Band 7	0.23	<b>1.43</b>	1.14	
	Band 41/Band 38	0.17	1.33	1.25		
DTS	WLAN	2.4GHz WLAN	1.02	0.94	0.94	1.54
NII		5GHz WLAN	<b>1.07</b>	0.92	1.04	1.48
DSS	Bluetooth	2.4GHz Bluetooth	0.17	0.13	0.13	1.49

Highest 10g SAR Summary				
Equipment Class	Frequency Band		Product Specific 10g SAR (W/kg) (Separation 0mm)	Highest Simultaneous Transmission 10g SAR (W/kg)
Licensed	GSM	GSM850	2.34	3.93
		GSM1900	2.84	
	WCDMA	Band V	2.80	
		Band II	3.34	
	LTE	Band 26	2.49	
		Band 2	<b>3.43</b>	
		Band 7	2.85	
		Band 41/Band 38	3.02	
NII	WLAN	5GHz WLAN	2.23	3.93

Date of Testing: 2020/11/12~2020/11/20

**Remark:** This device supports LTE B38 and B41. Since the supported frequency span for LTE B38 falls completely within the supports frequency span for LTE B41, both LTE bands have the same target power, and both LTE bands share the same transmission path; therefore, SAR was only assessed for LTE B41.

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.



### 2. Administration Data

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory		
Test Firm	Sporton International (Shenzhen) Inc.	
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595	
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CN1256	421272

Applicant	
Company Name	Motorola Mobility LLC
Address	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

Manufacturer	
Company Name	Motorola Mobility LLC
Address	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

### 3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

## 4. Equipment Under Test (EUT) Information

### 4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2127-2
FCC ID	IHDT56ZM2
IMEI Code	IMEI 1: 351546360021619 IMEI 2: 351546360021627
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC: 13.56 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+(16QAM uplink is not supported) LTE: QPSK, 16QAM, 64QAM WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC:ASK
HW Version	DVT2
SW Version	RRB31.30
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Production Unit
Remark:	<ol style="list-style-type: none"> <li>802.11n-HT40 is not supported in 2.4GHz WLAN.</li> <li>This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.</li> <li>This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications.</li> <li>This device 2.4GHz WLAN/5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.3GHz / 5.5GHz supports WiFi Direct (GC only).</li> <li>This device does not support DTM operation and supports GRPS/EGRPS mode up to multi-slot class 12.</li> <li>The device implements Proximity sensors/receiver detect mechanism/hotspot trigger reduced power for the power management for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity).</li> <li>The device will invoke corresponding work scenarios power level, which are provided in the operational description.</li> <li>For Some WWAN bands, sensor on reduced power level higher than hotspot reduced power level, so front/back sensor on SAR can represent hotspot conservatively.</li> <li>There are two different types of EUT. They are single SIM card mobile and dual SIM card mobile. The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we chose dual SIM card mobile to</li> </ol>



- perform all tests.
10. For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.
  11. The device has five headsets, only supplier is different, so we chose headset 1 to perform full SAR testing, and headset 2/3/4/5 only verified the worst case of headset 1.

**4.2 General LTE SAR Test and Reporting Considerations**

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																															
FCC ID	IHDT56ZM2																																																														
Equipment Name	Mobile Cellular Phone																																																														
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz																																																														
Channel Bandwidth	LTE Band 2: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 26: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz																																																														
uplink modulations used	QPSK / 16QAM / 64QAM																																																														
LTE Voice / Data requirements	Voice and Data																																																														
LTE Release Version	R12, Cat5																																																														
CA Support	Not supported																																																														
LTE MPR permanently built-in by design	<p><b>Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</b></p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (N<sub>RB</sub>)</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 3</td> </tr> <tr> <td>256 QAM</td> <td colspan="6" style="text-align: center;">≥ 1</td> <td>≤ 5</td> </tr> </tbody> </table>	Modulation	Channel bandwidth / Transmission bandwidth (N <sub>RB</sub> )						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Modulation	Channel bandwidth / Transmission bandwidth (N <sub>RB</sub> )						MPR (dB)																																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																								
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																								
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																								
256 QAM	≥ 1						≤ 5																																																								
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																														
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																														
Power reduction applied to satisfy SAR compliance	Yes, head/body-worn/ hotspot/extremity will trigger reduced power for some LTE bands, the detail please referred to section 13.																																																														




Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5		
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510				
M	21100	2535	21100	2535	21100	2535	21100	2535				
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				
LTE Band 26												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5		
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5		
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26965	841.5		
LTE Band 38												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580				
M	38000	2595	38000	2595	38000	2595	38000	2595				
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610				
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	39675	2498.5	39700	2501	39725	2503.5	39750	2506				
LM	40148	2545.8	40160	2547	40173	2548.3	40185	2549.5				
M	40620	2593	40620	2593	40620	2593	40620	2593				
HM	41093	2640.3	41080	2639	41068	2637.8	41055	2636.5				
H	41565	2687.5	41540	2685	41515	2682.5	41490	2680				



## 5. Proximity Sensor Triggering Test



### 5.1 Proximity sensor triggering distances(Per KDB616217§6.2)



- Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed and the tissue-equivalent medium for highest frequency (5720MHz) and lowest (850MHz) frequency was used for proximity sensor triggering testing.
- Capacitive proximity sensor placed coincident with antenna elements at the bottom end of the phone are utilized to determine when the device comes in proximity of the user's body at the front or back or bottom or left side surface of the device. There is no need to do sensor coverage testing for the proximity sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the proximity sensor entirely covers the antenna.
- When the proximity sensor is active, GSM850/1900, WCDMA band II/V, LTE band 2/7/26/38/41 and WLAN5.5GHZ reduced power will be active for front/ back body worn SAR.
- P-sensor can detect handheld state, GSM1900, WCDMA band II and LTE B2/7/38/41 for front/back/bottom sides of product specific 10g SAR condition reduced powers will be active for handheld SAR.
- The proximity sensors used to detect the proximity of the user's body at the front or back or bottom side surface of the device use a detection threshold distance. The data shown in the sections below shows the distance(s).
- For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed for body worn:  
Front: [12 mm](#)  
Back: [20 mm](#)
- For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed for handheld:  
Front: [9 mm](#)  
Back: [13 mm](#)  
Bottom side: [10 mm](#)



<P-Sensor>



Proximity Sensor Triggering Distance (mm)				
Position	Front		Back	
	Moving towards	Moving away	Moving towards	Moving away
Minimum	13	14	21	23









<Handheld>

Position	Front		Back		Bottom Side	
	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away
Minimum	10	12	14	17	11	14







## 6. RF Exposure Limits

### 6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Limits for Occupational/Controlled Exposure (W/kg)**

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

**Limits for General Population/Uncontrolled Exposure (W/kg)**

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

## **7. Specific Absorption Rate (SAR)**

### **7.1 Introduction**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### **7.2 SAR Definition**

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.



## 8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

**8.1 E-Field Probe**

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

**<EX3DV4 Probe>**

<b>Construction</b>	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
<b>Frequency</b>	10 MHz – >6 GHz Linearity: ±0.2 dB (30 MHz – 6 GHz)	
<b>Directivity</b>	±0.3 dB in TSL (rotation around probe axis) ±0.5 dB in TSL (rotation normal to probe axis)	
<b>Dynamic Range</b>	10 µW/g – >100 mW/g Linearity: ±0.2 dB (noise: typically <1 µW/g)	
<b>Dimensions</b>	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

**8.2 Data Acquisition Electronics (DAE)**

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



**Photo of DAE**


**8.3 Phantom**

**<SAM Twin Phantom>**

<b>Shell Thickness</b>	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
<b>Filling Volume</b>	Approx. 25 liters	
<b>Dimensions</b>	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
<b>Measurement Areas</b>	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

**<ELI Phantom>**

<b>Shell Thickness</b>	2 ± 0.2 mm (sagging: <1%)	
<b>Filling Volume</b>	Approx. 30 liters	
<b>Dimensions</b>	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

## 8.4 Device Holder

### <Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

### <Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

## 9. Measurement Procedures

The measurement procedures are as follows:

### <Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### 9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

### 9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

### 9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	$\leq 3$ GHz	$> 3$ GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	$5 \pm 1$ mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	$\leq 2$ GHz: $\leq 15$ mm $2 - 3$ GHz: $\leq 12$ mm	$3 - 4$ GHz: $\leq 12$ mm $4 - 6$ GHz: $\leq 10$ mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

### 9.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		$\leq 3$ GHz	$> 3$ GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$		$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm*	3 – 4 GHz: $\leq 5$ mm* 4 – 6 GHz: $\leq 4$ mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm	
	graded grid	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm	
<p>Note: <math>\delta</math> is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is <math>\leq 1.4</math> W/kg, <math>\leq 8</math> mm, <math>\leq 7</math> mm and <math>\leq 5</math> mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>				

### 9.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



### 10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d162	Dec. 05, 2018	Dec. 04, 2021
SPEAG	1900MHz System Validation Kit	D1900V2	5d182	Dec. 07, 2018	Dec. 06, 2021
SPEAG	2450MHz System Validation Kit	D2450V2	924	Sep. 02, 2020	Sep. 01, 2021
SPEAG	2600MHz System Validation Kit	D2600V2	1070	Dec. 07, 2018	Dec. 06, 2021
SPEAG	5000MHz System Validation Kit	D5GHzV2	1167	Aug. 03, 2018	Aug. 02, 2021
SPEAG	Data Acquisition Electronics	DAE4	715	Jul. 27, 2020	Jul. 26, 2021
SPEAG	Data Acquisition Electronics	DAE3	528	Mar. 16, 2020	Mar. 15, 2021
SPEAG	Dosimetric E-Field Probe	EX3DV4	7576	Jan. 22, 2020	Jan. 21, 2021
SPEAG	Dosimetric E-Field Probe	EX3DV4	7577	Sep. 30, 2020	Sep. 29, 2021
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1670	NCR	NCR
SPEAG	SAM Twin Phantom	SAM V5.0	1795	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201341952	Dec. 27, 2019	Dec. 26, 2020
Anritsu	Radio communication analyzer	MT8821C	6201588577	Mar. 26, 2020	Mar. 25, 2021
Agilent	Wireless Communication Test Set	E5515C	MY50267224	Jul. 21, 2020	Jul. 20, 2021
Agilent	Network Analyzer	E5071C	MY46523671	Oct. 15, 2020	Oct. 14, 2021
Speag	Dielectric Assessment KIT	DAK-3.5	1138	May 19, 2020	May 18, 2021
Agilent	Signal Generator	N5181A	MY50145381	Dec. 26, 2019	Dec. 25, 2020
Anritsu	Power Sensor	MA2411B	1306099	Jul. 21, 2020	Jul. 20, 2021
Anritsu	Power Meter	ML2495A	1349001	Jul. 21, 2020	Jul. 20, 2021
Anritsu	Power Sensor	MA2411B	1207253	Dec. 26, 2019	Dec. 25, 2020
Anritsu	Power Meter	ML2495A	1218010	Dec. 26, 2019	Dec. 25, 2020
R&S	CBT BLUETOOTH TESTER	CBT	100963	Dec. 26, 2019	Dec. 25, 2020
R&S	Spectrum Analyzer	FSP7	100818	Jul. 21, 2020	Jul. 20, 2021
TES	Hygrometer	1310	200505600	Jul. 30, 2020	Jul. 29, 2021
Anymetre	Thermo-Hygrometer	JR593	2015030903	Dec. 30, 2019	Dec. 29, 2020
AR	Amplifier	5S1G4	0333096		Note
mini-circuits	Amplifier	ZVE-3W-83+	599201528		Note
ARRA	Power Divider	A3200-2	N/A		Note
PASTERNAK	Dual Directional Coupler	PE2214-10	N/A		Note
Agilent	Dual Directional Coupler	778D	50422		Note
MCL	Attenuator 1	BW-S10W5	N/A		Note
Weinschel	Attenuator 2	3M-20	N/A		Note
Zhongjilianhe	Attenuator 3	MVE2214-03	N/A		Note

**Note:**

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.



## 11. System Verification

### 11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.2.




Fig 11.1 Photo of Liquid Height for Head SAR




Fig 11.2 Photo of Liquid Height for Body SAR

### 11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

#### Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

#### <Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )	Conductivity Target ( $\sigma$ )	Permittivity Target ( $\epsilon_r$ )	Delta ( $\sigma$ ) (%)	Delta ( $\epsilon_r$ ) (%)	Limit (%)	Date
835	Head	22.7	0.928	42.730	0.90	41.50	3.11	2.96	±5	2020/11/12
835	Head	22.5	0.929	41.793	0.90	41.50	3.22	0.71	±5	2020/11/14
1900	Head	22.6	1.457	39.135	1.40	40.00	4.07	-2.16	±5	2020/11/13
1900	Head	22.4	1.440	40.038	1.40	40.00	2.86	0.09	±5	2020/11/15
2450	Head	22.7	1.865	37.492	1.80	39.20	3.61	-4.36	±5	2020/11/14
2450	Head	22.6	1.732	40.764	1.80	39.20	-3.78	3.99	±5	2020/11/16
2600	Head	22.4	2.055	37.597	1.96	39.00	4.85	-3.60	±5	2020/11/14
2600	Head	22.3	1.894	40.240	1.96	39.00	-3.37	3.18	±5	2020/11/17
5250	Head	22.5	4.597	36.617	4.71	35.95	-2.40	1.86	±5	2020/11/18
5600	Head	22.6	5.006	36.080	5.07	35.50	-1.26	1.63	±5	2020/11/19
5750	Head	22.5	5.175	35.814	5.22	35.35	-0.86	1.31	±5	2020/11/20

### 11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

<1g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2020/11/12	835	Head	250	4d162	7576	528	2.37	9.61	9.48	-1.35
2020/11/14	835	Head	250	4d162	7577	715	2.57	9.61	10.28	6.97
2020/11/13	1900	Head	250	5d182	7576	528	9.79	39.60	39.16	-1.11
2020/11/15	1900	Head	250	5d182	7577	715	10.30	39.60	41.2	4.04
2020/11/14	2450	Head	250	924	7576	528	12.60	51.40	50.4	-1.95
2020/11/16	2450	Head	250	924	7577	715	12.80	51.40	51.2	-0.39
2020/11/14	2600	Head	250	1070	7576	528	14.30	58.10	57.2	-1.55
2020/11/17	2600	Head	250	1070	7577	715	14.10	58.10	56.4	-2.93
2020/11/18	5250	Head	100	1167	7577	715	7.82	77.00	78.2	1.56
2020/11/19	5600	Head	100	1167	7577	715	8.59	80.80	85.9	6.31
2020/11/20	5750	Head	100	1167	7577	715	7.84	76.90	78.4	1.95

<10g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2020/11/12	835	Head	250	4d162	7576	528	1.56	6.35	6.24	-1.73
2020/11/14	835	Head	250	4d162	7577	715	1.68	6.35	6.72	5.83
2020/11/13	1900	Head	250	5d182	7576	528	5.07	20.70	20.28	-2.03
2020/11/15	1900	Head	250	5d182	7577	715	5.30	20.70	21.2	2.42
2020/11/14	2450	Head	250	924	7576	528	5.67	24.00	22.68	-5.50
2020/11/16	2450	Head	250	924	7577	715	5.93	24.00	23.72	-1.17
2020/11/14	2600	Head	250	1070	7576	528	6.41	26.10	25.64	-1.76
2020/11/17	2600	Head	250	1070	7577	715	6.25	26.10	25	-4.21
2020/11/18	5250	Head	100	1167	7577	715	2.14	22.00	21.4	-2.73
2020/11/19	5600	Head	100	1167	7577	715	2.42	23.20	24.2	4.31
2020/11/20	5750	Head	100	1167	7577	715	2.15	21.60	21.5	-0.46




Fig 11.3.1 System Performance Check Setup



Fig 11.3.2 Setup Photo

## 12. RF Exposure Positions

### 12.1 Ear and handset reference point

Figure 12.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 12.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 12.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 12.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 12.1.1 Front, back, and side views of SAM twin phantom




Fig 12.1.2 Close-up side view of phantom showing the ear region.




Fig 12.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

### 12.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width  $w_t$  of the handset at the level of the acoustic output (point A in Figure 12.2.1 and Figure 12.2.2), and the midpoint of the width  $w_b$  of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 12.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 12.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 12.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 12.2.3. The actual rotation angles should be documented in the test report.




Fig 12.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 12.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 12.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

### 12.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 12.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 12.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

### 12.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 12.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is  $> 1.2 \text{ W/kg}$ , the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 12.4 Body Worn Position



## **12.5 Product Specific 10g SAR Exposure**

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at  $\leq 25$  mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

## **12.6 Wireless Router**

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ( $L \times W \geq 9$  cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.



### **13. Conducted RF Output Power (Unit: dBm)**

The detailed conducted power table can refer to Appendix E.

#### **<GSM Conducted Power>**

1. Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS 2Tx slots for GSM850/GSM1900 are considered as the primary mode.
3. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq 1/4$  dB higher than the primary mode, SAR measurement is not required for the secondary mode.

#### **<WCDMA Conducted Power>**

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

#### **HSDPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each
  - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
  - iii. Set RMC 12.2Kbps + HSDPA mode.
  - iv. Set Cell Power = -86 dBm
  - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
  - vi. Select HSDPA Uplink Parameters
  - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
  - viii. Set Ack-Nack Repetition Factor to 3
  - ix. Set CQI Feedback Cycle (k) to 4 ms
  - x. Set CQI Repetition Factor to 2
  - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

**Table C.10.1.4:  $\beta$  values for transmitter characteristics tests with HS-DPCCH**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta_{ACK}$  and  $\Delta_{NACK} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ , and  $\Delta_{CQI} = 24/15$  with  $\beta_{HS} = 24/15 * \beta_c$ .

Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{HS}/\beta_c = 24/15$ . For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

**Setup Configuration**

**HSUPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting \* :
  - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
  - ii. Set the Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
  - iii. Set Cell Power = -86 dBm
  - iv. Set Channel Type = 12.2k + HSPA
  - v. Set UE Target Power
  - vi. Power Ctrl Mode= Alternating bits
  - vii. Set and observe the E-TFCI
  - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

**Table C.11.1.3:  $\beta$  values for transmitter characteristics tests with HS-DPCCH and E-DCH**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note1)	$\beta_{ec}$	$\beta_{ed}$ (Note 4) (Note 5)	$\beta_{ed}$ (SF)	$\beta_{ed}$ (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4,  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ . For sub-test 5,  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 5/15$  with  $\beta_{hs} = 5/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF0) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

**Setup Configuration**

**DC-HSDPA 3GPP release 8 Setup Configuration:**


- a. The EUT was connected to Base Station referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set RMC 12.2Kbps + HSDPA mode.
  - ii. Set Cell Power = -25 dBm
  - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
  - iv. Select HSDPA Uplink Parameters
  - v. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
    - a). Subtest 1:  $\beta_c/\beta_d=2/15$
    - b). Subtest 2:  $\beta_c/\beta_d=12/15$
    - c). Subtest 3:  $\beta_c/\beta_d=15/8$
    - d). Subtest 4:  $\beta_c/\beta_d=15/4$
  - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
  - vii. Set Ack-Nack Repetition Factor to 3
  - viii. Set CQI Feedback Cycle (k) to 4 ms
  - ix. Set CQI Repetition Factor to 2
  - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

**C.8.1.12 Fixed Reference Channel Definition H-Set 12**

**Table C.8.1.12: Fixed Reference Channel H-Set 12**

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload ( $N_{INF}$ )	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		



**Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)**

**Setup Configuration**



**<WCDMA Conducted Power>**


**General Note:**

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq \frac{1}{4}$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than  $\frac{1}{4}$  dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA

**<LTE Conducted Power>**

**General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B5 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE B38 SAR test was covered by B41; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
  - a. the maximum output power, including tolerance, for the smaller band is  $\leq$  the larger band to qualify for the SAR test exclusion
  - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



**64QAM**



**16QAM**



<b>Special subframe (30720·T<sub>s</sub>): Normal cyclic prefix in downlink (UpPTS)</b>			
	<b>Special subframe configuration</b>	<b>Normal cyclic prefix in uplink</b>	<b>Extended cyclic prefix in uplink</b>
<b>Uplink duty factor in one special subframe</b>	<b>0~4</b>	7.13%	8.33%
	<b>5~9</b>	14.3%	16.7%

<b>Special subframe(30720·T<sub>s</sub>): Extended cyclic prefix in downlink (UpPTS)</b>			
	<b>Special subframe configuration</b>	<b>Normal cyclic prefix in uplink</b>	<b>Extended cyclic prefix in uplink</b>
<b>Uplink duty factor in one special subframe</b>	<b>0~3</b>	7.13%	8.33%
	<b>4~7</b>	14.3%	16.7%

The highest duty factor is resulted from:

For LTE Band 41 Power class 3

- i. Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- ii. special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- iii. for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is:  $(3+0.167)/5 = 63.3\%$
- iv. for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is:  $(3+0.143)/5 = 62.9\%$
- v. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix  $63.3\%/62.9\% = 1.006$  is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)\* Tune-up Scaling Factor\* scaling factor for extended cyclic prefix.



### <WLAN Conducted Power>

#### General Note:


1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
  - a. When the reported SAR of the initial test position is  $\leq 0.4$  W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
  - b. When the reported SAR of the test position is  $> 0.4$  W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is  $\leq 0.8$  W/kg or all required test position are tested.
  - c. For all positions/configurations, when the reported SAR is  $> 0.8$  W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.



<2.4GHz Bluetooth>

General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 77.36 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to100% for Bluetooth reported SAR calculation





## **14. Antenna Location**

The detailed antenna location information can refer to SAR Test Setup Photos.

## 15. SAR Test Results

### General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - b. For SAR testing of WLAN/Bluetooth signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
  - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)\*Tune-up Scaling Factor
  - d. For BT/WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)\* Duty Cycle scaling factor \* Tune-up scaling factor
  - e. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix  $63.3\%/62.9\% = 1.006$  is applied to scale-up the measured SAR result. The Reported TDD LTE SAR = measured SAR (W/kg)\* Tune-up Scaling Factor\* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - $\leq 0.8$  W/kg or  $2.0$  W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
  - $\leq 0.6$  W/kg or  $1.5$  W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - $\leq 0.4$  W/kg or  $1.0$  W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is  $\geq 0.8$ W/kg. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. Pre KDB648474 D04v01r03, when the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2$  W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset. When headset SAR is less than or equal than without headset SAR, no need to verify the remaining channels for headset SAR.
5. The device implements Proximity sensors/receiver detect mechanism/hotspot trigger reduced power for the power management for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity).
6. The device will invoke corresponding work scenarios power level, which are provided in the operational description.
7. For Some WWAN bands, sensor on reduced power level higher than hotspot reduced power level, so front/back sensor on SAR can represent hotspot conservatively.
8. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension  $> 15.0$  cm or an overall diagonal dimension  $> 16.0$  cm, when hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR  $> 1.2$  W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power (for handheld on state, the maximum full power means reduced power), including tolerance, allowed for phablet modes to compare with the  $1.2$  W/kg SAR test reduction threshold.
  - a. For this device SAR for WWAN transmitter scaled to maximum output power mode for product specific 10g SAR is higher than  $1.2$ W/kg of GSM850/1900, WCDMA Band II/V, LTE Band 2/7/26/38/41 therefore product specific 10g SAR is necessary.
  - b. WLAN 5.3/5.5GHz tested the product specific 10g SAR since it has no hotspot mode.
  - c. When 10-g product specific 10g SAR is considered, SAR thresholds is specified in the procedures for SAR test reduction and exclusion should be multiplied by 2.5.
9. The device has five headsets, only supplier is different, so we chose headset 1 to perform full SAR testing, and headset 2/3/4/5 only verified the worst case of headset 1.
10. For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed for body worn:  
Front: [12 mm](#)  
Back: [20 mm](#)
11. For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed for handheld:  
Front: [9 mm](#)  
Back: [13 mm](#)  
bottom side: [10 mm](#)

**GSM Note:**

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS 2Tx slots for GSM850/GSM1900 are considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq$  ¼ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

**WCDMA Note:**

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq$  ¼ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq$  1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than ¼ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

**LTE Note:**

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq$  0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $>$  1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is  $>$  not ½ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq$  1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is  $>$  not ½ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq$  1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B5 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE B38 SAR test was covered by LTE B41; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
  - a. the maximum output power, including tolerance, for the smaller band is  $\leq$  the larger band to qualify for the SAR test exclusion
  - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band



**WLAN Note:**

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is  $> 0.4$  W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is  $\leq 0.8$  W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is  $> 0.8$  W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.



15.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	GSM850	GPRS(2 Tx slots)	Right Cheek	Full	251	848.8	31.09	32.00	1.233	-0.18	0.436	0.538
	GSM850	GPRS(2 Tx slots)	Right Tilted	Full	251	848.8	31.09	32.00	1.233	0.03	0.210	0.259
	GSM850	GPRS(2 Tx slots)	Left Cheek	Full	251	848.8	31.09	32.00	1.233	-0.05	0.410	0.506
	GSM850	GPRS(2 Tx slots)	Left Tilted	Full	251	848.8	31.09	32.00	1.233	0.12	0.201	0.248
	GSM1900	GPRS(2 Tx slots)	Right Cheek	Full	661	1880	28.25	29.50	1.334	0.12	0.166	0.221
	GSM1900	GPRS(2 Tx slots)	Right Tilted	Full	661	1880	28.25	29.50	1.334	-0.16	0.121	0.161
02	GSM1900	GPRS(2 Tx slots)	Left Cheek	Full	661	1880	28.25	29.50	1.334	-0.08	0.182	0.243
	GSM1900	GPRS(2 Tx slots)	Left Tilted	Full	661	1880	28.25	29.50	1.334	0.05	0.164	0.219

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
03	WCDMA V	RMC 12.2Kbps	Right Cheek	Full	4182	836.4	23.13	24.00	1.222	0.08	0.356	0.435
	WCDMA V	RMC 12.2Kbps	Right Tilted	Full	4182	836.4	23.13	24.00	1.222	0.02	0.168	0.205
	WCDMA V	RMC 12.2Kbps	Left Cheek	Full	4182	836.4	23.13	24.00	1.222	-0.16	0.331	0.404
	WCDMA V	RMC 12.2Kbps	Left Tilted	Full	4182	836.4	23.13	24.00	1.222	0.05	0.161	0.197
	WCDMA II	RMC 12.2Kbps	Right Cheek	Full	9538	1907.6	23.22	24.00	1.197	-0.07	0.238	0.285
	WCDMA II	RMC 12.2Kbps	Right Tilted	Full	9538	1907.6	23.22	24.00	1.197	0.05	0.151	0.181
04	WCDMA II	RMC 12.2Kbps	Left Cheek	Full	9538	1907.6	23.22	24.00	1.197	-0.09	0.275	0.329
	WCDMA II	RMC 12.2Kbps	Left Tilted	Full	9538	1907.6	23.22	24.00	1.197	0.01	0.208	0.249



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
05	LTE Band 5	10M	QPSK	1	25	Right Cheek	Full	20525	836.5	23.25	24.00	1.189	0.04	0.325	<b>0.386</b>
	LTE Band 5	10M	QPSK	1	25	Right Tilted	Full	20525	836.5	23.25	24.00	1.189	0.03	0.160	0.190
	LTE Band 5	10M	QPSK	1	25	Left Cheek	Full	20525	836.5	23.25	24.00	1.189	0.13	0.304	0.361
	LTE Band 5	10M	QPSK	1	25	Left Tilted	Full	20525	836.5	23.25	24.00	1.189	-0.02	0.151	0.179
	LTE Band 5	10M	QPSK	25	12	Right Cheek	Full	20525	836.5	22.05	23.00	1.245	0.11	0.194	0.241
	LTE Band 5	10M	QPSK	25	12	Right Tilted	Full	20525	836.5	22.05	23.00	1.245	0.02	0.095	0.118
	LTE Band 5	10M	QPSK	25	12	Left Cheek	Full	20525	836.5	22.05	23.00	1.245	-0.18	0.182	0.227
	LTE Band 5	10M	QPSK	25	12	Left Tilted	Full	20525	836.5	22.05	23.00	1.245	0.08	0.088	0.110
06	LTE Band 26	15M	QPSK	1	37	Right Cheek	Full	26965	841.5	23.15	24.00	1.216	0.06	0.336	<b>0.409</b>
	LTE Band 26	15M	QPSK	1	37	Right Tilted	Full	26965	841.5	23.15	24.00	1.216	-0.12	0.148	0.180
	LTE Band 26	15M	QPSK	1	37	Left Cheek	Full	26965	841.5	23.15	24.00	1.216	-0.14	0.308	0.375
	LTE Band 26	15M	QPSK	1	37	Left Tilted	Full	26965	841.5	23.15	24.00	1.216	0.14	0.143	0.174
	LTE Band 26	15M	QPSK	36	39	Right Cheek	Full	26965	841.5	22.07	23.00	1.239	0.07	0.180	0.223
	LTE Band 26	15M	QPSK	36	39	Right Tilted	Full	26965	841.5	22.07	23.00	1.239	0.12	0.077	0.096
	LTE Band 26	15M	QPSK	36	39	Left Cheek	Full	26965	841.5	22.07	23.00	1.239	-0.08	0.166	0.206
	LTE Band 26	15M	QPSK	36	39	Left Tilted	Full	26965	841.5	22.07	23.00	1.239	0.02	0.074	0.092
07	LTE Band 2	20M	QPSK	1	49	Right Cheek	Full	18900	1880	23.09	24.00	1.233	-0.07	0.212	0.261
	LTE Band 2	20M	QPSK	1	49	Right Tilted	Full	18900	1880	23.09	24.00	1.233	0.02	0.133	0.164
	LTE Band 2	20M	QPSK	1	49	Left Cheek	Full	18900	1880	23.09	24.00	1.233	-0.02	0.221	<b>0.273</b>
	LTE Band 2	20M	QPSK	1	49	Left Tilted	Full	18900	1880	23.09	24.00	1.233	0.05	0.155	0.191
	LTE Band 2	20M	QPSK	50	0	Right Cheek	Full	18900	1880	21.90	23.00	1.288	-0.08	0.118	0.152
	LTE Band 2	20M	QPSK	50	0	Right Tilted	Full	18900	1880	21.90	23.00	1.288	0.05	0.083	0.106
	LTE Band 2	20M	QPSK	50	0	Left Cheek	Full	18900	1880	21.90	23.00	1.288	0.03	0.121	0.156
	LTE Band 2	20M	QPSK	50	0	Left Tilted	Full	18900	1880	21.90	23.00	1.288	0.06	0.098	0.126
08	LTE Band 7	20M	QPSK	1	49	Right Cheek	Full	21100	2535	23.29	24.00	1.178	-0.07	0.132	0.155
	LTE Band 7	20M	QPSK	1	49	Right Tilted	Full	21100	2535	23.29	24.00	1.178	-0.12	0.088	0.103
	LTE Band 7	20M	QPSK	1	49	Left Cheek	Full	21100	2535	23.29	24.00	1.178	0.11	0.196	<b>0.231</b>
	LTE Band 7	20M	QPSK	1	49	Left Tilted	Full	21100	2535	23.29	24.00	1.178	0.08	0.091	0.108
	LTE Band 7	20M	QPSK	50	0	Right Cheek	Full	21100	2535	22.37	23.00	1.156	0.03	0.115	0.133
	LTE Band 7	20M	QPSK	50	0	Right Tilted	Full	21100	2535	22.37	23.00	1.156	0.05	0.060	0.069
	LTE Band 7	20M	QPSK	50	0	Left Cheek	Full	21100	2535	22.37	23.00	1.156	-0.18	0.165	0.191
	LTE Band 7	20M	QPSK	50	0	Left Tilted	Full	21100	2535	22.37	23.00	1.156	0.05	0.079	0.091

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
09	LTE Band 41	20M	QPSK	1	49	Right Cheek	Full	40185	2549.5	23.25	24.00	1.189	62.9	1.006	0.09	0.091	0.109
	LTE Band 41	20M	QPSK	1	49	Right Tilted	Full	40185	2549.5	23.25	24.00	1.189	62.9	1.006	0.08	0.056	0.067
	LTE Band 41	20M	QPSK	1	49	Left Cheek	Full	40185	2549.5	23.25	24.00	1.189	62.9	1.006	0.14	0.140	<b>0.167</b>
	LTE Band 41	20M	QPSK	1	49	Left Tilted	Full	40185	2549.5	23.25	24.00	1.189	62.9	1.006	-0.08	0.062	0.074
	LTE Band 41	20M	QPSK	50	24	Right Cheek	Full	40185	2549.5	22.24	23.00	1.191	62.9	1.006	0.16	0.065	0.077
	LTE Band 41	20M	QPSK	50	24	Right Tilted	Full	40185	2549.5	22.24	23.00	1.191	62.9	1.006	0.05	0.041	0.049
	LTE Band 41	20M	QPSK	50	24	Left Cheek	Full	40185	2549.5	22.24	23.00	1.191	62.9	1.006	-0.03	0.091	0.109
	LTE Band 41	20M	QPSK	50	24	Left Tilted	Full	40185	2549.5	22.24	23.00	1.191	62.9	1.006	0.12	0.041	0.049





<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.09	0.299	0.379
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.02	0.335	0.425
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.14	0.633	0.802
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.09	0.631	0.800
10	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	Full	6	2437	18.50	19.50	1.259	99.31	1.007	0.1	0.802	<b>1.017</b>
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	Full	6	2437	18.50	19.50	1.259	99.31	1.007	0.02	0.704	0.892

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Cheek	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.02	0.261	0.406
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Tilted	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.19	0.294	0.457
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Cheek	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.05	0.395	0.615
11	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.09	0.531	<b>0.826</b>
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	Full	62	5310	15.72	17.00	1.343	96.32	1.038	0.04	0.369	0.514
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Cheek	Reduced	122	5610	15.54	17.00	1.401	92.79	1.078	0.08	0.318	0.480
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Tilted	Reduced	122	5610	15.54	17.00	1.401	92.79	1.078	0.15	0.395	0.597
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	Reduced	122	5610	15.54	17.00	1.401	92.79	1.078	-0.04	0.644	0.973
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	Reduced	122	5610	15.54	17.00	1.401	92.79	1.078	0.03	0.603	0.911
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	Reduced	138	5690	15.49	17.00	1.417	92.79	1.078	0.03	0.617	0.943
12	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	Reduced	138	5690	15.49	17.00	1.417	92.79	1.078	-0.14	0.701	<b>1.071</b>
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	Full	155	5775	12.25	13.5	1.334	92.79	1.078	0.01	<0.001	<0.001
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Tilted	Full	155	5775	12.25	13.5	1.334	92.79	1.078	0.02	<0.001	<0.001
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Cheek	Full	155	5775	12.25	13.5	1.334	92.79	1.078	0.13	0.223	0.321
13	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	Full	155	5775	12.25	13.5	1.334	92.79	1.078	-0.09	0.249	<b>0.358</b>

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Right Cheek	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.18	0.044	0.069
	Bluetooth	DH5 1Mbps	Right Tilted	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.09	0.051	0.079
14	Bluetooth	DH5 1Mbps	Left Cheek	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.14	0.109	<b>0.169</b>
	Bluetooth	DH5 1Mbps	Left Tilted	Full	39	2441	11.20	12.00	1.202	77.36	1.293	-0.01	0.107	0.166



15.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
15	GSM850	GPRS(2 Tx slots)	Front	5mm	Reduced	251	848.8	29.70	30.50	1.202	-0.04	0.568	0.683
	GSM850	GPRS(2 Tx slots)	Back	5mm	Reduced	251	848.8	29.70	30.50	1.202	0.11	1.060	1.274
	GSM850	GPRS(2 Tx slots)	Left Side	5mm	Reduced	251	848.8	29.70	30.50	1.202	-0.06	0.316	0.380
	GSM850	GPRS(2 Tx slots)	Right Side	5mm	Reduced	251	848.8	29.70	30.50	1.202	-0.03	0.442	0.531
	GSM850	GPRS(2 Tx slots)	Bottom Side	5mm	Reduced	251	848.8	29.70	30.50	1.202	-0.03	0.185	0.222
	GSM850	GPRS(2 Tx slots)	Back	5mm	Reduced	128	824.2	29.39	30.50	1.291	0.02	0.649	0.838
	GSM850	GPRS(2 Tx slots)	Back	5mm	Reduced	189	836.4	29.53	30.50	1.250	-0.1	0.878	1.098
	GSM1900	GPRS(2 Tx slots)	Front	5mm	Reduced	661	1880	25.76	27.00	1.330	-0.04	0.693	0.922
16	GSM1900	GPRS(2 Tx slots)	Back	5mm	Reduced	661	1880	25.76	27.00	1.330	0.11	0.821	1.092
	GSM1900	GPRS(2 Tx slots)	Left Side	5mm	Reduced	661	1880	24.72	26.00	1.343	0.04	0.173	0.232
	GSM1900	GPRS(2 Tx slots)	Right Side	5mm	Reduced	661	1880	24.72	26.00	1.343	-0.04	0.085	0.114
	GSM1900	GPRS(2 Tx slots)	Bottom Side	5mm	Reduced	661	1880	24.72	26.00	1.343	-0.04	0.747	1.003
	GSM1900	GPRS(2 Tx slots)	Bottom Side	5mm	Reduced	512	1850.2	24.67	26.00	1.358	0.14	1.030	1.399
	GSM1900	GPRS(2 Tx slots)	Bottom Side	5mm	Reduced	810	1909.8	24.68	26.00	1.355	0.03	0.938	1.271
	GSM1900	GPRS(2 Tx slots)	Front	5mm	Reduced	512	1850.2	25.59	27.00	1.384	0.12	0.733	1.014
	GSM1900	GPRS(2 Tx slots)	Front	5mm	Reduced	810	1909.8	25.74	27.00	1.337	0.19	0.703	0.940
	GSM1900	GPRS(2 Tx slots)	Back	5mm	Reduced	512	1850.2	25.59	27.00	1.384	0.13	0.805	1.114
	GSM1900	GPRS(2 Tx slots)	Back	5mm	Reduced	810	1909.8	25.74	27.00	1.337	0.11	0.822	1.099

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
17	WCDMA V	RMC 12.2Kbps	Front	5mm	Reduced	4182	836.4	21.94	23.00	1.276	-0.08	0.490	0.625
	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4182	836.4	21.94	23.00	1.276	-0.12	0.927	1.183
	WCDMA V	RMC 12.2Kbps	Left Side	5mm	Reduced	4182	836.4	21.94	23.00	1.276	0.07	0.335	0.428
	WCDMA V	RMC 12.2Kbps	Right Side	5mm	Reduced	4182	836.4	21.94	23.00	1.276	0.01	0.396	0.505
	WCDMA V	RMC 12.2Kbps	Bottom Side	5mm	Reduced	4182	836.4	21.94	23.00	1.276	0.13	0.169	0.216
	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4132	826.4	21.90	23.00	1.288	0.02	0.941	1.212
	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4233	846.6	21.83	23.00	1.309	-0.02	0.960	1.257
	WCDMA II	RMC 12.2Kbps	Front	5mm	Reduced	9538	1907.6	19.33	20.50	1.309	0.07	0.717	0.939
	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9538	1907.6	19.33	20.50	1.309	-0.12	0.813	1.064
	WCDMA II	RMC 12.2Kbps	Left Side	5mm	Reduced	9538	1907.6	17.92	19.00	1.282	0.11	0.215	0.276
	WCDMA II	RMC 12.2Kbps	Right Side	5mm	Reduced	9538	1907.6	17.92	19.00	1.282	0.12	0.073	0.094
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9538	1907.6	17.92	19.00	1.282	-0.05	0.840	1.077
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9262	1852.4	17.84	19.00	1.306	0.05	0.884	1.155
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9400	1880	17.87	19.00	1.297	0.11	0.822	1.066
	18	WCDMA II	RMC 12.2Kbps	Front	5mm	Reduced	9262	1852.4	19.08	20.50	1.387	0.1	0.660
WCDMA II		RMC 12.2Kbps	Front	5mm	Reduced	9400	1880	19.32	20.50	1.312	-0.1	0.734	0.963
WCDMA II		RMC 12.2Kbps	Back	5mm	Reduced	9262	1852.4	19.08	20.50	1.387	0.06	0.981	1.360
WCDMA II		RMC 12.2Kbps	Back	5mm	Reduced	9400	1880	19.32	20.50	1.312	0.01	0.887	1.164



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
19	LTE Band 5	10M	QPSK	1	25	Front	5mm	Full	20525	836.5	23.25	24.00	1.189	0.02	0.528	0.628
	LTE Band 5	10M	QPSK	1	25	Back	5mm	Full	20525	836.5	23.25	24.00	1.189	-0.08	0.998	1.186
	LTE Band 5	10M	QPSK	1	25	Left Side	5mm	Full	20525	836.5	23.25	24.00	1.189	0.18	0.364	0.433
	LTE Band 5	10M	QPSK	1	25	Right Side	5mm	Full	20525	836.5	23.25	24.00	1.189	0.08	0.403	0.479
	LTE Band 5	10M	QPSK	1	25	Bottom Side	5mm	Full	20525	836.5	23.25	24.00	1.189	-0.01	0.176	0.209
	LTE Band 5	10M	QPSK	25	12	Front	5mm	Full	20525	836.5	22.05	23.00	1.245	0.05	0.334	0.416
	LTE Band 5	10M	QPSK	25	12	Back	5mm	Full	20525	836.5	22.05	23.00	1.245	-0.08	0.608	0.757
	LTE Band 5	10M	QPSK	25	12	Left Side	5mm	Full	20525	836.5	22.05	23.00	1.245	0.01	0.233	0.290
	LTE Band 5	10M	QPSK	25	12	Right Side	5mm	Full	20525	836.5	22.05	23.00	1.245	-0.12	0.255	0.317
	LTE Band 5	10M	QPSK	25	12	Bottom Side	5mm	Full	20525	836.5	22.05	23.00	1.245	-0.01	0.118	0.147
LTE Band 5	10M	QPSK	50	0	Back	5mm	Full	20525	836.5	21.94	23.00	1.276	0.01	0.620	0.791	
20	LTE Band 26	15M	QPSK	1	37	Front	5mm	Reduced	26965	841.5	22.05	23.00	1.245	0.19	0.498	0.620
	LTE Band 26	15M	QPSK	1	37	Back	5mm	Reduced	26965	841.5	22.05	23.00	1.245	0.17	0.886	1.103
	LTE Band 26	15M	QPSK	1	37	Left Side	5mm	Reduced	26965	841.5	22.05	23.00	1.245	-0.09	0.335	0.417
	LTE Band 26	15M	QPSK	1	37	Right Side	5mm	Reduced	26965	841.5	22.05	23.00	1.245	-0.09	0.371	0.462
	LTE Band 26	15M	QPSK	1	37	Bottom Side	5mm	Reduced	26965	841.5	22.05	23.00	1.245	-0.06	0.117	0.146
	LTE Band 26	15M	QPSK	1	37	Back	5mm	Reduced	26765	821.5	22.04	23.00	1.247	0.17	0.862	1.075
	LTE Band 26	15M	QPSK	1	37	Back	5mm	Reduced	26865	831.5	22.01	23.00	1.256	0.12	0.963	1.210
	LTE Band 26	15M	QPSK	36	39	Front	5mm	Reduced	26965	841.5	22.01	23.00	1.256	-0.04	0.335	0.421
	LTE Band 26	15M	QPSK	36	39	Back	5mm	Reduced	26965	841.5	22.01	23.00	1.256	0.17	0.674	0.847
	LTE Band 26	15M	QPSK	36	39	Left Side	5mm	Reduced	26965	841.5	22.01	23.00	1.256	0.11	0.204	0.256
21	LTE Band 2	20M	QPSK	1	49	Front	5mm	Reduced	18900	1880	19.44	20.50	1.276	0.19	0.723	0.923
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	18900	1880	19.44	20.50	1.276	0.08	0.900	1.149
	LTE Band 2	20M	QPSK	1	49	Left Side	5mm	Reduced	18900	1880	17.77	19.00	1.327	0.1	0.173	0.230
	LTE Band 2	20M	QPSK	1	49	Right Side	5mm	Reduced	18900	1880	17.77	19.00	1.327	0.16	0.060	0.080
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	18900	1880	17.77	19.00	1.327	0.08	0.910	1.208
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	18700	1860	17.59	19.00	1.384	0.01	0.969	1.341
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	19100	1900	17.66	19.00	1.361	0.04	0.802	1.092
	LTE Band 2	20M	QPSK	1	49	Front	5mm	Reduced	18700	1860	19.28	20.50	1.324	0.14	0.764	1.012
	LTE Band 2	20M	QPSK	1	49	Front	5mm	Reduced	19100	1900	19.33	20.50	1.309	-0.02	0.702	0.919
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	18700	1860	19.28	20.50	1.324	0.04	0.911	1.206
21	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	19100	1900	19.33	20.50	1.309	0.06	0.823	1.077
	LTE Band 2	20M	QPSK	50	0	Front	5mm	Reduced	18900	1880	19.41	20.50	1.285	-0.14	0.726	0.933
	LTE Band 2	20M	QPSK	50	0	Back	5mm	Reduced	18900	1880	19.41	20.50	1.285	0.12	0.806	1.036
	LTE Band 2	20M	QPSK	50	0	Left Side	5mm	Reduced	18900	1880	17.73	19.00	1.340	0.04	0.172	0.230
	LTE Band 2	20M	QPSK	50	0	Right Side	5mm	Reduced	18900	1880	17.73	19.00	1.340	0.13	0.082	0.110
	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	Reduced	18900	1880	17.73	19.00	1.340	0.08	0.855	1.145
	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	Reduced	18700	1860	17.64	19.00	1.368	0.14	1.000	1.368
	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	Reduced	19100	1900	17.72	19.00	1.343	0.08	0.787	1.057
	LTE Band 2	20M	QPSK	50	0	Front	5mm	Reduced	18700	1860	19.36	20.50	1.300	-0.06	0.772	1.004
	LTE Band 2	20M	QPSK	50	0	Front	5mm	Reduced	19100	1900	19.35	20.50	1.303	0.04	0.729	0.950
LTE Band 2	20M	QPSK	50	0	Back	5mm	Reduced	18700	1860	19.36	20.50	1.300	0.01	0.947	1.231	
LTE Band 2	20M	QPSK	50	0	Back	5mm	Reduced	19100	1900	19.35	20.50	1.303	-0.06	0.843	1.099	
LTE Band 2	20M	QPSK	100	0	Front	5mm	Reduced	18900	1880	19.42	20.50	1.282	-0.08	0.694	0.890	
LTE Band 2	20M	QPSK	100	0	Back	5mm	Reduced	18900	1880	19.42	20.50	1.282	-0.12	0.894	1.146	
LTE Band 2	20M	QPSK	100	0	Bottom Side	5mm	Reduced	18900	1880	17.66	19.00	1.361	0.15	0.721	0.982	



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 7	20M	QPSK	1	49	Front	5mm	Reduced	21100	2535	16.31	17.00	1.172	0.13	0.377	0.442
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	21100	2535	16.31	17.00	1.172	0.14	0.865	1.014
	LTE Band 7	20M	QPSK	1	49	Left Side	5mm	Reduced	21100	2535	15.19	16.00	1.205	-0.02	0.091	0.110
	LTE Band 7	20M	QPSK	1	49	Right Side	5mm	Reduced	21100	2535	15.19	16.00	1.205	-0.03	0.039	0.047
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	21100	2535	15.19	16.00	1.205	-0.13	1.080	1.301
22	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	20850	2510	15.07	16.00	1.239	0.15	1.150	1.425
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	21350	2560	15.18	16.00	1.208	0.16	1.060	1.280
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	20850	2510	16.21	17.00	1.199	0.14	0.949	1.138
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	21350	2560	16.26	17.00	1.186	-0.11	0.837	0.992
	LTE Band 7	20M	QPSK	50	0	Front	5mm	Reduced	21100	2535	16.29	17.00	1.178	0.19	0.383	0.451
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Reduced	21100	2535	16.29	17.00	1.178	-0.09	0.846	0.996
	LTE Band 7	20M	QPSK	50	0	Left Side	5mm	Reduced	21100	2535	15.29	16.00	1.178	0.18	0.081	0.095
	LTE Band 7	20M	QPSK	50	0	Right Side	5mm	Reduced	21100	2535	15.29	16.00	1.178	0.05	0.052	0.061
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Reduced	21100	2535	15.29	16.00	1.178	0.04	1.050	1.236
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Reduced	20850	2510	15.21	16.00	1.199	0.07	1.180	1.415
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Reduced	21350	2560	15.25	16.00	1.189	0.14	0.926	1.101
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Reduced	20850	2510	16.16	17.00	1.213	-0.02	0.832	1.010
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Reduced	21350	2560	16.26	17.00	1.186	0.1	0.823	0.976
	LTE Band 7	20M	QPSK	100	0	Back	5mm	Reduced	21100	2535	16.27	17.00	1.183	0.1	0.842	0.996
	LTE Band 7	20M	QPSK	100	0	Bottom Side	5mm	Reduced	21100	2535	15.28	16.00	1.180	0.02	1.030	1.216



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	49	Front	5mm	Reduced	40185	2549.5	19.38	20.00	1.153	62.9	1.006	0.11	0.374	0.434
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Reduced	40185	2549.5	19.38	20.00	1.153	62.9	1.006	0.08	0.952	1.105
	LTE Band 41	20M	QPSK	1	49	Left Side	5mm	Reduced	40185	2549.5	18.02	18.50	1.117	62.9	1.006	-0.02	0.085	0.096
	LTE Band 41	20M	QPSK	1	49	Right Side	5mm	Reduced	40185	2549.5	18.02	18.50	1.117	62.9	1.006	0.02	0.056	0.063
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Reduced	40185	2549.5	18.02	18.50	1.117	62.9	1.006	0.06	0.962	1.081
23	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Reduced	39750	2506	17.61	18.50	1.227	62.9	1.006	0.17	1.080	1.334
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Reduced	40620	2593	17.63	18.50	1.222	62.9	1.006	0.07	0.731	0.898
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Reduced	41055	2636.5	17.69	18.50	1.205	62.9	1.006	0.1	0.695	0.843
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Reduced	41490	2680	17.66	18.50	1.213	62.9	1.006	0.02	0.669	0.817
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Reduced	39750	2506	19.28	20.00	1.180	62.9	1.006	0.05	1.050	1.247
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Reduced	40620	2593	19.28	20.00	1.180	62.9	1.006	-0.07	0.945	1.122
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Reduced	41055	2636.5	19.27	20.00	1.183	62.9	1.006	0.04	0.844	1.004
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Reduced	41490	2680	19.17	20.00	1.211	62.9	1.006	0.11	0.834	1.016
	LTE Band 41	20M	QPSK	50	24	Front	5mm	Reduced	40185	2549.5	19.32	20.00	1.169	62.9	1.006	0.09	0.370	0.435
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Reduced	40185	2549.5	19.32	20.00	1.169	62.9	1.006	0.03	0.919	1.081
	LTE Band 41	20M	QPSK	50	24	Left Side	5mm	Reduced	40185	2549.5	17.96	18.50	1.132	62.9	1.006	0.02	0.087	0.099
	LTE Band 41	20M	QPSK	50	24	Right Side	5mm	Reduced	40185	2549.5	17.96	18.50	1.132	62.9	1.006	-0.1	0.037	0.042
	LTE Band 41	20M	QPSK	50	24	Bottom Side	5mm	Reduced	40185	2549.5	17.96	18.50	1.132	62.9	1.006	-0.12	0.904	1.030
	LTE Band 41	20M	QPSK	50	24	Bottom Side	5mm	Reduced	39750	2506	17.76	18.50	1.186	62.9	1.006	-0.07	1.110	1.324
	LTE Band 41	20M	QPSK	50	24	Bottom Side	5mm	Reduced	40620	2593	17.69	18.50	1.205	62.9	1.006	0.14	0.738	0.895
	LTE Band 41	20M	QPSK	50	24	Bottom Side	5mm	Reduced	41055	2636.5	17.64	18.50	1.219	62.9	1.006	0.1	0.682	0.836
	LTE Band 41	20M	QPSK	50	24	Bottom Side	5mm	Reduced	41490	2680	17.79	18.50	1.178	62.9	1.006	0.17	0.539	0.639
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Reduced	39750	2506	19.19	20.00	1.205	62.9	1.006	0.09	1.000	1.212
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Reduced	40620	2593	19.23	20.00	1.194	62.9	1.006	0.18	0.922	1.107
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Reduced	41055	2636.5	19.20	20.00	1.202	62.9	1.006	0.12	0.842	1.018
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Reduced	41490	2680	19.27	20.00	1.183	62.9	1.006	0.16	0.811	0.965
	LTE Band 41	20M	QPSK	100	0	Back	5mm	Reduced	40185	2549.5	19.30	20.00	1.175	62.9	1.006	0.02	0.883	1.044
	LTE Band 41	20M	QPSK	100	0	Bottom Side	5mm	Reduced	40185	2549.5	17.86	18.50	1.159	62.9	1.006	0.15	0.932	1.086

<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.02	0.353	0.448
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	-0.13	0.644	0.816
	WLAN2.4GHz	802.11b 1Mbps	Left Side	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.07	0.046	0.058
	WLAN2.4GHz	802.11b 1Mbps	Right Side	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.11	0.355	0.450
	WLAN2.4GHz	802.11b 1Mbps	Top Side	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.05	0.417	0.529
24	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Full	6	2437	18.50	19.50	1.259	99.31	1.007	0.15	0.743	0.942



<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.2GHz	802.11n-HT40 MCS0	Front	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	0.01	0.201	0.301
25	WLAN5.2GHz	802.11n-HT40 MCS0	Back	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	0.09	0.616	<b>0.924</b>
	WLAN5.2GHz	802.11n-HT40 MCS0	Back	5mm	Full	38	5190	17.28	19.00	1.486	96.32	1.038	0.03	0.456	0.703
	WLAN5.2GHz	802.11n-HT40 MCS0	Left Side	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	0.11	0.092	0.138
	WLAN5.2GHz	802.11n-HT40 MCS0	Right Side	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	0.05	0.101	0.151
	WLAN5.2GHz	802.11n-HT40 MCS0	Top Side	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	-0.13	0.581	0.871
	WLAN5.2GHz	802.11n-HT40 MCS0	Top Side	5mm	Full	38	5190	17.28	19.00	1.486	96.32	1.038	0.06	0.529	0.816
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	5mm	Full	155	5775	12.25	13.5	1.334	92.79	1.078	-0.03	0.123	0.177
26	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm	Full	155	5775	12.25	13.5	1.334	92.79	1.078	0.15	0.436	<b>0.627</b>
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Side	5mm	Full	155	5775	12.25	13.5	1.334	92.79	1.078	0.01	<0.001	<0.001
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Side	5mm	Full	155	5775	12.25	13.5	1.334	92.79	1.078	-0.05	0.113	0.162
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Full	155	5775	12.25	13.5	1.334	92.79	1.078	0.14	0.386	0.555

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Front	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.09	0.074	0.116
27	Bluetooth	DH5 1Mbps	Back	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.08	0.083	<b>0.129</b>
	Bluetooth	DH5 1Mbps	Left Side	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	-0.07	0.006	0.009
	Bluetooth	DH5 1Mbps	Right Side	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.02	0.073	0.113
	Bluetooth	DH5 1Mbps	Top Side	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	-0.02	0.056	0.086



15.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS(2 Tx slots)	Front	5mm	-	Reduced	251	848.8	29.70	30.50	1.202	-0.04	0.568	0.683
28	GSM850	GPRS(2 Tx slots)	Back	5mm	-	Reduced	251	848.8	29.70	30.50	1.202	0.11	1.060	1.274
	GSM850	GPRS(2 Tx slots)	Back	5mm	-	Reduced	128	824.2	29.39	30.50	1.291	0.02	0.649	0.838
	GSM850	GPRS(2 Tx slots)	Back	5mm	-	Reduced	189	836.4	29.53	30.50	1.250	-0.1	0.878	1.098
	GSM850	GPRS(2 Tx slots)	Back	5mm	Headset 1	Reduced	251	848.8	29.70	30.50	1.202	-0.06	1.040	1.250
	GSM850	GPRS(2 Tx slots)	Back	5mm	Headset 1	Reduced	128	824.2	29.39	30.50	1.291	0.08	0.817	1.055
	GSM850	GPRS(2 Tx slots)	Back	5mm	Headset 1	Reduced	189	836.4	29.53	30.50	1.250	-0.18	0.910	1.138
	GSM850	GPRS(2 Tx slots)	Front	12mm	-	Full	251	848.8	31.09	32.00	1.233	0.03	0.356	0.439
	GSM850	GPRS(2 Tx slots)	Back	20mm	-	Full	251	848.8	31.09	32.00	1.233	0.05	0.321	0.396
	GSM1900	GPRS(2 Tx slots)	Front	5mm	-	Reduced	661	1880	25.76	27.00	1.330	-0.04	0.693	0.922
	GSM1900	GPRS(2 Tx slots)	Back	5mm	-	Reduced	661	1880	25.76	27.00	1.330	0.11	0.821	1.092
	GSM1900	GPRS(2 Tx slots)	Front	5mm	-	Reduced	512	1850.2	25.59	27.00	1.384	0.12	0.733	1.014
	GSM1900	GPRS(2 Tx slots)	Front	5mm	-	Reduced	810	1909.8	25.74	27.00	1.337	0.19	0.703	0.940
29	GSM1900	GPRS(2 Tx slots)	Back	5mm	-	Reduced	512	1850.2	25.59	27.00	1.384	0.12	0.805	1.114
	GSM1900	GPRS(2 Tx slots)	Back	5mm	-	Reduced	810	1909.8	25.74	27.00	1.337	0.11	0.822	1.099
	GSM1900	GPRS(2 Tx slots)	Front	12mm	-	Full	512	1850.2	28.21	29.50	1.346	0.07	0.512	0.689
	GSM1900	GPRS(2 Tx slots)	Back	20mm	-	Full	512	1850.2	28.21	29.50	1.346	-0.07	0.244	0.328

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	5mm	-	Reduced	4182	836.4	21.94	23.00	1.276	-0.08	0.490	0.625
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4182	836.4	21.94	23.00	1.276	-0.12	0.927	1.183
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4132	826.4	21.90	23.00	1.288	0.02	0.941	1.212
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4233	846.6	21.83	23.00	1.309	-0.16	0.960	1.257
30	WCDMA V	RMC 12.2Kbps	Back	5mm	Headset 1	Reduced	4233	846.6	21.83	23.00	1.309	-0.07	0.976	1.278
	WCDMA V	RMC 12.2Kbps	Back	5mm	Headset 1	Reduced	4182	836.4	21.94	23.00	1.276	0.16	0.932	1.190
	WCDMA V	RMC 12.2Kbps	Back	5mm	Headset 1	Reduced	4132	826.4	21.90	23.00	1.288	0.15	0.932	1.201
	WCDMA V	RMC 12.2Kbps	Front	12mm	-	Full	4182	836.4	23.13	24.00	1.222	0.1	0.266	0.325
	WCDMA V	RMC 12.2Kbps	Back	20mm	Headset 1	Full	4233	846.6	22.94	24.00	1.276	-0.04	0.261	0.333
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	Reduced	9538	1907.6	19.33	20.50	1.309	0.07	0.717	0.939
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9538	1907.6	19.33	20.50	1.309	-0.12	0.813	1.064
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	Reduced	9262	1852.4	19.08	20.50	1.387	0.1	0.784	1.087
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	Reduced	9400	1880	19.32	20.50	1.312	-0.1	0.734	0.963
31	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9262	1852.4	19.08	20.50	1.387	0.06	0.981	1.360
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9400	1880	19.32	20.50	1.312	0.01	0.887	1.164
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset 1	Reduced	9262	1852.4	19.08	20.50	1.387	0.14	0.978	1.356
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset 2	Reduced	9262	1852.4	19.08	20.50	1.387	0.07	0.966	1.340
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset 3	Reduced	9262	1852.4	19.08	20.50	1.387	0.11	0.977	1.355
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset 4	Reduced	9262	1852.4	19.08	20.50	1.387	-0.03	0.955	1.324
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset 5	Reduced	9262	1852.4	19.08	20.50	1.387	0.08	0.970	1.345
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset 1	Reduced	9400	1880	19.32	20.50	1.312	0.05	0.892	1.170
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset 1	Reduced	9538	1907.6	19.33	20.50	1.309	0.04	0.878	1.149
	WCDMA II	RMC 12.2Kbps	Front	12mm	-	Full	9262	1852.4	23.09	24.00	1.233	0.14	0.573	0.707
	WCDMA II	RMC 12.2Kbps	Back	20mm	-	Full	9262	1852.4	23.09	24.00	1.233	0.04	0.286	0.353



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 5	10M	QPSK	1	25	Front	5mm	-	Full	20525	836.5	23.25	24.00	1.189	0.02	0.528	0.628
32	LTE Band 5	10M	QPSK	1	25	Back	5mm	-	Full	20525	836.5	23.25	24.00	1.189	-0.08	0.998	1.186
	LTE Band 5	10M	QPSK	25	12	Front	5mm	-	Full	20525	836.5	22.05	23.00	1.245	0.05	0.334	0.416
	LTE Band 5	10M	QPSK	25	12	Back	5mm	-	Full	20525	836.5	22.05	23.00	1.245	-0.08	0.608	0.757
	LTE Band 5	10M	QPSK	50	0	Back	5mm	-	Full	20525	836.5	21.94	23.00	1.276	0.01	0.620	0.791
	LTE Band 26	15M	QPSK	1	37	Front	5mm	-	Reduced	26965	841.5	22.05	23.00	1.245	0.19	0.498	0.620
	LTE Band 26	15M	QPSK	1	37	Back	5mm	-	Reduced	26965	841.5	22.05	23.00	1.245	0.17	0.886	1.103
	LTE Band 26	15M	QPSK	1	37	Back	5mm	-	Reduced	26765	821.5	22.04	23.00	1.247	0.17	0.862	1.075
33	LTE Band 26	15M	QPSK	1	37	Back	5mm	-	Reduced	26865	831.5	22.01	23.00	1.256	0.12	0.963	1.210
	LTE Band 26	15M	QPSK	1	37	Back	5mm	Headset 1	Reduced	26865	831.5	22.01	23.00	1.256	0.01	0.890	1.118
	LTE Band 26	15M	QPSK	1	37	Back	5mm	Headset 1	Reduced	26765	821.5	22.04	23.00	1.247	-0.06	0.886	1.105
	LTE Band 26	15M	QPSK	1	37	Back	5mm	Headset 1	Reduced	26965	841.5	22.05	23.00	1.245	0.06	0.901	1.121
	LTE Band 26	15M	QPSK	1	37	Front	12mm	-	Full	26965	841.5	23.15	24.00	1.216	0.11	0.270	0.328
	LTE Band 26	15M	QPSK	1	37	Back	20mm	-	Full	26865	831.5	22.98	24.00	1.265	-0.14	0.270	0.341
	LTE Band 26	15M	QPSK	36	39	Front	5mm	-	Reduced	26965	841.5	22.01	23.00	1.256	-0.04	0.335	0.421
	LTE Band 26	15M	QPSK	36	39	Back	5mm	-	Reduced	26965	841.5	22.01	23.00	1.256	0.17	0.674	0.847
	LTE Band 26	15M	QPSK	36	39	Back	5mm	-	Reduced	26765	821.5	21.98	23.00	1.265	-0.03	0.581	0.735
	LTE Band 26	15M	QPSK	36	39	Back	5mm	-	Reduced	26865	831.5	21.99	23.00	1.262	-0.12	0.650	0.820
	LTE Band 26	15M	QPSK	75	0	Back	5mm	-	Reduced	26965	841.5	22.03	23.00	1.250	0.11	0.626	0.783
	LTE Band 2	20M	QPSK	1	49	Front	5mm	-	Reduced	18900	1880	19.44	20.50	1.276	0.19	0.723	0.923
	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	18900	1880	19.44	20.50	1.276	0.08	0.900	1.149
	LTE Band 2	20M	QPSK	1	49	Front	5mm	-	Reduced	18700	1860	19.28	20.50	1.324	0.14	0.764	1.012
	LTE Band 2	20M	QPSK	1	49	Front	5mm	-	Reduced	19100	1900	19.33	20.50	1.309	-0.02	0.702	0.919
	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	18700	1860	19.28	20.50	1.324	0.04	0.911	1.206
	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	19100	1900	19.33	20.50	1.309	0.06	0.823	1.077
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	18700	1860	19.28	20.50	1.324	-0.14	0.994	1.316
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	18900	1880	19.44	20.50	1.276	0.16	0.836	1.067
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	19100	1900	19.33	20.50	1.309	-0.07	0.797	1.043
	LTE Band 2	20M	QPSK	1	49	Front	12mm	-	Full	18700	1860	23.03	24.00	1.250	0.01	0.340	0.425
	LTE Band 2	20M	QPSK	1	49	Back	20mm	Headset 1	Full	18700	1860	23.03	24.00	1.250	0.05	0.163	0.204
	LTE Band 2	20M	QPSK	50	0	Front	5mm	-	Reduced	18900	1880	19.41	20.50	1.285	-0.14	0.726	0.933
	LTE Band 2	20M	QPSK	50	0	Back	5mm	-	Reduced	18900	1880	19.41	20.50	1.285	0.12	0.806	1.036
	LTE Band 2	20M	QPSK	50	0	Front	5mm	-	Reduced	18700	1860	19.36	20.50	1.300	-0.06	0.772	1.004
	LTE Band 2	20M	QPSK	50	0	Front	5mm	-	Reduced	19100	1900	19.35	20.50	1.303	0.04	0.729	0.950
	LTE Band 2	20M	QPSK	50	0	Back	5mm	-	Reduced	18700	1860	19.36	20.50	1.300	0.01	0.947	1.231
	LTE Band 2	20M	QPSK	50	0	Back	5mm	-	Reduced	19100	1900	19.35	20.50	1.303	-0.06	0.843	1.099
34	LTE Band 2	20M	QPSK	50	0	Back	5mm	Headset 1	Reduced	18700	1860	19.36	20.50	1.300	0.17	1.040	1.352
	LTE Band 2	20M	QPSK	50	0	Back	5mm	Headset 1	Reduced	18900	1880	19.41	20.50	1.285	0.04	0.889	1.143
	LTE Band 2	20M	QPSK	50	0	Back	5mm	Headset 1	Reduced	19100	1900	19.35	20.50	1.303	0.05	0.811	1.057
	LTE Band 2	20M	QPSK	50	0	Front	12mm	-	Full	18700	1860	21.86	23.00	1.300	-0.07	0.324	0.421
	LTE Band 2	20M	QPSK	50	0	Back	20mm	Headset 1	Full	18700	1860	21.86	23.00	1.300	0.08	0.165	0.215
	LTE Band 2	20M	QPSK	100	0	Front	5mm	-	Reduced	18900	1880	19.42	20.50	1.282	-0.08	0.694	0.890
	LTE Band 2	20M	QPSK	100	0	Back	5mm	-	Reduced	18900	1880	19.42	20.50	1.282	-0.12	0.894	1.146





Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 7	20M	QPSK	1	49	Front	5mm	-	Reduced	21100	2535	16.31	17.00	1.172	0.13	0.377	0.442
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	21100	2535	16.31	17.00	1.172	0.04	0.865	1.014
35	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	20850	2510	16.21	17.00	1.199	0.14	0.949	1.138
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	21350	2560	16.26	17.00	1.186	-0.11	0.837	0.992
	LTE Band 7	20M	QPSK	1	49	Front	12mm	-	Full	21100	2535	23.29	24.00	1.178	0.09	0.380	0.447
	LTE Band 7	20M	QPSK	1	49	Back	20mm	-	Full	20850	2510	22.90	24.00	1.288	0.03	0.296	0.381
	LTE Band 7	20M	QPSK	50	0	Front	5mm	-	Reduced	21100	2535	16.29	17.00	1.178	0.19	0.383	0.451
	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	Reduced	21100	2535	16.29	17.00	1.178	-0.09	0.846	0.996
	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	Reduced	20850	2510	16.16	17.00	1.213	-0.02	0.832	1.010
	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	Reduced	21350	2560	16.26	17.00	1.186	0.1	0.823	0.976
	LTE Band 7	20M	QPSK	100	0	Back	5mm	-	Reduced	21100	2535	16.27	17.00	1.183	0.1	0.842	0.996

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	49	Front	5mm	-	Reduced	40185	2549.5	19.38	20.00	1.153	62.9	1.006	0.11	0.394	0.457
	LTE Band 41	20M	QPSK	1	49	Back	5mm	-	Reduced	40185	2549.5	19.38	20.00	1.153	62.9	1.006	0.08	0.952	1.105
36	LTE Band 41	20M	QPSK	1	49	Back	5mm	-	Reduced	39750	2506	19.28	20.00	1.180	62.9	1.006	-0.11	1.050	1.247
	LTE Band 41	20M	QPSK	1	49	Back	5mm	-	Reduced	40620	2593	19.28	20.00	1.180	62.9	1.006	-0.07	0.945	1.122
	LTE Band 41	20M	QPSK	1	49	Back	5mm	-	Reduced	41055	2636.5	19.27	20.00	1.183	62.9	1.006	0.04	0.844	1.004
	LTE Band 41	20M	QPSK	1	49	Back	5mm	-	Reduced	41490	2680	19.17	20.00	1.211	62.9	1.006	0.11	0.834	1.016
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	39750	2506	19.28	20.00	1.180	62.9	1.006	0.15	0.943	1.120
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	40185	2549.5	19.38	20.00	1.153	62.9	1.006	-0.01	0.922	1.070
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	40620	2593	19.28	20.00	1.180	62.9	1.006	0.12	0.886	1.052
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	41055	2636.5	19.27	20.00	1.183	62.9	1.006	0.06	0.800	0.952
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	41490	2680	19.17	20.00	1.211	62.9	1.006	-0.08	0.801	0.976
	LTE Band 41	20M	QPSK	1	49	Front	12mm	-	Full	40185	2549.5	23.25	24.00	1.189	62.9	1.006	0.17	0.306	0.366
	LTE Band 41	20M	QPSK	1	49	Back	20mm	-	Full	39750	2506	22.85	24.00	1.303	62.9	1.006	-0.13	0.245	0.321
	LTE Band 41	20M	QPSK	50	24	Front	5mm	-	Reduced	40185	2549.5	19.32	20.00	1.169	62.9	1.006	0.09	0.370	0.435
	LTE Band 41	20M	QPSK	50	24	Back	5mm	-	Reduced	40185	2549.5	19.32	20.00	1.169	62.9	1.006	0.03	0.919	1.081
	LTE Band 41	20M	QPSK	50	24	Back	5mm	-	Reduced	39750	2506	19.19	20.00	1.205	62.9	1.006	0.09	1.000	1.212
	LTE Band 41	20M	QPSK	50	24	Back	5mm	-	Reduced	40620	2593	19.23	20.00	1.194	62.9	1.006	0.18	0.922	1.107
	LTE Band 41	20M	QPSK	50	24	Back	5mm	-	Reduced	41055	2636.5	19.20	20.00	1.202	62.9	1.006	0.12	0.842	1.018
	LTE Band 41	20M	QPSK	50	24	Back	5mm	-	Reduced	41490	2680	19.27	20.00	1.183	62.9	1.006	0.16	0.811	0.965
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Headset 1	Reduced	39750	2506	19.19	20.00	1.205	62.9	1.006	0.11	0.951	1.153
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Headset 1	Reduced	40185	2549.5	19.32	20.00	1.169	62.9	1.006	-0.09	0.881	1.037
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Headset 1	Reduced	40620	2593	19.23	20.00	1.194	62.9	1.006	0.02	0.859	1.032
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Headset 1	Reduced	41055	2636.5	19.20	20.00	1.202	62.9	1.006	0.17	0.780	0.943
	LTE Band 41	20M	QPSK	50	24	Back	5mm	Headset 1	Reduced	41490	2680	19.27	20.00	1.183	62.9	1.006	0.12	0.776	0.924
	LTE Band 41	20M	QPSK	100	0	Back	5mm	-	Reduced	40185	2549.5	19.30	20.00	1.175	62.9	1.006	0.02	0.883	1.044



<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	Ant 1	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.02	0.353	0.448
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Ant 1	Full	11	2462	18.50	19.50	1.259	99.31	1.007	-0.13	0.644	0.816
37	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Ant 1	Full	6	2437	18.50	19.50	1.259	99.31	1.007	0.15	0.743	<b>0.942</b>

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.3GHz	802.11n-HT40 MCS0	Front	5mm	Ant 1	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.08	0.220	0.342
38	WLAN5.3GHz	802.11n-HT40 MCS0	Back	5mm	Ant 1	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.14	0.669	<b>1.041</b>
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	5mm	Ant 1	Full	62	5310	15.72	17.00	1.342	96.32	1.038	0.17	0.492	0.685
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	5mm	Ant 1	Reduced	122	5610	13.54	15.00	1.401	92.79	1.078	0.06	0.169	0.255
39	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 1	Reduced	122	5610	13.54	15.00	1.401	92.79	1.078	0.19	0.586	<b>0.885</b>
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 1	Reduced	138	5610	13.49	15.00	1.416	92.79	1.078	0.04	0.491	0.749
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	12mm	Ant 1	Full	122	5610	17.54	19.00	1.401	92.79	1.078	-0.04	0.223	0.337
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	20mm	Ant 1	Full	122	5610	17.54	19.00	1.401	92.79	1.078	0.02	0.330	0.498
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	5mm	Ant 1	Full	155	5775	12.25	13.5	1.334	92.79	1.078	-0.03	0.123	0.177
40	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 1	Full	155	5775	12.25	13.5	1.334	92.79	1.078	0.15	0.436	<b>0.627</b>

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Front	5mm	Ant 1	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.09	0.074	0.116
41	Bluetooth	DH5 1Mbps	Back	5mm	Ant 1	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.08	0.083	<b>0.129</b>

**15.4 Product specific 10g SAR**

**<GSM SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
42	GSM850	GPRS(2 Tx slots)	Back	0mm	Full	251	848.8	31.09	32.00	1.233	0.04	1.900	<b>2.343</b>
	GSM850	GPRS(2 Tx slots)	Back	0mm	Full	128	824.2	30.81	32.00	1.315	0.08	1.740	2.288
	GSM850	GPRS(2 Tx slots)	Back	0mm	Full	189	836.4	30.93	32.00	1.279	-0.11	1.810	2.316
	GSM1900	GPRS(2 Tx slots)	Front	0mm	Reduced	661	1880	27.29	28.50	1.321	0.01	1.280	1.691
	GSM1900	GPRS(2 Tx slots)	Back	0mm	Reduced	661	1880	27.29	28.50	1.321	0.16	1.770	2.339
	GSM1900	GPRS(2 Tx slots)	Back	0mm	Reduced	512	1850.2	27.25	28.50	1.334	0.05	1.560	2.080
	GSM1900	GPRS(2 Tx slots)	Back	0mm	Reduced	810	1909.8	27.28	28.50	1.324	-0.08	1.980	2.622
	GSM1900	GPRS(2 Tx slots)	Bottom Side	0mm	Reduced	661	1880	27.29	28.50	1.321	0.07	2.050	2.709
43	GSM1900	GPRS(2 Tx slots)	Bottom Side	0mm	Reduced	512	1850.2	27.25	28.50	1.334	0.08	2.130	<b>2.840</b>
	GSM1900	GPRS(2 Tx slots)	Bottom Side	0mm	Reduced	810	1909.8	27.28	28.50	1.324	0.09	1.950	2.582
	GSM1900	GPRS(2 Tx slots)	Front	9mm	Full	661	1880	28.25	29.50	1.334	0.07	0.380	0.507
	GSM1900	GPRS(2 Tx slots)	Back	13mm	Full	810	1909.8	28.24	29.50	1.337	-0.12	0.296	0.396
	GSM1900	GPRS(2 Tx slots)	Bottom Side	10mm	Full	512	1850.2	28.21	29.50	1.346	0.09	0.535	0.720

**<WCDMA SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4182	836.4	23.13	24.00	1.222	0.15	2.270	2.773
	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4132	826.4	23.09	24.00	1.233	0.1	1.850	2.281
44	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4233	846.6	22.94	24.00	1.276	0.11	2.190	<b>2.795</b>
	WCDMA II	RMC 12.2Kbps	Front	0mm	Reduced	9538	1907.6	20.88	22.00	1.294	0.19	1.370	1.773
	WCDMA II	RMC 12.2Kbps	Back	0mm	Reduced	9538	1907.6	20.88	22.00	1.294	0.02	1.590	2.058
	WCDMA II	RMC 12.2Kbps	Back	0mm	Reduced	9262	1852.4	20.73	22.00	1.340	0.01	1.630	2.184
	WCDMA II	RMC 12.2Kbps	Back	0mm	Reduced	9400	1880	20.87	22.00	1.297	-0.12	1.890	2.452
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9538	1907.6	20.88	22.00	1.294	0.04	2.310	2.990
45	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9262	1852.4	20.73	22.00	1.340	0.16	2.490	<b>3.336</b>
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9400	1880	20.87	22.00	1.297	-0.08	2.470	3.204
	WCDMA II	RMC 12.2Kbps	Front	9mm	Full	9538	1907.6	23.22	24.00	1.197	-0.06	0.453	0.542
	WCDMA II	RMC 12.2Kbps	Back	13mm	Full	9400	1880	23.16	24.00	1.213	-0.04	0.320	0.388
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	Full	9262	1852.4	23.09	24.00	1.233	0.09	0.611	0.753



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
46	LTE Band 26	15M	QPSK	1	37	Back	0mm	Full	26965	841.5	23.15	24.00	1.216	-0.03	2.050	2.493
	LTE Band 26	15M	QPSK	1	37	Back	0mm	Full	26765	821.5	23.10	24.00	1.230	-0.04	1.920	2.362
	LTE Band 26	15M	QPSK	1	37	Back	0mm	Full	26865	831.5	22.98	24.00	1.265	0.08	1.950	2.466
	LTE Band 26	15M	QPSK	36	39	Back	0mm	Full	26965	841.5	22.07	23.00	1.239	0.17	1.150	1.425
	LTE Band 26	15M	QPSK	75	0	Back	0mm	Full	26965	841.5	21.99	23.00	1.262	0.11	1.150	1.451
	LTE Band 2	20M	QPSK	1	49	Front	0mm	Reduced	18900	1880	20.24	21.50	1.337	-0.13	0.980	1.310
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Reduced	18900	1880	20.24	21.50	1.337	0.07	1.440	1.925
	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	18900	1880	20.24	21.50	1.337	-0.02	1.930	2.580
	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	18700	1860	20.07	21.50	1.390	0.11	2.320	3.225
	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	19100	1900	20.20	21.50	1.349	0.14	2.060	2.779
	LTE Band 2	20M	QPSK	1	49	Front	9mm	Full	18900	1880	23.09	24.00	1.233	0.09	0.439	0.541
	LTE Band 2	20M	QPSK	1	49	Back	13mm	Full	18900	1880	23.09	24.00	1.233	-0.15	0.331	0.408
	LTE Band 2	20M	QPSK	1	49	Bottom Side	10mm	Full	18700	1860	23.03	24.00	1.250	-0.01	0.675	0.844
	LTE Band 2	20M	QPSK	50	0	Front	0mm	Reduced	18900	1880	20.20	21.50	1.349	0.15	1.010	1.362
	LTE Band 2	20M	QPSK	50	0	Back	0mm	Reduced	18900	1880	20.20	21.50	1.349	0.07	1.260	1.700
	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	Reduced	18900	1880	20.20	21.50	1.349	0.14	2.280	3.076
47	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	Reduced	18700	1860	20.04	21.50	1.400	0.13	2.450	3.429
	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	Reduced	19100	1900	20.17	21.50	1.358	0.05	2.170	2.948
	LTE Band 2	20M	QPSK	50	0	Front	9mm	Full	18900	1880	21.90	23.00	1.288	0.15	0.342	0.441
	LTE Band 2	20M	QPSK	50	0	Back	13mm	Full	18900	1880	21.90	23.00	1.288	0.07	0.241	0.310
	LTE Band 2	20M	QPSK	50	0	Bottom Side	10mm	Full	18700	1860	21.86	23.00	1.300	-0.06	0.511	0.664
	LTE Band 2	20M	QPSK	100	0	Front	0mm	Reduced	18900	1880	20.19	21.50	1.352	-0.14	0.960	1.298
	LTE Band 2	20M	QPSK	100	0	Back	0mm	Reduced	18900	1880	20.19	21.50	1.352	-0.06	1.260	1.704
	LTE Band 2	20M	QPSK	100	0	Bottom Side	0mm	Reduced	18900	1880	20.19	21.50	1.352	0.01	2.240	3.029
	LTE Band 7	20M	QPSK	1	49	Front	0mm	Reduced	21100	2535	18.42	19.00	1.143	0.11	0.844	0.965
	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	21100	2535	18.42	19.00	1.143	0.09	2.230	2.549
48	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	20850	2510	18.25	19.00	1.189	0.05	2.400	2.852
	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	21350	2560	18.29	19.00	1.178	0.01	2.180	2.567
	LTE Band 7	20M	QPSK	1	49	Bottom Side	0mm	Reduced	21100	2535	18.42	19.00	1.143	0.14	2.060	2.354
	LTE Band 7	20M	QPSK	1	49	Bottom Side	0mm	Reduced	20850	2510	18.25	19.00	1.189	-0.15	1.930	2.294
	LTE Band 7	20M	QPSK	1	49	Bottom Side	0mm	Reduced	21350	2560	18.29	19.00	1.178	-0.05	1.970	2.320
	LTE Band 7	20M	QPSK	1	49	Front	9mm	Full	21100	2535	23.29	24.00	1.178	0.04	0.280	0.330
	LTE Band 7	20M	QPSK	1	49	Back	13mm	Full	20850	2510	22.90	24.00	1.288	0.09	0.350	0.451
	LTE Band 7	20M	QPSK	1	49	Bottom Side	10mm	Full	21100	2535	23.29	24.00	1.178	0.18	0.771	0.908
	LTE Band 7	20M	QPSK	50	0	Front	0mm	Reduced	21100	2535	18.36	19.00	1.159	-0.15	0.871	1.009
	LTE Band 7	20M	QPSK	50	0	Back	0mm	Reduced	21100	2535	18.36	19.00	1.159	0.05	2.280	2.642
	LTE Band 7	20M	QPSK	50	0	Back	0mm	Reduced	20850	2510	18.19	19.00	1.205	0.11	2.240	2.699
	LTE Band 7	20M	QPSK	50	0	Back	0mm	Reduced	21350	2560	18.28	19.00	1.180	-0.03	2.220	2.620
	LTE Band 7	20M	QPSK	50	0	Bottom Side	0mm	Reduced	21100	2535	18.36	19.00	1.159	0.03	2.120	2.457
	LTE Band 7	20M	QPSK	50	0	Bottom Side	0mm	Reduced	20850	2510	18.19	19.00	1.205	0.1	2.030	2.446
	LTE Band 7	20M	QPSK	50	0	Bottom Side	0mm	Reduced	21350	2560	18.28	19.00	1.180	0.14	1.930	2.278
	LTE Band 7	20M	QPSK	100	0	Front	0mm	Reduced	21100	2535	17.98	19.00	1.265	-0.1	0.843	1.066
	LTE Band 7	20M	QPSK	100	0	Back	0mm	Reduced	21100	2535	17.98	19.00	1.265	0.05	2.240	2.833
	LTE Band 7	20M	QPSK	100	0	Bottom Side	0mm	Reduced	21100	2535	17.98	19.00	1.265	0.11	2.070	2.618



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
49	LTE Band 41	20M	QPSK	1	49	Back	0mm	Reduced	40185	2549.5	21.35	22.00	1.161	62.9	1.006	-0.15	2.400	2.804
	LTE Band 41	20M	QPSK	1	49	Back	0mm	Reduced	39750	2506	21.22	22.00	1.197	62.9	1.006	0.09	2.510	3.022
	LTE Band 41	20M	QPSK	1	49	Back	0mm	Reduced	40620	2593	21.23	22.00	1.194	62.9	1.006	-0.04	2.480	2.979
	LTE Band 41	20M	QPSK	1	49	Back	0mm	Reduced	41055	2636.5	21.19	22.00	1.205	62.9	1.006	-0.18	2.380	2.885
	LTE Band 41	20M	QPSK	1	49	Back	0mm	Reduced	41490	2680	21.25	22.00	1.189	62.9	1.006	0.1	1.970	2.355
	LTE Band 41	20M	QPSK	1	49	Bottom Side	0mm	Reduced	40185	2549.5	21.35	22.00	1.161	62.9	1.006	0.01	1.730	2.021
	LTE Band 41	20M	QPSK	1	49	Bottom Side	0mm	Reduced	39750	2506	21.22	22.00	1.197	62.9	1.006	0.17	1.990	2.396
	LTE Band 41	20M	QPSK	1	49	Bottom Side	0mm	Reduced	40620	2593	21.23	22.00	1.194	62.9	1.006	-0.01	1.680	2.018
	LTE Band 41	20M	QPSK	1	49	Bottom Side	0mm	Reduced	41055	2636.5	21.19	22.00	1.205	62.9	1.006	-0.01	1.650	2.000
	LTE Band 41	20M	QPSK	1	49	Bottom Side	0mm	Reduced	41490	2680	21.25	22.00	1.189	62.9	1.006	0.08	1.440	1.722
	LTE Band 41	20M	QPSK	1	49	Back	13mm	Full	39750	2506	22.85	24.00	1.303	62.9	1.006	0.06	0.261	0.342
	LTE Band 41	20M	QPSK	1	49	Bottom Side	10mm	Full	39750	2506	22.85	24.00	1.303	62.9	1.006	-0.05	0.640	0.839
	LTE Band 41	20M	QPSK	50	24	Back	0mm	Reduced	40185	2549.5	21.30	22.00	1.175	62.9	1.006	0.07	2.420	2.860
	LTE Band 41	20M	QPSK	50	24	Back	0mm	Reduced	39750	2506	21.17	22.00	1.211	62.9	1.006	0.13	2.280	2.777
	LTE Band 41	20M	QPSK	50	24	Back	0mm	Reduced	40620	2593	21.19	22.00	1.205	62.9	1.006	-0.08	2.150	2.606
	LTE Band 41	20M	QPSK	50	24	Back	0mm	Reduced	41055	2636.5	21.13	22.00	1.222	62.9	1.006	0.12	2.090	2.569
	LTE Band 41	20M	QPSK	50	24	Back	0mm	Reduced	41490	2680	21.22	22.00	1.197	62.9	1.006	-0.02	1.830	2.203
	LTE Band 41	20M	QPSK	50	24	Bottom Side	0mm	Reduced	40185	2549.5	21.30	22.00	1.175	62.9	1.006	0.05	1.890	2.234
	LTE Band 41	20M	QPSK	50	24	Bottom Side	0mm	Reduced	39750	2506	21.17	22.00	1.211	62.9	1.006	-0.05	2.040	2.484
	LTE Band 41	20M	QPSK	50	24	Bottom Side	0mm	Reduced	40620	2593	21.19	22.00	1.205	62.9	1.006	0.13	1.710	2.073
	LTE Band 41	20M	QPSK	50	24	Bottom Side	0mm	Reduced	41055	2636.5	21.13	22.00	1.222	62.9	1.006	-0.06	1.680	2.065
	LTE Band 41	20M	QPSK	50	24	Bottom Side	0mm	Reduced	41490	2680	21.22	22.00	1.197	62.9	1.006	0.08	1.560	1.878
	LTE Band 41	20M	QPSK	100	0	Back	0mm	Reduced	40185	2549.5	21.33	22.00	1.167	62.9	1.006	0.04	2.260	2.653
	LTE Band 41	20M	QPSK	100	0	Bottom Side	0mm	Reduced	40185	2549.5	21.33	22.00	1.167	62.9	1.006	-0.17	1.950	2.289

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
50	WLAN5.3GHz	802.11n-HT40 MCS0	Front	0mm	Ant 1	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.19	0.206	0.320
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	0mm	Ant 1	Full	54	5270	17.24	19.00	1.499	96.32	1.038	-0.05	0.438	0.681
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Side	0mm	Ant 1	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.09	0.010	0.016
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Side	0mm	Ant 1	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.14	0.089	0.138
	WLAN5.3GHz	802.11n-HT40 MCS0	Top Side	0mm	Ant 1	Full	54	5270	17.24	19.00	1.499	96.32	1.038	0.13	0.628	0.977
51	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	0mm	Ant 1	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.15	0.424	0.640
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	0mm	Ant 1	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.02	1.050	1.584
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Ant 1	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.08	0.064	0.097
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 1	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.05	0.317	0.478
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Ant 1	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.06	1.480	2.233
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Ant 1	Full	138	5690	17.49	19.00	1.417	92.79	1.078	-0.09	1.410	2.154



15.5 Repeated SAR Measurement

<1g>

No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power Reduction	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Left Cheek	0mm	Full	-	6	2437	18.50	19.50	1.259	99.31	1.007	0.1	0.802	1	1.017
2nd	WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Left Cheek	0mm	Full	-	6	2437	18.50	19.50	1.259	99.31	1.007	0.04	0.754	1.064	0.956
1st	GSM850	-	-	-	-	GPRS(2 Tx slots)	Back	5mm	Reduced	-	251	848.8	29.70	30.50	1.202		1.000	0.11	1.060	1	1.274
2nd	GSM850	-	-	-	-	GPRS(2 Tx slots)	Back	5mm	Reduced	-	251	848.8	29.70	30.50	1.202		1.000	0.02	1.000	1.060	1.202
1st	LTE Band 2	20M	QPSK	50	0	-	Back	5mm	Reduced	Headset 1	18700	1860	19.36	20.50	1.300		1.000	0.17	1.040	1	1.352
2nd	LTE Band 2	20M	QPSK	50	0	-	Back	5mm	Reduced	Headset1	18700	1860	19.36	20.50	1.300		1.000	0.12	1.020	1.020	1.326
1st	LTE Band 7	20M	QPSK	50	0	-	Bottom Side	5mm	Reduced	-	20850	2510	15.21	16.00	1.199		1.000	0.07	1.180	1	1.415
2nd	LTE Band 7	20M	QPSK	50	0	-	Bottom Side	5mm	Reduced	-	20850	2510	15.21	16.00	1.199		1.000	0.09	1.050	1.124	1.259

<10g>

No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	Full	4182	836.4	23.13	24.00	1.222		1.000	0.15	2.270	1	2.773
2nd	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	Full	4182	836.4	23.13	24.00	1.222		1.000	0.07	2.250	1.009	2.749
1st	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9262	1852.4	20.73	22.00	1.340		1.000	0.16	2.490	1	3.336
2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9262	1852.4	20.73	22.00	1.340		1.000	0.02	2.480	1.004	3.322
1st	LTE Band 41	20M	QPSK	1	49	-	Back	0mm	Reduced	39750	2506	21.22	22.00	1.197	62.9	1.006	0.09	2.510	1	3.022
2nd	LTE Band 41	20M	QPSK	1	49	-	Back	0mm	Reduced	39750	2506	21.22	22.00	1.197	62.9	1.006	0.08	2.440	1.029	2.938

General Note:

- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8W/kg$ .
- Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is  $\leq 1.2$  and the measured SAR  $< 1.45W/kg$ , only one repeated measurement is required.
- Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
- The ratio is the difference in percentage between original and repeated *measured SAR*.
- All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

### 16. Simultaneous Transmission Analysis

No.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product specific 10g SAR
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		Yes
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes	Yes
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Yes
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Yes
5.	GSM Voice + WLAN5.3/5.5GHz	Yes	Yes		Yes
6.	GPRS/EDGE + WLAN5.3/5.5GHz	Yes	Yes		Yes
7.	WCDMA + WLAN5.3/5.5GHz	Yes	Yes		Yes
8.	LTE + WLAN5.3/5.5GHz	Yes	Yes		Yes
9.	GSM Voice + WLAN5.2/5.8GHz	Yes	Yes		Yes
10.	GPRS/EDGE + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
11.	WCDMA + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
12.	LTE + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
13.	GSM Voice + Bluetooth	Yes	Yes		Yes
14.	GPRS/EDGE + Bluetooth	Yes	Yes	Yes	Yes
15.	WCDMA + Bluetooth	Yes	Yes	Yes	Yes
16.	LTE + Bluetooth	Yes	Yes	Yes	Yes

**General Note:**

- This device supports VoIP in GPRS, EGPRS, WCDMA, and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.
- EUT will choose each GSM, WCDMA and LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
- This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications.
- This device 2.4GHz WLAN/ 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WLAN Direct (GC/GO), and 5.3GHz / 5.5GHz supports WLAN Direct (GC only).
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment though they have independent antenna.
- WLAN 2.4GHz and Bluetooth share the same antenna so can't transmit simultaneously.
- According to the EUT character, WLAN 5GHz and Bluetooth can't transmit simultaneously.
- Chose the worst zoom scan SAR of WLAN correspondingly for co-located with WWAN analysis.
- The reported SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
  - 1g Scalar SAR summation < 1.6W/kg and 10g Scalar SAR summation < 4.0W/kg.
  - $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$ , and the peak separation distance is determined from the square root of  $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$ , where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
  - If  $SPLSR \leq 0.04$  for 1g SAR and  $SPLSR \leq 0.10$  for 10g SAR, simultaneously transmission SAR measurement is not necessary.
  - Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg and 10g SAR < 4.0W/kg.
  - The SPLSR calculated results please refer to section 16.5.

16.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	4	6	1+2 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	1+6 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)			
GSM	GSM850	Right Cheek	0.538	0.379	0.480	0.069	0.92	1.02	0.61
		Right Tilted	0.259	0.425	0.597	0.079	0.68	0.86	0.34
		Left Cheek	0.506	1.017	0.973	0.169	1.52	1.48	0.68
		Left Tilted	0.248	0.892	1.071	0.166	1.14	1.32	0.41
	GSM1900	Right Cheek	0.221	0.379	0.480	0.069	0.60	0.70	0.29
		Right Tilted	0.161	0.425	0.597	0.079	0.59	0.76	0.24
		Left Cheek	0.243	1.017	0.973	0.169	1.26	1.22	0.41
		Left Tilted	0.219	0.892	1.071	0.166	1.11	1.29	0.39
WCDMA	WCDMA V	Right Cheek	0.435	0.379	0.480	0.069	0.81	0.92	0.50
		Right Tilted	0.205	0.425	0.597	0.079	0.63	0.80	0.28
		Left Cheek	0.404	1.017	0.973	0.169	1.42	1.38	0.57
		Left Tilted	0.197	0.892	1.071	0.166	1.09	1.27	0.36
	WCDMA II	Right Cheek	0.285	0.379	0.480	0.069	0.66	0.77	0.35
		Right Tilted	0.181	0.425	0.597	0.079	0.61	0.78	0.26
		Left Cheek	0.329	1.017	0.973	0.169	1.35	1.30	0.50
		Left Tilted	0.249	0.892	1.071	0.166	1.14	1.32	0.42
LTE	LTE Band 5	Right Cheek	0.386	0.379	0.480	0.069	0.77	0.87	0.46
		Right Tilted	0.190	0.425	0.597	0.079	0.62	0.79	0.27
		Left Cheek	0.361	1.017	0.973	0.169	1.38	1.33	0.53
		Left Tilted	0.179	0.892	1.071	0.166	1.07	1.25	0.35
	LTE Band 26	Right Cheek	0.409	0.379	0.480	0.069	0.79	0.89	0.48
		Right Tilted	0.180	0.425	0.597	0.079	0.61	0.78	0.26
		Left Cheek	0.375	1.017	0.973	0.169	1.39	1.35	0.54
		Left Tilted	0.174	0.892	1.071	0.166	1.07	1.25	0.34
	LTE Band 2	Right Cheek	0.261	0.379	0.480	0.069	0.64	0.74	0.33
		Right Tilted	0.164	0.425	0.597	0.079	0.59	0.76	0.24
		Left Cheek	0.273	1.017	0.973	0.169	1.29	1.25	0.44
		Left Tilted	0.191	0.892	1.071	0.166	1.08	1.26	0.36
	LTE Band 7	Right Cheek	0.155	0.379	0.480	0.069	0.53	0.64	0.22
		Right Tilted	0.103	0.425	0.597	0.079	0.53	0.70	0.18
		Left Cheek	0.231	1.017	0.973	0.169	1.25	1.20	0.40
		Left Tilted	0.108	0.892	1.071	0.166	1.00	1.18	0.27
	LTE Band 41	Right Cheek	0.109	0.379	0.480	0.069	0.49	0.59	0.18
		Right Tilted	0.067	0.425	0.597	0.079	0.49	0.66	0.15
		Left Cheek	0.167	1.017	0.973	0.169	1.18	1.14	0.34
		Left Tilted	0.074	0.892	1.071	0.166	0.97	1.15	0.24





16.2 Hotspot Exposure Conditions

WWAN Band	Exposure Position	1	2	4	6	1+2 Summed 1g SAR (W/kg)	Case No	SPLSR	1+4	Case No	SPLSR	1+6	
		WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)				Summed 1g SAR (W/kg)			Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)
GSM	GSM850	Front	0.683	0.448	0.301	0.116	1.13			0.98			0.80
		Back	1.274	0.942	0.924	0.129	2.22	#01	0.02	2.20	#11	0.02	1.40
		Left side	0.380	0.058	0.138	0.009	0.44			0.52			0.39
		Right side	0.531	0.450	0.162	0.113	0.98			0.69			0.64
		Top side		0.529	0.871	0.086	0.53			0.87			0.09
		Bottom side	0.222				0.22			0.22			0.22
	GSM1900	Front	1.014	0.448	0.301	0.116	1.46			1.32			1.13
		Back	1.114	0.942	0.924	0.129	2.06	#02	0.02	2.04	#12	0.02	1.24
		Left side	0.232	0.058	0.138	0.009	0.29			0.37			0.24
		Right side	0.114	0.450	0.162	0.113	0.56			0.28			0.23
		Top side		0.529	0.871	0.086	0.53			0.87			0.09
		Bottom side	1.399				1.40			1.40			1.40
WCDMA	WCDMA V	Front	0.625	0.448	0.301	0.116	1.07			0.93			0.74
		Back	1.257	0.942	0.924	0.129	2.20	#03	0.03	2.18	#13	0.02	1.39
		Left side	0.428	0.058	0.138	0.009	0.49			0.57			0.44
		Right side	0.505	0.450	0.162	0.113	0.96			0.67			0.62
		Top side		0.529	0.871	0.086	0.53			0.87			0.09
		Bottom side	0.216				0.22			0.22			0.22
	WCDMA II	Front	1.087	0.448	0.301	0.116	1.54			1.39			1.20
		Back	1.360	0.942	0.924	0.129	2.30	#05	0.02	2.28	#14	0.02	1.49
		Left side	0.276	0.058	0.138	0.009	0.33			0.41			0.29
		Right side	0.094	0.450	0.162	0.113	0.54			0.26			0.21
		Top side		0.529	0.871	0.086	0.53			0.87			0.09
		Bottom side	1.155				1.16			1.16			1.16
LTE	LTE Band 5	Front	0.628	0.448	0.301	0.116	1.08			0.93			0.74
		Back	1.186	0.942	0.924	0.129	2.13	#06	0.02	2.11	#15	0.02	1.32
		Left side	0.433	0.058	0.138	0.009	0.49			0.57			0.44
		Right side	0.479	0.450	0.162	0.113	0.93			0.64			0.59
		Top side		0.529	0.871	0.086	0.53			0.87			0.09
		Bottom side	0.209				0.21			0.21			0.21
	LTE Band 26	Front	0.620	0.448	0.301	0.116	1.07			0.92			0.74
		Back	1.210	0.942	0.924	0.129	2.15	#07	0.02	2.13	#16	0.02	1.34
		Left side	0.417	0.058	0.138	0.009	0.48			0.56			0.43
		Right side	0.462	0.450	0.162	0.113	0.91			0.62			0.58
		Top side		0.529	0.871	0.086	0.53			0.87			0.09
		Bottom side	0.146				0.15			0.15			0.15
	LTE Band 2	Front	1.012	0.448	0.301	0.116	1.46			1.31			1.13
		Back	1.231	0.942	0.924	0.129	2.17	#08	0.02	2.16	#17	0.02	1.36
		Left side	0.230	0.058	0.138	0.009	0.29			0.37			0.24
		Right side	0.110	0.450	0.162	0.113	0.56			0.27			0.22
		Top side		0.529	0.871	0.086	0.53			0.87			0.09
		Bottom side	1.368				1.37			1.37			1.37
LTE Band 7	Front	0.451	0.448	0.301	0.116	0.90			0.75			0.57	
	Back	1.138	0.942	0.924	0.129	2.08	#09	0.02	2.06	#18	0.02	1.27	
	Left side	0.110	0.058	0.138	0.009	0.17			0.25			0.12	
	Right side	0.061	0.450	0.162	0.113	0.51			0.22			0.17	
	Top side		0.529	0.871	0.086	0.53			0.87			0.09	
	Bottom side	1.425				1.43			1.43			1.43	
LTE Band 41	Front	0.457	0.448	0.301	0.116	0.91			0.76			0.57	
	Back	1.247	0.942	0.924	0.129	2.19	#10	0.02	2.17	#19	0.02	1.38	
	Left side	0.099	0.058	0.138	0.009	0.16			0.24			0.11	
	Right side	0.063	0.450	0.162	0.113	0.51			0.23			0.18	
	Top side		0.529	0.871	0.086	0.53			0.87			0.09	
	Bottom side	1.334				1.33			1.33			1.33	



16.3 Body-Worn Accessory Exposure Conditions

WWAN Band	Exposure Position	1	2	4	6	1+2 Summed 1g SAR (W/kg)	Case No	SPLSR	1+4 Summed 1g SAR (W/kg)	Case No	SPLSR	1+6 Summed 1g SAR (W/kg)	
		WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)								
GSM	GSM850	Front	0.683	0.448	0.342	0.116	1.13			1.03		0.80	
		Back	1.274	0.942	1.041	0.129	2.22	#01	0.02	2.32	#20	0.02	1.40
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.250				1.25			1.25			1.25
	GSM1900	Front	1.014	0.448	0.342	0.116	1.46			1.36			1.13
		Back	1.114	0.942	1.041	0.129	2.06	#02	0.02	2.16	#21	0.02	1.24
		Front with Headset					0.00			0.00			0.00
		Back with Headset					0.00			0.00			0.00
WCDMA	WCDMA V	Front	0.625	0.448	0.342	0.116	1.07			0.97			0.74
		Back	1.257	0.942	1.041	0.129	2.20	#03	0.03	2.30	#22	0.03	1.39
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.278				1.28			1.28			1.28
	WCDMA II	Front	1.087	0.448	0.342	0.116	1.54			1.43			1.20
		Back	1.360	0.942	1.041	0.129	2.30	#05	0.02	2.40	#23	0.02	1.49
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.356				1.36			1.36			1.36
LTE	LTE Band 5	Front	0.628	0.448	0.342	0.116	1.08			0.97			0.74
		Back	1.186	0.942	1.041	0.129	2.13	#06	0.02	2.23	#24	0.02	1.32
		Front with Headset					0.00			0.00			0.00
		Back with Headset					0.00			0.00			0.00
	LTE Band 26	Front	0.620	0.448	0.342	0.116	1.07			0.96			0.74
		Back	1.210	0.942	1.041	0.129	2.15	#07	0.02	2.25	#25	0.02	1.34
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.121				1.12			1.12			1.12
	LTE Band 2	Front	1.012	0.448	0.342	0.116	1.46			1.35			1.13
		Back	1.231	0.942	1.041	0.129	2.17	#08	0.02	2.27	#26	0.02	1.36
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.352				1.35			1.35			1.35
	LTE Band 7	Front	0.451	0.448	0.342	0.116	0.90			0.79			0.57
		Back	1.138	0.942	1.041	0.129	2.08	#09	0.02	2.18	#27	0.02	1.27
		Front with Headset					0.00			0.00			0.00
		Back with Headset					0.00			0.00			0.00
LTE Band 41	Front	0.457	0.448	0.342	0.116	0.91			0.80			0.57	
	Back	1.247	0.942	1.041	0.129	2.19	#10	0.02	2.29	#28	0.02	1.38	
	Front with Headset					0.00			0.00			0.00	
	Back with Headset	1.153				1.15			1.15			1.15	



16.4 Product specific 10g SAR Exposure Conditions

WWAN Band		Exposure Position	1	4	1+4 Summed 10g SAR (W/kg)	Case No	SPLSR
			WWAN 10g SAR (W/kg)	5GHz WLAN 10g SAR (W/kg)			
GSM	GSM850	Front		0.640	0.64		
		Back	2.343	1.584	3.93		
		Left side		0.097	0.10		
		Right side		0.478	0.48		
		Top side		2.233	2.23		
		Bottom side			0.00		
	GSM1900	Front	1.691	0.640	2.33		
		Back	2.622	1.584	4.21	#29	0.05
		Left side		0.097	0.10		
		Right side		0.478	0.48		
		Top side		2.233	2.23		
		Bottom side	2.840		2.84		
WCDMA	WCDMA V	Front		0.640	0.64		
		Back	2.795	1.584	4.38	#30	0.06
		Left side		0.097	0.10		
		Right side		0.478	0.48		
		Top side		2.233	2.23		
		Bottom side			0.00		
	WCDMA II	Front	1.773	0.640	2.41		
		Back	2.452	1.584	4.04	#31	0.06
		Left side		0.097	0.10		
		Right side		0.478	0.48		
		Top side		2.233	2.23		
		Bottom side	3.336		3.34		
LTE	LTE Band 26	Front		0.640	0.64		
		Back	2.493	1.584	4.08	#32	0.05
		Left side		0.097	0.10		
		Right side		0.478	0.48		
		Top side		2.233	2.23		
		Bottom side			0.00		
	LTE Band 2	Front	1.362	0.640	2.00		
		Back	1.925	1.584	3.51		
		Left side		0.097	0.10		
		Right side		0.478	0.48		
		Top side		2.233	2.23		
		Bottom side	3.429		3.43		
	LTE Band 7	Front	1.066	0.640	1.71		
		Back	2.852	1.584	4.44	#33	0.06
		Left side		0.097	0.10		
		Right side		0.478	0.48		
		Top side		2.233	2.23		
		Bottom side	2.618		2.62		
	LTE Band 41	Front		0.640	0.64		
		Back	3.022	1.584	4.61	#34	0.07
		Left side		0.097	0.10		
		Right side		0.478	0.48		
		Top side		2.233	2.23		
		Bottom side	2.484		2.48		


Remark:

1. For Bluetooth Product specific 10g stand-alone SAR is not required for a transmitter or antenna, due to 1g hotspot SAR is <1.2W/kg.
2. If SPLSR ≤ 0.10 for 10g SAR, simultaneously transmission SAR measurement is not necessary.


### 16.5 SPLSR Evaluation and Analysis

**General Note:**


1. When standalone SAR is measured for both antennas in the pair, the peak location separation distance is computed by the square root of  $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$ , where  $(x1, y1, z1)$  and  $(x2, y2, z2)$  are the coordinates in the area scans or extrapolated peak SAR locations in the zoom scans, as appropriate.
2.  $SPLSR = (SAR1 + SAR2)1.5 / (\text{min. separation distance, mm})$ . If  $SPLSR \leq 0.04$  for 1g SAR and  $SPLSR \leq 0.10$  for 10g SAR, simultaneously transmission SAR measurement is not necessary.



Back for WWAN+WLAN2.4GHz\_5mm



Back for WWAN+WLAN5GHz\_5mm



Back for WWAN+WLAN5GHz \_0mm



WWAN+WAN2.4G 5mm											
Case Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 1 Plot No	GSM850	Back	1.274	5	-0.0315	-0.0715	-0.209	137.0	2.22	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
Case 2 Plot No	GSM1900 Cube 0	Back	1.114	5	-0.0055	-0.088	-0.209	157.6	2.06	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
	GSM1900 Cube 1	Back	1.079	5	-0.015	-0.088	-0.209	155.6	2.02	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
Case 3 Plot No	WCDMA V	Back	1.257	5	-0.019	-0.062	-0.209	129.3	2.20	0.03	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
Case 5 Plot No	WCDMA II	Back	1.36	5	-0.011	-0.0755	-0.209	144.2	2.30	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
Case 6 Plot No	LTE Band 5	Back	1.186	5	-0.0175	-0.07	-0.209	137.5	2.13	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
Case 7 Plot No	LTE Band 26	Back	1.21	5	-0.0165	-0.0715	-0.209	139.1	2.15	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
Case 8 Plot No	LTE Band 2 Cube 0	Back	1.231	5	-0.0055	-0.0755	-0.209	145.5	2.17	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
	LTE Band 2 Cube 1	Back	1.13	5	-0.0135	-0.076	-0.209	144.1	2.07	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
Case 9 Plot No	LTE Band 7 Cube 0	Back	1.138	5	-0.0142	-0.0744	-0.209	142.4	2.08	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
	LTE Band 7 Cube 1	Back	1.078	5	-0.0208	-0.0756	-0.209	142.4	2.02	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
Case 10 Plot No	LTE Band 41 Cube 0	Back	1.247	5	-0.0154	-0.0768	-0.209	144.5	2.19	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				
	LTE Band 41 Cube 1	Back	1.145	5	-0.0196	-0.0768	-0.209	143.8	2.09	0.02	Not required
	WLAN2.4GHz		0.942	5	-0.0432	0.065	-0.206				



WWAN+WAN5G 5mm											
Case Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 11 Plot No	GSM850	Back	1.274	5	-0.0315	-0.0715	-0.209	146.4	2.20	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 12 Plot No	GSM1900 Cube 0	Back	1.114	5	-0.0055	-0.088	-0.209	168.4	2.04	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
	GSM1900 Cube 1	Back	1.079	5	-0.015	-0.088	-0.209	165.9	2.00	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 13 Plot No	WCDMA V	Back	1.257	5	-0.019	-0.062	-0.209	139.7	2.18	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 14 Plot No	WCDMA II	Back	1.36	5	-0.011	-0.0755	-0.209	154.9	2.28	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 15 Plot No	LTE Band 5	Back	1.186	5	-0.0175	-0.07	-0.209	147.8	2.11	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 16 Plot No	LTE Band 26	Back	1.21	5	-0.0165	-0.0715	-0.209	149.5	2.13	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 17 Plot No	LTE Band 2 Cube 0	Back	1.231	5	-0.0055	-0.0755	-0.209	156.5	2.16	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
	LTE Band 2 Cube 1	Back	1.13	5	-0.0135	-0.076	-0.209	154.7	2.05	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 18 Plot No	LTE Band 7 Cube 0	Back	1.138	5	-0.0142	-0.0744	-0.209	152.9	2.06	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
	LTE Band 7 Cube 1	Back	1.078	5	-0.0208	-0.0756	-0.209	152.5	2.00	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 19 Plot No	LTE Band 41 Cube 0	Back	1.247	5	-0.0154	-0.0768	-0.209	154.9	2.17	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
	LTE Band 41 Cube 1	Back	1.145	5	-0.0196	-0.0768	-0.209	153.9	2.07	0.02	Not required
	WLAN5GHz		0.924	5	-0.055	0.073	-0.209				
Case 20 Plot No	GSM850	Back	1.274	5	-0.0315	-0.0715	-0.209	142.8	2.32	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				



Case Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 21 Plot No	GSM1900 Cube 0	Back	1.114	5	-0.0055	-0.088	-0.209	164.4	2.16	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
	GSM1900 Cube 1	Back	1.079	5	-0.015	-0.088	-0.209	162.0	2.12	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
Case 22 Plot No	WCDMA V	Back	1.257	5	-0.019	-0.062	-0.209	135.8	2.30	0.03	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
Case 23 Plot No	WCDMA II	Back	1.36	5	-0.011	-0.0755	-0.209	150.9	2.40	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
Case 24 Plot No	LTE Band 5	Back	1.186	5	-0.0175	-0.07	-0.209	144.0	2.23	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
Case 25 Plot No	LTE Band 26	Back	1.21	5	-0.0165	-0.0715	-0.209	145.6	2.25	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
Case 26 Plot No	LTE Band 2 Cube 0	Back	1.231	5	-0.0055	-0.0755	-0.209	152.4	2.27	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
	LTE Band 2 Cube 1	Back	1.13	5	-0.0135	-0.076	-0.209	150.7	2.17	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
Case 27 Plot No	LTE Band 7 Cube 0	Back	1.138	5	-0.0142	-0.0744	-0.209	149.0	2.18	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
	LTE Band 7 Cube 1	Back	1.078	5	-0.0208	-0.0756	-0.209	148.7	2.12	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
Case 28 Plot No	LTE Band 41 Cube 0	Back	1.247	5	-0.0154	-0.0768	-0.209	151.1	2.29	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				
	LTE Band 41 Cube 1	Back	1.145	5	-0.0196	-0.0768	-0.209	150.1	2.19	0.02	Not required
	WLAN5GHz		1.041	5	-0.051	0.07	-0.209				



WWAN+WAN5G 0mm											
Case 29 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 29 Plot No	GSM1900 Cube 0	Back	2.622	0	-0.0055	-0.0865	-0.209	164.0	4.21	0.05	Not required
	WLAN5GHz		1.584	0	-0.051	0.071	-0.206				
	GSM1900 Cube 1	Back	2.039	0	-0.031	-0.08	-0.209	152.3	3.62	0.05	Not required
	WLAN5GHz		1.584	0	-0.051	0.071	-0.206				
Case 30 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA V	Back	2.795	0	-0.0175	-0.0785	-0.209	153.2	4.38	0.06	Not required
	WLAN5GHz		1.584	0	-0.051	0.071	-0.206				
Case 31 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II	Back	2.452	0	-0.0375	-0.0665	-0.208	138.2	4.04	0.06	Not required
	WLAN5GHz		1.584	0	-0.051	0.071	-0.206				
Case 32 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 26	Back	2.493	0	-0.0245	-0.077	-0.209	150.4	4.08	0.05	Not required
	WLAN5GHz		1.584	0	-0.051	0.071	-0.206				
Case 33 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 7	Back	2.852	0	-0.0142	-0.072	-0.208	147.7	4.44	0.06	Not required
	WLAN5GHz		1.584	0	-0.051	0.071	-0.206				
Case 34 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 41	Back	3.022	0	-0.0034	-0.0648	-0.208	143.9	4.61	0.07	Not required
	WLAN5GHz		1.584	0	-0.051	0.071	-0.206				

**Test Engineer** : Changlin Huang, Bin He, Mengming Dai



## **17. Uncertainty Assessment**

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be  $\leq 30\%$ , for a confidence interval of  $k = 2$ . If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

## **18. References**

- [1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
- [2] ANSI/IEEE Std. C95.1-1992, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, September 1992
- [3] IEEE Std. 1528-2013, “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [6] FCC KDB 865664 D02 v01r02, “RF Exposure Compliance Reporting and Documentation Considerations” Oct 2015.
- [7] FCC KDB 447498 D01 v06, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, Oct 2015
- [8] FCC KDB 648474 D04 v01r03, “SAR Evaluation Considerations for Wireless Handsets”, Oct 2015.
- [9] FCC KDB 248227 D01 v02r02, “SAR Guidance for IEEE 802.11 (WiFi) Transmitters”, Oct 2015.
- [10] FCC KDB 616217 D04 v01r02, “SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers”, Oct 2015
- [11] FCC KDB 941225 D01 v03r01, “3G SAR MEAUREMENT PROCEDURES”, Oct 2015
- [12] FCC KDB 941225 D05 v02r05, “SAR Evaluation Considerations for LTE Devices”, Dec 2015
- [13] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.

-----THE END-----



## **Appendix A. Plots of System Performance Check**

The plots are shown as follows.

## System Check\_Head\_835MHz

**DUT: D835V2-SN:4d162**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL\_835\_201112 Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.928$  S/m;  $\epsilon_r = 42.73$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.15 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 61.50 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 3.51 W/kg

**SAR(1 g) = 2.37 W/kg; SAR(10 g) = 1.56 W/kg**

Maximum value of SAR (measured) = 3.15 W/kg



0 dB = 3.15 W/kg

## System Check\_Head\_835MHz

**DUT: D835V2-SN:4d162**


Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium: HSL\_835\_201114 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.929 \text{ S/m}$ ;  $\epsilon_r = 41.793$ ;  
 $\rho = 1000 \text{ kg/m}^3$   
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7577; ConvF(9.54, 9.54, 9.54); Calibrated: 2020.09.30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2020.07.27
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 3.50 W/kg

**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 59.84 V/m; Power Drift = -0.09 dB  
Peak SAR (extrapolated) = 3.84 W/kg  
**SAR(1 g) = 2.57 W/kg; SAR(10 g) = 1.68 W/kg**  
Maximum value of SAR (measured) = 3.43 W/kg



0 dB = 3.43 W/kg

## System Check\_Head\_1900MHz

**DUT: D1900V2-SN:5d182**


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_201113 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.457$  S/m;  $\epsilon_r = 39.135$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(8.58, 8.58, 8.58); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 14.8 W/kg

**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 99.56 V/m; Power Drift = 0.12 dB  
Peak SAR (extrapolated) = 18.2 W/kg  
**SAR(1 g) = 9.79 W/kg; SAR(10 g) = 5.07 W/kg**  
Maximum value of SAR (measured) = 15.3 W/kg



0 dB = 15.3 W/kg

## System Check\_Head\_1900MHz

**DUT: D1900V2-SN:5d182**


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_201115 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.44$  S/m;  $\epsilon_r = 40.038$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.6 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7577; ConvF(8.34, 8.34, 8.34); Calibrated: 2020.09.30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2020.07.27
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 16.4 W/kg

**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 87.86 V/m; Power Drift = 0.19 dB  
Peak SAR (extrapolated) = 19.8 W/kg  
**SAR(1 g) = 10.3 W/kg; SAR(10 g) = 5.3 W/kg**  
Maximum value of SAR (measured) = 16.4 W/kg



0 dB = 16.4 W/kg



## System Check\_Head\_2450MHz

**DUT: D2450V2-SN:924**


Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium: HSL\_2450\_201114 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.865$  S/m;  $\epsilon_r = 37.492$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(7.76, 7.76, 7.76); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 19.9 W/kg

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 86.25 V/m; Power Drift = 0.08 dB  
Peak SAR (extrapolated) = 27.1 W/kg  
**SAR(1 g) = 12.6 W/kg; SAR(10 g) = 5.67 W/kg**  
Maximum value of SAR (measured) = 19.8 W/kg



0 dB = 19.8 W/kg

## System Check\_Head\_2450MHz

**DUT: D2450V2-SN:924**


Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium: HSL\_2450\_201116 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.732$  S/m;  $\epsilon_r = 40.764$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7577; ConvF(7.95, 7.95, 7.95); Calibrated: 2020.09.30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2020.07.27
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 20.1 W/kg

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 82.62 V/m; Power Drift = 0.12 dB  
Peak SAR (extrapolated) = 27.0 W/kg  
**SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.93 W/kg**  
Maximum value of SAR (measured) = 19.9 W/kg



0 dB = 19.9 W/kg

## System Check\_Head\_2600MHz

**DUT: D2600V2-SN:1070**


Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1  
Medium: HSL\_2600\_201114 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.055$  S/m;  $\epsilon_r = 37.597$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(7.47, 7.47, 7.47); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Pin=250mW/Area Scan (71x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 24.9 W/kg

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 102.0 V/m; Power Drift = 0.15 dB  
Peak SAR (extrapolated) = 30.2 W/kg  
**SAR(1 g) = 14.3 W/kg; SAR(10 g) = 6.41 W/kg**  
Maximum value of SAR (measured) = 24.4 W/kg



0 dB = 24.4 W/kg

## System Check\_Head\_2600MHz

**DUT: D2600V2-SN:1070**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1  
Medium: HSL\_2600\_201117 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.894$  S/m;  $\epsilon_r = 40.24$ ;  $\rho = 1000$  kg/m<sup>3</sup>


Ambient Temperature : 23.6 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7577; ConvF(7.66, 7.66, 7.66); Calibrated: 2020.09.30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2020.07.27
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 22.6 W/kg

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 80.16 V/m; Power Drift = 0.12 dB  
Peak SAR (extrapolated) = 31.0 W/kg  
**SAR(1 g) = 14.1 W/kg; SAR(10 g) = 6.25 W/kg**  
Maximum value of SAR (measured) = 22.1 W/kg



0 dB = 22.1 W/kg

## System Check\_Head\_5250MHz

**DUT: D5GHzV2-SN:1167**


Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1  
Medium: HSL\_5250\_201118 Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.597$  S/m;  $\epsilon_r = 36.617$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7577; ConvF(5.4, 5.4, 5.4); Calibrated: 2020.09.30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2020.07.27
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 18.9 W/kg

**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 50.69 V/m; Power Drift = 0.04 dB  
Peak SAR (extrapolated) = 31.7 W/kg  
**SAR(1 g) = 7.82 W/kg; SAR(10 g) = 2.14 W/kg**  
Maximum value of SAR (measured) = 19.3 W/kg



0 dB = 19.3 W/kg

## System Check\_Head\_5600MHz

**DUT: D5GHzV2-SN:1167**


Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1  
Medium: HSL\_5600\_201119 Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.006$  S/m;  $\epsilon_r = 36.08$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7577; ConvF(4.79, 4.79, 4.79); Calibrated: 2020.09.30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2020.07.27
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 22.6 W/kg

**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 56.25 V/m; Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 39.8 W/kg  
**SAR(1 g) = 8.59 W/kg; SAR(10 g) = 2.42 W/kg**  
Maximum value of SAR (measured) = 22.5 W/kg



0 dB = 22.5 W/kg

## System Check\_Head\_5750MHz

**DUT: D5GHzV2-SN:1167**


Communication System: UID 0, CW (0); Frequency: 5750 MHz; Duty Cycle: 1:1  
Medium: HSL\_5750\_201120 Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.175$  S/m;  $\epsilon_r = 35.814$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7577; ConvF(5.02, 5.02, 5.02); Calibrated: 2020.09.30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2020.07.27
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 20.3 W/kg

**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 54.68 V/m; Power Drift = 0.18 dB  
Peak SAR (extrapolated) = 36.3 W/kg  
**SAR(1 g) = 7.84 W/kg; SAR(10 g) = 2.15 W/kg**  
Maximum value of SAR (measured) = 20.1 W/kg



0 dB = 20.1 W/kg



**Appendix B. Plots of High SAR Measurement**

The plots are shown as follows.



## 01\_GSM850\_GPRS(2 Tx slots)\_Right Cheek\_Ch251

Communication System: UID 0, GPRS/EDGE10 (0); Frequency: 848.8 MHz; Duty Cycle: 1:4.15  
 Medium: HSL\_835\_201112 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.942$  S/m;  $\epsilon_r = 42.559$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

### DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Ch251/Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.518 W/kg


**Ch251/Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.376 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.552 W/kg

**SAR(1 g) = 0.436 W/kg; SAR(10 g) = 0.336 W/kg**

Maximum value of SAR (measured) = 0.513 W/kg



0 dB = 0.513 W/kg

## 02\_GSM1900\_GPRS(2 Tx slots)\_Left Cheek\_Ch661


Communication System: UID 0, GPRS/EDGE10 (0); Frequency: 1880 MHz; Duty Cycle: 1:4.15  
Medium: HSL\_1900\_201113 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.436$  S/m;  $\epsilon_r = 39.231$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

### DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(8.58, 8.58, 8.58); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Ch661/Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.245 W/kg

**Ch661/Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 1.816 V/m; Power Drift = -0.08 dB  
Peak SAR (extrapolated) = 0.283 W/kg  
**SAR(1 g) = 0.182 W/kg; SAR(10 g) = 0.118 W/kg**  
Maximum value of SAR (measured) = 0.244 W/kg



0 dB = 0.244 W/kg

### 03\_WCDMA V\_RMC 12.2Kbps\_Right Cheek\_Ch4182


Communication System: UID 0, UMTS (0); Frequency: 836.4 MHz; Duty Cycle: 1:1  
Medium: HSL\_835\_201112 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.929$  S/m;  $\epsilon_r = 42.712$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Ch4182/Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.422 W/kg

**Ch4182/Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 7.178 V/m; Power Drift = 0.08 dB  
Peak SAR (extrapolated) = 0.446 W/kg  
**SAR(1 g) = 0.356 W/kg; SAR(10 g) = 0.275 W/kg**  
Maximum value of SAR (measured) = 0.414 W/kg



### 04\_WCDMA II\_RMC 12.2Kbps\_Left Cheek\_Ch9538


Communication System: UID 0, UMTS (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_201113 Medium parameters used:  $f = 1908 \text{ MHz}$ ;  $\sigma = 1.464 \text{ S/m}$ ;  $\epsilon_r = 39.09$ ;  $\rho = 1000 \text{ kg/m}^3$   
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(8.58, 8.58, 8.58); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Ch9538/Area Scan (71x81x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 0.362 W/kg

**Ch9538/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 2.024 V/m; Power Drift = -0.09 dB  
Peak SAR (extrapolated) = 0.436 W/kg  
**SAR(1 g) = 0.275 W/kg; SAR(10 g) = 0.173 W/kg**  
Maximum value of SAR (measured) = 0.371 W/kg



### 05\_LTE Band 5\_10M\_QPSK\_1RB\_25Offset\_Right Cheek\_Ch20525


Communication System: UID 0, LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_835\_201112 Medium parameters used:  $f = 836.5$  MHz;  $\sigma = 0.93$  S/m;  $\epsilon_r = 42.711$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Ch20525/Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.405 W/kg

**Ch20525/Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 6.965 V/m; Power Drift = 0.04 dB  
Peak SAR (extrapolated) = 0.411 W/kg  
**SAR(1 g) = 0.325 W/kg; SAR(10 g) = 0.252 W/kg**  
Maximum value of SAR (measured) = 0.377 W/kg



0 dB = 0.377 W/kg

### 06\_LTE Band 26\_15M\_QPSK\_1RB\_37Offset\_Right Cheek\_Ch26965


Communication System: UID 0, LTE (0); Frequency: 841.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_835\_201112 Medium parameters used:  $f = 841.5$  MHz;  $\sigma = 0.934$  S/m;  $\epsilon_r = 42.647$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.13 (7474)

**Ch26965/Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.401 W/kg

**Ch26965/Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 6.738 V/m; Power Drift = 0.06 dB  
Peak SAR (extrapolated) = 0.432 W/kg  
**SAR(1 g) = 0.336 W/kg; SAR(10 g) = 0.258 W/kg**  
Maximum value of SAR (measured) = 0.402 W/kg



0 dB = 0.402 W/kg