



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2141-2
FCC ID : IHDT56ZP2
STANDARD : 47 CFR Part 2, and 90(S)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
Test Date(s) : Jun. 26, 2021

We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test 6

 1.5 Modification of EUT 6

 1.6 Maximum Conducted Power and Emission Designator 6

 1.7 Re-use of Measured Data 7

 1.8 Testing Site..... 8

 1.9 Test Software 8

 1.10 Applied Standards 8

 1.11 Specification of Accessory 9

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 10

 2.1 Test Mode..... 10

 2.2 Connection Diagram of Test System 10

 2.3 Support Unit used in test configuration and system..... 11

 2.4 Frequency List of Low/Middle/High Channels..... 11

3 TEST RESULT..... 12

 3.1 Conducted Output Power Measurement..... 12

 3.2 Field Strength of Spurious Radiation Measurement 13

4 LIST OF MEASURING EQUIPMENT 16

5 UNCERTAINTY OF EVALUATION 17

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

APPENDIX D. REFERENCE REPORT



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1053 §90.691	Field Strength of Spurious Radiation	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 46.26 dB at 3258.000 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Mobile Cellular Phone
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2141-2
FCC ID	IHDT56ZP2
EUT supports Radios application	GSM/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n/ac/ax HT20/VHT20/HE20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 5GHz 802.11ax HE20/HE40/HE80/HE160 WLAN 6GHz 802.11a/n HT20/HT40 WLAN 6GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 6GHz 802.11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE NFC and GNSS
IMEI Code	Radiation : 354398490013240
HW Version	DVT2
SW Version	RRM31.43
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814 ~ 824 MHz
Rx Frequency	859 ~ 869 MHz
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	<Ant. 0>: 23.60 dBm <Ant. 1>: 22.56 dBm
Antenna Gain	<Ant. 0>: -2.12 dBi <Ant. 1>: -4.34 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

Remark: Only the maximum conducted power is shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power and Emission Designator

LTE Band 26		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)
1.4	814.7 ~ 823.3	0.2286	-	0.2084	-
3	815.5 ~ 822.5	0.2291	-	0.2133	-
5	816.5 ~ 821.5	0.2291	-	0.2089	-
10	819.0	0.2291	-	0.2094	-
15	821.5	0.2291	-	0.1905	-



1.7 Re-use of Measured Data

1.7.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: XT2141-2, FCC ID: IHDT56ZP2) is electrically identical to the reference device (Model: XT2143-1, FCC ID: IHDT56ZP3) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 484596 D01.

1.7.2 Difference Section

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., please refer to the Product Equality Declaration.

The re-used RF data includes the following bands provided in Appendix D (Sporton RF Report No. FW151701 for the reference device Model: XT2143-1, FCC ID: IHDT56ZP3).

1.7.3 Reference detail Section:

Equipment Class	Reference FCC ID	Folder Test	Report Title/Section
PCE	IHDT56ZP3	Part90S (Report No. FW151701)	All sections applicable except Power and RSE

1.7.4 Spot Check Verification Data Section

In order to confirm hardware similarity of the subject device with the reference device, spot check measurements were performed on the subject device for the following test items, the test result were consistent with FCC ID: IHDT56ZP3.

Assertions concerning the similarity of these devices are based on representations by the applicant. The applicant accepts full responsibility for the validity of the similarity claim, and for the determination that verification test data are sufficient to support it.

Test Item	Mode	IHDT56ZP3 Worst Result	IHDT56ZP2 Worst Result	Difference (dB)
Average Conducted Power (dBm)	LTE B26	22.43	23.60	1.17



1.8 Testing Site

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH01-SZ	CN1256	421272

1.9 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24

1.10 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 90(S)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



1.11 Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola (Salom)	Model Name	MC-301
AC Adapter 2	Brand Name	Motorola (Acbel)	Model Name	MC-301
Battery	Brand Name	Motorola (ATL)	Model Name	MB50
USB Cable 1	Brand Name	Motorola (Luxshare)	Model Name	SC18D13217
USB Cable 2	Brand Name	Motorola (Saibao)	Model Name	SC18D13215
USB Cable 3	Brand Name	Motorola (Cabletech)	Model Name	SC18D13216

2 Test Configuration of Equipment Under Test


2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v
Radiated Spurious Emission	26	Worst mode												v		
Note	<ol style="list-style-type: none"> The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. 															

2.2 Connection Diagram of Test System





2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	Fcc DoC	N/A	Shielded, 1.5m

2.4 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26765	-	-
	Frequency	821.5	-	-
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.



3.2 Field Strength of Spurious Radiation Measurement

3.2.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least $43 + 10 \log(P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log_{10}(P[\text{Watts}])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.2.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11. $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)

3.2.4 Test Setup


For radiated test from 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.2.5 Test Result of Field Strength of Spurious Radiated

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Jul. 21, 2020	Jun. 26, 2021	Jul. 20, 2021	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 22, 2020	Jun. 26, 2021	Jul. 21, 2022	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Jul. 15, 2020	Jun. 26, 2021	Jul. 14, 2021	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 25, 2020	Jun. 26, 2021	Jul. 24, 2021	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz-40GHz	Apr. 23, 2021	Jun. 26, 2021	Apr. 22, 2022	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 18, 2021	Jun. 26, 2021	Apr. 17, 2022	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5GHz	Oct. 16, 2020	Jun. 26, 2021	Oct. 15, 2021	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 17, 2020	Jun. 26, 2021	Oct. 16, 2021	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 21, 2020	Jun. 26, 2021	Jul. 20, 2021	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jun. 26, 2021	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 26, 2021	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 26, 2021	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required



5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.48dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.53dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.02dB
---	--------



Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power)

<Ant.0>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.
Channel				26765		
Frequency (MHz)				821.5		
15	QPSK	1	0	23.57		
15	QPSK	1	37	23.57		
15	QPSK	1	74	23.60		
15	QPSK	36	0	22.57		
15	QPSK	36	20	22.63		
15	QPSK	36	39	22.68		
15	QPSK	75	0	22.66		
15	16QAM	1	0	22.79		
15	16QAM	1	37	22.71		
15	16QAM	1	74	22.80		
15	16QAM	36	0	21.58		
15	16QAM	36	20	21.65		
15	16QAM	36	39	21.62		
15	16QAM	75	0	21.67		
15	64QAM	1	0	21.65		
15	64QAM	1	37	21.67		
15	64QAM	1	74	21.71		
15	64QAM	36	0	20.61		
15	64QAM	36	20	20.67		
15	64QAM	36	39	20.70		
15	64QAM	75	0	20.68		
Channel					26740	
Frequency (MHz)					819	
10	QPSK	1	0		23.49	
10	QPSK	1	25		23.43	
10	QPSK	1	49		23.60	
10	QPSK	25	0		22.57	
10	QPSK	25	12		22.60	
10	QPSK	25	25		22.57	
10	QPSK	50	0		22.62	
10	16QAM	1	0		23.20	
10	16QAM	1	25		23.11	
10	16QAM	1	49		23.21	
10	16QAM	25	0		21.63	



10	16QAM	25	12		21.57	
10	16QAM	25	25		21.72	
10	16QAM	50	0		21.67	
10	64QAM	1	0		21.90	
10	64QAM	1	25		21.99	
10	64QAM	1	49		21.91	
10	64QAM	25	0		20.70	
10	64QAM	25	12		20.73	
10	64QAM	25	25		20.82	
10	64QAM	50	0		20.64	
Channel				26715	26740	26765
Frequency (MHz)				816.5	819	821.5
5	QPSK	1	0	23.52	23.53	23.57
5	QPSK	1	12	23.42	23.34	23.31
5	QPSK	1	24	23.60	23.56	23.60
5	QPSK	12	0	22.68	22.57	22.76
5	QPSK	12	7	22.63	22.71	22.73
5	QPSK	12	13	22.71	22.71	22.70
5	QPSK	25	0	22.71	22.59	22.68
5	16QAM	1	0	23.15	23.05	22.90
5	16QAM	1	12	23.20	22.53	23.02
5	16QAM	1	24	22.84	22.60	22.80
5	16QAM	12	0	21.60	21.59	21.76
5	16QAM	12	7	21.87	21.79	21.72
5	16QAM	12	13	21.82	21.74	21.79
5	16QAM	25	0	21.60	21.60	21.70
5	64QAM	1	0	21.55	21.72	22.11
5	64QAM	1	12	21.73	21.89	22.13
5	64QAM	1	24	21.91	21.83	21.93
5	64QAM	12	0	20.62	20.63	20.70
5	64QAM	12	7	20.76	20.76	20.74
5	64QAM	12	13	20.71	20.67	20.62
5	64QAM	25	0	20.71	20.66	20.77
Channel				26705	26740	26775
Frequency (MHz)				815.5	819	822.5
3	QPSK	1	0	23.55	23.36	23.60
3	QPSK	1	8	23.50	23.48	23.56
3	QPSK	1	14	23.39	23.37	23.50
3	QPSK	8	0	22.73	22.62	22.68
3	QPSK	8	4	22.74	22.71	22.62
3	QPSK	8	7	22.59	22.68	22.75
3	QPSK	15	0	22.75	22.54	22.67
3	16QAM	1	0	22.67	22.95	22.97
3	16QAM	1	8	23.28	23.29	22.68
3	16QAM	1	14	22.58	22.39	23.17



3	16QAM	8	0	21.75	21.76	21.88
3	16QAM	8	4	21.70	21.80	21.76
3	16QAM	8	7	21.72	21.84	21.82
3	16QAM	15	0	21.69	21.58	21.75
3	64QAM	1	0	21.71	21.74	21.95
3	64QAM	1	8	21.97	22.06	22.11
3	64QAM	1	14	21.86	22.17	21.73
3	64QAM	8	0	20.71	20.70	20.86
3	64QAM	8	4	20.83	20.74	20.85
3	64QAM	8	7	20.66	20.67	20.71
3	64QAM	15	0	20.41	20.62	20.65
Channel				26697	26740	26783
Frequency (MHz)				814.7	819	823.3
1.4	QPSK	1	0	23.59	23.43	23.55
1.4	QPSK	1	3	23.40	23.58	23.53
1.4	QPSK	1	5	23.54	23.45	23.40
1.4	QPSK	3	0	23.56	23.58	23.56
1.4	QPSK	3	1	23.52	23.56	23.49
1.4	QPSK	3	3	23.53	23.47	23.51
1.4	QPSK	6	0	22.60	22.66	22.56
1.4	16QAM	1	0	22.67	22.70	22.98
1.4	16QAM	1	3	22.93	23.19	22.64
1.4	16QAM	1	5	22.72	23.00	22.82
1.4	16QAM	3	0	22.80	22.53	22.51
1.4	16QAM	3	1	22.94	22.80	22.70
1.4	16QAM	3	3	22.57	22.87	22.45
1.4	16QAM	6	0	21.70	21.55	21.61
1.4	64QAM	1	0	21.69	21.57	21.97
1.4	64QAM	1	3	21.60	21.93	22.00
1.4	64QAM	1	5	22.00	21.83	22.03
1.4	64QAM	3	0	21.89	21.50	21.67
1.4	64QAM	3	1	21.74	21.58	21.84
1.4	64QAM	3	3	21.76	21.70	21.85
1.4	64QAM	6	0	20.64	20.77	20.82



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

<Ant.0>

LTE Band 26 / 5MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1633.5	-63.60	-13	-50.60	-73.19	-66.85	4.00	9.40	H
	2450.25	-62.17	-13	-49.17	-75.63	-65.74	4.88	10.60	H
	3267	-59.84	-13	-46.84	-76.84	-64.77	5.52	12.60	H
	1633.5	-64.17	-13	-51.17	-73.71	-67.42	4.00	9.40	V
	2450.25	-62.11	-13	-49.11	-75.55	-65.68	4.88	10.60	V
	3267	-60.03	-13	-47.03	-76.89	-64.96	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 26 / 10MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1629	-63.64	-13	-50.64	-73.33	-66.89	4.00	9.40	H
	2443.5	-61.88	-13	-48.88	-75.33	-65.45	4.88	10.60	H
	3258	-59.26	-13	-46.26	-76.29	-64.19	5.52	12.60	H
	1629	-63.85	-13	-50.85	-73.46	-67.10	4.00	9.40	V
	2443.5	-61.68	-13	-48.68	-75.10	-65.25	4.88	10.60	V
	3258	-59.63	-13	-46.63	-76.50	-64.56	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 26 / 15MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1629.5	-64.11	-13	-51.11	-73.80	-67.34	3.98	9.36	H
	2444.25	-61.85	-13	-48.85	-75.30	-65.40	4.85	10.55	H
	3259	-59.64	-13	-46.64	-76.67	-64.57	5.50	12.58	H
	1629.5	-63.81	-13	-50.81	-73.42	-67.04	3.98	9.36	V
	2444.25	-61.81	-13	-48.81	-75.23	-65.36	4.85	10.55	V
	3259	-59.84	-13	-46.84	-76.71	-64.77	5.50	12.58	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



<Ant.1>

LTE Band 26 / 5MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1633.5	-63.52	-13	-50.52	-73.11	-66.77	4.00	9.40	H
	2450.25	-62.41	-13	-49.41	-75.87	-65.98	4.88	10.60	H
	3267	-59.95	-13	-46.95	-76.95	-64.88	5.52	12.60	H
	1633.5	-61.07	-13	-48.07	-70.61	-64.32	4.00	9.40	V
	2450.25	-62.05	-13	-49.05	-75.49	-65.62	4.88	10.60	V
	3267	-60.05	-13	-47.05	-76.91	-64.98	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 26 / 10MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1629	-64.44	-13	-51.44	-74.13	-67.69	4.00	9.40	H
	2443.5	-62.10	-13	-49.10	-75.55	-65.67	4.88	10.60	H
	3258	-59.81	-13	-46.81	-76.84	-64.74	5.52	12.60	H
	1629	-64.39	-13	-51.39	-74.00	-67.64	4.00	9.40	V
	2443.5	-62.00	-13	-49.00	-75.42	-65.57	4.88	10.60	V
	3258	-59.69	-13	-46.69	-76.56	-64.62	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 26 / 15MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1629.5	-64.48	-13	-51.48	-74.16	-67.71	3.98	9.36	H
	2444.25	-62.06	-13	-49.06	-75.51	-65.61	4.85	10.55	H
	3259	-59.73	-13	-46.73	-76.76	-64.66	5.50	12.58	H
	1629.5	-63.39	-13	-50.39	-73.00	-66.62	3.98	9.36	V
	2444.25	-62.24	-13	-49.24	-75.66	-65.79	4.85	10.55	V
	3259	-60.13	-13	-47.13	-77.00	-65.06	5.50	12.58	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Appendix D. Reference Report

Please refer to Sporton report number FW151701 which is issued separately.