



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2141-2
FCC ID : IHDT56ZP2
STANDARD : 47 CFR Part 2, 22, 24, 27
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Jun. 06, 2021 ~ Jul. 02, 2021

We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Derreck Chen

Reviewed by: Derreck Chen / Supervisor

Eric Shih

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
 People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY...3
SUMMARY OF TEST RESULT...4
1 GENERAL DESCRIPTION...5
1.1 Applicant...5
1.2 Manufacturer...5
1.3 Product Feature of Equipment Under Test...5
1.4 Product Specification of Equipment Under Test...6
1.5 Specification of Accessory...6
1.6 Modification of EUT...6
1.7 Maximum ERP/EIRP Power and Emission Designator...7
1.8 Testing Location...9
1.9 Test Software...10
1.10 Applicable Standards...10
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST...11
2.1 Test Mode...11
2.2 Connection Diagram of Test System...13
2.3 Support Unit used in test configuration and system...13
2.4 Measurement Results Explanation Example...13
2.5 Frequency List of Low/Middle/High Channels...14
3 CONDUCTED TEST ITEMS...16
3.1 Measuring Instruments...16
3.2 Test Setup...16
3.3 Test Result of Conducted Test...16
3.4 Conducted Output Power and ERP/EIRP...17
3.5 Peak-to-Average Ratio...18
3.6 Occupied Bandwidth...19
3.7 Conducted Band Edge...20
3.8 Conducted Spurious Emission...21
3.9 Frequency Stability...22
4 RADIATED TEST ITEMS...23
4.1 Measuring Instruments...23
4.2 Test Setup...23
4.3 Test Result of Radiated Test...24
4.4 Radiated Spurious Emission...25
5 LIST OF MEASURING EQUIPMENT...26
6 UNCERTAINTY OF EVALUATION...27
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG151701-01D	Rev. 01	Initial issue of report	Jul. 09, 2021



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power (5G NR n5)	ERP < 7 Watt		
	§24.232(c)	Equivalent Isotropic Radiated Power (5G NR n2, n25)	EIRP < 2Watt		
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (5G NR n66)	EIRP < 1Watt		
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Band Edge Measurement (5G NR n5) (5G NR n2, n25) (5G NR n66)	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Spurious Emission (5G NR n5) (5G NR n2, n25) (5G NR n66)	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Radiated Spurious Emission (5G NR n5) (5G NR n2, n25) (5G NR n66)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 24.22 dB at 10104.360 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2141-2
FCC ID	IHDT56ZP2
EUT supports Radios application	GSM/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n HT20 WLAN 2.4GHz 802.11ac/ax VHT20/HE20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 5GHz 802.11ax HE20/HE40/HE80/HE160 WLAN 6GHz 802.11a/n HT20/HT40 WLAN 6GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 6GHz 802.11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE NFC and GNSS
IMEI Code	Conducted: 354398490012424 Radiation: 354398490013240
HW Version	DVT2
SW Version	RRM31.43
EUT Stage	Identical Prototype

Remark: Only 5G NR bands n2/n5/n25/n66 are tested in this report, all the other RF bands are tested in the other reports separately.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz
Rx Frequency	5G NR n2 : 1930 MHz ~ 1990 MHz 5G NR n5 : 869 MHz ~ 894 MHz 5G NR n25 : 1930 MHz ~ 1995 MHz 5G NR n66 : 2110 MHz~ 2200 MHz
SCS	15kHz
Bandwidth	n2, n5: 5MHz / 10MHz / 15MHz / 20MHz n25 : 5MHz / 10MHz / 15MHz / 20MHz / 25MHz / 30MHz / 40MHz n66 : 5MHz / 10MHz / 15MHz / 20MHz / 30MHz / 40MHz
Antenna Gain	Main Antenna: 5G NR n2: 0.65 dBi 5G NR n5: -2.12 dBi 5G NR n25: 0.65 dBi 5G NR n66: 1.23 dBi
Type of Modulation	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

Remark:

1. The maximum ERP/EIRP is calculated from max output power and max antenna gain, only the maximum ERP/EIRP of Main Antenna is shown in the report.
2. 5G NR supports SA mode(n2/n25/n66) and NSA mode(n2/n5/n25/n66). For NSA mode of all EN-DC combination, we only show the combination of the maximum power among all NSA combinations in the report.
3. The EN-DC mode combination could be referred to the product spec.
4. For modulation of CP-OFDM and DFT-s-OFDM, the maximum power of CP-OFDM is lower than DFT-s-OFDM modulation, therefore, we chose higher power (DFT-s-OFDM modulation) to perform all tests and show in the report.

1.5 Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola (Salom)	Model Name	MC-301
AC Adapter 2	Brand Name	Motorola (Acbel)	Model Name	MC-301
Battery	Brand Name	Motorola (ATL)	Model Name	MB50
USB Cable 1	Brand Name	Motorola (Luxshare)	Model Name	SC18D13217
USB Cable 2	Brand Name	Motorola (Saibao)	Model Name	SC18D13215
USB Cable 3	Brand Name	Motorola (Cabletech)	Model Name	SC18D13216

1.6 Modification of EUT

No modifications are made to the EUT during all test items.



1.7 Maximum ERP/EIRP Power and Emission Designator

5G NR n2 SA		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1852.5 ~ 1907.5	0.2692	4M48G7D	0.2113	4M49W7D
10	1855.0 ~ 1905.0	0.2877	9M28G7D	0.2333	9M29W7D
15	1857.5 ~ 1902.5	0.2767	14M1G7D	0.2213	14M1W7D
20	1860.0 ~ 1900.0	0.2884	18M9G7D	0.2178	19M0W7D

5G NR n2 (EN DC_5A-n2A)		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1852.5 ~ 1907.5	0.2472	4M48G7D	0.2495	4M49W7D
10	1855.0 ~ 1905.0	0.2710	9M29G7D	0.2661	9M30W7D
15	1857.5 ~ 1902.5	0.2600	14M1G7D	0.2523	14M1W7D
20	1860.0 ~ 1900.0	0.2710	18M9G7D	0.2404	19M0W7D

5G NR n5 (EN DC_7A-n5A)		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	826.5 ~ 846.5	0.0783	4M47G7D	0.0789	4M49W7D
10	829.0 ~ 844.0	0.0773	9M27G7D	0.0778	9M28W7D
15	831.5 ~ 841.5	0.0782	14M1G7D	0.0755	14M1W7D
20	834.0 ~ 839.0	0.0826	18M9G7D	0.0755	19M0W7D



5G NR n25 SA		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1852.5 ~ 1912.5	0.2723	4M48G7D	0.2183	4M48W7D
10	1855.0 ~ 1910.0	0.2838	9M28G7D	0.2421	9M29W7D
15	1857.5 ~ 1907.5	0.2812	14M1G7D	0.2286	14M1W7D
20	1860.0 ~ 1905.0	0.2773	18M9G7D	0.2104	18M9W7D
25	1862.5 ~ 1902.5	0.2704	23M7G7D	0.2178	23M8W7D
30	1865.0 ~ 1900.0	0.2799	28M5G7D	0.2183	28M6W7D
40	1870.0 ~ 1895.0	0.2844	38M6G7D	0.2173	38M6W7D

5G NR n25 (EN DC_12A-n25A)		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1852.5 ~ 1912.5	0.2518	4M48G7D	0.2477	4M48W7D
10	1855.0 ~ 1910.0	0.2793	9M28G7D	0.2612	9M28W7D
15	1857.5 ~ 1907.5	0.2618	14M1G7D	0.2455	14M1W7D
20	1860.0 ~ 1905.0	0.2477	18M9G7D	0.2455	19M0W7D
25	1862.5 ~ 1902.5	0.2360	23M7G7D	0.2307	23M7W7D
30	1865.0 ~ 1900.0	0.2382	28M5G7D	0.2275	28M6W7D
40	1870.0 ~ 1895.0	0.2793	38M7G7D	0.2291	38M6W7D

5G NR n66 SA		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1712.5 ~ 1777.5	0.3221	4M48G7D	0.2547	4M48W7D
10	1715.0 ~ 1775.0	0.3243	9M28G7D	0.2884	9M29W7D
15	1717.5 ~ 1772.5	0.3258	14M1G7D	0.2618	14M1W7D
20	1720.0 ~ 1770.0	0.3236	18M9G7D	0.2761	18M9W7D
30	1725.0 ~ 1765.0	0.3126	28M6G7D	0.2466	28M6W7D
40	1730.0 ~ 1760.0	0.3266	38M6G7D	0.2466	38M6W7D



5G NR n66 (EN DC_2A-n66A)		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1712.5 ~ 1777.5	0.2891	4M48G7D	0.2323	4M48W7D
10	1715.0 ~ 1775.0	0.3090	9M29G7D	0.2366	9M30W7D
15	1717.5 ~ 1772.5	0.2985	14M1G7D	0.2270	14M1W7D
20	1720.0 ~ 1770.0	0.3221	18M9G7D	0.2366	19M0W7D
30	1725.0 ~ 1765.0	0.2812	28M6G7D	0.2259	28M6W7D
40	1730.0 ~ 1760.0	0.3221	38M6G7D	0.2270	38M6W7D

Note: All modulations have been tested, only the worst test results of PSK & QAM are shown in the report.

1.8 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-SZ/03CH04-SZ	CN1256	421272



1.9 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a
2.	03CH04-SZ	AUDIX	E3	6.2009-8-24

1.10 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22, 24, 27
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.




2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.


Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			

Test Items	5G NR	Bandwidth (MHz)							Modulation					RB #		Test Channel		
		5	10	15	20	25	30	40	PI/2 BPSK	QPSK	16QAM	64QAM	256 QAM	1	Full	L	M	H
Max. Output Power	n2	v	v	v	v	-	-	-	v	v	v	v	v	v	v	v	v	v
	n5	v	v	v	v	-	-	-	v	v	v	v	v	v	v	v	v	v
	n25	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	n66	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	n2				v	-	-	-	v	v				v	v	v	v	v
	n5				v	-	-	-	v	v				v	v	v	v	v
	n25				v				v	v				v	v	v	v	v
	n66				v	-			v	v				v	v	v	v	v
26dB and 99% Bandwidth	n2	v	v	v	v	-	-	-	v	v	v	v	v		v		v	
	n5	v	v	v	v	-	-	-	v	v	v	v	v		v		v	
	n25	v	v	v	v	v	v	v	v	v	v	v	v		v		v	
	n66	v	v	v	v	-	v	v	v	v	v	v	v		v		v	
Conducted Band Edge	n2	v	v		v	-	-	-	v	v				v	v	v		v
	n5	v	v		v	-	-	-	v	v				v	v	v		v
	n25	v			v			v	v	v				v	v	v		v
	n66	v			v	-		v	v	v				v	v	v		v



Test Items	5G NR	Bandwidth (MHz)							Modulation					RB #		Test Channel		
		5	10	15	20	25	30	40	PI/2 BPSK	QPSK	16QAM	64QAM	256 QAM	1	Full	L	M	H
Conducted Spurious Emission	n2	v	v		v	-	-	-	v	v				v		v	v	v
	n5	v	v		v	-	-	-	v	v				v		v	v	v
	n25	v			v			v	v	v				v		v	v	v
	n66	v			v	-		v	v	v				v		v	v	v
Frequency Stability	n2				v	-	-	-		v					v		v	
	n5				v	-	-	-		v					v		v	
	n25				v					v					v		v	
	n66				v	-				v					v		v	
E.R.P / E.I.R.P	n2	v	v	v	v	-	-		v	v	v	v	v	v	v	v	v	v
	n5	v	v	v	v	-	-		v	v	v	v	v	v	v	v	v	v
	n25	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	n66	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v	v	v
Radiated Spurious Emission	n2	Worst Case														v	v	v
	n5	Worst Case														v	v	v
	n25	Worst Case														v	v	v
	n66	Worst Case														v	v	v
Note	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																	

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.9 dB.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\
 &= 4.9 \text{ (dB)}
 \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

5G NR n2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	388000	392000	396000
	Frequency	1860	1880	1900
15	Channel	387500	392000	396500
	Frequency	1857.5	1880	1902.5
10	Channel	387000	392000	397000
	Frequency	1855	1880	1905
5	Channel	386500	392000	397500
	Frequency	1852.5	1880	1907.5

5G NR n5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	175800	176300	176800
	Frequency	834	836.5	839
15	Channel	175300	176300	177300
	Frequency	831.5	836.5	841.5
10	Channel	174800	176300	177800
	Frequency	829	836.5	844
5	Channel	174300	176300	178300
	Frequency	826.5	836.5	846.5



5G NR n25 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
40	Channel	390000	392500	395000
	Frequency	1870	1882.5	1895
30	Channel	389000	392500	396000
	Frequency	1865	1882.5	1900
25	Channel	388500	392500	396500
	Frequency	1862.5	1882.5	1902.5
20	Channel	388000	392500	397000
	Frequency	1860	1882.5	1905
15	Channel	387500	392500	397500
	Frequency	1857.5	1882.5	1907.5
10	Channel	387000	392500	398000
	Frequency	1855	1882.5	1910
5	Channel	386500	392500	398500
	Frequency	1852.5	1882.5	1912.5

5G NR n66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
40	Channel	426000	429000	432000
	Frequency	1730	1745	1760
30	Channel	425000	429000	433000
	Frequency	1725	1745	1765
20	Channel	424000	429000	434000
	Frequency	1720	1745	1770
15	Channel	423500	429000	434500
	Frequency	1717.5	1745	1772.5
10	Channel	423000	429000	435000
	Frequency	1715	1745	1775
5	Channel	422500	429000	435500
	Frequency	1712.5	1745	1777.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for 5G NR n5.

The EIRP of mobile transmitters must not exceed 2 Watts for 5G NR n2 and n25.

The EIRP of mobile transmitters must not exceed 1 Watts for 5G NR n66.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB) = -13dBm.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
= -13dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Signal Analyzer	KEYSIGHT	N9010B	MY60240803	10Hz~44GHz	Apr. 03, 2021	Jun. 06, 2021~ Jun. 23, 2021	Apr. 02, 2022	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 26, 2020	Jun. 06, 2021~ Jun. 23, 2021	Dec. 25, 2021	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 22, 2020	Jun. 06, 2021~ Jun. 23, 2021	Jul. 21, 2021	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 21, 2020	Jul. 01, 2021~ Jul. 02, 2021	Jul. 20, 2021	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Jul. 15, 2020	Jul. 01, 2021~ Jul. 02, 2021	Jul. 14, 2021	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 25, 2020	Jul. 01, 2021~ Jul. 02, 2021	Jul. 24, 2021	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 21, 2020	Jul. 01, 2021~ Jul. 02, 2021	Jul. 20, 2021	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 23, 2021	Jul. 01, 2021~ Jul. 02, 2021	Apr. 22, 2022	Radiation (03CH02-SZ)
LF Amplifier	Burgeon	BPA-530	102211	0.01~3000Mhz	Oct. 16, 2020	Jul. 01, 2021~ Jul. 02, 2021	Oct. 15, 2021	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 16, 2020	Jul. 01, 2021~ Jul. 02, 2021	Oct. 15, 2021	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010002470	N/A	NCR	Jul. 01, 2021~ Jul. 02, 2021	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Jul. 01, 2021~ Jul. 02, 2021	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Jul. 01, 2021~ Jul. 02, 2021	NCR	Radiation (03CH02-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 21, 2020	Jun. 30, 2021	Jul. 20, 2021	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	Oct. 26, 2020	Jun. 30, 2021	Oct. 25, 2021	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1474	1GHz~18GHz	Jul. 16, 2020	Jun. 30, 2021	Jul. 15, 2021	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 26, 2020	Jun. 30, 2021	Jul. 25, 2021	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHZ	Oct. 16, 2020	Jun. 30, 2021	Oct. 15, 2021	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P-R	1943528	1GHz~18GHz	Oct. 16, 2020	Jun. 30, 2021	Oct. 15, 2021	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 21, 2020	Jun. 30, 2021	Jul. 20, 2021	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY53270156	500MHz~26.5GHz	Oct. 16, 2020	Jun. 30, 2021	Oct. 15, 2021	Radiation (03CH04-SZ)
AC Power Source	Chroma	61601	N/A	N/A	NCR	Jun. 30, 2021	NCR	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 30, 2021	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 30, 2021	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required



6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

<03CH02-SZ>:

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.47dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.31dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.72dB
---	--------

<03CH04-SZ>:

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.1dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.9dB
---	-------

----- THE END -----



Appendix A. Test Results of Conducted Test

FR1 N2 SA

Transmitter Conducted Output Power And ERP/EIRP, ($G_T - L_C$)=0.65dB

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
2	15	5	386500	1852.5	DFT-s-OFDM PI/2 BPSK	12@6	23.3	23.95	0.2483
2	15	5	386500	1852.5	DFT-s-OFDM PI/2 BPSK	1@1	23.42	24.07	0.2553
2	15	5	386500	1852.5	DFT-s-OFDM PI/2 BPSK	1@23	23.41	24.06	0.2547
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	12@6	23.35	24	0.2512
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	1@1	23.55	24.2	0.2630
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	1@23	23.65	24.3	0.2692
2	15	5	386500	1852.5	DFT-s-OFDM 16 QAM	12@6	22.41	23.06	0.2023
2	15	5	386500	1852.5	DFT-s-OFDM 16 QAM	1@1	22.48	23.13	0.2056
2	15	5	386500	1852.5	DFT-s-OFDM 16 QAM	1@23	22.6	23.25	0.2113
2	15	5	386500	1852.5	DFT-s-OFDM 64 QAM	12@6	20.89	21.54	0.1426
2	15	5	386500	1852.5	DFT-s-OFDM 64 QAM	1@1	21.11	21.76	0.1500
2	15	5	386500	1852.5	DFT-s-OFDM 64 QAM	1@23	21.14	21.79	0.1510
2	15	5	386500	1852.5	DFT-s-OFDM 256 QAM	12@6	18.79	19.44	0.0879
2	15	5	386500	1852.5	DFT-s-OFDM 256 QAM	1@1	18.77	19.42	0.0875
2	15	5	386500	1852.5	DFT-s-OFDM 256 QAM	1@23	18.75	19.4	0.0871
2	15	5	386500	1852.5	CP-OFDM QPSK	13@6	21.88	22.53	0.1791
2	15	5	386500	1852.5	CP-OFDM QPSK	1@1	22.04	22.69	0.1858
2	15	5	386500	1852.5	CP-OFDM QPSK	1@23	22.22	22.87	0.1936
2	15	5	392000	1880.0	DFT-s-OFDM PI/2 BPSK	12@6	23.21	23.86	0.2432

2	15	5	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@1	23.31	23.96	0.2489
2	15	5	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@23	23.31	23.96	0.2489
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	12@6	23.2	23.85	0.2427
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	1@1	23.4	24.05	0.2541
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	1@23	23.47	24.12	0.2582
2	15	5	392000	1880.0	DFT-s-OFDM 16 QAM	12@6	22.11	22.76	0.1888
2	15	5	392000	1880.0	DFT-s-OFDM 16 QAM	1@1	22.49	23.14	0.2061
2	15	5	392000	1880.0	DFT-s-OFDM 16 QAM	1@23	22.56	23.21	0.2094
2	15	5	392000	1880.0	DFT-s-OFDM 64 QAM	12@6	20.87	21.52	0.1419
2	15	5	392000	1880.0	DFT-s-OFDM 64 QAM	1@1	21	21.65	0.1462
2	15	5	392000	1880.0	DFT-s-OFDM 64 QAM	1@23	21.01	21.66	0.1466
2	15	5	392000	1880.0	DFT-s-OFDM 256 QAM	12@6	18.64	19.29	0.0849
2	15	5	392000	1880.0	DFT-s-OFDM 256 QAM	1@1	18.7	19.35	0.0861
2	15	5	392000	1880.0	DFT-s-OFDM 256 QAM	1@23	18.71	19.36	0.0863
2	15	5	392000	1880.0	CP-OFDM QPSK	13@6	21.83	22.48	0.1770
2	15	5	392000	1880.0	CP-OFDM QPSK	1@1	21.59	22.24	0.1675
2	15	5	392000	1880.0	CP-OFDM QPSK	1@23	21.68	22.33	0.1710
2	15	5	397500	1907.5	DFT-s-OFDM PI/2 BPSK	12@6	23.35	24	0.2512
2	15	5	397500	1907.5	DFT-s-OFDM PI/2 BPSK	1@1	23.27	23.92	0.2466
2	15	5	397500	1907.5	DFT-s-OFDM PI/2 BPSK	1@23	23.27	23.92	0.2466
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	12@6	23.26	23.91	0.2460
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	1@1	23.36	24.01	0.2518
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	1@23	23.59	24.24	0.2655
2	15	5	397500	1907.5	DFT-s-OFDM 16 QAM	12@6	22.23	22.88	0.1941

2	15	5	397500	1907.5	DFT-s-OFDM 16 QAM	1@1	22.49	23.14	0.2061
2	15	5	397500	1907.5	DFT-s-OFDM 16 QAM	1@23	22.53	23.18	0.2080
2	15	5	397500	1907.5	DFT-s-OFDM 64 QAM	12@6	20.86	21.51	0.1416
2	15	5	397500	1907.5	DFT-s-OFDM 64 QAM	1@1	20.96	21.61	0.1449
2	15	5	397500	1907.5	DFT-s-OFDM 64 QAM	1@23	21.06	21.71	0.1483
2	15	5	397500	1907.5	DFT-s-OFDM 256 QAM	12@6	18.62	19.27	0.0845
2	15	5	397500	1907.5	DFT-s-OFDM 256 QAM	1@1	18.39	19.04	0.0802
2	15	5	397500	1907.5	DFT-s-OFDM 256 QAM	1@23	18.42	19.07	0.0807
2	15	5	397500	1907.5	CP-OFDM QPSK	13@6	21.79	22.44	0.1754
2	15	5	397500	1907.5	CP-OFDM QPSK	1@1	21.95	22.6	0.1820
2	15	5	397500	1907.5	CP-OFDM QPSK	1@23	21.59	22.24	0.1675
2	15	10	387000	1907.5	DFT-s-OFDM PI/2 BPSK	25@12	22.79	23.44	0.2208
2	15	10	387000	1907.5	DFT-s-OFDM PI/2 BPSK	1@1	23.51	24.16	0.2606
2	15	10	387000	1855.0	DFT-s-OFDM PI/2 BPSK	1@50	23.63	24.28	0.2679
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	25@12	23.31	23.96	0.2489
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	1@1	23.94	24.59	0.2877
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	1@50	23.88	24.53	0.2838
2	15	10	387000	1855.0	DFT-s-OFDM 16 QAM	25@12	22.37	23.02	0.2004
2	15	10	387000	1855.0	DFT-s-OFDM 16 QAM	1@1	23.02	23.67	0.2328
2	15	10	387000	1855.0	DFT-s-OFDM 16 QAM	1@50	23.03	23.68	0.2333
2	15	10	387000	1855.0	DFT-s-OFDM 64 QAM	25@12	21.03	21.68	0.1472
2	15	10	387000	1855.0	DFT-s-OFDM 64 QAM	1@1	21.44	22.09	0.1618
2	15	10	387000	1855.0	DFT-s-OFDM 64 QAM	1@50	21.45	22.1	0.1622
2	15	10	387000	1855.0	DFT-s-OFDM 256 QAM	25@12	18.84	19.49	0.0889

2	15	10	387000	1855.0	DFT-s-OFDM 256 QAM	1@1	19.22	19.87	0.0971
2	15	10	387000	1855.0	DFT-s-OFDM 256 QAM	1@50	19.06	19.71	0.0935
2	15	10	387000	1855.0	CP-OFDM QPSK	26@13	21.83	22.48	0.1770
2	15	10	387000	1855.0	CP-OFDM QPSK	1@1	22.27	22.92	0.1959
2	15	10	387000	1855.0	CP-OFDM QPSK	1@50	22.15	22.8	0.1905
2	15	10	392000	1880.0	DFT-s-OFDM PI/2 BPSK	25@12	23.18	23.83	0.2415
2	15	10	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@1	23.68	24.33	0.2710
2	15	10	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@50	23.66	24.31	0.2698
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	25@12	23.33	23.98	0.2500
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	1@1	23.55	24.2	0.2630
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	1@50	23.44	24.09	0.2564
2	15	10	392000	1880.0	DFT-s-OFDM 16 QAM	25@12	22.5	23.15	0.2065
2	15	10	392000	1880.0	DFT-s-OFDM 16 QAM	1@1	22.99	23.64	0.2312
2	15	10	392000	1880.0	DFT-s-OFDM 16 QAM	1@50	22.93	23.58	0.2280
2	15	10	392000	1880.0	DFT-s-OFDM 64 QAM	25@12	20.92	21.57	0.1435
2	15	10	392000	1880.0	DFT-s-OFDM 64 QAM	1@1	21.46	22.11	0.1626
2	15	10	392000	1880.0	DFT-s-OFDM 64 QAM	1@50	21.52	22.17	0.1648
2	15	10	392000	1880.0	DFT-s-OFDM 256 QAM	25@12	18.79	19.44	0.0879
2	15	10	392000	1880.0	DFT-s-OFDM 256 QAM	1@1	19.03	19.68	0.0929
2	15	10	392000	1880.0	DFT-s-OFDM 256 QAM	1@50	19.11	19.76	0.0946
2	15	10	392000	1880.0	CP-OFDM QPSK	26@13	21.75	22.4	0.1738
2	15	10	392000	1880.0	CP-OFDM QPSK	1@1	22.43	23.08	0.2032
2	15	10	392000	1880.0	CP-OFDM QPSK	1@50	22.37	23.02	0.2004
2	15	10	397000	1905.0	DFT-s-OFDM PI/2 BPSK	25@12	23.37	24.02	0.2523

2	15	10	397000	1905.0	DFT-s-OFDM PI/2 BPSK	1@1	23.21	23.86	0.2432
2	15	10	397000	1905.0	DFT-s-OFDM PI/2 BPSK	1@50	23.25	23.9	0.2455
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	25@12	23.31	23.96	0.2489
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	1@1	23.25	23.9	0.2455
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	1@50	23.45	24.1	0.2570
2	15	10	397000	1905.0	DFT-s-OFDM 16 QAM	25@12	22.15	22.8	0.1905
2	15	10	397000	1905.0	DFT-s-OFDM 16 QAM	1@1	22.45	23.1	0.2042
2	15	10	397000	1905.0	DFT-s-OFDM 16 QAM	1@50	22.44	23.09	0.2037
2	15	10	397000	1905.0	DFT-s-OFDM 64 QAM	25@12	20.99	21.64	0.1459
2	15	10	397000	1905.0	DFT-s-OFDM 64 QAM	1@1	20.91	21.56	0.1432
2	15	10	397000	1905.0	DFT-s-OFDM 64 QAM	1@50	20.96	21.61	0.1449
2	15	10	397000	1905.0	DFT-s-OFDM 256 QAM	25@12	18.76	19.41	0.0873
2	15	10	397000	1905.0	DFT-s-OFDM 256 QAM	1@1	19.07	19.72	0.0938
2	15	10	397000	1905.0	DFT-s-OFDM 256 QAM	1@50	19.05	19.7	0.0933
2	15	10	397000	1905.0	CP-OFDM QPSK	26@13	21.82	22.47	0.1766
2	15	10	397000	1905.0	CP-OFDM QPSK	1@1	21.51	22.16	0.1644
2	15	10	397000	1905.0	CP-OFDM QPSK	1@50	21.72	22.37	0.1726
2	15	15	387500	1857.5	DFT-s-OFDM PI/2 BPSK	36@18	23.38	24.03	0.2529
2	15	15	387500	1857.5	DFT-s-OFDM PI/2 BPSK	1@1	23.64	24.29	0.2685
2	15	15	387500	1857.5	DFT-s-OFDM PI/2 BPSK	1@77	23.51	24.16	0.2606
2	15	15	387500	1857.5	DFT-s-OFDM QPSK	36@18	23.37	24.02	0.2523
2	15	15	387500	1857.5	DFT-s-OFDM QPSK	1@1	23.77	24.42	0.2767
2	15	15	387500	1857.5	DFT-s-OFDM QPSK	1@77	23.58	24.23	0.2649
2	15	15	387500	1857.5	DFT-s-OFDM 16 QAM	36@18	22.35	23	0.1995

2	15	15	387500	1857.5	DFT-s-OFDM 16 QAM	1@1	22.8	23.45	0.2213
2	15	15	387500	1857.5	DFT-s-OFDM 16 QAM	1@77	22.7	23.35	0.2163
2	15	15	387500	1857.5	DFT-s-OFDM 64 QAM	36@18	20.92	21.57	0.1435
2	15	15	387500	1857.5	DFT-s-OFDM 64 QAM	1@1	21.05	21.7	0.1479
2	15	15	387500	1857.5	DFT-s-OFDM 64 QAM	1@77	21.04	21.69	0.1476
2	15	15	387500	1857.5	DFT-s-OFDM 256 QAM	36@18	18.84	19.49	0.0889
2	15	15	387500	1857.5	DFT-s-OFDM 256 QAM	1@1	18.96	19.61	0.0914
2	15	15	387500	1857.5	DFT-s-OFDM 256 QAM	1@77	18.9	19.55	0.0902
2	15	15	387500	1857.5	CP-OFDM QPSK	39@191	20.41	21.06	0.1276
2	15	15	387500	1857.5	CP-OFDM QPSK	1@1	21.96	22.61	0.1824
2	15	15	387500	1857.5	CP-OFDM QPSK	1@77	22.15	22.8	0.1905
2	15	15	392000	1880.0	DFT-s-OFDM PI/2 BPSK	36@18	23.24	23.89	0.2449
2	15	15	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@1	23.16	23.81	0.2404
2	15	15	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@77	23.15	23.8	0.2399
2	15	15	392000	1880.0	DFT-s-OFDM QPSK	36@18	23.29	23.94	0.2477
2	15	15	392000	1880.0	DFT-s-OFDM QPSK	1@1	22.81	23.46	0.2218
2	15	15	392000	1880.0	DFT-s-OFDM QPSK	1@77	23.22	23.87	0.2438
2	15	15	392000	1880.0	DFT-s-OFDM 16 QAM	36@18	22.33	22.98	0.1986
2	15	15	392000	1880.0	DFT-s-OFDM 16 QAM	1@1	22.16	22.81	0.1910
2	15	15	392000	1880.0	DFT-s-OFDM 16 QAM	1@77	22.49	23.14	0.2061
2	15	15	392000	1880.0	DFT-s-OFDM 64 QAM	36@18	20.83	21.48	0.1406
2	15	15	392000	1880.0	DFT-s-OFDM 64 QAM	1@1	20.9	21.55	0.1429
2	15	15	392000	1880.0	DFT-s-OFDM 64 QAM	1@77	21.21	21.86	0.1535
2	15	15	392000	1880.0	DFT-s-OFDM 256 QAM	36@18	18.7	19.35	0.0861

2	15	15	392000	1880.0	DFT-s-OFDM 256 QAM	1@1	18.88	19.53	0.0897
2	15	15	392000	1880.0	DFT-s-OFDM 256 QAM	1@77	19.05	19.7	0.0933
2	15	15	392000	1880.0	CP-OFDM QPSK	39@191	20.35	21	0.1259
2	15	15	392000	1880.0	CP-OFDM QPSK	1@1	21.43	22.08	0.1614
2	15	15	392000	1880.0	CP-OFDM QPSK	1@77	21.85	22.5	0.1778
2	15	15	396500	1902.5	DFT-s-OFDM PI/2 BPSK	36@18	23.3	23.95	0.2483
2	15	15	396500	1902.5	DFT-s-OFDM PI/2 BPSK	1@1	23.25	23.9	0.2455
2	15	15	396500	1902.5	DFT-s-OFDM PI/2 BPSK	1@77	23.33	23.98	0.2500
2	15	15	396500	1902.5	DFT-s-OFDM QPSK	36@18	23.3	23.95	0.2483
2	15	15	396500	1902.5	DFT-s-OFDM QPSK	1@1	23.33	23.98	0.2500
2	15	15	396500	1902.5	DFT-s-OFDM QPSK	1@77	23.52	24.17	0.2612
2	15	15	396500	1902.5	DFT-s-OFDM 16 QAM	36@18	22.39	23.04	0.2014
2	15	15	396500	1902.5	DFT-s-OFDM 16 QAM	1@1	22.39	23.04	0.2014
2	15	15	396500	1902.5	DFT-s-OFDM 16 QAM	1@77	22.43	23.08	0.2032
2	15	15	396500	1902.5	DFT-s-OFDM 64 QAM	36@18	20.98	21.63	0.1455
2	15	15	396500	1902.5	DFT-s-OFDM 64 QAM	1@1	21	21.65	0.1462
2	15	15	396500	1902.5	DFT-s-OFDM 64 QAM	1@77	20.94	21.59	0.1442
2	15	15	396500	1902.5	DFT-s-OFDM 256 QAM	36@18	18.75	19.4	0.0871
2	15	15	396500	1902.5	DFT-s-OFDM 256 QAM	1@1	18.94	19.59	0.0910
2	15	15	396500	1902.5	DFT-s-OFDM 256 QAM	1@77	18.83	19.48	0.0887
2	15	15	396500	1902.5	CP-OFDM QPSK	39@191	20.31	20.96	0.1247
2	15	15	396500	1902.5	CP-OFDM QPSK	1@1	21.58	22.23	0.1671
2	15	15	396500	1902.5	CP-OFDM QPSK	1@77	21.84	22.49	0.1774
2	15	20	388000	1902.5	DFT-s-OFDM PI/2 BPSK	50@25	23.21	23.86	0.2432

2	15	20	388000	1902.5	DFT-s-OFDM PI/2 BPSK	1@1	23.31	23.96	0.2489
2	15	20	388000	1902.5	DFT-s-OFDM PI/2 BPSK	1@104	23.3	23.95	0.2483
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	50@25	23.36	24.01	0.2518
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@1	23.43	24.08	0.2559
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@104	22.94	23.59	0.2286
2	15	20	388000	1860.0	DFT-s-OFDM 16 QAM	50@25	22.43	23.08	0.2032
2	15	20	388000	1860.0	DFT-s-OFDM 16 QAM	1@1	22.73	23.38	0.2178
2	15	20	388000	1860.0	DFT-s-OFDM 16 QAM	1@104	22.65	23.3	0.2138
2	15	20	388000	1860.0	DFT-s-OFDM 64 QAM	50@25	20.98	21.63	0.1455
2	15	20	388000	1860.0	DFT-s-OFDM 64 QAM	1@1	20.91	21.56	0.1432
2	15	20	388000	1860.0	DFT-s-OFDM 64 QAM	1@104	20.59	21.24	0.1330
2	15	20	388000	1860.0	DFT-s-OFDM 256 QAM	50@25	19.17	19.82	0.0959
2	15	20	388000	1860.0	DFT-s-OFDM 256 QAM	1@1	19.24	19.89	0.0975
2	15	20	388000	1860.0	DFT-s-OFDM 256 QAM	1@104	19.19	19.84	0.0964
2	15	20	388000	1860.0	CP-OFDM QPSK	53@26	21.93	22.58	0.1811
2	15	20	388000	1860.0	CP-OFDM QPSK	1@1	21.68	22.33	0.1710
2	15	20	388000	1860.0	CP-OFDM QPSK	1@104	21.73	22.38	0.1730
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	50@25	23.24	23.89	0.2449
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@1	23.15	23.8	0.2399
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@104	23.21	23.86	0.2432
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	50@25	23.29	23.94	0.2477
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	1@1	22.82	23.47	0.2223
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	1@104	23.49	24.14	0.2594
2	15	20	392000	1880.0	DFT-s-OFDM 16 QAM	50@25	22.33	22.98	0.1986

2	15	20	392000	1880.0	DFT-s-OFDM 16 QAM	1@1	22.15	22.8	0.1905
2	15	20	392000	1880.0	DFT-s-OFDM 16 QAM	1@104	22.45	23.1	0.2042
2	15	20	392000	1880.0	DFT-s-OFDM 64 QAM	50@25	20.91	21.56	0.1432
2	15	20	392000	1880.0	DFT-s-OFDM 64 QAM	1@1	20.91	21.56	0.1432
2	15	20	392000	1880.0	DFT-s-OFDM 64 QAM	1@104	21.02	21.67	0.1469
2	15	20	392000	1880.0	DFT-s-OFDM 256 QAM	50@25	18.78	19.43	0.0877
2	15	20	392000	1880.0	DFT-s-OFDM 256 QAM	1@1	19.14	19.79	0.0953
2	15	20	392000	1880.0	DFT-s-OFDM 256 QAM	1@104	19.17	19.82	0.0959
2	15	20	392000	1880.0	CP-OFDM QPSK	53@26	21.88	22.53	0.1791
2	15	20	392000	1880.0	CP-OFDM QPSK	1@1	21.42	22.07	0.1611
2	15	20	392000	1880.0	CP-OFDM QPSK	1@104	21.81	22.46	0.1762
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	50@25	23.37	24.02	0.2523
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	1@1	23.18	23.83	0.2415
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	1@104	23.12	23.77	0.2382
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	50@25	23.95	24.6	0.2884
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@1	23.3	23.95	0.2483
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@104	23.38	24.03	0.2529
2	15	20	396000	1900.0	DFT-s-OFDM 16 QAM	50@25	22.45	23.1	0.2042
2	15	20	396000	1900.0	DFT-s-OFDM 16 QAM	1@1	22.32	22.97	0.1982
2	15	20	396000	1900.0	DFT-s-OFDM 16 QAM	1@104	22.37	23.02	0.2004
2	15	20	396000	1900.0	DFT-s-OFDM 64 QAM	50@25	21.02	21.67	0.1469
2	15	20	396000	1900.0	DFT-s-OFDM 64 QAM	1@1	20.69	21.34	0.1361
2	15	20	396000	1900.0	DFT-s-OFDM 64 QAM	1@104	20.76	21.41	0.1384
2	15	20	396000	1900.0	DFT-s-OFDM 256 QAM	50@25	18.94	19.59	0.0910

2	15	20	396000	1900.0	DFT-s-OFDM 256 QAM	1@1	19.21	19.86	0.0968
2	15	20	396000	1900.0	DFT-s-OFDM 256 QAM	1@104	19.11	19.76	0.0946
2	15	20	396000	1900.0	CP-OFDM QPSK	53@26	21.93	22.58	0.1811
2	15	20	396000	1900.0	CP-OFDM QPSK	1@1	21.55	22.2	0.1660
2	15	20	396000	1900.0	CP-OFDM QPSK	1@104	21.81	22.46	0.1762

Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00284	PASS	NV
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00552	PASS	LV
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00534	PASS	HV
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00649	PASS	-30°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00641	PASS	-20°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00659	PASS	-10°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00416	PASS	0°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00368	PASS	10°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00689	PASS	20°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.0063	PASS	30°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00371	PASS	40°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.006	PASS	50°C

Peak to Average Ratio

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
2	15	20	388000	1860.0	DFT-s-OFDM PI/2 BPSK	100@0	4.21	13	PASS
2	15	20	388000	1860.0	DFT-s-OFDM PI/2 BPSK	1@0	4.2	13	PASS
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	100@0	5.23	13	PASS
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@0	8.05	13	PASS
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	100@0	4.64	13	PASS
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@0	3.72	13	PASS
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	5.59	13	PASS
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	1@0	5.01	13	PASS
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	100@0	4.32	13	PASS
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	1@0	4.28	13	PASS
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	100@0	5.44	13	PASS
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@0	4.32	13	PASS


N2(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_Low_CH




N2(20M)_DFT-s-OFDM_PI_2-BPSK_Edge_1RB_Left_Low_CH



N2(20M)_DFT-s-OFDM_QPSK_Outer_Full_Low_CH



N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Low_CH




N2(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_Mid_CH



N2(20M)_DFT-s-OFDM_PI_2-BPSK_Edge_1RB_Left_Mid_CH




N2(20M)_DFT-s-OFDM_QPSK_Outer_Full_Mid_CH




N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



N2(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_High_CH



N2(20M)_DFT-s-OFDM_PI_2-BPSK_Edge_1RB_Left_High_CH



N2(20M)_DFT-s-OFDM_QPSK_Outer_Full_High_CH




N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH




Occupied Bandwidth

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB OBW (MHz)
2	15	5	392000	1880.0	DFT-s-OFDM PI/2 BPSK	25@0	4.4831	4.838
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	25@0	4.4734	4.939
2	15	5	392000	1880.0	CP-OFDM QPSK	25@0	4.4672	4.883
2	15	5	392000	1880.0	CP-OFDM 16 QAM	25@0	4.494	4.957
2	15	5	392000	1880.0	CP-OFDM 64 QAM	25@0	4.4606	4.898
2	15	5	392000	1880.0	CP-OFDM 256 QAM	25@0	4.4776	4.925
2	15	10	392000	1880.0	DFT-s-OFDM PI/2 BPSK	50@0	8.9087	9.514
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	50@0	8.9244	9.546
2	15	10	392000	1880.0	CP-OFDM QPSK	52@0	9.284	9.924
2	15	10	392000	1880.0	CP-OFDM 16 QAM	52@0	9.2906	9.923
2	15	10	392000	1880.0	CP-OFDM 64 QAM	52@0	9.2744	9.796
2	15	10	392000	1880.0	CP-OFDM 256 QAM	52@0	9.2801	9.829
2	15	15	392000	1880.0	DFT-s-OFDM PI/2 BPSK	75@0	13.394	14.09
2	15	15	392000	1880.0	DFT-s-OFDM QPSK	75@0	13.437	14.14
2	15	15	392000	1880.0	CP-OFDM QPSK	79@0	14.098	14.83
2	15	15	392000	1880.0	CP-OFDM 16 QAM	79@0	14.108	14.81
2	15	15	392000	1880.0	CP-OFDM 64 QAM	79@0	14.113	14.86
2	15	15	392000	1880.0	CP-OFDM 256 QAM	79@0	14.082	14.81
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	100@0	17.917	18.67
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	17.873	18.71
2	15	20	392000	1880.0	CP-OFDM QPSK	106@0	18.928	19.78
2	15	20	392000	1880.0	CP-OFDM 16 QAM	106@0	18.951	19.74
2	15	20	392000	1880.0	CP-OFDM 64 QAM	106@0	18.93	19.78
2	15	20	392000	1880.0	CP-OFDM 256 QAM	106@0	18.957	19.8

N2(5M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_Mid_CH




N2(5M)_DFT-s-OFDM_QPSK_Outer_Full_Mid_CH




N2(5M)_CP-OFDM_QPSK_Outer_Full_Mid_CH




N2(5M)_CP-OFDM_16QAM_Outer_Full_Mid_CH




N2(5M)_CP-OFDM_64QAM_Outer_Full_Mid_CH



N2(5M)_CP-OFDM_256QAM_Outer_Full_Mid_CH




N2(10M)_DFT-s-OFDM_PI_2-
BPSK_Outer_Full_Mid_CH



N2(10M)_DFT-s-
OFDM_QPSK_Outer_Full_Mid_CH




N2(10M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N2(10M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH




N2(10M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N2(10M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH




N2(15M)_DFT-s-OFDM_PI_2- BPSK_Outer_Full_Mid_CH



N2(15M)_DFT-s- OFDM_QPSK_Outer_Full_Mid_CH



N2(15M)_CP- OFDM_QPSK_Outer_Full_Mid_CH




N2(15M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH




N2(15M)_CP-OFDM_64 QAM_Outer_Full_Mid_CH




N2(15M)_CP-OFDM_256 QAM_Outer_Full_Mid_CH




N2(20M)_DFT-s-OFDM_PI_2- BPSK_Outer_Full_Mid_CH



N2(20M)_DFT-s- OFDM_QPSK_Outer_Full_Mid_CH




N2(20M)_CP- OFDM_QPSK_Outer_Full_Mid_CH




N2(20M)_CP-OFDM_16 QAM_Outer_Full_Mid_CH



N2(20M)_CP-OFDM_64 QAM_Outer_Full_Mid_CH



N2(20M)_CP-OFDM_256 QAM_Outer_Full_Mid_CH




Conducted Spurious Emissions


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
2	15	5	386500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	5	386500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	5	392000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	5	392000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	5	397500	1907.5	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	5	397500	1907.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	10	387000	1855.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	10	387000	1855.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	10	392000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	10	392000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	10	397000	1905.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	10	397000	1905.0	DFT-s-OFDM BPSK	1@0	see graph	PASS

2	15	10	397000	1905.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	20	388000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	20	388000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	20	392000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	20	392000	1880.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	20	396000	1900.0	DFT-s-OFDM BPSK	1@0	see graph	---
2	15	20	396000	1900.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@0	see graph	---
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@0	see graph	PASS


N2(5M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(5M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Low_CH




N2(5M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Mid_CH




N2(5M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH




N2(5M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_High_CH




N2(5M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH




N2(10M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH




N2(10M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N2(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH




N2(10M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH



N2(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH




N2(20M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Low_CH




N2(20M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Mid_CH




N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



N2(20M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_High_CH



N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH




Conducted Band Edge


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
2	15	5	386500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	5	386500	1852.5	DFT-s-OFDM BPSK	25@0	see graph	PASS
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	25@0	see graph	PASS
2	15	5	397500	1907.5	DFT-s-OFDM BPSK	1@24	see graph	PASS
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	1@24	see graph	PASS
2	15	5	397500	1907.5	DFT-s-OFDM BPSK	25@0	see graph	PASS
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	25@0	see graph	PASS
2	15	10	387000	1855.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	10	387000	1855.0	DFT-s-OFDM BPSK	50@0	see graph	PASS
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	50@0	see graph	PASS
2	15	10	397000	1905.0	DFT-s-OFDM BPSK	1@51	see graph	PASS
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	1@51	see graph	PASS
2	15	10	397000	1905.0	DFT-s-OFDM BPSK	50@0	see graph	PASS
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	50@0	see graph	PASS
2	15	20	388000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
2	15	20	388000	1860.0	DFT-s-OFDM BPSK	100@0	see graph	PASS
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	100@0	see graph	PASS
2	15	20	396000	1900.0	DFT-s-OFDM BPSK	1@105	see graph	PASS
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@105	see graph	PASS

2	15	20	396000	1900.0	DFT-s-OFDM BPSK	100@0	see graph	PASS
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	100@0	see graph	PASS


N2(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH




N2(5M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N2(5M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH




N2(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N2(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH




N2(5M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH




N2(5M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH




N2(10M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N2(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH




N2(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH_CHP_PA
SS




N2(10M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N2(10M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH



N2(10M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH



N2(10M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH




N2(10M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH




N2(10M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH




N2(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH



N2(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH




N2(20M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N2(20M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH




N2(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N2(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N2(20M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH



N2(20M)_DFT-s-OFDM_QPSK_Outer_Full_High_CH



FR1 N2 NSA

LTE Band: 5, LTE BW: 10M, LTE ARFCN: Mid

Transmitter Conducted Output Power And ERP/EIRP, ($G_T - L_C$)=0.65dB

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
2	15	5	386500	1852.5	DFT-s-OFDM PI/2 BPSK	12@6	23.07	23.72	0.2355
2	15	5	386500	1852.5	DFT-s-OFDM PI/2 BPSK	1@1	23.16	23.81	0.2404
2	15	5	386500	1852.5	DFT-s-OFDM PI/2 BPSK	1@23	23.18	23.83	0.2415
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	12@6	23.03	23.68	0.2333
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	1@1	23.17	23.82	0.241
2	15	5	386500	1852.5	DFT-s-OFDM QPSK	1@23	23.16	23.81	0.2404
2	15	5	386500	1852.5	DFT-s-OFDM 16 QAM	12@6	23.1	23.75	0.2371
2	15	5	386500	1852.5	DFT-s-OFDM 16 QAM	1@1	23.28	23.93	0.2472
2	15	5	386500	1852.5	DFT-s-OFDM 16 QAM	1@23	23.12	23.77	0.2382
2	15	5	386500	1852.5	DFT-s-OFDM 64 QAM	12@6	22.21	22.86	0.1932
2	15	5	386500	1852.5	DFT-s-OFDM 64 QAM	1@1	22.4	23.05	0.2018
2	15	5	386500	1852.5	DFT-s-OFDM 64 QAM	1@23	22.38	23.03	0.2009
2	15	5	386500	1852.5	DFT-s-OFDM 256 QAM	12@6	20.07	20.72	0.118
2	15	5	386500	1852.5	DFT-s-OFDM 256 QAM	1@1	19.66	20.31	0.1074
2	15	5	386500	1852.5	DFT-s-OFDM 256 QAM	1@23	19.59	20.24	0.1057
2	15	5	386500	1852.5	CP-OFDM QPSK	13@6	23.09	23.74	0.2366
2	15	5	386500	1852.5	CP-OFDM QPSK	1@1	23.1	23.75	0.2371
2	15	5	386500	1852.5	CP-OFDM QPSK	1@23	23.28	23.93	0.2472

2	15	5	392000	1880.0	DFT-s-OFDM PI/2 BPSK	12@6	23.05	23.7	0.2344
2	15	5	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@1	23.16	23.81	0.2404
2	15	5	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@23	23.14	23.79	0.2393
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	12@6	23.05	23.7	0.2344
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	1@1	23.19	23.84	0.2421
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	1@23	23.17	23.82	0.241
2	15	5	392000	1880.0	DFT-s-OFDM 16 QAM	12@6	22.83	23.48	0.2228
2	15	5	392000	1880.0	DFT-s-OFDM 16 QAM	1@1	22.48	23.13	0.2056
2	15	5	392000	1880.0	DFT-s-OFDM 16 QAM	1@23	23.1	23.75	0.2371
2	15	5	392000	1880.0	DFT-s-OFDM 64 QAM	12@6	21.61	22.26	0.1683
2	15	5	392000	1880.0	DFT-s-OFDM 64 QAM	1@1	21.43	22.08	0.1614
2	15	5	392000	1880.0	DFT-s-OFDM 64 QAM	1@23	22.33	22.98	0.1986
2	15	5	392000	1880.0	DFT-s-OFDM 256 QAM	12@6	20.01	20.66	0.1164
2	15	5	392000	1880.0	DFT-s-OFDM 256 QAM	1@1	19.59	20.24	0.1057
2	15	5	392000	1880.0	DFT-s-OFDM 256 QAM	1@23	19.58	20.23	0.1054
2	15	5	392000	1880.0	CP-OFDM QPSK	13@6	22.36	23.01	0.2
2	15	5	392000	1880.0	CP-OFDM QPSK	1@1	22.21	22.86	0.1932
2	15	5	392000	1880.0	CP-OFDM QPSK	1@23	23.15	23.8	0.2399
2	15	5	397500	1907.5	DFT-s-OFDM PI/2 BPSK	12@6	23.04	23.69	0.2339
2	15	5	397500	1907.5	DFT-s-OFDM PI/2 BPSK	1@1	23.15	23.8	0.2399
2	15	5	397500	1907.5	DFT-s-OFDM PI/2 BPSK	1@23	23.19	23.84	0.2421
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	12@6	23.05	23.7	0.2344
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	1@1	23.1	23.75	0.2371
2	15	5	397500	1907.5	DFT-s-OFDM QPSK	1@23	23.06	23.71	0.235

2	15	5	397500	1907.5	DFT-s-OFDM 16 QAM	12@6	23.07	23.72	0.2355
2	15	5	397500	1907.5	DFT-s-OFDM 16 QAM	1@1	23.25	23.9	0.2455
2	15	5	397500	1907.5	DFT-s-OFDM 16 QAM	1@23	23.32	23.97	0.2495
2	15	5	397500	1907.5	DFT-s-OFDM 64 QAM	12@6	22.08	22.73	0.1875
2	15	5	397500	1907.5	DFT-s-OFDM 64 QAM	1@1	22.06	22.71	0.1866
2	15	5	397500	1907.5	DFT-s-OFDM 64 QAM	1@23	22.33	22.98	0.1986
2	15	5	397500	1907.5	DFT-s-OFDM 256 QAM	12@6	20	20.65	0.1161
2	15	5	397500	1907.5	DFT-s-OFDM 256 QAM	1@1	19.61	20.26	0.1062
2	15	5	397500	1907.5	DFT-s-OFDM 256 QAM	1@23	19.6	20.25	0.1059
2	15	5	397500	1907.5	CP-OFDM QPSK	13@6	22.92	23.57	0.2275
2	15	5	397500	1907.5	CP-OFDM QPSK	1@1	23.1	23.75	0.2371
2	15	5	397500	1907.5	CP-OFDM QPSK	1@23	22.9	23.55	0.2265
2	15	10	387000	1855.0	DFT-s-OFDM PI/2 BPSK	25@12	23.08	23.73	0.236
2	15	10	387000	1855.0	DFT-s-OFDM PI/2 BPSK	1@1	23.63	24.28	0.2679
2	15	10	387000	1855.0	DFT-s-OFDM PI/2 BPSK	1@50	23.61	24.26	0.2667
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	25@12	23.16	23.81	0.2404
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	1@1	23.63	24.28	0.2679
2	15	10	387000	1855.0	DFT-s-OFDM QPSK	1@50	23.68	24.33	0.271
2	15	10	387000	1855.0	DFT-s-OFDM 16 QAM	25@12	23.17	23.82	0.241
2	15	10	387000	1855.0	DFT-s-OFDM 16 QAM	1@1	23.6	24.25	0.2661
2	15	10	387000	1855.0	DFT-s-OFDM 16 QAM	1@50	23.38	24.03	0.2529
2	15	10	387000	1855.0	DFT-s-OFDM 64 QAM	25@12	22.22	22.87	0.1936
2	15	10	387000	1855.0	DFT-s-OFDM 64 QAM	1@1	22.89	23.54	0.2259
2	15	10	387000	1855.0	DFT-s-OFDM 64 QAM	1@50	22.89	23.54	0.2259

2	15	10	387000	1855.0	DFT-s-OFDM 256 QAM	25@12	20.06	20.71	0.1178
2	15	10	387000	1855.0	DFT-s-OFDM 256 QAM	1@1	20.05	20.7	0.1175
2	15	10	387000	1855.0	DFT-s-OFDM 256 QAM	1@50	20.07	20.72	0.118
2	15	10	387000	1855.0	CP-OFDM QPSK	26@13	23.07	23.72	0.2355
2	15	10	387000	1855.0	CP-OFDM QPSK	1@1	23.61	24.26	0.2667
2	15	10	387000	1855.0	CP-OFDM QPSK	1@50	23.57	24.22	0.2642
2	15	10	392000	1880.0	DFT-s-OFDM PI/2 BPSK	25@12	23	23.65	0.2317
2	15	10	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@1	23.56	24.21	0.2636
2	15	10	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@50	23.55	24.2	0.263
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	25@12	23.19	23.84	0.2421
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	1@1	23.08	23.73	0.236
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	1@50	23.58	24.23	0.2649
2	15	10	392000	1880.0	DFT-s-OFDM 16 QAM	25@12	22.81	23.46	0.2218
2	15	10	392000	1880.0	DFT-s-OFDM 16 QAM	1@1	22.26	22.91	0.1954
2	15	10	392000	1880.0	DFT-s-OFDM 16 QAM	1@50	23.51	24.16	0.2606
2	15	10	392000	1880.0	DFT-s-OFDM 64 QAM	25@12	21.56	22.21	0.1663
2	15	10	392000	1880.0	DFT-s-OFDM 64 QAM	1@1	21.29	21.94	0.1563
2	15	10	392000	1880.0	DFT-s-OFDM 64 QAM	1@50	22.77	23.42	0.2198
2	15	10	392000	1880.0	DFT-s-OFDM 256 QAM	25@12	20	20.65	0.1161
2	15	10	392000	1880.0	DFT-s-OFDM 256 QAM	1@1	19.48	20.13	0.103
2	15	10	392000	1880.0	DFT-s-OFDM 256 QAM	1@50	19.98	20.63	0.1156
2	15	10	392000	1880.0	CP-OFDM QPSK	26@13	22.48	23.13	0.2056
2	15	10	392000	1880.0	CP-OFDM QPSK	1@1	22.04	22.69	0.1858
2	15	10	392000	1880.0	CP-OFDM QPSK	1@50	23.49	24.14	0.2594

2	15	10	397000	1905.0	DFT-s-OFDM PI/2 BPSK	25@12	23.11	23.76	0.2377
2	15	10	397000	1905.0	DFT-s-OFDM PI/2 BPSK	1@1	23.07	23.72	0.2355
2	15	10	397000	1905.0	DFT-s-OFDM PI/2 BPSK	1@50	23.06	23.71	0.235
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	25@12	23.17	23.82	0.241
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	1@1	23.08	23.73	0.236
2	15	10	397000	1905.0	DFT-s-OFDM QPSK	1@50	23.14	23.79	0.2393
2	15	10	397000	1905.0	DFT-s-OFDM 16 QAM	25@12	23.16	23.81	0.2404
2	15	10	397000	1905.0	DFT-s-OFDM 16 QAM	1@1	22.39	23.04	0.2014
2	15	10	397000	1905.0	DFT-s-OFDM 16 QAM	1@50	22.98	23.63	0.2307
2	15	10	397000	1905.0	DFT-s-OFDM 64 QAM	25@12	22.12	22.77	0.1892
2	15	10	397000	1905.0	DFT-s-OFDM 64 QAM	1@1	21.31	21.96	0.157
2	15	10	397000	1905.0	DFT-s-OFDM 64 QAM	1@50	22.02	22.67	0.1849
2	15	10	397000	1905.0	DFT-s-OFDM 256 QAM	25@12	20.04	20.69	0.1172
2	15	10	397000	1905.0	DFT-s-OFDM 256 QAM	1@1	20.07	20.72	0.118
2	15	10	397000	1905.0	DFT-s-OFDM 256 QAM	1@50	20.07	20.72	0.118
2	15	10	397000	1905.0	CP-OFDM QPSK	26@13	23.04	23.69	0.2339
2	15	10	397000	1905.0	CP-OFDM QPSK	1@1	22.14	22.79	0.1901
2	15	10	397000	1905.0	CP-OFDM QPSK	1@50	22.72	23.37	0.2173
2	15	15	387500	1857.5	DFT-s-OFDM PI/2 BPSK	36@18	23.18	23.83	0.2415
2	15	15	387500	1857.5	DFT-s-OFDM PI/2 BPSK	1@1	23.41	24.06	0.2547
2	15	15	387500	1857.5	DFT-s-OFDM PI/2 BPSK	1@77	23.31	23.96	0.2489
2	15	15	387500	1857.5	DFT-s-OFDM QPSK	36@18	23.1	23.75	0.2371
2	15	15	387500	1857.5	DFT-s-OFDM QPSK	1@1	23.5	24.15	0.26
2	15	15	387500	1857.5	DFT-s-OFDM QPSK	1@77	23.41	24.06	0.2547

2	15	15	387500	1857.5	DFT-s-OFDM 16 QAM	36@18	23.13	23.78	0.2388
2	15	15	387500	1857.5	DFT-s-OFDM 16 QAM	1@1	23.37	24.02	0.2523
2	15	15	387500	1857.5	DFT-s-OFDM 16 QAM	1@77	23.29	23.94	0.2477
2	15	15	387500	1857.5	DFT-s-OFDM 64 QAM	36@18	22.2	22.85	0.1928
2	15	15	387500	1857.5	DFT-s-OFDM 64 QAM	1@1	22.59	23.24	0.2109
2	15	15	387500	1857.5	DFT-s-OFDM 64 QAM	1@77	22.54	23.19	0.2084
2	15	15	387500	1857.5	DFT-s-OFDM 256 QAM	36@18	20.06	20.71	0.1178
2	15	15	387500	1857.5	DFT-s-OFDM 256 QAM	1@1	19.81	20.46	0.1112
2	15	15	387500	1857.5	DFT-s-OFDM 256 QAM	1@77	19.76	20.41	0.1099
2	15	15	387500	1857.5	CP-OFDM QPSK	39@191	21.65	22.3	0.1698
2	15	15	387500	1857.5	CP-OFDM QPSK	1@1	23.4	24.05	0.2541
2	15	15	387500	1857.5	CP-OFDM QPSK	1@77	23.16	23.81	0.2404
2	15	15	392000	1880.0	DFT-s-OFDM PI/2 BPSK	36@18	23	23.65	0.2317
2	15	15	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@1	23.07	23.72	0.2355
2	15	15	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@77	23.17	23.82	0.241
2	15	15	392000	1880.0	DFT-s-OFDM QPSK	36@18	23.1	23.75	0.2371
2	15	15	392000	1880.0	DFT-s-OFDM QPSK	1@1	22.43	23.08	0.2032
2	15	15	392000	1880.0	DFT-s-OFDM QPSK	1@77	23.16	23.81	0.2404
2	15	15	392000	1880.0	DFT-s-OFDM 16 QAM	36@18	22.66	23.31	0.2143
2	15	15	392000	1880.0	DFT-s-OFDM 16 QAM	1@1	21.59	22.24	0.1675
2	15	15	392000	1880.0	DFT-s-OFDM 16 QAM	1@77	23.09	23.74	0.2366
2	15	15	392000	1880.0	DFT-s-OFDM 64 QAM	36@18	21.46	22.11	0.1626
2	15	15	392000	1880.0	DFT-s-OFDM 64 QAM	1@1	20.54	21.19	0.1315
2	15	15	392000	1880.0	DFT-s-OFDM 64 QAM	1@77	22.31	22.96	0.1977

2	15	15	392000	1880.0	DFT-s-OFDM 256 QAM	36@18	19.96	20.61	0.1151
2	15	15	392000	1880.0	DFT-s-OFDM 256 QAM	1@1	19.27	19.92	0.0982
2	15	15	392000	1880.0	DFT-s-OFDM 256 QAM	1@77	19.84	20.49	0.1119
2	15	15	392000	1880.0	CP-OFDM QPSK	39@191	20.95	21.6	0.1445
2	15	15	392000	1880.0	CP-OFDM QPSK	1@1	21.36	22.01	0.1589
2	15	15	392000	1880.0	CP-OFDM QPSK	1@77	23.07	23.72	0.2355
2	15	15	396500	1902.5	DFT-s-OFDM PI/2 BPSK	36@18	23.07	23.72	0.2355
2	15	15	396500	1902.5	DFT-s-OFDM PI/2 BPSK	1@1	23.12	23.77	0.2382
2	15	15	396500	1902.5	DFT-s-OFDM PI/2 BPSK	1@77	23.15	23.8	0.2399
2	15	15	396500	1902.5	DFT-s-OFDM QPSK	36@18	23.22	23.87	0.2438
2	15	15	396500	1902.5	DFT-s-OFDM QPSK	1@1	23.15	23.8	0.2399
2	15	15	396500	1902.5	DFT-s-OFDM QPSK	1@77	23.18	23.83	0.2415
2	15	15	396500	1902.5	DFT-s-OFDM 16 QAM	36@18	22.74	23.39	0.2183
2	15	15	396500	1902.5	DFT-s-OFDM 16 QAM	1@1	22.52	23.17	0.2075
2	15	15	396500	1902.5	DFT-s-OFDM 16 QAM	1@77	22.88	23.53	0.2254
2	15	15	396500	1902.5	DFT-s-OFDM 64 QAM	36@18	21.51	22.16	0.1644
2	15	15	396500	1902.5	DFT-s-OFDM 64 QAM	1@1	21.49	22.14	0.1637
2	15	15	396500	1902.5	DFT-s-OFDM 64 QAM	1@77	21.9	22.55	0.1799
2	15	15	396500	1902.5	DFT-s-OFDM 256 QAM	36@18	20.11	20.76	0.1191
2	15	15	396500	1902.5	DFT-s-OFDM 256 QAM	1@1	19.88	20.53	0.113
2	15	15	396500	1902.5	DFT-s-OFDM 256 QAM	1@77	19.86	20.51	0.1125
2	15	15	396500	1902.5	CP-OFDM QPSK	39@191	21.36	22.01	0.1589
2	15	15	396500	1902.5	CP-OFDM QPSK	1@1	22.28	22.93	0.1963
2	15	15	396500	1902.5	CP-OFDM QPSK	1@77	22.43	23.08	0.2032

2	15	20	388000	1860.0	DFT-s-OFDM PI/2 BPSK	50@25	23.18	23.83	0.2415
2	15	20	388000	1860.0	DFT-s-OFDM PI/2 BPSK	1@1	23.07	23.72	0.2355
2	15	20	388000	1860.0	DFT-s-OFDM PI/2 BPSK	1@104	23.05	23.7	0.2344
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	50@25	23.1	23.75	0.2371
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@1	23.15	23.8	0.2399
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@104	22.78	23.43	0.2203
2	15	20	388000	1860.0	DFT-s-OFDM 16 QAM	50@25	23.16	23.81	0.2404
2	15	20	388000	1860.0	DFT-s-OFDM 16 QAM	1@1	23.02	23.67	0.2328
2	15	20	388000	1860.0	DFT-s-OFDM 16 QAM	1@104	21.96	22.61	0.1824
2	15	20	388000	1860.0	DFT-s-OFDM 64 QAM	50@25	22.21	22.86	0.1932
2	15	20	388000	1860.0	DFT-s-OFDM 64 QAM	1@1	22.32	22.97	0.1982
2	15	20	388000	1860.0	DFT-s-OFDM 64 QAM	1@104	20.91	21.56	0.1432
2	15	20	388000	1860.0	DFT-s-OFDM 256 QAM	50@25	20.06	20.71	0.1178
2	15	20	388000	1860.0	DFT-s-OFDM 256 QAM	1@1	20.16	20.81	0.1205
2	15	20	388000	1860.0	DFT-s-OFDM 256 QAM	1@104	19.57	20.22	0.1052
2	15	20	388000	1860.0	CP-OFDM QPSK	53@26	23.07	23.72	0.2355
2	15	20	388000	1860.0	CP-OFDM QPSK	1@1	23.12	23.77	0.2382
2	15	20	388000	1860.0	CP-OFDM QPSK	1@104	21.62	22.27	0.1687
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	50@25	23.09	23.74	0.2366
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@1	23.08	23.73	0.236
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@104	23.1	23.75	0.2371
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	50@25	23.14	23.79	0.2393
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	1@1	22.49	23.14	0.2061
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	1@104	23.14	23.79	0.2393

2	15	20	392000	1880.0	DFT-s-OFDM 16 QAM	50@25	22.69	23.34	0.2158
2	15	20	392000	1880.0	DFT-s-OFDM 16 QAM	1@1	21.64	22.29	0.1694
2	15	20	392000	1880.0	DFT-s-OFDM 16 QAM	1@104	23.01	23.66	0.2323
2	15	20	392000	1880.0	DFT-s-OFDM 64 QAM	50@25	21.48	22.13	0.1633
2	15	20	392000	1880.0	DFT-s-OFDM 64 QAM	1@1	20.63	21.28	0.1343
2	15	20	392000	1880.0	DFT-s-OFDM 64 QAM	1@104	22.28	22.93	0.1963
2	15	20	392000	1880.0	DFT-s-OFDM 256 QAM	50@25	20.06	20.71	0.1178
2	15	20	392000	1880.0	DFT-s-OFDM 256 QAM	1@1	19.3	19.95	0.0989
2	15	20	392000	1880.0	DFT-s-OFDM 256 QAM	1@104	20.2	20.85	0.1216
2	15	20	392000	1880.0	CP-OFDM QPSK	53@26	22.45	23.1	0.2042
2	15	20	392000	1880.0	CP-OFDM QPSK	1@1	21.41	22.06	0.1607
2	15	20	392000	1880.0	CP-OFDM QPSK	1@104	23.09	23.74	0.2366
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	50@25	23.68	24.33	0.271
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	1@1	23.14	23.79	0.2393
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	1@104	23.09	23.74	0.2366
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	50@25	23.11	23.76	0.2377
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@1	23.03	23.68	0.2333
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@104	23.04	23.69	0.2339
2	15	20	396000	1900.0	DFT-s-OFDM 16 QAM	50@25	22.57	23.22	0.2099
2	15	20	396000	1900.0	DFT-s-OFDM 16 QAM	1@1	22.97	23.62	0.2301
2	15	20	396000	1900.0	DFT-s-OFDM 16 QAM	1@104	22.92	23.57	0.2275
2	15	20	396000	1900.0	DFT-s-OFDM 64 QAM	50@25	21.4	22.05	0.1603
2	15	20	396000	1900.0	DFT-s-OFDM 64 QAM	1@1	22.25	22.9	0.195
2	15	20	396000	1900.0	DFT-s-OFDM 64 QAM	1@104	21.96	22.61	0.1824

2	15	20	396000	1900.0	DFT-s-OFDM 256 QAM	50@25	20.12	20.77	0.1194
2	15	20	396000	1900.0	DFT-s-OFDM 256 QAM	1@1	20.18	20.83	0.1211
2	15	20	396000	1900.0	DFT-s-OFDM 256 QAM	1@104	20.07	20.72	0.118
2	15	20	396000	1900.0	CP-OFDM QPSK	53@26	22.34	22.99	0.1991
2	15	20	396000	1900.0	CP-OFDM QPSK	1@1	23.07	23.72	0.2355
2	15	20	396000	1900.0	CP-OFDM QPSK	1@104	22.63	23.28	0.2128

Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00351	PASS	NV
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00535	PASS	LV
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00494	PASS	HV
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00566	PASS	-30°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00696	PASS	-20°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00464	PASS	-10°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00607	PASS	0°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00457	PASS	10°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00357	PASS	20°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00413	PASS	30°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.00369	PASS	40°C
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	-0.0066	PASS	50°C

Peak to Average Ratio

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
2	15	20	388000	1860.0	DFT-s-OFDM PI/2 BPSK	100@0	4.06	13	PASS
2	15	20	388000	1860.0	DFT-s-OFDM PI/2 BPSK	1@0	3.42	13	PASS
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	100@0	4.8	13	PASS
2	15	20	388000	1860.0	DFT-s-OFDM QPSK	1@0	4.84	13	PASS
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	100@0	4.4	13	PASS
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	1@0	3.16	13	PASS
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	4.94	13	PASS
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	1@0	4.8	13	PASS
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	100@0	4.2	13	PASS
2	15	20	396000	1900.0	DFT-s-OFDM PI/2 BPSK	1@0	3.49	13	PASS
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	100@0	5.05	13	PASS
2	15	20	396000	1900.0	DFT-s-OFDM QPSK	1@0	5.1	13	PASS


B5_N2(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_Low_CH




B5_N2(20M)_DFT-s-OFDM_PI_2-BPSK_Edge_1RB_Left_Low_CH



B5_N2(20M)_DFT-s-OFDM_QPSK_Outer_Full_Low_CH



B5_N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Low_CH



B5_N2(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_Mid_CH



B5_N2(20M)_DFT-s-OFDM_PI_2-BPSK_Edge_1RB_Left_Mid_CH



B5_N2(20M)_DFT-s-OFDM_QPSK_Outer_Full_Mid_CH




B5_N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



B5_N2(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_High_CH



B5_N2(20M)_DFT-s-OFDM_PI_2-BPSK_Edge_1RB_Left_High_CH



B5_N2(20M)_DFT-s-OFDM_QPSK_Outer_Full_High_CH



B5_N2(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH



Occupied Bandwidth

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB OBW (MHz)
2	15	5	392000	1880.0	DFT-s-OFDM PI/2 BPSK	25@0	4.4646	4.827
2	15	5	392000	1880.0	DFT-s-OFDM QPSK	25@0	4.4733	4.848
2	15	5	392000	1880.0	CP-OFDM QPSK	25@0	4.4762	4.944
2	15	5	392000	1880.0	CP-OFDM 16 QAM	25@0	4.4909	4.926
2	15	5	392000	1880.0	CP-OFDM 64 QAM	25@0	4.4887	4.983
2	15	5	392000	1880.0	CP-OFDM 256 QAM	25@0	4.4707	4.922
2	15	10	392000	1880.0	DFT-s-OFDM PI/2 BPSK	50@0	8.8961	9.468
2	15	10	392000	1880.0	DFT-s-OFDM QPSK	50@0	8.9195	9.545
2	15	10	392000	1880.0	CP-OFDM QPSK	52@0	9.2931	9.959
2	15	10	392000	1880.0	CP-OFDM 16 QAM	52@0	9.2787	9.892
2	15	10	392000	1880.0	CP-OFDM 64 QAM	52@0	9.284	9.884
2	15	10	392000	1880.0	CP-OFDM 256 QAM	52@0	9.2979	9.864
2	15	15	392000	1880.0	DFT-s-OFDM PI/2 BPSK	75@0	13.404	14.05
2	15	15	392000	1880.0	DFT-s-OFDM QPSK	75@0	13.394	14.15
2	15	15	392000	1880.0	CP-OFDM QPSK	79@0	14.099	14.8
2	15	15	392000	1880.0	CP-OFDM 16 QAM	79@0	14.105	14.84
2	15	15	392000	1880.0	CP-OFDM 64 QAM	79@0	14.121	14.78
2	15	15	392000	1880.0	CP-OFDM 256 QAM	79@0	14.078	14.86
2	15	20	392000	1880.0	DFT-s-OFDM PI/2 BPSK	100@0	17.876	18.73
2	15	20	392000	1880.0	DFT-s-OFDM QPSK	100@0	17.876	18.72
2	15	20	392000	1880.0	CP-OFDM QPSK	106@0	18.917	20.78
2	15	20	392000	1880.0	CP-OFDM 16 QAM	106@0	18.953	20.27
2	15	20	392000	1880.0	CP-OFDM 64 QAM	106@0	18.918	21.48
2	15	20	392000	1880.0	CP-OFDM 256 QAM	106@0	18.983	19.82