



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2139-1, XT2139-2
FCC ID : IHDT56ZU1
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : May 27, 2021 ~ Jun. 21, 2021

We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager



Sporton International (Kunshan) Inc.

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test 5

 1.4 Product Specification of Equipment Under Test 6

 1.5 Modification of EUT 7

 1.6 Specification of Accessory 7

 1.7 Maximum ERP/EIRP Power, and Emission Designator 8

 1.8 Testing Location 8

 1.9 Test Software 9

 1.10 Applicable Standards 9

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 10

 2.1 Test Mode..... 10

 2.2 Connection Diagram of Test System 11

 2.3 Support Unit used in test configuration 11

 2.4 Measurement Results Explanation Example 11

 2.5 Frequency List of Low/Middle/High Channels..... 12

3 CONDUCTED TEST RESULT..... 13

 3.1 Measuring Instruments..... 13

 3.2 Test Setup 13

 3.3 Test Result of Conducted Test..... 13

 3.4 Conducted Output Power and ERP/EIRP 14

 3.5 Peak-to-Average Ratio 15

 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 16

 3.7 Conducted Band Edge 17

 3.8 Conducted Spurious Emission 18

 3.9 Frequency Stability..... 19

4 RADIATED TEST ITEMS 20

 4.1 Measuring Instruments..... 20

 4.2 Test Setup 20

 4.3 Test Result of Radiated Test..... 21

 4.4 Field Strength of Spurious Radiation Measurement 22

5 LIST OF MEASURING EQUIPMENT 23

6 UNCERTAINTY OF EVALUATION 24

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG152401A	Rev. 01	Initial issue of report	Jul. 01, 2021



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 29.47 dB at 9396.000 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2139-1, XT2139-2
FCC ID	IHDT56ZU1
EUT supports Radios application	GSM/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE FM Receiver, NFC and GNSS
IMEI Code	Conducted: 351214780015915/351214780015901 Radiation: 868253050047485/868253050047493
HW Version	DVT2
SW Version	RRK31.Q3-3
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz WCDMA: Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz WCDMA: Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz
Maximum Output Power to Antenna	Ant 0: GSM/GPRS/EDGE: 850: 31.97 dBm 1900: 29.22 dBm WCDMA: Band V: 23.27 dBm Band IV: 22.99 dBm Ant 4: GSM/GPRS/EDGE: 850: 31.88 dBm WCDMA: Band II: 23.13 dBm Band V: 23.01 dBm
Antenna Type	PIFA Antenna
Antenna Gain	Cellular Band: -3.5 dBi PCS Band: 0.2 dBi AWS Band: -1.4 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM

Note: The maximum EIRP is calculated from max Output power and max antenna gain, only the maximum EIRP is shown in the report.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(Salom)	Model Name	MC-301
AC Adapter 1(EU)	Brand Name	Motorola(Salom)	Model Name	MC-302
AC Adapter 1(UK)	Brand Name	Motorola(Salom)	Model Name	MC-303
AC Adapter 1(AU)	Brand Name	Motorola(Salom)	Model Name	MC-305
AC Adapter 1(AR)	Brand Name	Motorola(Salom)	Model Name	MC-306
AC Adapter 1(BR)	Brand Name	Motorola(Salom)	Model Name	MC-307
AC Adapter 2(US)	Brand Name	Motorola(Acbel)	Model Name	MC-301
AC Adapter 2(EU)	Brand Name	Motorola(Acbel)	Model Name	MC-302
AC Adapter 2(UK)	Brand Name	Motorola(Acbel)	Model Name	MC-303
AC Adapter 2(IN)	Brand Name	Motorola(Acbel)	Model Name	MC-304
AC Adapter 2(AU)	Brand Name	Motorola(Acbel)	Model Name	MC-305
AC Adapter 2(AR)	Brand Name	Motorola(Acbel)	Model Name	MC-306
AC Adapter 2(CHILE)	Brand Name	Motorola(Acbel)	Model Name	MC-309
AC Adapter 3(BR)	Brand Name	Motorola(Flex)	Model Name	MC-307
Battery	Brand Name	Motorola(ATL)	Model Name	NT50
Earphone 1	Brand Name	Motorola(Lyand)	Model Name	MH191(SH38C81577)
Earphone 2	Brand Name	Motorola(LCHSE)	Model Name	MH191(SH38C81576)
Earphone 3	Brand Name	Motorola(NEW LEADER)	Model Name	MH202(S928D09678)
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D13215
USB Cable 2	Brand Name	Motorola(Cabletech)	Model Name	SC18D13216
USB Cable 3	Brand Name	Motorola(Luxshare)	Model Name	SC18D13217



1.7 Maximum ERP/EIRP Power, and Emission Designator

For Ant.0:

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 22	GSM850 (GSM)	824.2 ~ 848.8	GMSK	0.4285	240KGXW
Part 22	GSM850 (EDGE)	824.2 ~ 848.8	8PSK	0.0962	240KG7W
Part 22	WCDMA Band V	826.4 ~ 846.6	BPSK	0.0578	4M16F9W
Part 24	GSM1900 (GSM)	1850.2 ~ 1909.8	GMSK	0.8750	240KGXW
Part 24	GSM1900 (EDGE)	1850.2 ~ 1909.8	8PSK	0.3319	240KG7W
Part 27	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.1442	4M14F9W

For Ant.4:

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 24	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.2153	4M15F9W

1.8 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309



1.9 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.10 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band IV	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

The following shows an offset computation example with RF cable loss 5.4 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 5.4 + 10 = 15.4 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 01, 2020	May 27, 2021	Oct. 31, 2021	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	Aug. 27, 2020	May 27, 2021	Aug. 26, 2021	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 03, 2020	May 27, 2021	Jul. 02, 2021	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 13, 2021	Jun. 21, 2021	Apr. 12, 2022	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 1, 2020	Jun. 21, 2021	Oct. 31, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	May. 30, 2021	Jun. 21, 2021	May. 29, 2022	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 01, 2020	Jun. 21, 2021	Oct. 31, 2021	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Jan. 06, 2021	Jun. 21, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 06, 2021	Jun. 21, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 07, 2021	Jun. 21, 2021	Jan. 06, 2022	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Jan. 06, 2021	Jun. 21, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 14, 2020	Jun. 21, 2021	Oct. 13, 2021	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jun. 21, 2021	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jun. 21, 2021	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jun. 21, 2021	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.3dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8dB
---	-------

----- THE END -----



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)and ERP/EIRP

For Ant.0:

GSM850	Burst Average Power (dBm)			ERP(W)		
	TX Channel	128	189			
Frequency (MHz)	824.2	836.4	848.8	L	M	H
GSM 1 Tx slot	31.89	31.91	31.97	0.4207	0.4227	0.4285
GPRS 1 Tx slot	31.85	31.90	31.96	0.4169	0.4217	0.4276
GPRS 2 Tx slots	30.83	31.04	30.98	0.3296	0.3459	0.3412
GPRS 3 Tx slots	29.03	29.20	29.13	0.2178	0.2265	0.2228
GPRS 4 Tx slots	27.82	27.94	27.85	0.1648	0.1694	0.1660
EDGE 1 Tx slot	25.48	25.38	25.44	0.0962	0.0940	0.0953
EDGE 2 Tx slots	24.01	24.03	23.93	0.0685	0.0689	0.0673
EDGE 3 Tx slots	21.83	21.51	21.55	0.0415	0.0385	0.0389
EDGE 4 Tx slots	20.22	20.21	20.21	0.0286	0.0286	0.0286

GSM1900	Burst Average Power (dBm)			EIRP(W)		
	TX Channel	512	661			
Frequency (MHz)	1850.2	1880	1909.8	L	M	H
GSM 1 Tx slot	29.22	29.03	29.01	0.8750	0.8375	0.8337
GPRS 1 Tx slot	29.17	29.02	28.99	0.8650	0.8356	0.8299
GPRS 2 Tx slots	28.37	28.23	28.22	0.7194	0.6966	0.6950
GPRS 3 Tx slots	26.58	26.47	26.45	0.4764	0.4645	0.4624
GPRS 4 Tx slots	25.61	25.35	25.36	0.3811	0.3589	0.3597
EDGE 1 Tx slot	24.97	25.01	24.78	0.3289	0.3319	0.3148
EDGE 2 Tx slots	23.65	23.76	23.47	0.2427	0.2489	0.2328
EDGE 3 Tx slots	21.31	21.37	21.05	0.1416	0.1435	0.1334
EDGE 4 Tx slots	20.12	19.93	19.70	0.1076	0.1030	0.0977



Band		WCDMA V			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458			
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.20	23.26	23.11	0.0569	0.0577	0.0557
3GPP Rel 99	RMC 12.2Kbps	23.26	23.27	23.14	0.0577	0.0578	0.0561
3GPP Rel 6	HSDPA Subtest-1	22.70	22.66	22.69	0.0507	0.0502	0.0506
3GPP Rel 6	HSDPA Subtest-2	22.64	22.65	22.66	0.0500	0.0501	0.0502
3GPP Rel 6	HSDPA Subtest-3	22.20	22.16	22.19	0.0452	0.0448	0.0451
3GPP Rel 6	HSDPA Subtest-4	22.17	22.18	22.21	0.0449	0.0450	0.0453
3GPP Rel 8	DC-HSDPA Subtest-1	22.67	22.63	22.66	0.0504	0.0499	0.0502
3GPP Rel 8	DC-HSDPA Subtest-2	22.61	22.62	22.63	0.0497	0.0498	0.0499
3GPP Rel 8	DC-HSDPA Subtest-3	22.17	22.13	22.16	0.0449	0.0445	0.0448
3GPP Rel 8	DC-HSDPA Subtest-4	22.14	22.15	22.18	0.0446	0.0447	0.0450
3GPP Rel 6	HSUPA Subtest-1	20.64	20.59	20.62	0.0316	0.0312	0.0314
3GPP Rel 6	HSUPA Subtest-2	20.62	20.62	20.60	0.0314	0.0314	0.0313
3GPP Rel 6	HSUPA Subtest-3	21.69	21.66	21.64	0.0402	0.0399	0.0397
3GPP Rel 6	HSUPA Subtest-4	20.37	20.31	20.35	0.0296	0.0292	0.0295
3GPP Rel 6	HSUPA Subtest-5	21.64	21.64	21.67	0.0397	0.0397	0.0400
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	19.56	19.46	19.33	0.0246	0.0240	0.0233



Band		WCDMA IV			EIRP(W)		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	22.73	22.95	22.90	0.1358	0.1429	0.1413
3GPP Rel 99	RMC 12.2Kbps	22.75	22.99	22.97	0.1365	0.1442	0.1435
3GPP Rel 6	HSDPA Subtest-1	22.06	21.98	22.04	0.1164	0.1143	0.1159
3GPP Rel 6	HSDPA Subtest-2	22.05	21.96	21.99	0.1161	0.1138	0.1146
3GPP Rel 6	HSDPA Subtest-3	21.61	21.52	21.54	0.1050	0.1028	0.1033
3GPP Rel 6	HSDPA Subtest-4	21.54	21.44	21.50	0.1033	0.1009	0.1023
3GPP Rel 8	DC-HSDPA Subtest-1	22.03	21.96	22.01	0.1156	0.1138	0.1151
3GPP Rel 8	DC-HSDPA Subtest-2	22.02	21.94	21.96	0.1153	0.1132	0.1138
3GPP Rel 8	DC-HSDPA Subtest-3	21.58	21.50	21.51	0.1042	0.1023	0.1026
3GPP Rel 8	DC-HSDPA Subtest-4	21.51	21.42	21.47	0.1026	0.1005	0.1016
3GPP Rel 6	HSUPA Subtest-1	20.17	20.14	20.18	0.0753	0.0748	0.0755
3GPP Rel 6	HSUPA Subtest-2	20.20	20.09	20.18	0.0759	0.0740	0.0755
3GPP Rel 6	HSUPA Subtest-3	21.24	21.14	21.02	0.0964	0.0942	0.0916
3GPP Rel 6	HSUPA Subtest-4	19.78	19.65	19.71	0.0689	0.0668	0.0678
3GPP Rel 6	HSUPA Subtest-5	22.03	22.15	22.23	0.1156	0.1189	0.1211
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	19.23	19.28	19.37	0.0607	0.0614	0.0627



For Ant. 4

GSM850	Burst Average Power (dBm)			ERP(W)		
	TX Channel	128	189			
Frequency (MHz)	824.2	836.4	848.8	L	M	H
GSM 1 Tx slot	31.78	31.88	31.70	0.4102	0.4198	0.4027
GPRS 1 Tx slot	31.76	31.84	31.68	0.4083	0.4159	0.4009
GPRS 2 Tx slots	30.71	30.86	30.77	0.3206	0.3319	0.3251
GPRS 3 Tx slots	28.85	29.01	28.89	0.2089	0.2168	0.2109
GPRS 4 Tx slots	27.61	27.83	27.63	0.1570	0.1652	0.1578
EDGE 1 Tx slot	25.23	25.32	25.38	0.0908	0.0927	0.0940
EDGE 2 Tx slots	23.89	23.82	23.88	0.0667	0.0656	0.0665
EDGE 3 Tx slots	21.61	21.57	21.44	0.0394	0.0391	0.0379
EDGE 4 Tx slots	20.03	20.12	20.04	0.0274	0.0280	0.0275

Band		WCDMA V			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458	L	M	H
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	22.84	22.99	22.71	0.0524	0.0542	0.0508
3GPP Rel 99	RMC 12.2Kbps	22.89	23.01	22.79	0.0530	0.0545	0.0518
3GPP Rel 6	HSDPA Subtest-1	22.03	22.05	22.07	0.0435	0.0437	0.0439
3GPP Rel 6	HSDPA Subtest-2	22.02	22.04	22.09	0.0434	0.0436	0.0441
3GPP Rel 6	HSDPA Subtest-3	21.51	21.56	21.58	0.0385	0.0390	0.0392
3GPP Rel 6	HSDPA Subtest-4	21.50	21.52	21.54	0.0385	0.0386	0.0388
3GPP Rel 8	DC-HSDPA Subtest-1	22.00	22.02	22.04	0.0432	0.0434	0.0436
3GPP Rel 8	DC-HSDPA Subtest-2	21.99	22.01	22.06	0.0431	0.0433	0.0438
3GPP Rel 8	DC-HSDPA Subtest-3	21.48	21.53	21.55	0.0383	0.0387	0.0389
3GPP Rel 8	DC-HSDPA Subtest-4	21.47	21.49	21.51	0.0382	0.0384	0.0385
3GPP Rel 6	HSUPA Subtest-1	20.04	20.00	20.02	0.0275	0.0272	0.0274
3GPP Rel 6	HSUPA Subtest-2	20.07	20.00	20.00	0.0277	0.0272	0.0272
3GPP Rel 6	HSUPA Subtest-3	21.09	21.06	21.06	0.0350	0.0348	0.0348
3GPP Rel 6	HSUPA Subtest-4	19.83	19.72	19.53	0.0262	0.0255	0.0244
3GPP Rel 6	HSUPA Subtest-5	21.13	21.03	21.03	0.0353	0.0345	0.0345
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	19.21	19.20	19.46	0.0227	0.0226	0.0240



Band		WCDMA II			EIRP(W)		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938			
Frequency (MHz)		1852.4	1880	1907.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.10	23.01	22.87	0.2138	0.2094	0.2028
3GPP Rel 99	RMC 12.2Kbps	23.13	23.03	22.97	0.2153	0.2104	0.2075
3GPP Rel 6	HSDPA Subtest-1	22.60	22.57	22.51	0.1905	0.1892	0.1866
3GPP Rel 6	HSDPA Subtest-2	22.56	22.56	22.56	0.1888	0.1888	0.1888
3GPP Rel 6	HSDPA Subtest-3	22.10	22.09	22.06	0.1698	0.1694	0.1683
3GPP Rel 6	HSDPA Subtest-4	22.07	22.08	22.05	0.1687	0.1690	0.1679
3GPP Rel 8	DC-HSDPA Subtest-1	22.57	22.55	22.48	0.1892	0.1884	0.1854
3GPP Rel 8	DC-HSDPA Subtest-2	22.53	22.54	22.53	0.1875	0.1879	0.1875
3GPP Rel 8	DC-HSDPA Subtest-3	22.07	22.07	22.03	0.1687	0.1687	0.1671
3GPP Rel 8	DC-HSDPA Subtest-4	22.04	22.06	22.02	0.1675	0.1683	0.1667
3GPP Rel 6	HSUPA Subtest-1	20.54	20.53	20.49	0.1186	0.1183	0.1172
3GPP Rel 6	HSUPA Subtest-2	20.56	20.57	20.51	0.1191	0.1194	0.1178
3GPP Rel 6	HSUPA Subtest-3	21.60	21.57	21.56	0.1514	0.1503	0.1500
3GPP Rel 6	HSUPA Subtest-4	20.10	20.03	20.09	0.1072	0.1054	0.1069
3GPP Rel 6	HSUPA Subtest-5	21.52	21.52	21.52	0.1486	0.1486	0.1486
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	19.00	19.34	19.22	0.0832	0.0899	0.0875





A1. GSM

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	3.10	PASS
Middle CH	0.12	3.19	
Highest CH	0.20	3.07	

Mode	GSM1900		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	3.45	PASS
Middle CH	0.12	3.54	
Highest CH	0.12	3.39	







26dB Bandwidth


Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.31	0.28
Middle CH	0.32	0.28
Highest CH	0.32	0.29

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.31	0.29
Middle CH	0.31	0.29
Highest CH	0.31	0.29



GSM850 (GSM)

Lowest Channel



Date: 27 MAY 2021 14:51:44


GSM850 (EDGE class 8)

Lowest Channel




Date: 27 MAY 2021 15:21:29

Middle Channel




Date: 27 MAY 2021 14:51:59

Middle Channel




Date: 27 MAY 2021 15:21:45

Highest Channel



Date: 27 MAY 2021 14:52:15

Highest Channel




Date: 27 MAY 2021 15:22:01



GSM1900 (GSM)


Lowest Channel



Date: 27 MAY 2021 16:03:39


GSM1900 (EDGE class 8)

Lowest Channel




Date: 27 MAY 2021 16:34:06

Middle Channel




Date: 27 MAY 2021 16:03:55

Middle Channel




Date: 27 MAY 2021 16:34:22

Highest Channel



Date: 27 MAY 2021 16:04:11

Highest Channel



Date: 27 MAY 2021 16:34:38



Occupied Bandwidth


Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.24	0.24
Middle CH	0.24	0.23
Highest CH	0.24	0.24

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.24	0.24
Middle CH	0.24	0.23
Highest CH	0.24	0.23



GSM850 (GSM)


Lowest Channel



Date: 27 MAY 2021 14:52:32


GSM850 (EDGE class 8)

Lowest Channel




Date: 27 MAY 2021 15:22:18

Middle Channel




Date: 27 MAY 2021 14:52:48

Middle Channel




Date: 27 MAY 2021 15:22:35

Highest Channel



Date: 27 MAY 2021 14:53:04

Highest Channel




Date: 27 MAY 2021 15:22:51



GSM1900 (GSM)


Lowest Channel



Date: 27 MAY 2021 16:04:27


GSM1900 (EDGE class 8)

Lowest Channel




Date: 27 MAY 2021 16:34:55

Middle Channel




Date: 27 MAY 2021 16:04:43

Middle Channel




Date: 27 MAY 2021 16:35:11

Highest Channel



Date: 27 MAY 2021 16:04:59



Highest Channel




Date: 27 MAY 2021 16:35:28




Conducted Band Edge








Conducted Spurious Emission





GSM1900 (GSM)


Lowest Channel



Date: 27 MAY 2021 16:09:13


GSM1900 (EDGE class 8)

Lowest Channel




Date: 27 MAY 2021 16:39:43

Middle Channel




Date: 27 MAY 2021 16:10:38

Middle Channel




Date: 27 MAY 2021 16:41:08

Highest Channel



Date: 27 MAY 2021 16:12:03

Highest Channel



Date: 27 MAY 2021 16:42:34



Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0107	0.0271	PASS
40	Normal Voltage	0.0030	0.0126	
30	Normal Voltage	0.0170	0.0087	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0145	0.0155	
0	Normal Voltage	0.0045	0.0169	
-10	Normal Voltage	0.0120	0.0234	
-20	Normal Voltage	0.0159	0.0065	
-30	Normal Voltage	0.0143	0.0109	
20	Maximum Voltage	0.0096	0.0132	
20	Normal Voltage	0.0120	0.0203	
20	Battery End Point	0.0191	0.0042	



Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0043	0.0176	PASS
40	Normal Voltage	0.0015	0.0131	
30	Normal Voltage	0.0119	0.0023	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0138	0.0112	
0	Normal Voltage	0.0136	0.0135	
-10	Normal Voltage	0.0089	0.0174	
-20	Normal Voltage	0.0021	0.0127	
-30	Normal Voltage	0.0118	0.0119	
20	Maximum Voltage	0.0052	0.0018	
20	Normal Voltage	0.0011	0.0134	
20	Battery End Point	0.0119	0.0022	

Note:

1. Normal Voltage = 3.87V. ; Battery End Point (BEP) =3.6V. ; Maximum Voltage =4.45V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



A2. WCDMA


Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.93	2.84	2.87	PASS
Middle CH	3.13	3.10	2.90	
Highest CH	3.16	3.25	2.75	



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 27 MAY 2021 12:23:34


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 27 MAY 2021 12:33:55

Middle Channel



Date: 27 MAY 2021 12:23:40

Middle Channel



Date: 27 MAY 2021 12:34:01

Highest Channel




Date: 27 MAY 2021 12:23:46

Highest Channel



Date: 27 MAY 2021 12:34:07





26dB Bandwidth

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.71	4.70	4.70
Middle CH	4.70	4.70	4.70
Highest CH	4.70	4.68	4.71