



Exhibit 11: SAR Test Report IHDT5DY1

Date of test: 29 – 31 Oct, 2003
Date of Report: 26 Nov, 2003

Laboratory: Motorola Personal Communications Sector Product Safety & Compliance Laboratory
 600 N. US Highway 45
 Room: MW113
 Libertyville, Illinois 60048

Test Responsible: Steven Hauswirth
 Principal Staff Engineer

Accreditation: This laboratory is accredited to ISO/IEC 17025-1999 to perform the following tests:



<p><u>Tests:</u> Electromagnetic Specific Absorption Rate</p> <p>Simulated Tissue Preparation RF Power Measurement</p>	<p><u>Procedures:</u> ANSI/IEEE C95.1-1992, 1999 (SAR) IEEE C95.3-1991 IEEE P1528 (<i>DRAFT</i>) FCC OET Bulletin 65 (<i>including Supplements A, B, C</i>) Australian Communications Authority Radio Communications (Electromagnetic Radiation – Human Exposure) Standard 1999 CENELEC EN 50361 (2001) APP-0247 DOI-0876, 0900, 0902, 0904, 0915</p>
--	---

On the following products or types of products:
 Wireless Communications Devices (Examples): Two Way Radios; Portable Phones (including Cellular, Licensed Non-Broadcast and PCS); Low Frequency Readers; and Pagers

A2LA certificate #1651-01

Statement of Compliance: Motorola declares under its sole responsibility that portable cellular telephone FCC ID IHDT5DY1 to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines (FCC 47 CFR §2.1093). It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below:

(none)

©Motorola, Inc. 2003

This test report shall not be reproduced except in full, without written approval of the laboratory.

The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report.

Motorola encourages all feedback, both positive and negative, on this test report.

Table of Contents

1. INTRODUCTION..... 3

2. DESCRIPTION OF THE DEVICE UNDER TEST 3

2.1 Antenna description.....3

2.2 Device description.....3

3. TEST EQUIPMENT USED..... 3

3.1 Dosimetric System3

3.2 Additional Equipment.....4

3.2 Additional Equipment.....4

4. ELECTRICAL PARAMETERS OF THE TISSUE SIMULATING LIQUID 4

5. SYSTEM ACCURACY VERIFICATION..... 4

6. TEST RESULTS 5

6.1 Head Adjacent Test Results.....6

6.2 Body Worn Test Results7

APPENDIX 1: SAR DISTRIBUTION COMPARISON FOR SYSTEM ACCURACY VERIFICATION 9

APPENDIX 2: SAR DISTRIBUTION PLOTS FOR PHANTOM HEAD ADJACENT USE 10

APPENDIX 3: SAR DISTRIBUTION PLOTS FOR BODY WORN CONFIGURATION..... 13

APPENDIX 4: PROBE CALIBRATION CERTIFICATE 15

APPENDIX 5: DIPOLE CHARACTERIZATION CERTIFICATE..... 16

APPENDIX 6: MEASUREMENT UNCERTAINTY BUDGET..... 17

APPENDIX 7: PHOTOGRAPHS OF DEVICE UNDER TEST20

1. Introduction

The Motorola Personal Communications Sector Product Safety Laboratory has performed measurements of the maximum potential exposure to the user of portable cellular phone (FCC ID IHDT5DY1). The Specific Absorption Rate (SAR) of this product was measured. The portable cellular phone was tested in accordance with FCC OET Bulletin 65 Supplement C 01-01.

2. Description of the Device Under Test

a. Antenna description

Type	External	
Location	Upper Right Corner of Phone	
Dimensions	Length	19mm
	Width	9mm
Configuration	Helix	

b. Device description

FCC ID Number	IHDT56DY1	
Serial number	33881DFA	
Mode(s) of Operation	800 AMPS	800 CDMA
Modulation Mode(s)	AMPS	CDMA
Maximum Output Power Setting	27.0dBm	25.2dBm
Duty Cycle	1:1	1:1
Transmitting Frequency Rang(s)	824.04-848.97 MHz	824.70-848.31 MHz
Production Unit or Identical Prototype (47 CFR §2.908)	Identical Prototype	
Device Category	Portable	
RF Exposure Limits	General Population / Uncontrolled	

3. Test Equipment Used

3.1 Dosimetric System

The Motorola Personal Communications Sector Product Safety & Compliance Laboratory utilizes a Dosimetric Assessment System (Dasy3™ v3.1d) manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. All the SAR measurements are taken within a shielded enclosure. The overall RSS uncertainty of the measurement system is ±11.7% (K=1) with an expanded uncertainty of ±23.0% (K=2). The measurement uncertainty budget is given in Appendix 6. Per IEEE 1528, this uncertainty budget is applicable to the SAR range of 0.4 W/kg to 10 W/kg. The list of calibrated equipment used for the measurements is shown below.

Description	Serial Number	Cal Due Date
DASY3 DAE V1	SN386	18-Mar-04
E-Field Probe ET3DV6	SN1514	31-Jul-04
Dipole Validation Kit, D900V2	SN096	24-Jun-04
S.A.M. Phantom used for 800MHz	TP-1131	

3.2 Additional Equipment

Description	Serial Number	Cal Due Date
Signal Generator HP8648C	3847A04822	6-Feb-05
Power Meter E4419B	GB39511087	6-Feb-04
Power Sensor #1 - 8481A	US39210929	6-Feb-04
Power Sensor #2 - 8481A	US39210933	6-Feb-04
Network Analyzer HP8753ES	US39172529	18-Jun-04
Dielectric Probe Kit HP85070B	US33020235	N/A

4. Electrical parameters of the tissue simulating liquid

Prior to conducting SAR measurements, the relative permittivity, ϵ_r , and the conductivity, σ , of the tissue simulating liquids were measured with the HP85070 Dielectric Probe Kit. These values, along with the temperature of the tissue simulate are shown in the table below. The recommended limits for maximum permittivity and minimum conductivity are also shown. These come from the Federal Communication Commission, OET Bulletin 65 Supplement C 01-01. It is seen that the measured parameters are satisfactory for compliance testing.

f (MHz)	Tissue type	Limits / Measured	Dielectric Parameters		
			ϵ_r	σ (S/m)	Temp (°C)
835	Head	Measured, 29-Oct-03	41.3	0.9	19.1
		Measured, 30-Oct-03	41.1	0.89	19.4
		Measured, 31-Oct-03	41.1	0.89	19.6
		Recommended Limits	41.5 ±5%	0.90 ±5%	18-25
	Body	Measured, 31-Oct-03	53.9	0.98	20.1
		Recommended Limits	55.2 ±5%	0.97 ±5%	18-25

The list of ingredients and the percent composition used for the tissue simulates are indicated in the table below.

Ingredient	800MHz Head	800MHz Body	1900MHz Head	1900MHz Body
Sugar	57.0	44.9	--	30.80
DGBE	--	--	47.0	--
Water	40.45	53.06	52.8	68.91
Salt	1.45	0.94	0.2	0.29
HEC	1.0	1.0	--	--
Bact.	0.1	0.1	--	--

5. System Accuracy Verification

A system accuracy verification of the DASY3 was performed using the measurement equipment listed in Section 3.1. The daily system accuracy verification occurs within center section of the SAM phantom.

A SAR measurement was performed to see if the measured SAR was within +/- 10% from the target SAR indicated on the dipole certification sheet. These tests were done at 900MHz and/or 1800MHz. These frequencies are within 100MHz of the mid-band frequency of the test device. This is within the allowable window given in Supplement C 01-01 *Appendix D System Verification* section item #5. The test was conducted on the same days as the

measurement of the DUT. Recommended limits for maximum permittivity, minimum conductivity are shown in the table below. These come from the Federal Communication Commission, OET Bulletin 65 Supplement C 01-01. The obtained results from the system accuracy verification are displayed in the table below. The distributions of SAR compare well with those of the reference measurements (see Appendix 1). The tissue stimulant depth was verified to be 15.0cm ±0.5cm. Z-axis scans showing the SAR penetration are also included in Appendix 1. SAR values are normalized to 1W forward power delivered to the dipole.

f (MHz)	Description	SAR (W/kg) , 1gram	Dielectric Parameters		Ambient Temp (°C)	Tissue Temp (°C)
			ϵ_r	σ (S/m)		
900	Measured, 29-Oct-03	11.1	40.4	0.96	20	19.8
	Measured, 30-Oct-03	11.1	40.3	0.95	20	20.2
	Measured, 31-Oct-03	11.1	40.3	0.95	20	20.4
	Recommended Limits	11.6	41.5 ±5%	0.97 ±5%	18-25	18-25

The following probe conversion factors were used on the E-Field probe(s) used for the system accuracy verification measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN1514	900	6.3	7 of 11
		1800	N/A	N/A

6. Test Results

The test sample was operated in a test mode that allows control of the transmitter without the need to place actual phone calls. For the purposes of this test the unit is commanded to test mode and manually set to the proper channel, transmitter power level and transmit mode of operation. The phone was tested in the configurations stipulated in OET Bulletin 65 Supplement C 01-01. Motorola also followed the requirements in Supplement. C / Appendix D: SAR Measurement Procedures, section titled “*Devices Operating Next To A Person’s Ear* “. These directions state “The device should be tested on the left and right side of the head phantom in the “Cheek/Touch” and “Ear/Tilt” positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tile/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).“

The DASY v3.1d SAR measurement system specified in section 3.1 was utilized within the intended operations as set by the SPEAG™ setup. The phone was positioned into the measurement configurations using the positioner supplied with the DASY 3.1d SAR measurement system. The measured dielectric constant of the material used for the positioner is less than 2.9 and the loss tangent is less than 0.02 (± 30%) at 850MHz. The default settings for the “coarse” and “cube” scans were chosen and use for measurements. The grid spacing of the course scan was set to 15cm as shown in the SAR plots included in appendix 2 and 3. Please refer to the DASY manual for additional information on SAR scanning procedures and algorithms used.


The Cellular Phone (FCC ID IHDT5DY1) has the SNN5691AA as the only available battery option. This battery was used to do all of the SAR testing. The phone was placed in the SAR measurement system with a fully charged battery.

6.1 Head Adjacent Test Results

To aid in positioning repeatability, the ear reference line of the device and the axis reference line of the device have been physically added using a non-metallic marker.

- Per Figure 1, the "Ear Reference Line" is centered vertically through the center of the listening area (as defined by the speaker holes in the housing).
- The "Axis Reference Line" bisects the front surface of the device at its top and bottom edges.
- The intersection of these two lines defines the location of the "Ear Reference Point".

The lines drawn on the device extended to the outside edges, as shown in blue in the figure below, & wrap around the sides of the device.



The SAR results shown in tables 1 and 2 are maximum SAR values averaged over 1 gram of phantom tissue. Also shown are the measured conducted output powers, the temperature of the test facility during the test, the temperature of the tissue simulate after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is $New\ SAR = Old\ SAR * 10^{(-drift/10)}$. The SAR reported at the end of the measurement process by the DASY™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test. The test conditions indicated as bold numbers in the following table are included in Appendix 2

The SAR measurements were performed using the SAM phantoms listed in section 3.1. Since same phantoms and tissue simulate are used for the system accuracy verification as the device SAR measurements, the Z-axis scans included in within Appendix 1 are applicable for verification of tissue simulate depth to be 15.0cm ±0.5cm. All other test conditions measured lower SAR values than those included in Appendix 2. Note that 800MHz digital mode SAR measurements were performed in accordance with Supplement C.

The following probe conversion factors were used on the E-Field probe(s) used for the head adjacent measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN1514	835	6.3	7 of 11
		1900	N/A	N/A

f (MHz)	Description	Conducted Output Power (dBm)	Cheek / Touch Position							
			Left Head				Right Head			
			Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)	Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)
Analog 800MHz	Channel 991	26.94	1.18	0.07	1.18	19.1	1.16	-0.09	1.18	19.4
	Channel 384	27.06	1.14	-0.08	1.16	19.1	1.11	-0.02	1.12	19.4
	Channel 799	27.05	1.02	0.02	1.02	19.1	1.01	-0.16	1.05	19.3
Digital 800MHz	Channel 1013	25.21								
	Channel 384	25.27	0.773	-0.13	0.80	19.4	0.719	0.04	0.72	19.5
	Channel 777	25.16								

Table 1: SAR measurement results for the portable cellular telephone FCC ID IHDT5DY1 at highest possible output power. Measured against the left head in the Cheek/Touch Position.

f (MHz)	Description	Conducted Output Power (dBm)	15° Tilt Position							
			Left Head				Right Head			
			Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)	Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)
Analog 800MHz	Channel 991	26.94	0.943	-0.03	0.95	19.4				
	Channel 384	27.06	0.908	0.07	0.91	19.5	0.772	0.05	0.77	19.4
	Channel 799	27.05	0.818	-0.18	0.85	19.5				
Digital 800MHz	Channel 1013	25.21								
	Channel 384	25.27	0.603	0.07	0.60	19.5	0.55	0.04	0.55	19.6
	Channel 777	25.16								

Table 2: SAR measurement results for the portable cellular telephone FCC ID IHDT5DY1 at highest possible output power. Measured against the left head in the 15° Tilt Position.

6.2 Body Worn Test Results

The SAR results shown in table 3 are the maximum SAR values averaged over 1 gram of phantom tissue. Also shown are the measured conducted output powers, the temperature of the test facility during the test, the temperature of the tissue simulate after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is $New\ SAR = Old\ SAR * 10^{(-drift/10)}$. The SAR reported at the end of the measurement process by the DASY™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test. The test conditions indicated as bold numbers in the following table are included in Appendix 3. Note that 800MHz digital mode SAR measurements were performed in accordance with OET Bulletin 65 Supplement C 01-01. All other test conditions measured lower SAR values than those included in Appendix 3.

A “flat” phantom was for the body-worn tests. This “flat” phantom is made out of 1” thick natural High Density Polyethylene with a thickness at the bottom equal to 2.0mm. It measures 52.7cm(long) x 26.7cm(wide) x 21.2cm(tall). The measured dielectric constant of the material used is less than 2.3 and the loss tangent is less than 0.0046 all the way up to 2.184GHz.

The tissue stimulant depth was verified to be 15.0cm ±0.5cm. The same device holder described in section 6 was used for positioning the phone. There are no Body-Worn Accessories available for this phone at the time of testing hence the device was tested per the supplement C testing guidelines for devices that do not have body worn accessories. The phone was placed 15mm away from a flat phantom per the supplement C standard guidelines to perform SAR measurement. The cellular phone was tested with a headset connected to the device for all body-worn SAR measurements.

The following probe conversion factors were used on the E-Field probe(s) used for the body worn measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN1514	835	6.1	8 of 11
		1900	N/A	N/A

f (MHz)	Description	Conducted Output Power (dBm)	Body Worn w/ 15mm Separation Distance							
			Front of Phone Towards Phantom				Back of Phone Towards Phantom			
			Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)	Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)
Analog 800MHz	Channel 991	26.94								
	Channel 384	27.06	0.311	0.08	0.31	19.4	0.552	0.01	0.55	20.0
	Channel 799	27.05								
Digital 800MHz	Channel 1013	25.21								
	Channel 384	25.27	0.21	0.00	0.21	19.6	0.349	-0.05	0.35	20.3
	Channel 777	25.16								

Table 3: SAR measurement results for the portable cellular telephone FCC ID IHDT5DY1 at highest possible output power. Measured against the body.

Appendix 1

SAR distribution comparison for the system accuracy verification

Dipole 900 MHz

900MHz System Performance Check / Dipole Sn# 96

Forward Power = 249mW Reflected Power = -22.56dB

Room Temp at time of measurement = 20C Simulant Temp at time of measurement = 19.8C.


R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03; Flat

Probe: ET3DV6 - SN1514 - Validation.3; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 900 MHz VALIDATION: $\sigma = 0.96$ mho/m $\epsilon_r = 40.4$ $\rho = 1.00$ g/cm³

Cubes (2): Peak: 4.37 mW/g ± 0.00 dB, SAR (1g): 2.76 mW/g ± 0.00 dB, SAR (10g): 1.74 mW/g ± 0.02 dB, (Worst-case extrapolation)

Penetration depth: 11.6 (10.7, 12.7) [mm]

Powerdrift: 0.08 dB



Dipole 900 MHz

900 MHz System Performance Check / Dipole Sn# 96

Forward Power = 248mW Reflected Power = -22.09dB

Room Temp at time of measurement = 20C. Simulant Temp at time of measurement = 20.2C.


R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03; Flat

Probe: ET3DV6 - SN1514 - Validation.3; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 900 MHz VALIDATION: $\sigma = 0.95$ mho/m $\epsilon_r = 40.3$ $\rho = 1.00$ g/cm³

Cubes (2): Peak: 4.37 mW/g ± 0.02 dB, SAR (1g): 2.75 mW/g ± 0.03 dB, SAR (10g): 1.74 mW/g ± 0.03 dB, (Worst-case extrapolation)

Penetration depth: 11.5 (10.7, 12.7) [mm]

Powerdrift: -0.08 dB



Dipole 900 MHz

900MHz System Performance Check / Dipole Sn# 96

Forward Power = 249mW Reflected Power = -22.56dB

Room Temp at time of measurement = 20C Simulant Temp at time of measurement = 19.8C.


R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Section; Position: ; Frequency: 900 MHz

Probe: ET3DV6 - SN1514 - Validation.3; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 900 MHz VALIDATION: $\sigma = 0.96$ mho/m $\epsilon_r = 40.4$ $\rho = 1.00$ g/cm³

: , ()

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Penetration depth: 11.3 (10.4, 12.6) [mm]



Dipole 900 MHz

900 MHz System Performance Check / Dipole Sn# 96

Forward Power = 248mW Reflected Power = -22.09dB

Room Temp at time of measurement = 20C. Simulant Temp at time of measurement = 20.2C.


R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Section; Position: ; Frequency: 900 MHz

Probe: ET3DV6 - SN1514 - Validation.3; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 900 MHz VALIDATION: $\sigma = 0.95$ mho/m $\epsilon_r = 40.3$ $\rho = 1.00$ g/cm³

: , ()

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Penetration depth: 11.4 (10.5, 12.7) [mm]



Dipole 900 MHz

900 MHz System Performance Check / Dipole Sn# 96

Forward Power = 252mW Reflected Power = -22.23dB

Room Temp at time of measurement = 20 Simulant Temp at time of measurement = 20.4


R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03; Flat

Probe: ET3DV6 - SN1514 - Validation.3; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 900 MHz VALIDATION: $\sigma = 0.95$ mho/m $\epsilon_r = 40.3$ $\rho = 1.00$ g/cm³

Cubes (2): Peak: 4.43 mW/g ± 0.02 dB, SAR (1g): 2.79 mW/g ± 0.02 dB, SAR (10g): 1.76 mW/g ± 0.03 dB, (Worst-case extrapolation)

Penetration depth: 11.6 (10.8, 12.7) [mm]

Powerdrift: 0.02 dB



Dipole 900 MHz

900 MHz System Performance Check / Dipole Sn# 96

Forward Power = 252mW Reflected Power = -22.23dB

Room Temp at time of measurement = 20 Simulant Temp at time of measurement = 20.4


R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Section; Position: ; Frequency: 900 MHz

Probe: ET3DV6 - SN1514 - Validation.3; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 900 MHz VALIDATION: $\sigma = 0.95$ mho/m $\epsilon_r = 40.3$ $\rho = 1.00$ g/cm³

: , ()

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Penetration depth: 11.5 (10.6, 12.7) [mm]



Appendix 2

SAR distribution plots for Phantom Head Adjacent Use

s/n: 33881DFA

Ch# 991 / Pwr Step: 2

Type of Modulation: Analog 800

DEVICE POSITION (cheek or rotated): Cheek

Antenna Position: Fixed

Battery Model #: SNN5691

R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Left Hand Section; Position: (90°,180°); Frequency: 824 MHz


Probe: ET3DV6 - SN1514 - IEEE Head.2; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.90$ mho/m $\epsilon_r = 41.3$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 1.18 mW/g, SAR (10g): 0.820 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 15.0

Penetration depth: 15.3 (14.4, 16.3) [mm]

Powerdrift: 0.07 dB



s/n: 33881DFA

Ch# 991 / Pwr Step: 2

Type of Modulation: Analog 800

DEVICE POSITION (cheek or rotated): Cheek

Antenna Position: Fixed

Battery Model #: SNN5691

R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Right Hand Section; Position: (90°,180°); Frequency: 824 MHz


Probe: ET3DV6 - SN1514 - IEEE Head.2; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.89$ mho/m $\epsilon_r = 41.1$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 1.16 mW/g, SAR (10g): 0.815 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 15.0

Penetration depth: 15.7 (14.7, 16.8) [mm]

Powerdrift: -0.09 dB



s/n: 33881DFA

Ch# 384 / Pwr Step: Always Up

Type of Modulation: CDMA 800

DEVICE POSITION (cheek or rotated): Cheek

R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Left Hand Section; Position: (90°,180°); Frequency: 837 MHz

Probe: ET3DV6 - SN1514 - IEEE Head.2; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.89$ mho/m $\epsilon_r = 41.1$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 0.773 mW/g, SAR (10g): 0.526 mW/g, (Worst-case extrapolation)


Coarse: Dx = 15.0, Dy = 15.0, Dz = 15.0

Penetration depth: 15.0 (14.0, 16.0) [mm]

Powerdrift: -0.13 dB

Antenna Position: Fixed

Battery Model #: SNN5691



s/n: 33881DFA

Ch# 384 / Pwr Step: Always Up

Type of Modulation: CDMA 800

DEVICE POSITION (cheek or rotated): Cheek

R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Right Hand Section; Position: (90°,180°); Frequency: 837 MHz

Probe: ET3DV6 - SN1514 - IEEE Head.2; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.89$ mho/m $\epsilon_r = 41.1$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 0.719 mW/g, SAR (10g): 0.498 mW/g, (Worst-case extrapolation)


Coarse: Dx = 15.0, Dy = 15.0, Dz = 15.0

Penetration depth: 16.0 (15.9, 16.2) [mm]

Powerdrift: 0.04 dB

Antenna Position: Fixed

Battery Model #: SNN5691






Figure 1. Typical 800MHz AMPS Head Adjacent Contour Overlaid on Phone (Cheek Touch)




Figure 2. Typical 800MHz CDMA Head Adjacent Contour Overlaid on Phone (Cheek Touch)

s/n: 33881DFA

Ch# 991 / Pwr Step: 2

Type of Modulation: Analog 800

Antenna Position: Fixed

Battery Model #: SNN5691

DEVICE POSITION (cheek or rotated): Rotated

R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Left Hand Section; Position: (90°,180°); Frequency: 824 MHz


Probe: ET3DV6 - SN1514 - IEEE Head.2; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.89$ mho/m $\epsilon_r = 41.1$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 0.943 mW/g, SAR (10g): 0.609 mW/g, (Worst-case extrapolation)

Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0

Penetration depth: 12.5 (12.2, 12.9) [mm]

Powerdrift: -0.03 dB



s/n: 33881DFA

Ch# 384 / Pwr Step: 2

Type of Modulation: Analog 800

DEVICE POSITION (cheek or rotated): Rotated

Antenna Position: Fixed

Battery Model #: SNN5691

R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Right Hand Section; Position: (90°,180°); Frequency: 837 MHz


Probe: ET3DV6 - SN1514 - IEEE Head.2; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.89$ mho/m $\epsilon_r = 41.1$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 0.772 mW/g, SAR (10g): 0.507 mW/g, (Worst-case extrapolation)

Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0

Penetration depth: 12.7 (12.1, 13.5) [mm]

Powerdrift: 0.05 dB



s/n: 33881DFA

Ch# 384 / Pwr Step: Always Up

Type of Modulation: CDMA 800

DEVICE POSITION (cheek or rotated): Rotated

R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Left Hand Section; Position: (90°,180°); Frequency: 837 MHz

Probe: ET3DV6 - SN1514 - IEEE Head.2; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.89$ mho/m $\epsilon_r = 41.1$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 0.603 mW/g, SAR (10g): 0.377 mW/g, (Worst-case extrapolation)


Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0

Penetration depth: 11.8 (10.9, 13.0) [mm]

Powerdrift: 0.07 dB

Antenna Position: Fixed

Battery Model #: SNN5691



s/n: 33881DFA

Ch# 384 / Pwr Step: Always Up

Type of Modulation: CDMA 800

DEVICE POSITION (cheek or rotated): Rotated

R4 TP-1131 SUGAR sam expanded (Rev. 2)-9Jan03 Phantom; Right Hand Section; Position: (90°,180°); Frequency: 837 MHz

Probe: ET3DV6 - SN1514 - IEEE Head.2; ConvF(6.30,6.30,6.30); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.89$ mho/m $\epsilon_r = 41.1$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 0.550 mW/g, SAR (10g): 0.356 mW/g, (Worst-case extrapolation)


Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0

Penetration depth: 12.6 (12.0, 13.4) [mm]

Powerdrift: 0.04 dB

Antenna Position: Fixed

Battery Model #: SNN5691






Figure 3. Typical 800MHz AMPS Head Adjacent Contour Overlaid on Phone (15 ° Tilt)




Figure 4. Typical 800MHz CDMA Head Adjacent Contour Overlaid on Phone (15 ° Tilt)

Appendix 3

SAR distribution plots for Body Worn Configuration

s/n: 33881DFA

Ch# 384 / Pwr Step: 02 (OTA)

Type of Modulation: Analog 800

Back of Phone 15mm from Flat Phantom

R4 - Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 1 Section; Position: (0°,0°); Frequency: 837 MHz

Probe: ET3DV6 - SN1514 - FCC Body.2; ConvF(6.10,6.10,6.10); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.98$ mho/m $\epsilon_r = 53.9$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 0.552 mW/g, SAR (10g): 0.374 mW/g, (Worst-case extrapolation)


Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 14.7 (13.5, 16.1) [mm]


Powerdrift: 0.01 dB

Antenna Position: Fixed

Battery Model #: SNN5691



SAR_{Tot} [mW/g]



s/n: 33881DFA

Ch# 384 / Pwr Step: Always Up

Type of Modulation: CDMA 800

Back of Phone 15mm from Flat Phantom

R4 - Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 1 Section; Position: (0°,0°); Frequency: 837 MHz

Probe: ET3DV6 - SN1514 - FCC Body.2; ConvF(6.10,6.10,6.10); Crest factor: 1.0; 835 MHz Head & Body: $\sigma = 0.98$ mho/m $\epsilon_r = 53.9$ $\rho = 1.00$ g/cm³

Cube 7x7x7: SAR (1g): 0.349 mW/g, SAR (10g): 0.238 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 14.4 (13.3, 15.6) [mm]

Powerdrift: -0.05 dB

Antenna Position: Fixed

Battery Model #: SNN5691






Figure 5. Typical 800 MHz AMPS Body-Worn Contour Overlaid on Phone




Figure 6. Typical 800 MHz CDMA Body-Worn Contour Overlaid on Phone

Appendix 4
Probe Calibration Certificate

Client

Motorola MRO

CALIBRATION CERTIFICATE

Object(s)

ET3DV6 - SN 1514

Calibration procedure(s)

QA CAL-01 v2
 Calibration procedure for dosimetric E-field probes

Calibration date:

July 31, 2003

Condition of the calibrated item



In Tolerance (according to the specific calibration document)

This calibration statement documents traceability of M&TE used in the calibration procedures and conformity of the procedures with the ISO/IEC 17025 international standard.

All calibrations have been conducted in the closed laboratory facility: environment temperature 22 +/- 2 degrees Celsius and humidity < 75%.

Calibration Equipment used (M&TE critical for calibration)

Model Type	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
RF generator HP 8684C	US3642U01700	4-Aug-99 (SPEAG, in house check Aug-02)	In house check: Aug-05
Power sensor E4412A	MY41495277	2-Apr-03 (METAS, No 252-0250)	Apr-04
Power sensor HP 8481A	MY41092180	18-Sep-02 (Agilent, No. 20020918)	Sep-03
Power meter EPM E4419B	GB41293874	2-Apr-03 (METAS, No 252-0250)	Apr-04
Network Analyzer HP 8753E	US37390585	18-Oct-01 (Agilent, No. 24BR1033101)	In house check: Oct 03
Fluke Process Calibrator Type 702	SN: 6295803	3-Sep-01 (ELCAL, No.2360)	Sep-03

	Name	Function	Signature
Calibrated by:	Nico Vetterli	Technician	
Approved by:	Katja Pekoic	Laboratory Director	

Date issued: July 31, 2003

This calibration certificate is issued as an intermediate solution until the accreditation process (based on ISO/IEC 17025 International Standard) for Calibration Laboratory of Schmid & Partner Engineering AG is completed.

Probe ET3DV6

SN:1514

Manufactured:	November 24, 1999
Last calibration:	July 25, 2002
Recalibrated:	July 31, 2003

Calibrated for DASYS Systems

(Note: non-compatible with DASYS2 system!)

DASY - Parameters of Probe: ET3DV6 SN:1514

Sensitivity in Free Space

NormX	1.70 $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	1.86 $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	1.79 $\mu\text{V}/(\text{V}/\text{m})^2$

Diode Compression

DCP X	93	mV
DCP Y	93	mV
DCP Z	93	mV

Sensitivity in Tissue Simulating Liquid

Head **900 MHz** $\epsilon_r = 41.5 \pm 5\%$ $\sigma = 0.97 \pm 5\%$ mho/m
Valid for f=800-1000 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X

ConvF X	6.3 $\pm 9.5\%$ (k=2)	Boundary effect:
ConvF Y	6.3 $\pm 9.5\%$ (k=2)	Alpha 0.58
ConvF Z	6.3 $\pm 9.5\%$ (k=2)	Depth 1.95

Head **1800 MHz** $\epsilon_r = 40.0 \pm 5\%$ $\sigma = 1.40 \pm 5\%$ mho/m
Valid for f=1710-1910 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X

ConvF X	5.1 $\pm 9.5\%$ (k=2)	Boundary effect:
ConvF Y	5.1 $\pm 9.5\%$ (k=2)	Alpha 0.55
ConvF Z	5.1 $\pm 9.5\%$ (k=2)	Depth 2.48

Boundary Effect

Head **900 MHz** **Typical SAR gradient: 5 % per mm**

Probe Tip to Boundary		1 mm	2 mm
SAR _{be} [%] Without Correction Algorithm		9.7	5.1
SAR _{be} [%] With Correction Algorithm		0.2	0.4





Head **1800 MHz** **Typical SAR gradient: 10 % per mm**



Probe Tip to Boundary		1 mm	2 mm
SAR _{be} [%] Without Correction Algorithm		13.9	9.0
SAR _{be} [%] With Correction Algorithm		0.1	0.0

Sensor Offset


Probe Tip to Sensor Center	2.7	mm
Optical Surface Detection	0.8 \pm 0.2	mm

Receiving Pattern (ϕ , $\theta = 0^\circ$)






Isotropy Error (ϕ), $\theta = 0^\circ$





Frequency Response of E-Field


(TEM-Cell:ifi110, Waveguide R22)



Dynamic Range f(SAR_{brain}) (Waveguide R22)




Conversion Factor Assessment



Head	900 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.97 \pm 5\% \text{ mho/m}$
Valid for f=800-1000 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X			
	ConvF X	6.3 $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	6.3 $\pm 9.5\%$ (k=2)	Alpha 0.58
	ConvF Z	6.3 $\pm 9.5\%$ (k=2)	Depth 1.95

Head	1800 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
Valid for f=1710-1910 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X			
	ConvF X	5.1 $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	5.1 $\pm 9.5\%$ (k=2)	Alpha 0.55
	ConvF Z	5.1 $\pm 9.5\%$ (k=2)	Depth 2.48

Conversion Factor Assessment



Body **900 MHz** $\epsilon_r = 55.0 \pm 5\%$ $\sigma = 1.05 \pm 5\% \text{ mho/m}$

Valid for f=800-1000 MHz with Head Tissue Simulating Liquid according to OET 65 Suppl. C


ConvF X	6.1 $\pm 9.5\%$ (k=2)	Boundary effect:
ConvF Y	6.1 $\pm 9.5\%$ (k=2)	Alpha 0.51
ConvF Z	6.1 $\pm 9.5\%$ (k=2)	Depth 2.18

Body **1800 MHz** $\epsilon_r = 53.3 \pm 5\%$ $\sigma = 1.52 \pm 5\% \text{ mho/m}$

Valid for f=1710-1910 MHz with Head Tissue Simulating Liquid according to OET 65 Suppl. C

ConvF X	4.7 $\pm 9.5\%$ (k=2)	Boundary effect:
ConvF Y	4.7 $\pm 9.5\%$ (k=2)	Alpha 0.57
ConvF Z	4.7 $\pm 9.5\%$ (k=2)	Depth 2.85


Conversion Factor Assessment



Body	1950 MHz	$\epsilon_r = 53.3 \pm 5\%$	$\sigma = 1.52 \pm 5\% \text{ mho/m}$
	ConvF X	4.5 $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	4.5 $\pm 9.5\%$ (k=2)	Alpha 0.80
	ConvF Z	4.5 $\pm 9.5\%$ (k=2)	Depth 2.23

Head	1950 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
	ConvF X	5.0 $\pm 8.9\%$ (k=2)	Boundary effect:
	ConvF Y	5.0 $\pm 8.9\%$ (k=2)	Alpha 0.60
	ConvF Z	5.0 $\pm 8.9\%$ (k=2)	Depth 2.44

Conversion Factor Assessment



Body 2450 MHz $\epsilon_r = 52.7 \pm 5\%$ $\sigma = 1.95 \pm 5\%$ mho/m

Valid for f=2400-2500 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C

ConvF X	4.4 \pm 8.9% (k=2)	Boundary effect:
ConvF Y	4.4 \pm 8.9% (k=2)	Alpha 1.55
ConvF Z	4.4 \pm 8.9% (k=2)	Depth 1.45


Head 2450 MHz $\epsilon_r = 39.2 \pm 5\%$ $\sigma = 1.80 \pm 5\%$ mho/m

Valid for f=2400-2500 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X

ConvF X	4.7 \pm 8.9% (k=2)	Boundary effect:
ConvF Y	4.7 \pm 8.9% (k=2)	Alpha 1.24
ConvF Z	4.7 \pm 8.9% (k=2)	Depth 1.67

Deviation from Isotropy in HSL

Error ($\theta\phi$), $f = 900$ MHz



Appendix 5
Dipole Characterization Certificate

Certification of System Performance Check Targets

Based on APP-0396

-Historical Data-

	835MHz	900MHz	1800MHz	1900MHz	
P1528 Target: Advanced Extrapolation	9.5	10.8	38.1	39.7	(W/kg)
Measurement Uncertainty (k=1):	10.2%	10.2%	10.2%	10.2%	
Measurement Period:	November '02 - June '03	November '02 - June '03	November '02 - June '03	November '02 - June '03	
# of tests performed:	169	728	868	26	
Grand Average: Worst Case Extrapolation	10.1	11.6	39.7	42.0	(W/kg)
% Delta (Average - P1528 Target)	6.5%	7.7%	4.2%	5.9%	
Is % Delta <= Measurement Uncertainty?	Yes	Yes	Yes	Yes	
Accept/Reject Average as new system performance check target?	ACCEPT	ACCEPT	ACCEPT	ACCEPT	
	Applicable 835MHz Dipole Serial Numbers:	Applicable 900MHz Dipole Serial Numbers:	Applicable 1800MHz Dipole Serial Numbers:	Applicable 1900MHz Dipole Serial Numbers:	
	420(TR), 421(TR)	77, 78	246(TR), 250(TR)	514(TR), 518(TR)	
	422(TR), 423(TR)	79, 80	251(TR), 258(TR)	519(TR), 520(TR)	
	424(TR), 425(TR)	91, 92	259(TR), 262(TR)	523(TR), 524(TR)	
	431(TR), 432(TR)	93, 94	263(TR), 271(TR)	526(TR), 527(TR)	
	433(TR), 434(TR)	95, 96	272(TR), 273(TR)	528(TR), 529(TR)	
	436(TR)	97	276(TR), 277(TR)	530(TR), 533(TR)	
			279(TR), 280(TR)		
			281(TR), 282(TR)		
			283(TR), 284(TR)		

-New System Performance Check Targets- per APP-0396

(based on analysis of historical data)

Frequency	SAR Target (W/kg)	Permittivity	Conductivity (S/m)
835MHz	10.1	41.5 ± 5%	0.90 ± 5%
900MHz	11.6	41.5 ± 5%	0.97 ± 5%
1800MHz	39.7	40.0 ± 5%	1.40 ± 5%
1900MHz	42.0	40.0 ± 5%	1.40 ± 5%

-Approvals-

Submitted by: Date:

Signed: *Marge Kaunas*

Comments:

Approved by: Date:

Signed: *Antonio Faraone*

Comments:

Appendix 6
Measurement Uncertainty Budget

Uncertainty Budget for Device Under Test									
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1 g)	<i>c_i</i> (10 g)	1 g <i>u_i</i> (±%)	10 g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration	E.2.1	9.5	N	2.00	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	5.8	R	1.73	1	1	3.3	3.3	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1.0	N	1.00	1	1	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1	1	0.5	0.5	∞
Integration Time	E.2.8	1.3	R	1.73	1	1	0.8	0.8	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.3	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	1.1	R	1.73	1	1	0.6	0.6	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	3.9	R	1.73	1	1	2.3	2.3	∞
Test sample Related									
Test Sample Positioning	E.4.2	3.6	N	1.00	1	1	3.6	3.6	29
Device Holder Uncertainty	E.4.1	2.8	N	1.00	1	1	2.8	2.8	8
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	10.0	R	1.73	0.64	0.43	3.7	2.5	∞
Liquid Permittivity - deviation from target values	E.3.2	10.0	R	1.73	0.6	0.49	3.5	2.8	∞
Liquid Permittivity - measurement uncertainty	E.3.3	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Combined Standard Uncertainty			RSS				11.72	11.09	1363
Expanded Uncertainty (95% CONFIDENCE LEVEL)			<i>k</i> =2				22.98	21.75	

Uncertainty Budget for System Performance Check (dipole & flat phantom)

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1 g)	<i>c_i</i> (10 g)	1 g <i>u_i</i> (±%)	10 g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration	E.2.1	9.5	N	2.00	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0	0	0.0	0.0	∞
Boundary Effect	E.2.3	5.8	R	1.73	1	1	3.3	3.3	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1.0	N	1.00	1	1	1.0	1.0	∞
Response Time	E.2.7	0.0	R	1.73	1	1	0.0	0.0	∞
Integration Time	E.2.8	0.0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.3	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	1.1	R	1.73	1	1	0.6	0.6	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	3.9	R	1.73	1	1	2.3	2.3	∞
Dipole									
Dipole Axis to Liquid Distance	8, E.4.2	1.0	R	1.73	1	1	0.6	0.6	∞
Input Power and SAR Drift Measurement	8, 6.6.2	4.7	R	1.73	1	1	2.7	2.7	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	10.0	R	1.73	0.64	0.43	3.7	2.5	∞
Liquid Permittivity - deviation from target values	E.3.2	10.0	R	1.73	0.6	0.49	3.5	2.8	∞
Liquid Permittivity - measurement uncertainty	E.3.3	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Combined Standard Uncertainty			RSS				10.16	9.43	99999
Expanded Uncertainty (95% CONFIDENCE LEVEL)			<i>k=2</i>				19.92	18.48	

Appendix 7

Photographs of the device under test





