



# FCC Test Report

APPLICANT : Motorola Mobility LLC  
EQUIPMENT : Wireless Earphones  
BRAND NAME : Motorola  
MODEL NAME : XT2441-1  
FCC ID : IHDT6AB1  
STANDARD : 47 CFR Part 15 Subpart B  
CLASSIFICATION : Certification  
TEST DATE(S) : Dec. 08, 2023 ~ Dec. 21, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



**Sporton International Inc. (Kunshan)**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY ..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1. GENERAL DESCRIPTION ..... 5**

    1.1. Applicant..... 5

    1.2. Manufacturer ..... 5

    1.3. Product Feature of Equipment Under Test ..... 5

    1.4. Product Specification of Equipment Under Test ..... 5

    1.5. Product Specification of Charging Case ..... 5

    1.6. Modification of EUT ..... 6

    1.7. Test Location ..... 6

    1.8. Test Software ..... 6

    1.9. Applicable Standards ..... 6

    1.10. Specification of Accessory ..... 6

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 7**

    2.1. Test Mode ..... 7

    2.2. Connection Diagram of Test System ..... 8

    2.3. Support Unit used in test configuration and system..... 8

    2.4. EUT Operation Test Setup ..... 8

**3. TEST RESULT ..... 9**

    3.1. Test of AC Conducted Emission Measurement ..... 9

    3.2. Test of Radiated Emission Measurement ..... 13

**4. LIST OF MEASURING EQUIPMENT ..... 18**

**5. MEASUREMENT UNCERTAINTY ..... 19**

**APPENDIX A. SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC3N2901	Rev. 01	Initial issue of report	Jan. 09, 2024



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 12.49 dB at 0.582 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 9.68 dB at 30.000 MHz

**Conformity Assessment Condition:**

The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. Please refer to each test results in the section "Measurement Uncertainty".

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



# 1. General Description

## 1.1. Applicant

Motorola Mobility LLC  
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2. Manufacturer

Motorola Mobility LLC  
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Wireless Earphones
Brand Name	Motorola
Model Name	XT2441-1
FCC ID	IHDT6AB1
EUT supports Radios application	Bluetooth BR/EDR/LE
S/N Code	FFLTL231126000822/FFLTR231126000734
HW Version	DVT
SW Version	moto_buds_600 stereo
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/ Rx Frequency	Bluetooth: 2400 MHz ~ 2483.5 MHz
Antenna Type	Bluetooth: FPC Antenna
Type of Modulation	Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) :π/4-DQPSK Bluetooth (3Mbps) : 8-DPSK

## 1.5. Product Specification of Charging Case

Charging Case Specification	
Rx Frequency	WPT: 110kHz~ 205 kHz
Antenna Type	WPT: Coil Antenna



### 1.6. Modification of EUT

No modifications are made to the EUT during all test items.

### 1.7. Test Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH07-KS	CN1257	314309

### 1.8. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH07-KS	AUDIX	E3	210616
2.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.9. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

### 1.10. Specification of Accessory

Accessories Information				
<b>Battery 1</b>	<b>Brand Name</b>	Chongqing VDL Electronics Co., LTD.	<b>Model Name</b>	1054PF4C1
<b>Battery 2</b>	<b>Brand Name</b>	Chongqing VDL Electronics Co., LTD.	<b>Model Name</b>	721833PF5
<b>USB Cable</b>	<b>Brand Name</b>	Jieye	<b>Model Name</b>	JY-C03-411



## 2. Test Configuration of Equipment Under Test


### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: Earbuds + Charging case close + USB Cable (Charging from Adaptor) Mode 2: Earbuds bluetooth Link With Phone + Charging case open + USB Cable (EUT Charging from Wireless charger ) + Adaptor Connect to Wireless charger
Radiated Emissions	Mode 1: Earbuds bluetooth Link With Phone + Mic + Voice call Mode 2: Earbuds bluetooth Link With Phone + Play Music Mode 3: Earbuds + Charging case close + USB Cable (Charging from Adaptor) Mode 4: Earbuds bluetooth Link With Phone + Charging case open + USB Cable (EUT Charging from Wireless charger ) + Adaptor Connect to Wireless charger
<b>Remark:</b> <ol style="list-style-type: none"> <li data-bbox="284 1167 1230 1196">1. The worst case of AC is mode 2; only the test data of this mode is reported.</li> <li data-bbox="284 1216 1230 1245">2. The worst case of RE is mode 3; only the test data of this mode is reported.</li> </ol>	

## 2.2. Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

## 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Mobile Phone	iPhone	iPhone 13 Pro 256GB	CCAI215G0120T0	N/A	N/A
2.	Wireless charger	moshi	99MO022219	N/A	N/A	N/A
3.	Adapter	MOTO	MC-101	N/A	N/A	N/A

## 2.4. EUT Operation Test Setup

The following programs installed in the EUT were programmed during the test.

1. Bluetooth link with EUT.





### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test Setup




AMN = Artificial mains network (LISN)  
 AE = Associated equipment  
 EUT = Equipment under test  
 ISN = Impedance stabilization network



3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	24.2~25.6°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS  
 Condition : FCC IC-QP LISN-060105-L 2023 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.152	34.57	-31.34	65.91	24.10	0.05	10.42	QP
2	0.152	26.47	-29.44	55.91	16.00	0.05	10.42	Average
3	0.212	30.53	-32.61	63.14	20.10	0.03	10.40	QP
4	0.212	21.23	-31.91	53.14	10.80	0.03	10.40	Average
5	0.582	35.54	-20.46	56.00	25.41	-0.05	10.18	QP
6 *	0.582	31.74	-14.26	46.00	21.61	-0.05	10.18	Average
7	0.634	36.41	-19.59	56.00	26.31	-0.06	10.16	QP
8	0.634	31.41	-14.59	46.00	21.31	-0.06	10.16	Average
9	2.044	30.74	-25.26	56.00	20.80	-0.14	10.08	QP
10	2.044	27.44	-18.56	46.00	17.50	-0.14	10.08	Average
11	27.127	34.85	-25.15	60.00	23.59	-0.33	11.59	QP
12	27.127	27.15	-22.85	50.00	15.89	-0.33	11.59	Average



Test Engineer :	Amos Zhang	Temperature :	24.2~25.6°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS  
 Condition : FCC IC-QP LISN-060105-N 2023 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.150	36.56	-29.44	66.00	26.10	0.04	10.42	QP
2	0.150	29.56	-26.44	56.00	19.10	0.04	10.42	Average
3	0.289	32.71	-27.83	60.54	22.40	-0.03	10.34	QP
4	0.289	29.01	-21.53	50.54	18.70	-0.03	10.34	Average
5	0.582	37.21	-18.79	56.00	27.10	-0.07	10.18	QP
6 *	0.582	33.51	-12.49	46.00	23.40	-0.07	10.18	Average
7	0.871	35.51	-20.49	56.00	25.50	-0.09	10.10	QP
8	0.871	32.11	-13.89	46.00	22.10	-0.09	10.10	Average
9	1.310	32.08	-23.92	56.00	22.11	-0.11	10.08	QP
10	1.310	25.68	-20.32	46.00	15.71	-0.11	10.08	Average
11	27.562	31.00	-29.00	60.00	19.80	-0.40	11.60	QP
12	27.562	25.60	-24.40	50.00	14.40	-0.40	11.60	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



### 3.2. Test of Radiated Emission Measurement

#### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### **3.2.3. Test Procedures**


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Jiang	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal




Site : 03CH07-KS  
 Condition : FCC CLASS-B 3m 3117 SN00240132 HORIZONTAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	200.72	23.00	-20.50	43.50	38.30	14.82	2.07	32.19	---	---	Peak
2	232.73	28.03	-17.97	46.00	41.47	16.44	2.22	32.10	---	---	Peak
3 p	291.90	35.46	-10.54	46.00	45.89	19.14	2.50	32.07	---	---	Peak
4	430.61	23.30	-22.70	46.00	29.80	22.60	3.02	32.12	---	---	Peak
5	565.44	26.46	-19.54	46.00	29.04	26.27	3.46	32.31	---	---	Peak
6	936.95	32.47	-13.53	46.00	28.99	30.07	4.45	31.04	---	---	Peak
7	5301.00	41.91	-32.09	74.00	60.23	34.50	10.77	63.59	---	---	Peak
8	8871.00	42.95	-31.05	74.00	55.11	36.10	14.14	62.40	---	---	Peak
9	10503.00	43.80	-30.20	74.00	52.46	37.80	15.63	62.09	---	---	Peak
10	13971.00	46.79	-27.21	74.00	50.82	39.11	17.97	61.11	---	---	Peak
11	15212.00	47.37	-26.63	74.00	50.69	40.26	18.60	62.18	---	---	Peak
12	17218.00	48.55	-25.45	74.00	50.19	41.47	19.85	62.96	---	---	Peak





Test Engineer :	Jiang	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical



Site : 03CH07-KS  
 Condition : FCC CLASS-B 3m 3117 SN00240132 VERTICAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 p	30.00	30.32	-9.68	40.00	36.75	25.18	0.50	32.11	---	---	Peak
2	77.53	17.76	-22.24	40.00	35.69	13.00	1.14	32.07	---	---	Peak
3	200.72	27.18	-16.32	43.50	42.48	14.82	2.07	32.19	---	---	Peak
4	292.87	32.59	-13.41	46.00	42.98	19.17	2.51	32.07	---	---	Peak
5	669.23	28.20	-17.80	46.00	30.07	26.58	3.78	32.23	---	---	Peak
6	950.53	32.34	-13.66	46.00	28.11	30.70	4.48	30.95	---	---	Peak
7	4893.00	46.31	-27.69	74.00	65.08	34.30	10.41	63.48	---	---	Peak
8	7409.00	46.02	-27.98	74.00	61.19	35.72	12.85	63.74	---	---	Peak
9	9925.00	47.61	-26.39	74.00	57.43	37.22	15.25	62.29	---	---	Peak
10	13665.00	45.87	-28.13	74.00	49.95	39.23	17.74	61.05	---	---	Peak
11	16164.00	48.62	-25.38	74.00	50.78	40.93	19.12	62.21	---	---	Peak
12	17133.00	49.58	-24.42	74.00	51.25	41.52	19.79	62.98	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	May 16, 2023	Dec. 08, 2023 ~Dec. 09, 2023	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Dec. 08, 2023 ~Dec. 09, 2023	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Dec. 08, 2023 ~Dec. 09, 2023	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Dec. 08, 2023 ~Dec. 09, 2023	Oct. 10, 2024	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Oct. 10, 2023	Dec. 11, 2023 ~Dec. 21, 2023	Oct. 09, 2024	Radiation (03CH07-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 10, 2023	Dec. 11, 2023 ~Dec. 21, 2023	Oct. 09, 2024	Radiation (03CH07-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Aug. 12, 2023	Dec. 11, 2023 ~Dec. 21, 2023	Aug. 11, 2024	Radiation (03CH07-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 06, 2023	Dec. 11, 2023 ~Dec. 21, 2023	Apr. 05, 2024	Radiation (03CH07-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Oct. 16, 2023	Dec. 11, 2023 ~Dec. 21, 2023	Oct. 15, 2024	Radiation (03CH07-KS)
Amplifier	EM	EM18G40GGA	060851	18~40GHz	Jan. 05, 2023	Dec. 11, 2023 ~Dec. 21, 2023	Jan. 04, 2024	Radiation (03CH07-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 05, 2023	Dec. 11, 2023 ~Dec. 21, 2023	Jan. 04, 2024	Radiation (03CH07-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Oct. 10, 2023	Dec. 11, 2023 ~Dec. 21, 2023	Oct. 09, 2024	Radiation (03CH07-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Dec. 11, 2023 ~Dec. 21, 2023	NCR	Radiation (03CH07-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Dec. 11, 2023 ~Dec. 21, 2023	NCR	Radiation (03CH07-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Dec. 11, 2023 ~Dec. 21, 2023	NCR	Radiation (03CH07-KS)

NCR: No Calibration Required



## 5. Measurement Uncertainty

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.94dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	6.20dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.86dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.24dB
---	--------