



RF EXPOSURE EVALUATION METHOD

**FCC ID: IKQBTFMA
IC:6955A-BTFMA**

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

BT

EDR			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
GFSK			
CH00	2402	-1.141	0.769
CH39	2441	-1.681	0.679
CH78	2480	-1.664	0.682
π/4DQPSK			
CH00	2402	0.899	1.230
CH39	2441	0.367	1.088
CH78	2480	0.368	1.088
8DPSK			
CH00	2402	1.270	1.340
CH39	2441	0.708	1.177
CH78	2480	0.679	1.169

Remark: The best case gain of the antenna is 0dBi.

0 dBi logarithmic terms convert to numeric result is nearly 1.00

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,mm})] \cdot [\sqrt{f(\text{GHz})}]$

BT

Test Channel	max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)	(min. test separation distance,mm)]	[f(GHz)]	Result	Limit
GFSK						
CH00	-1.141	0.769	5	2.402	0.238	3
CH39	-1.681	0.679	5	2.441	0.212	3
CH78	-1.664	0.682	5	2.480	0.215	3
$\pi/4$ DQPSK						
CH00	0.899	1.230	5	2.402	0.381	3
CH39	0.367	1.088	5	2.441	0.340	3
CH78	0.368	1.088	5	2.480	0.343	3
8DPSK						
CH00	1.270	1.340	5	2.402	0.415	3
CH39	0.708	1.177	5	2.441	0.368	3
CH78	0.679	1.169	5	2.480	0.368	3

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.