


| Applicant: Scosche Industries, Inc.   |   |
|---|---|
| FCC ID: IKQMPQ  |   |
| RF Exposure Requirements ( FCC KDB 680106 D01)  |   |
| Requirements  | Statements  |
| (a) Power transfer frequency is less than 1 MHz   | The resonator system shall operate at 122-138KHz  |
| (b) Output power from each primary coil is less than 5 watts  | 15W   |
| (c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils | This device single coil, please refer to product Photo:  |
| (d) Client device is inserted in or placed directly in contact with the transmitter   | User placed RX directly in contact with the transmitter.  |
| (e) The maximum coupling surface area of the transmit (charging) device is between 60 cm <sup>2</sup> and 400 cm <sup>2</sup> .   | Length 53 mm and Width 53 mm  |
| (f) Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit.  | Please refer to "SA170118D03 Test Report".  |

*Rex Lai*

Rex Lai  
Assistant Manager  
Bureau Veritas Consumer Products Services (H.K.) Ltd., Hsinchu Branch