

FCC Test Report

Report No.: AGC12678220806FE10

FCC ID	:	IKQMPQ5A
APPLICATION PURPOSE		Original Equipment
PRODUCT DESIGNATION	:	Wireless Car Charger
BRAND NAME	:	() SCOSCHE () SCOSCHE
MODEL NAME	:	MPQ5A, MPQ5AMPSPC-UB, MPQ5WD-XTSP, MPQ5DV-XTSP
APPLICANT	:	Scosche Industries Inc
DATE OF ISSUE	:	Oct. 13, 2022
STANDARD(S)	:	FCC Part 15 Subpart C
REPORT VERSION	:	V 1.0 V 1.0
<u>Attestation of</u>	<u>G</u> lo	bal Compliance (Shenzhen) Co., Ltd





REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Oct. 13, 2022	Valid	Initial Release



TABLE OF CONTENTS

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	6
2.3 RELATED SUBMITTAL(S) / GRANT (S)	7
2.4 TEST METHODOLOGY	7
2.5 SPECIAL ACCESSORIES	7
2.6 EQUIPMENT MODIFICATIONS	7
2.7 ANTENNA REQUIREMENT	7
3. TEST ENVIRONMENT	8
3.1 ADDRESS OF THE TEST LABORATORY	8
3.2 TEST FACILITY	8
3.3 ENVIRONMENTAL CONDITIONS	9
3.4 MEASUREMENT UNCERTAINTY	9
3.5 LIST OF EQUIPMENTS USED	10
4.SYSTEM TEST CONFIGURATION	11
4.1 EUT CONFIGURATION	
4.2 EUT EXERCISE	11
4.3 CONFIGURATION OF TESTED SYSTEM	
4.4 EQUIPMENT USED IN TESTED SYSTEM	11
4.5 SUMMARY OF TEST RESULTS	
5. DESCRIPTION OF TEST MODES	
6. FIELD STRENGTH OF FUNDAMENTAL	
6.1 PROVISIONS APPLICABLE	14
6.3 FIELD STRENGTH CALCULATION	
6.4 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	17
6.5 MEASUREMENT RESULTS	18
7. 20 DB BANDWIDTH	
7.1 PROVISIONS APPLICABLE	
7.2 MEASUREMENT PROCEDURE	
7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
7.4 MEASUREMENT RESULTS	
8. AC POWER LINE CONDUCTED EMISSION TEST	
8.1 LIMITS OF LINE CONDUCTED EMISSION TEST	26

^{8.2} MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION) 26 Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



AP	PENDIX B: PHOTOGRAPHS OF TEST EUT	. 28
AP	PENDIX A: PHOTOGRAPHS OF TEST SETUP	. 28
	8.5 MEASUREMENT RESULTS	. 27
	8.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	. 27
	8.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	. 27



1. GENERAL INFORMATION

Applicant	Scosche Industries Inc	
Address	1550 Pacific Ave, Oxnard California 93033, United States	
Manufacturer	Scosche Industries Inc	
Address	1550 Pacific Ave, Oxnard California 93033, United States	
Factory	Scosche Industries Inc	
Address	1550 Pacific Ave, Oxnard California 93033, United States	
Product Designation	Wireless Car Charger	
Brand Name	D SCOSCHE DE SCOSCHE	
Test Model	MPQ5A	
Series Model(s)	MPQ5AMPSPC-UB, MPQ5WD-XTSP, MPQ5DV-XTSP	
Difference Description	The series models are identical except for model name and the accessories of wireless charger.	
Deviation from Standard	No any deviation from the test method	
Date of receipt of test item	Sep. 05, 2022	
Date of test	Sep. 05, 2022 to Oct. 12, 2022	
Test Result	Pass	
Test Report Form No	AGCTR-ER-FCC-WPTV1.0	

Bibo zhay Prepared By Bibo Zhang Oct. 13, 2022 (Project Engineer) **Reviewed By** Calvin Liu Oct. 13, 2022 (Reviewer) Max Zhan Approved By Max Zhang Oct. 13, 2022 (Authorized Officer)



Page 6 of 28



2. PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	CPS8600-V0
Software Version	84F5
Frequency Band	111kHz-148kHz
Operation Frequency	138.2kHz
Modulation Type	FSK
Number of channels	1
Field Strength of Fundamental	67.31dBuV/m (Max)
Antenna Designation	Integrated coil antenna
Antenna Gain	0dBi
Wireless Charging Output Power	15W / 10W / 7.5W / 5W
Wireless Charging Input Power	DC 12V, 2A
Adapter Information	N/A

2.2 TEST FREQUENCY LIST

Frequency Band	Channel Number	Frequency
111KHz-148KHz	01	138.2kHz



2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: IKQMPQ5A** filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title		
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
2	FCC 47 CFR Part 15	Radio Frequency Devices		
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices		

2.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7 ANTENNA REQUIREMENT

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antennathat uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a brokenantenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0 dBi.



3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS		
Temperature range (°C)	15 - 35	-20 - 50		
Relative humidty range	20 % - 75 %	20 % - 75 %		
Pressure range (kPa)	86 - 106	86 - 106		
Power supply				
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.				

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$		
Uncertainty of Radiated Emission below 150kHz	$U_c = \pm 4.2 \text{ dB}$		
Uncertainty of Radiated Emission below 30MHz	$U_c = \pm 3.8 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	U _c = ±2 %		
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %		



3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
LISN	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test Software	R&S	ES-K1	Ver.V1.71	N/A	N/A
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
Test Software	Tonscend	JS32-RE	Ver.2.5	N/A	N/A



4.SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:



4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement: Test Accessories Come From The Laboratory

Item	Equipment	Model No.	Identifier	Note
1	DC12V Battery	L2 400-H	N/A	AE
2	wireless charging load	N/A	N/A	AE

☐ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	Wireless Car Charger	MPQ5A	IKQMPQ5A	EUT



4.5 SUMMARY OF TEST RESULTS

ltem	FCC Rules	Description Of Test	Result
1	§15.203	Antenna Equipment	Pass
2	§15.209(a)(f)	Radiated Spurious Emission	Pass
3	§15.215(c)	20dB Bandwidth	Pass
4	§15.205(a)	Restricted Bands of Operation	Pass
5	§15.207	AC Power Line Conducted Emission	N/A

Note: 1.N/A means not applicable

Note: 2. The EUT was supplied by DC source and does not require evaluation of AC Power Line Conducted Emission.



5. DESCRIPTION OF TEST MODES

	Summary table of Test Cases
	Equipment type / Modulation
Test Item	WPT_(TX:138.2KHz)/ FSK
Radiated&Conducted Test Cases	Mode 1: DUT + Wireless load (Full load mode) Mode 2: DUT + Wireless load (Half load mode) Mode 3: DUT + Wireless load (Null Load mode)
Note:	rst case was recorded in the report, if no other cases.

For Radiated Emission, 3axis were chosen for testing for each applicable mode.



6. FIELD STRENGTH OF FUNDAMENTAL

6.1 PROVISIONS APPLICABLE

Test Requirement:	FCC Part15 C Section	on 15.209				
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	9kHz to 1GHz					
Test site:	Measurement Distar	nce: 3m				
	Frequency	Detector	RBW	VBW	Value	
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak	
Receiver setup:	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak	
Receiver setup.	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak	
		Peak	1MHz	3MHz	Peak	
	Above 1GHz	Peak	1MHz	10Hz	Average	
	1		1	1	-	

Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Quasi-peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Limits for frequency Above 30MHz

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
	54.00	Average Value
Above 1GHz	74.00	Peak Value

Remark: (1) Emission level dB μ V = 20 log Emission level μ V/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



6.2 MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



6.3 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where FS = Field Strength in $dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where $FS = Field Strength in dB\mu V/m$ RR = RA - AG - AV in dB μ V LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m.

This value in dB μ V/m was converted to its corresponding level in μ V/m.

 $\begin{array}{ll} {\sf RA} = 52.0 \ d{\sf B}\mu{\sf V}/{\sf m} & \\ {\sf AF} = 7.4 \ d{\sf B}/{\sf m} & {\sf RR} = 18.0 \ d{\sf B}\mu{\sf V} \\ {\sf CF} = 1.6 \ d{\sf B} & {\sf LF} = 9.0 \ d{\sf B} \\ {\sf AG} = 29.0 \ d{\sf B} & \\ {\sf AV} = 5.0 \ d{\sf B} & \\ {\sf FS} = {\sf RR} + {\sf LF} \\ {\sf FS} = 18 + 9 = 27 \ d{\sf B}\mu{\sf V}/{\sf m} & \\ \end{array}$

Level in μ V/m = Common Antilogarithm [(27 dB μ V/m)/20] = 22.4 μ V/m

Magnetic field strength calculation (9 kHz – 30 MHz)

When the limit is in terms of magnetic field, the following equation applies: U(dP(x)/m) = V(dP(x)/n) + C(dP) = CPA(dP) + AFU(dP(x)/m)

```
H[dB(\mu A/m)] = V[dB(\mu V)] + LC [dB] - GPA [dB] + AFH [dB(S/m)]
```

Where,

H is the magnetic field strength (to be compared with the limit), V is the voltage level measured by the receiver or spectrum analyzer, LC is the cable loss, GPA is the gain of the preamplifier (if used), and AFH is the magnetic antenna factor.

If the "electrical" antenna factor is used instead, the above equation becomes:


 $H[dB(\mu A/m)] = V[dB(\mu V)] + LC [dB] - GPA [dB] + AFE [dB(m-1)] - 51.5 [dB\Omega]$

where AFE is the "electric" antenna factor, as provided by the antenna calibration laboratory.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




6.4 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)



RADIATED EMISSION TEST SETUP 9KHz-30MHz

RADIATED EMISSION TEST SETUP 30MHz-1000MHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.



6.5 MEASUREMENT RESULTS

ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 9KHz-150KHz

	E	LECT		JIESTI	N THE FRE		ANGE 9	(Hz-150)	\Hz	
UT		Wirele	ess Car Cl	narger		Model Name			MPQ5A	
Temperatu	re	22° ()			Relative Humidity			55%	
Pressure		960hF	⁵ a			Test Voltag	Nor	Normal Voltage		
Test Mode		Mode	1			Antenna		Fac	е	
130 () dBuV/m									
									Limit:	
									Margin:	
									_	
70										
	mark An	A	1	3	3	ł	5			
	a ndoord Ad	n Mullip	Window	Annual Install Press	warden and a	mor My mon	hall		r Munthingungur	
							- 1 7 Wy	ulil war velievywar	M. MANY WAR	
10.0										
0.	009				(MHz)					
	No	. Mk.	Freq.	Readin Level	g Correct Factor	Measure- ment	Limit	Over		
			MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	
	1		0.0155	12.04	27.93	39.97	123.1	-83.20	peak	
	2	2	0.0241	11.70	27.29	38.99	119.5	-80.60	peak	
	3	3	0.0352	13.43	26.46	39.89	116.5	-76.64	peak	
	4	ļ	0.0435	12.99	25.84	38.83	114.8	-75.98	peak	
	5	5	0.0687	13.68	23.96	37.64	111.1	-73.48	peak	
			0.4000	45.70	04.55	07.04	405.4	00.45	a set i	

RESULT: PASS

6 *

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

21.55

67.31

105.4

-38.15

peak

0.1382

45.76



	-	-		_						
EUT		Wirele	ess Car Ch	arger		Model Nam	ne	MP	Q5A	
Temperatur	е	22° (C			Relative Humidity			55%	
Pressure		960hl	Pa			Test Voltag	je	Nor	Normal Voltage	
Test Mode		Mode	1			Antenna		Fac	Face	
130.0) dBuV/	m								
									Limit: Margin:	
					_				margin.	
										
70										6
										6 X
			1	2		4	5			
	man	Aman	walk where	monthing	Mont	~ MMM	na Aurr			
				r r	•			han yaamada bahad	4 min milanya	14
10.0										
0.1	009				(MHz)					0.150
				Reading	Correct	Measure-				
	No	. Mk.	Freq.	Level	Factor	ment	Limit	Over		
			MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	
	1	1	0.0154	11.58	27.94	39.52	123.2	-83.70	peak	
	2	2	0.0239	10.19	27.30	37.49	119.6	-82.17	peak	
	3	3	0.0354	10.70	26.44	37.14	116.4	-79.34	peak	
	4	1	0.0483	12.65	25.48	38.13	113.9	-75.84	peak	
	ŧ	5	0.0623	14.24	24.44	38.68	111.9	-73.23	peak	
	(6 *	0.1382	45.55	21.55	67.10	105.4	-38.36	peak	

ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 9KHz-150KHz

RESULT: PASS



EUT Wireless Car Charger Model Name MPQ5A Temperature 22° C Relative Humidity 55% Pressure 960hPa Test Voltage Normal Voltage Test Mode Mode 1 Antenna Side		ELECIP		IESI IN I				JNNZ-30		
Pressure 960hPa Test Voltage Normal Voltage Test Mode Mode 1 Antenna Side	EUT	Wirele	ess Car Ch	narger		Model Nar	ne	MPC	Q5A	
Test Mode Mode 1 Antenna Side Image: Side <td< th=""><th>Temperature</th><th>22° (</th><th>C</th><th></th><th></th><th>Relative H</th><th>umidity</th><th>55%</th><th>)</th><th></th></td<>	Temperature	22° (C			Relative H	umidity	55%)	
$\frac{110.0 dBW/m}{4 dBW/m}$	Pressure	960hF	Pa			Test Volta	ge	Norr	mal Volta	ige
No. Mk. Freq. Reading Level Correct Factor Measure- ment Limit Over 1 0.2730 4.06 21.30 25.36 99.23 -73.87 peak 2 0.5552 7.68 20.92 28.60 72.71 44.11 peak 3 0.8305 7.95 21.15 29.10 69.22 40.12 peak 4<* 1.1054 7.35 21.38 28.73 66.73 -38.00 peak	Test Mode	Mode	: 1			Antenna		Side)	
5 2.5807 4.40 22.29 26.69 69.54 -42.85 peak	110.0 dBu	V/m	0.5552	Reading Level dBuV 4.06 7.68	(NH2) Correct Factor dB 21.30 20.92	Measure- ment dBuV/m 25.36 28.60	5 Limit dB/m 99.23 72.71	Over dB -73.87 -44.11	Limit: Margin: Augustion Margin: Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Margin Augustion Augus	30.000
		4 *	1.1054	7.35	21.38	28.73	66.73	-38.00	peak	-
6 7.8102 2.57 23.78 26.35 69.54 -43.19 peak	_	5	2.5807	4.40	22.29	26.69	69.54	-42.85	peak	_
		6	7.8102	2.57	23.78	26.35	69.54	-43.19	peak	_

ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 150KHz-30MHz

RESULT: PASS



	ELECT							-	
EUT	Wirele	ess Car Ch	narger		Model Na	me	MP	Q5A	
Temperature	22° (2			Relative H	lumidity	55%	0	
Pressure	960hl	Pa			Test Volta	ge	Nor	mal Volta	age
Test Mode	Mode	1			Antenna		Fac	е	
110.0 dB	3uV/m								
								Limit: Margin:	
-10 0.150	mundan and and a second	2 3 1 1 0.5	Marry Marry Marry	м-////////////////////////////////////	nnhannan	5		ymr, Mrog	yljuliVe 30.000
-10 0.150	No. Mk.	Mudermundand	Reading		Measurement	5	Over	ymr, Mry	
-10 0.150		0.5	Reading	(MHz) Correct	Measure	5		Detector	30.000
-10 0.150		0.5	Reading	(MH2) Correct Factor	Measurement	5 Limit	Over		30.000
-10 0.150	No. Mk.	0.5	Reading Level dBuV	(MH2) Correct Factor dB	Measure ment dBuV/m	5 Limit dB/m	Over	Detector	30.000
-10 0.150	No. Mk.	рекоронализија 0.5 Freq. MHz 0.2757	Reading Level dBuV 9.32	(MH2) Correct Factor dB 21.29	Measure- ment dBuV/m 30.61	5 - Limit dB/m 99.14	Over dB -68.53	Detector	30.000
-10 0.150	No. Mk.	мнz 0.2757 0.4148	Reading Level dBuV 9.32 8.30	(MHz) Correct Factor dB 21.29 21.04	Measurement dBuV/m 30.61 29.34	5 - Limit dB/m 99.14 95.35	Over dB -68.53 -66.01	Detector peak peak	30.000
-10 0.150	No. Mk.	мнг 0.2757 0.4148 0.5523	Reading Level dBuV 9.32 8.30 9.02	(MHz) Correct Factor dB 21.29 21.04 20.92	Measurement dBuV/m 30.61 29.34 29.94	5 Limit dB/m 99.14 95.35 72.76	Over dB -68.53 -66.01 -42.82	Detector peak peak peak	30.000

ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 150KHz-30MHz

RESULT: PASS

NOTES:

- 1. Peak detector is used for frequency below 30MHz.
- 2. Negative value in the margin column shows emission below limit.
- 3. All measurements were made with 0.6m loop antenna at 3m distance. All emissions are below the QP limit.
- 4. Corr. Factor= Antenna Factor (dB/m) + Cable Loss (dB)
- 5. Loop antenna is used for the emission under 30MHz.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/



	R		EMISSION	BELOW 1	GHz			
EUT	Wireless 0	Car Chargei	-	Model	Name	N	IPQ5A	
Temperature	22° C			Relativ	e Humidi	ty 5	55%	
Pressure	960hPa	960hPa				Ν	Normal Voltage	
Test Mode	Mode 1	Mode 1			a	F	lorizontal	
70.0 /0.1/1								
72.0 dBuV/m 32 -8 30.000 40	50 60 70 8		3 4 (MHz)	5	Malan Mura,		Limit: Margin:	
30.000 40	50 60 70 80	D	(MHz)	30	10 400	500 60	0 700 1000.0	
No. M	· · · ·	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	
1	31.9546	26.25	4.23	30.48	40.00	-9.52	peak	
	10 0505	17.05	0.00	00.00	10.00	40.00		
2	43.0505	17.25	6.68	23.93	40.00	-16.07	· ·	
3	140.3421	9.78	19.62	29.40	43.50	-14.10	peak	
3	140.3421 202.8104	9.78 11.96	19.62 19.80	29.40 31.76	43.50 43.50	-14.10 -11.74	peak peak	
3 4 5	140.3421	9.78 11.96 10.94	19.62 19.80 21.93	29.40 31.76 32.87	43.50 43.50 46.00	-14.10 -11.74 -13.13	peak peak peak	

RADIATED EMISSION BELOW 1GHz

RESULT: PASS



		RADIATED	EMISSION	BELOW 1	GHz			
EUT	Wireless	Car Charge	r	Model	Name		MPQ5A	
Temperature	22° C			Relativ	e Humidit	t y	55%	
Pressure	960hPa			Test Vo	oltage	I	Normal Voltag	
Test Mode	Mode 1			Antenn	na	`	Vertical	
72.0 dBu∀/m					White and the street		Limit: — Margin: —	
-9 30.000 40	50 60 70	80	(MHz)	3	00 400	500 (500 700 1000	
		Deedine	Ormert					
No.	Mk. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	
1	* 35.0048	21.75	13.23	34.98	40.00	-5.02	peak	
2	64.8865	11.22	17.99	29.21	40.00	-10.79	9 peak	
3	4.40,0005	18.36	17.22	35.58	43.50	-7.92	peak	
0	143.8295	10.00						
4	143.8295		17.19	35.24	43.50	-8.26	peak	
		18.05	17.19 20.94	35.24 32.98		-8.26 -13.02	-	

RADIATED EMISSION BELOW 1GHz

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

- 2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.
- 3. The "Factor" value can be calculated automatically by software of measurement system.



7. 20 dB BANDWIDTH

7.1 PROVISIONS APPLICABLE

N/A

7.2 MEASUREMENT PROCEDURE

Set the parameters of SPA as below:

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. Centre frequency = Operation Frequency
- 3. The resolution bandwidth of 300 Hz and the video bandwidth of 1 kHz were used.
- 4. Span: 3kHz, Sweep time: Auto
- 5. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 6. Measured the spectrum width with power higher than 20dB below carrier.
- 7. Measured the 99% OBW.
- 8. Record the plots and Reported.

7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)



Spectrum Analyzer



7.4 MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and -20dB Bandwidth								
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (kHz)	-20dB Bandwidth (kHz)	Limits (MHz)	Pass or Fail			
FSK	0.1382	0.729	0.816	N/A	Pass			

Test Graphs of Occupied Bandwidth&-20dB Bandwidth

Agilent Spectrum Analyzer - Occupied BW	ORREC	SENSE:INT	ALIGN AUTO	11:55:25 A	MOct 12, 2022		
Center Freq 138.200 kHz		Center Freq: 138.200 Trig: Free Run		Radio Std		Fre	quency
#1	Gain:Low #Atten: 10 dB		Avginoid.> iono	Radio Device: BTS			
10 dB/div Ref 10.00 dBm Log							
0.00						С	enter Freq
-10.0							131.000 kHz
-20.0							
-30.0							
-40.0							
-60.0							
-70.0							
-80.0							
Center 138.2 kHz				Sr	oan 3 kHz		05.04
#Res BW 300 Hz	#VBW 1 kHz				40.87 ms		CF Step 300 Hz
Occupied Bandwidth		Total Po	wer -27.	7 dBm		<u>Auto</u>	Man
	7 29 H					_	
						F	req Offset 0 Hz
Transmit Freq Error	-44	Hz OBW Po	ower 9	9.00 %			0112
x dB Bandwidth	816 I	Hz xdB	-20	.00 dB			
MSG			STAT	IS			
			UIAN				



8. AC POWER LINE CONDUCTED EMISSION TEST

8.1 LIMITS OF LINE CONDUCTED EMISSION TEST


Fragmenta	Maximum RF Line Voltage			
Frequency	Q.P. (dBµV)	Average (dBµV)		
150kHz~500kHz	66-56	56-46		
500kHz~5MHz	56	46		
5MHz~30MHz	60	50		

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

8.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





8.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

8.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

8.5 MEASUREMENT RESULTS

Not Applicable

Note: The EUT was supplied by DC source and does not require evaluation of AC Power Line Conducted Emission.



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC12678220806AP02

APPENDIX B: PHOTOGRAPHS OF TEST EUT

Refer to the Report No.: AGC12678220806AP03

-----END OF REPORT-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.