

TEST REPORT

Report Number: 100967210ATL-001

November 15, 2012

Product Designation: 99112

Standard: 47 CFR Part 15, Subpart C (15.231 - Periodic operation in the band 40.66-40.70 MHz and above 70 MHz)
RSS-210, Issue 8, 2010

Tested by:

Intertek Testing Services NA Inc.
1950 Evergreen Blvd., Suite 100
Duluth, GA 30096

Client:

Hunter Fan
7130 Goodlett Farms Parkway, Ste 400
Memphis, TN 38016
Contact: Robert Davis
Phone: 901-248-2212
Fax: 901-248-2382
rdavis@hunterfan.com

Tests performed by:



Jeremy O. Pickens
Senior Staff Engineer

Report reviewed by:



Richard C. Bianco
EMC Team Leader

All services undertaken are subject to the following general policy: This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST, or any agency of the US Government.

1.0 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 3.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested complies with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested.

2.0 Test Summary

Section	Test Full Name	Test Date	Result
4.0	System setup including cable interconnection details, support equipment and simplified block diagram. (System Setup)		
5.0	Overview of EUT (Low Power Transmitters) (EUT Overview)		
6.0	Restrictions (FCC 15C-15.231 / RSS-210 A1.1)		
7.0	Duty Cycle Determination (FCC 15A-15.35(c) / RSS-GEN 4.5)	11/15/2012	
8.0	Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)	11/15/2012	PASS
9.0	Bandwidth Requirements (FCC 15.231(c) / RSS-210 A1.1.3)	11/15/2012	PASS
NA	Conducted Emissions for Intentional Radiators (FCC 15.207 / RSS-GEN 7.2.4) was waived due to the device was battery-powered.		

3.0 Description of Equipment Under Test

Equipment Under Test			
Description	Manufacturer	Model Number	Serial Number
Ceiling Fan Remote	Hunter Fan	99112	N/A

EUT receive date:	November 7, 2012
EUT receive condition:	Good

Description of EUT provided by Client:

The EUT was a hand held wireless transmitter used for remote control of a ceiling fan and light assembly.

Description of EUT exercising:


During testing, the device was powered from a new internal CR2032 battery and configured to transmit continuously.

4.0 System setup including cable interconnection details, support equipment and simplified block diagram. (System Setup)

Method:

Record the details of EUTcabling, document the support equipment, and show the interconnections in a block diagram.

Drawing:



Setup Diagram

4.0 System setup including cable interconnection details, support equipment and simplified block diagram. (System Setup)

EUT Cabling						
ID	Description	Length	Shielding	Ferrites	Connection	
					From	To
None						

Support Equipment			
Description	Manufacturer	Model Number	Serial Number
None			

5.0 Overview of EUT (Low Power Transmitters) (EUT Overview)

Method:

Complete the overview spreadsheet.

Related Submittal(s) Grants: This report is for use with an application for certification of a low power transmitter. One transmitter is included in the application.

Data:

Applicant	Hunter Fan Company
	7130 Goodlett Parkway, Suite 400
	Memphis, TN 38016
Trade Name & Model No.	99112
FCC Identifier	IN2TX37
IC Identifier	3558A-TX37
Frequency Range (MHz)	434
Antenna Type (15.203)	Integral
Manufacturer name & address	Shenzhen H and T Intelligent Control Co.,Ltd Shenzhen , Guangdong, CHINA
Related Submittals and Grants:	This report is for use with an application for certification of a low power transmitter. One transmitter is included in the application.
Additions, deviations and exclusions from standards	None


6.0 Restrictions (FCC 15C-15.231 / RSS-210 A1.1)

Method:

15.231(a) The provisions of this section are restricted to periodic operation within the band 40.66-40.70 MHz and above 70 MHz. Except as shown in paragraph (e) of this section, the intentional radiator is restricted to the transmission of a control signal such as those used with alarm systems, door openers, remote switches, etc. Continuous transmissions, voice, video and the radio control of toys are not permitted. Data is permitted to be sent with a control signal. The following conditions shall be met to comply with the provisions for this periodic operation:

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.
- (4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition
- (5) Transmission of set-up information for security systems may exceed the transmission duration limits in paragraphs (a)(1) and (a)(2) of this section, provided such transmissions are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data.

Plot:



Date: 15.NOV.2012 15:12:48

10s Plot

6.0 Restrictions (FCC 15C-15.231 / RSS-210 A1.1)

15.231(a), RSS-210 A1.1	Response	Requirement
Frequency Range (Mhz, max)	433.9	40.66-40.70 MHz and > 70MHz
Frequency Range (MHz, min)	433.9	40.66-40.70 MHz and > 70MHz
Transmit only control signal?	Yes	Only control signal allowed
Continuous transmission?	No	No
Voice transmission?	No	No
Video transmission?	No	No
Radio control of toy?	No	No

15.231(a)(1), RSS-210 A1.1.1(a)

Manually operated?	Yes	
Deactivates within 5 seconds?	Yes	Yes
Show plot (10 second sweep)	Present	

15.231(a)(2), RSS-210 A1.1.1(b)

Automatically operated?	No	
Deactivates within 5 seconds?	N/A	
Show plot (10 second sweep)	N/A	

15.231(a)(3), RSS-210 A1.1.1(c)

Periodically transmits at predetermined intervals?	No	Allowed, with restrictions
Polling signals?	No	Allowed, with restrictions
Polling rate and timing	N/A	< 2 seconds per hour

15.231(a)(4), RSS-210 A1.1.1(d)


For Emergency Use?	No	Allowed
--------------------	----	---------

15.231(a)(5)

Exceed 15.231(a)(1) or (a)(2) requirements?	No	Allowed for professional install
---	----	----------------------------------

7.0 Duty Cycle Determination (FCC 15A-15.35(c) / RSS-GEN 4.5)

Plot:




Date: 15.NOV.2012 15:15:01

100ms Plot - Full Pulse Train

7.0 Duty Cycle Determination (FCC 15A-15.35(c) / RSS-GEN 4.5)

Plot:




Date: 15.NOV.2012 15:15:50

Pulse Train - 0-14ms (Pulse Width 1)

7.0 Duty Cycle Determination (FCC 15A-15.35(c) / RSS-GEN 4.5)

Plot:




Date: 15.NOV.2012 15:16:59

Pulse Train - 14-34ms (Pulse Width 2)

7.0 Duty Cycle Determination (FCC 15A-15.35(c) / RSS-GEN 4.5)

Plot:




Date: 15.NOV.2012 15:20:22

Pulse Train - 34-54ms (Pulse Width 3)

7.0 Duty Cycle Determination (FCC 15A-15.35(c) / RSS-GEN 4.5)

Plot:




Date: 15.NOV.2012 15:20:43

Pulse Train - 54-74ms

7.0 Duty Cycle Determination (FCC 15A-15.35(c) / RSS-GEN 4.5)

Plot:



Date: 15.NOV.2012 15:21:07

Pulse Train - 74-94ms

7.0 Duty Cycle Determination (FCC 15A-15.35(c) / RSS-GEN 4.5)

Duration of Pulse Train, T (mSec): 105
 Averaging Interval, A_I (mSec): 100
 Number of different Pulses, N: 3

	Number (#P _x)	Pulse Width, mSec (PW _x)	Product (#P _x)*(PW _x)
Pulse Width 1	12	0.404	4.848
Pulse Width 2	33	0.833	27.489
Pulse Width 3	33	0.417	13.761
Pulse Width 4			
Pulse Width 5			
Pulse Width 6			
Pulse Width 7			
Pulse Width 8			
Pulse Width 9			
Pulse Width 10			

Duty Cycle: 0.46098
 Duty Cycle Correction Factor, dB: -6.7

$$T_{on} = (PW_1 * \#P_1) + (PW_2 * \#P_2) + \dots + (PW_n * \#P_n)$$

$$DutyCycle = T_{on} \div A_I$$

$$DCCF = 20 * \text{Log}_{10}(DutyCycle)$$

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)

Method:

(b) In addition to the provisions of §15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the limits specified in FCC Part 15.231(b).

Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in §15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

For radiated emission measurements, the EUT is attached to a styro-foam block and placed on a non-conductive table whose top is 80cm above the ground plane. If the EUT is handheld, the signal shall be aximized through rotation and placement in the three orthogonal axes.

During the test the EUT is rotated and the antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters.

Radiated emissions are taken at 3 meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. All readings are extrapolated back to the equivalent 3-meter reading using inverse scaling with distance.

Radiated emission measurements were performed from 30 MHz to 10 times the highest frequency generated in the EUT. When provided, emissions plots are taken with a peak detector unless otherwise indicated.

Analyzer resolution is:

- 100 kHz or greater for frequencies 1000 MHz and below,
- 1 MHz for frequencies above 1000 MHz.

Equipment setup for radiated disturbance tests shall follow the guidelines of ANSI C63.4:2003.

The Peak value of the Field Strength was measured. The Average value was obtained from the Peak by subtracting the Duty Cycle Correction Factor or by using an average detector.


Test Equipment Used:

Description:	Manufacturer:	Model:	Asset Number:	Cal Date:	Cal Due:
7m Cable, 0.01-18GHz	Storm Products Co.	A81-0303-275.6	ST-5	07/25/2012	07/25/2013
7m Cable, 0.01-18GHz	Storm Products Co.	A81-0303-275.6	ST-4	07/25/2012	07/25/2013
Antenna, BiLog, 20-2000MHz	Chase	CBL6112A	211518	02/21/2012	02/21/2013
Antenna, Horn, <18 GHz	EMCO	3115	213061	07/19/2012	07/19/2013
Cable MP3, 18 GHz, N, 10m	Megaphase	G919-NKNK-394	MP3	05/07/2012	05/07/2013
Cable, 3-meters, 1-18GHz	Megaphase	EM18-N1N1-119	MP-HF-1	06/28/2012	06/28/2013
Cable, 3-meters, 1-18GHz	Megaphase	EM18-N1N1-119	MP-HF-2	06/28/2012	06/28/2013
Cable, N-N 3 meters, 18GHz	Megaphase	TM18 NKNK 118	E203	05/07/2012	05/07/2013
Cable, N-N, 3 meters, 18GHz	Megaphase	TM18-NKNK-118	E206	05/07/2012	05/07/2013
EMI Receiver	Hewlett Packard	8546A	213109	12/29/2011	12/29/2012
EMI Receiver, Preselector section	Hewlett Packard	85460A	213108	12/29/2011	12/29/2012
Excel spreadsheet for radiated emissions	Software	Excel - RE Worksh	SW004	12/08/2011	12/08/2012
Filter, 1 GHz High Pass	Filtek	HP12/1000-5AB	213156a	07/06/2012	07/06/2013
Preamplifier, 10 MHz to 2000 MHz, 30 dB gain	Mini-Circuits	ZKL-2	200069	07/19/2012	07/19/2013
Preamplifier, 20 MHz to 18 GHz, 40 dB	A.H. Systems	PAM-0118	200108	05/22/2012	05/22/2013
Spectrum Analyzer, 20Hz-50GHz	Rohde & Schwarz	FSU 50	100005	12/07/2011	12/07/2012
Tile - software profile for radiated and conducted emissions testing.	Software	Tile - Emissions	SW006	12/08/2011	12/08/2012

Results: The sample tested was found to Comply.

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)


Plot:



Peak Plot - 30-1000MHz - X-Axis

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)


Plot:



Peak Plot - 1-5GHz - X-Axis

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)


Plot:



Peak Plot - 30-1000MHz - Y-Axis

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)


Plot:



Peak Plot - 1-5GHz - Y-Axis

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)


Plot:



Peak Plot - 30-1000MHz - Z-Axis

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)

Plot:



Peak Plot - 1-5GHz - Z-Axis

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)

Date: 10/25/2012

Frequency Range (MHz): 1000-5000

Test Distance (m): 3

Input power: 3.3Vdc CR2032 Battery

Modifications for compliance (y/n): n

A	B	C	D	E	F	G	H	I	J	K	
Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Duty Cycle Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Axis / Detector	
v	433.943	94.8	17.1	3.9	37.1	0.0	78.7	100.8	-22.1	X / Peak	
v	433.943	94.8	17.1	3.9	37.1	6.7	72.0	80.8	-8.8	X / Peak	
h	433.943	85.2	17.2	3.9	37.1	0.0	69.2	100.8	-31.6	X / Peak	
h	433.943	85.2	17.2	3.9	37.1	6.7	62.5	80.8	-18.3	X / Peak	
v	433.943	96.2	17.1	3.9	37.1	0.0	80.1	100.8	-20.7	Y / Peak	
v	433.943	96.2	17.1	3.9	37.1	6.7	73.4	80.8	-7.4	Y / Peak	
h	433.943	90.6	17.2	3.9	37.1	0.0	74.6	100.8	-26.2	Y / Peak	
h	433.943	90.6	17.2	3.9	37.1	6.7	67.9	80.8	-12.9	Y / Peak	
v	433.943	96.6	17.1	3.9	37.1	0.0	80.5	100.8	-20.3	Z / Peak	
v	433.943	96.6	17.1	3.9	37.1	6.7	73.8	80.8	-7.0	Z / Peak	
h	433.943	92.0	17.2	3.9	37.1	0.0	76.0	100.8	-24.8	Z / Peak	
h	433.943	92.0	17.2	3.9	37.1	6.7	69.3	80.8	-11.5	Z / Peak	
h	867.886	56.1	21.5	5.7	36.4	0.0	46.9	80.8	-33.9	X / Peak	
h	867.886	56.1	21.5	5.7	36.4	6.7	40.2	60.8	-20.6	X / Peak	
Calculations		G=C+D+E-F			I=G-H						

Note: X, Y, and Z denote the EUT was placed in the X, Y and Z orthogonal axes.

Note: P indicates peak detection. A indicates the peak reading corrected by the duty cycle.

Tabular Data - 30-1000MHz

8.0 Radiated Emissions (FCC 15.231(b) / RSS-210 A1.1.2)

Data:

Date: 10/25/2012

Frequency Range (MHz): 1000-5000

Test Distance (m): 3

Input power: 3.3Vdc CR2032 Battery

Modifications for compliance (y/n): n

A	B	C	D	E	F	G	H	I	J	K	
Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Duty Cycle Factor dB	Net dB(uV/m)	3m Limit dB(uV/m)	Margin dB	Axis / Detector	
X-Axis											
h	1301.829	64.1	25.6	2.8	37.2	0.0	55.2	74.0	-18.8	X / Peak *	
h	1301.829	64.1	25.6	2.8	37.2	6.7	48.5	54.0	-5.5	X / Peak *	
v	1735.772	52.5	25.8	2.1	37.5	0.0	42.8	74.0	-31.2	X / Peak *	
v	1735.772	52.5	25.8	2.1	37.5	6.7	36.1	54.0	-17.9	X / Peak *	
h	3471.544	48.0	31.0	3.2	37.9	0.0	44.3	80.8	-36.5	X / Peak	
h	3471.544	48.0	31.0	3.2	37.9	6.7	37.6	60.8	-23.2	X / Peak	
Y-Axis											
h	1301.829	68.0	25.6	2.8	37.2	0.0	59.1	74.0	-14.9	Y / Peak *	
h	1301.829	68.0	25.6	2.8	37.2	6.7	52.4	54.0	-1.6	Y / Peak *	
v	1301.829	66.2	25.8	2.8	37.2	0.0	57.5	74.0	-16.5	Y / Peak *	
v	1301.829	66.2	25.8	2.8	37.2	6.7	50.8	54.0	-3.2	Y / Peak *	
h	1735.772	58.8	25.9	2.1	37.5	0.0	49.2	74.0	-24.8	Y / Peak *	
h	1735.772	58.8	25.9	2.1	37.5	6.7	42.5	54.0	-11.5	Y / Peak *	
h	3037.601	52.8	30.0	3.2	37.7	0.0	48.3	80.8	-32.5	Y / Peak	
h	3037.601	52.8	30.0	3.2	37.7	6.7	41.6	60.8	-19.2	Y / Peak	
h	3905.481	43.7	32.5	3.3	37.8	0.0	41.7	74.0	-32.3	Y / Peak	
h	3905.481	43.7	32.5	3.3	37.8	6.7	35.0	54.0	-19.0	Y / Peak	
Z-Axis											
v	1301.829	68.8	25.8	2.8	37.2	0.0	60.1	74.0	-13.9	Z / Peak *	
v	1301.829	68.8	25.8	2.8	37.2	6.7	53.4	54.0	-0.6	Z / Peak *	
h	1735.772	66.2	25.9	2.1	37.5	0.0	56.6	74.0	-17.4	Z / Peak *	
h	1735.772	66.2	25.9	2.1	37.5	6.7	49.9	54.0	-4.1	Z / Peak *	
h	2603.658	52.6	28.8	2.7	37.7	0.0	46.4	80.8	-34.4	Z / Peak	
h	2603.658	52.6	28.8	2.7	37.7	6.7	39.7	60.8	-21.1	Z / Peak	
h	3037.601	53.0	30.0	3.2	37.7	0.0	48.5	80.8	-32.3	Z / Peak	
h	3037.601	53.0	30.0	3.2	37.7	6.7	41.8	60.8	-19.0	Z / Peak	
h	3905.601	44.7	32.5	3.3	37.8	0.0	42.7	80.8	-38.1	Z / Peak	
h	3905.601	44.7	32.5	3.3	37.8	6.7	36.0	60.8	-24.8	Z / Peak	
Calculations		G=C+D+E-F			I=G-H						

Note: X, Y, and Z denote the EUT was placed in the X, Y and Z orthogonal axes.

Note: P indicates peak detection. A indicates the peak reading corrected by the duty cycle.

* Restricted band of operation

Tabular Data - 1000-5000MHz

9.0 Bandwidth Requirements (FCC 15.231(c) / RSS-210 A1.1.3)

Method:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.


- Center Frequency is set to the fundamental of transmitter.
- Resolution Bandwidth is set to approximately 1% of the emission bandwidth.
- Video Bandwidth is set greater than or equal to the Resolution Bandwidth.

Test Equipment Used:

Description:	Manufacturer:	Model:	Asset Number:	Cal Date:	Cal Due:
Spectrum Analyzer, 20Hz-50GHz	Rohde & Schwarz	FSU 50	100005	12/07/2011	12/07/2012

Results: The sample tested was found to Comply.

Plot:




Date: 15.NOV.2012 04:39:53

20dB Bandwidth

9.0 Bandwidth Requirements (FCC 15.231(c) / RSS-210 A1.1.3)

Plot:



Date: 15.NOV.2012 04:42:54

Occupied Bandwidth

9.0 Bandwidth Requirements (FCC 15.231(c) / RSS-210 A1.1.3)

Fundamental Frequency MHz	Measured Bandwidth MHz	Bandwidth Limit MHz
20dB Bandwidth		
433.9	0.132	1.08475
99% Bandwidth		
433.9	0.607	1.08475

Suggested Instrument Settings	
RBW (kHz):	11
VBW (kHz):	33
Span (MHz):	1.085
Sweep time (s):	>1