



RF Exposure Calculation

Exposure of Humans to RF Fields Requirements

Applicant : Kenwood Corporation
Type of Equipment : GPS NAVIGATION SYSTEM
Model No. : DNX9960
FCC ID : IOM39622A

Regulations Applied : CFR 47 FCC 15.247
References Documents : CFR 47 FCC 2.1091, 2.1093 and OET65 Appendix A

RF Exposure Calculations :

The following minimum separation distance between the EUT's antenna and the human body was calculated in accordance with FCC OET65 Appendix A Table(B) "Limit for General Population / Uncontrolled Exposure".

The maximum permissible exposure level is defined with $1\text{mW}/\text{cm}^2$.

The minimum separation distance where the exposure level reaches the permitted level can be calculated as bellow:

Where:
$$S = P * G / 4\pi R^2$$

R = 20.0 cm (Separation distance)

P = 1.403 mW (= 1.47 dBm Max. conducted output power at antenna terminal)

G = 0.646(numeric gain) (= -1.9 dBi Max. antenna Gain)

S = Calculated Value

($S_{\text{Limit}} = 1.0 \text{ mW}/\text{cm}^2$ for 2.4 GHz (Max. permissible exposure level))

Then $S = 0.000180 \text{ mW}/\text{cm}^2$.

The calculated value is under the Maximum permissible exposure level.

Summary:

The EUT complies with the RF exposure requirement of the above regulation.

Eiichi Saegusa
Manager

Japan Quality Assurance Organization
SAFETY & EMC CENTER
EMC Engineering Dept. Testing Division