



Issue Date : March 2, 2010  
Page 1 of 1

## RF Exposure Calculation

### Exposure of Humans to RF Fields Requirements

---

Applicant	:	Kenwood Corporation
Type of Equipment	:	MONITOR WITH DVD RECEIVER
Model No.	:	DDX896
FCC ID	:	IOM39623

---

Regulations Applied : CFR 47 FCC 15.247  
References Documents : CFR 47 FCC 2.1091, 2.1093 and OET65 Appendix A

#### RF Exposure Calculations :

The following minimum separation distance between the EUT's antenna and the human body was calculated in accordance with FCC OET65 Appendix A Table(B) "Limit for General Population / Uncontrolled Exposure".

The maximum permissible exposure level is defined with  $1\text{mW/cm}^2$ .

The minimum separation distance where the exposure level reaches the permitted level can be calculated as bellow:

$$S = P * G / 4\pi R^2$$

Where:

R = 20.0 cm (Separation distance)

P = 1.094 mW (= 0.39 dBm Max. conducted output power at antenna terminal)

G = 0.646 (numeric gain) (= -1.9 dBi Max. antenna Gain)

S = Calculated Value


( $S_{\text{Limit}} = 1.0 \text{ mW/cm}^2$  for 2.4 GHz (Max. permissible exposure level))

Then S = 0.000141 mW/cm<sup>2</sup>.

The calculated value is under the Maximum permissible exposure level.

#### Summary:

The EUT complies with the RF exposure requirement of the above regulation.

  
\_\_\_\_\_  
Eiichi Saegusa  
Manager  
Japan Quality Assurance Organization  
SAFETY & EMC CENTER  
EMC Engineering Dept. Testing Division