<u>RF Exposure / SAR Statement</u> No.: 13294722S

| Applicant | : | JVCKENWOOD Corporation |
|--------------------|---|------------------------------|
| Type of EUT | : | GPS NAVIGATION SYSTEM |
| Model Noumber of E | : | DNR1007XR |
| FCC ID | : | IOMJ5240 |

JVCKENW OOD Corporation declares that Model : DNR1007XR complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091(for mobile). DNR1007XR is intended to be used Bluetooth and Wireless LAN simultaneously within 20 cm.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "DNR1007XR" as calculated from FCC Part 1, §1.1310, TA BLE 1 (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm^2 uncontrolled exposure limit. The Friis formula used was:

S = ((P1 * G1) + (P2 * G2)) / (4*
$$\pi$$
 * r²)

Where

| P1 = | 0.97 | mW (Maximum average output power) *1) | | | | |
|------|-------|---|-------|----------------|--|--|
| P2 = | 18.88 | mW (Maximum average output power) *2) | | | | |
| G1 = | 0.27 | Numerical Antenna gain; equal to | -5.70 | dBi *1) | | |
| G2 = | 0.69 | Numerical Antenna gain; equal to | -1.60 | dBi *2) | | |
| r = | 20.0 | cm | | | | |

For: DNR1007XR (Bluetooth and Wireless LAN)

 $S = 0.00265 \text{ mW/cm}^2$

Even taking into account the tolerance, this device can be satisfied with the limits.

*1) Bluetooth value

*2) Wireless LAN (2.4 GHz band) value

This calculation was made to show that the EUT complies with the limit in simultaneous transmitting of Bluetooth and Wireless LAN.

UL Japan, Inc. Shonan EMC Lab.

 1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220
 JAPAN

 Telephone
 :
 +81 463 50 6400

 Facsimile
 :
 +81 463 50 6401