

## **CO-5P RF and Optical Mouse with Charger Specification**

### **1.Preface:**

The functionality and performance requirements related to the mouse are defined in this specification.

### **2.Version:**

#### **2.1 Radio Frequency**

27MHz, Dual Channels, 256 Changeable ID/Per Channel

#### **2.2 Interface**

PS/2 Interface


USB Interface

PS/2,USB Combo

### **3.Physical Characteristics and Configuration:**

#### **3.1 Dimension (Ref)**

Mouse	125.1mm(L)*68.3mm(W)*36.5mm(H)
Receiver	114mm(L)*99.5mm(W)*81.7mm(H)



#### **3.2 Material**

Mouse	Body	ABS
	Wheel	Rubber
Receiver	Body	ABS

- 3.3 Finish            Texture
- 3.4 Color            To be defined by ID
- 3.5 Button
  - Mouse            5 buttons, 1 scroll wheel, 1 ID switch, and 1 channel switch.
  - Receiver        1 ID switch and 1 channel switch
- 3.6 Mechanical Performance (Ref)
  - 3.6.1 Operating force of mouse buttons:  $80 \pm 20\text{gf}$
  - 3.6.2 Operating force of browser switches:  $170 \pm 25\text{gf}$
  - 3.6.3 Operating force of wheel scrolling:  $20 \pm 10\text{gf}$
  - 3.6.4 Operating force of movable:  $60 \pm 10\text{gf}$
  - 3.6.5 Mouse Weight:  $140 \pm 15\text{g}$  With Battery

#### 4. Electrical Specification:

- 4.1 Compatibility

The PS/2 mode shall be compatible with IBM PC/XT/AT/386/486/PENTIUM and works with operating system such as DOS, Windows 95/98/2000/ME, and NT as well as the most software applications.
- 4.2 Technical on Mouse

Optical sensor for X/Y axis, the precise sensor detects motion on hundreds of surfaces, including wood, plastic, and even your pants leg. Wheel button uses a mechanical encoder.
- 4.3 Sensor Report Rate on Mouse

1500 times per second
- 4.4 Sensor Light on Mouse

Red LED
- 4.5 Power Requirement (**Receiver**)
  - 4.5.1 PS2 Mode
    - Operating voltage:  $5\text{VDC} \pm 5\%$
    - Operating current:  $30\text{mA}$  (max.)
  - 4.5.2 Adaptor for Power
    - Input:  $230\text{V/AC}$   $50\text{Hz}$
    - Output:  $6\text{V/DC}$   $300\text{mA}$
- 4.6 Cable

The length of the cable on receiver is 1.5 meters and the color is defined by ID.
- 4.7 Operation Angle

The mouse operation angle is 360 degrees.
- 4.8 Operation Distance

The RF mouse operation distance is 1 meter (mouse to receiver set).

#### 4.9 ID Changeable

The ID is changed by ID button.

#### 4.10 Battery

4.10.1 Rechargeable Battery Type: AAA \* 2

4.10.2 Battery Consumption: Mouse will be on sleep mode, while non-used after 90~100 seconds. Mouse works again, need to push any button on it.

Operation mode      55mA (max.)

Stand-by mode      30mA (max.)

Sleep mode      0.30mA (max.)

4.10.3 Battery Low Indicator: When the battery voltage is less than 2.3V, the indicator on the rubber wheel should be light while moving the mouse.

#### 4.11 Tracking Speed

The unit shall be capable of tracking between 50mm/s and 254mm/s of hand movement on the matt white paper without loss of data.

#### 4.12 Charging

Put the mouse on the charger (receiver) for charging 6~8hrs at least for 1' st using.

The charge indicator on the receiver is red LED. While charging current over 80~100mA, the charge LED will be light steadily. If charging current below 80~100mA, the indicator will be flash and the flash cycle time depends on the current strength.

#### 4.13 Data Transmission

The indicator for data transmission is green LED. While moving the mouse or changing the ID number, the LED will be flash. Otherwise, the indicator lights steadily.

### 5. Software:

Buttons Definition (Default):

Button	Left (1)	Right (2)	Wheel (3)	S-Left (4)	S-Right (5)
Click	Select	Context Menu	Scroll Up/Down	Scroll Left	Scroll Right
Double Click	Command				
Others			Programmable	Programmable	Programmable

Note:

1. Press and hold down both the 4th and 5th buttons about 3 seconds for returning to default setting.
2. 4D Browser Menu:
  - a. Browser Setup      Scroll Speed  
                                 Track Speed  
                                 Double Click Speed

Zoom-in size, factor

- b. Programmable Buttons - 3<sup>rd</sup> button programmable  
4<sup>th</sup> button programmable  
5<sup>th</sup> button programmable

## 6. Reliability Testing Specification:

Individual units must pass any and all of the following tests. The order of testing is subject to the tester. Passing the test is defined as functioning properly without significant damage; including but not limited to mechanical failure, electrical failure, chips or cracks in the housing or significant changes in the tactile feel.

### 6.1 Mean Time Between Failure (MTBF)

The unit shall have an expected MTBF under operating conditions of not less than 150,000 hours (on condition 6 hours per day operation, 250 days per year with 99% confidence level).

### 6.2 Button Switch Activation

The unit shall survive a minimum of 1,000,000 times (for all of the micro switches on mouse).  
Tested at 2 cycles per second.

### 6.3 Scroll Rotation

The unit shall be rotated a minimum of 100,000 cycles at a speed of 10 cycles per minutes without electrical load after which measurement shall be made.

### 6.4 Tracking Life

The unit shall survive a minimum of 100km at a speed of 10cm per second.

### 6.5 Drop Shock with Bare Unit

Drop the unit from 76cm height onto a concrete floor, on the top, bottom and 3 sides without cable side of the unit (1 time for each side). The unit should be without damage. Damage is defined as failure of the unit to function properly, chips in the housing, or mechanical failure of any of the parts.

### 6.6 Drop Shock in Gift Box

Drop the unit in box from 91cm onto a concrete floor, on the 4 corners and 6 sides of the box (1 time for each side). Resulting damage should be minimal and shall not allow for contents to escape from packaging.

### 6.7 Drop Shock in Carton

Unit shall survive a drop test in the weight of product carton on 1 corner, 3 edges and 6 sides from the height onto a concrete floor (1 time for each side).

</= 9.5kg-----91cm

</= 18.6kg-----76.2cm

</= 27.6kg-----61cm

$\leq 45.3\text{kg}$ ----- $45.7\text{cm}$

#### 6.8 High Temperature Test for Operating Pattern

The unit is kept at the temperature of 0 to 40 degrees Celsius and relative humidity of 0% to 95% for 250 hours and then left at ambient room temperature for 1 hour.

#### 6.9 Heat Cycle Test for Shipment Pattern

-40 degrees Celsius to 65 degrees Celsius under 0% to 90% relative humidity with total time of 40 hours, and then left at ambient room temperature for 2 hours.

#### 6.10 Cable Bending Strength

The cable must withstand bending 60 degrees any direction from its centerline; the detail testing conditions as followed:

Load: 100 grams force

Angle:  $\pm 60$  degrees around 25.4cm diameter

Speed: 30 cycles/min

Criteria: Min 5,000 cycles, with no visible damage and no breakage in each wire.

#### 6.11 Vibration

Unit shall survive a vibration within a frequency range of 10 to 200 Hz at 0.015 square of g/Hz and 200 to 500 Hz at -6 dB/Oct for X, Y, and Z axis and 0.5 hour per axis.

### 7. Reliability Performance:

After having been subjected to any and all of the reliability tests outlined in section 6.0, the unit shall meet the following performance specifications:

Button Actuation:

25~55 grams force at outer edge of button (minimum force of actuation)

40~80 grams force at the center of the button.

The buttons must be free from both pre-travel and over-travel.

Pre-travel occurs when the button or the keycap is permitted to move before it contacts the switch.

Over-travel occurs when the button or keycap continues to compress the switch after it is completely depressed.

### 8. Environmental Standards:

#### 8.1 Operating temperature and humidity

Temperature:  $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$

Humidity: 0% ~ 85% RH

#### 8.2 Storage temperature and humidity

Temperature:  $-30^{\circ}\text{C} \sim 60^{\circ}\text{C}$

Humidity: 0% ~ 90% RH

## 9.Safety and Standards:

The mouse is certified to comply with the limits for class B computing device pursuant, to subpart of part 15 of FCC rules and CE Mark.