

Test Report

1/16

Report No.

C3115523

FCC ID

IOW203UP

Specifications

FCC Part 15, Class B

Test Method

ANSI C63.4 1992

Applicant

Chic Technology Corp.

Applicant
address16F., No. 150, Chien-I Road, 235 Chung Ho City,
Taipei Hsien, Taiwan, R.O.C.

Items tested

Wireless Optical Mouse

Model No.

RMO 203UP (Sample # C31522)

Frequency Range

26.96MHz to 27.28MHz

Results

Compliance (As detailed within this report)

Date

03/26/2003 (month / day / year)(Sample received)

04/02/2003 (month / day / year)(Tested)

Prepared by

Project Engineer

Authorized by

V. General Manager
(Jacob Lin)

Issue date

May 21, 2003

(month / day / year)

Modifications

None

Tested by

Training Research Co., Ltd. (**Accredited by NVLAP**)

Office at

1F, No. 255, Nan Yang Street, Hsichih, Taipei Hsien 221, Taiwan

Open site at

No. 15, Lane 530, Pa-Lian RD., Sec. 1, Hsichih City, Taipei Hsien, Taiwan, R.O.C.

Conditions of issue :

- *This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.*
- *The test data in this test report are following the procedures in accordance with the terms of accreditation.*
- *This test report and measurements made by TRC are traceable to the NIST only Conducted and Radiated Method (TRC is accredited by NVLAP, code No.: 200174-0).*
- *The device has been tested is fully complied with the requirements the Directive FCC Part 15.*

Report No.: C3115523

Training Research Co., Ltd., TEL: 886-2-26461146, Fax: 886-2-26461778

Contents

Chapter 1 Introduction

Description of EUT	3
Configuration of Test Setup	4
List of Support Equipment	5

Chapter 2 Conducted Emission Test

Test Condition and Setup	6
Conducted Test Placement	7

Chapter 3 Peak Power Measurement (Frequency Band: 26.96 ~ 27.28)

Test Setup	8
Test Procedure	8

Chapter 4 Radiated Emission Test

Test Condition and Setup	9
Radiated Test Placement	10

Appendix A:

Conducted test result	11
-----------------------------	----

Appendix B:

Peak Power and Radiated test result	13
---	----

Appendix C:

Band Edge of Measurement	15
--------------------------------	----

Chapter 1 Introduction

Description of EUT:

EUT : Wireless Optical Mouse
Model No. : RMO 203UP
Product name : Wireless Optical Mouse
Frequency Range : 26.96 – 27.28 MHz
Power Type : Transmitter: Powered by two 1.5VDC AA batteries

*This EUT has two channels (each with 256 IDs):

1. 27.1000 MHz
2. 27.0500 MHz

Test method:

Pretest was found that the emission of operating mode is worse than standby mode. So, The final test is made at the operating mode.


During the measurement, there are two channel and four modes tested: “Transmitting used Channel 1“, “Transmitting used Channel 2“, “Charging 110V/60Hz” and “Charging 230V/50Hz” modes. The radiation pretest was found out the testing mode: “Transmitting used Channel 1” was the worst case and we only recorded worse cases in this report.

While testing, the EUT was made to transmit continuously and adjusted at a position, which transmitted the maximum emission.

The test placement as the photographs showed is the worst emission placed. (If the emission is close to the ambient, the resolution BW and view resolution will be reduced and the data will be recorded by detection of maximum hold peak mode.)

The testing configuration of test setup is showing in the next page.

Configuration of Test Setup (Test mode: “Transmitting”)




Connections:

EUT:

- *Put two AA size, 1.5V battery into the battery cell of EUT, powers the subject device.
- The EUT does not be connected with any product.

Configuration of Test Setup (Test mode: “Charging by Adaptor”)



Connections:

EUT(Tx):

- *Put two AA size, 1.5V battery into the battery cell of EUT, powers the subject device.
- Put the EUT(Tx) on the EUT(Rx) to charge.

EUT(Rx):

- *USB Jack --- with a 142cm long shielded USB cable that terminated.
- *Power Jack --- via a 1.86m long power cable with a power adapter to the power source.

List of Support Equipment

Conducted (Radiated) test:

N/A

Chapter 2 Conducted Emission Test

Test Condition and Setup:

All the equipment is placed and setup according to the ANSI C63.4 – 1992. The EUT is assembled on a wooden table that is 80 cm high, is placed 40 cm from the back-wall that is a vertical conducting plane. One LISN is for EUT, the other LISN is for support equipment. They are all placed on the conductive ground. The EUT's LISN connect a line switch box for selecting L1 or L2, then connect to a preamplifier and Spectrum.

The spectrum measured from 150KHz to 30MHz. Conducted emission levels are detected at max. peak mode. But if the max. peak mode failed or over average limit, it will be measured by QP and average detection mode using the Receiver.

While testing, there is the worst-emission plot printed at peak detection mode, and there are more than 6 highest emissions relative to limit recorded. The plot is kept as the original data, not included in test report.

List of test Instrument :

<u>Instrument Name</u>	<u>Model No.</u>	<u>Brand</u>	<u>Serial No.</u>	<u>Calibration Date</u>	
				<u>Last time</u>	<u>Next time</u>
Receiver	SCR3102	SCHAFFNER	012	03/29/02	03/28/03
LISN (EUT)	3825/2	EMCO	9411-2284	06/17/02	06/16/03
LISN (Support E.)	3825/2	EMCO	9210-2007	05/31/02	05/31/03
Preamplifier	EQ3-006	TRC	-----	05/15/02	05/15/03
Line switch box	EQ3-007	TRC	-----	05/15/02	05/15/03

The level of confidence of 95% , the uncertainty of measurement of conducted emission is ± 2.02 dB .

Test Result: Pass (Appendix A)


Conducted Test Placement: (Photographs)(Test mode: Charging)



Chapter 3 Peak Power Measurement (Frequency Band: 26.96 ~ 27.28)

Test Setup:

1. Test Setup:



2. Test Procedure:

- The EUT was setup in the anechoic chamber as shown above.
- The loop antenna was located upon its plane vertical, 3-meter distance from the EUT. The center of the loop is 1-meter above the ground plane.
- In order to find the maximum radiation, the EUT was rotated 360°. The measuring antenna was rotated about its axis at each azimuth about the EUT.

List of test Instrument :

Instrument Name	Model No.	Brand	Serial No.	Calibration Date	
				Last time	Next time
Receiver	SCR3102	SCHAFFNER	012	03/29/03	03/28/04
Control Box	TWR95-4	TRC	C9001-2	N/A	N/A
Antenna	6502	EMCO	9206-2777	06/10/02	06/09/03
Open test side (Antenna, Amplify, cable calibrated together)				05/15/03	05/15/04

The level of confidence of 95% , the uncertainty of measurement of radiated emission is ± 3.44 dB .

Test Result : Appendix A

Chapter 4 Radiated Emission Test

Test Condition and Setup:

Pretest : Prior to the final test ,the EUT is placed in an anechoic chamber, and scan from 30MHz to 1GHz. The devices rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit. This is done to ensure the radiation exactly emits form the EUT.

Final test: Final radiation measurement was made on a **3 – meter** open-field test site. The EUT's maximum emission of radiation is placed on a nonconductive table, which is 0.8m height, the top surface is 1.0 x 1.5 meter. All placement is according to ANSI C63.4 - 1992.

The emissions was examined from 30 MHz to 1000 MHz measured by receiver.

The whole range Antenna is used to measure frequency from 30 MHz to 1 GHz. The final test is used the receiver.

Measure more than six top marked frequencies generated form pretest by computer step by step at each frequency. The EUT is rotated 360 degrees, and antenna is raised and lowered from 1 to 4 meters to find the maximum emission levels. The antenna is used with both horizontal and vertical polarization.

Appropriated preamplifier, which is made by TRC is used for improving sensitivity and precautions is taken to avoid overloading. The spectrum analyzer's 6dB bandwidth is set to 120 KHz, and the EUT is measured at quasi-peak mode.

If the emission is close to the frequency band of ambient, the tester will recheck the data and the corrected data will be written in the test data sheet. If the emission is just within the ambient, the data from shield room will be taken as the final data.

List of test Instrument :

Instrument Name	Model No.	Brand	Serial No.	<u>Calibration Date</u>	
				Last time	Next time
Receiver	SCR3102	SCHAFFNER	012	03/29/03	03/28/04
Control Box	TWR95-4	TRC	C9001-2	N/A	N/A
Antenna	CBL6141A	SCHAFFNER	4188	11/29/02	11/28/03
Open test side (Antenna, Amplify, cable calibrated together)				05/15/03	05/15/04

The level of confidence of 95% , the uncertainty of measurement of radiated emission is ± 3.44 dB .

Test Result : Pass (Appendix A)

Radiated Test Placement: (Photographs)



Appendix A

Conducted Emission Test Result: (Test mode: Charging 230V/50Hz)

Testing room : Temperature : 24 ° C Humidity : 66 % RH

Line 1

Frequency (KHz)	READING AMPLITUDE			LIMIT		Margin (dB)
	Peak (dBmV)	Quasi-Peak (dBmV)	Average (dBmV)	Quasi-Peak (dBmV)	Average (dBmV)	
329.00	20.64	***.**	***.**	60.89	50.89	-30.25
352.00	23.03	***.**	***.**	60.23	50.23	-27.20
371.00	20.52	***.**	***.**	59.69	49.69	-29.17
560.00	20.65	***.**	***.**	56.00	46.00	-25.35
701.00	20.52	***.**	***.**	56.00	46.00	-25.48
739.00	20.08	***.**	***.**	56.00	46.00	-25.92
1307.00	22.23	***.**	***.**	56.00	46.00	-23.77
20000.00	21.79	***.**	***.**	60.00	50.00	-28.21
21560.00	24.97	***.**	***.**	60.00	50.00	-25.03
23050.00	21.04	***.**	***.**	60.00	50.00	-28.96

Line 2

Frequency (KHz)	READING AMPLITUDE			LIMIT		Margin (dB)
	Peak (dBmV)	Quasi-Peak (dBmV)	Average (dBmV)	Quasi-Peak (dBmV)	Average (dBmV)	
416.00	24.99	***.**	***.**	58.40	48.40	-23.41
467.00	23.53	***.**	***.**	56.94	46.94	-23.42
493.00	23.80	***.**	***.**	56.20	46.20	-22.40
505.00	24.93	***.**	***.**	56.00	46.00	-21.07
521.00	23.10	***.**	***.**	56.00	46.00	-22.90
560.00	26.42	***.**	***.**	56.00	46.00	-19.58
582.00	26.30	***.**	***.**	56.00	46.00	-19.70
597.00	22.71	***.**	***.**	56.00	46.00	-23.29
620.00	23.57	***.**	***.**	56.00	46.00	-22.43
851.00	22.30	***.**	***.**	56.00	46.00	-23.70

***The reading amplitudes are all under limit.**

Conducted Emission Test Result: (Test mode: Charging 110V/60Hz)

Testing room : Temperature : 24° C Humidity : 66 % RH

Line 1

Frequency (KHz)	READING AMPLITUDE			LIMIT		Margin (dB)
	Peak (dBmV)	Quasi-Peak (dBmV)	Average (dBmV)	Quasi-Peak (dBmV)	Average (dBmV)	
150.00	21.89	***.***	***.***	66.00	56.00	-34.11
165.00	21.18	***.***	***.***	65.57	55.57	-34.39
173.00	20.18	***.***	***.***	65.34	55.34	-35.17
192.00	21.63	***.***	***.***	64.80	54.80	-33.17
212.00	21.70	***.***	***.***	64.23	54.23	-32.53
349.00	22.27	***.***	***.***	60.31	50.31	-28.05
560.00	20.72	***.***	***.***	56.00	46.00	-25.28
1257.00	20.39	***.***	***.***	56.00	46.00	-25.61
1324.00	23.19	***.***	***.***	56.00	46.00	-22.81
21560.00	30.32	***.***	***.***	60.00	50.00	-19.68

Line 2

Frequency (KHz)	READING AMPLITUDE			LIMIT		Margin (dB)
	Peak (dBmV)	Quasi-Peak (dBmV)	Average (dBmV)	Quasi-Peak (dBmV)	Average (dBmV)	
206.00	20.19	***.***	***.***	64.40	54.40	-34.21
215.00	21.07	***.***	***.***	64.14	54.14	-33.07
222.00	22.27	***.***	***.***	63.94	53.94	-31.67
352.00	21.51	***.***	***.***	60.23	50.23	-28.72
422.00	20.03	***.***	***.***	58.23	48.23	-28.20
560.00	20.87	***.***	***.***	56.00	46.00	-25.13
1307.00	21.41	***.***	***.***	56.00	46.00	-24.59
20000.00	22.74	***.***	***.***	60.00	50.00	-27.26
20960.00	37.66	***.***	***.***	60.00	50.00	-17.34
21560.00	22.09	***.***	***.***	60.00	50.00	-27.91

*The reading amplitudes are all under limit.

Appendix B

Peak Power Test Result: (Horizontal)

Frequency	Reading Amplitude	Correction Factors	Corrected Amplitude	Limit	Margin
MHz	dBμV/m	dB	dBμV/m	dBμV/m	dB
27.0500	69.46	-8.30	61.16	80.00	-18.84

Radiated Emission Test Result: (Horizontal)

Test Conditions:

Testing site : Temperature : 25 ° C Humidity : 73 % RH

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B Limit	Margin
MHz	dBμV/m	m	degree	dB	dBμV/m	dBμV/m	dB
54.0838	21.82	2.50	332	-6.21	15.61	40.00	-24.39
81.1488	29.75	2.50	284	-9.90	19.85	40.00	-20.15
108.1925	30.99	2.50	273	-6.37	24.62	43.52	-18.90
135.2388	30.43	2.50	309	-4.40	26.03	43.52	-17.49
162.2950	24.35	2.50	117	-5.59	18.76	43.52	-24.76
216.3950	34.21	1.00	118	-2.71	31.50	46.02	-14.52
270.4900	23.85	1.00	280	-1.10	22.75	46.02	-23.27
327.5875	12.72	1.00	252	0.27	12.99	46.02	-33.03

Note:

- Margin = Amplitude – limit, *if margin is minus means under limit.*
- Corrected Amplitude = Reading Amplitude – Correction Factors
- Correction factor = Antenna factor + (Cable Loss – Amplitude gain)
(For example : 30MHz correction factor = 15.5 + (–15.26) = 0.24 dB/m)

Peak Power Test Result: (Vertical)

Frequency	Reading Amplitude	Correction Factors	Corrected Amplitude	Limit	Margin
MHz	dBμV/m	dB/m	dBμV	dBμV/m	dB
27.0500	54.01	-8.30	45.71	80.00	-34.29

Radiated Emission Test Result: (Vertical)

Test Conditions:

Testing site : Temperature : 25 ° C Humidity : 73 % RH

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B Limit	Margin
MHz	dBμV/m	m	degree	dB	dBμV/m	dBμV/m	dB
54.0838	23.12	2.50	47	-6.21	16.91	40.00	-23.09
81.1468	25.27	2.50	191	-9.90	15.37	40.00	-24.63
108.1905	25.28	0.98	120	-6.37	18.91	43.52	-24.61
135.2380	27.21	0.98	326	-4.40	22.81	43.52	-20.71
162.2900	22.46	0.98	349	-5.59	16.87	43.52	-26.65
216.2900	29.47	0.98	282	-2.71	26.76	46.02	-19.26
243.4350	35.71	2.50	15	-2.26	33.45	46.02	-12.57
270.4900	21.71	2.50	34	-1.10	20.61	46.02	-25.41
327.5825	12.89	2.50	158	0.27	13.16	46.02	-32.86


Note:

1. Margin = Amplitude – limit, *if margin is minus means under limit.*
2. Corrected Amplitude = Reading Amplitude – Correction Factors
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)
(For example : 30MHz correction factor = 15.5 + (–15.26) = 0.24 dB/m)

Appendix C


Band Edge of Measurement: (Frequency Band: 26.96 ~ 27.28)

Lower channel



26.96MHz << Class B Limit.

Upper channel:



27.28 MHz >> Class B Limit.