

## FCC 47 CFR PART 15 SUBPART C

Product Type : VIRB Elite  
Applicant : Garmin International Inc.  
Address : 1200 E., 151st. Street, Olathe, Kansas, United States, 66062  
Trade Name : Garmin  
Model Number : O3AHGT01  
Test Specification : FCC 47 CFR PART 15 SUBPART C: Oct., 2012  
Canada RSS-210 ISSUE 8: Dec., 2010  
Canada RSS-Gen ISSUE 3: Dec., 2010  
ANSI C63.4-2009  
Receive Date : May 08, 2013  
Test Period : Jul. 02~Jul.16, 2013  
Issue Date : Jul. 30, 2013

### Issue by

A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade City,  
Taoyuan County 334, Taiwan R.O.C.  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

**Note:** This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

**Revision History**

Rev.	Issue Date	Revisions	Revised By
00	Jul. 30, 2013	Initial Issue	

## Verification of Compliance

Issued Date: 07/30/2013

Product Type : VIRB Elite  
Applicant : Garmin International Inc.  
Address : 1200 E., 151st. Street, Olathe, Kansas, United States, 66062  
Trade Name : Garmin  
Model Number : O3AHGT01  
FCC ID : IPH-02114  
EUT Rated Voltage : DC 5.0V  
Test Voltage : 120 Vac / 60 Hz  
Applicable Standard : FCC 47 CFR PART 15 SUBPART C: Oct., 2012  
Canada RSS-210 ISSUE 8: Dec., 2010  
Canada RSS-Gen ISSUE 3: Dec., 2010  
ANSI C63.4-2009



Test Result : Complied

Performing Lab. : A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade City,  
Taoyuan County 334, Taiwan R.O.C.  
Tel : +886-3-2710188 / Fax : +886-3-2710190  
Taiwan Accreditation Foundation accreditation number: 1330  
<http://www.atl-lab.com.tw/e-index.htm>



The above equipment was tested by A Test Lab Techno Corp. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2009 and the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247 .

The test results of this report relate only to the tested sample identified in this report.

Approved By :  (Manager)      Reviewed By :  (Testing Engineer)      (Fly Lu)

## TABLE OF CONTENTS

<b>1</b>	<b>General Information .....</b>	<b>6</b>
<b>2</b>	<b>EUT Description .....</b>	<b>7</b>
<b>3</b>	<b>Test Methodology .....</b>	<b>8</b>
3.1.	Mode of Operation.....	8
3.2.	EUT Exercise Software .....	8
3.3.	Configuration of Test System Details .....	9
3.4.	Test Site Environment .....	9
<b>4</b>	<b>Conducted Emission Measurement .....</b>	<b>10</b>
4.1.	Limit .....	10
4.2.	Test Instruments .....	10
4.3.	Test Setup.....	10
4.4.	Test Procedure .....	11
4.5.	Test Result.....	12
<b>5</b>	<b>Radiated Emission Measurement.....</b>	<b>14</b>
5.1.	Limit .....	14
5.2.	Test Instruments .....	14
5.3.	Setup .....	15
5.4.	Test Procedure .....	16
5.5.	Test Result.....	18
<b>6</b>	<b>Maximum Conducted Output Power Measurement.....</b>	<b>23</b>
6.1.	Limit .....	23
6.2.	Test Setup.....	23
6.3.	Test Instruments .....	23
6.4.	Test Procedure .....	23
6.5.	Test Result.....	24
<b>7</b>	<b>6dB RF Bandwidth and 99 % Occupied Bandwidth Measurement .....</b>	<b>25</b>
7.1.	Limit .....	25
7.2.	Test Setup.....	25
7.3.	Test Instruments .....	25
7.4.	Test Procedure .....	25
7.5.	Test Result.....	26
7.6.	Test Graphs .....	27
<b>8</b>	<b>Maximum Power Density Measurement .....</b>	<b>29</b>
8.1.	Limit .....	29
8.2.	Test Setup.....	29
8.3.	Test Instruments .....	29
8.4.	Test Procedure .....	29
8.5.	Test Result.....	30
8.6.	Test Graphs .....	31

<b>9</b>	<b>Out of Band Conducted Emissions Measurement .....</b>	<b>33</b>
9.1.	Limit .....	33
9.2.	Test Setup.....	33
9.3.	Test Instruments .....	33
9.4.	Test Procedure .....	33
9.5.	Test Graphs .....	34
<b>10</b>	<b>Band Edges Measurement .....</b>	<b>36</b>
10.1.	Limit .....	36
10.2.	Test Setup.....	36
10.3.	Test Instruments .....	36
10.4.	Test Procedure .....	37
10.5.	Test Result.....	38
<b>11</b>	<b>Antenna Measurement.....</b>	<b>46</b>
11.1.	Limit .....	46
11.2.	Antenna Connector Construction .....	46

## 1 General Information

### 1.1 Summary of Test Result

Standard		Item	Result	Remark
15.247	RSS-GEN			
15.207	7.2.2	AC Power Conducted Emission	PASS	----
----	6	Receiver Radiated Emissions	PASS	----
Standard		Item	Result	Remark
15.247	RSS-210			
15.247(d)	A8.5	Transmitter Radiated Emissions	PASS	----
15.247(b)(3)	A8.4	Max. Output Power	PASS	----
15.247(a)(2)	A8.2 (a)	6dB RF Bandwidth	PASS	----
15.247(e)	A8.2 (b)	Power Spectral Density	PASS	----
15.247(c)	A8.5	Out of Band Conducted Spurious Emission	PASS	----
15.247(d)	A8.5	Band Edge Measurement	PASS	----
15.247(c)	A8.5	Occupied Bandwidth Measurement	PASS	----
15.203	-	Antenna Requirement	PASS	----

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

### 1.2 Measurement Uncertainty

#### Conducted Emission

The measurement uncertainty is evaluated as  $\pm 2.24$  dB.

#### Radiated Emission

The measurement uncertainty is evaluated as  $\pm 3.072$ dB.

## 2 EUT Description

Product	VIRB Elite
Trade Name	Garmin
Model No.	O3AHGT01
Applicant	Garmin International Inc. 1200 E., 151st. Street, Olathe, Kansas, United States, 66062
Manufacturer	Garmin Corporation No.68, Zhangshu 2nd Rd., Xizhi Dist., New Taipei City 221, Taiwan
FCC ID	IPH-02114
Frequency Range	IEEE 802.11b / 802.11g: 2412 ~ 2462 MHz
Modulation Type	IEEE 802.11b:DSSS IEEE 802.11g:DSSS + OFDM
Antenna Type	Chip antenna
Antenna Gain	2.22 dBi
RF Output Power	IEEE 802.11b: 0.039 W / 15.90 dBm IEEE 802.11g: 0.046 W / 16.59 dBm

### 3 Test Methodology

#### 3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Normal Operation Mode
Mode 2: IEEE 802.11b Link Mode
Mode 3: IEEE 802.11g Link Mode
Mode 4: Receiver Mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

IEEE 802.11b mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE 802.11g mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.


#### 3.2. EUT Exercise Software

1. Setup the EUT shown on 3.3.
2. Turn on the power of all equipment.
3. Turn on Wi-Fi function link to AP.
4. EUT run test program.




### 3.3. Configuration of Test System Details

#### Conducted Emissions



#### Radiated Emissions



### 3.4. Test Site Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950

## 4 Conducted Emission Measurement

### 4.1. Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50


### 4.2. Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Test Receiver	R&S	ESCI	100367	06/06/2013	(1)
LISN	R&S	ENV216	101040	03/04/2013	(1)
LISN	R&S	ENV216	101041	03/04/2013	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 4.3. Test Setup



#### 4.4. Test Procedure


The power line conducted emission measurements were performed in a shielded enclosure. The EUT was assembled on a wooden table which is 80 centimeters high, was placed 40 centimeters from the back wall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and EMCO Model 3162/2 SH Line Impedance Stabilization Networks (LISN). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPR quasi-peak detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 4.1.


**4.5. Test Result**

Standard:	FCC Part 15C	Line:	L1
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	1	Date:	07/16/2013
		Test By:	Fly Lu
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1820	28.13	18.09	9.62	37.75	27.71	64.39	54.39	-26.64	-26.68	Pass
2	0.2340	22.95	11.12	9.62	32.57	20.74	62.31	52.31	-29.74	-31.57	Pass
3	0.5820	21.94	10.64	9.63	31.57	20.27	56.00	46.00	-24.43	-25.73	Pass
4	1.0540	14.74	0.41	9.67	24.41	10.08	56.00	46.00	-31.59	-35.92	Pass
5	2.5980	14.54	1.70	9.72	24.26	11.42	56.00	46.00	-31.74	-34.58	Pass
6	14.5420	19.60	8.28	9.84	29.44	18.12	60.00	50.00	-30.56	-31.88	Pass

Standard:	FCC Part 15C	Line:	N
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	1	Date:	07/16/2013
		Test By:	Fly Lu
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1860	28.03	19.35	9.63	37.66	28.98	64.21	54.21	-26.55	-25.23	Pass
2	0.3780	27.31	16.55	9.63	36.94	26.18	58.32	48.32	-21.38	-22.14	Pass
3	0.5060	28.47	18.70	9.63	38.10	28.33	56.00	46.00	-17.90	-17.67	Pass
4	0.6260	21.59	11.98	9.64	31.23	21.62	56.00	46.00	-24.77	-24.38	Pass
5	1.4980	23.48	15.85	9.67	33.15	25.52	56.00	46.00	-22.85	-20.48	Pass
6	15.2820	20.98	9.73	9.94	30.92	19.67	60.00	50.00	-29.08	-30.33	Pass

## 5 Radiated Emission Measurement

### 5.1. Limit

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

### 5.2. Test Instruments


3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/21/2013	(1)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/21/2013	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/21/2013	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/21/2013	(1)
Broadband Antenna (30MHz~1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	9163-270	07/01/2013	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/10/2013	(1)
Horn Antenna (18~40GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9170	9170-320	06/13/2013	(1)
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	08/14/2012	(3)
Test Site	ATL	TE01	888001	08/28/2012	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.


Note: N.C.R. = No Calibration Request.

### 5.3. Setup

Below 1GHz



Above 1GHz



## 5.4. Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna (mode VULB9163) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 – 26.5 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).



The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

(1)  $\text{Amplitude (dBuV/m)} = \text{FI (dBuV)} + \text{AF (dBuV)} + \text{CL (dBuV)} - \text{Gain (dB)}$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

(2)  $\text{Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Dis(dB)}$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 5.5. Test Result

### Below 1GHz

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	1	Date:	07/02/2013
		Test By:	Fly Lu

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
95.0000	42.02	-14.94	27.08	43.50	-16.42	QP	H
199.0000	38.31	-13.89	24.42	43.50	-19.08	QP	H
360.0000	30.27	-8.73	21.54	46.00	-24.46	QP	H
504.0000	30.56	-6.76	23.80	46.00	-22.20	QP	H
648.0000	31.87	-4.10	27.77	46.00	-18.23	QP	H
864.0000	29.06	-0.52	28.54	46.00	-17.46	QP	H
94.5000	45.00	-15.06	29.94	43.50	-13.56	QP	V
199.0000	38.92	-13.89	25.03	43.50	-18.47	QP	V
504.0000	37.12	-6.76	30.36	46.00	-15.64	QP	V
648.0000	34.85	-4.10	30.75	46.00	-15.25	QP	V
792.0000	29.94	-1.70	28.24	46.00	-17.76	QP	V
936.0000	28.49	0.88	29.37	46.00	-16.63	QP	V

Note: No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

**Above 1GHz**

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	07/02/2013
Frequency:	2412MHz	Test By:	Fly Lu

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2939.000	36.51	5.75	42.26	74.00	-31.74	peak	H
4465.000	34.83	10.75	45.58	74.00	-28.42	peak	H
6299.000	34.11	16.80	50.91	74.00	-23.09	peak	H
2953.000	37.36	5.79	43.15	74.00	-30.85	peak	V
4507.000	35.59	10.89	46.48	74.00	-27.52	peak	V
6369.000	33.20	17.00	50.20	74.00	-23.80	peak	V

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	07/02/2013
Frequency:	2437MHz	Test By:	Fly Lu

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2925.000	37.39	5.72	43.11	74.00	-30.89	peak	H
4514.000	35.07	10.92	45.99	74.00	-28.01	peak	H
6390.000	33.30	17.08	50.38	74.00	-23.62	peak	H
2918.000	37.74	5.70	43.44	74.00	-30.56	peak	V
4493.000	34.96	10.86	45.82	74.00	-28.18	peak	V
6390.000	32.92	17.08	50.00	74.00	-24.00	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	O3AHGT01			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	2			Date:	07/02/2013		
Frequency:	2462MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2939.000	36.83	5.75	42.58	74.00	-31.42	peak	H
4563.000	34.86	11.05	45.91	74.00	-28.09	peak	H
6383.000	32.65	17.06	49.71	74.00	-24.29	peak	H
2883.000	37.49	5.61	43.10	74.00	-30.90	peak	V
4521.000	35.39	10.93	46.32	74.00	-27.68	peak	V
6418.000	33.54	17.16	50.70	74.00	-23.30	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	O3AHGT01			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	3			Date:	07/02/2013		
Frequency:	2412MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3002.000	37.26	5.91	43.17	74.00	-30.83	peak	H
4535.000	34.80	10.97	45.77	74.00	-28.23	peak	H
6341.000	33.01	16.92	49.93	74.00	-24.07	peak	H
3009.000	37.74	5.93	43.67	74.00	-30.33	peak	V
4493.000	35.50	10.86	46.36	74.00	-27.64	peak	V
6201.000	33.41	16.49	49.90	74.00	-24.10	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	O3AHGT01			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	3			Date:	07/02/2013		
Frequency:	2437MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2939.000	36.77	5.75	42.52	74.00	-31.48	peak	H
4542.000	35.53	10.99	46.52	74.00	-27.48	peak	H
6383.000	32.82	17.06	49.88	74.00	-24.12	peak	H
2869.000	37.46	5.57	43.03	74.00	-30.97	peak	V
4521.000	35.31	10.93	46.24	74.00	-27.76	peak	V
6299.000	33.72	16.80	50.52	74.00	-23.48	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	O3AHGT01			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	3			Date:	07/02/2013		
Frequency:	2462MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2827.000	37.64	5.46	43.10	74.00	-30.90	peak	H
4570.000	35.20	11.06	46.26	74.00	-27.74	peak	H
6201.000	33.08	16.49	49.57	74.00	-24.43	peak	H
2890.000	37.59	5.63	43.22	74.00	-30.78	peak	V
4549.000	34.35	11.01	45.36	74.00	-28.64	peak	V
6355.000	32.97	16.97	49.94	74.00	-24.06	peak	V


Standard:	RSS-Gen	Test Distance:	3m					
Test item:	Radiated Emission	Power:	AC 120V/60Hz					
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH					
Mode:	4	Date:	07/02/2013					
Modulation:	IEEE 802.11b	Test By:	Fly Lu					
Frequency:	2437MHz							
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/)	Peak (dBuV/m)	AVG. (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2967.000	34.82	5.82	40.64	74.00	54.00	-33.36	peak	H
4535.000	34.04	10.97	45.01	74.00	54.00	-28.99	peak	H
6411.000	31.91	17.14	49.05	74.00	54.00	-24.95	peak	H
2918.000	35.63	5.70	41.33	74.00	54.00	-32.67	peak	V
4542.000	33.03	10.99	44.02	74.00	54.00	-29.98	peak	V
6446.000	32.15	17.24	49.39	74.00	54.00	-24.61	peak	V

## 6 Maximum Conducted Output Power Measurement

### 6.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm.

### 6.2. Test Setup



### 6.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Single Channel PK Power Sensor	Agilent	N1911A	MY45101619	12/19/2012	(1)
Wideband Power Meter	Agilent	N1921A	MY45241957	12/19/2012	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 6.4. Test Procedure

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor. The maximum peak output power shall not exceed 1 watt.

Use a direct connection between the antenna port of transmitter and the power sensor, for prevent the power sensor input attenuation 40-50 dB. Set the RBW Bandwidth of the emission or use a channel power meter mode.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm). For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to  $(\text{GAIN} - 6)/3$  dBm.

The antenna port of the EUT was connected to the input of a power sensor. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

**6.5. Test Result**

Model Number	O3AHGT01					
Test Item	Maximum Conducted Output Power					
Test Mode	Mode 2: IEEE 802.11b Link Mode					
Date of Test	07/02/2013			Test Site	TE05	
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)
		(dBm)	(W)	(dBm)	(W)	
2412	1	12.93	0.020	<b>15.90</b>	<b>0.039</b>	< 30
2437		11.86	0.015	14.97	0.031	< 30
2462		10.95	0.012	14.05	0.025	< 30
2437	2	11.54	0.014	14.95	0.031	< 30
2437	5.5	10.41	0.011	14.76	0.030	< 30
2437	11	9.12	0.008	14.80	0.030	< 30

Model Number	O3AHGT01					
Test Item	Maximum Conducted Output Power					
Test Mode	Mode 3: IEEE 802.11g Link Mode					
Date of Test	07/02/2013			Test Site	TE05	
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)
		(dBm)	(W)	(dBm)	(W)	
2412	6	9.60	0.009	<b>16.59</b>	<b>0.046</b>	<30
2437		8.91	0.008	16.49	0.045	<30
2462		7.88	0.006	16.17	0.041	<30
2437	9	8.07	0.006	16.47	0.044	<30
2437	12	5.33	0.003	16.45	0.044	<30
2437	18	3.69	0.002	16.46	0.044	<30
2437	24	0.90	0.001	16.44	0.044	<30
2437	36	-0.35	0.001	16.44	0.044	<30
2437	48	-3.10	0.000	16.42	0.044	<30
2437	54	-3.24	0.000	16.41	0.044	<30




## 7 6dB RF Bandwidth and 99 % Occupied Bandwidth Measurement

### 7.1. Limit

6dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

99 % Occupied Bandwidth: N/A

### 7.2. Test Setup



### 7.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Test Site	ATL	TE05	TE05	N.C.R.	-----

dRemark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 7.4. Test Procedure

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of Oct 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

6dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels (Channel low, middle, high)

99 % Occupied Bandwidth: The transmitter shall be operated at its maximum carrier power measured under normal test conditions.




The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.

**7.5. Test Result**

Model Number	O3AHGT01		
Test Item	6dB RF Bandwidth and 99 % Occupied Bandwidth		
Test Mode	Mode 1: IEEE 802.11b Link Mode		
Date of Test	07/02/2013	Test Site	TE05
Frequency (MHz)	6dB RF Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6dB RF Bandwidth Limit (MHz)
2412	9.549	14.1761	> 0.500
2437	9.100	14.0568	> 0.500
2462	8.994	14.0729	> 0.500

Model Number	O3AHGT01		
Test Item	6dB RF Bandwidth and 99 % Occupied Bandwidth		
Test Mode	Mode 2: IEEE 802.11g Link Mode		
Date of Test	07/02/2013	Test Site	TE05
Frequency (MHz)	6dB RF Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6dB RF Bandwidth Limit (MHz)
2412	15.186	17.8463	> 0.500
2437	15.098	16.7482	> 0.500
2462	15.168	16.5321	> 0.500

7.6. Test Graphs

Mode 2: IEEE 802.11b Link Mode	
2412	
2437	
2462	


Mode 3: IEEE 802.11g Link Mode	
2412	<p>Agilent R T Freq/Channel</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 15 dBm #Atten 20 dB</p> <p>#Peak Log 10 dB/ Offst 6.5 dB</p> <p>Center 2.412 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p><b>Occupied Bandwidth 17.8463 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -298.096 kHz</p> <p>x dB Bandwidth 15.186 MHz</p> <p>Copyright 2000-2007 Agilent Technologies</p>
2437	<p>Agilent R T Freq/Channel</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 15 dBm #Atten 20 dB</p> <p>#Peak Log 10 dB/ Offst 6.5 dB</p> <p>Center 2.437 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p><b>Occupied Bandwidth 16.7482 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -74.649 kHz</p> <p>x dB Bandwidth 15.098 MHz</p> <p>Copyright 2000-2007 Agilent Technologies</p>
2462	<p>Agilent R T Freq/Channel</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 15 dBm #Atten 20 dB</p> <p>#Peak Log 10 dB/ Offst 6.5 dB</p> <p>Center 2.462 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p><b>Occupied Bandwidth 16.5321 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -32.841 kHz</p> <p>x dB Bandwidth 15.168 MHz</p> <p>Copyright 2000-2007 Agilent Technologies</p>

## 8 Maximum Power Density Measurement

### 8.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 8.2. Test Setup



### 8.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 8.4. Test Procedure

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.




1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3$  RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

**8.5. Test Result**

Model Number	O3AHGT01		
Test Item	Maximum Power Density		
Test Mode	Mode 2: IEEE 802.11b Link Mode		
Date of Test	07/02/2013	Test Site	TE05
Frequency (MHz)	Reading (dBm/100KHz)		Limit (dBm)
2412	5.19		< 8
2437	4.25		< 8
2462	3.01		< 8

Model Number	O3AHGT01		
Test Item	Maximum Power Density		
Test Mode	Mode 3: IEEE 802.11g Link Mode		
Date of Test	07/02/2013	Test Site	TE05
Frequency (MHz)	Reading (dBm/100KHz)		Limit (dBm)
2412	2.62		< 8
2437	1.30		< 8
2462	0.51		< 8

8.6. Test Graphs

Mode 2: IEEE 802.11b Link Mode																																																			
2412	 <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Agilent</th> <th>R</th> <th>T</th> <th>Freq/Channel</th> </tr> </thead> <tbody> <tr> <td>Ref 15 dBm</td> <td>#Atten 20 dB</td> <td>Mkr1 2.411 000 GHz</td> <td>5.19 dBm</td> <td>Center Freq 2.41200000 GHz</td> </tr> <tr> <td>Log 10 dB/Offst 6.5 dB</td> <td>LgAv</td> <td>M1 S2</td> <td>S3 FC</td> <td>Start Freq 2.40450000 GHz</td> </tr> <tr> <td>Ⓔ(f): FTun Swp</td> <td></td> <td></td> <td></td> <td>Stop Freq 2.41950000 GHz</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>CF Step 1.50000000 MHz Auto Man</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Freq Offset 0.00000000 Hz</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Signal Track On Off</td> </tr> <tr> <td colspan="2">Center 2.412 000 GHz</td> <td colspan="2">Span 15 MHz</td> <td></td> </tr> <tr> <td colspan="2">#Res BW 100 kHz</td> <td colspan="2">#VBW 300 kHz</td> <td>Sweep 1.44 ms (601 pts)</td> </tr> <tr> <td colspan="5">Copyright 2000-2007 Agilent Technologies</td> </tr> </tbody> </table>	Agilent		R	T	Freq/Channel	Ref 15 dBm	#Atten 20 dB	Mkr1 2.411 000 GHz	5.19 dBm	Center Freq 2.41200000 GHz	Log 10 dB/Offst 6.5 dB	LgAv	M1 S2	S3 FC	Start Freq 2.40450000 GHz	Ⓔ(f): FTun Swp				Stop Freq 2.41950000 GHz					CF Step 1.50000000 MHz Auto Man					Freq Offset 0.00000000 Hz					Signal Track On Off	Center 2.412 000 GHz		Span 15 MHz			#Res BW 100 kHz		#VBW 300 kHz		Sweep 1.44 ms (601 pts)	Copyright 2000-2007 Agilent Technologies				
Agilent		R	T	Freq/Channel																																															
Ref 15 dBm	#Atten 20 dB	Mkr1 2.411 000 GHz	5.19 dBm	Center Freq 2.41200000 GHz																																															
Log 10 dB/Offst 6.5 dB	LgAv	M1 S2	S3 FC	Start Freq 2.40450000 GHz																																															
Ⓔ(f): FTun Swp				Stop Freq 2.41950000 GHz																																															
				CF Step 1.50000000 MHz Auto Man																																															
				Freq Offset 0.00000000 Hz																																															
				Signal Track On Off																																															
Center 2.412 000 GHz		Span 15 MHz																																																	
#Res BW 100 kHz		#VBW 300 kHz		Sweep 1.44 ms (601 pts)																																															
Copyright 2000-2007 Agilent Technologies																																																			
2437	 <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Agilent</th> <th>R</th> <th>T</th> <th>Freq/Channel</th> </tr> </thead> <tbody> <tr> <td>Ref 15 dBm</td> <td>#Atten 20 dB</td> <td>Mkr1 2.437 500 GHz</td> <td>4.25 dBm</td> <td>Center Freq 2.43700000 GHz</td> </tr> <tr> <td>Log 10 dB/Offst 6.5 dB</td> <td>LgAv</td> <td>M1 S2</td> <td>S3 FC</td> <td>Start Freq 2.42950000 GHz</td> </tr> <tr> <td>Ⓔ(f): FTun Swp</td> <td></td> <td></td> <td></td> <td>Stop Freq 2.44450000 GHz</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>CF Step 1.50000000 MHz Auto Man</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Freq Offset 0.00000000 Hz</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Signal Track On Off</td> </tr> <tr> <td colspan="2">Center 2.437 000 GHz</td> <td colspan="2">Span 15 MHz</td> <td></td> </tr> <tr> <td colspan="2">#Res BW 100 kHz</td> <td colspan="2">#VBW 300 kHz</td> <td>Sweep 1.44 ms (601 pts)</td> </tr> <tr> <td colspan="5">Copyright 2000-2007 Agilent Technologies</td> </tr> </tbody> </table>	Agilent		R	T	Freq/Channel	Ref 15 dBm	#Atten 20 dB	Mkr1 2.437 500 GHz	4.25 dBm	Center Freq 2.43700000 GHz	Log 10 dB/Offst 6.5 dB	LgAv	M1 S2	S3 FC	Start Freq 2.42950000 GHz	Ⓔ(f): FTun Swp				Stop Freq 2.44450000 GHz					CF Step 1.50000000 MHz Auto Man					Freq Offset 0.00000000 Hz					Signal Track On Off	Center 2.437 000 GHz		Span 15 MHz			#Res BW 100 kHz		#VBW 300 kHz		Sweep 1.44 ms (601 pts)	Copyright 2000-2007 Agilent Technologies				
Agilent		R	T	Freq/Channel																																															
Ref 15 dBm	#Atten 20 dB	Mkr1 2.437 500 GHz	4.25 dBm	Center Freq 2.43700000 GHz																																															
Log 10 dB/Offst 6.5 dB	LgAv	M1 S2	S3 FC	Start Freq 2.42950000 GHz																																															
Ⓔ(f): FTun Swp				Stop Freq 2.44450000 GHz																																															
				CF Step 1.50000000 MHz Auto Man																																															
				Freq Offset 0.00000000 Hz																																															
				Signal Track On Off																																															
Center 2.437 000 GHz		Span 15 MHz																																																	
#Res BW 100 kHz		#VBW 300 kHz		Sweep 1.44 ms (601 pts)																																															
Copyright 2000-2007 Agilent Technologies																																																			
2462	 <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Agilent</th> <th>R</th> <th>T</th> <th>Freq/Channel</th> </tr> </thead> <tbody> <tr> <td>Ref 15 dBm</td> <td>#Atten 20 dB</td> <td>Mkr1 2.461 500 GHz</td> <td>3.01 dBm</td> <td>Center Freq 2.46200000 GHz</td> </tr> <tr> <td>Log 10 dB/Offst 6.5 dB</td> <td>LgAv</td> <td>M1 S2</td> <td>S3 FC</td> <td>Start Freq 2.45450000 GHz</td> </tr> <tr> <td>Ⓔ(f): FTun Swp</td> <td></td> <td></td> <td></td> <td>Stop Freq 2.46950000 GHz</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>CF Step 1.50000000 MHz Auto Man</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Freq Offset 0.00000000 Hz</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Signal Track On Off</td> </tr> <tr> <td colspan="2">Center 2.462 000 GHz</td> <td colspan="2">Span 15 MHz</td> <td></td> </tr> <tr> <td colspan="2">#Res BW 100 kHz</td> <td colspan="2">#VBW 300 kHz</td> <td>Sweep 1.44 ms (601 pts)</td> </tr> <tr> <td colspan="5">Copyright 2000-2007 Agilent Technologies</td> </tr> </tbody> </table>	Agilent		R	T	Freq/Channel	Ref 15 dBm	#Atten 20 dB	Mkr1 2.461 500 GHz	3.01 dBm	Center Freq 2.46200000 GHz	Log 10 dB/Offst 6.5 dB	LgAv	M1 S2	S3 FC	Start Freq 2.45450000 GHz	Ⓔ(f): FTun Swp				Stop Freq 2.46950000 GHz					CF Step 1.50000000 MHz Auto Man					Freq Offset 0.00000000 Hz					Signal Track On Off	Center 2.462 000 GHz		Span 15 MHz			#Res BW 100 kHz		#VBW 300 kHz		Sweep 1.44 ms (601 pts)	Copyright 2000-2007 Agilent Technologies				
Agilent		R	T	Freq/Channel																																															
Ref 15 dBm	#Atten 20 dB	Mkr1 2.461 500 GHz	3.01 dBm	Center Freq 2.46200000 GHz																																															
Log 10 dB/Offst 6.5 dB	LgAv	M1 S2	S3 FC	Start Freq 2.45450000 GHz																																															
Ⓔ(f): FTun Swp				Stop Freq 2.46950000 GHz																																															
				CF Step 1.50000000 MHz Auto Man																																															
				Freq Offset 0.00000000 Hz																																															
				Signal Track On Off																																															
Center 2.462 000 GHz		Span 15 MHz																																																	
#Res BW 100 kHz		#VBW 300 kHz		Sweep 1.44 ms (601 pts)																																															
Copyright 2000-2007 Agilent Technologies																																																			

Mode 3: IEEE 802.11g Link Mode

2412	<p>Agilent R T Freq/Channel</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.414 49 GHz #Peak 2.62 dBm Log 10 dB/Offst 6.5 dB LgAv M1 S2 S3 FC E(f): FTun Swp</p> <p>Center 2.412 00 GHz Span 23 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.2 ms (601 pts)</p> <p>Copyright 2000-2007 Agilent Technologies</p> <p>Center Freq 2.41200000 GHz Start Freq 2.40050000 GHz Stop Freq 2.42350000 GHz CF Step 2.30000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>
2437	<p>Agilent R T Freq/Channel</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.434 51 GHz #Peak 1.30 dBm Log 10 dB/Offst 6.5 dB LgAv M1 S2 S3 FC E(f): FTun Swp</p> <p>Center 2.437 00 GHz Span 23 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.2 ms (601 pts)</p> <p>Copyright 2000-2007 Agilent Technologies</p> <p>Center Freq 2.43700000 GHz Start Freq 2.42550000 GHz Stop Freq 2.44850000 GHz CF Step 2.30000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>
2462	<p>Agilent R T Freq/Channel</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.464 49 GHz #Peak 0.51 dBm Log 10 dB/Offst 6.5 dB LgAv M1 S2 S3 FC E(f): FTun Swp</p> <p>Center 2.462 00 GHz Span 23 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.2 ms (601 pts)</p> <p>Copyright 2000-2007 Agilent Technologies</p> <p>Center Freq 2.46200000 GHz Start Freq 2.45050000 GHz Stop Freq 2.47350000 GHz CF Step 2.30000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>




## 9 Out of Band Conducted Emissions Measurement

### 9.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### 9.2. Test Setup



### 9.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Spectrum Analyzer	Agilent	E4408B	MY45107753	07/09/2012	(1)
Test Site	ATL	TE05	TE05	N.C.R.	----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.


### 9.4. Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band.

The test was performed at 3 channels (Channel 1, 6, 11)

9.5. Test Graphs



Mode 3: IEEE 802.11g Link Mode


<p>2412</p>	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.41 GHz -1.646 dBm</p> <p>Peak Log 10 dB/Offst 6.5 dB DI -17.4 dBm</p> <p>Start 30 MHz Stop 26.5 GHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.41 GHz</td> <td>-1.646 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.41 GHz	-1.646 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.41 GHz	-1.646 dBm							
<p>2437</p>	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.44 GHz -2.785 dBm</p> <p>Peak Log 10 dB/Offst 6.5 dB DI -18.7 dBm</p> <p>Start 30 MHz Stop 26.5 GHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.44 GHz</td> <td>-2.785 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	-2.785 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	-2.785 dBm							
<p>2462</p>	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.46 GHz -2.894 dBm</p> <p>Peak Log 10 dB/Offst 6.5 dB DI -19.5 dBm</p> <p>Start 30 MHz Stop 26.5 GHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.46 GHz</td> <td>-2.894 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.46 GHz	-2.894 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.46 GHz	-2.894 dBm							

## 10 Band Edges Measurement

### 10.1.Limit

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 10.2.Test Setup



### 10.3.Test Instruments

3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/16/2012	(2)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/21/2013	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/21/2013	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/21/2013	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/10/2013	(1)
Test Site	ATL	TE01	888001	08/18/2012	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

#### **10.4. Test Procedure**

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of Oct 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The emissions on the harmonics frequencies, the limits, and the margin of compliance are presented. These tests were made when the transmitter was in full radiated power. The additional test was performed to show compliance with the requirement at the band-edge frequency 2483.5 MHz and up to 2500 MHz and at 2390.0 MHz.


The transmitter was configured with the worst case antenna and setup to transmit at the highest channel. Then the field strength was measured at 2483.5 MHz.

The transmitter was then configured with the worst case antenna and setup to transmit at the lowest channel. Then the field strength was measured at 2390.0 MHz. These tests were performed at 4 different bit rates.

For measurements the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.


**10.5. Test Result**

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	07/02/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.090	50.22	3.88	54.10	74.00	-19.90	peak
2	2389.090	37.77	3.88	41.65	54.00	-12.35	AVG
3	2390.000	49.00	3.88	52.88	74.00	-21.12	peak
4	2390.000	37.88	3.88	41.76	54.00	-12.24	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	07/02/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.570	51.39	3.85	55.24	74.00	-18.76	peak
2	2385.570	38.12	3.85	41.97	54.00	-12.03	AVG
3	2390.000	49.66	3.88	53.54	74.00	-20.46	peak
4	2390.000	38.41	3.88	42.29	54.00	-11.71	AVG


Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	07/02/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	47.51	4.50	52.01	74.00	-21.99	peak
2	2483.500	38.67	4.50	43.17	54.00	-10.83	AVG
3	2490.640	48.88	4.55	53.43	74.00	-20.57	peak
4	2490.640	37.37	4.55	41.92	54.00	-12.08	AVG




Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	07/02/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	48.16	4.50	52.66	74.00	-21.34	peak
2	2483.500	38.59	4.50	43.09	54.00	-10.91	AVG
3	2488.320	49.56	4.53	54.09	74.00	-19.91	peak
4	2488.320	37.92	4.53	42.45	54.00	-11.55	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	3	Date:	07/02/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.540	58.57	3.87	62.44	74.00	-11.56	peak
2	2388.540	40.53	3.87	44.40	54.00	-9.60	AVG
3	2390.000	58.24	3.88	62.12	74.00	-11.88	peak
4	2390.000	41.44	3.88	45.32	54.00	-8.68	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	3	Date:	07/02/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.760	59.96	3.88	63.84	74.00	-10.16	peak
2	2388.760	41.24	3.88	45.12	54.00	-8.88	AVG
3	2390.000	58.77	3.88	62.65	74.00	-11.35	peak
4	2390.000	42.46	3.88	46.34	54.00	-7.66	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	3	Date:	07/02/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	56.52	4.50	61.02	74.00	-12.98	peak
2	2483.500	40.12	4.50	44.62	54.00	-9.38	AVG
3	2483.800	59.40	4.51	63.91	74.00	-10.09	peak
4	2483.800	40.05	4.51	44.56	54.00	-9.44	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	O3AHGT01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	3	Date:	07/02/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	59.97	4.50	64.47	74.00	-9.53	peak
2	2483.500	43.19	4.50	47.69	54.00	-6.31	AVG
3	2483.600	65.71	4.50	70.21	74.00	-3.79	peak
4	2483.600	43.12	4.50	47.62	54.00	-6.38	AVG

## **11 Antenna Measurement**

### **11.1.Limit**

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **11.2.Antenna Connector Construction**

The antenna used in this product is Chip antenna. And the maximum Gain of this antenna is only 2.22 dBi.