



FCC Test Report

FOR:

Model Number: 0247901
Model Name: nuLink! 23xx
Personal Navigation Device

FCC ID: IPH-0247901

47 CFR Part 15.247 for FHSS Systems

TEST REPORT #: EMC_GARMI_033_11001_15.247

DATE: 2011-03-15



FCC listed
A2LA Accredited

IC recognized #
3462B

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecomusa.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686

Board of Directors: Dr. Harald Ansoerge, Hans Peter May

TABLE OF CONTENTS

1 Assessment 4

2 Administrative Data..... 5

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report5

2.2 Identification of the Client5

2.3 Identification of the Manufacturer5

3 Equipment under Test (EUT) 6

3.1 Specification of the Equipment under Test6

3.2 Identification of the Equipment Under Test (EUT).....7

3.3 Identification of Accessory equipment7

4 Subject of Investigation 8

5 Summary of Measurement Results..... 9

6 Measurements..... 10

6.1 Radiated Measurement Procedure10

6.2 Conducted Measurement Procedure12

6.3 Maximum Peak Output Power13

6.3.1 *References:*13

6.3.2 *Measurement requirements:*13

6.3.3 *Limits:*13

6.3.4 *Test Conditions:*.....13

6.3.5 *Test Result:*14

6.4 Restricted Band Edge Compliance15

6.4.1 *References:*15

6.4.2 *Limits: §15.247/15.205:*.....15

6.4.3 *Measurement Procedure:*15

6.4.4 *Test Data/plots:*16

6.5 Spectrum Bandwidth/ 20dB Bandwidth22

6.5.1 *References:*22

6.5.2 *Measurement requirements:*22

6.5.3 *Limits:*22

6.5.4 *Test Conditions:*.....22

6.5.5 *Test Result:*23

6.5.6 *Test Data/plots:*24

6.6 Carrier Frequency Separation29

6.6.1 *Limits:*29

6.6.2 *Test Result:*29

6.6.3 *Test Conditions:*.....29

6.6.4 *Test Data/plot:*29

- 6.7 Number of hopping channels30
 - 6.7.1 Limits:30
 - 6.7.2 Test Result:30
 - 6.7.3 Test Conditions:.....30
 - 6.7.4 Test Data/plot:.....30
- 6.8 Time of occupancy (Dwell time)31
 - 6.8.1 Limits:31
 - 6.8.2 Test Result:31
- 6.9 Power Spectral Density (Hybrid system in Inquiry mode/ Page scan)32
 - 6.9.1 Limits: § 15.247 (e)32
 - 6.9.2 Test Result:32
- 6.10 Transmitter Spurious Emissions- Conducted.....33
 - 6.10.1 Reference and Limits:33
 - 6.10.2 Test Conditions:33
 - 6.10.3 Test Result:.....33
 - 6.10.4 Test data/ plots:.....34
- 6.11 Transmitter Spurious Emissions- Radiated.....36
 - 6.11.1 References:36
 - 6.11.2 Measurement requirements:.....36
 - 6.11.3 Limits:36
 - 6.11.4 Test Result:.....37
 - 6.11.5 Test data/ plots:.....38
- 6.12 Receiver Spurious Emissions- Radiated46
 - 6.12.1 Limits:46
 - 6.12.2 Test Conditions:46
 - 6.12.3 Test Result:.....46
 - 6.12.4 Test data/ plots:.....47
- 6.13 AC Power Line Conducted Emissions.....50
 - 6.13.1 References:50
 - 6.13.2 Limits:50
 - 6.13.3 Test Conditions:50
 - 6.13.4 Results50
 - 6.13.5 Test Results:51
- 7 Test Equipment and Ancillaries used for tests..... 53**
- 8 Test Setup Info: 54**
- 9 Revision History 55**



1 Assessment

The following device was tested against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations.

No deviations were ascertained during the course of the tests performed.

Company	Description	Model #
Garmin International	Connected Personal Navigation Device	0247901

Responsible for Testing Laboratory:

2011-03-15 Compliance Sajay Jose
(Test Lab Manager)

Date	Section	Name	Signature
------	---------	------	-----------

Responsible for the Report:

2011-03-15 Compliance Josie Sabado
(EMC Engineer)

Date	Section	Name	Signature
------	---------	------	-----------

The test results of this test report relate exclusively to the test item specified in Section 3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Address:	411 Dixon Landing Road Milpitas, CA 95035 U.S.A.
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Test Lab Director:	Heiko Strehlow
Responsible Project Leader:	Rami Saman

2.2 Identification of the Client

Applicant's Name:	Garmin International Inc.
Street Address:	1200 E. 151 st Street
City/Zip Code	Olathe KS 66062
Country	USA
Contact Person:	Van Ruggles
Phone No.	913.397.8448
Fax:	913.397.8282
e-mail:	van.ruggles@garmin.com

2.3 Identification of the Manufacturer

Manufacturer's Name:	Garmin International Inc.
Manufacturers Address:	No. 68 Jangshu 2 nd Road
City/Zip Code	Shijr, Taipei County
Country	Taiwan

3 Equipment under Test (EUT)

3.1 Specification of the Equipment under Test

Marketing Name /	nuLink! 23xx
Model No:	0247901
HW / SW Revision :	6.0/2.00
Module Information:	Sierra Wireless SL6087 HW: 210 SW: 7.44.1
FCC-ID :	IPH-0247901
Product Description:	Connected Personal Navigation Device with Quadband GSM/GPRS/EGPRS cellular modem and GPS Receiver.
Frequency Range / number of channels:	Bluetooth: 2400-2483.5MHz / 79;
Type(s) of Modulation:	Bluetooth: GFSK, DQPSK, 8DPSK;
Antenna Type / gain / position / min. distance to other antenna (if appl):	Bluetooth: Integral Chip antenna / 2.2dBic Peak Gain;
Output Powers (max):	Bluetooth Radiated: 7.2 dBm Bluetooth Conducted: 5.0 dBm
Power Supply	Lithium battery pack (dedicated), 5.0 VDC;
Operating Temperature Range	-20°C to 55°C
Prototype / Production unit	Prototype Sample

Notes:

Model number 0247901 is sold under 3 marketing names- nuLink! 2390, nuLink! 2340 and nuLink! 2320. The only difference between these models is in the internal memory size.

All testing was performed on the 2390 model and test data reported in this document is applicable for the 2340 and 2320 models.

3.2 Identification of the Equipment Under Test (EUT)

EUT #	Serial Number	HW Version	SW Version	Model	Notes/Comments
1	25A000268	6	2.00	nuLink! 2390	Radiated Sample
2	25A000267	4	2.00	nuLink! 2390	Conducted Sample

3.3 Identification of Accessory equipment

AE #	Type	Manufacturer	Model	Serial Number
1	Vehicle Charger	Garmin	FA-0501000CB	F10102022462
2	Car Holder	Garmin	N/A	N/A
3	USB Cable	Garmin	N/A	N/A
4	Laptop Computer	Dell	E6400	14686084801

4 Subject of Investigation

The objective of the measurements done by Cetecom Inc. was to measure the performance of the EUT as specified by requirements listed in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations.

This test report is to support a request for new equipment authorization under the FCC ID: **IPH-0247901**.

All testing was performed on the product referred to in Section 3 as EUT.
This test report contains full radiated and conducted testing results as per

- 47 CFR Part 15: Title 47 of the Code of Federal Regulations: Chapter I-Federal Communications Commission subchapter A- General, Part 15- Radio Frequency Devices.

During the testing process the EUT was tested on a single channel using PRBS payload using DH5, 2DH5 or 3DH5 packets, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

5 Summary of Measurement Results

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	Fail	NA	NP	Result
§15.247(b)(4)	Antenna Gain	Nominal	GFSK	■	□	□	□	Complies
§15.247(e)	Power Spectral Density	Nominal	GFSK $\pi/4$ DQPSK 8DPSK	□	□	■	□	-
§15.247(a)(1)	Carrier Frequency Separation	Nominal	GFSK	■	□	□	□	Complies
§15.247(a)(1)	Number of Hopping Channels	Nominal	GFSK	■	□	□	□	Complies
§15.247(a)(1)(iii)	Time of occupancy	Nominal	-	■	□	□	□	Complies
§15.247(a)(1)	Spectrum Bandwidth	Nominal	GFSK $\pi/4$ DQPSK 8DPSK	■	□	□	□	Complies
§15.247(b)(1)	Maximum Output Power	Nominal	GFSK $\pi/4$ DQPSK 8DPSK	■	□	□	□	Complies
§15.247(d)	Band edge compliance-Conducted	Nominal	GFSK $\pi/4$ DQPSK 8DPSK	□	□	□	■	-
§15.247(d)	Band edge compliance-Radiated	Nominal	GFSK $\pi/4$ DQPSK 8DPSK	■	□	□	□	Complies
§15.247(d)	TX Spurious emissions-Conducted	Nominal	GFSK	■	□	□	□	Complies
§15.247(d)	TX Spurious emissions-Radiated	Nominal	GFSK	■	□	□	□	Complies
§15.209(a)	TX Spurious Emissions Radiated<30MHz	Nominal	GFSK	■	□	□	□	Complies
§15.109	RX Spurious Emissions Radiated	Nominal	GFSK	■	□	□	□	Complies
§15.107(a)	Conducted Emissions <30MHz	Nominal	GFSK	■	□	□	□	Complies

Note: NA= Not Applicable; NP= Not Performed.

1. Band Edge compliance-conducted is NOT PERFORMED as the device passes radiated measurement.
2. Power Spectral Density is NOT APPLICABLE for devices with hopping functionality.

6 Measurements

6.1 Radiated Measurement Procedure

ANSI C63.4 Section 8.3.1.1: Exploratory radiated emission measurements

Exploratory radiated measurements shall be performed at the measurement distance or at a closer distance than that specified for compliance to determine the emission characteristics of the EUT. At near distances, for EUTs of comparably small size, it is relatively easy to determine the spectrum signature of the EUT and, if applicable, the EUT configuration that produces the maximum level of emissions. A shielded room may be used for exploratory testing, but may have anomalies that can lead to significant errors in amplitude measurements.

Broadband antennas and a spectrum analyzer or a radio-noise meter with a panoramic display are often useful in this type of testing. It is recommended that either a headset or loudspeaker be connected as an aid in detecting ambient signals and finding frequencies of significant emission from the EUT when the exploratory and final testing is performed in an OATS with strong ambient signals. Caution should be taken if either antenna height between 1 and 4 meters or EUT azimuth is not fully explored. Not fully exploring these parameters during exploratory testing may require complete testing at the OATS or semi-anechoic chamber when the final full spectrum testing is conducted.

The EUT should be set up in its typical configuration and arrangement, and operated in its various modes. For tabletop systems, cables or wires should be manipulated within the range of likely arrangements. For floor-standing equipment, the cables or wires should be located in the same manner as the user would install them and no further manipulation is made. For combination EUTs, the tabletop and floor-standing portions of the EUT shall follow the procedures for their respective setups and cable manipulation. If the manner of cable installation is not known, or if it changes with each installation, cables or wires for floor-standing equipment shall be manipulated to the extent possible to produce the maximum level of emissions.

For each mode of operation required to be tested, the frequency spectrum shall be monitored. Variations in antenna height between 1 and 4 m, antenna polarization, EUT azimuth, and cable or wire placement (each variable within bounds specified elsewhere) shall be explored to produce the emission that has the highest amplitude relative to the limit. A step-by-step technique for determining this emission can be found in Annex C.

When measuring emissions above 1 GHz, the frequencies of maximum emission shall be determined by manually positioning the antenna close to the EUT and by moving the antenna over all sides of the EUT while observing a spectral display. It will be advantageous to have prior knowledge of the frequencies of emissions above 1 GHz. If the EUT is a device with dimensions approximately equal to that of the measurement antenna beamwidth, the measurement antenna shall be aligned with the EUT.

ANSI C63.4 Section 8.3.1.2: Final radiated emission measurements

Based on the measurement results in 8.3.1.1, the one EUT, cable and wire arrangement, and mode of operation that produces the emission that has the highest amplitude relative to the limit is selected for the final measurement. The final measurement is then performed on a site meeting the requirements of 5.3, 5.4, or 5.5 as appropriate without variation of the EUT arrangement or EUT mode of operation. If the EUT is relocated from an exploratory test site to a final test site, the highest emission shall be remaximized at the final test location before final radiated emissions measurements are performed. However, antenna height and polarity and EUT azimuth are to be varied. In addition, the full frequency spectrum (for the range to be checked for meeting compliance) shall be investigated.


This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. During the full frequency spectrum investigation, particular focus should be made on those frequencies found in exploratory testing that were used to find the final test configuration, mode of operation, and arrangement (associated with achieving the least margin with respect to the limit). This full spectrum test constitutes the compliance measurement.

For measurements above 1 GHz, use the cable, EUT arrangement, and mode of operation determined in the exploratory testing to produce the emission that has the highest amplitude relative to the limit. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the antenna in the “cone of radiation” from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response. The antenna may have to be higher or lower than the EUT, depending on the EUT’s size and mounting height, but the antenna should be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. If the transmission line for the measurement antenna restricts its range of height and polarization, the steps needed to ensure the correct measurement of the maximum emissions, shall be described in detail in the report of measurements. Data collected shall satisfy the report requirements of Clause 10.

NOTES

- 1— Where limits are specified by agencies for both average and peak (or quasi-peak) detection, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
- 2—Use of waveguide and flexible waveguide may be necessary at frequencies above 10 GHz to achieve usable signal-to noise ratios at required measurement distances. If so, it may be necessary to restrict the height search of the antenna, and special care should be taken to ensure that maximum emissions are correctly measured.
- 3—All presently known devices causing emissions above 10 GHz are physically small compared with the beam-widths of typical horn antennas used for EMC measurements. For such EUTs and frequencies, it may be preferable to vary the height and polarization of the EUT instead of the receiving antenna to maximize the measured emissions.

6.2 Conducted Measurement Procedure



1. Connect the equipment as shown in the above diagram.
2. Adjust the settings of the Digital Radio Communication Tester (DRT) to connect the EUT at the required channel.
3. Measurements are to be performed with the EUT set to the low, middle and high channels.

6.3 Maximum Peak Output Power

6.3.1 References: **FCC CFR §2.1046**

6.3.2 Measurement requirements:

6.3.2.1 FCC 2.1046: RF power output.

Power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on circuit elements as specified. The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.

6.3.3 Limits:

6.3.3.1 §15.247 (b)(1)

The maximum peak conducted output power of the intentional radiator shall not exceed the following: For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

6.3.4 Test Conditions:

Tnom: 25°C; Vnom: 5.0V

Hopping OFF

Spectrum Analyzer settings:

RBW=VBW=3MHz, Detector: Peak- Max Hold.

Sweep Time: Auto

Span=3MHz

Antenna Gain (dBi): 2.2 dB

6.3.5 Test Result:

Max Peak Output Power- Conducted (dBm)			
Modulation	Frequency (MHz)		
	2402	2441	2480
GFSK	5.0	4.5	4.1
$\pi/4$ DQPSK	4.9	4.4	4.0
8-DPSK	5.0	4.6	4.2
Measurement Uncertainty: ± 0.5 dB			

Max Peak Output Power- Radiated (dBm)			
Modulation	Frequency (MHz)		
	2402	2441	2480
GFSK	7.2	6.7	6.3
$\pi/4$ DQPSK	7.1	6.6	6.2
8-DPSK	7.2	6.8	6.4
Measurement Uncertainty: ± 3.0 dB			

**Note: Radiated EIRP is calculated as
*Conducted Measurement + Antenna Gain***

6.3.5.1 Measurement Result

Pass.

6.4 Restricted Band Edge Compliance

6.4.1 References:
FCC CFR §2.1053

6.4.2 Limits: §15.247/15.205

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

6.4.3 Measurement Procedure:

Peak measurements are made using a peak detector and RBW=1MHz.

Average measurements performed using a peak detector and according to video averaging procedure with RBW=1MHz and VBW=10Hz.

*PEAK LIMIT= 74dBμV/m

*AVG. LIMIT= 54dBμV/m


Measurement Uncertainty: ±3.0dB

6.4.3.1 Measurement Result

Pass.


6.4.4 Test Data/plots:

Lower band edge peak -GFSK modulation




— MaxPeak-ClearWrite — MaxPeak-MaxHold — FCC 15.247 Pk

Lower band edge average -GFSK modulation




— MaxPeak-MaxHold — FCC 15.247 Avg

Higher band edge peak -GFSK modulation




— MaxPeak-Clear/Write — MaxPeak-MaxHold — FCC 15.247 Pk

Higher band edge average-GFSK modulation




— MaxPeak-MaxHold — FCC 15.247 Avg

Lower band edge peak - $\pi/4$ DQPSK modulation




— MaxPeak-ClearWrite — MaxPeak-MaxHold — FCC 15.247 Pk

Lower band edge average - $\pi/4$ DQPSK modulation




— MaxPeak-MaxHold — FCC 15.247 Avg

Higher band edge peak $-\pi/4$ DQPSK modulation




MaxPeak-ClearWrite MaxPeak-MaxHold FCC 15.247 Pk

Higher band edge average $-\pi/4$ DQPSK modulation




MaxPeak-MaxHold FCC 15.247 Avg

Lower band edge peak - 8DPSK modulation




— MaxPeak-ClearWrite — MaxPeak-MaxHold — FCC 15.247 Pk

Lower band edge average -8DPSK modulation




— MaxPeak-MaxHold — FCC 15.247 Avg

Higher band edge peak - 8DPSK modulation



— MaxPeak-ClearWrite — MaxPeak-MaxHold — FCC 15.247 Pk

Higher band edge average-8DPSK modulation



— MaxPeak-MaxHold — FCC 15.247 Avg

6.5 Spectrum Bandwidth/ 20dB Bandwidth

6.5.1 References: **FCC CFR §2.1049**

6.5.2 Measurement requirements:

6.5.2.1 FCC 2.1049: Occupied bandwidth

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable.

(h) Transmitters employing digital modulation techniques-when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated.

6.5.3 Limits:

6.5.3.1 §15.247 (a)(1)

Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

GFSK < 1000 kHz

$\pi / 4$ DQPSK < 1500 kHz

8 dPSK < 1500kHz

6.5.4 Test Conditions:

Tnom: 25°C; Vnom: 5.0 V

Hopping OFF

Spectrum Analyzer settings:

RBW=10kHz, VBW=30kHz, Detector: Peak- Max hold;

Sweep Time: Auto

Span=2MHz

6.5.5 Test Result:


20dB Bandwidth (kHz)			
Modulation	Frequency (MHz)		
	2402	2441	2480
GFSK	0.958	0.859	0.953
$\pi/4$ DQPSK	1.351	1.350	1.335
8-DPSK	1.359	1.366	1.342
Measurement Uncertainty: ± 10 kHz			

6.5.5.1 Measurement Result


Pass.

6.5.6 Test Data/plots:


20dB Bandwidth GFSK 2402MHz




20dB Bandwidth GFSK 2441MHz




20dB Bandwidth GFSK 2480MHz




20dB Bandwidth $\pi / 4$ DQPSK 2402MHz




20dB Bandwidth $\pi / 4$ DQPSK 2441MHz




20dB Bandwidth $\pi / 4$ DQPSK 2480MHz




20dB Bandwidth 8PSK 2402MHz



20dB Bandwidth 8PSK 2441MHz



20dB Bandwidth 8PSK 2480MHz



6.6 Carrier Frequency Separation

6.6.1 Limits:

§ 15.247 (a) (1)

Minimum 25kHz or 2/3 of the 20dB bandwidth of the hopping system

6.6.2 Test Result:

Modulation: GFSK

Channel Separation: 1022 MHz

6.6.3 Test Conditions:

Tnom: 25°C; Vnom: 5.0V

Hopping ON


Spectrum Analyzer settings:

RBW=30kHz, VBW=100kHz, Detector: Peak- Max hold;

Sweep Time: Auto

Span=2MHz

6.6.4 Test Data/plot:



Date: 31.JAN.2011 16:17:33

6.6.4.1 Measurement Result

Pass.

6.7 Number of hopping channels

6.7.1 Limits:

§ 15.247 (a) (1)

Atleast 15 non-overlapping channels

6.7.2 Test Result:

Modulation: GFSK

Number of hopping channels: 79

6.7.3 Test Conditions:

Tnom: 25°C; Vnom: 4.2 V

Hopping ON


Spectrum Analyzer settings:

RBW=30kHz, VBW=100kHz, Detector: Peak- Max hold;

Sweep Time: Auto

Span=Full range

6.7.4 Test Data/plot:



Date: 31.JAN.2011 16:12:50

6.7.4.1 Measurement Result

Pass.

6.8 Time of occupancy (Dwell time)

6.8.1 Limits:

§ 15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

6.8.2 Test Result:

For Bluetooth devices:

The dwell time of 0.4 s within a 31.6 second period in data mode is independent from the packet type (packet length). The calculation for a 31.6 second period is as follows:

Dwell time = time slot length * hop rate / number of hopping channels * 31.6 s

Example for a DH1 packet (with a maximum length of one time slot)

Dwell time = $625 \mu\text{s} * 1600 \text{ 1/s} / 79 * 31.6 \text{ s} = 0.4 \text{ s}$ (in a 31.6 s period)

For multi-slot packet the hopping is reduced according to the length of the packet.

Example for a DH5 packet (with a maximum length of five time slots)

Dwell time = $5 * 625 \mu\text{s} * 1600 * 1/5 * 1/s / 79 * 31.6 \text{ s} = 0.4 \text{ s}$ (in a 31.6 s period)

This is according to Bluetooth Core Specification for all Bluetooth devices. Therefore all BT devices satisfy FCC requirement on time of occupancy (dwell time) in the data mode.

6.8.2.1 Test Result

Pass.

6.9 Power Spectral Density (Hybrid system in Inquiry mode/ Page scan)

6.9.1 Limits: § 15.247 (e)

For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

6.9.2 Test Result:

Not Applicable for FHSS systems.

6.10 Transmitter Spurious Emissions- Conducted

6.10.1 Reference and Limits:

6.10.1.1 § 15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

30dBm for the transmitter.

-20dBc in the frequency range 30MHz- 25GHz.

6.10.2 Test Conditions:

Tnom: 25°C; Vnom: 5.0 V

Hopping OFF

Spectrum Analyzer settings:

RBW=100kHz, VBW=300kHz, Detector: Peak- Max hold;

Sweep Time: Auto

Span=Full range

Testing under worst case scenario (highest output power) with GFSK modulation reported here.

6.10.3 Test Result:


Conducted Spurious Emissions			
Channel	Frequency (MHz)	Amplitude (dBm)	Limits
		GFSK	
Low	2412	-2.69	30dBm
	Spurious	All other peaks >20dB below carrier	-20dBc
Mid	2437	-2.96	30 dBm
	Spurious	All other peaks >20dB below carrier	-20dBc
High	2462	-2.74	30 dBm
	Spurious	All other peaks >20dB below carrier	-20dBc
Measurement Uncertainty: ±1.0 dB			

6.10.3.1 Measurement Result

Pass.


6.10.4 Test data/ plots:

Conducted Spurious Emissions GFSK 2402MHz



Date: 31.JAN.2011 16:21:00


Conducted Spurious Emissions GFSK 2441MHz



Date: 31.JAN.2011 16:22:28



Conducted Spurious Emissions GFSK 2480MHz



Date: 31.JAN.2011 16:23:34



6.11 Transmitter Spurious Emissions- Radiated

6.11.1 References:

FCC CFR 2.1053

6.11.2 Measurement requirements:

6.11.2.1 FCC 2.1053: Field strength of spurious radiation.

Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission.

6.11.3 Limits:

§15.247/15.205

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under Section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB.

*PEAK LIMIT= 74dB μ V/m

*AVG. LIMIT= 54dB μ V/m

Table 1:

Frequency of emission (MHz)	Field strength ($\mu\text{V/m}$)
30–88	100 (40dB $\mu\text{V/m}$)
88–216	150 (43.5 dB $\mu\text{V/m}$)
216–960	200 (46 dB $\mu\text{V/m}$)
Above 960	500 (54 dB $\mu\text{V/m}$)

Table 2:

Frequency of emission (MHz)	Field strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30

6.11.4 Test Result:**Test mode: Modulation: GFSK- since highest conducted power**

Unless mentioned otherwise, the emissions outside the limit lines in the plots are from the transmit signal.

Plots reported here represent the worse case emissions for horizontal and vertical antenna polarizations and for three orientations of the EUT.

Measurement Uncertainty: $\pm 3.0\text{dB}$

6.11.4.1 Measurement Result


Pass.

6.11.5 Test data/ plots:

Transmitter Radiated Spurious Emission:<30MHz


Note: Worst case representation for all modes of operation in this frequency range-

Limits adjusted for 3m measurement.



— FCC 15.9kHz.LimitLine — Preview Result 1


Transmitter Radiated Spurious Emission- Ch0- 30M-1GHz



— FCC 15.LimitLine — MaxPeak-ClearWrite
* Data Reduction Result ◆ Final Measurement Result




Transmitter Radiated Spurious Emission- Ch0- 1G-18GHz



- 74 dBµV per m.LimitLine
- 54 dBµV per m.LimitLine
- Preview Result 1
- Preview Result 2
- Data Reduction Result 1 [4]
- Data Reduction Result 2 [4]
- Final Result 1
- Final Result 2


Transmitter Radiated Spurious Emission- Ch39- 30M-1GHz



— FCC 15.LimitLine — MaxPeak-ClearWrite
* Data Reduction Result ◆ Final Measurement Result



Transmitter Radiated Spurious Emission- Ch39- 1G-18GHz




- 74 dBuV per m LimitLine
- 54 dBuV per m LimitLine
- Preview Result 1
- Preview Result 2
- * Data Reduction Result 1 [4]
- * Data Reduction Result 2 [4]
- ◆ Final Result 1
- ◆ Final Result 2




Transmitter Radiated Spurious Emission- Ch39- 18G-26GHz

Note: Worst case representation for all modes of operation and channels in this frequency range-




— 74 dBuV per m.LimitLine — 54 dBuV per m.LimitLine — Preview Result 1 — Preview Result 2

Transmitter Radiated Spurious Emission- Ch78- 30M-1GHz





Transmitter Radiated Spurious Emission- Ch78- 1G-18GHz



- 74 dBuV per m
- 54 dBuV per m
- MaxPeak-ClearWrite
- Average-ClearWrite

6.12 Receiver Spurious Emissions- Radiated

6.12.1 Limits:

6.12.1.1 FCC CFR §15.109

Frequency of emission (MHz)	Field strength (μV/m)	Measurement Distance (m)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 (40dBμV/m)	3
88–216	150 (43.5 dBμV/m)	3
216–960	200 (46 dBμV/m)	3
Above 960	500 (54 dBμV/m)	3

6.12.2 Test Conditions:

Modulation: GFSK

Measurement Uncertainty: ±3.0dB

6.12.3 Test Result:

No significant emissions measurable. Plots reported here represent the worse case emissions for horizontal and vertical antenna polarizations and for three orientations of the EUT.


6.12.3.1 Measurement Result

Pass.

6.12.4 Test data/ plots:


Receive Mode: <30MHz

Note: Limits adjusted for 3m measurement.




— FCC 15.9kHz.LimitLine — Preview Result 1

Receive Mode: 30MHz-1GHz



— FCC 15.LimitLine — MaxPeak-ClearWrite
* Data Reduction Result ♦ Final Measurement Result

Receive Mode: 1GHz-18GHz



— MaxPeak-ClearWrite — Average-ClearWrite

6.13 AC Power Line Conducted Emissions

6.13.1 References:

FCC: CFR Part 15.207

The purpose of this test is to measure unwanted radio frequency currents induced in any AC conductor external to the equipment which could conduct interference to other equipment via the AC electrical network.

6.13.2 Limits:

6.13.2.1 §15.207 Conducted limits- Intentional Radiators:

(a) Except as shown in paragraphs (b) and (c) of this section of the CFR, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table (1), as measured using a 50 μH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Table 1:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

Analyzer Settings: CISPR Bandwidth- 9KHz.

6.13.3 Test Conditions:

Modulation: GFSK- Transmit and Receive modes of operation

Measurement Uncertainty: ±3.0dB

6.13.4 Results


Plots shown here represent the combined worse case emissions for power lines, phases and neutral line.

6.13.4.1 Measurement Result

Pass.


6.13.5 Test Results:

BT TX Mode:



— EN 55022 Voltage on Mains QP.LimitLine — EN 55022 Voltage on Mains AV.LimitLine
— Preview Result 1 — Preview Result 2

BT RX Mode:



— EN 55022 Voltage on Mains QP.LimitLine — EN 55022 Voltage on Mains AV.LimitLine
— Preview Result 1 — Preview Result 2

Test Report #: EMC_GARMI_033_11001_15.247

Date of Report : 2011-03-15



Page 53 of 55



7 Test Equipment and Ancillaries used for tests

Instrument/Ancillary	Model	Manufacturer	Serial No.	Cal Date	Cal Interval
Radio Communication Tester	CMU 200	Rohde & Schwarz	101821	June 2010	1 year
Bluetooth Tester	CBT	Rohde & Schwarz	100212	May 2009	2 Years
EMI Receiver/Analyzer	ESIB 40	Rohde & Schwarz	100107	May 2010	1 year
Spectrum Analyzer	FSU	Rohde & Schwarz	200302	Jul 2010	1 year
Loop Antenna	6512	EMCO	00049838	April 2009	2 years
Biconilog Antenna	3141	EMCO	0005-1186	June 2009	2 years
Horn Antenna (1-18GHz)	3115	ETS	00035111	Jan 2009	3 years
Horn Antenna (18-40GHz)	3116	ETS	00070497	Jan 2009	3 years
Communication Antenna	IBP5-900/1940	Kathrein	n/a	n/a	n/a
High Pass Filter	5HC2700	Trilithic Inc.	9926013	Part of system calibration	
High Pass Filter	4HC1600	Trilithic Inc.	9922307	Part of system calibration	
6GHz High Pass Filter	HPM50106	Microtronics	001	Part of system calibration	
Pre-Amplifier	JS4-00102600	Miteq	00616	Part of system calibration	
LISN	R&S	ESH3-Z6	836154/011	May 2009	2 Years
Power Smart Sensor	R&S	NRP-Z81	100161	June 2010	1 Year
DC Power Supply	E3610A	Hewlett Packard	KR83021224	n/a	n/a
Multimeter	179	Fluke	N/A	Feb 2010	1 Year
Temp Hum Logger	TM320	Dickson	03280063	Feb 2010	1 Year
Temp Hum Logger	TM325	Dickson	5285354	Feb 2010	1 Year

8 **Test Setup Info:**



Test Report #: **EMC_GARMI_033_11001_15.247**

Date of Report : 2011-03-15

Page 55 of 55



9 Revision History

Date	Report Name	Changes to report	Report prepared by
2011-03-15	EMC_GARMI_033_11001_15.247	First Version	J Sabado