SAR Test Exclusion	Calculat	or								
Insert values in yel	llow high	lighted bo	xes to det	ermine SA	R Exclusion	า				
Max Power	2	mW								
Min Separation		mm	When the	minimum	test senar	ation dista	nce is < 5 r	nm a dista	ance of 5 m	m is
Frequency	_	GHz	When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.					5		
Trequency	2.4	GIIZ	аррпса с	determini	c JAN 1631	CACIUSIOII.				
Answer 0.6 Must be less than or equal to 3.0 for SAR Exclusion										
Answer	0.6	iviust be it	ess than or	equal to 5	OUTOF SAK	EXCIUSION				
				Exclusion						
		TCBs are excluded from granting if:								
		General Population: The Answer is equal to or greater than 24 (8x threshold)								
		Controlled Use: The Answer is equal to or greater than 60 (20x threshold)								
		and, when published RF exposure KDB procedures are not established for SAR								
	testing or when SAR data is not provided to support compliance.									
Please also note th	ne follow	ing: [FCC	KDB auote	These te	st exclusio	n condition	ns are base	d on sourc	e-based	
time-averaged max			-							
up tolerance, and t										
_ ·			•		-	•				
test separation distance is determined by the smallest distance from the antenna and radiating structures or										
outer surface. [End	<u> quotej</u>									

Rogers Labs, Inc. 4405 West 259th Terrace Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

Garmin International, Inc. Model: A03119-00 Test #: 161031

Test to: CFR47 15C, RSS-247, RSS-210

File: A03119 00 RF Exemption

SN's: 688 / 690

FCC ID: IPH-03119-00 IC: 1792A-03119-00 Date: December 21, 2016

Page 1 of 2

RSS-102

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance

Frequency	Exemption Limits (mW)							
(MHz)	At separation distance of							
	≤5 mm	10 mm	15 mm	20 mm	25 mm			
≤300	71 mW	101 mW	132 mW	162 mW	193 mW			
450	52 mW	70 mW	88 mW	106 mW	123 mW			
835	17 mW	30 mW	42 mW	55 mW	67 mW			
1900	7 mW	10 mW	18 mW	34 mW	60 mW			
2450	4 mW	7 mW	15 mW	30 mW	52 mW			
3500	2 mW	6 mW	16 mW	32 mW	55 mW			
5800	1 mW	$6 \mathrm{mW}$	15 mW	27 mW	41 mW			

Frequency	Exemption Limits (mW)							
(MHz)	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm			
≤300	223 mW	254 mW	284 mW	315 mW	345 mW			
450	141 mW	159 mW	177 mW	195 mW	213 mW			
835	80 mW	92 mW	105 mW	117 mW	130 mW			
1900	99 mW	153 mW	225 mW	316 mW	431 mW			
2450	83 mW	123 mW	173 mW	235 mW	309 mW			
3500	86 mW	124 mW	170 mW	225 mW	290 mW			
5800	56 mW	71 mW	85 mW	97 mW	106 mW			

The device operating with 5mW output power and maintaining a 10 cm distance complies with the requirements of RSS-102 Table 1 exclusion for SAR evaluation

Rogers Labs, Inc. 4405 West 259th Terrace Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

Garmin International, Inc. Model: A03119-00

Test #: 161031

Test to: CFR47 15C, RSS-247, RSS-210

File: A03119 00 RF Exemption

SN's: 688 / 690

FCC ID: IPH-03119-00 IC: 1792A-03119-00 Date: December 21, 2016

Page 2 of 2