

Test Report Serial Number: Test Report Date: Project Number:

45461500 R2.0	
15 July 2019	
1432	

SAR Test Report - New Certification

Applicant.	Maximum Reported 10g SAR					
GARMIN		Extremity DTS	0.15			
Garmin International Inc.	ISED	Extremity DTS	0.15	W/kg		
1200 East 151 St.		General Pop. Limit:	4.00			
Olathe, KS, 66062 USA						
FCC ID:		ISED Certification	Number			
IPH-03558		1792A-03558 Product Name / PMN				
Product Model Number / HVIN						
A03558		A03558				

In Accordance With:

FCC 47 CFR §2.1093

Radiofrequency Radiation Exposure Evaluation: Portable Devices

IC RSS-102 Issue 5

Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

Approved By:

Ben Hewson, President Celltech Labs Inc. 21-364 Lougheed Rd. Kelowna, BC, V1X 7R8 Canada









Test Lab Certificate: 2470.01

IC Registration 3874A-1

This report shall not be reproduced in any form without the expressed written consent of Celltech Labs Inc.



15 July 2019

Table of Contents

4
5
6
7
8
9
10
10 11
12
13
13
14
14
15
15
18
18
19
19
20
21
21 22
21 22 22
21 22 22 23 23
21 22 22 23 23 24
21 22 23 23 24 24
21 22 23 23 24 24 24 25
21 22 23 23 24 24 25 26
21 22 23 23 24 24 25 26 26
21 22 22 23 23 24 24 26 26 28
21 22 23 23 24 24 26 26 26 28
21 22 22 23 24 24 25 26 26 26 28 28 29
21 22 22 23 23 24 24 26 26 26 26 28 28 29 29
21 22 23 23 24 24 26 26 26 26 26 28 29 29 29 29 30

©2019 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the expressed written permission of Celltech Labs Inc. Page 2 of 50



19.0 TEST EQUIPMENT LIST	
TABLE 19.0 EQUIPMENT LIST AND CALIBRATION	
20.0 FLUID COMPOSITION	
TABLE 20.0 FLUID COMPOSITION 2450MHz BODY TSL	
APPENDIX A – SYSTEM VERIFICATION PLOTS	
SPC-2450B Mar 05 2019	
APPENDIX B – MEASUREMENT PLOTS OF MAXIMUMUM MEASURED SAR	
Garmin-2450B Mar 06 2019 Garmin-2450B Mar 06 2019	
APPENDIX C - SETUP PHOTOS	
APPENDIX D – DUT AND ACCESSORY PHOTOS	
APPENDIX E – PROBE CALIBRATION	
APPENDIX F – DIPOLE CALIBRATION	
APPENDIX G - PHANTOM	



1.0 DOCUMENT CONTROL

Samples Tested By:	Trevor Whillock			
Report Prepared By:	Trevor Whillock			
Report Reviewed By:	Ben Hewson			
Report Issue Number	Description	Ву	Report Issue Date	
R0.0	Draft	Trevor Whillock	10 June 2019	
R0.1	Section 2.0,7.0 & 11.0- Revised Rated Power	Trevor Whillock	21 June 2019	
P1.0	Inital Release	Trovor Whillock	26 June 2010	
K1.0	Section 2.0 -Added Reference to Manufacturer		20 Julie 2019	
	Section 16.0 -Revised Normalized Target Values and Deviation in SPC Report			
R2.0	Section 19.0- Revised Equipment Table to Include Corrrect Probe Cal Dates	Trevor Whillock 15 July 2		
	Appendix E- Changed Cal Probe Report to Correlate with System Check and Test Dates			



2.0 CLIENT AND DEVICE INFORMATION

Client Information						
Applicant Name	Garmin International Inc.					
	1200 East 151 St.					
Applicant Address	Olathe, KS,66062					
	USA					
Manufacturer Name	Garmin Corporation					
	No.68, Zhangshu 2nd Rd., Xizhi Dist.					
Manufacturer Address	New Taipei City 221					
	Taiwan, R.O.C					
	DUT Information					
Device Identifier(s):	FCC ID: IPH-03558					
Device identifier (3).	IC: 1792A-03558					
Type of Equipment:	Digital Transmission System (DTS) FCC Part 15, RSS 247					
	Low Power Communication Device Transmitter (DXX) FCC Part 15					
Device Model(s) / HVIN:	A03558					
Device Marketing Name / PMN:	A03558					
Test Sample Serial No.:	T/A Sample - Identical Prototype					
Transmit Fraguency Pange:	WiFi: 2412 - 2462 MHz					
Transmit requency range.	BT: 2402 - 2480 MHz					
	NFC: 13.56 MHz					
Number of Channels:	See Section 8.0					
	WiFi 2.4GHz: 802.11b: 11.12 dBm Avg. / 802.11g:12.16 dBm Avg. / 802.11n:11.79 dBm avg.					
Manuf. Max. Avg Rated Output Power:	BT:GFSK:11.70 dBm Avg. / PI/4-DQPSK: 8.74 dBm Avg. / 8-DPSK: 8.63 dBm Avg.					
	BLE: GMSK: -0.31 dBm Avg.					
	ANT: GFSK: -0.31 dBm Avg.					
	WiFi 802.11b/g/n: DSSS, OFDM, MCS0-7					
Modulation	BT: GFSK, PI/4-DQPSK					
	BLE:GMSK					
	ANT:GFSK					
Duty Cycle:	100.0%					
DUT Power Source:	5V USB, Internal Li-ion battery					
Deviation(s) from standard/procedure:	None					
Modification of DUT:	None					



3.0 SCOPE OF EVALUATION

The A03558, FCC ID: IPH-03558 ISED ID: 1792A-03558, is a wrist-worn transceiver that is capable of operating in the 2.4GHz WiFi and Bluetooth frequency bands with an additional NFC feature that operates at a fixed frequency of 13.56MHz. The device is intended for General Population Use. The product operates from an internal proprietary Li-ion rechargeable battery which can be connected to a compliant USB interface port, AC or DC adapter for charging. Test samples provided by the manufacturer were capable of transmitting at select frequencies and modulations preset by the manufacturer. An additional antenna modification was prepared for one sample allowing the ability to connect test equipment for antenna port conducted power analysis. The DUT was evaluated for SAR at the maximum conducted output power level, preset by the manufacturer and in accordance with the procedures described in IEEE 1528, IEC 62209-2, FCC KDB 865646, 447498, 248227 and RSS 102.



4.0 NORMATIVE REFERENCES

	Normative References*
ANSI / ISO 17025:2017	General Requirements for competence of testing and calibration laboratories
FCC CFR Title 47 Part 2	Code of Federal Regulations
Title 47:	Telecommunication
Part 2.1093:	Radiofrequency Radiation Exposure Evaluation: Portable Devices
Health Canada	
Safety Code 6 (2015)	Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3kHz to 300GHz
Industry Canada Spectrum	Management & Telecommunications Policy
RSS-102 Issue 5:	Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
IEEE International Committe	ee on Electromagnetic Safety
IEEE 1528-2013:	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR)
	in the Human Head from Wireless Communications Devices: Measurement Techniques
IEC International Standard	
IEC 62209-2 2010	Human exposure to radio frequency fields from hand-held and body-mounted wireless communication
	devices - Part 2
FCC KDB	
KDB 865664 D01v01r04	SAR Measurement Requirements for 100MHz to 6GHz
FCC KDB	
KDB 447498 D01v06	Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies
FCC KDB	
KDB 248227 D01v02r02	SAR Test Guidane for IEEE 802.11 (WiFI) Transmitters
* When the issue number	or issue date is omitted, the latest version is assumed.



5.0 STATEMENT OF COMPLIANCE

This measurement report demonstrates that samples of the product model(s) were evaluated for Specific Absorption Rate (SAR) on the date(s) shown, in accordance with the Measurement Procedures cited and were found to comply with the Standard(s) Applied based on the Exposure Limits of the Use Group indicated for which the product is intended to be used.

Applicant:	Model / HVIN:	
Garmin International Inc.	A03558	
Standard(s) Applied:	Measurement Procedure(s):	
FCC 47 CFR §2.1093	FCC KDB 865664, FCC KDB 447498, FC	C KDB 248227
Health Canada's Safety Code 6	Industry Canada RSS-102 Issue 5	
	IEEE Standard 1528-2013, IEC 62209-2	
Reason For Issue:	Use Group:	Limits Applied:
x New Certification	x General Population / Uncontrolled	1.6W/kg - 1g Volume
Class I Permissive Change		8.0W/kg - 1g Volume
Class II Permissive Change	Occupational / Controlled	x 4.0W/kg - 10g Volume
Reason for Change:		Date(s) Evaluated:
Original Filing		March 5th & 6th, 2019

The results of this investigation are based solely on the test sample(s) provided by the applicant which was not adjusted, modified or altered in any manner whatsoever except as required to carry out specific tests or measurements. A description of the device, operating configuration, detailed summary of the test results, methodologies and procedures used during this evaluation, the equipment used and the various provisions of the rules are included in this test report.

the data reported herein is true and accurate within the tolerance of the Measurement Instrument Uncertainty; that	Juit
I tests and measurements were performed in accordance with accepted practices or procedures; and that all tests and easurements were performed by me or by trained personnel under my direct supervision. The results of this investigation 'e based solely on the test sample(s) provided by the client which were not adjusted, modified or altered in any manner based solely and the test sample to carry out specific tests or measurements. This test report has been completed in	Trevor Whillock Test Lab Engineer Celltech Labs Inc.
accordance with ISO/IEC 17025.	15 July 2019 Date



6.0 SAR MEASUREMENT SYSTEM

SAR Measurement System

Celltech Labs Inc. SAR measurement facility employs a Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY6 measurement system is comprised of the measurement server, a robot controller, a computer, a near-field probe, a probe alignment sensor, an Elliptical Planar Phantom (ELI) phantom and a specific anthropomorphic mannequin (SAM) phantom for Head and/or Body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller and a teach pendant (Joystick) to control the robot's servo motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical form the DAE to digital electronic signal and transfers data to the DASY6 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gainswitching multiplexer, a fast 16-bit AD-converter, a command decoder and a control logic unit. Transmission to the DASY6 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot utilizes a controller with built in VME-bus computer.



DASY 6 SAR System





7.0 RF CONDUCTED POWER MEASUREMENT

Table 7.0 Conducted Power Measurements

	Conducted Power Measurements									
		Measured	Rated	Rated		SAR Test				
	Frequency	Power	Power	Power	Delta	Channel				
Channel	(MHz)	(dBm)	(dBm)	(W)	(dB)	(Y/N)	Mode	Modulatio	on	
1	2412	11.03	11.12	0.01	-0.09	-		DSS-1Mbps		
2	2417	10.81	11.12	0.01	-0.31	-		DSS-1Mbps		
3	2422	10.82	11.12	0.01	-0.30	-		DSS-1Mbps		
4	2427	10.76	11.12	0.01	-0.36	-		DSS-1Mbps		
5	2432	10.81	11.12	0.01	-0.31	-		DSS-1Mbps		
6	2437	11.02	11.12	0.01	-0.10	-		DSS-1Mbps		
7	2442	10.87	11.12	0.01	-0.25	-		DSS-1Mbps	000 11h	
8	2447	11.01	11.12	0.01	-0.11	-		DSS-1Mbps	002.110	
9	2452	10.90	11.12	0.01	-0.22	-		DSS-1Mbps		
10	2457	10.89	11.12	0.01	-0.23	-		DSS-1Mbps		
11	2462	10.91	11.12	0.01	-0.21	-		DSS-1Mbps		
		11.07	11.12	0.01	-0.05	-		DSS-2Mbps	1	
		10.59	11.12	0.01	-0.53	-		DSS-5.5Mbps		
		10.79	11.12	0.01	-0.33	-		DSS-11Mbps		
1	2412	11.92	12.16	0.02	-0.24	-		OFDM-6Mbps		
		12.16	12.16	0.02	0.00	Y		OFDM-54Mbps	802.11g	
		11.79	11.79	0.02	0.00	-	WLAN 2.4G	MCS-0		
		11.79	11.79	0.02	0.00	-		MCS-7	802.11n	
		11.06	11.12	0.01	-0.06	-		DSS-2Mbps		
		10.55	11.12	0.01	-0.57	-		DSS-5.5Mbps		
		10.60	11.12	0.01	-0.52	-		DSS-11Mbps	802.11b	
6	2437	11.81	12.16	0.02	-0.35	-		OFDM-6Mbps		
		11.96	12.16	0.02	-0.20	Y		OFDM-54Mbps	802.11g	
		11.70	11.79	0.02	-0.09	-		MCS-0		
		11.72	11.79	0.02	-0.07	-		MCS-7	802.11n	
		11.05	11.12	0.01	-0.07	-		DSS-2Mbps		
		10.56	11.12	0.01	-0.56	-		DSS-5.5Mbps		
		10.43	11.12	0.01	-0.69	-		DSS-11Mbps	802.11b	
11	2462	11.79	12.16	0.02	-0.37	-		OFDM-6Mbps		
		11.93	12.16	0.02	-0.23	Y		OFDM-54Mbps	802.11g	
		11.62	11.79	0.02	-0.17	-		MCS-0		
		11.73	11.79	0.02	-0.06	-		MCS-7	802.11n	



Table 7.1 Conducted Power Measurements

Conducted Power Measurements									
		Measured	Rated	Rated		SAR Test			
	Frequency	Power	Power	Power	Delta	Channel			
Channel	(MHz)	(dBm)	(dBm)	(W)	(dB)	(Y/N)	Mode	Modulation	
2	2402	11.65	11.70	0.01	-0.05	Y			
41	2441	10.62	11.70	0.01	-1.08	-			
80	2480	10.63	11.70	0.01	-1.07	-		BT(GFSK)	
		7.08	8.74	0.01	-1.66	-	BT/BLE/ANT	BT(PI/4-DQPSK)	
2	2402	7.08	8.63	0.01	-1.55	-		BT(8-DPSK)	
2	2402	-1.40	-0.31	0.001	-1.09	-		BLE(GMSK)	
		-1.80	-0.31	0.001	-1.49	-		ANT(GFSK)	

The rated power and tolerance are stated for typical transmission modes and data rates. Some modes and data rates may produce lower than rated conducted power levels. Power measurements taken across the various channels, modes and data rates did not produce levels in excess of the Rated Power plus Tolerance. SAR was evaluated using the power level setting and duty cycle specified by the manufacturer to be the max output power and produce the most conservative SAR. SAR was evaluated at the <u>maximum</u> <u>average</u> tune up tolerance. See section 2.0 Client and Device Information for details. The <u>reported</u> SAR was not scaled down.



8.0 NUMBER OF TEST CHANNELS (N_c) AND CONFIGURATIONS

This device is a wrist-worn device and was evaluated for extremity SAR. Although the intended use is to be wrist-worn with the back side of the device in contact with the human skin, the device was additionally evaluated to the worst case setup configuration leveraged from a previous EU evaluation. The Front side (Screen) of the device was found to be the worst case setup configuration and produced the highest SAR.

WiFi SAR Evaluation:

SAR was evaluated in OFDM mode with a sample rate of 54Mbps at a 100% duty cycle. The power level setting selected was specified by the manufacturer to be the max output power and produce the most conservative SAR.

As per FCC KDB 24827, the required 802.11 test channels are Ch1, Ch6 and Ch 11. Highest conducted output power was found on channel 1. Based on evaluated SAR level of the highest output channel; SAR test reduction methodology was applied to reduce the total number of required test channels and exclude channel 6 and channel 11 from SAR test evaluation.

When applicable, SAR test reduction methods may be utilized.

The initial test configuration for 2.4 GHz transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band.

When the reported SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until reported SAR is \leq 1.2 W/kg or all required channels are tested.

While 1-g SAR thresholds are specified in the procedures for SAR test reduction and exclusion, these thresholds should be multiplied by 2.5 when 10-g extremity SAR is considered.

Therefore; Channel 6 and 11 was not required for evaluation in any exposure configuration.

BT/BLE/ANT SAR Test Evaluation:

Bluetooth was evaluated for SAR at 9.52% duty cycle in the worst-case configuration from the WiFi test evaluation.

General SAR Test Reduction Considerations

As per KDB 447498D01,

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid band or highest output power channel is:

c) \leq 0.4W/kg or 1.0W/kg, for 1-g or 10-g respectively, when the transmission band is \geq 200Mh

BLE/ANT was not evaluated for SAR.

Per FCC KDB 447498 4.3.1 the BLE/ANT transmitter meets the standalone SAR test exclusion criteria. See section 11.0 for details.

NOTE: This device is not capable of simultaneous transmission between the BT/BLE/ANT and WiFi transmitters.

NFC:

The RFID transmitter is a low power communication device transmitter and does not require standalone SAR evaluation. Simultaneous transmission evaluation with it and the 802.11b/g/n or BT 802.15 is not required



9.0 ACCESSORIES EVALUATED

Table 9.0 Accessories Evaluated

	Manufacturer's Accessory List								
Test Report ID Number	Manufacturer's Part Number	Description	SAR Evaluated	SAR Tested					
B1	010-12932-01	18mm Watch Band, Black Silicone Strap	Y	Y					
B2	B07229DFS3	18mm Watch Band, stainless steel Metal Business Strap	Y	Y					
P1	362-00087-00	AC Adapter, 5.0V, 1.0A, USB-A Recpt	n/a	n/a					
P2	320-01069-20	USB Charging Cable	n/a	n/a					



10.0 SAR MEASUREMENT SUMMARY

Table 10.0: Measured Results

	Measured SAR Results (10g) - BODY(FCC/ISED)													
Date Plot I ID # M	Plot	DUT	Test Type	Test Freq.	Test Freq.	Accessories			DUT Spacing		Meas. Cond.	Measured SAR	SAR Drift	
	wodei			Modulation	Antenna	Battery	Body	Audio	DUT	Antenna	Power	10g		
				(MHz)		ID	ID	ID	ID	(<i>mm</i>)	(<i>mm</i>)	(dBm)	(<i>W/kg</i>)	(dB)
	Extremity SAR													
					WiFi & B	8T 2.4 GHz								
05 Mar 2019	B1	A03558	BODY-Back Side	2412	OFDM-54Mbps	n/a	n/a	B1	n/a	0	0	12.16	0.017	-0.190
05 Mar 2019	B2	A03558	BODY-Back Side	2412	OFDM-54Mbps	n/a	n/a	B2	n/a	0	0	12.16	0.013	0.800
06 Mar 2019	B3	A03558	BODY-Front Side	2412	OFDM-54Mbps	n/a	n/a	B1	n/a	0	0	12.16	0.095	-0.050
06 Mar 2019	B4	A03558	BODY-Back Side	2402	BT-GFSK	n/a	n/a	B1	n/a	0	0	11.65	0.022	0.600
06 Mar 2019	B5	A03558	BODY-Front Side	2402	BT-GFSK	n/a	n/a	B1	n/a	0	0	11.65	0.152	0.140
FCC 47 CFR 2.1093			093		Health Canada Safety Code 6		Extremity	10g A	verage	4.0	W/kg	Ge	eneral Popul	ation

Reference Section 8.0 for details



11.0 SCALING OF MAXIMUM MEASURED SAR

Table 11.0 SAR Scaling

			Scaling of I	Maximum	Measure	ed SAR ⁽¹⁾)				
			Meas		Measured			sured	Measured		
		Freq	Fluid Deviation				Conducted Power			er Drift	
Plot ID	Configuration	(MHz)	Permittivity	Condu	uctivity		(dBm)		(dB)		(W/kg)
B3	BODY-Front Side	2412	3.26%	3.8	37%		12.16		-0.	190	0.095
B5	BODY-Front Side	2402	3.39%	2.8	4%		11.65		0.	140	0.152
				Step	1						
			F	luid Sensitivity	Adjustment						
		Scale					Measured				Step 1 Adjusted
		Factor					SAR				SAR (10g)
Plot ID		(%)		X			(W/kg)			=	(W/kg)
B3		n/a		Х			0.095			=	0.095
B5		n/a		Х			0.152			=	0.152
				Step	2						
			Man	ufacturer's Tun	e-Up Tolerand	e					
	Measure	d	Ra	ted			Step 4 Adjusted SAD				Step 2 Adjusted
	Conducted P	ower	Po	wer		Delta		Step 1 Auju	ISLEU JAN		SAR (10g)
Plot ID	(dBm)		(dE	3m)		(dB)	+	(W/	(W/kg)		(W/kg)
B3	12.16		12	.16		0.0	+	0.095		=	0.095
B5	11.65		11	.70		-0.05	+	0.152		=	0.154
	Step 3 (ISED)										
				Drift Adjus	stment						
		Measured				64	on 2 Adjusted				Step 3 Adjusted
		Drift				Step 2 Aujusted SAN					SAR (10g)
Plot ID		(dB)		+	(W/kg)					=	(W/kg)
B3		-0.190		+			0.095		=	0.099	
B5		0.140		+	0.154 = 0.						
				Step 4 (FCC)						
			Simultaneous	Transmission	- Bluetooth a	nd/or WiFi					
	Rated Output		Separation		Estima	ted SAR		Stop 2 Adiu			Step 4 Adjusted
	Power (Pmax)	Freq	Distance		S	AR		Step 2 Aujt	JSIEU SAIN		SAR (10g)
Plot ID	(mW)	(MHz)	(mm)		(W	/kg)	+	(W/	kg)	=	(W/kg)
B3	12.16	2412	0		n	la	+	0.0	95	=	0.095
B5	11.7	2402	0			la	+	0.1	54	=	0.154
				Step	5						
				Reported	I SAR						
FCC								SED			
	From Steps 1 and 2				From Steps 1 through 3						
Plot ID		1	g SAR (W/kg)			1g SAR (W/kg)					
B3			0.095			0.099					
B5	0.154				0.154						



The SAR test exclusion threshold for the BLE/ANT transmitter as per FCC KDB 447498 4.3.1 is as follows:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] X [√f(GHz)] ≤ 7.5 for 10-g SAR

[(0.931)/(5)] X [√2.402] =0.289≤ 7.5

Where: max. power of channel, including tune-up tolerance, mW = 0.931 mW min. test separation distance, mm = 5mm f(GHz) = 2.402 GHz

Therefore; the BLE/ANT Transmitter meets the SAR test exclusion criteria.

NOTE: This device is not capable of simultaneous transmission between the BT/BLE/ANT and WiFi transmitters.

The RFID transmitter is a low power communication device transmitter and does not require standalone SAR evaluation. Simultaneous transmission evaluation with it and the 802.11b/g/n or BT 802.15 is not required



NOTES to Table 11.0

(1) Scaling of the Maximum Measured SAR is based on the highest, 100% duty cycle, Face, Body and/or Head SAR measured of ALL test channels, configurations and accessories used during THIS evaluation. The Measured Fluid Deviation parameters apply only to deviation of the tissue equivalent fluids used at the frequencies which produced the highest measured SAR. The Measured Conducted Power applies to the Conducted Power measured at the frequencies producing the highest Face and Body SAR. The Measured Drift is the SAR drift associated with that specific SAR measurement. The Reported SAR is the accumulation of all SAR Adjustments from the applicable Steps 1 through 4.

The Plot ID is for indentification of the SAR Measurement Plots in Annex A of this report.

NOTE: Some of the scaling factors in Steps 1 through 4 may not apply and are identified by light gray text.

Step 1

Per IEC-62209-1 and FCC KDB 865664. Scaling required only when Measured Fluid Deviation is greater than 5%. If the Measured Fluid Deviation is greater than 5%, Table 9.1 will be shown and will indicate the SAR scaling factor in percent (%). SAR is MULTIPLIED by this scaling factor only when the scaling factor is positive (+).

Step 2

Per KDB 447498. Scaling required only when the difference (Delta) between the Measured Conducted Power and the Manufacturer's Rated Conducted Power is (-) Negative. The absolute value of Delta is ADDED to the SAR.

Step 3

Per IEC 62209-1. Scaling required only when Measured Drift is (-) Negative. The absolute value of Measured Drift is added to Reported or Simultaneous Reported SAR.
Step 4

Per KDB 447498 4.3.2. The SAR, either measured or calculated, of ANY and ALL simultaneous transmitters must be added together and includes all contributors.

Step 5

The Reported SAR is the Maximum Final Adjusted Cumulative SAR from the applicable Steps 1 through 4 and are reported on Page 1 of this report.

I attest that the data reported herein is true and accurate within the tolerance of the Measurement Instrument Uncertainty; that all tests and measurements were performed in accordance with accepted practices or procedures; and that all tests and measurements were performed by me or by trained personnel under my direct supervision. The results of this investigation are based solely on the test sample(s) provided by the client which were not adjusted, modified or altered in any manner w hatsoever, except as required to carry out specific tests or measurements. This test report has been completed in accordance with ISO/IEC 17025.

Trevor Whillock Test Lab Engineer Celltech Labs Inc.

15 July 2019



12.0 SAR EXPOSURE LIMITS

Table 12.0 Exposure Limits

SAR RF EXPOSURE LIMITS									
FOC 47 CEDS2 4002	Lisetth Conside Safety Code C	General Population /	Occupational /						
FCC 47 CFRg2.1093	Health Canada Safety Code 6	Uncontrolled Exposure ⁽⁴⁾	Controlled Exposure ⁽⁵⁾						
Spa	tial Average ⁽¹⁾	0.08 W/ka	0.4.W/ka						
(averaged	over the whole body)	0.00 W/kg	0. 4 W/kg						
Sp	oatial Peak ⁽²⁾	1.6.W/kg	8 0 W/ka						
(Head and Trunk av	eraged over any 1 g of tissue)	1.0 W/kg	0.0 W/kg						
Sp	oatial Peak ⁽³⁾	4.0 W/ka	20.0 W/ka						
(Hands/Wrists/Feet/Ankles averaged over 10 g)									
(1) The Spatial Averag	e value of the SAR averaged over	the whole body.							
(2) The Spatial Peak v shape of a cube and o	value of the SAR averaged over a over the appropriate averaging tim	any 1 gram of tissue, defin e.	ed as a tissue volume in the						
(3) The Spatial Peak value of the SAR averaged over any 10 grams of tissue, defined as a tissue volume in the shape of a cube and over the appropriate averaging time.									
(4) Uncontrolled environments are defined as locations where there is potential exposure to individuals who have no knowledge or control of their potential exposure.									
(5) Controlled environ knowledge of their pot	(5) Controlled environments are defined as locations where there is potential exposure to individuals who have knowledge of their potential exposure and can exercise control over their exposure.								



13.0 DETAILS OF SAR EVALUATION

13.0 Day Log

	Dielectric							
Date	Ambient Temp ^o C	Fluid Temp °C	Pressure (kPa)	Humidity	TSL	Fluid	SPC	Test
05 Mar 2019	23	22.1	103.6	25%	2450B	Х	Х	X
06 Mar 2019	23	22.5	101.1	25%	2450B			Х



13.1 DUT Setup and Configuration

	DUT Setup and Configuration
1	The DUT was evaluated for SAR in accordance with the procedures described in IEEE 1528, FCC KDB 865646, 447498, 248277, and RSS-102. The device was evaluated at a phantom separation distance of 0mm with the back side of the deivce against the phantom.
2	The Device was capable of transmitting at various modulations and data rates. The Conducted Power was higher when measured in OFDM-54Mbps mode at 100% duty cycle than any other 2.4 GHz WiFi configuration. The DUT was evaluated for SAR in OFDM-54Mbps mode at the maximum conducted output power level, preset by the manufacturer.
3	The Device was capable of transmitting at various modulations and data rates. The Conducted Power was higher when measured in GFSK Mode for 2.4GHz Blutooth band than any other configuration.SAR was evaluated in GFSK mode using power level setting specified by the manufacture to be the max output power and produce the most conservative SAR. The highest measured maximum output power was measured on Ch 2 in GFSK mode.
4	Each SAR evaluation was performed with a fully charged battery.



13.2 DUT Positioning

DUT Positioning

Positioning

The DUT Positioner was securely fastened to the Phantom Platform. Registration marks were placed on the DUT and the Positioner to ensure consistent positioning of the DUT for each test evaluation.

FACE Configuration

This device is not intended to be held to the face and was not tested in the FACE configuration.

BODY Configuration

The DUT was securely clamped into the device holder with the surface of the DUT normally in contact with the body in direct contact with the bottom of the phantom, or 0mm separation from the DUTs accessory to the phantom surface.

HEAD Configuration

This device is not intended to be held to the ear and was not tested in the HEAD configuration.

Limb Worn Configuration

The DUT was positioned with the back side directly againts the phantom surface with the strap opened to allow direct contact or 0mm of the DUT and watch band to the phantom surface.

13.3 General Procedures and Report

General Procedures and Reporting

General Procedures

The fluid dielectric parameters of the Active Tissue Simulating Liquid (TSL) were measured as described in this Section, recorded and entered into the DASY Measurement Server. Active meaning the TSL used during the SAR evaluation of the DUT. The temperature of the Active TSL was measured and recorded prior to performing a System Performance Check (SPC). An SPC was performed with the Active TSL prior to the start of the test series. The temperature of the Active TSL was measured throughout the day and the Active TSL temperature was maintained to $\pm 0.5^{\circ}$ C. The Active TSL temperature was maintained to within $\pm 2.0^{\circ}$ C throughout the test series. The liquid parameters shall be measured within 24 hours before the start of a test series and if it takes longer than 48 hours, the liquid parameters shall also be measured at the end of the test series.

An Area Scan exceeding the length and width of the DUT projection was performed and the locations of all maximas within 2dB of the Peak SAR recorded. A Zoom Scan centered over the Peak SAR location(s) was performed and the 1g and 10g SAR values recorded. The resolutions of the Area Scan and Zoom Scan are described in the Scan Resolution table(s) in this Section. A Power Reference Measurement was taken at the phantom reference point immediately prior to the Area Scan. A Power Drift measurement was taken at the phantom reference point immediately prior to the Area Scan. A Zoom Scan from the <u>Maximum Distance to Phantom Surface</u> to the fluid surface was performed following the power drift measurement.

Reporting

The 1g SAR, 10g SAR and power drift measurements are recorded in the SAR Measurement Summary tables in the SAR Measurement Summary Section of this report. The SAR values shown in the 100% DC (Duty Cycle) column are the SAR values reported by the SAR Measurement Server with the DUT operating at 100% transmit duty cycle. These tables also include other information such as transmit channel and frequency, modulation, accessories tested and DUT-phantom separation distance.

In the Scaling of Maximum Measured SAR Section of this report, the highest measured SAR in the BODY configuration, within the entire scope of this assessment, are, when applicable, scaled for Fluid Sensitivity, Manufacturer's Tune-Up Tolerance, Simultaneous Transmission and Drift. With the exception of Duty Cycle correction/compensation, SAR values are <u>ONLY</u> scaled up, not down. The final results of this scaling is the *reported SAR* which appears on the Cover Page of this report.



13.4 Fluid Dielectric and Systems Performance Check

Fluid Dielectric and Systems Performance Check

Fluid Dielectric Measurement Procedure

The fluid dielectric parameters of the Tissue Simulating Liquid (TSL) are measured using the Open-Ended Coax Method connected to an Agilent 8753ET Network Analyzer connected to a measurement server running Aprel Dielectric Property Measurement System. A frequency range of \pm 100MHz for frequencies > 300MHz and \pm 50MHz for frequencies \leq 300MHz with frequency step size of 10MHz is used. The center frequency is centered around the SAR measurement probe's calibration point for that TSL frequency range. A calibration of the setup is performed using a short-open-deionized water (at 23°C in a 300ml beaker) method. A sample of the TSL is placed in a 300ml beaker and the open-ended coax is submerged approximately 8mm below the fluid surface in the approximate center of the beaker. A check of the setup is made to ensure no air is trapped under the open-ended coax. The sample of TSL is measured and compared to the FCC KDB 865664 targets for HEAD or BODY for the entire fluid measurement range. Fluid adjustment are made if the dielectric parameters are > 5% in range that the DUT is to be tested. If the adjustments fail to bring the parameters to \leq 5% but are < 10%, the SAR Fluid Sensitivity as per IEC 62201-1 and FCC KDB 865664 are applied to the highest measured SAR. A TSL with dielectric parameters > 10% in the DUT test frequency range are not used.

Systems Performance Check

The fluid dielectric parameters of the Active TSL are entered into the DASY Measurement Server at each of the 10MHz step size intervals. Active meaning the TSL used during the SAR evaluation of the DUT. The DASY Measurement System will automatically interpolate the dielectric parameters for DUT test frequencies that fall between the 10MHz step intervals.

A Systems Performance Check (SPC) is performed in accordance with IEEE 1528 "System Check" and FCC KDB 865664 "System Verification". A validation source, dipole or Confined Loop Antenna (CLA), is placed under the geometric center of the phantom and separated from the phantom in accordance to the validation source's Calibration Certificate data. A CW signal set to the frequency of the validate source's and SAR measurement probe's calibration frequency with a forward power set to the validation source's Calibration Certificate data power setting is applied to the validation source. An Area Scan is centered over the projection of the validation source's feed point and an Area Scan is taken. A Zoom Scan centered over the Peak SAR measurement of the Area Scan and the 1g and 10g SAR is measured. The measured 1g and 10g SAR is compared to the 1g and 10g SAR measurements from the validation source's Calibration Certificate. When required, the measured SAR is normalized to 1.0W and compared to the normalized SAR indicated on the validation source's Calibration Certificate. The SPC is considered valid when the measured and normalized SAR is 10% of the measured and normalize SAR of the validation source's Calibration Certificate.

The fluid dielectric parameters of the Active TSL and SPC are repeated when the Active TSL has been in use for greater than 84 hours or if the Active TSL temperature has exceed $\pm 1^{\circ}$ C of the initial fluid analysis.

13.5 Scan Resolution 100MHz to 2GHz

Scan Resolution 100MHz to 2GHz								
Maximum distance from the closest measurement point to phantom surface:	4 + 1 mm							
(Geometric Center of Probe Center)	41100							
Maximum probe angle normal to phantom surface.	E ⁰ ± 1 ⁰							
(Flat Section ELI Phantom)	9. T 1.							
Area Scan Spatial Resolution ΔX, ΔY	15 mm							
Zoom Scan Spatial Resolution ΔX , ΔY	7.5 mm							
Zoom Scan Spatial Resolution ΔZ	5 mm							
(Uniform Grid)	5 1111							
Zoom Scan Volume X, Y, Z	30 mm							
Phantom	ELI							
Fluid Depth	150 ± 5 mm							
An Area Scan with an area extending beyond the device was used to locate the candidate maximas within 2dB of the global maxima.								
A Zoom Scan centered over the peak SAR location(s) determined by the Area Scan was used								
to determine the 1-gram and 10-gram peak spatial-average SAR								



13.6 Scan Resolution 2GHz to 3GHz

Scan Resolution 2GHz to 3GHz							
Maximum distance from the closest measurement point to phantom surface:							
(Geometric Center of Probe Center)	4 ± 1 mm						
Maximum probe angle normal to phantom surface.	F 0 + 40						
(Flat Section ELI Phantom)	5° ± 1°						
Area Scan Spatial Resolution ΔX, ΔY	12 mm						
Zoom Scan Spatial Resolution ΔX , ΔY	5 mm						
Zoom Scan Spatial Resolution ΔZ	F						
(Uniform Grid)	5 mm						
Zoom Scan Volume X, Y, Z	30 mm						
Phantom	ELI						
Fluid Depth	150 ± 5 mm						
An Area Scan with an area extending beyond the device was used to locate the candidate maximas within 2dB of the global maxima.							
A Zoom Scan centered over the peak SAR location(s) determined by the Area Scan was used							
to determine the 1-gram and 10-gram peak spatial-average SAR							

13.7 Scan Resolution 5GHz to 6GHz

Scan Resolution 5GHz to 6GHz								
Maximum distance from the closest measurement point to phantom surface:	4 ± 1 mm							
(Geometric Center of Probe Center)	4111111							
Maximum probe angle normal to phantom surface.	$E^{0} \pm 4^{0}$							
(Flat Section ELI Phantom)	5 1							
Area Scan Spatial Resolution ΔX , ΔY	10 mm							
Zoom Scan Spatial Resolution ΔX , ΔY	4 mm							
Zoom Scan Spatial Resolution ∆Z	2 mm							
(Uniform Grid)	2 11111							
Zoom Scan Volume X, Y, Z	22 mm							
Phantom	ELI							
Fluid Depth	100 ± 5 mm							
An Area Scan with an area extending beyond the device was used to locate the candidate maximas within 2dB of the global maxima.								
A Zoom Scan centered over the peak SAR location(s) determined by the Area Scan was used								
to determine the 1-gram and 10-gram peak spatial-average SAR								



14.0 MEASUREMENT UNCERTAINTIES

Table 14.0 Measurement Uncertainty

UNCERTAINTY BUDGET FOR DEVICE EVALUATION (IEEE 1528-2013 Table 9)										
						Stand	Stand	Vi		
Source of Uncertainty	1528	Toler	Prob	Div	Ci	Ci	Unct	Unct	or	
	Section	±%	Dist				±%	±%	$V_{\rm eff}$	
Measurement System					(1g)	(10g)	(1g)	(10g)		
EX3DV4 Probe Calibration** (k=1)	E.2.1	6.7	N	1	1	1	6.7	6.7	8	
Axial Isotropy** (<i>k</i> =1)	E.2.2	0.6	R	√3	0.7	0.7	0.2	0.2	8	
Hemispherical Isotropy** (k=1)	E.2.2	3.2	R	√3	0.7	0.7	1.3	1.3	8	
Boundary Effect*	E.2.3	1.0	R	√3	1	1	0.6	0.6	8	
Linearity** (<i>k</i> =1)	E.2.4	0.5	R	√3	1	1	0.3	0.3	8	
System Detection Limits*	E.2.4	1.0	R	√3	1	1	0.6	0.6	8	
Modulation Response** (<i>k</i> =1)	E.2.5	8.3	R	√3	1	1	4.8	4.8	8	
Readout Electronics*	E.2.6	0.3	N	1	1	1	0.3	0.3	8	
Response Time*	E.2.7	0.8	R	√3	1	1	0.5	0.5	8	
Integration Time*	E.2.8	2.6	R	√3	1	1	1.5	1.5	8	
RF Ambient Conditions - Noise	E.6.1	0.0	R	√3	1	1	0.0	0.0	10	
RF Ambient Conditions - Reflection	E.6.1	0.0	R	√3	1	1	0.0	0.0	10	
Probe Positioner Mechanical Tolerance*	E.6.2	0.0	R	√3	1	1	0.0	0.0	8	
Probe Positioning wrt Phantom Shell*	E.6.3	0.4	R	√3	1	1	0.2	0.2	8	
Post-processing*	E.5	2.0	R	√3	1	1	1.2	1.2	8	
Test Sample Related										
Test Sample Positioning	E.4.2	2.2	Ν	1	1	1	2.2	2.2	5	
Device Holder Uncertainty*	E.4.1	3.6	Ν	1	1	1	3.6	3.6	×	
SAR Drift Measurement ⁽²⁾	E.2.9	0.0	R	√3	1	1	0.0	0.0	8	
SAR Power Scaling ⁽³⁾	E.6.5	0.0	R	√3	1	1	0.0	0.0	8	
Phantom and Tissue Parameters										
Phantom Uncertainty*	E.3.1	6.1	R	√3	1	1	3.5	3.5	8	
SAR Correction Uncertainty	E.3.2	1.6	N	1	1	0.84	1.6	1.3	8	
Liquid Conductivity (measurement)	E.3.3	5.0	Ν	1	0.78	0.71	3.9	3.6	10	
Liquid Permittivity (measurement)	E.3.3	5.0	Ν	1	0.23	0.26	1.2	1.3	10	
Liquid Conductivity (Temperature)	E.3.2	0.4	R	√3	0.78	0.71	0.2	0.2	10	
Liquid Permittivity Temperature)	E.3.2	0.2	R	√3	0.23	0.26	0.0	0.0	10	
Effective Degrees of Freedom	1)							V _{eff} =	1141	
Combined Standard Uncertainty			RSS				11.1	11.0		
Expanded Uncertainty (95% Confiden	ce Interval)		k=2				22.2	21.9		
Measurement Un	Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003									

(1) The Effective Degrees of Freedom is > 30

Therefore a coverage factor of k=2 represents an approximate confidence level of 95%.

(2) The SAR Value is compensated for Drift

(3) SAR Power Scaling not Required

* Provided by SPEAG for DASY4



Table 14.1 Calculation of Degrees of Freedom

Calculation of the Degrees and Effective Degrees of Freedom										
v _i = <i>n</i> - 1	$v_{eff} = \frac{u_c^4}{m}$ $\sum_{i=1}^{\infty} \frac{c_i^4 u_i^4}{v_i}$									



15.0 FLUID DIELECTRIC PARAMETERS

Table 15.0 Fluid Dielectric Parameters 2450MHz BODY TSL

Aprel Laboratory Test Result for UIM Dielectric Parameter Tue 05/Mar/2019 09:12:25 Freq Frequency(GHz) FCC_eHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon FCC_sHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma FCC_eB FCC Limits for Body Epsilon FCC_sB FCC Limits for Body Sigma Test_e Epsilon of UIM Test_s Sigma of UIM										
Freq	FCC_eBI	FCC_sB	Test_e	Test_s						
2.3500	52.83	1.85	54.66	1.91						
2.3600	52.82	1.86	54.63	1.91						
2.3700	52.81	1.87	54.46	1.91						
2.3800	52.79	1.88	54.54	1.92						
2.3900	52.78	1.89	54.32	1.94						
2.4000	52.77	1.90	54.59	1.95						
2.4100	52.75	1.91	54.41	1.98						
2.4200	52.74	1.92	54.69	2.01						
2.4300	52.73	1.93	54.15	2.06						
2.4400	52.71	1.94	54.38	2.03						
2.4500	52.70	1.95	54.64	2.06						
2.4600	52.69	1.96	54.61	2.07						
2.4700	52.67	1.98	54.46	2.05						
2.4800	52.66	1.99	54.54	2.06						
2.4900	52.65	2.01	54.14	2.08						
2.5000	52.64	2.02	54.08	2.11						
2.5100	52.62	2.04	54.13	2.12						
2.5200	52.61	2.05	54.11	2.16						
2.5300	52.60	2.06	54.17	2.17						
2.5400	52.59	2.08	54.07	2.18						
2.5500	52.57	2.09	54.32	2.20						



			FLUID	DIELECTRIC	PARAMETE	RS	
Date:	5 Mar 2019	Fluid Te	emp: 22.1	Frequency:	2450MHz	Tissue:	Body
Freq (MHz)		Test_e Test_s		Target_e	Target_s	Deviation Permittivity	Deviation Conductivity
2350.0000		54.6600	1.9100	52.8300	1.85	3.46%	3.24%
2360.0000		54.6300	1.9100	52.8200	1.86	3.43%	2.69%
2370.0000		54.4600	1.9100	52.8100	1.87	3.12%	2.14%
2380.0000		54.5400	1.9200	52.7900	1.88	3.32%	2.13%
2390.0000		54.3200	1.9400	52.7800	1.89	2.92%	2.65%
2400.0000		54.5900	1.9500	52.7700	1.90	3.45%	2.63%
2402.0000	*	54.5540	1.9560	52.7660	1.90	3.39%	2.84%
2410.0000		54.4100	1.9800	52.7500	1.91	3.15%	3.66%
2412.0000	*	54.4660	1.9860	52.7480	1.91	3.26%	3.87%
2420.0000		54.6900	2.0100	52.7400	1.92	3.70%	4.69%
2430.0000		54.1500	2.0600	52.7300	1.93	2.69%	6.74%
2437.0000	*	54.3110	2.0390	52.7160	1.94	3.03%	5.27%
2440.0000		54.3800	2.0300	52.7100	1.94	3.17%	4.64%
2450.0000		54.6400	2.0600	52.7000	1.95	3.68%	5.64%
2460.0000		54.6100	2.0700	52.6900	1.96	3.64%	5.61%
2462.0000	*	54.5800	2.0660	52.6860	1.96	3.59%	5.19%
2470.0000		54.4600	2.0500	52.6700	1.98	3.40%	3.54%
2472.0000		54.4760	2.0520	52.6680	1.98	3.43%	3.53%
2480.0000		54.5400	2.0600	52.6600	1.99	3.57%	3.52%
2490.0000		54.1400	2.0800	52.6500	2.01	2.83%	3.48%
2500.0000		54.0800	2.1100	52.6400	2.02	2.74%	4.46%
2510.0000		54.1300	2.1200	52.6200	2.04	2.87%	3.92%
2520.0000		54.1100	2.1600	52.6100	2.05	2.85%	5.37%
2530.0000		54.1700	2.1700	52.6000	2.06	2.98%	5.34%
2540.0000		54.0700	2.1800	52.5900	2.08	2.81%	4.81%
2550.0000		54.3200	2.2000	52.5700	2.09	3.33%	5.26%

*Channel Frequency Tested



16.0 SYSTEM VERIFICATION TEST RESULTS

Table 16.0 System Verification Results 2450MHz BODY TSL

System Verification Test Results							
Date		Frequency	Validation Source				
		(MHz)	P/N		S/N		
05 Mar 2019		2450	D2450V2		825		
	Fluid	Ambient	Ambient	Forward	Source		
Fluid Type	Temp	Temp	Humidity	Power	Spacing		
	°C	°C	(%)	(mW)	(mm)		
Body	22.1	23	25%	250	10		
Fluid Parameters							
Permittivity			Conductivity				
Measured	Target	Deviation	Measured Target		Deviation		
54.64	52.70	3.68%	2.06 1.95		5.64%		
Measured SAR							
	1 gram 10 gram						
Measured	Target	Deviation	Measured	Target	Deviation		
12.80	12.80	0.00%	5.90	6.05	-2.48%		
	Measured SAR Normalized to 1.0W						
1 gram			10 gram				
Normalized	Target	Deviation	Normalized	Target	Deviation		
51.20	50.40	1.59%	23.60	23.70	-0.42%		
Prior to the SAR evaluations, system checks were performed on the planar section of the							

phantom and a SPEAG validations, system checks were performed on the planar section of the phantom and a SPEAG validation dipole in accordance with the procedures described in IEEE 1528-2013, FCC KDB 846224 and IEC 62209-1.

The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using a Dielectric Probe Kit and a Network Analyzer.

The forward power was applied to the dipole and the system was verified to a tolerance of +10% from the system manufacturer's dipole calibration target SAR value.

The forward power applied was same forward power applied by the calibration lab during the calibration of this validation source.



17.0 SYSTEM VALIDATION SUMMARY

Table 17.0 System Validation Summary

System Validation Summary											
Frequency	Validation	Probe	Probe	Validation	Source Tissue		Tissue Dielectrics		Validation Results		
(MHz)	Date	Model	S/N	Source	S/N	IIssue	Permitivity	Conductivity	Sensitivity	Linearity	Isotropy
30	24-Sep-18	EX3DV4	3600	CLA-30	1005	Head	50.15	0.72	Pass	Pass	Pass
150	27-Jun-18	EX3DV4	3600	CLA-150	4007	Body	66.48	0.79	Pass	Pass	Pass
150	11-Jul-18	EX3DV4	3600	CLA-150	4007	Head	51.51	0.81	Pass	Pass	Pass
450	08-May-17	EX3DV4	3600	D450V3	1068	Body	54.65	0.95	Pass	Pass	Pass
450	16-May-17	EX3DV4	3600	D450V3	1068	Head	43.70	0.83	Pass	Pass	Pass
835	03-May-18	EX3DV4	3600	D835V2	4d075	Body	53.31	1.00	Pass	Pass	Pass
835	19-May-17	EX3DV4	3600	D835V2	4d075	Head	42.01	0.89	Pass	Pass	Pass
900	08-May-18	EX3DV4	3600	D900V2	045	Body	54.46	1.10	Pass	Pass	Pass
900	02-Aug-17	EX3DV4	3600	D900V2	045	Head	39.10	0.93	Pass	Pass	Pass
1640	06-May-18	EX3DV4	3600	1620-S-2	207-00102	Body	39.87	1.27	Pass	Pass	Pass
1640	07-May-18	EX3DV4	3600	1620-S-2	207-00102	Head	39.87	1.27	Pass	Pass	Pass
1800	21-Jul-17	EX3DV4	3600	D1800V2	247	Body	54.77	1.53	Pass	Pass	Pass
1800	18-Jul-17	EX3DV4	3600	D1800V2	247	Head	40.70	1.33	Pass	Pass	Pass
2450	23-May-18	EX3DV4	3600	D2450V2	825	Body	49.51	1.92	Pass	Pass	Pass
2450	24-May-18	EX3DV4	3600	D2450V2	825	Head	37.95	1.87	Pass	Pass	Pass
5250	24-Jul-18	EX3DV4	3600	D5GHzV2	1031	Body	46.42	5.69	Pass	Pass	Pass
5250	24-Jul-18	EX3DV4	3600	D5GHzV2	1031	Head	35.96	4.99	Pass	Pass	Pass
5750	25-Jul-18	EX3DV4	3600	D5GHzV2	1031	Body	47.10	5.60	Pass	Pass	Pass



18.0 MEASUREMENT SYSTEM SPECIFICATIONS

Table 18.0 Measurement System Specifications

Measurement System Specification						
Specifications						
Positioner	Stäubli Unimation Corp. Robot Model: TX90XL					
Repeatability	-/- 0.035 mm					
No. of axis	6.0					
Data Acquisition Electronic (DAE) System						
Cell Controller						
Processor Intel(R) Core(TM) i7-7700						
Clock Speed	3.60 GHz					
Operating System	Windows 10 Professional					
Data Converter						
Features	Signal Amplifier, multiplexer, A/D converter, and control logic					
Software	Measurement Software: DASY6, V 6.4.0.12171 / DASY52 V52.10.0.1446					
	Postprocessing Software: SEMCAD X, V14.6.10(Deployment Build)					
Connecting Lines Optical downlink for data and status info., Optical uplink for commands and clock						
DASY Measurement Server						
Function	Real-time data evaluation for field measurements and surface detection					
Hardware	Intel ULV Celeron CPU 400 MHz; 128 MB chip disk; 128 MB RAM					
Connections	COM1, COM2, DAE, Robot, Ethernet, Service Interface					
E-Field Probe						
Model	EX3DV4					
Serial No.	3600					
Construction	Triangular core fiber optic detection system					
Frequency	10 MHz to 6 GHz					
Linearity	±0.2 dB (30 MHz to 3 GHz)					
Phantom						
Туре	SAM Phantom					
Shell Material	Fiberglass					
Thickness	2mm +/2mm					
Volume	> 30 Liter					



Measurement System Specification					
Probe Specification					
	Symmetrical design with triangular core;				
Construction:	Built-in shielding against static charges				
Calibration:	In head simulating tissue at frequencies of 900 MHz				
Frequency:	10 MHz to > 6 GHz; Linearity: \pm 0.2 dB (30 MHz to 3 GHz)				
Directivity:	\pm 0.2 dB in head tissue (rotation around probe axis)				
Directivity.	\pm 0.4 dB in head tissue (rotation normal to probe axis)				
Dynamic Range:	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB				
Surface Detect:	\pm 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces				
	Overall length: 330 mm; Tip length: 16 mm;				
Dimensions:	Body diameter: 12 mm; Tip diameter: 6.8 mm				
	Distance from probe tip to dipole centers: 2.7 mm				
Application:	General dosimetry up to 3 GHz; Compliance tests of mobile phone	EX3DV4 E-Field Probe			
Phantom Specification					
The SAM V5.0 phant 2.0mm +/2mm at t IEEE 1528-2013, IEC	SAM Phantom				
Device Positioner Specification					
The DASY device po and the device inclina between the ear ope contains three pair of adjusted to the stand	sitioner has two scales for device rotation (with respect to the body axis) ation (with respect to the line between the ear openings). The plane nings and the mouth tip has a rotation angle of 65 ⁰ . The bottom plate f bolts for locking the device holder. The device holder positions are ard measurement positions in the three sections.	Device Positioner			



19.0 TEST EQUIPMENT LIST

Table 19.0 Equipment List and Calibration

Test Equipment List						
DESCRIPTION	ASSET NO.	SERIAL NO.	DATE CALIBRATED	CALIBRATION DUE		
Schmid & Partner DASY 6 System	-	-	-	-		
-DASY Measurement Server	00158	1078	CNR	CNR		
-Robot	00046	599396-01	CNR	CNR		
-DAE4	00019	353	20-Apr-18	20-Apr-19		
-EX3DV4 E-Field Probe	00213	3600	25-Apr-18	25-Apr-19		
-CLA 30 Validation Dipole	00300	1005	23-Nov-17	23-Nov-20		
-CLA150 Validation Dipole	00251	4007	27-Apr-17	27-Apr-20		
-D450V3 Validation Dipole	00221	1068	23-Apr-18	23-Apr-21		
-D750V3 Validation Dipole	00238	1061	19-Mar-19	19-Mar-22		
-D835V2 Validation Dipole	00217	4D075	20-Apr-18	20-Apr-21		
-D900V2 Validation Dipole	00020	54	24-Apr-17	24-Apr-20		
-D1640/1620-S-2 Validation Dipole	00299	207-00102	07-Nov-17	07-Nov-20		
-D2450V2 Validation Dipole*	00219	825	24-Apr-18	24-Apr-21		
-D5GHzV2 Validation Dipole	00126	1031	26-Apr-18	26-Apr-21		
ELI Phantom	00247	1234	CNR	CNR		
SAM Phantom	00154	1033	CNR	CNR		
HP 85070C Dielectric Probe Kit	00033	none	CNR	CNR		
Gigatronics 8652A Power Meter	00007	1835801	26-Mar-19	26-Mar-22		
Gigatronics 80701A Power Sensor	00248	1833687	26-Mar-19	26-Mar-22		
Gigatronics 80334A Power Sensor	00237	1837001	26-Mar-19	26-Mar-22		
HP 8753ET Network Analyzer	00134	US39170292	29-Dec-17	29-Dec-20		
Rohde & Schwarz SMR20 Signal Generator	00006	100104	29-May-17	29-May-20		
Amplifier Research 10W1000C Power Amplifier	00041	27887	CNR	CNR		
Amplifier Research 5S1G4 Power Amplifier	00106	26235	CNR	CNR		
Narda Directional Coupler 3020A	00064	-	CNR	CNR		
Traceable VWR Thermometer	00291	-	19-Nov-16	19-Nov-19		
Traceable VWR Jumbo Humidity/Thermometer	00295	170120555	17-Feb-17	17-Feb-20		
DC-18G 10W 30db Attenuator	00102	-	COU	COU		
R&S FSP40 Spectrum Analyzer	00241	100500	15-May-18	15-May-21		
RF Cable-SMA	00311	-	CNR	CNR		
HP Calibration Kit	00145	-	10-Feb-17	10-Feb-20		

CNR = Calibration Not Required

SB=Stand By

COU = Calibrate on Use

* Per KDB 865664 3.2.2; Supporting documentation is included in the report for validation dipoles exceeding the recommended anual calibration cycle. When applicable, reference Appendix F



20.0 FLUID COMPOSITION

Table 20.0 Fluid Composition 2450MHz BODY TSL

Tissue Simulating Liquid (TSL) Composition						
Component by Percent Weight						
Water	Glycol	Salt ⁽¹⁾	HEC ⁽²⁾	Bacteriacide ⁽³⁾		
69.98	30.0	0.02	0.0	0.0		

(1) Non-lodinized

(2) HydroxyEthyl-Cellulose: Sigma-Aldrich P/N 54290-500g

(3) Dow Chemical Dowicil 75 Antimicrobial Perservative



APPENDIX A – SYSTEM VERIFICATION PLOTS

Date/Time: 3/5/2019 9:58:36 AM

Test Laboratory: Celltech Labs

SPC-2450B Mar 05 2019

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN:825

Communication System: UID 0, CW (0); Communication System Band: FullSpan (0.0 - 6000.0 MHz); Frequency: 2450 MHz;Communication System PAR: 0 dB; PMF: 1

Medium: TSL_2450B[05MR19] Medium parameters used: f = 2450 MHz; σ = 2.06 S/m; ϵ_r = 54.64; ρ = 1000 kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 SN3600; ConvF(6.54, 6.54, 6.54); Calibrated: 4/25/2018, ConvF(6.54, 6.54, 6.54); Calibrated: 4/25/2018, ConvF(6.54, 6.54); Calibrated: 4/25/2018;
 - Modulation Compensation:
 - Sensor-Surface: 4mm (Mechanical Surface Detection), z = -1.5, 31.0, 151.0
- Electronics: DAE4 Sn353; Calibrated: 4/20/2018
- Phantom: Twin-SAM V4.0 (30deg probe tilt); Type: QD 000 P40 CC;
- DASY52 52.10.1(1476);

Frequency: 2450 MHz

SPC/SPC 2450B Input=250mw, Target=12.8W/kg/Area Scan (4x9x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 13.1 W/kg

SPC/SPC 2450B Input=250mw, Target=12.8W/kg/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 80.38 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 26.2 W/kg SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.9 W/kg Maximum value of SAR (measured) = 14.6 W/kg

SPC/SPC 2450B Input=250mw, Target=12.8W/kg/Z Scan (1x1x22): Measurement grid: dx=20mm, dy=20mm, dz=5mm

Penetration depth = 7.770 (7.518, 7.910) [mm] Maximum value of SAR (interpolated) = 21.8 W/kg









APPENDIX B – MEASUREMENT PLOTS OF MAXIMUMUM MEASURED SAR

Plot B3

Date/Time: 3/6/2019 11:49:26 AM

Test Laboratory: Celltech Labs

Garmin-2450B Mar 06 2019

DUT: A03558; Type: Sports Watch;

Communication System: UID 10077 - CAB, IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps); Communication System Band: WLAN 2.4GHz (2412.0 - 2484.0 MHz); Frequency: 2412 MHz;Communication System PAR: 11 dB; PMF: 1.62742

Medium: TSL_2450B[05MR19] Medium parameters used (interpolated): f = 2412 MHz; σ = 1.986 S/m; ϵ_r = 54.466; ρ = 1000 kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 SN3600; ConvF(6.54, 6.54, 6.54); Calibrated: 4/25/2018, ConvF(6.54, 6.54); Calibrated: 4/25/2018, ConvF(6.54, 6.54); Calibrated: 4/25/2018;
 - Modulation Compensation: PMR for UID 10077 CAB, Calibrated: 4/25/2018
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 4mm (Mechanical Surface Detection), z = -1.5, 31.0, 151.0
- Electronics: DAE4 Sn353; Calibrated: 4/20/2018
- Phantom: Twin-SAM V4.0 (30deg probe tilt); Type: QD 000 P40 CC;
- DASY52 52.10.1(1476);

Frequency: 2412 MHz

2450B/B3 A03558, Body-Front, 2412 MHz, Silicone Band-WIFI 2 2/Area Scan (8x7x1): Measurement grid: dx=12mm, dy=12mm

Info: Interpolated medium parameters used for SAR evaluation. Maximum value of SAR (measured) = 0.216 W/kg

2450B/B3 A03558, Body-Front, 2412 MHz, Silicone Band-WIFI 2 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 11.58 V/m; Power Drift = -0.05 dB Peak SAR (extrapolated) = 0.521 W/kg SAR(1 g) = 0.237 W/kg; SAR(10 g) = 0.095 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.282 W/kg

2450B/B3 A03558, Body-Front, 2412 MHz, Silicone Band-WIFI 2 2/Z Scan (1x1x19): Measurement grid: dx=20mm, dy=20mm, dz=20mm

Info: Interpolated medium parameters used for SAR evaluation. Penetration depth = n/a (n/a, 8.067) [mm] Maximum value of SAR (interpolated) = 0.389 W/kg









Plot B5

Date/Time: 3/6/2019 11:09:08 AM

Test Laboratory: Celltech Labs

Garmin-2450B Mar 06 2019

DUT: A03558; Type: Sports Watch;

Communication System: UID 10030 - CAA, IEEE 802.15.1 Bluetooth (GFSK, DH1); Communication System Band: ISM 2.4 GHz Band (2400.0 - 2483.5 MHz); Frequency: 2402 MHz;Communication System PAR: 5.3 dB; PMF: 1.83865

Medium: TSL_2450B[05MR19] Medium parameters used (interpolated): f = 2402 MHz; σ = 1.956 S/m; ϵ_r = 54.554; ρ = 1000 kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 SN3600; ConvF(6.54, 6.54, 6.54); Calibrated: 4/25/2018, ConvF(6.54, 6.54); Calibrated: 4/25/2018, ConvF(6.54, 6.54); Calibrated: 4/25/2018;
 - Modulation Compensation: PMR for UID 10030 CAA, Calibrated: 4/25/2018
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 4mm (Mechanical Surface Detection), z = -1.5, 31.0, 151.0
- Electronics: DAE4 Sn353; Calibrated: 4/20/2018
- Phantom: Twin-SAM V4.0 (30deg probe tilt); Type: QD 000 P40 CC;
- DASY52 52.10.1(1476);

Frequency: 2402 MHz

2450B/B5 A03558, Body-Front, 2402 MHz, Silicone Band-BT/Area Scan (8x7x1): Measurement grid: dx=12mm, dy=12mm

Info: Interpolated medium parameters used for SAR evaluation. Maximum value of SAR (measured) = 0.307 W/kg

2450B/B5 A03558, Body-Front, 2402 MHz, Silicone Band-BT/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 13.16 V/m; Power Drift = 0.14 dB Peak SAR (extrapolated) = 0.718 W/kg SAR(1 g) = 0.378 W/kg; SAR(10 g) = 0.152 W/kg

Info: Interpolated medium parameters used for SAR evaluation. Maximum value of SAR (measured) = 0.436 W/kg

2450B/B5 A03558, Body-Front, 2402 MHz, Silicone Band-BT/Z Scan (1x1x19): Measurement grid: dx=20mm, dy=20mm, dz=20mm

Info: Interpolated medium parameters used for SAR evaluation. Penetration depth = n/a (n/a, 8.612) [mm] Maximum value of SAR (interpolated) = 0.599 W/kg





