

Application For Grant of Certification

FOR

Model: A03672
2402-2480 MHz (DTS)
Broadband Digital Transmission System
FCC ID: IPH-03672
IC: 1792A-03672

FOR


Garmin International, Inc.

1200 East 151st Street
Olathe, KS 66062

FCC Designation: US5305
IC Test Site Registration: 3041A-1

Test Report Number: 190218

Authorized Signatory: *Scot D. Rogers*
Scot D. Rogers



ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

Engineering Test Report For Grant of Certification Application

FOR
47 CFR, PART 15C - Intentional Radiators
47 CFR Paragraph 15.247 and
Industry Canada RSS-GEN and RSS-247
License Exempt Intentional Radiator

For
Garmin International, Inc.

1200 East 151st Street
Olathe, KS 66062

Digital Transmission System
Model: A03672

Frequency Range 2402-2480 MHz
FCC ID: IPH-03672
IC: 1792A-03672

Test Date: February 18, 2019

Certifying Engineer: *Scot D. Rogers*
Scot D. Rogers
Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Telephone/Facsimile: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory.
This report must not be used by the client to claim product certification, approval, or
endorsement by NVLAP, NIST, or any agency of the Federal Government.

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 3

Garmin International, Inc.
Model: A03672
Test: 190218
Test to: CFR47 15C, RSS-Gen RSS-247
File: A03672 DTS TstRpt A03672 r3

SN's: 3989371048 / 3989371063
FCC ID: IPH-03672
IC: 1792A-03672
Date: March 19, 2019
Page 2 of 58

Table of Contents

TABLE OF CONTENTS.....	3
REVISIONS.....	6
FOREWORD.....	7
OPINION / INTERPRETATION OF RESULTS	7
EQUIPMENT TESTED.....	9
Equipment Function and Configuration.....	10
Equipment Configuration.....	10
APPLICATION FOR CERTIFICATION.....	11
APPLICABLE STANDARDS & TEST PROCEDURES	12
TESTING PROCEDURES	12
AC Line Conducted Emission Test Procedure	12
Radiated Emission Test Procedure.....	12
Antenna Port Conducted Emission Test Procedure.....	13
Diagram 1 Test arrangement for radiated emissions of tabletop equipment.....	14
Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS).....	15
Diagram 3 Test arrangement for Antenna Port Conducted emissions	16
TEST SITE LOCATIONS	16
LIST OF TEST EQUIPMENT	17
UNITS OF MEASUREMENTS	18
ENVIRONMENTAL CONDITIONS.....	18
STATEMENT OF MODIFICATIONS AND DEVIATIONS	18
INTENTIONAL RADIATORS.....	18
Antenna Requirements	18

Restricted Bands of Operation.....19

Table 1 Harmonic Radiated Emissions in Restricted Bands Data Tx 1 (2EDR (PI/4 DQPSK)19

Table 2 Harmonic Radiated Emissions in Restricted Bands Data Tx 1 (3EDR (8DPSK).....20

Table 3 Harmonic Radiated Emissions in Restricted Bands Data Tx 1 (BLE (GMSK).....21

Table 4 Harmonic Radiated Emissions in Restricted Bands Data Tx 2 (2EDR (PI/4 DQPSK)22

Table 5 Harmonic Radiated Emissions in Restricted Bands Data Tx 2 (3EDR (8DPSK).....23

Table 6 Harmonic Radiated Emissions in Restricted Bands Data Tx 2 (BLE (GMSK).....24

Summary of Results for Radiated Emissions in Restricted Bands24

General Radiated Emissions Procedure.....25

Table 7 General Radiated Emissions Data26

Summary of Results for General Radiated Emissions26

Operation in the Band 2400 – 2483.5 MHz27

Figure 1 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 1 (PI/4 DPQSK)28

Figure 2 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 1 (8DPSK).....28

Figure 3 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 1 (GMSK)29

Figure 4 Plot of Transmitter Emissions Low Band Edge Tx 1 (PI/4 DPQSK).....29

Figure 5 Plot of Transmitter Emissions Low Band Edge Tx 1 (8DPSK)30

Figure 6 Plot of Transmitter Emissions Low Band Edge Tx 1 (GMSK)30

Figure 7 Plot of Transmitter Emissions High Band Edge Tx 1 (PI/4 DPQSK)31

Figure 8 Plot of Transmitter Emissions High Band Edge Tx 1 (8DPSK).....31

Figure 9 Plot of Transmitter Emissions High Band Edge Tx 1 (GMSK)32

Figure 10 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 1 (PI/4 DPQSK).....32

Figure 11 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 1 (PI/4 DPQSK).....33

Figure 12 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 1 (8DPSK)33

Figure 13 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 1 (8DPSK)34

Figure 14 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 1 (GMSK).....34

Figure 15 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 1 (GMSK).....35

Figure 16 Plot of Transmitter Power Spectral Density Tx 1 (PI/4 DPQSK)35

Figure 17 Plot of Transmitter Power Spectral Density Tx 1 (8DPSK).....36

Figure 18 Plot of Transmitter Power Spectral Density Tx 2 (GMSK)36

Figure 19 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 2 (PI/4 DPQSK)37

Figure 20 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 2 (8DPSK).....37

Figure 21 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 2 (GMSK)38

Figure 22 Plot of Transmitter Emissions Low Band Edge Tx 2 (PI/4 DPQSK).....38
 Figure 23 Plot of Transmitter Emissions Low Band Edge Tx 2 (8DPSK)39
 Figure 24 Plot of Transmitter Emissions Low Band Edge Tx 2 (GMSK).....39
 Figure 25 Plot of Transmitter Emissions High Band Edge Tx 2 (PI/4 DPQSK)40
 Figure 26 Plot of Transmitter Emissions High Band Edge Tx 2 (8DPSK).....40
 Figure 27 Plot of Transmitter Emissions High Band Edge Tx 2 (GMSK)41
 Figure 28 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 2 (PI/4 DPQSK).....41
 Figure 29 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 2 (PI/4 DPQSK).....42
 Figure 30 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 2 (8DPSK)42
 Figure 31 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 2 (8DPSK)43
 Figure 32 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 2 (GMSK).....43
 Figure 33 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 2 (GMSK).....44
 Figure 34 Plot of Transmitter Power Spectral Density Tx 2 (PI/4 DPQSK)44
 Figure 35 Plot of Transmitter Power Spectral Density Tx 2 (8DPSK).....45
 Figure 36 Plot of Transmitter Power Spectral Density Tx 2 (GMSK)45
Transmitter Emissions Data.....46
 Table 9 Transmitter Radiated Emissions Tx 1 (PI/4 DPQSK)46
 Table 10 Transmitter Radiated Emissions Tx 1 (8DPSK)47
 Table 11 Transmitter Radiated Emissions Tx 1 (GMSK).....48
 Table 12 Transmitter Radiated Emissions Tx 2 (PI/4 DPQSK)49
 Table 13 Transmitter Radiated Emissions Tx 2 (8DPSK).....50
 Table 14 Transmitter Radiated Emissions Tx 2 (GMSK).....51
 Table 15 Transmitter Antenna Port Conducted Data.....52
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator.....53
ANNEX..... 54
Annex A Measurement Uncertainty Calculations.....55
Annex B Additional Test Equipment.....56
Annex C Rogers Qualifications.....57
Annex D Rogers Labs Certificate of Accreditation.....58

Revisions

Revision 3 Issued April 8, 2019 – Updated report to address Model Name correction

Revision 2 Issued March 28, 2019 – Updated Table of Contents

Revision 1 Issued March 19, 2019

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 3

Garmin International, Inc.
Model: A03672
Test: 190218
Test to: CFR47 15C, RSS-Gen RSS-247
File: A03672 DTS TstRpt A03672 r3

SN's: 3989371048 / 3989371063
FCC ID: IPH-03672
IC: 1792A-03672
Date: March 19, 2019
Page 6 of 58

Foreword

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under Code of Federal Regulations Title 47 (47 CFR) Paragraph 15.247 and Industry Canada RSS-GEN, Issue 5 and RSS-247 Issue 2, operation in the 2400 – 2483.5 MHz band.

Name of Applicant: Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062

M/N: A03672

FCC ID: IPH-03672

Industry Canada ID: 1792A-03672

Frequency Range: Both Tx 1 and Tx 2 operate across the 2402-2480 MHz band

Mode	Power (Watts)	99% OBW (kHz)	6-dB OBW (kHz)
Tx 1 2EDR (PI/4 DQPSK)	0.003	1,210.0	1,097.8
Tx 1 3EDR (8DPSK)	0.003	1,217.9	1,105.8
Tx 1 BLE (GMSK)	0.001	1,033.7	711.5
Tx 2 2EDR (PI/4 DQPSK)	0.006	1,234.0	1,089.7
Tx 2 3EDR (8DPSK)	0.006	1,234.0	1,089.7
Tx 2 BLE (GMSK)	0.004	1,025.6	721.2

This report addresses EUT Operations as Digital Transmission System using the following Transmitter modulations: Bluetooth® 2EDR (PI/4 DQPSK), 3EDR (8DPSK), and BLE (GMSK)

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Emissions 15.205, RSS-GEN	-7.4	Complies
Emissions as per 47 CFR paragraphs 2 and 15.207	N/A	Complies
Emissions as per 47 CFR paragraphs 2 and 15.209	-7.4	Complies
Harmonic Emissions per 47 CFR 15.247	-4.3	Complies
Power Spectral Density per 47 CFR 15.247	-17.6	Complies

Tests performed include

47CFR

15.247 (a) (2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one-Watt limit can be based on a measurement of the maximum conducted output power.

Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

RSS-247 Issue 2

5.2 Digital transmission systems

DTSs include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to the bands 902-928 MHz and 2400-2483.5 MHz

a)The minimum 6 dB bandwidth shall be 500 kHz.

b)The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d),(i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.4 Transmitter output power and equivalent isotropically radiated power (e.i.r.p.) requirements

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 3

Garmin International, Inc.
Model: A03672
Test: 190218
Test to: CFR47 15C, RSS-Gen RSS-247
File: A03672 DTS TstRpt A03672 r3

SN's: 3989371048 / 3989371063
FCC ID: IPH-03672
IC: 1792A-03672
Date: March 19, 2019
Page 8 of 58

d) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

5.5 Unwanted emissions

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Equipment Tested

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT	A03672	3989371048
EUT#2	A03672	3989371063
Interface Cable	OEM Wiring Harness N/A	

This reports documents test result for the two transmitters when providing communications as Digital Transmission Systems. Test results in this report relate only to the items tested

SW Version: 0.62

Equipment Function and Configuration

The EUT is a digital display unit providing vehicle information and touch screen input for the user. The design is vehicle mounted for use as a mobile transportation device. The design incorporates two transmitter circuitries operating in the 2402-2480 MHz band. The design offers cabled interface capabilities for the installation vehicle wiring harness as well as and wireless communications with compatible equipment. The EUT operates form direct current power provided by the installation vehicle and offers no provision for interface with utility AC power or other equipment as documented in this report. The transmitters designs provide wireless communications across the 2402-2480 MHz band. The design incorporates two transmitter systems providing communication modes including Bluetooth® Basic Rate (GFSK), 2EDR (PI/4 DQPSK), 3EDR (8DPSK), and BLE (GMSK). The EUT was arranged as described by the manufacturer emulating typical user configurations for testing purposes. Both transmitters were operational during testing to investigate intermodulation or collocation concerns. The EUT offers no other interface connections than those in the configuration option shown below as described by the manufacturer. For testing purposes, the EUT received power from external DC supply. During testing, the test system was configured to operate in manufacturer defined modes. Two samples were provided for testing, one representative of production hardware design, and the other modified for testing purposes replacing the integral antennas with RF connection ports. The antenna modifications offered testing facility the ability to connect test equipment to the temporary antenna ports for testing antenna port conducted emissions. The test samples were provided with test software enabling testing personnel the ability to enable transmitter functions on defined channels and modes. The test software enabled near 100% transmit duty cycle for testing purposes. As requested by the manufacturer and required by regulations, the equipment was tested for emissions compliance using the available configurations with the worse-case data presented. Test results in this report relate only to the products described in this report.

Equipment Configuration

- 1) Unit operating off internal battery



Unit under Test

Application for Certification

- (1) Manufacturer: Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062
- (2) Identification: M/N: A03672
FCC ID: IPH-03672 IC: 1792A-03672
- (3) Instruction Book:
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from Direct Current Power provided by installation vehicle. The EUT offers other interface ports for connection with vehicle system as presented in this filing.
- (9) Transition Provisions of 47 CFR 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards & Test Procedures

The following information is submitted in accordance with the eCFR Federal Communications Code of Federal Regulations, dated February 18, 2019, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.247, and Industry Canada RSS-GEN Issue 5, and RSS-247 Issue 2. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013. This report documents compliance for the EUT operations as Digital Transmission Systems operation.

Testing Procedures

AC Line Conducted Emission Test Procedure


The EUT operates on direct current power only provided by the aircraft installation. Therefore, no AC line conducted emission testing was required or performed.

Radiated Emission Test Procedure

Radiated emissions testing was performed as required in 47 CFR 15, KDB 558074 D01, v5, RSS-247 and specified in ANSI C63.10-2013. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. The frequency spectrum from 9 kHz to 25,000 MHz was searched for during preliminary investigation. Refer to diagrams one and two showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

Antenna Port Conducted Emission Test Procedure

The EUT was assembled as required for operation placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed presented in the regulations and specified in ANSI C63.10-2013. Testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and the spectrum analyzer. Refer to diagram three showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.



1—A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).


1.1—LISN spaced at least 80 cm from the nearest part of the EUT chassis.

2—Antenna can be integral or detachable, depending on the EUT (see 6.3.1).

3—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).

4—For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 1 Test arrangement for radiated emissions of tabletop equipment



AC Line Conducted Emissions (0.150 -30 MHz)		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak / Quasi Peak
Emissions (30-1000 MHz)		
RBW	AVG. BW	Detector Function
120 kHz	300 kHz	Peak / Quasi Peak
Emissions (Above 1000 MHz)		
RBW	Video BW	Detector Function
100 kHz	100 kHz	Peak
1 MHz	1 MHz	Peak / Average

Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)




Diagram 3 Test arrangement for Antenna Port Conducted emissions

Test Site Locations

- Conducted EMI AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259th Terrace, Louisburg, KS
- Radiated EMI The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259th Terrace, Louisburg, KS
- Registered Site # FCC Site: US5305 and Industry Canada Registration: 3041A-1
- NVLAP Accreditation Lab code 200087-0

List of Test Equipment

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
<input type="checkbox"/> LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	5/2/2018	5/2/2019
<input type="checkbox"/> LISN	Compliance Design	FCC-LISN-2.Mod.cd,(126)	.15-30MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303071)	9kHz-40 GHz	10/16/2018	10/16/2019
<input type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/16/2018	10/16/2019
<input type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/16/2018	10/16/2019
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/16/2018	10/16/2019
<input type="checkbox"/> Antenna	EMCO	3147 (40582)	200-1000MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	5/2/2018	5/2/2020
<input type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/16/2018	10/24/2019
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	5/15/2017	5/15/2019
<input checked="" type="checkbox"/> Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	1/31/2019	1/31/2020
<input type="checkbox"/> Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	12/22/2017	12/22/2018
<input type="checkbox"/> Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2019
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Power Meter	Agilent	N1911A with N1921A	0.05-40 GHz	5/2/2018	5/2/2019
<input type="checkbox"/> Generator	Rohde & Schwarz	SMB100A6 (100150)	20Hz-6 GHz	5/2/2018	5/2/2019
<input type="checkbox"/> Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50114 (017)1.5G HPF	30-18000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50105 (059) 6G HPF	30-18000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Fairview	SA6NFN100W-14 (1625)	30-1800 MHz	5/2/2018	5/2/2019
<input checked="" type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	5/2/2018	5/2/2019
<input checked="" type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1436)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (14362)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (14452)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1736)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	JFW Industries	50FH-010-10 (1)	30-18000 MHz	5/2/2018	5/2/2019
<input checked="" type="checkbox"/> Weather station	Davis	6312 (A81120N075)		10/26/2018	10/26/2019

Rogers Labs, Inc.
 4405 West 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214
 Revision 3

Garmin International, Inc.
 Model: A03672
 Test: 190218
 Test to: CFR47 15C, RSS-Gen RSS-247
 File: A03672 DTS TstRpt A03672 r3

SN's: 3989371048 / 3989371063
 FCC ID: IPH-03672
 IC: 1792A-03672
 Date: March 19, 2019
 Page 17 of 58

Units of Measurements

Conducted EMI Data is in dB μ V; dB referenced to one microvolt

Radiated EMI Data is in dB μ V/m; dB/m referenced to one microvolt per meter

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Gain = amplification gains and/or cable losses

RFS (dB μ V/m @ 3m) = FSM (dB μ V) + A.F. (dB) - Gain (dB)

Environmental Conditions

Ambient Temperature 19.3° C

Relative Humidity 31%

Atmospheric Pressure 1035.2 mb

Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to demonstrate compliance with the 47 CFR Part 15C, RSS-Gen, and RSS-247 emission requirements. There were no deviations to the specifications.

Intentional Radiators

The following information is submitted in support demonstration of compliance with the requirements of 47 CFR, Subpart C, paragraph 15.247 and Industry Canada RSS-247 and RSS-Gen the following information is submitted.

Antenna Requirements

The EUT incorporates integral antenna system and offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 Harmonic Radiated Emissions in Restricted Bands Data Tx 1 (2EDR (PI/4 DQPSK))

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Quasi-Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Quasi-Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)
2390.0	43.3	N/A	30.5	43.5	N/A	30.2	54.0
2483.5	61.5	N/A	37.7	51.4	N/A	33.9	54.0
4804.0	47.6	N/A	34.7	47.4	N/A	34.9	54.0
4882.0	47.2	N/A	34.5	47.6	N/A	34.6	54.0
4960.0	47.7	N/A	34.7	48.2	N/A	34.8	54.0
7206.0	51.6	N/A	38.2	51.4	N/A	38.1	54.0
7323.0	51.2	N/A	38.3	51.7	N/A	38.4	54.0
7440.0	50.6	N/A	38.2	51.2	N/A	38.1	54.0
12010.0	56.7	N/A	44.0	57.2	N/A	44.3	54.0
12205.0	57.3	N/A	44.0	57.4	N/A	44.2	54.0
12400.0	57.3	N/A	44.4	57.4	N/A	44.4	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 2 Harmonic Radiated Emissions in Restricted Bands Data Tx 1 (3EDR (8DPSK))

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
2390.0	45.0	N/A	30.8	43.8	N/A	30.1	54.0
2483.5	60.4	N/A	37.8	51.6	N/A	34.3	54.0
4804.0	47.4	N/A	34.7	47.8	N/A	34.7	54.0
4882.0	48.2	N/A	34.6	47.9	N/A	34.8	54.0
4960.0	47.9	N/A	34.7	47.4	N/A	34.7	54.0
7206.0	51.0	N/A	38.2	51.0	N/A	38.0	54.0
7323.0	51.2	N/A	38.2	51.7	N/A	38.4	54.0
7440.0	50.6	N/A	38.2	51.1	N/A	38.1	54.0
12010.0	57.1	N/A	44.2	57.1	N/A	44.1	54.0
12205.0	57.2	N/A	44.4	57.1	N/A	44.3	54.0
12400.0	57.2	N/A	44.4	57.7	N/A	44.5	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 3 Harmonic Radiated Emissions in Restricted Bands Data Tx 1 (BLE (GMSK))

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Quasi-Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Quasi-Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)
2390.0	43.3	N/A	30.1	44.0	N/A	29.9	54.0
2483.5	59.4	N/A	35.8	50.5	N/A	32.4	54.0
4804.0	47.6	N/A	34.8	48.5	N/A	34.7	54.0
4884.0	47.4	N/A	34.5	47.9	N/A	34.6	54.0
4960.0	47.3	N/A	34.8	47.6	N/A	34.7	54.0
7206.0	51.0	N/A	38.0	51.0	N/A	38.2	54.0
7326.0	51.5	N/A	38.2	51.2	N/A	38.3	54.0
7440.0	51.1	N/A	38.1	51.4	N/A	38.1	54.0
12010.0	57.5	N/A	44.1	57.4	N/A	44.2	54.0
12210.0	57.1	N/A	44.1	56.8	N/A	44.2	54.0
12400.0	57.3	N/A	44.4	57.2	N/A	44.3	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 4 Harmonic Radiated Emissions in Restricted Bands Data Tx 2 (2EDR (PI/4 DQPSK))

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
2390.0	43.7	N/A	30.2	46.3	N/A	31.4	54.0
2483.5	53.8	N/A	39.2	61.4	N/A	46.6	54.0
4804.0	47.6	N/A	34.7	47.5	N/A	34.8	54.0
4882.0	47.5	N/A	34.3	47.6	N/A	34.4	54.0
4960.0	47.3	N/A	34.7	47.9	N/A	34.8	54.0
7206.0	51.3	N/A	38.1	50.7	N/A	38.1	54.0
7323.0	51.7	N/A	38.1	51.3	N/A	38.2	54.0
7440.0	51.2	N/A	38.1	52.0	N/A	38.1	54.0
12010.0	57.3	N/A	44.2	56.4	N/A	44.0	54.0
12205.0	57.3	N/A	44.1	57.4	N/A	44.2	54.0
12400.0	58.3	N/A	44.3	57.4	N/A	44.3	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 5 Harmonic Radiated Emissions in Restricted Bands Data Tx 2 (3EDR (8DPSK))

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
2390.0	44.1	N/A	30.3	49.2	N/A	31.8	54.0
2483.5	56.0	N/A	40.4	62.5	N/A	46.6	54.0
4804.0	47.6	N/A	34.7	47.8	N/A	34.7	54.0
4882.0	47.2	N/A	34.4	47.5	N/A	34.4	54.0
4960.0	47.7	N/A	34.7	48.0	N/A	35.0	54.0
7206.0	51.1	N/A	38.0	51.0	N/A	38.1	54.0
7323.0	51.1	N/A	38.2	51.1	N/A	38.3	54.0
7440.0	51.0	N/A	38.1	51.1	N/A	38.1	54.0
12010.0	57.4	N/A	44.3	57.3	N/A	44.3	54.0
12205.0	57.2	N/A	44.2	57.3	N/A	44.2	54.0
12400.0	57.5	N/A	44.5	57.1	N/A	44.4	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 6 Harmonic Radiated Emissions in Restricted Bands Data Tx 2 (BLE (GMSK))

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Quasi-Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Quasi-Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)
2390.0	42.4	N/A	29.8	43.4	N/A	30.2	54.0
2483.5	45.7	N/A	32.4	51.4	N/A	37.1	54.0
4804.0	47.8	N/A	34.7	47.6	N/A	34.7	54.0
4884.0	47.8	N/A	34.5	47.6	N/A	34.5	54.0
4960.0	47.7	N/A	34.8	47.5	N/A	34.7	54.0
7206.0	50.6	N/A	38.1	51.6	N/A	38.1	54.0
7326.0	51.6	N/A	38.2	51.0	N/A	38.2	54.0
7440.0	51.4	N/A	38.1	51.3	N/A	38.2	54.0
12010.0	57.1	N/A	44.2	57.2	N/A	44.3	54.0
12210.0	57.1	N/A	44.3	57.3	N/A	44.1	54.0
12400.0	57.0	N/A	44.3	57.7	N/A	44.2	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of 47 CFR Part 15C RSS-Gen, and RSS-247 Intentional Radiators. The EUT worst-case BT and Wi-Fi operations demonstrated a minimum radiated emission margin of -7.4 dB below the requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available mode during testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated measurements were performed. Final data was taken with the EUT located on the OATS at 3 meters distance between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers above 1 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

Table 7 General Radiated Emissions Data

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
181.5	36.2	29.8	N/A	32.6	24.7	N/A	40.0
199.0	37.0	32.6	N/A	27.0	21.9	N/A	40.0
223.4	36.4	31.2	N/A	30.9	25.3	N/A	40.0
239.8	27.5	20.5	N/A	26.5	20.8	N/A	47.0
245.3	35.0	30.7	N/A	31.0	23.9	N/A	47.0
257.4	38.0	33.6	N/A	34.3	26.8	N/A	47.0
273.2	40.0	35.4	N/A	33.4	28.8	N/A	47.0
297.1	32.2	27.6	N/A	33.1	27.9	N/A	47.0
320.3	39.2	34.4	N/A	36.5	30.9	N/A	47.0
339.6	43.4	38.2	N/A	35.2	30.6	N/A	47.0
347.0	38.8	33.9	N/A	30.6	25.9	N/A	47.0
397.4	36.2	31.2	N/A	30.6	25.3	N/A	47.0
419.2	36.4	32.1	N/A	33.8	28.2	N/A	47.0
423.5	38.8	34.4	N/A	41.3	36.6	N/A	47.0
427.9	39.0	34.6	N/A	38.1	33.5	N/A	47.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47 CFR Part 15C paragraph 15.209, RSS-247 and RSS-GEN Intentional Radiators. The EUT demonstrated a minimum margin of -7.4 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 2400 – 2483.5 MHz

Test procedures of ANSI C63.10-2013 paragraph 6, and KDB 558074 were used during transmitter testing. Test sample #2 was provided for testing antenna port conducted emissions. This sample was modified by replacing the internal antenna with a 50-ohm antenna port connector and attenuator for testing purposes. The transmitter peak and average power was measured at the antenna port using a wideband RF power meter as described in KDB 558074 and ANSI C63.10-2013. Average power measured did not include any time intervals during which the transmitter was off or transmitting at a reduced power level. The peak Power Spectral Density (PKPSD) was measured as defined in KDB 558074 and ANSI C63.10-2013. DTS Emission bandwidth was measured as described in KDB 558074 and ANSI C63.10-2013. The amplitude of each harmonic and general radiated emission was measured on the OATS at distance of 3 meters from the FSM antenna (radiated emission testing was performed on sample #1 representative of production equipment with integral antenna). The EUT was positioned on supporting turntable elevated as required above the ground plane, at a distance of 3 meters from the FSM antenna. Radiated emission investigations were performed from 9 kHz to 25,000 MHz. Each radiated emission was maximized by varying the FSM antenna height and polarization, and by rotating the turntable. The worst-case amplitude of each emission was then recorded from the analyzer display. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Radiated Emissions were measured in dBµV/m @ 3 meters. Plots were taken of transmitter performance (using sample #2) for reference in this and other documentation.




Figure 1 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 1 (PI/4 DPQSK)




Figure 2 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 1 (8DPSK)




Figure 3 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 1 (GMSK)




Figure 4 Plot of Transmitter Emissions Low Band Edge Tx 1 (PI/4 DPQSK)




Figure 5 Plot of Transmitter Emissions Low Band Edge Tx 1 (8DPSK)




Figure 6 Plot of Transmitter Emissions Low Band Edge Tx 1 (GMSK)




Figure 7 Plot of Transmitter Emissions High Band Edge Tx 1 (PI/4 DPQSK)




Figure 8 Plot of Transmitter Emissions High Band Edge Tx 1 (8DPSK)




Figure 9 Plot of Transmitter Emissions High Band Edge Tx 1 (GMSK)




Figure 10 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 1 (PI/4 DPQSK)




Figure 13 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 1 (8DPSK)




Figure 14 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 1 (GMSK)




Figure 15 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 1 (GMSK)




Figure 16 Plot of Transmitter Power Spectral Density Tx 1 (PI/4 DPQSK)




Figure 17 Plot of Transmitter Power Spectral Density Tx 1 (8DPSK)




Figure 18 Plot of Transmitter Power Spectral Density Tx 2 (GMSK)




Figure 19 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 2 (PI/4 DPQSK)




Figure 20 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 2 (8DPSK)




Figure 21 Plot of Transmitter Emissions Operation in 2402-2480 MHz Tx 2 (GMSK)




Figure 22 Plot of Transmitter Emissions Low Band Edge Tx 2 (PI/4 DPQSK)




Figure 23 Plot of Transmitter Emissions Low Band Edge Tx 2 (8DPSK)




Figure 24 Plot of Transmitter Emissions Low Band Edge Tx 2 (GMSK)




Figure 25 Plot of Transmitter Emissions High Band Edge Tx 2 (PI/4 DPQSK)




Figure 26 Plot of Transmitter Emissions High Band Edge Tx 2 (8DPSK)




Figure 27 Plot of Transmitter Emissions High Band Edge Tx 2 (GMSK)




Figure 28 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 2 (PI/4 DPQSK)




Figure 29 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 2 (PI/4 DPQSK)




Figure 30 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 2 (8DPSK)




Figure 31 Plot of Transmitter Emissions 99% Occupied Bandwidth Tx 2 (8DPSK)




Figure 32 Plot of Transmitter Emissions 6-dB% Occupied Bandwidth Tx 2 (GMSK)




Figure 35 Plot of Transmitter Power Spectral Density Tx 2 (8DPSK)




Figure 36 Plot of Transmitter Power Spectral Density Tx 2 (GMSK)

Transmitter Emissions Data

Table 9 Transmitter Radiated Emissions Tx 1 (PI/4 DPQSK)

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
2402.0	--	--	--	--	--
4804.0	47.6	34.7	47.4	34.9	54.0
7206.0	51.6	38.2	51.4	38.1	54.0
9608.0	53.5	40.4	53.5	40.5	54.0
12010.0	56.7	44.0	57.2	44.3	54.0
14412.0	59.3	46.2	59.7	46.3	54.0
16814.0	62.9	49.6	62.2	49.5	54.0
2441.0	--	--	--	--	--
4882.0	47.2	34.5	47.6	34.6	54.0
7323.0	51.2	38.3	51.7	38.4	54.0
9764.0	53.1	40.4	53.3	40.3	54.0
12205.0	57.3	44.0	57.4	44.2	54.0
14646.0	60.0	46.8	59.4	46.7	54.0
17087.0	62.3	49.6	62.7	49.5	54.0
2480.0	--	--	--	--	--
4960.0	47.7	34.7	48.2	34.8	54.0
7440.0	50.6	38.2	51.2	38.1	54.0
9920.0	53.2	40.5	53.6	40.5	54.0
12400.0	57.3	44.4	57.4	44.4	54.0
14880.0	59.2	46.4	59.5	46.4	54.0
17360.0	62.3	49.1	62.1	49.0	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 10 Transmitter Radiated Emissions Tx 1 (8DPSK)

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)
2402.0	--	--	--	--	--
4804.0	47.4	34.7	47.8	34.7	54.0
7206.0	51.0	38.2	51.0	38.0	54.0
9608.0	53.4	40.4	53.3	40.7	54.0
12010.0	57.1	44.2	57.1	44.1	54.0
14412.0	59.2	46.3	59.3	46.2	54.0
16814.0	62.3	49.5	62.7	49.7	54.0
2441.0	--	--	--	--	--
4882.0	48.2	34.6	47.9	34.8	54.0
7323.0	51.2	38.2	51.7	38.4	54.0
9764.0	53.3	40.4	53.3	40.4	54.0
12205.0	57.2	44.4	57.1	44.3	54.0
14646.0	60.1	46.7	59.7	46.7	54.0
17087.0	62.4	49.6	63.0	49.6	54.0
2480.0	--	--	--	--	--
4960.0	47.9	34.7	47.4	34.7	54.0
7440.0	50.6	38.2	51.1	38.1	54.0
9920.0	53.4	40.4	53.6	40.5	54.0
12400.0	57.2	44.4	57.7	44.5	54.0
14880.0	59.5	46.4	59.3	46.4	54.0
17360.0	62.2	49.0	62.0	49.1	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 11 Transmitter Radiated Emissions Tx 1 (GMSK)

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)
2402.0	--	--	--	--	--
4804.0	47.6	34.8	48.5	34.7	54.0
7206.0	51.0	38.0	51.0	38.2	54.0
9608.0	53.9	40.4	53.4	40.4	54.0
12010.0	57.5	44.1	57.4	44.2	54.0
14412.0	58.6	46.2	59.1	46.3	54.0
16814.0	62.4	49.5	61.8	49.4	54.0
2442.0	--	--	--	--	--
4884.0	47.4	34.5	47.9	34.6	54.0
7326.0	51.5	38.2	51.2	38.3	54.0
9768.0	53.1	40.2	53.0	40.2	54.0
12210.0	57.1	44.1	56.8	44.2	54.0
14652.0	59.6	46.7	60.2	46.6	54.0
17094.0	62.5	49.2	62.3	49.3	54.0
2480.0	--	--	--	--	--
4960.0	47.3	34.8	47.6	34.7	54.0
7440.0	51.1	38.1	51.4	38.1	54.0
9920.0	53.3	40.3	52.8	40.2	54.0
12400.0	57.3	44.4	57.2	44.3	54.0
14880.0	59.1	46.3	59.5	46.4	54.0
17360.0	61.6	48.8	62.3	48.8	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 12 Transmitter Radiated Emissions Tx 2 (PI/4 DPQSK)

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)
2402.0	--	--	--	--	--
4804.0	47.6	34.7	47.5	34.8	54.0
7206.0	51.3	38.1	50.7	38.1	54.0
9608.0	53.4	39.9	52.3	39.6	54.0
12010.0	57.3	44.2	56.4	44.0	54.0
14412.0	59.4	46.3	59.1	46.3	54.0
16814.0	62.7	49.5	63.3	49.5	54.0
2441.0	--	--	--	--	--
4882.0	47.5	34.3	47.6	34.4	54.0
7323.0	51.7	38.1	51.3	38.2	54.0
9764.0	52.9	40.1	53.0	40.2	54.0
12205.0	57.3	44.1	57.4	44.2	54.0
14646.0	59.6	46.7	59.2	46.7	54.0
17087.0	62.7	49.2	61.6	49.3	54.0
2480.0	--	--	--	--	--
4960.0	47.3	34.7	47.9	34.8	54.0
7440.0	51.2	38.1	52.0	38.1	54.0
9920.0	53.2	40.4	53.3	40.1	54.0
12400.0	58.3	44.3	57.4	44.3	54.0
14880.0	59.4	46.4	59.5	46.4	54.0
17360.0	61.3	48.8	62.3	48.8	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 13 Transmitter Radiated Emissions Tx 2 (8DPSK)

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)
2402.0	--	--	--	--	--
4804.0	47.6	34.7	47.8	34.7	54.0
7206.0	51.1	38.0	51.0	38.1	54.0
9608.0	53.2	40.4	53.3	40.2	54.0
12010.0	57.4	44.3	57.3	44.3	54.0
14412.0	59.3	46.3	59.6	46.3	54.0
16814.0	62.2	49.4	62.4	49.3	54.0
2441.0	--	--	--	--	--
4882.0	47.2	34.4	47.5	34.4	54.0
7323.0	51.1	38.2	51.1	38.3	54.0
9764.0	53.4	40.1	53.7	40.1	54.0
12205.0	57.2	44.2	57.3	44.2	54.0
14646.0	59.5	46.7	59.3	46.7	54.0
17087.0	62.4	49.3	62.2	49.3	54.0
2480.0	--	--	--	--	--
4960.0	47.7	34.7	48.0	35.0	54.0
7440.0	51.0	38.1	51.1	38.1	54.0
9920.0	53.6	40.3	53.3	40.3	54.0
12400.0	57.5	44.5	57.1	44.4	54.0
14880.0	59.2	46.3	59.2	46.4	54.0
17360.0	61.9	48.8	61.8	48.8	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 14 Transmitter Radiated Emissions Tx 2 (GMSK)

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)
2402.0	--	--	--	--	--
4804.0	47.8	34.7	47.6	34.7	54.0
7206.0	50.6	38.1	51.6	38.1	54.0
9608.0	53.1	40.0	53.2	40.3	54.0
12010.0	57.1	44.2	57.2	44.3	54.0
14412.0	59.2	46.3	59.0	46.4	54.0
16814.0	62.5	49.4	62.7	49.4	54.0
2442.0	--	--	--	--	--
4884.0	47.8	34.5	47.6	34.5	54.0
7326.0	51.6	38.2	51.0	38.2	54.0
9768.0	53.2	40.2	53.8	40.2	54.0
12210.0	57.1	44.3	57.3	44.1	54.0
14652.0	59.6	46.7	60.3	46.7	54.0
17094.0	62.2	49.3	61.7	49.2	54.0
2480.0	--	--	--	--	--
4960.0	47.7	34.8	47.5	34.7	54.0
7440.0	51.4	38.1	51.3	38.2	54.0
9920.0	52.7	40.1	52.5	39.8	54.0
12400.0	57.0	44.3	57.7	44.2	54.0
14880.0	59.8	46.4	59.6	46.7	54.0
17360.0	61.4	48.8	61.7	48.8	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 15 Transmitter Antenna Port Conducted Data

Frequency MHz	Antenna Port Average Output Power (Watts)	99% Occupied Bandwidth (kHz)	6-dB Occupied Bandwidth (kHz)	Peak Power Spectral Density (dBm)
Tx 1 2EDR (PI/4 DPQSK)				
2402	0.003	1,210.0	1,097.8	-12.9
2441	0.002	1,210.0	1,097.8	-13.0
2480	0.002	1,210.0	1,089.7	-13.7
Tx 1 3EDR (8DPSK)				
2402	0.003	1,217.9	1,105.8	-14.2
2441	0.003	1,217.9	1,105.8	-14.3
2480	0.003	1,217.9	1,105.8	-14.7
Tx 1 BLE (GMSK)				
2402	0.001	1,025.6	711.5	-15.1
2441	0.001	1,033.7	701.9	-15.0
2480	0.001	1,033.7	701.9	-15.5
Tx 2 2EDR (PI/4 DPQSK)				
2412	0.006	1,234.0	1,081.7	-9.6
2437	0.005	1,234.0	1,089.7	-10.0
2462	0.005	1,226.0	1,089.7	-10.0
Tx 2 3EDR (8DPSK)				
2412	0.006	1,234.0	1,089.7	-10.3
2437	0.006	1,234.0	1,089.7	-10.5
2462	0.006	1,226.0	1089.7	-11.0
Tx 2 BLE (GMSK)				
2412	0.004	1,025.6	711.5	-11.2
2437	0.003	1,025.6	706.7	-11.3
2462	0.003	1,025.6	721.2	-11.8

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated and conducted emission requirements of 47CFR Part 15.247, RSS-GEN, and RSS-247 Digital Transmission Systems. Average output power measured at the antenna port was 0.006 Watts. The peak power spectral density measured at the antenna port presented a minimum margin of -17.6 dB below the requirements. The EUT demonstrated a minimum margin of -4.3 dB below the harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements. There were no other deviations or exceptions to the requirements.

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Additional Test Equipment
- Annex C Rogers Qualifications
- Annex D Rogers Labs Certificate of Accreditation

Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16-4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.14
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

Annex B Additional Test Equipment

List of Test Equipment	Calibration	Date (m/d/y)	Due
Antenna: Schwarzbeck Model: BBA 9106/VHBB 9124 (9124-627)		5/2/2018	5/2/2019
Antenna: Schwarzbeck Model: VULP 9118 A (VULP 9118 A-534)		5/2/2018	5/2/2019
Antenna: EMCO 6509		10/16/2018	10/16/2020
Antenna: EMCO 3143 (9607-1277) 20-1200 MHz		5/2/2018	5/2/2019
Antenna: EMCO Dipole Set 3121C		2/23/2018	2/23/2019
Antenna: C.D. B-101		2/23/2018	2/23/2019
Antenna: Solar 9229-1 & 9230-1		2/23/2018	2/23/2019
Cable: Belden 8268 (L3)		10/16/2018	10/16/2019
Cable: Time Microwave: 4M-750HF290-750		10/16/2018	10/16/2019
Frequency Counter: Leader LDC-825 (8060153)		5/2/2018	5/2/2019
Oscilloscope Scope: Tektronix 2230		2/23/2018	2/23/2019
Wattmeter: Bird 43 with Load Bird 8085		2/23/2018	2/23/2019
R.F. Generator: SMB100A6 s/n 100623		5/2/2018	5/2/2019
R.F. Generator: SBMBV100A s/n: 260771		5/2/2018	5/2/2019
R.F. Generators: HP 606A, HP 8614A, HP 8640B		2/23/2018	2/23/2019
R.F. Power Amp 65W Model: 470-A-1010		2/23/2018	2/23/2019
R.F. Power Amp 50W M185- 10-501		2/23/2018	2/23/2019
R.F. Power Amp A.R. Model: 10W 1010M7		2/23/2018	2/23/2019
R.F. Power Amp EIN Model: A301		2/23/2018	2/23/2019
LISN: Compliance Eng. Model 240/20		5/2/2018	5/2/2019
LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08		5/2/2018	5/2/2019
Audio Oscillator: H.P. 201CD		2/23/2018	2/23/2019
ESD Test Set 2010i		2/23/2018	2/23/2019
Oscilloscope Scope: Tektronix MDO 4104		2/23/2018	2/23/2019
EMC Transient Generator HVT TR 3000		2/23/2018	2/23/2019
AC Power Source (Ametech, California Instruments)		2/23/2018	2/23/2019
Fast Transient Burst Generator Model: EFT/B-101		2/23/2018	2/23/2019
Field Intensity Meter: EFM-018		2/23/2018	2/23/2019
KEYTEK Ecat Surge Generator		2/23/2018	2/23/2019
ESD Simulator: MZ-15		2/23/2018	2/23/2019
Shielded Room not required			

Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has approximately 30 years' experience in the field of electronics. Engineering experience includes six years in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

Positions Held


Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.



Scot D. Rogers

Annex D Rogers Labs Certificate of Accreditation

United States Department of Commerce
National Institute of Standards and Technology

NVLAP®

Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 200087-0

Rogers Labs, Inc.
Louisburg, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

2018-02-21 through 2019-03-31
Effective Dates




For the National Voluntary Laboratory Accreditation Program

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 3

Garmin International, Inc.
Model: A03672
Test: 190218
Test to: CFR47 15C, RSS-Gen RSS-247
File: A03672 DTS TstRpt A03672 r3

SN's: 3989371048 / 3989371063
FCC ID: IPH-03672
IC: 1792A-03672
Date: March 19, 2019
Page 58 of 58