

FCC RF Exposure Report

FCC ID	:	IPH-03958
Equipment	:	Smart Watch
Model No.	:	A03958
Brand Name	:	GARMIN
Applicant	:	Garmin International, Inc.
Address	:	1200 E. 151st Street Olathe, KS 66062 United States
Standard	:	47 CFR FCC Part 2.1093
Received Date	:	Apr. 30, 2020
Tested Date	:	Mar. 27 ~ Jun. 09, 2020

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

Reviewed by:

Approved by:

one C

Along Chen/ Assistant Manager Gary Chang / Manager





Table of Contents

1	EXPOSURE EVALUATION OF PORTABLE DEVICES	4
1.1	SAR TEST EXCLUSION THRESHOLD FOR 100MHz to 6GHz and \leq 50mm	4
1.2	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	5
1.4	EVALUATION RESULTS	6
2	TEST LABORATORY INFORMATION	7



Release Record

Report No.	Version	Description	Issued Date
FA051401	Rev. 01	Initial issue	Jul. 01, 2020



1 EXPOSURE EVALUATION OF PORTABLE DEVICES

1.1 SAR TEST EXCLUSION THRESHOLD FOR 100MHz to 6GHz and \leq 50mm

Frequency (MHz)	5	10	15	20	25	Separation distance (mm)
150	39	77	116	155	194	
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	SAR Test Exclusion
1900	11	22	33	44	54	Threshold (mW)
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Note: 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above table

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

•f(GHz) is the RF channel transmit frequency in GHz

• Power and distance are rounded to the nearest mW and mm before calculation

• The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



1.2 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

1.3 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2) $\,$

Parameters	Uncertainty				
Conducted power	±0.808 dB				

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1.4 EVALUATION RESULTS

Maximum Conducted Output Power Result							
Conditi	RF Output Power (dBm)						
Modulation Mode	Freq. (MHz)	Average Power (dBm)	Rated Power (dBm)	Rated Power (mW)	Distance (mm)	Threshold	SAR Test Exclusion Thresholds
LE-1Mbps	2402	0.44	0.5	1.12	5	0.35	7.5
LE-1Mbps	2440	-0.02	0	1	5	0.31	7.5
LE-1Mbps	2480	-0.41	0	1	5	0.31	7.5
BT-BR(1Mbps)	2402	12.60	13	19.95	5	6.18	7.5
BT-BR(1Mbps)	2441	12.59	13	19.95	5	6.23	7.5
BT-BR(1Mbps)	2480	12.58	13	19.95	5	6.28	7.5
BT-EDR(2Mbps)	2402	9.02	9.5	8.91	5	2.76	7.5
BT-EDR(2Mbps)	2441	9.14	9.5	8.91	5	2.78	7.5
BT-EDR(2Mbps)	2480	8.90	9	7.94	5	2.50	7.5
BT-EDR(3Mbps)	2402	9.05	9.5	8.91	5	2.76	7.5
BT-EDR(3Mbps)	2441	9.14	9.5	8.91	5	2.78	7.5
BT-EDR(3Mbps)	2480	8.91	9	7.94	5	2.50	7.5

Maximum Conducted Output Power Result							
Conditi	RF Output Power (dBm)						
Modulation Mode	Freq. (MHz)	Average Power (dBm)	Rated Power (dBm)	Rated Power (mW)	Distance (mm)	Threshold	SAR Test Exclusion Thresholds
802.11b	2412	10.55	11	12.59	5	3.91	7.5
802.11b	2437	10.04	10.5	11.22	5	3.50	7.5
802.11b	2462	9.33	9.5	8.91	5	2.80	7.5
802.11g	2412	11.33	11.5	14.13	5	4.39	7.5
802.11g	2437	10.85	11	12.59	5	3.93	7.5
802.11g	2462	10.32	10.5	11.22	5	3.52	7.5
802.11 HT20	2412	11.25	11.5	14.13	5	4.39	7.5
802.11 HT20	2437	10.77	11	12.59	5	3.93	7.5
802.11 HT20	2462	10.21	10.5	11.22	5	3.52	7.5

Thresholds is < SAR test exclusion thresholds. Thus, SAR test is not required.



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <u>http://www.icertifi.com.tw</u>.

Linkou Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C. Kwei Shan Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C. Kwei Shan Site II Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155 Email: ICC_Service@icertifi.com.tw

—END—