

# FCC Test Report

Product Name	LinkCard
Model No.	IXWW22
FCC ID.	IPH-04150

Applicant	Garmin International, Inc.
Address	1200 E. 151st Street Olathe, KS 66062 United States

Date of Receipt	Jun. 17, 2021
Issued Date	Aug. 27, 2021
Report No.	2160704R-E3032110108
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

# Test Report


Issued Date: Aug. 27, 2021

Report No.: 2160704R-E3032110108




Product Name	LinkCard
Applicant	Garmin International, Inc.
Address	1200 E. 151st Street Olathe, KS 66062 United States
Manufacturer	Garmin International, Inc.
Model No.	IXWW22
FCC ID.	IPH-04150
EUT Rated Voltage	DC 9~16V
EUT Test Voltage	AC 120V
Trade Name	GARMIN
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C ANSI C63.4: 2014, ANSI C63.10: 2013
Test Result	Complied

Documented By :




(Project Specialist / Ida Tung)

Tested By :



(Senior Engineer / Bill Lin)

Approved By :



(Supervisor / Eason Chen)

## TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION .....</b>	<b>6</b>
1.1. EUT Description.....	6
1.2. Tested System Details.....	8
1.3. Configuration of Tested System .....	8
1.4. EUT Exercise Software .....	8
1.5. Test Facility .....	9
1.6. List of Test Equipment.....	10
1.7. Uncertainty .....	11
<b>2. CONDUCTED EMISSION .....</b>	<b>12</b>
2.1. Test Setup .....	12
2.2. Limits.....	12
2.3. Test Procedure .....	13
2.4. Test Result of Conducted Emission.....	14
<b>3. PEAK POWER OUTPUT .....</b>	<b>16</b>
3.1. Test Setup .....	16
3.2. Limit .....	16
3.3. Test Procedure .....	16
3.4. Test Result of Peak Power Output.....	17
<b>4. RADIATED EMISSION .....</b>	<b>19</b>
4.1. Test Setup .....	19
4.2. Limits.....	20
4.3. Test Procedure .....	21
4.4. Test Result of Radiated Emission.....	22
<b>5. RF ANTENNA CONDUCTED TEST .....</b>	<b>36</b>
5.1. Test Setup .....	36
5.2. Limits.....	36
5.3. Test Procedure .....	36
5.4. Test Result of RF Antenna Conducted Test.....	37
<b>6. BAND EDGE .....</b>	<b>39</b>
6.1. Test Setup .....	39
6.2. Limit .....	40
6.3. Test Procedure .....	40
6.4. Test Result of Band Edge .....	41
<b>7. CHANNEL NUMBER.....</b>	<b>53</b>
7.1. Test Setup .....	53
7.2. Limit .....	53
7.3. Test Procedure .....	53
7.4. Test Result of Channel Number.....	54
<b>8. CHANNEL SEPARATION.....</b>	<b>56</b>
8.1. Test Setup .....	56
8.2. Limit .....	56
8.3. Test Procedure .....	56
8.4. Test Result of Channel Separation.....	57
<b>9. DWELL TIME.....</b>	<b>61</b>
9.1. Test Setup .....	61
9.2. Limit .....	61
9.3. Test Procedure .....	61

---

9.4.	Test Result of Dwell Time .....	62
<b>10.</b>	<b>OCCUPIED BANDWIDTH .....</b>	<b>66</b>
10.1.	Test Setup .....	66
10.2.	Limits.....	66
10.3.	Test Procedure .....	66
10.4.	Test Result of Occupied Bandwidth .....	67
<b>11.</b>	<b>DUTY CYCLE .....</b>	<b>71</b>
11.1.	Test Setup .....	71
11.2.	Test Result of Duty Cycle.....	72
<b>12.</b>	<b>EMI REDUCTION METHOD DURING COMPLIANCE TESTING .....</b>	<b>74</b>
Appendix 1: EUT Test Photographs		
Appendix 2: EUT Detailed Photographs		

---

## Revision History

<b>Report No.</b>	<b>Version</b>	<b>Description</b>	<b>Issued Date</b>
2160704R-E3032110108	V1.0	Initial issue of report.	Aug. 27, 2021

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	LinkCard
Trade Name	GARMIN
Model No.	IXWW22
FCC ID.	IPH-04150
Frequency Range	2402 – 2480MHz
Channel Number	79
Type of Modulation	FHSS: GFSK(1Mbps) / $\pi$ /4DQPSK(2Mbps) / 8DPSK(3Mbps)
Antenna Type	Chip Antenna
Channel Control	Auto
Antenna Gain	Refer to the table “Antenna List”
Contain Module	Cypress / CYW89820

#### Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	INPAQ	VGAP-CLA-AS-A1	Chip Antenna	1.46 dBi for 2.4 GHz

Note: The antenna of EUT conforms to FCC 15.203.

Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 00:	2402 MHz	Channel 20:	2422 MHz	Channel 40:	2442 MHz	Channel 60:	2462 MHz
Channel 01:	2403 MHz	Channel 21:	2423 MHz	Channel 41:	2443 MHz	Channel 61:	2463 MHz
Channel 02:	2404 MHz	Channel 22:	2424 MHz	Channel 42:	2444 MHz	Channel 62:	2464 MHz
Channel 03:	2405 MHz	Channel 23:	2425 MHz	Channel 43:	2445 MHz	Channel 63:	2465 MHz
Channel 04:	2406 MHz	Channel 24:	2426 MHz	Channel 44:	2446 MHz	Channel 64:	2466 MHz
Channel 05:	2407 MHz	Channel 25:	2427 MHz	Channel 45:	2447 MHz	Channel 65:	2467 MHz
Channel 06:	2408 MHz	Channel 26:	2428 MHz	Channel 46:	2448 MHz	Channel 66:	2468 MHz
Channel 07:	2409 MHz	Channel 27:	2429 MHz	Channel 47:	2449 MHz	Channel 67:	2469 MHz
Channel 08:	2410 MHz	Channel 28:	2430 MHz	Channel 48:	2450 MHz	Channel 68:	2470 MHz
Channel 09:	2411 MHz	Channel 29:	2431 MHz	Channel 49:	2451 MHz	Channel 69:	2471 MHz
Channel 10:	2412 MHz	Channel 30:	2432 MHz	Channel 50:	2452 MHz	Channel 70:	2472 MHz
Channel 11:	2413 MHz	Channel 31:	2433 MHz	Channel 51:	2453 MHz	Channel 71:	2473 MHz
Channel 12:	2414 MHz	Channel 32:	2434 MHz	Channel 52:	2454 MHz	Channel 72:	2474 MHz
Channel 13:	2415 MHz	Channel 33:	2435 MHz	Channel 53:	2455 MHz	Channel 73:	2475 MHz
Channel 14:	2416 MHz	Channel 34:	2436 MHz	Channel 54:	2456 MHz	Channel 74:	2476 MHz
Channel 15:	2417 MHz	Channel 35:	2437 MHz	Channel 55:	2457 MHz	Channel 75:	2477 MHz
Channel 16:	2418 MHz	Channel 36:	2438 MHz	Channel 56:	2458 MHz	Channel 76:	2478 MHz
Channel 17:	2419 MHz	Channel 37:	2439 MHz	Channel 57:	2459 MHz	Channel 77:	2479 MHz
Channel 18:	2420 MHz	Channel 38:	2440 MHz	Channel 58:	2460 MHz	Channel 78:	2480 MHz
Channel 19:	2421 MHz	Channel 39:	2441 MHz	Channel 59:	2461 MHz		

Note:

1. The EUT is a LinkCard with built-in Bluetooth transceiver, this report for Bluetooth V4.2 LE + EDR.
2. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. These tests were conducted on a sample for the purpose of demonstrating compliance of transmitter with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.
5. The test mode is based on the Bluetooth technology, while testing 1Mbps, 2Mbps and 3Mbps, the worst case is 1Mbps and 3Mbps, and only worse case data is recorded in this report.

Test Mode	Mode 1: Transmit - 1Mbps Mode 2: Transmit - 3Mbps
-----------	--


### 1.2. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Power Adapter	PHIHONG	PSAC24A-120L6	N/A	N/A
2 Notebook PC	DELL	Latitude E5440	HG26TZ1	N/A
3 LINKCARD fixture board	Garmin	105-04151-00 VER 2	N/A	N/A
4 UART to USB adapter board	Garmin	EPCB-0000721 GARMIN V3	N/A	N/A

Signal Cable Type	Signal cable Description
A Power Cable	Non-shielded, 1.8m
B Power Cable	Non-shielded, 1.5m
C Power Cable	Non-shielded, 0.2m
D Signal Cable	Non-shielded, 0.2m
E Signal Cable	Non-shielded, 0.2m
F USB Cable	Shielded, 1.0m, with one ferrite core bonded.

### 1.3. Configuration of Tested System



### 1.4. EUT Exercise Software

1. Setup the EUT as shown in Section 1.3.
2. Execute software “CyBluetool Version 0.1.97.1” on the EUT.
3. Configure the test mode, the test channel, and the data rate.
4. Press “OK” to start the continuous Transmit.
5. Verify that the EUT works properly.



## 1.5. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual
Conducted Emission	Temperature (°C)	10~40 °C	27.8 °C
	Humidity (%RH)	10~90 %	55.2 %
Radiated Emission	Temperature (°C)	10~40 °C	22.5 °C
	Humidity (%RH)	10~90 %	62.5 %
Conductive	Temperature (°C)	10~40 °C	22.0 °C
	Humidity (%RH)	10~90 %	55.0 %

**USA : FCC Registration Number: TW0033**

**Canada : IC Registration Number: 26930**

Site Description : Accredited by TAF  
Accredited Number: 3023

Test Laboratory : DEKRA Testing and Certification Co., Ltd  
Address : No. 26, Huaya 1st Rd., Guishan Dist.,  
Taoyuan City 333411, Taiwan, R.O.C.  
Phone number : 886-3-275-7255  
Fax number : 866-3-327-5505  
Email address : [info.tw@dekra.com](mailto:info.tw@dekra.com)  
Website : <http://www.dekra.com.tw>

## 1.6. List of Test Equipment

### For Conduction measurements /SH1

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due. Date
X	EMI Test Receiver	R&S	ESR7	101601	2021.01.04	2022.01.03
X	Two-Line V-Network	R&S	ENV216	101306	2021.04.08	2022.04.07
X	Two-Line V-Network	R&S	ENV216	101307	2021.05.04	2022.05.03
X	Coaxial Cable	DEKRA	RG400_BNC	RF001	2021.05.24	2022.05.23

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “X” are used to measure the final test results.
3. Test Software version : DEKRA Testing System V2.0

### For Conducted measurements /SH2

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due. Date
X	Spectrum Analyzer	R&S	FSV30	103466	2020.12.28	2021.12.27
X	Peak Power Analyzer	Anritsu	ML2496A	1548002	2021.02.24	2022.02.23
X	Wideband Power Sensor	Anritsu	MA2411B	1531023	2021.02.24	2022.02.23
X	Wideband Power Sensor	Anritsu	MA2411B	1531022	2021.02.24	2022.02.23

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “X” are used to measure the final test results.
3. Test Software version : DEKRA Conduction Test System V9.0.5.

### For Radiated measurements /966-3

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due. Date
X	Loop Antenna	AMETEK	HLA6121	56736	2021.04.14	2022.04.13
X	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-678	2020.09.04	2021.09.03
X	Horn Antenna	ETS-Lindgren	3117	00203761	2020.11.23	2021.11.22
X	Horn Antenna	Com-Power	AH-840	101087	2021.06.16	2022.06.15
X	Pre-Amplifier	EMCI	EMC001330	980302	2021.07.26	2022.07.25
X	Pre-Amplifier	EMCI	EMC051835SE	980312	2021.02.24	2022.02.23
X	Pre-Amplifier	EMCI	EMC05820SE	980308	2020.09.18	2021.09.17
X	Pre-Amplifier	EMCI	EMC184045SE	980369	2021.04.27	2022.04.26
X	Filter	MICRO TRONICS	BRM50702	G251	2020.09.17	2021.09.16
	Filter	MICRO TRONICS	BRM50716	G188	2020.09.17	2021.09.16
X	EMI Test Receiver	R&S	ESR	102793	2020.12.17	2021.12.16
X	Spectrum Analyzer	R&S	FSV3044	101113	2021.02.03	2022.02.02
X	Coaxial Cable	SUHNER	SUCOFLEX 106	RF002	2021.03.03	2022.03.02
X	Mircoflex Cable	HUBER SUHNER	SUCOFLEX 102	MY3381/2	2021.06.25	2022.06.24

Note:

1. Loop Antenna is calibrated every two years, the other equipments are calibrated every one year.
2. The test instruments marked with “X” are used to measure the final test results.
3. Test Software version : DEKRA Testing System V2.0

## 1.7. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document, and is described in each test chapter of this report.


The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty	
Conducted Emission	±3.42 dB	
Peak Power Output	±0.91 dB	
Radiated Emission	Under 1GHz ±4.06 dB	Above 1GHz ±3.73 dB
RF Antenna Conducted Test	±2.53 dB	
Band Edge	Under 1GHz ±4.06 dB	Above 1GHz ±3.73 dB
Channel Number	N/A	
Channel Separation	±682.83 Hz	
Dwell Time	±2.31 ms	
Occupied Bandwidth	±682.83 Hz	
Duty Cycle	±2.31 ms	

## 2. Conducted Emission

### 2.1. Test Setup



### 2.2. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dB $\mu$ V) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

### 2.3. Test Procedure

The EUT and Peripherals are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs.)


Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

The EUT setup and the test procedure are according to ANSI C63.4, 2014 to comply with the requirements of FCC 47CFR Subpart C.

### 2.4. Test Result of Conducted Emission

Model No	IXWW22	Site	SH1
Test Voltage	AC 120V/60Hz	Test Date	2021/8/17
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Jason Tuan
Phase	L1	Temperature (°C)	27.8
Test Condition	BT 3Mbps,2.441G	Humidity (%RH)	55.2
Note	--		




No	Frequency (MHz)	Emission Level (dBuV)	Limit (dBuV)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	0.159	46.20	65.53	-19.33	36.54	9.66	QP
2	0.159	30.01	55.53	-25.52	20.35	9.66	AV
*3	0.192	47.05	63.95	-16.90	37.40	9.65	QP
4	0.192	34.32	53.95	-19.63	24.67	9.65	AV
5	0.206	45.12	63.37	-18.25	35.47	9.65	QP
6	0.206	30.04	53.37	-23.33	20.39	9.65	AV
7	0.206	45.81	63.35	-17.54	36.16	9.65	QP
8	0.206	30.18	53.35	-23.17	20.53	9.65	AV
9	0.214	44.97	63.06	-18.09	35.32	9.65	QP
10	0.214	30.31	53.06	-22.75	20.66	9.65	AV
11	0.237	38.10	62.21	-24.11	28.45	9.65	QP
12	0.237	28.76	52.21	-23.45	19.11	9.65	AV

Note:

1. “ \* “ means this data is the worst emission level.
2. Emission Level = Reading Level + Correct Factor.
3. Margin = Emission Level – Limit.
4. Correct Factor = LISN insertion loss + Cable loss.

Model No	IXWW22	Site	SH1
Test Voltage	AC 120V/60Hz	Test Date	2021/8/17
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Jason Tuan
Phase	N	Temperature (°C)	27.8
Test Condition	BT 3Mbps,2.441G	Humidity (%RH)	55.2
Note	--		




No	Frequency (MHz)	Emission Level (dBuV)	Limit (dBuV)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	0.163	45.01	65.32	-20.31	35.34	9.67	QP
2	0.163	30.14	55.32	-25.18	20.47	9.67	AV
3	0.172	46.96	64.85	-17.89	37.29	9.67	QP
4	0.172	31.89	54.85	-22.96	22.22	9.67	AV
*5	0.190	46.40	64.05	-17.65	36.73	9.67	QP
6	0.190	34.92	54.05	-19.13	25.25	9.67	AV
7	0.205	44.96	63.39	-18.43	35.29	9.67	QP
8	0.205	30.08	53.39	-23.31	20.41	9.67	AV
9	0.237	38.45	62.21	-23.76	28.78	9.67	QP
10	0.237	28.97	52.21	-23.24	19.30	9.67	AV
11	0.245	40.22	61.92	-21.70	30.55	9.67	QP
12	0.245	20.37	51.92	-31.55	10.70	9.67	AV

Note:

1. “ \* “ means this data is the worst emission level.
2. Emission Level = Reading Level + Correct Factor.
3. Margin = Emission Level – Limit.
4. Correct Factor = LISN insertion loss + Cable loss.

### 3. Peak Power Output

#### 3.1. Test Setup



#### 3.2. Limit

The maximum peak power shall be less 1Watt.

#### 3.3. Test Procedure

Tested according to FHSS test procedure of KDB 558074 section 9 (b for compliance to FCC 47CFR 15.247 requirements.



### 3.4. Test Result of Peak Power Output

Product : LinkCard  
Test Item : Peak Power Output  
Test Mode : Mode 1: Transmit - 1Mbps  
Test Date : 2021/07/06

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402	2.64	1 Watt= 30 dBm	Pass
Channel 39	2441	1.26	1 Watt= 30 dBm	Pass
Channel 78	2480	1.99	1 Watt= 30 dBm	Pass


Product : LinkCard  
Test Item : Peak Power Output  
Test Mode : Mode 2: Transmit - 3Mbps  
Test Date : 2021/07/06

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402	2.76	1 Watt= 30 dBm	Pass
Channel 39	2441	3.16	1 Watt= 30 dBm	Pass
Channel 78	2480	2.53	1 Watt= 30 dBm	Pass


## 4. Radiated Emission

### 4.1. Test Setup


Radiated Emission Under 30MHz



Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



## 4.2. Limits

### ➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

<b>FCC Part 15 Subpart C Paragraph 15.209 Limits</b>		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

- Remarks:
1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
  2. In the Above Table, the tighter limit applies at the band edges.
  3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

### 4.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.


The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The measurement frequency range from 9kHz - 10th Harmonic of fundamental was investigated.

#### 4.4. Test Result of Radiated Emission

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 1: Transmit - 1Mbps	Engineer	Nick Chen
Polarity	Horizontal	Temperature (°C)	22.5
Test Condition	BT 1Mbps,2.402G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4804.000	43.62	74.00	-30.38	47.09	-3.47	PK
2	7206.000	45.52	74.00	-28.48	44.92	0.60	PK
* 3	9608.000	46.09	74.00	-27.91	43.62	2.47	PK

Remark:

1. "\*" means this data is the worst emission level;  
"!" means this data is over limit.
2. Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
3. Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 1: Transmit - 1Mbps	Engineer	Nick Chen
Polarity	Vertical	Temperature (°C)	22.5
Test Condition	BT 1Mbps,2.402G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4804.000	43.20	74.00	-30.80	46.67	-3.47	PK
2	7206.000	45.84	74.00	-28.16	45.24	0.60	PK
* 3	9608.000	46.30	74.00	-27.70	43.83	2.47	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 1: Transmit - 1Mbps	Engineer	Nick Chen
Polarity	Horizontal	Temperature (°C)	22.5
Test Condition	BT 1Mbps,2.441G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4882.000	43.09	74.00	-30.91	46.47	-3.38	PK
2	7323.000	45.91	74.00	-28.09	45.26	0.65	PK
* 3	9764.000	46.25	74.00	-27.75	43.65	2.60	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.



Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 1: Transmit - 1Mbps	Engineer	Nick Chen
Polarity	Vertical	Temperature (°C)	22.5
Test Condition	BT 1Mbps,2.441G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4882.000	43.31	74.00	-30.69	46.69	-3.38	PK
2	7323.000	45.24	74.00	-28.76	44.59	0.65	PK
* 3	9764.000	46.08	74.00	-27.92	43.48	2.60	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 1: Transmit - 1Mbps	Engineer	Nick Chen
Polarity	Horizontal	Temperature (°C)	22.5
Test Condition	BT 1Mbps,2.48G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4960.000	43.56	74.00	-30.44	46.74	-3.18	PK
2	7440.000	44.45	74.00	-29.55	43.85	0.60	PK
* 3	9920.000	46.62	74.00	-27.38	43.78	2.84	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 1: Transmit - 1Mbps	Engineer	Nick Chen
Polarity	Vertical	Temperature (°C)	22.5
Test Condition	BT 1Mbps,2.48G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4960.000	44.42	74.00	-29.58	47.60	-3.18	PK
2	7440.000	44.48	74.00	-29.52	43.88	0.60	PK
* 3	9920.000	46.14	74.00	-27.86	43.30	2.84	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Nick Chen
Polarity	Horizontal	Temperature (°C)	22.5
Test Condition	BT 3Mbps,2.402G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4804.000	44.22	74.00	-29.78	47.69	-3.47	PK
* 2	7206.000	46.15	74.00	-27.85	45.55	0.60	PK
3	9608.000	45.88	74.00	-28.12	43.41	2.47	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Nick Chen
Polarity	Vertical	Temperature (°C)	22.5
Test Condition	BT 3Mbps,2.402G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4804.000	43.25	74.00	-30.75	46.72	-3.47	PK
* 2	7206.000	45.48	74.00	-28.52	44.88	0.60	PK
3	9608.000	45.33	74.00	-28.67	42.86	2.47	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Nick Chen
Polarity	Horizontal	Temperature (°C)	22.5
Test Condition	BT 3Mbps,2.441G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4882.000	43.27	74.00	-30.73	46.65	-3.38	PK
2	7323.000	45.85	74.00	-28.15	45.20	0.65	PK
* 3	9764.000	45.89	74.00	-28.11	43.29	2.60	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Nick Chen
Polarity	Vertical	Temperature (°C)	22.5
Test Condition	BT 3Mbps,2.441G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4882.000	43.22	74.00	-30.78	46.60	-3.38	PK
* 2	7323.000	45.65	74.00	-28.35	45.00	0.65	PK
3	9764.000	44.98	74.00	-29.02	42.38	2.60	PK

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Nick Chen
Polarity	Horizontal	Temperature (°C)	22.5
Test Condition	BT 3Mbps,2.48G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4960.000	44.28	74.00	-29.72	47.46	-3.18	PK
2	7440.000	46.28	74.00	-27.72	45.68	0.60	PK
* 3	9920.000	47.16	74.00	-26.84	44.32	2.84	PK

**Remark:**

1. "\*" means this data is the worst emission level;  
 "!" means this data is over limit.
2. Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
3. Margin= Emission Level- Limit.



Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Nick Chen
Polarity	Vertical	Temperature (°C)	22.5
Test Condition	BT 3Mbps,2.48G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4960.000	43.46	74.00	-30.54	46.64	-3.18	PK
2	7440.000	44.58	74.00	-29.42	43.98	0.60	PK
* 3	9920.000	47.06	74.00	-26.94	44.22	2.84	PK

**Remark:**

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Nick Chen
Polarity	Horizontal	Temperature (°C)	22.5
Test Condition	BT 3Mbps,2.441G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	95.960	37.79	43.50	-5.71	54.66	-16.87	QP
2	239.520	36.14	46.00	-9.86	47.97	-11.83	QP
3	395.690	33.05	46.00	-12.95	41.00	-7.95	QP
4	494.630	38.68	46.00	-7.32	44.66	-5.98	QP
* 5	594.540	40.67	46.00	-5.33	44.32	-3.65	QP
6	851.590	33.75	46.00	-12.25	34.15	-0.40	QP

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

Model No	IXWW22	Site	966-1
Test Voltage	AC 120 V / 60 Hz	Test Date	2021/8/13
Test Mode	Mode 2: Transmit - 3Mbps	Engineer	Nick Chen
Polarity	Vertical	Temperature (°C)	22.5
Test Condition	BT 3Mbps,2.441G,	Humidity (%RH)	62.5




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	95.960	33.89	43.50	-9.61	50.76	-16.87	QP
2	279.290	32.63	46.00	-13.37	43.38	-10.75	QP
3	395.690	29.69	46.00	-16.31	37.64	-7.95	QP
4	491.720	36.54	46.00	-9.46	42.59	-6.05	QP
* 5	594.540	39.96	46.00	-6.04	43.61	-3.65	QP
6	841.890	32.18	46.00	-13.82	32.73	-0.55	QP

Remark:

- "\*" means this data is the worst emission level;  
"!" means this data is over limit.
- Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+ Cable Loss- Pre Amp).
- Margin= Emission Level- Limit.

## 5. RF Antenna Conducted Test

### 5.1. Test Setup



### 5.2. Limits

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.


### 5.3. Test Procedure

Tested according to FHSS test procedure of KDB558074 section 9 b) for compliance to FCC 47CFR 15.247 requirements.


### 5.4. Test Result of RF Antenna Conducted Test

Product : LinkCard  
Test Item : RF Antenna Conducted Test  
Test Mode : Mode 1: Transmit - 1Mbps  
Test Date : 2021/07/06


**Figure Channel 00:**



**Figure Channel 39:**




**Figure Channel 78:**




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : LinkCard  
Test Item : RF Antenna Conducted Test  
Test Mode : Mode 2: Transmit - 3Mbps  
Test Date : 2021/07/06


**Figure Channel 00:**



**Figure Channel 39:**



**Figure Channel 78:**




Note: The above test pattern is synthesized by multiple of the frequency range.


## 6. Band Edge

### 6.1. Test Setup

#### RF Conducted Measurement



#### RF Radiated Measurement:



## 6.2. Limit

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

## 6.3. Test Procedure

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.


The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz, respectively.



### 6.4. Test Result of Band Edge

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 1: Transmit - 1Mbps (2402MHz)  
 Test Date : 2021/08/12

#### Horizontal



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2388.841	49.57	74.00	-24.43	39.22	10.35	PK
2	2390.000	47.65	74.00	-26.35	37.30	10.35	PK
3	2400.000	50.70	--	--	40.36	10.34	PK
4	2402.174	81.83	--	--	71.48	10.35	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection.


Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Average Measurement (dBm)	Margin (dB)	Average Limit (dBm)	Result
00 (Average)	2388.841	49.57	-24.731	24.839	-29.161	54.000	Pass
00 (Average)	2390	47.65	-24.731	22.919	-31.081	54.000	Pass
00 (Average)	2400	50.7	-24.731	25.969	--	--	Pass
00 (Average)	2402.174	81.83	-24.731	57.099	--	--	Pass

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor
2. The Duty Cycle is refer to section 15.

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 1: Transmit - 1Mbps (2402MHz)  
 Test Date : 2021/08/12

**Vertical**



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	46.72	74.00	-27.28	36.37	10.35	PK
2	2400.000	50.07	--	--	39.73	10.34	PK
3	2401.884	80.94	--	--	70.59	10.35	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection.


Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Average Measurement (dBm)	Margin (dB)	Average Limit (dBm)	Result
00 (Average)	2390	46.72	-24.731	21.989	-32.011	54.000	Pass
00 (Average)	2400	50.07	-24.731	25.339	--	--	Pass
00 (Average)	2401.884	80.94	-24.731	56.209	--	--	Pass

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor
2. The Duty Cycle is refer to section 15.

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 1: Transmit - 1Mbps (2480MHz)  
 Test Date : 2021/08/12

**Horizontal**



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2479.877	85.52	--	--	74.71	10.81	PK
2	2483.500	48.54	74.00	-25.46	37.70	10.84	PK
3	2490.746	49.47	74.00	-24.53	38.56	10.91	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection.


Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Average Measurement (dBm)	Margin (dB)	Average Limit (dBm)	Result
78 (Average)	2479.877	85.52	-24.731	60.789	--	--	Pass
78 (Average)	2483.5	48.54	-24.731	23.809	-30.191	54.000	Pass
78 (Average)	2490.746	49.47	-24.731	24.739	-29.261	54.000	Pass

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor
2. The Duty Cycle is refer to section 15.

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 1: Transmit - 1Mbps (2480MHz)  
 Test Date : 2021/08/12

**Vertical**



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2479.877	80.19	--	--	69.38	10.81	PK
2	2483.500	49.35	74.00	-24.65	38.51	10.84	PK
3	2489.152	50.40	74.00	-23.60	39.51	10.89	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection.


Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Average Measurement (dBm)	Margin (dB)	Average Limit (dBm)	Result
78 (Average)	2479.877	80.19	-24.731	55.459	--	--	Pass
78 (Average)	2483.5	49.35	-24.731	24.619	-29.381	54.000	Pass
78 (Average)	2489.152	50.4	-24.731	25.669	-28.331	54.000	Pass

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor
2. The Duty Cycle is refer to section 15.

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 2: Transmit - 3Mbps (2402MHz)  
 Test Date : 2021/08/12

**Horizontal**



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2383.043	48.56	74.00	-25.44	38.20	10.36	PK
2	2390.000	46.24	74.00	-27.76	35.89	10.35	PK
3	2400.000	60.67	--	--	50.33	10.34	PK
4	2402.029	85.87	--	--	75.52	10.35	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection.


Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Average Measurement (dBm)	Margin (dB)	Average Limit (dBm)	Result
00 (Average)	2383.043	48.56	-24.731	23.829	-30.171	54.000	Pass
00 (Average)	2390	46.24	-24.731	21.509	-32.491	54.000	Pass
00 (Average)	2400	60.67	-24.731	35.939	--	--	Pass
00 (Average)	2402.029	85.87	-24.731	61.139	--	--	Pass

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor
2. The Duty Cycle is refer to section 15.

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 2: Transmit - 3Mbps (2402MHz)  
 Test Date : 2021/08/12

**Vertical**



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	46.51	74.00	-27.49	36.16	10.35	PK
2	2400.000	56.23	--	--	45.89	10.34	PK
3	2402.029	79.63	--	--	69.28	10.35	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection.


Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Average Measurement (dBm)	Margin (dB)	Average Limit (dBm)	Result
00 (Average)	2390	46.51	-24.731	21.779	-32.221	54.000	Pass
00 (Average)	2400	56.23	-24.731	31.499	--	--	Pass
00 (Average)	2402.029	79.63	-24.731	54.899	--	--	Pass

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor
2. The Duty Cycle is refer to section 15.

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 2: Transmit - 3Mbps (2480MHz)  
 Test Date : 2021/08/12

**Horizontal**



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2480.022	99.80	--	--	88.99	10.81	PK
2	2483.500	61.73	74.00	-12.27	50.89	10.84	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection.


Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Average Measurement (dBm)	Margin (dB)	Average Limit (dBm)	Result
78 (Average)	2480.022	99.8	-24.731	75.069	--	--	Pass
78 (Average)	2483.5	61.73	-24.731	36.999	-17.001	54.000	Pass

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor
2. The Duty Cycle is refer to section 15.

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 2: Transmit - 3Mbps (2480MHz)  
 Test Date : 2021/08/12

**Vertical**



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2480.022	95.01	--	--	84.20	10.81	PK
2	2483.500	57.11	74.00	-16.89	46.27	10.84	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection.

Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Average Measurement (dBm)	Margin (dB)	Average Limit (dBm)	Result
78 (Average)	2480.022	95.01	-24.731	70.279	--	--	Pass
78 (Average)	2483.5	57.11	-24.731	32.379	-21.621	54.000	Pass

Note:


1. Average Measurement=Peak Measurement + Duty Cycle Factor
2. The Duty Cycle is refer to section 15.



Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 1: Transmit - 1Mbps(Hopping off)  
 Test Date : 2021/06/28


Measurement Level	Result
$\Delta$ (dB)	
> 20	PASS

Figure Channel 00:



Date: 28 JUN 2021 19:55:07

Figure Channel 78:




Date: 28 JUN 2021 20:11:33

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 2: Transmit - 3Mbps (Hopping off)  
 Test Date : 2021/08/05


Measurement Level	Result
$\Delta$ (dB)	
> 20	PASS

Figure Channel 00:



Date: 5.AUG.2021 13:45:08

Figure Channel 78:




Date: 5.AUG.2021 14:03:32

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 1: Transmit - 1Mbps(Hopping on)  
 Test Date : 2021/06/28


Measurement Level	Result
$\Delta$ (dB)	
> 20	PASS

Figure Channel Hopping:



Date: 28 JUN 2021 19:58:16

Figure Channel Hopping:




Date: 28 JUN 2021 20:16:19

Product : LinkCard  
 Test Item : Band Edge  
 Test Mode : Mode 2: Transmit - 3Mbps (Hopping on)  
 Test Date : 2021/08/08


Measurement Level	Result
$\Delta$ (dB)	
> 20	PASS

**Figure Channel Hopping:**



Date: 5 AUG 2021 13:49:41


**Figure Channel Hopping:**



Date: 5 AUG 2021 14:08:59

## 7. Channel Number

### 7.1. Test Setup



### 7.2. Limit

Frequency hopping systems operating in the 2400-2483.5 MHz bands shall use at least 75 hopping frequencies.

### 7.3. Test Procedure


Tested according to FHSS test procedure of KDB558074 section 9 (b for compliance to FCC 47CFR 15.247 requirements.

### 7.4. Test Result of Channel Number

Product : LinkCard  
 Test Item : Channel Number  
 Test Mode : Mode 1: Transmit - 1Mbps  
 Test Date : 2021/06/28


Frequency Range (MHz)	Measurement (Hopping Channel)	Required Limit (Hopping Channel)	Result
2402 ~ 2480	79	>75	Pass

2402-2421MHz




Date: 28 JUN 2021 20:18:31

2422-2441MHz




Date: 28 JUN 2021 20:19:28

2442-2461MHz



Date: 28 JUN 2021 20:20:30

2462-2480MHz




Date: 28 JUN 2021 20:21:56

Product : LinkCard  
 Test Item : Channel Number  
 Test Mode : Mode 2: Transmit - 3Mbps  
 Test Date : 2021/08/05


Frequency Range (MHz)	Measurement (Hopping Channel)	Required Limit (Hopping Channel)	Result
2402 ~ 2480	79	>75	Pass

2402-2421MHz




Date: 5.AUG.2021 14:11:55

2422-2441MHz




Date: 5.AUG.2021 14:16:03

2442-2461MHz



Date: 5.AUG.2021 14:20:25


2462-2480MHz



Date: 5.AUG.2021 14:25:21

## 8. Channel Separation

### 8.1. Test Setup



### 8.2. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### 8.3. Test Procedure

Tested according to FHSS test procedure of KDB558074 section 9 (b for compliance to FCC 47CFR 15.247 requirements).




### 8.4. Test Result of Channel Separation

Product : LinkCard  
 Test Item : Channel Separation  
 Test Mode : Mode 1: Transmit - 1Mbps  
 Test Date : 2021/06/28

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Limit (kHz)	Limit of (2/3)*20dB Bandwidth (kHz)	Result
00	2402	1000	>25 kHz	686.0	Pass
39	2441	1000	>25 kHz	680.0	Pass
78	2480	1000	>25 kHz	680.0	Pass


NOTE: The 20dB Bandwidth is refer to section 10.

Channel 00 (2402MHz)




Date: 28 JUN 2021 19:54:13

### Channel 39 (2441MHz)



Date: 28 JUN 2021 20:03:35

### Channel 78 (2480MHz)




Date: 28 JUN 2021 20:10:23

Product : LinkCard  
 Test Item : Channel Separation  
 Test Mode : Mode 2: Transmit - 3Mbps  
 Test Date : 2021/08/05

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Limit (kHz)	Limit of (2/3)*20dB Bandwidth (kHz)	Result
00	2402	1000	>25 kHz	874.0	Pass
39	2441	1000	>25 kHz	882.0	Pass
78	2480	1000	>25 kHz	876.0	Pass


NOTE: The 20dB Bandwidth is refer to section 10.

Channel 00 (2402MHz)




Date: 5.AUG.2021 13:44:16

### Channel 39 (2441MHz)



Date: 5.AUG.2021 13:55:00


### Channel 78 (2480MHz)



Date: 5.AUG.2021 14:02:25

## 9. Dwell Time

### 9.1. Test Setup



### 9.2. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 9.3. Test Procedure

Tested according to FHSS test procedure of KDB558074 section 9 (b for compliance to FCC 47CFR 15.247 requirements).


### 9.4. Test Result of Dwell Time

Product : LinkCard  
 Test Item : Dwell Time  
 Test Mode : Mode 1: Transmit - 1Mbps (Channel 00,39,78)  
 Test Date : 2021/06/29

Frequency (MHz)	Time slot length (ms)	Hopping of Number	Sweep time (ms)	Dwell Time (ms)	Limit (ms)	Result
2402	2.950	105	31600	309.750	400	Pass
2441	2.940	106	31600	311.640	400	Pass
2480	2.950	109	31600	321.550	400	Pass


Dwell time = Time slot length (ms)\*Hopping of Number

CH 00 Time slot length




Date: 29 JUN 2021 00:11:31

CH 00 Hopping of Number




Date: 29 JUN 2021 00:15:02

CH 39 Time slot length



Date: 29 JUN 2021 00:12:44


CH 39 Hopping of Number



Date: 29 JUN 2021 00:16:17

CH 78 Time slot length

CH 78 Hopping of Number



Note:


The dwell times of the packet type of DH1, DH3, and DH5 are tested. Only the worst case is shown on the report.

Product : LinkCard  
 Test Item : Dwell Time  
 Test Mode : Mode 2: Transmit - 3Mbps (Channel 00,39,78)  
 Test Date : 2021/06/29

Frequency (MHz)	Time slot length (ms)	Hopping of Number	Sweep time (ms)	Dwell Time (ms)	Limit (ms)	Result
2402	2.890	104	31600	300.560	400	Pass
2441	2.890	105	31600	303.450	400	Pass
2480	2.890	107	31600	309.230	400	Pass


Dwell time = Time slot length (ms)\*Hopping of Number

CH 00 Time slot length




Date: 29 JUN 2021 00:21:21

CH 00 Hopping of Number




Date: 29 JUN 2021 00:28:10

CH 39 Time slot length



Date: 29 JUN 2021 00:21:48


CH 39 Hopping of Number



Date: 29 JUN 2021 00:26:31




### CH 78 Time slot length



Date: 29 JUN 2021 00:22:19

### CH 78 Hopping of Number




Date: 29 JUN 2021 00:25:00

#### Note:

The dwell times of the packet type of DH1, DH3, and DH5 are tested. Only the worst case is shown on the report.

## 10. Occupied Bandwidth

### 10.1. Test Setup



### 10.2. Limits

N/A

### 10.3. Test Procedure


Tested according to FHSS test procedure of KDB558074 section 9 (b for compliance to FCC 47CFR 15.247 requirements.

### 10.4. Test Result of Occupied Bandwidth

Product : LinkCard  
 Test Item : Occupied Bandwidth Data  
 Test Mode : Mode 1: Transmit - 1Mbps  
 Test Date : 2021/06/28


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	1029	--	NA
39	2441	1020	--	NA
78	2480	1020	--	NA

Figure Channel 00:




Date: 28 JUN 2021 19:59:35

Figure Channel 39:



Date: 28 JUN 2021 20:06:40

Figure Channel 78:




Date: 28 JUN 2021 20:23:54

Product : LinkCard  
 Test Item : Occupied Bandwidth Data  
 Test Mode : Mode 2: Transmit - 3Mbps  
 Test Date : 2021/08/05


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	1311	--	NA
39	2441	1323	--	NA
78	2480	1314	--	NA

Figure Channel 00:




Date: 5.AUG.2021 13:50:55

Figure Channel 39:



Date: 5.AUG.2021 13:58:38


Figure Channel 78:



Date: 5.AUG.2021 14:27:01


**11. Duty Cycle**

**11.1. Test Setup**



### 11.2. Test Result of Duty Cycle

Product : LinkCard  
 Test Item : Duty Cycle Data  
 Test Mode : Mode 1: Transmit - 1Mbps



Date: 16.AUG.2021 16:50:39

Time on of 100ms= 2.9ms\*2= 5.8ms


Duty Cycle= 5.8ms / 100ms= 0.058

Duty Cycle correction factor= 20 LOG 0.058= -24.731 dB

<b>Duty Cycle correction factor</b>	<b>-24.731</b>	<b>dB</b>
-------------------------------------	----------------	-----------



Product : LinkCard  
 Test Item : Duty Cycle Data  
 Test Mode : Mode 2: Transmit - 3Mbps



Date: 16.AUG.2021 16:51:43

Time on of 100ms= 2.9ms\*2= 5.8ms

Duty Cycle= 5.8ms / 100ms= 0.058

Duty Cycle correction factor= 20 LOG 0.058= -24.731 dB

<b>Duty Cycle correction factor</b>	<b>-24.731</b>	<b>dB</b>
-------------------------------------	----------------	-----------

## **12. EMI Reduction Method During Compliance Testing**

No modification was made during testing.