

## FCC/ISED Test Report

**Prepared for:** Garmin International, Inc.

**Address:** 1200 E. 151<sup>st</sup> Street  
Olathe, Kansas, 66062, USA

**Product:** A04263

**Test Report No:** R20220817-20-E2

**Approved by:**



**Nic S. Johnson, NCE**

Technical Manager

iNARTE Certified EMC Engineer #EMC-003337-NE

**DATE:** September 2, 2022

**Total Pages:** 41

*The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.*



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

**REVISION PAGE**

Rev. No.	Date	Description
0	1 September 2022	Original – NJohnson Prepared by FLane, GLarsen



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

## CONTENTS

Revision Page ..... 2

**1.0 Summary of test results ..... 4**

**2.0 EUT Description ..... 5**

**2.1 Equipment under test ..... 5**

**2.2 Description of test modes ..... 5**

**2.3 Description of support units ..... 5**

**3.0 Laboratory and General Test Description ..... 6**

**3.1 Laboratory description ..... 6**

**3.2 Test personnel ..... 6**

**3.3 Test equipment ..... 7**

**3.4 General Test Procedure and Setup for Radio Measurements ..... 8**

**4.0 Results ..... 9**

**4.1 Output Power ..... 10**

**4.2 Bandwidth ..... 11**

**4.3 Duty Cycle ..... 12**

**4.4 Radiated emissions ..... 13**

**4.5 Conducted Spurious Emissions ..... 18**

**4.6 Band edges ..... 21**

**4.8 Conducted AC Mains Emissions ..... 23**

**4.6 Carrier Frequency Separation, Number of Hopping Channels, Time of occupancy ..... 26**

**Appendix A: Sample Calculation ..... 30**

**Appendix B – Measurement Uncertainty ..... 32**

**Appendix C – Graphs and Tables ..... 33**

**REPORT END ..... 41**



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

## 1.0 SUMMARY OF TEST RESULTS

The worst-case measurements were reported in this report. Summary of test results presented in this report correspond to the following section (Please see the checked box below for the rule part used):

### FCC Part 15.247

The EUT has been tested according to the following specifications:

- (1) US Code of Federal Regulations, Title 47, Part 15
- (2) ISED RSS-Gen, Issue 5
- (3) ISED RSS-247, Issue 2

APPLIED STANDARDS AND REGULATIONS		
Standard Section	Test Type	Result
FCC Part 15.35 RSS Gen, Issue 5, Section 6.10	Duty Cycle	Pass
FCC Part 15.247(a)(1) RSS-247 Issue 2 Section 5.2	Peak output power	Pass
FCC Part 15.247(a)(1) RSS-247 Issue 2 Section 5.2	Bandwidth	Pass
FCC Part 15.209 RSS-Gen Issue 4, Section 7.1	Receiver Radiated Emissions	Pass
FCC Part 15.209 (restricted bands), 15.247 (unrestricted) RSS-247 Issue 2 Section 5.5, RSS-Gen Issue 4, Section 8.9	Transmitter Radiated Emissions	Pass
FCC Part 15.209, 15.247(d) RSS-247 Issue 2 Section 11.13	Band Edge Measurement	Pass
FCC Part 15.207 RSS-Gen Issue 4, Section 7.1	Conducted Emissions	Pass



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

## 2.0 EUT DESCRIPTION

### 2.1 EQUIPMENT UNDER TEST

#### Summary and Operating Condition:

<b>EUT</b>	A04263
<b>IC</b>	17921A-04263
<b>FCC ID</b>	IPH-04263
<b>EUT Received</b>	19 August 2022
<b>EUT Tested</b>	19 August 2022- 30 August 2022
<b>Serial No.</b>	3422062008 (Radiated Measurements) 3422062025 (Conducted Measurements)
<b>Operating Band</b>	2400 – 2483.5 MHz
<b>Device Type</b>	<input type="checkbox"/> GMSK <input type="checkbox"/> GFSK <input checked="" type="checkbox"/> BT BR <input type="checkbox"/> BT EDR 2MB <input type="checkbox"/> BT EDR 3MB <input type="checkbox"/> 802.11x
<b>Power Supply / Voltage</b>	Internal Battery/ 5VDC Charger: Garmin (Phi Hong) MN: AQ27A-59CFA (Representative Power Supply)
<b>Antenna Type / Gain (dBi)</b>	Trace Antenna -6.95 dBi

NOTE: For more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 2.2 DESCRIPTION OF TEST MODES

The operating range of the EUT is dependent on the device type found in section 2.1:

For Bluetooth Transmissions:

Channel	Frequency
Low	2402 MHz
Mid	2440 MHz
High	2480 MHz

For 802.11x Transmissions:

Channel	Frequency
Low	2412 MHz
Mid	2437 MHz
High	2462 MHz

These are the only representative channels tested in the frequency range according to FCC Part 15.31 and RSS-Gen Table A1. See the operational description for a list of all channel frequency and designations.

### 2.3 DESCRIPTION OF SUPPORT UNITS

None

### 3.0 LABORATORY AND GENERAL TEST DESCRIPTION

#### 3.1 LABORATORY DESCRIPTION

All testing was performed at the following Facility:

The Nebraska Center for Excellence in Electronics (NCEE Labs)  
 4740 Discovery Drive  
 Lincoln, NE 68521

A2LA Certificate Number:	1953.01
FCC Accredited Test Site Designation No:	US1060
Industry Canada Test Site Registration No:	4294A-1
NCC CAB Identification No:	US0177

Environmental conditions varied slightly throughout the tests:

Relative humidity of  $35 \pm 4\%$   
 Temperature of  $22 \pm 3^\circ$  Celsius



#### 3.2 TEST PERSONNEL

No.	PERSONNEL	TITLE	ROLE
1	Nic Johnson	Technical Manager	Review/editing
2	Fox Lane	Test Engineer	Testing and report
3	Grace Larsen	Test Engineer	Testing and report
4	Ethan Schmidt	Test Technician	Testing

**Notes:**

All personnel are permanent staff members of NCEE Labs. No testing or review was sub-contracted or performed by sub-contracted personnel.



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

### 3.3 TEST EQUIPMENT

DESCRIPTION AND MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CALIBRATION DATE	CALIBRATION DUE DATE
Keysight MXE Signal Analyzer (44GHz)**	N9038A	MY59050109	July 19, 2022	July 19, 2024
Keysight MXE Signal Analyzer (26.5GHz)**	N9038A	MY56400083	July 19, 2022	July 19, 2024
Keysight EXA Signal Analyzer**	N9010A	MY56070862	July 20, 2021	July 20, 2023
SunAR RF Motion	JB1	A082918-1	July 26, 2022	July 26, 2023
EMCO Horn Antenna	3115	6416	July 28, 2021	July 28, 2022
EMCO Horn Antenna***	3116	2576	March 9, 2020	March 9, 2023
Com-Power LISN, Single Phase**	LI-220C	20070017	July 18, 2022	July 18, 2024
8447F POT H64 Preamplifier*	8447F POT H64	3113AD4667	March 21, 2022	March 21, 2024
Rohde & Schwarz Preamplifier**	TS-PR18	3545700803	August 22, 2022	August 22, 2024
Trilithic High Pass Filter*	6HC330	23042	March 21, 2022	March 21, 2024
ETS – Lindgren- VSWR on 10m Chamber***	10m Semi-anechoic chamber-VSWR	4740 Discovery Drive	July 30, 2020	July 30, 2023
NCEE Labs-NSA on 10m Chamber*	10m Semi-anechoic chamber-NSA	NCEE-001	May 25, 2022	May 25, 2024
TDK Emissions Lab Software	V11.25	700307	NA	NA
RF Cable (preamplifier to antenna)*	MFR-57500	90-195-040	August 22, 2022	August 22, 2024
RF Cable (antenna to 10m chamber bulkhead)*	FSCM 64639	01E3872	September 24, 2021	September 24, 2023
RF Cable (10m chamber bulkhead to control room bulkhead)*	FSCM 64639	01E3864	September 24, 2021	September 24, 2023
RF Cable (control room bulkhead to test receiver)*	FSCM 64639	01F1206	September 24, 2021	September 24, 2023
N connector bulkhead (10m chamber)*	PE9128	NCEEBH1	September 24, 2021	September 24, 2023
N connector bulkhead (control room)*	PE9128	NCEEBH2	September 24, 2021	September 24, 2023


\*Internal Characterization

\*\*2 Year Cal Cycle

\*\*\*3 Year Cal Cycle

**Notes:**

All equipment is owned by NCEE Labs and stored permanently at NCEE Labs facilities.

	Report Number:	R20220817-20-E2	Rev	0
	Prepared for:	Garmin International, Inc.		

### 3.4 GENERAL TEST PROCEDURE AND SETUP FOR RADIO MEASUREMENTS

Measurement type presented in this report (Please see the checked box below):

#### Conducted

The conducted measurements were performed by connecting the output of the transmitter directly into a spectrum analyzer using an impedance matched cable and connector soldered to the EUT in place of the antenna. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.



Figure 1 - Bandwidth Measurements Test Setup

#### Radiated

All the radiated measurements were taken at a distance of 3m from the EUT. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.




Figure 2 - Radiated Emissions Test Setup





Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

#### 4.0 RESULTS

DTS Radio Measurements								
CHANNEL	Transmitter	Occupied Bandwidth (kHz)	20 dB Bandwidth (kHz)	AVERAGE OUTPUT POWER (dBm)	AVERAGE OUTPUT POWER (mW)	RESULT	No. of Hopping Channels	ON Time (µs)
							79	377.0
Low	Continuous	890.12	946.70	6.95	4.95	PASS	Channel Separation	Time of Occupancy
Mid	Continuous	889.45	948.90	6.90	4.89	PASS		
High	Continuous	887.20	933.30	6.97	4.97	PASS		
Occupied Bandwidth = N/A; Frequency Separation Limit > 2/3 * 20dB Bandwidth.			Peak Output Power Limit = 125mW; Time of Occupancy Limit < 0.4s; Time of Occupancy = ON Time * # of transmissions over 3.16s * 10 Period of Time of Occupancy = 0.4 * # of Channels = 0.4 * 79 = 31.6s Average Output Power = (Average Output Power on Analyzer) + (DCCF For Power) See Sec 4.3 for further information on DCCF					
Unrestricted Band-Edge								
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Relative Highest out of band level (dBuV)	Relative Fundamental (dBuV)	Delta (dB)	Min Delta (dB)	Result	
Low	Continuous	2390.00	67.537	114.717	47.180	30.00	PASS	
Low	Hopping	2390.00	65.119	114.484	49.365	30.00	PASS	
High	Continuous	2483.50	52.221	114.220	61.999	30.00	PASS	
High	Hopping	2483.50	52.096	114.528	62.432	30.00	PASS	
Peak Restricted Band-Edge								
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)	Measurement Type	Limit (dBuV/m @ 3m)	Margin	Result	
Low	Continuous	2390.00	53.792	Peak	73.98	20.188	PASS	
High	Continuous	2483.50	54.590	Peak	73.98	19.39	PASS	
*Limit shown is the peak limit taken from FCC Part 15.209								
Average Restricted Band-Edge								
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)**	Measurement Type	Limit (dBuV/m @ 3m)*	Margin	Result	
Low	Continuous	2390.00	44.422	Average	53.98	9.558	PASS	
High	Continuous	2483.50	45.889	Average	53.98	8.091	PASS	
*Limit shown is the average limit taken from FCC Part 15.209								
**Average Highest out of band level = SA Average Level – DCCF for emissions. C63.10 Sec. 11.12.2.5.2								
See Sec 4.3 for more information on DCCF								



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

#### 4.1 OUTPUT POWER

**Test Method:** All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

**Limits of power measurements:**

**For FCC Part 15.249 Device:**

For Informational Purposes only

**For FCC Part 15.247 Device:**

The maximum allowed peak output power is 125mW.

**Test procedures:**

Details can be found in section 3.4 of this report.

**Deviations from test standard:**

No deviation.

**Test setup:**

Details can be found in section 3.4 of this report.

**EUT operating conditions:**

Details can be found in section 2.1 of this report.

**Test results:**

**Pass**

Comments:

1. All the output power plots can be found in the Appendix C.
2. All the measurements were found to be compliant.
3. The measurements are listed in the tables below.
4. Compiled values can be found in the Results section, 4.0.



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

## 4.2 BANDWIDTH

**Test Method:** All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

### Limits of bandwidth measurements:

#### For FCC Part 15.249 Device:

For Informational Purposes only

#### For FCC Part 15.247 Device:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### Test procedures:

Details can be found in section 3.4 of this report.

### Deviations from test standard:

No deviation.

### Test setup:

Test setup details can be found in section 3.4 of this report.

### EUT operating conditions:

Details can be found in section 2.1 of this report.

### Test results:

## Pass

Comments:

1. All the bandwidth plots can be found in the Appendix C.
2. All the measurements were found to be compliant.

### 4.3 DUTY CYCLE

#### Test Method:




Figure 3 - Radiated Emissions Plot, BTBR, Duty Cycle

$$\begin{aligned} \text{DCCF for Emissions (Duty Cycle Correction Factor)} &= 20 * \text{Log}(\text{Duty Cycle} / 100) \\ -2.30 &= 20 * \text{Log}(76.7 / 100) \end{aligned}$$

$$\begin{aligned} \text{DCCF for Power (Duty Cycle Correction Factor)} &= 20 * \text{Log}(\text{Duty Cycle} / 100) \\ -1.15 &= 10 * \text{Log}(76.7 / 100) \end{aligned}$$

#### 4.4 RADIATED EMISSIONS

**Test Method:** ANSI C63.10-2013, Section 6.5, 6.6

**Limits for radiated emissions measurements:**

Emissions radiated outside of the specified bands shall be applied to the limits in 15.209 as followed:

FREQUENCIES (MHz)	FIELD STRENGTH (μV/m)	MEASUREMENT DISTANCE (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	3
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 \* log \* Emission level (μV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20dB under any condition of modulation.
4. The EUT was tested for spurious emissions while running off of battery power and external USB power. The worse-case emissions were produced while running off of USB power, so results from this mode are presented.




Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

**Test procedures:**

- a. The EUT was placed on the top of a rotating table above the ground plane in a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The table was 0.8m high for measurements from 30MHz-1Ghz and 1.5m for measurements from 1GHz and higher.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna was a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are used to make the measurement.
- d. For each suspected emission, the EUT was arranged to maximize its emissions and then the antenna height was varied from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum emission reading.
- e. The test-receiver system was set to use a peak detector with a specified resolution bandwidth. For spectrum analyzer measurements, the composite maximum of several analyzer sweeps was used for final measurements.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The EUT was maximized in all 3 orthogonal positions. The results are presented for the axis that had the highest emissions.

### Test setup:



**Figure 4 - Radiated Emissions Test Setup**

### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequencies below 1GHz.
2. The resolution bandwidth 1 MHz for all measurements and at frequencies above 1GHz, A peak detector was used for all measurements above 1GHz. Measurements were made with an EMI Receiver.


### Deviations from test standard:

No deviation.


### EUT operating conditions

Details can be found in section 2.1 of this report.

**Test results:**



**Figure 5 - Radiated Emissions Plot, Receive**



**Figure 6 - Radiated Emissions Plot, BTBR**

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value





Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

Quasi-Peak Measurements, BTBR								
Frequency	Level	Limit	Margin	Height	Angle	PoI	Channel	Modulation
MHz	dB $\mu$ V/m	dB $\mu$ V/m	dB	cm.	deg.			
49.189680	29.36	40.00	10.64	104.00	69.00	V	Low	BTBR
44.099280	28.97	40.00	11.03	107.00	249.00	V		Rx
173.046480	25.76	43.52	17.76	118.00	100.00	V		Rx

EUT was measured in 3 orthogonal angles, worst case was reported, all other emissions found to be at least 6dB below limit line

Peak Measurements, BTBR								
Frequency	Level	Limit	Margin	Height	Angle	PoI	Channel	Modulation
MHz	dB $\mu$ V/m	dB $\mu$ V/m	dB	cm.	deg.			
2401.400000	94.76	NA	NA	207	25	V	Low	BT BR
2440.146000	100.48	NA	NA	197	28	V	Mid	BT BR
2480.150000	101.09	NA	NA	178	32	V	High	BT BR

All other emissions found to be at least 6dB below limit line

Average Measurements, BTBR								
Frequency	Level	Limit	Margin	Height	Angle	PoI	Channel	Modulation
MHz	dB $\mu$ V/m	dB $\mu$ V/m	dB	cm.	deg.			
2401.400000	92.46	NA	NA	207	25	V	Low	BT BR
2440.146000	98.18	NA	NA	197	28	V	Mid	BT BR
2480.150000	98.79	NA	NA	178	32	V	High	BT BR

\*Average Levels Obtained from; Average Level = Peak Level + DCCF for emissions, for more information on DCCF see Sec 4.3

All other emissions found to be at least 6dB below limit line



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

#### 4.5 CONDUCTED SPURIOUS EMISSIONS

**Test Method:** ANSI C63.10-2013, Section 7.8.8

**Limits of spurious emissions:**

From FCC Part 15.247:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Test procedures:**

The highest emissions level was measured and recorded. All spurious measurements were evaluated to 20dB below the fundamental. More details can be found in section 3.4 of this report.

**Deviations from test standard:**

No deviation.

**Test setup:**

Test setup details can be found in section 3.4 of this report.

**EUT operating conditions:**

Details can be found in section 2.1 of this report.

**Test results:**

The highest value measured was 11.130 dBm at the fundamental emissions. All other values were at least 20 dB lower.




Figure 7 - Radiated Emissions Plot, BTBR, 30M – 1G




Figure 8 - Radiated Emissions Plot, BTBR, 1G – 3.6G




Figure 9 - Radiated Emissions Plot, BTBR, 3.6G – 25G



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

#### 4.6 BAND EDGES

**Test Method:** All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

**Limits of band-edge measurements:**

**For FCC Part 15.249 Device:**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

**For FCC Part 15.247 Device:**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

**Test procedures:**

The highest emissions level beyond the band-edge was measured and recorded. All band edge measurements were evaluated to the general limits in Part 15.209. More details can be found in section 3.4 of this report.

**Deviations from test standard:**

No deviation.

**Test setup:**

Test setup details can be found in section 3.4 of this report.

**EUT operating conditions:**

Details can be found in section 2.1 of this report.



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

**Test results:**

**Pass**

Comments:

1. All the band edge plots can be found in the Appendix C.
2. If the device falls under FCC Part 15.247 (Details can be found in summary of test results), compliance is shown in the unrestricted band edges by showing minimum delta of 20 dB between peak and the band edge.
3. The restricted band edge compliance is shown by comparing to the general limit defined in Part 15.209. The limit shown in the graph accounts for the antenna gain of the device.

## 4.7 CONDUCTED AC MAINS EMISSIONS

**Test Method:** ANSI C63.10-2013, Section(s) 6.2

**Limits for conducted emissions measurements:**

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

**Notes:**

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

**Test Procedures:**

- a. The EUT was placed 0.8m above a ground reference plane and 0.4 meters from the conducting wall of a shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). The LISN provides 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference as well as the ground.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits are not reported.
- d. Results were compared to the 15.207 limits.

**Deviation from the test standard:**

No deviation

**EUT operating conditions:**

Details can be found in section 2.1 of this report.

Test Results:




Figure 10 - Conducted Emissions Plot, Line, TX




Figure 11 - Conducted Emissions Plot, Neutral, TX






Figure 12 - Conducted Emissions Plot, Line, IDLE




Figure 13 - Conducted Emissions Plot, Neutral, IDLE



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

#### 4.8 CARRIER FREQUENCY SEPERATION, NUMBER OF HOPPING CHANNELS, TIME OF OCCUPANCY

**Test Method:** ANSI C63.10, Section 7.8.2, 7.8.3, 7.8.4, FCC DA 00-705

##### **Limits for Time of Occupancy**

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Dwell time =  $79 * 0.4 = 31.6$  seconds

##### **Test procedures:**

The method from FCC DA 00-705

Measurements were performed conducted

##### **Test setup:**

Measurements were performed Conducted, see section 3.4 for more details

##### **EUT operating conditions:**

EUT was charging while testing was performed

##### **Test results:**

**ON Time = 377us**

**Time of Occupancy/31.6s = On time \* number of transmissions over 3.16 seconds \* 10**

**$377us * 31 * 10 = 116.9ms < 400ms$  (FCC 15.247 Limit)**

**Total Hop Count = 79**

**Minimum Frequency Separation = 1MHz**

**Limit =  $2/3 * 20dB$  Bandwidth or 25kHz whichever is greater =  $890.12kHz * 2/3 = 593.41kHz$**




Figure 14 – On time, STD




Figure 15 – Dwell Time, 3.16s




Figure 16 – Dwell Time, 31.6s




Figure 17 – Minimum Frequency Separation, 1MHz




Figure 18 – Hop Count, 2400-2441.5MHz




Figure 19 – Hop Count, 2441.5-2482MHz



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

**APPENDIX A: SAMPLE CALCULATION**

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF - (-CF + AG) + AV$$

where FS = Field Strength

- RA = Receiver Amplitude
- AF = Antenna Factor
- CF = Cable Attenuation Factor
- AG = Amplifier Gain
- AV = Averaging Factor (if applicable)


Assume a receiver reading of 55 dB $\mu$ V is obtained. The Antenna Factor of 12 and a Cable Factor of 1.1 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.1 dB $\mu$ V/m.

$$FS = 55 + 12 - (-1.1 + 20) + 0 = 48.1 \text{ dB}\mu\text{V/m}$$

The 48.1 dB $\mu$ V/m value can be mathematically converted to its corresponding level in  $\mu$ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(48.1 \text{ dB}\mu\text{V/m})/20] = 254.1 \mu\text{V/m}$$

AV is calculated by the taking the  $20 \cdot \log(T_{on}/100)$  where  $T_{on}$  is the maximum transmission time in any 100ms window.

	Report Number:	R20220817-20-E2	Rev	0
	Prepared for:	Garmin International, Inc.		

### EIRP Calculations

In cases where direct antenna port measurement is not possible or would be inaccurate, output power is measured in EIRP. The maximum field strength is measured at a specified distance and the EIRP is calculated using the following equation;

$$EIRP \text{ (Watts)} = [\text{Field Strength (V/m)} \times \text{antenna distance (m)}]^2 / 30$$

$$\text{Power (watts)} = 10^{[\text{Power (dBm)}/10]} / 1000$$

$$\text{Voltage (dB}\mu\text{V)} = \text{Power (dBm)} + 107 \text{ (for } 50\Omega \text{ measurement systems)}$$

$$\text{Field Strength (V/m)} = 10^{[\text{Field Strength (dB}\mu\text{V/m)} / 20]} / 10^6$$

$$\text{Gain} = 1 \text{ (numeric gain for isotropic radiator)}$$

Conversion from 3m field strength to EIRP (d=3):

$$EIRP = [\text{FS(V/m)} \times d^2]/30 = \text{FS [0.3]} \quad \text{for } d = 3$$

$$EIRP(\text{dBm}) = \text{FS}(\text{dB}\mu\text{V/m}) - 10(\log 10^9) + 10\log[0.3] = \text{FS}(\text{dB}\mu\text{V/m}) - 95.23$$

*10log( 10^9) is the conversion from micro to milli*



Report Number:	R20220817-20-E2	Rev	0
Prepared for:	Garmin International, Inc.		

**APPENDIX B – MEASUREMENT UNCERTAINTY**


Where relevant, the following measurement uncertainty levels have been for tests performed in this test report:

<b>Test</b>	<b>Frequency Range</b>	<b>Uncertainty Value (dB)</b>
Radiated Emissions, 3m	30MHz - 1GHz	±4.31
Radiated Emissions, 3m	1GHz - 18GHz	±5.08
Emissions limits, conducted	30MHz – 18GHz	±3.03


Expanded uncertainty values are calculated to a confidence level of 95%.




APPENDIX C – GRAPHS AND TABLES




01 Average Output Power, Low Channel, BTBR




02 Average Output Power, Mid Channel, BTBR




03 Average Output Power, High Channel, BTBR




04 OBW, Low, BTBR




05 OBW, Mid, BTBR




06 OBW, High, BTBR




07 20dB BW, Low, BTBR




08 20dB BW, Mid, BTBR




09 20dB BW, High, BTBR




10 Lower Bandedge Restricted, BTBR




11 Higher Bandedge Restricted, BTBR




12 Lower Bandedge Unrestricted, BTBR



13 Higher Bandedge Unrestricted, BTBR



14 Lower Bandedge Unrestricted, BTBR, Hopping



15 Higher Bandedge Unrestricted, BTBR, Hopping





Report Number:

R20220817-20-E2

Rev

0

Prepared for:

Garmin International, Inc.

REPORT END