





FCC Test Report

FCC ID : IPH-04390

Equipment : Smart Watch

Model No. : A04390
Brand Name : GARMIN

Applicant : Garmin International, Inc.

Address : 1200 E. 151st Street Olathe, KS 66062 United

States

Standard : 47 CFR FCC Part 15.247

Received Date : Apr. 07, 2022

Tested Date : Apr. 18 ~ May 09, 2022

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chely/ Assistant Manager

Gary Chand / Manages

Report No.: FR240702AC Page : 1 of 18
Report Version: Rev. 01



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Reference Guidance	9
1.7	Deviation from Test Standard and Measurement Procedure	9
1.8	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Facility	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	6dB and Occupied Bandwidth	11
3.2	Conducted Output Power	12
3.3	Power Spectral Density	13
3.4	Unwanted Emissions into Restricted Frequency Bands	14
3.5	Emissions in Non-Restricted Frequency Bands	16
3.6	AC Power Line Conducted Emissions	17
4	TEST LABORATORY INFORMATION	18

- Appendix A. 6dB and Occupied Bandwidth
- **Appendix B. Conducted Output Power**
- **Appendix C. Power Spectral Density**
- Appendix D. Unwanted Emissions into Restricted Frequency Bands
- **Appendix E. Emissions in Non-Restricted Frequency Bands**
- **Appendix F. AC Power Line Conducted Emissions**



Release Record

Report No.	Version	Description	Issued Date
FR240702AC	Rev. 01	Initial issue	Jun. 01, 2022

Report No.: FR240702AC Page: 3 of 18



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emission	[dBuV]: 0.788MHz 25.45 (Margin -20.55dB) - AV	Pass
15.247(d)	Unwanted Emissions	[dBuV/m at 3m]: 2390.00MHz	Pass
15.209	Onwanted Emissions	69.80 (Margin -4.20dB) - PK	F a 5 5
15.247(b)(3) Conducted Output Power		Max Power [dBm]: 20.86	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e) Power Spectral Density		Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FR240702AC Page: 4 of 18



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information						
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS	
2400-2483.5	b	2412-2462	1-11 [11]	1	1-11 Mbps	
2400-2483.5	g	2412-2462	1-11 [11]	1	6-54 Mbps	
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	1	MCS 0-7	

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Note 2: DSSS-DBPSK, DQPSK, CCK modulation

OFDM - BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Details

Ant. No.	Brand	Model	Туре	Connector	Gain (dBi)
1	Garmin	117-01806-0X	PIFA	N/A	-2.08

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Type	5Vdc from adapter
rower type	3.87Vdc from battery

1.1.4 Accessories

	Accessories				
No.	Equipment	Description			
1	Battery	Brand: Garmin Model: 361-00136-20 Power Rating: 3.87V, 205mAh			
2	USB cable	Brand: GARMIN Model: 320-01069-10 Line: 0.52m shielded without core			

Report No.: FR240702AC Page: 5 of 18



1.1.5 Channel List

Frequency band (MHz)	2400~2483.5				
802.11 b / g / n HT20					
Channel	Frequency(MHz)				
1	2412				
2	2417				
3	2422				
4	2427				
5	2432				
6	2437				
7	2442				
8	2447				
9	2452				
10	2457				
11	2462				

1.1.6 Test Tool and Duty Cycle

Test Tool	WiFi Test, Version:4.01					
	Mode	Duty Cycle (%)	Duty Factor (dB)			
Duty Cycle and Duty	11b	100.00%	0.00			
Factor	11g	100.00%	0.00			
	HT20	100.00%	0.00			

1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)	Power Index
11b	2412	default
11b	2437	default
11b	2462	default
11g	2412	default
11g	2437	default
11g	2462	default
HT20	2412	default
HT20	2437	default
HT20	2462	default


Report No.: FR240702AC Page: 6 of 18




1.2 Local Support Equipment List

	Support Equipment List						
No.	Equipment	Brand	Model	FCC ID	Remarks		
1	Adapter	samsung	ETA-U90JWS				

1.3 Test Setup Chart





Report No.: FR240702AC Page: 7 of 18



1.4 The Equipment List

Test Item	Conducted Emission					
Test Site	Conduction room 1 / (CO01-WS)					
Tested Date	May 09, 2022					
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until	
Receiver	R&S	ESR3	101658	Feb. 16, 2022	Feb. 15, 2023	
LISN	R&S	ENV216	101579	Apr. 21, 2022	Apr. 20, 2023	
LISN (Support Unit)	SCHWARZBECK	NSLK 8127	8127667	Jan .07, 2022	Jan .06, 2023	
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 19, 2021	Oct. 18, 2022	
50 ohm terminal (Support Unit)	NA	50	04	May 25, 2021	May 24, 2022	
Measurement Software AUDIX e3 6.120210k NA NA						
Note: Calibration Interval of instruments listed above is one year.						

Test Item	Radiated Emission					
Test Site	966 chamber1 / (03CH01-WS)					
Tested Date	Apr. 18 ~ Apr. 23, 2022					
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until	
Receiver	R&S	ESR3	101657	Mar. 15, 2022	Mar. 14, 2023	
Spectrum Analyzer	R&S	FSV40	101498	Nov. 29, 2021	Nov. 28, 2022	
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 08, 2021	Nov. 07, 2022	
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jun. 30, 2021	Jun. 29, 2022	
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 03, 2021	Dec. 02, 2022	
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170508	Jan. 11, 2022	Jan. 10, 2023	
Preamplifier	EMC	EMC02325	980225	Jun. 29, 2021	Jun. 28, 2022	
Preamplifier	Agilent	83017A	MY39501308	Sep. 28, 2021	Sep. 27, 2022	
Preamplifier	EMC	EMC184045B	980192	Jul. 14, 2021	Jul. 13, 2022	
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 05, 2021	Oct. 04, 2022	
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 05, 2021	Oct. 04, 2022	
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 05, 2021	Oct. 04, 2022	
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 05, 2021	Oct. 04, 2022	
RF Cable	EMC	EMC104-35M-35M- 8000	210920	Oct. 05, 2021	Oct. 04, 2022	
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 05, 2021	Oct. 04, 2022	
Measurement Software	AUDIX	e3	6.120210g	NA	NA	
Note: Calibration Interval of instruments listed above is one year.						

Report No.: FR240702AC Page: 8 of 18



Test Item	RF Conducted							
Test Site	(TH01-WS)	(TH01-WS)						
Tested Date	Apr. 29, 2022							
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV40	101910	Apr. 18, 2022	Apr. 17, 2023			
Power Meter	Anritsu	ML2495A	1241002	Nov. 07, 2021	Nov. 06, 2022			
Power Sensor	Anritsu	MA2411B	1207366	Nov. 07, 2021	Nov. 06, 2022			
Measurement Software	Sporton	SENSE-15247_DTS	V5.10.7.18	NA	NA			
Note: Calibration Interval of instruments listed above is one year.								

1.5 Test Standards

47 CFR FCC Part 15.247 ANSI C63.10-2013

1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.7 Deviation from Test Standard and Measurement Procedure

None

1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Uncertainty				
Parameters	Uncertainty			
Bandwidth	±34.130 Hz			
Conducted power	±0.808 dB			
Power density	±0.583 dB			
Conducted emission	±2.715 dB			
AC conducted emission	±2.92 dB			
Unwanted Emission ≤ 1GHz	±3.41 dB			
Unwanted Emission > 1GHz	±4.59 dB			

Report No.: FR240702AC Page: 9 of 18



2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	CO01-WS, 03CH01-WS, TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

FCC Designation No.: TW2732FCC site registration No.: 181692

➤ ISED#: 10807A

➤ CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emission	Charging			1
Unwanted Emissions ≤ 1GHz	11g	2437	6 Mbps	2
Unwanted Emissions ≤ 1GHz	Charging			1
Unwanted Emissions >1GHz	11b 11g HT20	2412 / 2437 / 2462 2412 / 2437 / 2462 2412 / 2437 / 2462	1 Mbps 6 Mbps MCS 0	2
Conducted Output Power 6dB bandwidth Power spectral density	11b 11g HT20	2412 / 2437 / 2462 2412 / 2437 / 2462 2412 / 2437 / 2462	1 Mbps 6 Mbps MCS 0	2

NOTE:

- 1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.
- 2. The EUT had been tested by following test configurations.

1) Configuration 1: Charging mode

2) Configuration 2: Battery mode

Report No.: FR240702AC Page: 10 of 18



3 Transmitter Test Results

3.1 6dB and Occupied Bandwidth

3.1.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.1.2 Test Procedures

6dB Bandwidth

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

- 1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
- 2. Detector = Sample, Trace mode = max hold.
- 3 Sweep = auto couple, Allow the trace to stabilize.
- 4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.1.3 Test Setup



3.1.4 Test Results

Ambient Condition	23°C / 64%	Tested By	Brad Wu

Refer to Appendix A.

Report No.: FR240702AC Page: 11 of 18



3.2 Conducted Output Power

3.2.1 Limit of Conducted Output Power

Conducted power shall not exceed 1Watt.

Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.

Antenna gain > 6dBi

Non Fixed, point to point operations.

The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB


Fixed, point to point operations

Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.2.3 Test Setup



3.2.4 Test Results

Ambient Condition	23°C / 64%	Tested By	Brad Wu

Refer to Appendix B.

Report No.: FR240702AC Page: 12 of 18



3.3 Power Spectral Density

3.3.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.3.2 Test Procedures

Peak PSD

- 1. Set the RBW = 3 kHz, VBW = 10 kHz.
- Detector = Peak, Sweep time = auto couple.
- 3. Trace mode = max hold, allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.


Average PSD, duty cycle ≥ 98%

- Set the RBW = 30 kHz, VBW = 100 kHz.
- 2. Detector = RMS, Sweep time = auto couple.
- 3. Sweep time = auto couple.
- 4. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- 5. Use the peak marker function to determine the maximum amplitude level.

Average PSD, duty cycle < 98%

- 1 Set the RBW = 30 kHz, VBW = 100 kHz. Detector = RMS.
- Set the sweep time to: \geq 10 (number of measurement points in sweep) x (total on/off period of the transmitted signal).
- 3 Perform the measurement over a single sweep.
- 4 Use the peak marker function to determine the maximum amplitude level.
- 5 Add 10 log (1/x), where x is the duty cycle.

3.3.3 Test Setup



3.3.4 Test Results

Refer to Appendix C.

Report No.: FR240702AC Page: 13 of 18



3.4 Unwanted Emissions into Restricted Frequency Bands

3.4.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit					
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)		
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300		
0.490~1.705	24000/F(kHz)	33.8 - 23	30		
1.705~30.0	30	29	30		
30~88	100	40	3		
88~216	150	43.5	3		
216~960	200	46	3		
Above 960	500	54	3		

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:**

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.4.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR240702AC Page: 14 of 18



3.4.3 Test Setup



3.4.4 Test Results

Refer to Appendix D.

Report No.: FR240702AC Page: 15 of 18



3.5 Emissions in Non-Restricted Frequency Bands

3.5.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.5.2 Test Procedures


Reference level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Scan Frequency range is up to 25GHz
- 4. Use the peak marker function to determine the maximum amplitude level

3.5.3 Test Setup



3.5.4 Test Results

Ambient Condition	23°C / 64%	Tested By	Brad Wu
-------------------	------------	-----------	---------

Refer to Appendix E.

Report No.: FR240702AC Page: 16 of 18



3.6 AC Power Line Conducted Emissions


3.6.1 Limit of AC Power Line Conducted Emissions

Conducted Emissions Limit					
Frequency Emission (MHz) Quasi-Peak Average					
0.15-0.5	66 - 56 *	56 - 46 *			
0.5-5	56	46			
5-30	60	50			
Note 1: * Decreases with the logarithm of the frequency.					

3.6.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

3.6.3 Test Setup



Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.6.4 Test Results

Refer to Appendix F.

Report No.: FR240702AC Page: 17 of 18



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No.30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan (R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

--END---

Report No.: FR240702AC Page: 18 of 18



Appendix A



Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
0.4.0.400=011	(112)	(112)		(112)	(112)
2.4-2.4835GHz	-	-	-	-	-
802.11b_Nss1,(1Mbps)_1TX	12.1M	14.093M	14M1G1D	12.075M	13.968M
802.11g_Nss1,(6Mbps)_1TX	16.525M	16.792M	16M8D1D	16.475M	16.742M
802.11n HT20_Nss1,(MCS0)_1TX	17.7M	17.866M	17M9D1D	17.675M	17.791M


Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth; Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit	Port 1-N dB	Port 1-OBW
		(Hz)	(Hz)	(Hz)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-
2412MHz	Pass	500k	12.075M	13.968M
2437MHz	Pass	500k	12.075M	14.093M
2462MHz	Pass	500k	12.1M	13.968M
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-
2412MHz	Pass	500k	16.475M	16.742M
2437MHz	Pass	500k	16.5M	16.792M
2462MHz	Pass	500k	16.525M	16.742M
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-
2412MHz	Pass	500k	17.7M	17.791M
2437MHz	Pass	500k	17.675M	17.866M
2462MHz	Pass	500k	17.7M	17.791M

Port X-N dB = Port X 6dB down bandwidth; Port X-OBW = Port X 99% occupied bandwidth












802.11g_Nss1,(6Mbps)_1TX **EBW** 2412MHz 2.412GHz 2.412GHz 10--10-Span Span 0-50MHz 50MHz -20 -RBW RBW -10-100kHz -30 300kHz -20 -VBW VBW -30 -300kHz 1MHz Sweep Time Sweep Time 100ms 100ms -50 Detector Type Detector Type -60 -60 -Peak Sample Port1 / 2.4G 2.41G 2.387G 2.4G 2.41G 2.42G 2.43G 2.437G 2.387G 2.42G 2.43G 2.437G 6dB(Hz) FI-6dB(Hz) Fh-6dB(Hz) OBW(Hz) FI-OBW(Hz) Fh-OBW(Hz) Limit(Hz) 16.475M 2.403725G 2.4202G 16.742M 2.403554G 2.420296G 500k





















Summary

Mode	Total Power	Total Power	
	(dBm)	(W)	
2.4-2.4835GHz	-	-	
802.11b_Nss1,(1Mbps)_1TX	15.89	0.03882	
802.11g_Nss1,(6Mbps)_1TX	13.79	0.02393	
802.11n HT20_Nss1,(MCS0)_1TX	13.76	0.02377	

Result

Mode	Result	DG	Port 1	Total Power	Power Limit	EIRP	EIRP Limit
		(dBi)	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	-2.08	13.39	13.39	-	11.31	-
2437MHz	Pass	-2.08	15.89	15.89	-	13.81	-
2462MHz	Pass	-2.08	13.21	13.21	1	11.13	-
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	-2.08	11.15	11.15	-	9.07	-
2437MHz	Pass	-2.08	13.79	13.79	-	11.71	-
2462MHz	Pass	-2.08	10.51	10.51	-	8.43	-
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	-2.08	10.76	10.76	-	8.68	-
2437MHz	Pass	-2.08	13.76	13.76	-	11.68	-
2462MHz	Pass	-2.08	10.45	10.45	-	8.37	-

DG = Directional Gain; Port X = Port X output power



Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.11b_Nss1,(1Mbps)_1TX	18.28	0.06730
802.11g_Nss1,(6Mbps)_1TX	20.86	0.12190
802.11n HT20_Nss1,(MCS0)_1TX	20.82	0.12078

Result

Mode	Result	DG	Port 1	Total Power	Power Limit	EIRP	EIRP Limit
		(dBi)	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	-2.08	16.05	16.05	30.00	13.97	36.00
2437MHz	Pass	-2.08	18.28	18.28	30.00	16.20	36.00
2462MHz	Pass	-2.08	15.86	15.86	30.00	13.78	36.00
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	-2.08	20.06	20.06	30.00	17.98	36.00
2437MHz	Pass	-2.08	20.86	20.86	30.00	18.78	36.00
2462MHz	Pass	-2.08	19.85	19.85	30.00	17.77	36.00
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	-2.08	19.81	19.81	30.00	17.73	36.00
2437MHz	Pass	-2.08	20.82	20.82	30.00	18.74	36.00
2462MHz	Pass	-2.08	19.79	19.79	30.00	17.71	36.00

DG = Directional Gain; Port X = Port X output power



Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
802.11b_Nss1,(1Mbps)_1TX	-13.88
802.11g_Nss1,(6Mbps)_1TX	-11.03
802.11n HT20_Nss1,(MCS0)_1TX	-11.57

RBW= 3 kHz

Result


Mode	Result	DG	Port 1	PD	PD Limit
		(dBi)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-
2412MHz	Pass	-2.08	-17.02	-17.02	8.00
2437MHz	Pass	-2.08	-13.88	-13.88	8.00
2462MHz	Pass	-2.08	-16.17	-16.17	8.00
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-
2412MHz	Pass	-2.08	-14.23	-14.23	8.00
2437MHz	Pass	-2.08	-11.03	-11.03	8.00
2462MHz	Pass	-2.08	-14.45	-14.45	8.00
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-
2412MHz	Pass	-2.08	-14.87	-14.87	8.00
2437MHz	Pass	-2.08	-11.57	-11.57	8.00
2462MHz	Pass	-2.08	-14.57	-14.57	8.00

DG = Directional Gain; RBW = 3kHz;


PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

RBW= 3 kHz



























Configuration 2: Battery mode

Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Page No. : 1 of 22





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



Unwanted Emission (Above 1GHz) for 11b




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain





*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain




Unwanted Emissions (Above 1GHz) for 11g



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)


*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain





*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain




Unwanted Emissions (Above 1GHz) for HT20



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)


*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain





*Factor includes antenna factor, cable loss and amplifier gain






*Factor includes antenna factor, cable loss and amplifier gain



Configuration 1: Charging mode

Unwanted Emissions (Below 1GHz)




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.






*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.





























Page No. : 1 of 2



