

SAR Test Report - New Application

Applicant:



Maximum Reported 10g SAR			
Extremity (wrist)	Wifi (DTS)	0.31	W/kg
	BT/BLE (DSS)	0.20	
General Pop. Limit:		4.00	

Garmin International Inc.
Olathe, KS, 66062
USA

FCC ID:

IPH-04431

Product Model Number / HVIN

A04431

IC Registration Number

Product Name / PMN

A04431

In Accordance With:

FCC 47 CFR §2.1093

Radiofrequency Radiation Exposure Evaluation: Portable Devices

Approved By:



Ben Hewson, President
Celltech Labs Inc.
21-364 Lougheed Rd.
Kelowna, BC, V1X 7R8
Canada



Test Lab Certificate: 2470.01



**Industry
Canada**

IC Registration 3874A



FCC Registration: CA3874

This report shall not be reproduced in any form without the expressed written consent of Celltech Labs Inc.

Table of Contents

1.0 DOCUMENT CONTROL	4
2.0 CLIENT AND DEVICE INFORMATION	5
3.0 SCOPE OF EVALUATION	6
4.0 NORMATIVE REFERENCES	7
5.0 STATEMENT OF COMPLIANCE	8
6.0 SAR MEASUREMENT SYSTEM	9
7.0 RF CONDUCTED POWER MEASUREMENT	10
TABLE 7.0 CONDUCTED POWER MEASUREMENTS – 2.4GHZ WIFI.....	10
TABLE 7.1 CONDUCTED POWER MEASUREMENTS – BT.....	11
8.0 NUMBER OF TEST CHANNELS (N_C) / SAR TEST REDUCTION	12
9.0 ACCESSORIES EVALUATED	13
10.0 SAR MEASUREMENT SUMMARY	14
TABLE 10.0: MEASURED RESULTS.....	14
11.0 SCALING OF MAXIMUM MEASURE SAR	15
TABLE 11.0 SAR SCALING – EXTREMITY.....	15
TABLE 11.1 SAR TEST EXCLUSION, TEST REDUCTION AND SIMULTANEOUS EVALUATION.....	17
12.0 SAR EXPOSURE LIMITS	18
TABLE 12.0 EXPOSURE LIMITS.....	18
13.0 DETAILS OF SAR EVALUATION	19
13.0 DAY LOG.....	19
13.1 DUT SETUP AND CONFIGURATION.....	20
13.2 DUT POSITIONING.....	20
13.3 GENERAL PROCEDURES AND REPORTING.....	21
13.4 FLUID DIELECTRIC AND SYSTEMS PERFORMANCE CHECK.....	22
13.5 SCAN RESOLUTION 100MHZ TO 2GHZ.....	22
13.6 SCAN RESOLUTION 2GHZ TO 3GHZ.....	23
13.7 SCAN RESOLUTION 5GHZ TO 6GHZ.....	23
14.0 MEASUREMENT UNCERTAINTIES	24
TABLE 14.0 MEASUREMENT UNCERTAINTY.....	24
15.0 FLUID DIELECTRIC PARAMETERS	25
TABLE 15.0 FLUID DIELECTRIC PARAMETERS 2450MHZ HEAD TSL.....	25
16.0 SYSTEM VERIFICATION TEST RESULTS	26
TABLE 16.0 SYSTEM VERIFICATION RESULTS 2450MHZ HEAD TSL.....	26
17.0 SYSTEM VALIDATION SUMMARY	27
TABLE 17.0 SYSTEM VALIDATION SUMMARY.....	27
18.0 MEASUREMENT SYSTEM SPECIFICATIONS	27
TABLE 18.0 MEASUREMENT SYSTEM SPECIFICATIONS.....	27
19.0 TEST EQUIPMENT LIST	29
TABLE 19.0 EQUIPMENT LIST AND CALIBRATION.....	29

<i>20.0 FLUID COMPOSITION</i>	30
TABLE 20.0 FLUID COMPOSITION 2450MHZ HEAD TSL	30
<i>END OF REPORT</i>	30
<i>APPENDIX A – SYSTEM VERIFICATION PLOTS</i>	31
<i>APPENDIX B – MEASUREMENT PLOTS OF MAXIMUM MEASURED SAR</i>	33
<i>APPENDIX C - SETUP PHOTOS</i>	37
FIGURE C.1 – PHOTO – SETUP: EXTREMITY, DUT BACK	37
<i>APPENDIX D – PROBE CALIBRATION</i>	38
<i>APPENDIX E – DIPOLE CALIBRATION</i>	39
<i>APPENDIX F - PHANTOM</i>	40

1.0 DOCUMENT CONTROL

Revision History					
Samples Tested By:		Ben Hewson	Date(s) of Evaluation:		26 March 2023
Report Prepared By:		Ben Hewson	Report Reviewed By:		Art Voss
Report Revision	Description of Revision	Revised Section	Revised By	Revision Date	
0.1	Draft	n/a	Ben Hewson	5 April 2023	
0.2	update to NFC info	2, 11	Ben Hewson	12 April 2023	
1.0	Initial Release	n/a	Ben Hewson	12 April 2023	

2.0 CLIENT AND DEVICE INFORMATION

Client Information	
Applicant Name	Garmin International Inc.
Applicant Address	1200 East 151 St
	Olathe, KS, 66062
	USA
DUT Information	
Device Identifier(s):	FCC ID: IPH-04431
	ISED ID:
Device Model(s) / HVIN:	A04431
EUT Name:	A04431
Test Sample Serial No.:	Production Sample Prototype
Device Type:	Extremity Worn Digital Device
Equipment Class	Digital Transmission System (DTS)
	Spread Spectrum Transmission System (DSS)
	Low Power Communication Device (DXX)
	Global Navigation Satellite System (GNSS) Receivers
	NFC - Low Power Communication Device Transmitter (DXX)
Transmit Frequency Range:	ANT (DXX): 2402-2480MHz
	BT (DTS, DSS): 2402-2480MHz
	WiFi (DTS): 2412-2462MHz
Manuf. Max. Rated Output Power:	ANT (DXX): 2.35mW (3.71dBm); NFC 0.0001mW (-40dBm)
	BT BR (DSS): 12.0mW (10.79dBm)
	BT 2EDR (DTS): 8.91mW (9.50dBm)
	BT 3EDR (DTS): 8.06mW (9.50dBm)
	BT LE1 (DTS): 2.37mW (3.75dBm)
	BT LE2 (DTS): 2.33mW (3.67dBm)
	802.11b (DTS): 0.06W (17.78dBm)
	802.11g (DTS): 0.09W (19.51dBm)
802.11n (DTS): 0.09W (19.58dBm)	
Antenna Type and Gain:	2.4GHz: -3.43 dBi Direct Contact Antenna
Modulation:	ANT: GFSK:
	BT BR: GFSK
	BT 2EDR: $\pi/4$ -DQPSK
	BT 3EDR: 8DPSK
	BLE: GMSK
	WiFi: CCK, DSSS, OFDM, MCS
DUT Power Source:	5V USB, Internal Li-Ion Battery
Deviation(s) from standard/procedure:	None
Modification of DUT:	None

3.0 SCOPE OF EVALUATION

This Certification Report was prepared on behalf of:

Garmin International Inc.

, (the '*Applicant*'), in accordance with the applicable Federal Communications Commission (FCC) CFR 47 (the '*Rules*'). The scope of this investigation was limited to only the equipment, devices and accessories (the '*Equipment*') supplied by the *Applicant*. The tests and measurements performed on this *Equipment* were only those set forth in the applicable *Rules* and/or the Test and Measurement Standards they reference. The *Rules* applied and the Test and Measurement Standards used during this evaluation appear in the Normative References section of this report. The limits set forth in the technical requirements of the applicable *Rules* were applied to the measurement results obtained during this evaluation and, unless otherwise noted, these limits were used as the Pass/Fail criteria. The Pass/Fail statements made in this report apply to only the tests and measurements performed on only the *Equipment* tested during this evaluation. Where applicable and permissible, information including test and measurement data and/or results from previous evaluations of same or similar equipment, devices and/or accessories may be cited in this report.

As per FCC 47 CFR Part §2.1091 and §2.1093, an RF Exposure evaluation report is required for this *Equipment* and the results of the RF Exposure evaluation appear in this report.

The A04431 FCC ID: IPH-04431, is a wrist-worn transceiver that is capable of operating in the 2.4GHz WiFi and Bluetooth frequency bands and has an additional NFC feature that operates at a fixed transmit frequency of 13.56MHz. The device is not capable of simultaneous transmission between transmitters. The device is intended for General Population Use. The product operates from an internal proprietary Li-ion rechargeable battery which can be connected to a compliant USB interface port, AC or DC adapter for charging. Test samples provided by the manufacturer were capable of transmitting at select frequencies and modulations preset by the manufacturer. An additional antenna modification was prepared for one sample allowing the ability to connect test equipment for antenna port conducted power analysis.

4.0 NORMATIVE REFERENCES


Normative References*	
ANSI / ISO 17025	General Requirements for competence of testing and calibration laboratories
FCC CFR Title 47 Part 2 Title 47: Part 2.1093:	Code of Federal Regulations Telecommunication Radiofrequency Radiation Exposure Evaluation: Portable Devices
IEC International Standard /IEEE International Committee on Electromagnetic Safety IEC/IEEE 62209-1528	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1528; Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)
FCC KDB KDB 865664 D01v01r04	SAR Measurement Requirements for 100MHz to 6GHz
FCC KDB KDB 447498 D01v06	Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies
FCC KDB KDB 248227 D01v02r02	SAR Guidance for IEEE 802.11 (WiFi) Transmitters
* When the issue number or issue date is omitted, the latest version is assumed.	

5.0 STATEMENT OF COMPLIANCE

This measurement report demonstrates that samples of the product model(s) were evaluated for Specific Absorption Rate (SAR) on the date(s) shown, in accordance with the Measurement Procedures cited and were found to comply with the Standard(s) Applied based on the Exposure Limits of the Use Group indicated for which the product is intended to be used.

Applicant: Garmin International Inc.		Model / HVIN: A04431
Standard(s) Applied: FCC 47 CFR §2.1093		Measurement Procedure(s): FCC KDB 865664, FCC KDB 447498, FCC KDB 248227 IEC/IEEE Standard 62209-1528
Reason For Issue: <input checked="" type="checkbox"/> New Certification <input type="checkbox"/> Class I Permissive Change <input type="checkbox"/> Class II Permissive Change	Use Group: <input checked="" type="checkbox"/> General Population / Uncontrolled <input type="checkbox"/> Occupational / Controlled	Limits Applied: <input type="checkbox"/> 1.6W/kg - 1g Volume <input type="checkbox"/> 8.0W/kg - 1g Volume <input checked="" type="checkbox"/> 4.0W/kg - 10g Volume
Reason for Change:		Date(s) Evaluated: 26 March 2023

The results of this investigation are based solely on the test sample(s) provided by the applicant which was not adjusted, modified or altered in any manner whatsoever except as required to carry out specific tests or measurements. A description of the device, operating configuration, detailed summary of the test results, methodologies and procedures used during this evaluation, the equipment used and the various provisions of the rules are included in this test report.

<p>I attest that the data reported herein is true and accurate within the tolerance of the Measurement Instrument Uncertainty; that all tests and measurements were performed in accordance with accepted practices or procedures; and that all tests and measurements were performed by me or by trained personnel under my direct supervision. The results of this investigation are based solely on the test sample(s) provided by the client which were not adjusted, modified or altered in any manner whatsoever, except as required to carry out specific tests or measurements. This test report has been completed in accordance with ISO/IEC 17025.</p>	
	<p>Ben Hewson Celltech Labs Inc.</p>
	<p>26 March 2023 Date</p>

6.0 SAR MEASUREMENT SYSTEM

SAR Measurement System

Celltech Labs Inc. SAR measurement facility employs a Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY6 measurement system is comprised of the measurement server, a robot controller, a computer, a near-field probe, a probe alignment sensor, an Elliptical Planar Phantom (ELI) phantom and a specific anthropomorphic mannequin (SAM) phantom for Head and/or Body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller and a teach pendant (Joystick) to control the robot's servo motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical form the DAE to digital electronic signal and transfers data to the DASY6 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter, a command decoder and a control logic unit. Transmission to the DASY6 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot utilizes a controller with built in VME-bus computer.



DASY 6 SAR System with SAM Phantom



DASY 6 Measurement Controller

7.0 RF CONDUCTED POWER MEASUREMENT

Table 7.0 Conducted Power Measurements – 2.4GHz WiFi

A04431-Conducted Power Measurements									
Channel	Frequency (MHz)	Measured Power (dBm)	Rated Power (dBm)	Delta (dB)	SAR Test Channel (Y/N)	Mode	BW (MHz)	Modulation	
1	2412	17.78			-	WLAN 2.4G	20	DSSS-1Mbps	802.11b
		17.21			-			DSSS-2Mbps	
		17.35			-			DSSS-5.5Mbps	
		17.35			-			DSSS-11Mbps	
1	2412	17.78	17.78	0.00	Y				
6	2437	17.57	17.78	-0.22	Y			DSSS-1Mbps	
11	2462	16.83	17.78	-0.95	Y				
1	2412	10.86	11.31	-0.45	-	WLAN 2.4G	20	OFDM-12Mbps	802.11g
6	2437	19.51	19.51	0.00					
11	2462	13.62	14.75	-1.13					
1	2412	11.53	12.01	-0.48	-	WLAN 2.4G	20	MCS-2	802.11n
5	2432	19.58	19.58	0.00	-				
6	2437	19.36	19.58	-0.22	-				
11	2462	15.36	15.75	-0.39					

Table 7.1 Conducted Power Measurements – BT

A04431- Conducted Power Measurements							
Mode	Modulation	Frequency (MHz)	Measured Power (dBm)	Measured Power (mW)	Rated Power (mW)	Delta (mW)	SAR test Channel
ANT	GFSK	2402.00	0.09	1.02	2.35	-1.33	-
		2440.00	3.56	2.27	2.35	-0.08	-
		2478.00	3.71	2.35	2.35	0.00	-
		2480.00	0.53	1.13	2.35	-1.22	-
BT BR	GFSK	2402.00	9.69	9.32	12.00	-2.68	-
		2440.00	9.91	9.79	12.00	-2.21	-
		2480.00	10.79	12.00	12.00	0.00	Y
BT 2EDR	$\pi/4$ -DQPSK	2402.00	8.99	7.93	8.91	-0.98	-
		2440.00	9.27	8.46	8.91	-0.45	-
		2460.00	9.50	8.91	8.91	0.00	-
		2480.00	9.20	8.31	8.91	-0.60	-
BT 3EDR	8DPSK	2402.00	8.57	7.20	8.06	-0.86	-
		2440.00	8.71	7.43	8.06	-0.63	-
		2460.00	9.06	8.06	8.06	0.00	-
		2480.00	8.73	7.46	8.06	-0.60	-
BT LE1	GMSK	2402.00	-0.32	0.93	2.37	-1.44	-
		2440.00	3.48	2.23	2.37	-0.14	-
		2460.00	3.75	2.37	2.37	0.00	-
		2480.00	0.57	1.14	2.37	-1.23	-
BT LE2	GMSK	2440.00	3.67	2.33	2.33	0.00	-
		2460.00	3.60	2.29	2.33	-0.04	-
		2478.00	0.61	1.15	2.33	-1.18	-

The rated power and tolerance are stated for typical transmission modes and data rates. Some modes and data rates may produce lower than rated conducted power levels. Power measurements taken across the various channels, modes and data rates did not produce levels in excess of the Rated Power plus Tolerance. SAR was evaluated using the power level setting and duty cycle specified by the manufacturer to be the max output power and produce the most conservative SAR. SAR was evaluated at the maximum average tune up tolerance. See section 2.0 Client and Device Information for details. The reported SAR was not scaled down.

8.0 NUMBER OF TEST CHANNELS (N_c) / SAR TEST REDUCTION

2.4GHz WiFi SAR Evaluation

In accordance with FCC KDB 248227, when higher maximum output power is not specified for the other channels, channels 1, 6 and 11 are used to configure 22 MHz DSSS and 20 MHz OFDM channels for SAR measurements.

802.11b DSSS SAR Test Requirements

802.11b DSSS SAR test reduction is determined according to the following:

a) When the reported SAR of the highest measured maximum output power channel (see 3.1) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.

b) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

When 10g Extremity applies, the test reduction thresholds are multiplied by 2.5, or 2.0W/kg and 3W/kg, respectively.

2.4GHz 802.11g/n OFDM SAR Test Requirements

SAR is not required for the following 2.4 GHz OFDM conditions:

a) When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.

b) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

When 10g Extremity applies, the test reduction threshold is multiplied by 2.5, or 3W/kg.

BT/BLE/ANT SAR Test Requirements

General SAR test reduction per FCC KDB 447498D01

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid band or highest output power channel is:

≤ 0.8 W/kg or 2.0W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 Mhz.

9.0 ACCESSORIES EVALUATED

The silicone band (non-metallic) that comes with this device was removed for SAR evaluations. The metal component of the band, a metal spring bar that holds the band to the device was installed for the testing.

10.0 SAR MEASUREMENT SUMMARY

Table 10.0: Measured Results

Measured 10g SAR Results - EXTREMITY Configuration																
Date	Plot ID	Test Frequency (MHz)	DUT Configuration					Accessories	Spacing		Measured SAR (W/kg)	SAR Drift (dB)	Delta Power (dB)	Crest Factor (n)	Fluid Sensitivity (n)	reported SAR (W/kg)
			Pos	Mode	BW	Mod	BR		DUT (mm)	Antenna (mm)						
3/26/2023	E20	2412	Back Side	802.11b-00	20	DSSS	1		0	0	0.218	-0.120	0.000	1.000	1.000	0.224
3/26/2023	E21	2437	Back Side	802.11b-00	20	DSSS	1		0	0	0.205	-0.270	-0.210	1.000	1.000	0.229
3/26/2023	E22	2462	Back Side	802.11b-00	20	DSSS	1		0	0	0.238	-0.220	-0.950	1.000	1.000	0.312
3/26/2023	E30	2480	Back Side	BT BR		GFSK			0	0	0.202	-0.050	0.000	1.000	1.000	0.204
Applicable SAR Limit								Use Group				Limit				
FCC CFR 2.1093			Health Canada Safety Code 6					General Population/User Unaware				4 W/kg				

11.0 SCALING OF MAXIMUM MEASURE SAR

Table 11.0 SAR Scaling – Extremity

Scaling of Maximum Measured SAR (10g)				
Measured Parameters		Configuration		
		Extremity	Extremity	
Plot ID		E22	E30	
Maximum Measured SAR _M		0.238	0.202	(W/kg)
Frequency		2462	2480	(MHz)
Drift	Power Drift	-0.220	-0.050	(dB)
Conducted Power		16.830	10.790	(dBm)
DC	Transmit Duty Cycle	100.000	100.0	(%)
Fluid Deviation from Target				
Δe	Permittivity	-6.56%	-6.69%	
Δσ	Conductivity	5.52%	4.37%	

Fluid Sensitivity Calculation (10g)			EEE 62209-1528
Delta SAR = Ce * Δe + Cσ * Δσ			
Ce = (0.003456*f ³) - (0.03531*f ²) + (0.07675*f) - 0.186			
Cσ = (0.004479*f ³) - (0.01586*f ²) - (0.1972*f) + 0.7717			
f	Frequency (GHz)	2.462	2.48
Ce		-0.159	-0.160
Cσ		0.257	0.253
Ce * Δe		0.010	0.011
Cσ * Δσ		0.014	0.011
ΔSAR		0.025 ⁽³⁾	0.022 ⁽³⁾

Note(3): Delta SAR is Positive, SAR Adjustment for Fluid Sensitivity is not Required, in accordance with ISED Notice 2012-DRS0529

Manufacturer's Tuneup Tolerance				
Measured Conducted Power		16.830	10.790	(dBm)
Rated Conducted Power		17.780	10.790	(dBm)
ΔP		-0.950	0.000 ⁽⁴⁾	(dB)

Note(4): SAR was Evaluated at the Maximum Tuneup Tolerance. SAR Adjustment is not Required.

Crest Factor				
Transmit Duty Cycle (DC)		100.000	100.0	(%)
CF (1/DC)		1.000 ⁽⁵⁾	1.00	###

Note(5): Crest Factor = 1 (100% Duty Cycle), Crest Factor Adjustment not Required.

SAR Adjustment for Fluid Sensitivity				
SAR ₁ = SAR _M X [ΔSAR]		0.238	0.202	(W/kg)
SAR Adjustment for Tuneup Tolerance				
SAR ₂ = SAR ₁ + [ΔP]		0.296	0.202	(W/kg)
SAR Adjustment for Drift				
SAR ₃ = SAR ₂ + [Drift]		0.312	0.204	(W/kg)
SAR Adjustment for Crest Factor				
SAR ₄ = SAR ₃ x [CF]		0.312	0.204	(W/kg)
reported 10g SAR				
SAR ₄		0.31	0.20	(W/kg)

NOTES to Table 11.0

(1) Scaling of the Maximum Measured SAR is based on the highest, 100% duty cycle, Face, Body and/or Head SAR measured of ALL test channels, configurations and accessories used during THIS evaluation. The Measured Fluid Deviation parameters apply only to deviation of the tissue equivalent fluids used at the frequencies which produced the highest measured SAR. The Measured Conducted Power applies to the Conducted Power measured at the frequencies producing the highest Face and Body SAR. The Measured Drift is the SAR drift associated with that specific SAR measurement. The Reported SAR is the accumulation of all SAR Adjustments from the applicable Steps 1 through 4. The Plot ID is for identification of the SAR Measurement Plots in Annex A of this report.

NOTE: Some of the scaling factors in Steps 1 through 4 may not apply and are identified by light gray text.

Step 1

Per IEC/IEEE 62209-1528 and FCC KDB 865664. Scaling required only when Measured Fluid Deviation is greater than 5%. If the Measured Fluid Deviation is greater than 5%, Table 9.1 will be shown and will indicate the SAR scaling factor in percent (%). SAR is MULTIPLIED by this scaling factor only when the scaling factor is positive (+).

Step 2

Per KDB 447498. Scaling required only when the difference (Delta) between the Measured Conducted Power and the Manufacturer's Rated Conducted Power is (-) Negative. The absolute value of Delta is ADDED to the SAR.

Step 3

Per IEC/IEEE 62209-1528. Scaling required only when Measured Drift is (-) Negative. The absolute value of Measured Drift is added to Reported or Simultaneous Reported SAR.

Step 4

Per KDB 447498 4.3.2. The SAR, either measured or calculated, of ANY and ALL simultaneous transmitters must be added together and includes all contributors.

Step 5

The Reported SAR is the Maximum Final Adjusted Cumulative SAR from the applicable Steps 1 through 4 and are reported on Page 1 of this report.

Table 11.1 SAR Test Exclusion, Test Reduction and Simultaneous Evaluation

SAR Test Exclusion BLE/ANT

The SAR test exclusion threshold for the BLE/ANT transmitter as per FCC KDB 447498 4.3.1 is as follows:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 7.5$ for 10-g SAR

$$\text{Max. Power} = 3.71\text{mW}$$

$$f = 2.478\text{GHz}$$

$$\text{Distance} = 5\text{mm}$$

$$[3.71\text{mW} / 5\text{mm}] \times [\sqrt{2.478}] = 1.17 \leq 7.5$$

The BLE/ANT transmitters meet the SAR test exclusion threshold

SAR Test Exclusion NFC

The SAR test exclusion threshold for the NFC transmitter as per FCC KDB 447498 4.3.1 is as follows:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 7.5$ for 10-g SAR

$$\text{Max. Power}(EIRP) = 0.0001\text{mW}$$

$$f = 0.01356\text{GHz}$$

$$\text{Distance} = 5\text{mm}$$

$$[0.0001\text{mW} / 5\text{mm}] \times [\sqrt{0.01356}] = 0.000002 \leq 7.5$$

The NFC transmitters meet the SAR test exclusion threshold

802.11b DSSS SAR Test Reduction

802.11b DSSS SAR was evaluated on all required channels. 802.11b DSSS SAR Test Reduction was not applied.

a) When the reported SAR of the highest measured maximum output power channel (see 3.1) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.

b) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

When 10g Extremity applies, the test reduction thresholds are multiplied by 2.5, or 2.0W/kg and 3W/kg, respectively.

2.4GHz 802.11g/n OFDM SAR Test Reduction

$$\text{Max. Power DSSS } (P_{DSSS}) = 60\text{mW}$$

$$\text{Max. Power OFDM } (P_{OFDM}) = 89.3\text{mW}$$

$$\text{Max. reported DSSS SAR } (SAR_{DSSS}) = 0.312\text{W/kg } 10\text{g Extremity}$$

$$\text{Exclusion} = [P_{OFDM} / P_{DSSS}] \times SAR_{DSSS} \leq 3.0\text{W/kg } 10\text{g}$$

$$\text{Exclusion} = [89.3\text{mW} / 60\text{mW}] \times 0.312\text{W/kg} = 0.465\text{W/kg} \leq 3.0\text{W/kg} \text{ for } 10\text{g Extremity}$$

The 2.4GHz 802.11g/n OFDM transmitter meets the SAR test exclusion requirement

Bluetooth SAR Test Reduction

Bluetooth was evaluated for SAR at a transmit duty cycle of 100 % in the worst-case configuration from the WiFi test evaluation.

The duty cycle cannot be altered in test mode or by the user.

General SAR test reduction per FCC KDB 447498D01

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid band or highest output power channel is:

$\leq 0.8\text{W/kg}$ or 2.0W/kg , for 1-g or 10-g respectively, when the transmission band is $\leq 100\text{MHz}$.

Simultaneous SAR Evaluation

This device is not capable of simultaneous transmission between the BT/BLE/ANT and WiFi transmitters.

The WiFi and Bluetooth transmitters were evaluated for Standalone SAR Only.

Simultaneous transmission evaluation with NFC and 802.11b/g/n/BT/BLT/ANT is not required

12.0 SAR EXPOSURE LIMITS

Table 12.0 Exposure Limits

SAR RF EXPOSURE LIMITS			
FCC 47 CFR§2.1093	Health Canada Safety Code 6	General Population / Uncontrolled Exposure ⁽⁴⁾	Occupational / Controlled Exposure ⁽⁵⁾
Spatial Average ⁽¹⁾ (averaged over the whole body)		0.08 W/kg	0.4 W/kg
Spatial Peak ⁽²⁾ (Head and Trunk averaged over any 1 g of tissue)		1.6 W/kg	8.0 W/kg
Spatial Peak ⁽³⁾ (Hands/Wrists/Feet/Ankles averaged over 10 g)		4.0 W/kg	20.0 W/kg
(1) The Spatial Average value of the SAR averaged over the whole body.			
(2) The Spatial Peak value of the SAR averaged over any 1 gram of tissue, defined as a tissue volume in the shape of a cube and over the appropriate averaging time.			
(3) The Spatial Peak value of the SAR averaged over any 10 grams of tissue, defined as a tissue volume in the shape of a cube and over the appropriate averaging time.			
(4) Uncontrolled environments are defined as locations where there is potential exposure to individuals who have no knowledge or control of their potential exposure.			
(5) Controlled environments are defined as locations where there is potential exposure to individuals who have knowledge of their potential exposure and can exercise control over their exposure.			

13.0 DETAILS OF SAR EVALUATION

13.0 Day Log

DAY LOG					Fluid Dielectric	SPC	Test	Task
Date	Ambient Temp (°C)	Fluid Temp (°C)	Relative Humidity (%)	Barometric Pressure (kPa)				
26 Mar 2023	24.7	23.5	20%	101.0	X	X	X	2450

*Per IEC/IEEE 62209-1528, test series was started within 24 hours of Fluid Parameter Measurement

13.1 DUT Setup and Configuration

DUT Setup and Configuration	
1	The device was evaluated for Extremity (wrist worn), from a flat phantom filled with head tissue-equivalent medium. The DUT was evaluated for SAR in accordance with the procedures described in RSS-102, IEC/IEEE 62209-1528, FCC KDB 447498, 865664, 248227.
2	<p>2.4GHz 802.11g/n OFDM SAR Test Exclusion</p> <p>As Per KDB 248227 D01v02r02 - 5.2.2, b) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2W/kg$</p> <p>When applying this formula to Body limits the adjusted SAR is $\leq 1.5W/kg$, and for Extremity limits is $\leq 3.0W/kg$.</p> <p>Maximum 802.11g/n OFDM specified power(POFDM)= 19.51 dBm (89.33mW) Maximum 802.11b DSSS specified power (PDSSS)= 17.78 dBm (59.98mW) Ratio OFDM/DSSS power = 1.73 dBm (1.10%) Highest reported SAR (SARMAX)= 0.31W/kg</p> <p>POFDM/PDSSS X SARMAX = 0.34 W/kg $\leq 3.0 W/kg$ (Extremity) and $\leq 1.5 W/kg$ (Body) and SAR test exclusion applies.</p>
3	The Device was capable of transmitting at various modulations, data rates and duty cycles. The Conducted Power was highest when measured in DSSS Mode-5.5 Mbps at 100% Duty cycle than any other configuration in the 2.4GHz Band. The DUT was evaluated for SAR at the maximum conducted output power level, preset by the manufacturer.
4	Bluetooth was evaluated for SAR in BT BR (GFSK) mode with a transmit duty cycle of 100% in the worst-case configuration from the WiFi test evaluation. The Duty cycle could not be altered in test mode or by the user. The DUT was evaluated for SAR at the maximum conducted output power level, preset by the manufacturer.
5	Each SAR evaluation was performed with a fully charged battery.

13.2 DUT Positioning

DUT Positioning	
Positioning	The DUT Positioner was securely fastened to the Phantom Platform. Registration marks were placed on the DUT and the Positioner to ensure consistent positioning of the DUT for each test evaluation.
FACE Configuration	Devices that are designed to be worn on the wrist and may operate with in speaker mode for voice communication, with the device positioned next to the mouth. When next-to-mouth SAR evaluation is required, the device is positioned at 10mm from a flat phantom filled with head tissue-equivalent medium.
BODY Configuration	Devices that are designed to be worn on the Body are positioned on the device holder with the surface of the DUT being 5mm from bottom of the phantom in the Body configuration.
HEAD Configuration	This device is not intended to be held to the ear and was not tested in the HEAD configuration.
Limb Worn Configuration	Devices that are designed to be worn on the wrist are positioned with the back side directly against the phantom surface with the strap removed or opened to allow direct contact of the DUT to the phantom surface.

13.3 General Procedures and Reporting

General Procedures and Reporting	
General Procedures	<p>The fluid dielectric parameters of the Active Tissue Simulating Liquid (TSL) were measured as described in this Section, recorded and entered into the DASY Measurement Server. Active meaning the TSL used during the SAR evaluation of the DUT. The temperature of the Active TSL was measured and recorded prior to performing a System Performance Check (SPC). An SPC was performed with the Active TSL prior to the start of the test series. The temperature of the Active TSL was measured throughout the day and the Active TSL temperature was maintained to $\pm 0.5^{\circ}\text{C}$. The Active TSL temperature was maintained to within $\pm 1.0^{\circ}\text{C}$ throughout the test series. TSL analysis and SPC were repeated when the Active TSL use exceeded 84 hours.</p> <p>An Area Scan exceeding the length and width of the DUT projection was performed and the locations of all maximas within 2dB of the Peak SAR recorded. A Zoom Scan centered over the Peak SAR location(s) was performed and the 1g and 10g SAR values recorded. The resolutions of the Area Scan and Zoom Scan are described in the Scan Resolution table(s) in this Section. A Power Reference Measurement was taken at the phantom reference point immediately prior to the Area Scan. A Power Drift measurement was taken at the phantom reference point immediately following the Zoom Scan to determine the power drift. A Z-Scan from the <u>Maximum Distance to Phantom Surface</u> to the fluid surface was performed following the power drift measurement.</p>
Reporting	<p>Where appropriate the 1g SAR, 10g SAR and power drift measurements are recorded in the SAR Measurement Summary tables in the SAR Measurement Summary Section of this report. The SAR values shown in the 100% DC (Duty Cycle) column are the SAR values reported by the SAR Measurement Server with the DUT operating at or compensated for a 100% transmit duty cycle. A duty cycle compensation (crest factor) and fluid sensitivity scaling factor is shown, as well as other information such as transmit channel and frequency, modulation, accessories tested and DUT-phantom separation distance.</p> <p>In the Scaling of Maximum Measured SAR Section of this report, the highest measured SAR in the BODY and/or FACE and/or EXTREMITY (limb-worn) configurations, within the entire scope of this assessment, are, when applicable, scaled for Fluid Sensitivity, Manufacturer's Tune-Up Tolerance, Simultaneous Transmission and Drift. With the exception of Duty Cycle correction/compensation, SAR values are <u>ONLY</u> scaled up, not down. The final results of this scaling is the <u>reported SAR</u> which appears on the Cover Page of this report.</p>

13.4 Fluid Dielectric and Systems Performance Check

Fluid Dielectric and Systems Performance Check	
Fluid Dielectric Measurement Procedure	
<p>The fluid dielectric parameters of the Tissue Simulating Liquid (TSL) are measured using the Open-Ended Coax Method connected to an Agilent 8753ET Network Analyzer connected to a measurement server running Aprel Dielectric Property Measurement System. A frequency range of $\pm 100\text{MHz}$ for frequencies $> 300\text{MHz}$ and $\pm 50\text{MHz}$ for frequencies $\leq 300\text{MHz}$ with frequency step size of 10MHz is used. The center frequency is centered around the SAR measurement probe's calibration point for that TSL frequency range. A calibration of the setup is performed using a short-open-deionized water (at 23°C in a 300ml beaker) method. A sample of the TSL is placed in a 300ml beaker and the open-ended coax is submerged approximately 8mm below the fluid surface in the approximate center of the beaker. A check of the setup is made to ensure no air is trapped under the open-ended coax. The sample of TSL is measured and compared to the FCC KDB 865664 targets for HEAD or BODY for the entire fluid measurement range. Fluid adjustment are made if the dielectric parameters are $> 5\%$ in range that the DUT is to be tested. If the adjustments fail to bring the parameters to $\leq 5\%$ but are $< 10\%$, the SAR Fluid Sensitivity as per IEC\IEEE 62209-1528 and FCC KDB 865664 are applied to the highest measured SAR. A TSL with dielectric parameters $> 10\%$ in the DUT test frequency range are not used.</p>	
Systems Performance Check	
<p>The fluid dielectric parameters of the Active TSL are entered into the DASY Measurement Server at each of the 10MHz step size intervals. Active meaning the TSL used during the SAR evaluation of the DUT. The DASY Measurement System will automatically interpolate the dielectric parameters for DUT test frequencies that fall between the 10MHz step intervals.</p> <p>A Systems Performance Check (SPC) is performed in accordance with IEC\IEEE 62209-1528 "System Check" and FCC KDB 865664 "System Verification". A validation source, dipole or Confined Loop Antenna (CLA), is placed under the geometric center of the phantom and separated from the phantom in accordance to the validation source's Calibration Certificate data. A CW signal set to the frequency of the validate source's and SAR measurement probe's calibration frequency with a forward power set to the validation source's Calibration Certificate data power setting is applied to the validation source. An Area Scan is centered over the projection of the validation source's feed point and an Area Scan is taken. A Zoom Scan centered over the Peak SAR measurement of the Area Scan and the 1g and 10g SAR is measured. The measured 1g and 10g SAR is compared to the 1g and 10g SAR measurements from the validation source's Calibration Certificate. When required, the measured SAR is normalized to 1.0W and compared to the normalized SAR indicated on the validation source's Calibration Certificate. The SPC is considered valid when the measured and normalized SAR is $\leq 10\%$ of the measured and normalize SAR of the validation source's Calibration Certificate.</p> <p>The fluid dielectric parameters of the Active TSL and SPC are repeated when the Active TSL has been in use for greater than 84 hours or if the Active TSL temperature has exceed $\pm 1^\circ\text{C}$ of the initial fluid analysis.</p>	

13.5 Scan Resolution 100MHz to 2GHz

Scan Resolution 100MHz to 2GHz	
Maximum distance from the closest measurement point to phantom surface: (Geometric Center of Probe Center)	$4 \pm 1 \text{ mm}$
Maximum probe angle normal to phantom surface. (Flat Section ELI Phantom)	$5^\circ \pm 1^\circ$
Area Scan Spatial Resolution $\Delta X, \Delta Y$	15 mm
Zoom Scan Spatial Resolution $\Delta X, \Delta Y$	7.5 mm
Zoom Scan Spatial Resolution ΔZ (Uniform Grid)	5 mm
Zoom Scan Volume X, Y, Z	30 mm
Phantom	ELI
Fluid Depth	$150 \pm 5 \text{ mm}$
An Area Scan with an area extending beyond the device was used to locate the candidate maximas within 2dB of the global maxima.	
A Zoom Scan centered over the peak SAR location(s) determined by the Area Scan was used to determine the 1-gram and 10-gram peak spatial-average SAR	

13.6 Scan Resolution 2GHz to 3GHz

Scan Resolution 2GHz to 3GHz	
Maximum distance from the closest measurement point to phantom surface: (Geometric Center of Probe Center)	4 ± 1 mm
Maximum probe angle normal to phantom surface. (Flat Section ELI Phantom)	5° ± 1°
Area Scan Spatial Resolution $\Delta X, \Delta Y$	12 mm
Zoom Scan Spatial Resolution $\Delta X, \Delta Y$	5 mm
Zoom Scan Spatial Resolution ΔZ (Uniform Grid)	5 mm
Zoom Scan Volume X, Y, Z	30 mm
Phantom	ELI
Fluid Depth	150 ± 5 mm
An Area Scan with an area extending beyond the device was used to locate the candidate maximas within 2dB of the global maxima.	
A Zoom Scan centered over the peak SAR location(s) determined by the Area Scan was used to determine the 1-gram and 10-gram peak spatial-average SAR	

13.7 Scan Resolution 5GHz to 6GHz

Scan Resolution 5GHz to 6GHz	
Maximum distance from the closest measurement point to phantom surface: (Geometric Center of Probe Center)	4 ± 1 mm
Maximum probe angle normal to phantom surface. (Flat Section ELI Phantom)	5° ± 1°
Area Scan Spatial Resolution $\Delta X, \Delta Y$	10 mm
Zoom Scan Spatial Resolution $\Delta X, \Delta Y$	4 mm
Zoom Scan Spatial Resolution ΔZ (Uniform Grid)	2 mm
Zoom Scan Volume X, Y, Z	22 mm
Phantom	ELI
Fluid Depth	100 ± 5 mm
An Area Scan with an area extending beyond the device was used to locate the candidate maximas within 2dB of the global maxima.	
A Zoom Scan centered over the peak SAR location(s) determined by the Area Scan was used to determine the 1-gram and 10-gram peak spatial-average SAR	

14.0 MEASUREMENT UNCERTAINTIES

Table 14.0 Measurement Uncertainty

Measurement uncertainty table is not required per KDB 865664 D01 v01r04 section 2.8.2 page 12. SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is ≥ 1.5 W/kg for 1-g SAR. The equivalent ratio (1.5/1.6) should be applied to extremity and occupational exposure conditions. The highest reported SAR value is less than 1.5W/kg. Therefore, the measurement uncertainty table is not required.

15.0 FLUID DIELECTRIC PARAMETERS

Table 15.0 Fluid Dielectric Parameters 2450MHz HEAD TSL

 Aprel Laboratory
 Test Result for UIM Dielectric Parameter
 Sun 26/Mar/2023 12:55:13
 Freq Frequency(GHz)
 FCC_eHFCC OET 65 Supplement C (June 2001) Limits for Head Epsilon
 FCC_sHFCC OET 65 Supplement C (June 2001) Limits for Head Sigma
 Test_e Epsilon of UIM
 Test_s Sigma of UIM

Freq	FCC_eHFCC	sHFCC	Test_e	Test_s
2.4100	39.27	1.76	36.91	1.83
2.4200	39.25	1.77	36.71	1.84
2.4300	39.24	1.78	36.68	1.84
2.4400	39.22	1.79	36.60	1.85
2.4500	39.20	1.80	36.73	1.87
2.4600	39.19	1.81	36.60	1.91
2.4700	39.17	1.82	36.67	1.92
2.4800	39.16	1.83	36.54	1.91

FLUID DIELECTRIC PARAMETERS								Fluid Sensitivity Calculation IEC/IEEE 62209-1528 7.8.2			
Date:	26-Mar-2023	Fluid Temp:	23.5	Frequency:	2450MHz	Tissue:	Head	ΔSAR 1g	ΔSAR 10g	SAR Correction Factor (1)	
Freq (MHz)	Test ε	Test σ (S/m)	Target ε	Target σ (S/m)	Deviation Permittivity	Deviation Conductivity	1g			10g	
2410.0000		36.9100	1.8300	39.2700	1.76	-6.01%	3.98%	0.033	0.020	1.000	1.000
2412.0000	*	36.8700	1.8320	39.2660	1.76	-6.10%	3.97%	0.033	0.020	1.000	1.000
2420.0000		36.7100	1.8400	39.2500	1.77	-6.47%	3.95%	0.034	0.021	1.000	1.000
2430.0000		36.6800	1.8400	39.2400	1.78	-6.52%	3.37%	0.031	0.019	1.000	1.000
2437.0000	*	36.6240	1.8470	39.2260	1.79	-6.63%	3.36%	0.031	0.019	1.000	1.000
2440.0000		36.6000	1.8500	39.2200	1.79	-6.68%	3.35%	0.031	0.019	1.000	1.000
2450.0000		36.7300	1.8700	39.2000	1.80	-6.30%	3.89%	0.033	0.020	1.000	1.000
2460.0000		36.6000	1.9100	39.1900	1.81	-6.61%	5.52%	0.041	0.025	1.000	1.000
2462.0000	*	36.6140	1.9120	39.1860	1.81	-6.56%	5.52%	0.041	0.025	1.000	1.000
2470.0000		36.6700	1.9200	39.1700	1.82	-6.38%	5.49%	0.040	0.024	1.000	1.000
2480.0000	*	36.5400	1.9100	39.1600	1.83	-6.69%	4.37%	0.036	0.022	1.000	1.000

16.0 SYSTEM VERIFICATION TEST RESULTS

Table 16.0 System Verification Results 2450MHz HEAD TSL

System Verification Test Results					
Date		Frequency (MHz)	Validation Source		
			P/N		S/N
26 Mar 2023		2450	D2450V2		825
Fluid Type	Fluid Temp °C	Ambient Temp °C	Ambient Humidity (%)	Forward Power (mW)	Source Spacing (mm)
Head	23.5	25	20%	250	10
Fluid Parameters					
Permittivity			Conductivity		
Measured	Target	Deviation	Measured	Target	Deviation
36.73	39.20	-6.30%	1.87	1.80	3.89%
Measured SAR					
1 gram			10 gram		
Measured	Target	Deviation	Measured	Target	Deviation
14.30	13.18	8.50%	6.49	6.01	8.08%
Measured SAR Normalized to 1.0W					
1 gram			10 gram		
Normalized	Target	Deviation	Normalized	Target	Deviation
57.20	52.72	8.50%	25.96	24.02	8.10%
<p>Prior to the SAR evaluations, system checks were performed on the planar section of the phantom and a SPEAG validation dipole in accordance with the procedures described in IEC/IEEE 62209-1528 and FCC KDB 846224,</p> <p>The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using a Dielectric Probe Kit and a Network Analyzer.</p> <p>The forward power was applied to the dipole and the system was verified to a tolerance of +10% from the system manufacturer's dipole calibration target SAR value.</p> <p>The forward power applied was same forward power applied by the calibration lab during the calibration of this validation source.</p>					

17.0 SYSTEM VALIDATION SUMMARY

Table 17.0 System Validation Summary

SAR Validation Summary Chart							
Validation Date	Validation Source	Source S/N	Validation Frequency	Tissue	Linearity	Isotropy	Extrapolation
3-May-22	D2450V2	825	2450	Head	✓	✓	✓

18.0 MEASUREMENT SYSTEM SPECIFICATIONS


Table 18.0 Measurement System Specifications

Measurement System Specification	
Specifications	
Positioner	Stäubli Unimation Corp. Robot Model: TX90XL
Repeatability	+/- 0.035 mm
No. of axis	6.0
Data Acquisition Electronic (DAE) System	
Cell Controller	
Processor	Intel(R) Core(TM) i7-7700
Clock Speed	3.60 GHz
Operating System	Windows 10 Professional
Data Converter	
Features	Signal Amplifier, multiplexer, A/D converter, and control logic
Software	Measurement Software: DASY6, V 6.4.0.12171 / DASY52 V10.2(1504)
	Postprocessing Software: SEMCAD X, V14.6.12(7470)
Connecting Lines	Optical downlink for data and status info., Optical uplink for commands and clock
DASY Measurement Server	
Function	Real-time data evaluation for field measurements and surface detection
Hardware	Intel ULV Celeron CPU 400 MHz; 128 MB chip disk; 128 MB RAM
Connections	COM1, COM2, DAE, Robot, Ethernet, Service Interface
E-Field Probe	
Model	EX3DV4
Serial No.	3600
Construction	Triangular core fiber optic detection system
Frequency	10 MHz to 6 GHz
Linearity	±0.2 dB (30 MHz to 3 GHz)
Phantom	
Type	MFP V5.1C Planar Phantom
Shell Material	Fiberglass
Thickness	2mm +/- .2mm
Volume	> 8 Liter


Table 18.1

Measurement System Specification (Continued)


Probe Specification

Construction:	Symmetrical design with triangular core; Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents (e.g. DGBE))	
Calibration:	ISO/IEC 17025	
Frequency:	4 MHz - 10 GHz; Linearity: ± 0.2 dB (30 MHz - 10 GHz)	
Directivity:	± 0.1 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range:	10 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB (noise: typically <1 mW/g)	
Dimensions:	Overall length: 337 mm; (tip: 20 mm) Tip diameter: 2.5 mm; Tip (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	
Application:	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better than 30%	EX3DV4 E-Field Probe


Phantom Specification

<p>The ELI V5.0 phantom is an elliptical planar fiberglass shell phantom with a shell thickness of 2.0mm +/- .2mm at the planar area. This phantom conforms to OET Bulletin 65, Supplement C, IEC\IEEE 62209-1528.</p>	
	ELI Phantom


Phantom Specification

<p>The SAM V4.0 phantom is a flat planar fiberglass shell phantom with a shell thickness of 2.0mm +/- .2mm at the planar area. This phantom conforms to OET Bulletin 65, Supplement C, IEC\IEEE 62209-1528.</p>	
	SAM Phantom

Phantom Specification

<p>The MFP V5.1C phantom is a flat planar fiberglass shell phantom with a shell thickness of 2.0mm +/- .2mm at the planar area. This phantom conforms to OET Bulletin 65, Supplement C, IEC\IEEE 62209-1528.</p>	
	MFP Phantom

Device Positioner Specification

<p>The DASY device positioner has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.</p>	
	Device Positioner

19.0 TEST EQUIPMENT LIST

Table 19.0 Equipment List and Calibration

Test Equipment List				
DESCRIPTION	ASSET NO.	SERIAL NO.	DATE CALIBRATED	CALIBRATION DUE
Schmid & Partner DASY 6 System	-	-	-	-
-DASY Measurement Server	00158	1078	CNR	CNR
-Robot	00046	599396-01	CNR	CNR
-DAE4	00019	353	14-Apr-22	14-Apr-23
-EX3DV4 E-Field Probe	00213	3600	20-Apr-22	20-Apr-23
-D2450V2 Validation Dipole	00219	825	24-Apr-21	24-Apr-24
MFP Phantom	00355	1177/2	CNR	CNR
HP 85070C Dielectric Probe Kit	00033	none	CNR	CNR
HP 8753ET Network Analyzer	00134	US39170292	6-Jan-21	6-Jan-24
Rohde & Schwarz SMR20 Signal Generator	00006	100104	11-Aug-20	11-Aug-23
Amplifier Research 10W1000C Power Amplifier	00041	27887	CNR	CNR
Amplifier Research 5S1G4 Power Amplifier	00106	26235	CNR	CNR
Narda Directional Coupler 3020A	00064	-	CNR	CNR
Kangaroo VWR Humidity/Thermometer	00334	192385455	5-Aug-19	5-Jan-23
Digital Multi Meter DMR-1800	00250	TE182	23-Jun-20	23-Jun-23
Bipolar Power Supply 6299A	00086	1144A02155	CNR	CNR
DC-18G 10W 30db Attenuator	00102	-	COU	COU
R&S FSP40 Spectrum Analyzer	00241	100500	9-Aug-21	9-Aug-24
HP 8566B Spectrum Analyzer	00051	2747A055100	29-Jun-20	29-Jun-23
RF Cable-SMA	00311	-	CNR	CNR
HP Calibration Kit	00145	-	CNR	CNR

CNR = Calibration Not Required

COU = Calibrate on Use

Note: Per KDB 865664, Dipoles are evaluated annually for return loss and impedance. The dipole's SAR target can only be assessed by the SAR equipment manufacturer and remains the target until the dipole is recalibrated by the manufacturer. The dipole's SAR is evaluated and compared to this target during each and every System Verification which is performed prior to and/or during each DUT SAR evaluation. The results of these verifications are shown in Section 16.0

20.0 FLUID COMPOSITION

Table 20.0 Fluid Composition 2450MHz HEAD TSL

Tissue Simulating Liquid (TSL) Composition				2450MHz Head
Component by Percent Weight				
Water	Glycol	Salt ⁽¹⁾	HEC ⁽²⁾	Bacteriacide ⁽³⁾
52.0	48.0	0.0	0.0	0.0

(1) Non-Iodinized

(2) HydroxyEthyl-Cellulose: Sigma-Aldrich P/N 54290-500g

(3) Dow Chemical Dowicil 75 Antimicrobial Perservative

END OF REPORT

APPENDIX A – SYSTEM VERIFICATION PLOTS

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN:825
Procedure Name: SPC 2450H_Input=250mw, Target=[11.86]13.18][14.50]W/kg 2

Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2450$ MHz; $\sigma = 1.87$ S/m; $\epsilon_r = 36.73$; $\rho = 1000$ kg/m³
Phantom section: Left Section

Date/Time: 3/26/2023 1:22:44 PM

DASY5 Configuration:

- Probe: EX3DV4 - SN3600; ConvF(6.58, 6.58, 6.58) @ 2450 MHz; Calibrated: 4/20/2022
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 4/14/2022
- Phantom: MFP_V5.1C (20deg probe tilt); Type: QD 000 P51 Cx; Serial: 00355
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

SPC/SPC 2450H_Input=250mw, Target=[11.86]13.18][14.50]W/kg 2/Area Scan (9x4x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 13.8 W/kg

SPC/SPC 2450H_Input=250mw, Target=[11.86]13.18][14.50]W/kg 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 92.44 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 31.5 W/kg

SAR(1 g) = 14.3 W/kg; SAR(10 g) = 6.49 W/kg

Smallest distance from peaks to all points 3 dB below = 10.8 mm



Ratio of SAR at M2 to SAR at M1 = 46.3%

Maximum value of SAR (measured) = 16.1 W/kg

SPC/SPC 2450H_Input=250mw, Target=[11.86]13.18][14.50]W/kg 2/Z Scan (1x1x22): Measurement grid: dx=20mm, dy=20mm, dz=5mm

Penetration depth = 6.729 (6.498, 6.864) [mm]

Maximum value of SAR (interpolated) = 26.9 W/kg



APPENDIX B – MEASUREMENT PLOTS OF MAXIMUM MEASURED SAR

Plot E22

DUT: A04431; Type: Extremity Worn Transmitter; Serial: Production Sample Prototype
Procedure Name: E22-A04431-00,Extremity-Back Side, 2462 MHz, WIFI, DSSS-1Mbps

Communication System: UID 0, CW (0); Frequency: 2462 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 1.912$ S/m; $\epsilon_r = 36.614$; $\rho = 1000$ kg/m³
Phantom section: Left Section

Date/Time: 3/26/2023 3:22:19 PM

DASY5 Configuration:

- Probe: EX3DV4 - SN3600; ConvF(6.58, 6.58, 6.58) @ 2462 MHz; Calibrated: 4/20/2022
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 4/14/2022
- Phantom: MFP_V5.1C (20deg probe tilt); Type: QD 000 P51 Cx; Serial: 00355
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

2450H A04431/E22-A04431-00,Extremity-Back Side, 2462 MHz, WIFI, DSSS-1Mbps/Area Scan (6x6x1): Measurement grid:
dx=12mm, dy=12mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.692 W/kg

2450H A04431/E22-A04431-00,Extremity-Back Side, 2462 MHz, WIFI, DSSS-1Mbps/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.56 V/m; Power Drift = -0.22 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.542 W/kg; SAR(10 g) = 0.238 W/kg

Smallest distance from peaks to all points 3 dB below = 7.1 mm

Ratio of SAR at M2 to SAR at M1 = 53.2%

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.639 W/kg


2450H A04431/E22-A04431-00,Extremity-Back Side, 2462 MHz, WIFI, DSSS-1Mbps/Z Scan (1x1x17): Measurement grid:

dx=20mm, dy=20mm, dz=20mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Penetration depth = n/a (n/a, 7.939) [mm]

Maximum value of SAR (interpolated) = 0.722 W/kg



Plot E30

DUT: A04431; Type: Extremity Worn Transmitter; Serial: Production Sample Prototype
Procedure Name: E30-A04431-00,Extremity-Back Side, 2480 MHz, BT BR (GFSK)

Communication System: UID 0, CW (0); Frequency: 2480 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2480$ MHz; $\sigma = 1.91$ S/m; $\epsilon_r = 36.54$; $\rho = 1000$ kg/m³
Phantom section: Left Section

Date/Time: 3/26/2023 4:28:06 PM

DASY5 Configuration:

- Probe: EX3DV4 - SN3600; ConvF(6.58, 6.58, 6.58) @ 2480 MHz; Calibrated: 4/20/2022
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 4/14/2022
- Phantom: MFP_V5.1C (20deg probe tilt); Type: QD 000 P51 Cx; Serial: 00355
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

2450H A04431/E30-A04431-00,Extremity-Back Side, 2480 MHz, BT BR (GFSK)/Area Scan (6x6x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 0.468 W/kg

2450H A04431/E30-A04431-00,Extremity-Back Side, 2480 MHz, BT BR (GFSK)/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 14.06 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.912 W/kg
SAR(1 g) = 0.460 W/kg; SAR(10 g) = 0.202 W/kg
Smallest distance from peaks to all points 3 dB below = 6.4 mm
Ratio of SAR at M2 to SAR at M1 = 52.6%
Maximum value of SAR (measured) = 0.525 W/kg

2450H A04431/E30-A04431-00,Extremity-Back Side, 2480 MHz, BT BR (GFSK)/Z Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=20mm
Penetration depth = n/a (n/a, 7.820) [mm]
Maximum value of SAR (interpolated) = 0.553 W/kg

