

FCC Test Report

FCC ID : IPH-04780
Equipment : IVI Unit
Model No. : TGWW
Brand Name : GARMIN
Applicant : Garmin International, Inc.
Address : 1200 E. 151st Street Olathe, KS 66062 United States
Standard : 47 CFR FCC Part 15.247
Received Date : Dec. 15, 2023
Tested Date : Dec. 18 ~ Dec. 29, 2023

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:



Along Chen / Assistant Manager



Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	8
1.3	Test Setup Chart	9
1.4	The Equipment List	10
1.5	Test Standards	11
1.6	Reference Guidance	11
1.7	Deviation from Test Standard and Measurement Procedure.....	11
1.8	Measurement Uncertainty	11
2	TEST CONFIGURATION.....	12
2.1	Testing Facility	12
2.2	The Worst Test Modes and Channel Details	13
3	TRANSMITTER TEST RESULTS	14
3.1	Unwanted Emissions into Restricted Frequency Bands	14
3.2	Unwanted Emissions into Non-Restricted Frequency Bands	17
3.3	Conducted Output Power	18
3.4	Number of Hopping Frequency	19
3.5	20dB and Occupied Bandwidth.....	20
3.6	Channel Separation.....	21
3.7	Number of Dwell Time.....	22
4	TEST LABORATORY INFORMATION	23

Appendix A. Unwanted Emissions into Restricted Frequency Bands

Appendix B. Unwanted Emissions into Non-Restricted Frequency Bands

Appendix C. Conducted Output Power

Appendix D. Number of Hopping Frequency

Appendix E. 20dB and Occupied Bandwidth

Appendix F. Channel Separation

Appendix G. Number of Dwell Time

Release Record

Report No.	Version	Description	Issued Date
FR3D1301AD	Rev. 01	Initial issue	Jan. 25, 2024

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emission	Note ¹	N/A
15.247(d) 15.209	Unwanted Emissions	[dBuV/m at 3m]: 41.95MHz 33.25 (Margin -6.75dB) - PK	Pass
15.247(d)	Band Edge	Meet the requirement of limit	Pass
15.247(b)(1)	Conducted Output Power	Power [dBm]: 1.08	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Meet the requirement of limit	Pass
15.247(a)(1)	Hopping Channel Separation	Meet the requirement of limit	Pass
15.247(a)(1)(iii)	Dwell Time	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

N/A means Not Applicable.
Note¹: The EUT consumes DC power from battery, so the test is not required.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	3 Mbps

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: Bluetooth BR uses a GFSK.
 Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.

1.1.2 Antenna Details

Ant. No.	Brand	Model	Type	Connector	Gain (dBi)
1	HARADA	39215	RHCP	R-SMA	0.3

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc
--------------------------	-------

1.1.4 Accessories

N/A

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

1.1.6 Test Tool and Duty Cycle

Test Tool	Bluetooth Simulator, Brand: R&S, Model: CMW270	
Modulation Mode	Duty Cycle Of Test Signal (%)	Duty Factor (dB)
DH5	77.99%	1.08
2DH5	78.16%	1.07
3DH5	78.85%	1.03

1.1.7 Power Index of Test Tool


Modulation Mode	Test Frequency (MHz)		
	2402	2441	2480
GFSK/1Mbps	Default	Default	Default
$\pi/4$ -DQPSK /2Mbps	Default	Default	Default
8DPSK/3Mbps	Default	Default	Default

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Card reader	TCSTAR	TYC-MF007	---	---
2	12V DC Battery	Hotai Motor Co, Ltd.	S55B24LS	---	---
3	Cell phone	SAMSUNG	A8	---	---
4	Speaker	GARMIN	TG SPK	---	Provided by applicant.
5	Fixture Board	GARMIN	TG_FB	---	Provided by applicant.
6	Laptop	DELL	Latitude E5470	DoC	---

Note: The fixture board and laptop are disconnected from EUT and removed from test table when EUT is set to transmit continuously.

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Dec. 18 ~ Dec. 25, 2023				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Mar. 03, 2023	Mar. 02, 2024
Spectrum Analyzer	R&S	FSV40	101498	Nov. 23, 2023	Nov. 22, 2024
Loop Antenna	R&S	HFH2-Z2	100330	Oct. 31, 2023	Oct. 30, 2024
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 31, 2023	Jul. 30, 2024
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Nov. 27, 2023	Nov. 26, 2024
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 30, 2023	Oct. 29, 2024
Preamplifier	EMC	EMC02325	980225	Jun. 28, 2023	Jun. 27, 2024
Preamplifier	EMC	EMC118A45SE	980898	Jul. 14, 2023	Jul. 13, 2024
Preamplifier	EMC	EMC184045SE	980903	Jul. 17, 2023	Jul. 16, 2024
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 03, 2023	Oct. 02, 2024
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 03, 2023	Oct. 02, 2024
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 03, 2023	Oct. 02, 2024
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 03, 2023	Oct. 02, 2024
RF Cable	EMC	EMC104-35M-35M- 8000	210920	Oct. 03, 2023	Oct. 02, 2024
RF Cable	EMC	EMC104-35M-35M- 3000	210922	Oct. 03, 2023	Oct. 02, 2024
Attenuator	Pasternack	PE7005-10	10-1	Oct. 05, 2023	Oct. 04, 2024
HIGHPASS FILTER 3.1-18G	WHK	WHK3.1/18G-10SS	39	Oct. 05, 2023	Oct. 04, 2024
Measurement Software	Sporton	SENSE-15247_FS	V5.10.8	NA	NA
Measurement Software	Sporton	SENSE-EMI	V5.10.8	NA	NA
Wireless connectivity tester	R&S	CMW270	100856	Nov. 14, 2023	Nov. 13, 2024

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Dec. 29, 2023				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101910	Apr. 14, 2023	Apr. 13, 2024
Power Meter	Anritsu	ML2495A	1241002	Nov. 21, 2023	Nov. 20, 2024
Power Sensor	Anritsu	MA2411B	1207366	Nov. 21, 2023	Nov. 20, 2024
Attenuator	Pasternack	PE7005-10	10-2	Oct. 05, 2023	Oct. 04, 2024
Measurement Software	Sporton	SENSE-15247_FS	V5.10.8	NA	NA
Wireless connectivity tester	R&S	CMW270	100856	Nov. 14, 2023	Nov. 13, 2024
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

47 CFR FCC Part 15.247
ANSI C63.10-2013

1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.7 Deviation from Test Standard and Measurement Procedure

None

1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.130 Hz
Conducted power	± 0.808 dB
Power density	± 0.583 dB
Conducted emission	± 2.715 dB
AC conducted emission	± 2.92 dB
Radiated emission ≤ 1 GHz	± 3.41 dB
Radiated emission > 1 GHz	± 4.59 dB
Time	$\pm 0.1\%$

2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	03CH01-WS, TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps)
Radiated Emissions \leq 1GHz	GFSK	2480	1Mbps
Radiated Emissions $>$ 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps
Conducted Output Power	GFSK $\pi/4$ DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps
Number of Hopping Channels	GFSK $\pi/4$ DQPSK 8DPSK	2402~2480 2402~2480 2402~2480	1Mbps 2Mbps 3Mbps
Hopping Channel Separation 20dB and Occupied bandwidth	GFSK $\pi/4$ DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps
Dwell Time	GFSK $\pi/4$ DQPSK 8DPSK	2402 2402 2402	1Mbps 2Mbps 3Mbps
NOTE:			
1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The Z-plane results were found as the worst case and were shown in this report.			

3 Transmitter Test Results

3.1 Unwanted Emissions into Restricted Frequency Bands

3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. Radiated emission above 1GHz / Peak value
RBW=1MHz, VBW=3MHz and Peak detector
Radiated emission above 1GHz / Average value for harmonics
The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:
3.
$$20\log(\text{Duty cycle}) = 20\log \frac{1\text{s} / 1600 * 5}{100\text{ ms}} = -30.1\text{dB}$$
4. Radiated emission above 1GHz / Average value for other emissions
RBW=1MHz, VBW=1/T and Peak detector

3.1.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.1.4 Test Results

Refer to Appendix A.

3.2 Unwanted Emissions into Non-Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.2.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.2.3 Test Setup



3.2.4 Test Results

Ambient Condition	22°C / 63%	Tested By	Roger Lu
--------------------------	------------	------------------	----------

Refer to Appendix B.

3.3 Conducted Output Power

3.3.1 Limit of Conducted Output Power

- 1 Watt
For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
- 0.125 Watt
For all other frequency hopping systems in the 2400–2483.5 MHz band.
- 0.125 Watt
For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.3.2 Test Procedures

1. A wideband power meter is used for power measurement. Bandwidth of power sensor and meter is 50MHz
2. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.3.3 Test Setup



3.3.4 Test Results

Ambient Condition	22°C / 63%	Tested By	Roger Lu
--------------------------	------------	------------------	----------

Refer to Appendix C.

3.4 Number of Hopping Frequency


3.4.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.4.2 Test Procedures

1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
2. Allow trace to stabilize.

3.4.3 Test Setup



3.4.4 Test Results

Ambient Condition	22°C / 63%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix D.

3.5 20dB and Occupied Bandwidth

3.5.1 Test Procedures


20dB Bandwidth

1. Set RBW=20kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak , Trace max hold
2. Allow trace to stabilize
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set RBW=20kHz, VBW=100kHz, Sweep time = Auto, Detector=Sample , Trace max hold
2. Allow trace to stabilize
3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.5.2 Test Setup



3.5.3 Test Results

Ambient Condition	22°C / 63%	Tested By	Roger Lu
--------------------------	------------	------------------	----------

Refer to Appendix E.

3.6 Channel Separation


3.6.1 Limit of Channel Separation

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.6.2 Test Procedures

1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak Trace max hold
2. Allow trace to stabilize
3. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.6.3 Test Setup



3.6.4 Test Results

Ambient Condition	22°C / 63%	Tested By	Roger Lu
--------------------------	------------	------------------	----------

Refer to Appendix F.

3.7 Number of Dwell Time


3.7.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.7.2 Test Procedures

1. Set RBW=300 kHz, VBW=1 MHz, Sweep time=8 ms, Detector=Peak, Span=0 Hz, Trace max hold.
2. Enable gating and trigger function of spectrum analyzer to measure burst on time.
3. Set RBW=300 kHz, VBW=1 MHz, Sweep time=5 s / 2 s, Detector=Peak, Span=0 Hz, Trace max hold.
4. Enable gating and trigger function of spectrum analyzer to measure burst on number of transmission.
5. Set RBW=300 kHz, VBW=1 MHz, Sweep time=31.6 s / 8 s, Detector=Peak, Span=0 Hz, Trace max hold.
6. Enable gating and trigger function of spectrum analyzer to measure burst on number of transmission of entire time cycle.

3.7.3 Test Setup



3.7.4 Test Results

Ambient Condition	22°C / 63%	Tested By	Roger Lu
--------------------------	------------	------------------	----------

Refer to Appendix G.

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==




Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 1	Pass	PK	41.95M	33.25	40.00	-6.75	Vertical




Mode 1



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	35.18M	31.86	40.00	-8.14	-9.48	3	Vertical	-	-	-	41.34	17.98	0.54	28.00
PK	41.95M	33.25	40.00	-6.75	-8.47	3	Vertical	-	-	-	41.72	18.98	0.59	28.04
PK	92.27M	31.83	43.50	-11.67	-14.25	3	Vertical	-	-	-	46.08	13.18	0.90	28.33
PK	217.15M	27.29	46.00	-18.71	-11.92	3	Vertical	-	-	-	39.21	15.14	1.38	28.44
PK	319.24M	28.16	46.00	-17.84	-7.43	3	Vertical	-	-	-	35.59	19.28	1.69	28.40
PK	505.18M	30.72	46.00	-15.28	-2.86	3	Vertical	-	-	-	33.58	23.20	2.18	28.24



Mode 1



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	91.14M	34.28	43.50	-9.22	-14.42	3	Horizontal	-	-	-	48.70	13.01	0.90	28.33
PK	165.48M	30.19	43.50	-13.31	-9.02	3	Horizontal	-	-	-	39.21	18.20	1.20	28.42
PK	188.14M	29.14	43.50	-14.36	-11.07	3	Horizontal	-	-	-	40.21	16.07	1.29	28.43
PK	217.35M	28.64	46.00	-17.36	-11.91	3	Horizontal	-	-	-	40.55	15.15	1.38	28.44
PK	254.12M	29.83	46.00	-16.17	-9.86	3	Horizontal	-	-	-	39.69	17.08	1.49	28.43
PK	264.18M	29.31	46.00	-16.69	-9.33	3	Horizontal	-	-	-	38.64	17.57	1.53	28.43




Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
BT-BR(1Mbps)	Pass	AV	2.39G	36.71	54.00	-17.29	3	Vertical	18	2.31	-
BT-EDR(3Mbps)	Pass	AV	2.4835G	36.77	54.00	-17.23	3	Horizontal	333	1.19	-



2.4-2.4835GHz_BT-BR(1Mbps)

2402MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	49.72	74.00	-24.28	54.10	3	Vertical	18	2.31	-	27.60	4.95	36.93
AV	2.39G	36.71	54.00	-17.29	41.09	3	Vertical	18	2.31	-	27.60	4.95	36.93
PK	4.804G	48.18	74.00	-25.82	48.56	3	Vertical	136	1.00	-	31.29	6.85	38.52
AV	4.804G	18.08	54.00	-35.92	-	3	Vertical	136	1.00	-	-	-	-
PK	12.01G	55.34	74.00	-18.66	49.07	3	Vertical	45	1.00	-	39.20	10.02	42.95
AV	12.01G	25.24	54.00	-28.76	-	3	Vertical	45	1.00	-	-	-	-



2.4-2.4835GHz_BT-BR(1Mbps)

2402MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	50.36	74.00	-23.64	54.74	3	Horizontal	323	1.93	-	27.60	4.95	36.93
AV	2.39G	36.56	54.00	-17.44	40.94	3	Horizontal	323	1.93	-	27.60	4.95	36.93
PK	4.804G	46.42	74.00	-27.58	46.80	3	Horizontal	26	1.00	-	31.29	6.85	38.52
AV	4.804G	16.32	54.00	-37.68	-	3	Horizontal	26	1.00	-	-	-	-
PK	12.01G	55.43	74.00	-18.57	49.16	3	Horizontal	22	1.00	-	39.20	10.02	42.95
AV	12.01G	25.33	54.00	-28.67	-	3	Horizontal	22	1.00	-	-	-	-



2.4-2.4835GHz_BT-BR(1Mbps)

2441MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	49.68	74.00	-24.32	54.06	3	Vertical	17	2.36	-	27.60	4.95	36.93
AV	2.39G	36.49	54.00	-17.51	40.87	3	Vertical	17	2.36	-	27.60	4.95	36.93
PK	2.4835G	49.67	74.00	-24.33	54.42	3	Vertical	17	2.36	-	27.20	5.06	37.01
AV	2.4835G	36.35	54.00	-17.65	41.10	3	Vertical	17	2.36	-	27.20	5.06	37.01
PK	4.882G	48.31	74.00	-25.69	48.82	3	Vertical	148	1.00	-	31.14	6.92	38.57
AV	4.882G	18.21	54.00	-35.79	-	3	Vertical	148	1.00	-	-	-	-
PK	7.323G	52.37	74.00	-21.63	47.25	3	Vertical	155	1.00	-	36.15	8.43	39.46
AV	7.323G	22.27	54.00	-31.73	-	3	Vertical	155	1.00	-	-	-	-



2.4-2.4835GHz_BT-BR(1Mbps)

2441MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	50.35	74.00	-23.65	54.73	3	Horizontal	331	1.31	-	27.60	4.95	36.93
AV	2.39G	36.45	54.00	-17.55	40.83	3	Horizontal	331	1.31	-	27.60	4.95	36.93
PK	2.4835G	49.94	74.00	-24.06	54.69	3	Horizontal	331	1.31	-	27.20	5.06	37.01
AV	2.4835G	36.59	54.00	-17.41	41.34	3	Horizontal	331	1.31	-	27.20	5.06	37.01
PK	4.882G	46.27	74.00	-27.73	46.78	3	Horizontal	21	1.00	-	31.14	6.92	38.57
AV	4.882G	16.17	54.00	-37.83	-	3	Horizontal	21	1.00	-	-	-	-
PK	7.323G	49.70	74.00	-24.30	44.58	3	Horizontal	191	1.00	-	36.15	8.43	39.46
AV	7.323G	19.60	54.00	-34.40	-	3	Horizontal	191	1.00	-	-	-	-



2.4-2.4835GHz_BT-BR(1Mbps)

2480MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4835G	49.47	74.00	-24.53	54.22	3	Vertical	12	2.33	-	27.20	5.06	37.01
AV	2.4835G	36.53	54.00	-17.47	41.28	3	Vertical	12	2.33	-	27.20	5.06	37.01
PK	4.96G	48.74	74.00	-25.26	49.01	3	Vertical	141	1.00	-	31.36	6.99	38.62
AV	4.96G	18.64	54.00	-35.36	-	3	Vertical	141	1.00	-	-	-	-
PK	7.44G	52.51	74.00	-21.49	47.28	3	Vertical	152	1.00	-	36.34	8.50	39.61
AV	7.44G	22.41	54.00	-31.59	-	3	Vertical	152	1.00	-	-	-	-



2.4-2.4835GHz_BT-BR(1Mbps)

2480MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4835G	49.81	74.00	-24.19	54.56	3	Horizontal	330	1.20	-	27.20	5.06	37.01
AV	2.4835G	36.29	54.00	-17.71	41.04	3	Horizontal	330	1.20	-	27.20	5.06	37.01
PK	4.96G	46.75	74.00	-27.25	47.02	3	Horizontal	24	1.00	-	31.36	6.99	38.62
AV	4.96G	16.65	54.00	-37.35	-	3	Horizontal	24	1.00	-	-	-	-
PK	7.44G	49.98	74.00	-24.02	44.75	3	Horizontal	186	1.00	-	36.34	8.50	39.61
AV	7.44G	19.88	54.00	-34.12	-	3	Horizontal	186	1.00	-	-	-	-



2.4-2.4835GHz_BT-EDR(3Mbps)

2402MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	50.03	74.00	-23.97	54.41	3	Vertical	22	2.25	-	27.60	4.95	36.93
AV	2.39G	36.60	54.00	-17.40	40.98	3	Vertical	22	2.25	-	27.60	4.95	36.93
PK	4.804G	48.09	74.00	-25.91	48.47	3	Vertical	131	1.00	-	31.29	6.85	38.52
AV	4.804G	17.99	54.00	-36.01	-	3	Vertical	131	1.00	-	-	-	-
PK	12.01G	55.21	74.00	-18.79	48.94	3	Vertical	39	1.00	-	39.20	10.02	42.95
AV	12.01G	25.11	54.00	-28.89	-	3	Vertical	39	1.00	-	-	-	-



2.4-2.4835GHz_BT-EDR(3Mbps)

2402MHz_TX



Legend:

- Lim.PK (Red dashed line)
- PK (Blue solid line)
- Lim.AV (Red dashed line)
- AV (Blue solid line)


18/12/2023

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	49.70	74.00	-24.30	54.08	3	Horizontal	327	1.21	-	27.60	4.95	36.93
AV	2.39G	36.49	54.00	-17.51	40.87	3	Horizontal	327	1.21	-	27.60	4.95	36.93
PK	4.804G	46.47	74.00	-27.53	46.85	3	Horizontal	25	1.00	-	31.29	6.85	38.52
AV	4.804G	16.37	54.00	-37.63	-	3	Horizontal	25	1.00	-	-	-	-
PK	12.01G	55.37	74.00	-18.63	49.10	3	Horizontal	18	1.00	-	39.20	10.02	42.95
AV	12.01G	25.27	54.00	-28.73	-	3	Horizontal	18	1.00	-	-	-	-



2.4-2.4835GHz_BT-EDR(3Mbps)

2441MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	50.08	74.00	-23.92	54.46	3	Vertical	15	2.31	-	27.60	4.95	36.93
AV	2.39G	36.50	54.00	-17.50	40.88	3	Vertical	15	2.31	-	27.60	4.95	36.93
PK	2.4835G	49.24	74.00	-24.76	53.99	3	Vertical	15	2.31	-	27.20	5.06	37.01
AV	2.4835G	36.57	54.00	-17.43	41.32	3	Vertical	15	2.31	-	27.20	5.06	37.01
PK	4.882G	48.36	74.00	-25.64	48.87	3	Vertical	142	1.00	-	31.14	6.92	38.57
AV	4.882G	18.26	54.00	-35.74	-	3	Vertical	142	1.00	-	-	-	-
PK	7.323G	52.27	74.00	-21.73	47.15	3	Vertical	153	1.00	-	36.15	8.43	39.46
AV	7.323G	22.17	54.00	-31.83	-	3	Vertical	153	1.00	-	-	-	-



2.4-2.4835GHz_BT-EDR(3Mbps)

2441MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	50.30	74.00	-23.70	54.68	3	Horizontal	330	1.33	-	27.60	4.95	36.93
AV	2.39G	36.59	54.00	-17.41	40.97	3	Horizontal	330	1.33	-	27.60	4.95	36.93
PK	2.4835G	49.41	74.00	-24.59	54.16	3	Horizontal	330	1.33	-	27.20	5.06	37.01
AV	2.4835G	36.59	54.00	-17.41	41.34	3	Horizontal	330	1.33	-	27.20	5.06	37.01
PK	4.882G	46.40	74.00	-27.60	46.91	3	Horizontal	25	1.00	-	31.14	6.92	38.57
AV	4.882G	16.30	54.00	-37.70	-	3	Horizontal	25	1.00	-	-	-	-
PK	7.323G	49.81	74.00	-24.19	44.69	3	Horizontal	186	1.00	-	36.15	8.43	39.46
AV	7.323G	19.71	54.00	-34.29	-	3	Horizontal	186	1.00	-	-	-	-



2.4-2.4835GHz_BT-EDR(3Mbps)

2480MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4835G	49.96	74.00	-24.04	54.71	3	Vertical	14	2.26	-	27.20	5.06	37.01
AV	2.4835G	36.47	54.00	-17.53	41.22	3	Vertical	14	2.26	-	27.20	5.06	37.01
PK	4.96G	48.80	74.00	-25.20	49.07	3	Vertical	138	1.00	-	31.36	6.99	38.62
AV	4.96G	18.70	54.00	-35.30	-	3	Vertical	138	1.00	-	-	-	-
PK	7.44G	52.61	74.00	-21.39	47.38	3	Vertical	146	1.00	-	36.34	8.50	39.61
AV	7.44G	22.51	54.00	-31.49	-	3	Vertical	146	1.00	-	-	-	-







2.4-2.4835GHz_BT-EDR(3Mbps)



2480MHz_TX






Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4835G	50.46	74.00	-23.54	55.21	3	Horizontal	333	1.19	-	27.20	5.06	37.01
AV	2.4835G	36.77	54.00	-17.23	41.52	3	Horizontal	333	1.19	-	27.20	5.06	37.01
PK	4.96G	46.61	74.00	-27.39	46.88	3	Horizontal	25	1.00	-	31.36	6.99	38.62
AV	4.96G	16.51	54.00	-37.49	-	3	Horizontal	25	1.00	-	-	-	-
PK	7.44G	49.92	74.00	-24.08	44.69	3	Horizontal	164	1.00	-	36.34	8.50	39.61
AV	7.44G	19.82	54.00	-34.18	-	3	Horizontal	164	1.00	-	-	-	-












2.4-2.4835GHz_BT-BR(1Mbps)

2402MHz


Hopping Ch Bandedge (Non-restricted Band)



2.4-2.4835GHz_BT-EDR(2Mbps)

2402MHz


Hopping Ch Bandedge (Non-restricted Band)



2.4-2.4835GHz_BT-EDR(3Mbps)

2402MHz

Hopping Ch Bandedge (Non-restricted Band)



Limit(dBm)	Ref(Hz)	Ref(dBm)	BE-l(Hz)	BE-l(dBm)	BE-h(Hz)	BE-h(dBm)
-22.06	2.46901G	-2.06	2.39791G	-47.05	2.48383G	-50.86



Summary

Mode	Total Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1.08	0.00128
BT-EDR(2Mbps)	-0.03	0.00099
BT-EDR(3Mbps)	0.24	0.00106

Result

Mode	Result	Antenna Gain (dBi)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
BT-BR(1Mbps)	-	-	-	-	-	-
2402MHz	Pass	0.30	-0.21	21.00	0.09	27.00
2441MHz	Pass	0.30	0.64	21.00	0.94	27.00
2480MHz	Pass	0.30	1.08	21.00	1.38	27.00
BT-EDR(2Mbps)	-	-	-	-	-	-
2402MHz	Pass	0.30	-1.32	21.00	-1.02	27.00
2441MHz	Pass	0.30	-0.44	21.00	-0.14	27.00
2480MHz	Pass	0.30	-0.03	21.00	0.27	27.00
BT-EDR(3Mbps)	-	-	-	-	-	-
2402MHz	Pass	0.30	-0.97	21.00	-0.67	27.00
2441MHz	Pass	0.30	-0.12	21.00	0.18	27.00
2480MHz	Pass	0.30	0.24	21.00	0.54	27.00

DG = Directional Gain; Port X = Port X output power



Summary

Mode	Total Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	0.81	0.00121
BT-EDR(2Mbps)	-2.68	0.00054
BT-EDR(3Mbps)	-2.65	0.00054

Result

Mode	Result	Antenna Gain (dBi)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
BT-BR(1Mbps)	-	-	-	-	-	-
2402MHz	Pass	0.30	-0.59	-	-0.29	-
2441MHz	Pass	0.30	0.37	-	0.67	-
2480MHz	Pass	0.30	0.81	-	1.11	-
BT-EDR(2Mbps)	-	-	-	-	-	-
2402MHz	Pass	0.30	-4.07	-	-3.77	-
2441MHz	Pass	0.30	-3.14	-	-2.84	-
2480MHz	Pass	0.30	-2.68	-	-2.38	-
BT-EDR(3Mbps)	-	-	-	-	-	-
2402MHz	Pass	0.30	-4.06	-	-3.76	-
2441MHz	Pass	0.30	-3.13	-	-2.83	-
2480MHz	Pass	0.30	-2.65	-	-2.35	-

Note: Average power is for reference only



Summary

Mode	Max-Hop No
2.4-2.4835GHz	-
BT-BR(1Mbps)	79
BT-EDR(2Mbps)	79
BT-EDR(3Mbps)	79

Result


Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2402MHz	Pass	79	15
BT-EDR(2Mbps)	-	-	-
2402MHz	Pass	79	15
BT-EDR(3Mbps)	-	-	-
2402MHz	Pass	79	15



2.4-2.4835GHz_BT-BR(1Mbps)

Hopping-FS

2402MHz




Hopping No	Limit
79	15

2.4-2.4835GHz_BT-EDR(2Mbps)

Hopping-FS

2402MHz




Hopping No	Limit
79	15



2.4-2.4835GHz_BT-EDR(3Mbps)

Hopping-FS

2402MHz



Hopping No	Limit
79	15



Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-BR(1Mbps)	1.383M	936.149k	936KF1D	1.152M	910.409k
BT-EDR(2Mbps)	1.315M	1.193M	1M19G1D	1.293M	1.178M
BT-EDR(3Mbps)	1.301M	1.199M	1M20G1D	1.301M	1.183M

Max-N dB = Maximum 20dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 20dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.152M	919.283k
2441MHz	Pass	Inf	1.383M	936.149k
2480MHz	Pass	Inf	1.188M	910.409k
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.293M	1.19M
2441MHz	Pass	Inf	1.309M	1.178M
2480MHz	Pass	Inf	1.315M	1.193M
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.301M	1.183M
2441MHz	Pass	Inf	1.301M	1.199M
2480MHz	Pass	Inf	1.301M	1.194M



Port X-N dB = Port X 20dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth



2.4-2.4835GHz_BT-BR(1Mbps)

EBW-FS



2402MHz



2.4-2.4835GHz_BT-BR(1Mbps)

EBW-FS

2441MHz







2.4-2.4835GHz_BT-BR(1Mbps)

EBW-FS

2480MHz




20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.188M	2.479453G	2.480641G	910.409k	2.479546G	2.480456G	Inf	1

2.4-2.4835GHz_BT-EDR(2Mbps)

EBW-FS

2402MHz





20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.293M	2.401357G	2.402649G	1.19M	2.401398G	2.402588G	Inf	1



2.4-2.4835GHz_BT-EDR(2Mbps)

EBW-FS



2441MHz



2.4-2.4835GHz_BT-EDR(2Mbps)

EBW-FS



2480MHz



2.4-2.4835GHz_BT-EDR(3Mbps)

EBW-FS



2402MHz



2.4-2.4835GHz_BT-EDR(3Mbps)

EBW-FS

2441MHz







2.4-2.4835GHz_BT-EDR(3Mbps)

EBW-FS

2480MHz





Summary

Mode	Max-Space (Hz)	Min-Space (Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1.002M	1.0005M
BT-EDR(2Mbps)	1.002M	1.0005M
BT-EDR(3Mbps)	1.005M	1.0005M

Result

Mode	Result	Fl (Hz)	Fh (Hz)	Ch.Space (Hz)	Limit (Hz)
BT-BR(1Mbps)	-	-	-	-	-
2402MHz	Pass	2.40198G	2.40298G	1.0005M	767.232k
2441MHz	Pass	2.440968G	2.441968G	1.0005M	921.078k
2480MHz	Pass	2.478968G	2.47997G	1.002M	791.208k
BT-EDR(2Mbps)	-	-	-	-	-
2402MHz	Pass	2.40198G	2.402982G	1.002M	861.138k
2441MHz	Pass	2.44098G	2.44198G	1.0005M	871.794k
2480MHz	Pass	2.478981G	2.479982G	1.0005M	875.79k
BT-EDR(3Mbps)	-	-	-	-	-
2402MHz	Pass	2.40198G	2.40298G	1.0005M	866.466k
2441MHz	Pass	2.440978G	2.44198G	1.002M	866.466k
2480MHz	Pass	2.478977G	2.479982G	1.005M	866.466k

2.4-2.4835GHz_BT-BR(1Mbps)

Channel Separation-FS

2.402G/2.403GHz



2.4-2.4835GHz_BT-BR(1Mbps)

Channel Separation-FS

2.441G/2.442GHz



2.4-2.4835GHz_BT-BR(1Mbps)

Channel Separation-FS

2.48G/2.479GHz




Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478968G	2.47997G	1.002M	791.208k

2.4-2.4835GHz_BT-EDR(2Mbps)

Channel Separation-FS

2.402G/2.403GHz




Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.40198G	2.402982G	1.002M	861.138k

2.4-2.4835GHz_BT-EDR(2Mbps)

Channel Separation-FS

2.441G/2.442GHz




F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.44098G	2.44198G	1.0005M	871.794k

2.4-2.4835GHz_BT-EDR(2Mbps)

Channel Separation-FS

2.48G/2.479GHz




F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478981G	2.479982G	1.0005M	875.79k

2.4-2.4835GHz_BT-EDR(3Mbps)

Channel Separation-FS

2.402G/2.403GHz




F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.40198G	2.40298G	1.0005M	866.466k

2.4-2.4835GHz_BT-EDR(3Mbps)

Channel Separation-FS

2.441G/2.442GHz



F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.440978G	2.44198G	1.002M	866.466k



2.4-2.4835GHz_BT-EDR(3Mbps)

Channel Separation-FS

2.48G/2.479GHz



F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478977G	2.479982G	1.005M	866.466k



Summary

Mode	Max-Dwell (s)
2.4-2.4835GHz	-
BT-BR(1Mbps)	311.1731m_DH5
BT-BR-AFH(1Mbps)	312.606m_DH5-AFH
BT-EDR(2Mbps)	329.7618m_DH5
BT-EDR-AFH(2Mbps)	313.173m_DH5-AFH
BT-EDR(3Mbps)	330.27372m_DH5
BT-EDR-AFH(3Mbps)	290.425m_DH5-AFH

Result/ Non AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (ms)	Number of transmission in a 5 s
BT-BR(1Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	31.6	0.31117	0.4	2.89625	17
BT-EDR(2Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	31.6	0.32976	0.4	2.89875	18
BT-EDR(3Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	31.6	0.33027	0.4	2.90325	18

Note 1: Dwell time =Number of transmission in a 5 second x Tx On Time x 6.32



Note 2: DH5 was the worst mode.



Result/ AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (ms)	Number of transmission in a 2 s
BT-BR-AFH(1Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	8	0.31261	0.4	2.89450	27
BT-EDR-AFH(2Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	8	0.31317	0.4	2.89975	27
BT-EDR-AFH(3Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	8	0.29043	0.4	2.90425	25

Note 1: Dwell time =Number of transmission in a 2 second x Tx On Time x 4

Note 2: DH5 was the worst mode.








2.4-2.4835GHz_BT-EDR-AFH(2Mbps)

Dwell-FS

2402MHz



2.4-2.4835GHz_BT-EDR-AFH(3Mbps)

Dwell-FS

2402MHz

