

FCC/ISED Test Report

Prepared for: Garmin International, Inc.

Address: 1200 E. 151st Street
Olathe, Kansas, 66062, USA

Product: C04112

Test Report No: R20220122-21-E1

Approved by:



Mahendra Karthik Vepuri, NCE
EMC Test Engineer,
iNARTE Certified EMC Engineer #EMC-041453-E

DATE: June 6, 2022

Total Pages: 38

The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above-named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

REVISION PAGE

| Rev. No. | Date | Description |
|----------|-------------|-----------------------------------------------------------|
| 0 | 6 June 2022 | Original - KVepuri Prepared by FLane, GLarsen, KVepuri |



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

CONTENTS

Revision Page 2

1.0 Summary of test results 4

2.0 EUT Description 5

2.1 Equipment under test 5

2.2 Description of test modes 5

2.3 Description of support units 5

3.0 Laboratory and General Test Description 6

3.1 Laboratory description 6

3.2 Test personnel 6

3.3 Test equipment 7

3.4 General Test Procedure and Setup for Radio Measurements 8

4.0 Results 9

4.1 Output Power 10

4.2 Duty Cycle 11

4.3 Radiated emissions 12


4.4 Band edges 19

Appendix A: Sample Calculation 20

Appendix B – Measurement Uncertainty 22

Appendix C – Graphs and Tables 23

REPORT END 38

| | | | | |
|----------------------------------------------------------------------------------|----------------|----------------------------|-----|---|
|  | Report Number: | R20220122-21-E1 | Rev | 0 |
| | Prepared for: | Garmin International, Inc. | | |

1.0 SUMMARY OF TEST RESULTS

The intention of this report is to determine, if the EUT can be qualified as Class II permissive change (FCC ID: IPH-A04112). The manufacturer made modifications to the EUT that qualify for a C2PC. Manufacturer has declared that the changes would not change conducted measurements. So, only the measurements that would be affected due to these changes are investigated in this report. The measurements that can be done in conducted manner are ignored as they won't be affected due to these changes. The worst-case measurements were reported in this report. Summary of test results presented in this report correspond to the following section(s):

FCC Part 15.247 ☒

The EUT has been tested according to the following specifications:

- (1) US Code of Federal Regulations, Title 47, Part 15
- (2) ISED RSS-Gen, Issue 5
- (3) ISED RSS-247, Issue 2

| APPLIED STANDARDS AND REGULATIONS | | |
|------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------|
| Standard Section | Test Type | Result |
| FCC Part 15.35 RSS Gen, Issue 5, Section 6.10 | Duty Cycle | Pass |
| FCC Part 15.247(b)(3) RSS-247 Issue 2 Section 5.4(d) | Peak output power | Pass |
| FCC Part 15.209 RSS-Gen Issue 5, Section 7.3 | Receiver Radiated Emissions | Pass |
| FCC Part 15.209 (restricted bands), 15.247 (unrestricted) RSS-247 Issue 2 Section 5.5, RSS-Gen Issue 5, Section 8.9 | Transmitter Radiated Emissions | Pass |
| FCC Part 15.209, 15.247(d) RSS-247 Issue 2 Section 5.5 | Band Edge Measurement | Pass |



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

2.0 EUT DESCRIPTION

2.1 EQUIPMENT UNDER TEST

Summary and Operating Condition:

| | |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EUT | C04112 |
| EUT Received | 25 February 2022 |
| EUT Tested | 1 March 2022- 26 May 2022 |
| Serial No. | 3400415111 (Conducted Unit) 3412218493 (Radiated Unit) |
| Operating Band | 2400 – 2483.5 MHz |
| Device Type | <input checked="" type="checkbox"/> GMSK <input checked="" type="checkbox"/> GFSK <input type="checkbox"/> BT BR <input type="checkbox"/> BT EDR 2MB <input type="checkbox"/> BT EDR 3MB <input type="checkbox"/> 802.11x |
| Power Supply / Voltage | Internal Battery/ 5VDC Charger: Garmin (Phi Hong) MN: PSAI10R-050Q (Representative Power Supply) |

NOTE: For more detailed features description, please refer to the manufacturer's specifications or user's manual.

This report is a class II permissive change;
see FCCID: IPH-A04112

2.2 DESCRIPTION OF TEST MODES

The operating range of the EUT is dependent on the device type found in section 2.1:

For GFSK and GMSK 1MB Transmissions:

| Channel | Frequency |
|---------|-----------|
| Low | 2402 MHz |
| Mid | 2440 MHz |
| High | 2480 MHz |

For GMSK 2MB Transmissions:

| Channel | Frequency |
|---------|-----------|
| Low | 2404 MHz |
| Mid | 2440 MHz |
| High | 2478 MHz |

These are the only representative channels tested in the frequency range according to FCC Part 15.31 and RSS-Gen Table A1. See the operational description for a list of all channel frequency and designations.

2.3 DESCRIPTION OF SUPPORT UNITS

None

3.0 LABORATORY AND GENERAL TEST DESCRIPTION

3.1 LABORATORY DESCRIPTION

All testing was performed at the following Facility:

The Nebraska Center for Excellence in Electronics (NCEE Labs)
 4740 Discovery Drive
 Lincoln, NE 68521

| | |
|--------------------------------------------|---------|
| A2LA Certificate Number: | 1953.01 |
| FCC Accredited Test Site Designation No: | US1060 |
| Industry Canada Test Site Registration No: | 4294A-1 |
| NCC CAB Identification No: | US0177 |

Environmental conditions varied slightly throughout the tests:

Relative humidity of 35 ± 4%
 Temperature of 22 ± 3° Celsius



3.2 TEST PERSONNEL

| No. | PERSONNEL | TITLE | ROLE |
|-----|----------------|-------------------|--------------------|
| 1 | Nic Johnson | Technical Manager | Review/editing |
| 2 | Fox Lane | Test Engineer | Testing and report |
| 3 | Karthik Vepuri | Test Engineer | Testing and report |
| 4 | Blake Winter | Test Engineer | Testing |
| 5 | Grace Larsen | Test Engineer | Testing and report |

Notes:

All personnel are permanent staff members of NCEE Labs. No testing or review was sub-contracted or performed by sub-contracted personnel.



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

3.3 TEST EQUIPMENT

| DESCRIPTION AND MANUFACTURER | MODEL NO. | SERIAL NO. | LAST CALIBRATION DATE | CALIBRATION DUE DATE |
|-----------------------------------------------------------|------------|------------|-----------------------|----------------------|
| Keysight MXE Signal Analyzer (44GHz) | N9038A | MY59050109 | July 21, 2021 | July 21, 2023 |
| Keysight MXE Signal Analyzer (26.5GHz) | N9038A | MY56400083 | May 5, 2020 | May 5, 2023 |
| Keysight EXA Signal Analyzer | N9010A | MY56070862 | July 20, 2021 | July 20, 2023 |
| SunAR RF Motion | JB1 | A091418 | July 27, 2021 | July 27, 2022 |
| EMCO Horn Antenna | 3115 | 6416 | July 28, 2021 | July 28, 2023 |
| Rohde & Schwarz Preamplifier* | TS-PR18 | 3545700803 | March 21, 2022 | March 21, 2024 |
| Agilent Preamp* | 87405A | 3950M00669 | March 21, 2022 | March 21, 2024 |
| Trilithic High Pass Filter* | 6HC330 | 23042 | March 21, 2022 | March 21, 2024 |
| TDK Emissions Lab Software | V11.25 | 700307 | NA | NA |
| RF Cable (preamplifier to antenna)* | MFR-57500 | 01-07-002 | April 14, 2020 | April 14, 2022 |
| RF Cable (antenna to 10m chamber bulkhead)* | FSCM 64639 | 01E3872 | September 24, 2021 | September 24, 2023 |
| RF Cable (10m chamber bulkhead to control room bulkhead)* | FSCM 64639 | 01E3864 | September 24, 2021 | September 24, 2023 |
| RF Cable (control room bulkhead to test receiver)* | FSCM 64639 | 01F1206 | September 24, 2021 | September 24, 2023 |
| N connector bulkhead (10m chamber)* | PE9128 | NCEEBH1 | September 24, 2021 | September 24, 2023 |
| N connector bulkhead (control room)* | PE9128 | NCEEBH2 | September 24, 2021 | September 24, 2023 |

*Internal Characterization

Notes:

All equipment is owned by NCEE Labs and stored permanently at NCEE Labs facilities.

3.4 GENERAL TEST PROCEDURE AND SETUP FOR RADIO MEASUREMENTS

Measurement type presented in this report (Please see the checked box below):

Conducted

The conducted measurements were performed by connecting the output of the transmitter directly into a spectrum analyzer using an impedance matched cable and connector soldered to the EUT in place of the antenna. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.



Figure 1 - Bandwidth Measurements Test Setup

Radiated

All the radiated measurements were taken at a distance of 3m from the EUT. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.




Figure 2 - Radiated Emissions Test Setup



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

4.0 RESULTS

| DTS Radio Measurements | | | | |
|------------------------|-------------|-------------------------|------------------------|--------|
| CHANNEL | Transmitter | PEAK OUTPUT POWER (dBm) | PEAK OUTPUT POWER (mW) | RESULT |
| Low | GFSK | 0.997 | 1.26 | PASS |
| Mid | GFSK | 3.666 | 2.33 | PASS |
| High | GFSK | -0.196 | 0.96 | PASS |
| Low | GMSK 1Mb | 1.289 | 1.35 | PASS |
| Mid | GMSK 1Mb | 3.695 | 2.34 | PASS |
| High | GMSK 1Mb | -0.639 | 0.86 | PASS |
| Low | GMSK 2Mb | 4.122 | 2.58 | PASS |
| Mid | GMSK 2Mb | 4.013 | 2.52 | PASS |
| High | GMSK 2Mb | -0.457 | 0.90 | PASS |

Peak Output Power Limit = 30dBm / 1000mW;

| Peak Restricted Band-Edge | | | | | | | |
|---------------------------|----------|----------------------------------------|-----------------------------------------|------------------|---------------------|--------|--------|
| CHANNEL | Mode | Band edge /Measurement Frequency (MHz) | Highest out of band level (dBuV/m @ 3m) | Measurement Type | Limit (dBuV/m @ 3m) | Margin | Result |
| Low | GMSK 1MB | 2390.00 | 52.32 | Peak | 73.98 | 21.66 | PASS |
| Low | GMSK 2MB | 2390.00 | 51.97 | Peak | 73.98 | 22.01 | PASS |
| Low | GFSK | 2390.00 | 51.52 | Peak | 73.98 | 22.46 | PASS |
| High | GMSK 1MB | 2483.50 | 53.12 | Peak | 73.98 | 20.86 | PASS |
| High | GMSK 2MB | 2483.50 | 54.63 | Peak | 73.98 | 19.35 | PASS |
| High | GFSK | 2483.50 | 54.01 | Peak | 73.98 | 19.98 | PASS |

*Limit shown is the peak limit taken from FCC Part 15.209

| Average Restricted Band-Edge | | | | | | | |
|------------------------------|----------|----------------------------------------|-----------------------------------------|------------------|---------------------|--------|--------|
| CHANNEL | Mode | Band edge /Measurement Frequency (MHz) | Highest out of band level (dBuV/m @ 3m) | Measurement Type | Limit (dBuV/m @ 3m) | Margin | Result |
| Low | GMSK 1MB | 2390.00 | 39.33 | Average | 53.98 | 14.65 | PASS |
| Low | GMSK 2MB | 2390.00 | 40.63 | Average | 53.98 | 13.35 | PASS |
| Low | GFSK | 2390.00 | 39.39 | Average | 53.98 | 14.59 | PASS |
| High | GMSK 1MB | 2483.50 | 41.64 | Average | 53.98 | 12.34 | PASS |
| High | GMSK 2MB | 2483.50 | 45.03 | Average | 53.98 | 8.95 | PASS |
| High | GFSK | 2483.50 | 42.48 | Average | 53.98 | 11.50 | PASS |

*Limit shown is the average limit taken from FCC Part 15.209



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

4.1 OUTPUT POWER

Test Method: All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

Limits of power measurements:

For FCC Part 15.247 Device:

The maximum allowed peak output power is 30 dBm / 1000 mW.

Test procedures:

Details can be found in section 3.4 of this report.

Deviations from test standard:

No deviation.

Test setup:

Details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test results:

Pass

Comments:

1. All the output power plots can be found in the Appendix C.
2. All the measurements were found to be compliant.
3. The measurements are listed in the tables below.
4. Compiled values can be found in the Results section, 4.0.



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

4.2 DUTY CYCLE

Test Method:

All Modulations/transmitters shown have a duty cycle of >98%.

4.3 RADIATED EMISSIONS

Test Method: ANSI C63.10-2013, Section 6.5, 6.6

Limits for radiated emissions measurements:

Emissions radiated outside of the specified bands shall be applied to the limits in 15.209 as followed:

| FREQUENCIES (MHz) | FIELD STRENGTH ($\mu\text{V/m}$) | MEASUREMENT DISTANCE (m) |
|-------------------|------------------------------------|--------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 3 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

NOTE:


1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = $20 * \log * \text{Emission level } (\mu\text{V/m})$.
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20dB under any condition of modulation.
4. The EUT was tested for spurious emissions while running off of battery power and external USB power. The worse-case emissions were produced while running off of USB power, so results from this mode are presented.



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

Test procedures:

- a. The EUT was placed on the top of a rotating table above the ground plane in a 10-meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The table was 0.8m high for measurements from 30MHz-1Ghz and 1.5m for measurements from 1GHz and higher.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna was a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are used to make the measurement.
- d. For each suspected emission, the EUT was arranged to maximize its emissions and then the antenna height was varied from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum emission reading.
- e. The test-receiver system was set to use a peak detector with a specified resolution bandwidth. For spectrum analyzer measurements, the composite maximum of several analyzer sweeps was used for final measurements.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise, the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The EUT was maximized in all 3 orthogonal positions. The results are presented for the axis that had the highest emissions.

Test setup:

Figure 3 - Radiated Emissions Test Setup
NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequencies below 1GHz.
2. The resolution bandwidth 1 MHz for all measurements and at frequencies above 1GHz, A peak detector was used for all measurements above 1GHz. Measurements were made with an EMI Receiver.

Deviations from test standard:

No deviation.

EUT operating conditions

Details can be found in section 2.1 of this report.

Test results:




Figure 4 - Radiated Emissions Plot, Receive




Figure 5 - Radiated Emissions Plot, GFSK




Figure 6 - Radiated Emissions Plot, GSK 1MB




Figure 7 - Radiated Emissions Plot, GSK 2MB

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value

| Peak Measurements, GMSK-GFSK | | | | | | | | |
|------------------------------|--------------|--------------|--------|--------|-------|-----|---------|------------|
| Frequency | Level | Limit | Margin | Height | Angle | Pol | Channel | Modulation |
| MHz | dB μ V/m | dB μ V/m | dB | cm. | deg. | | | |
| 2402.276 | 91.74 | NA | NA | 259 | 226 | V | Low | GMSK 1MB |
| 2439.784 | 99.60 | NA | NA | 135 | 194 | H | Mid | GMSK 1MB |
| 2480.296 | 96.16 | NA | NA | 129 | 195 | H | High | GMSK 1MB |
| 7211.340 | 57.04 | 73.98 | 16.94 | 183 | 4 | H | Low | GMSK 1MB |
| 9614.912 | 54.50 | 73.98 | 19.48 | 349 | 290 | H | Low | GMSK 1MB |
| 7319.224 | 57.40 | 73.98 | 16.58 | 194 | 354 | H | Mid | GMSK 1MB |
| 9759.252 | 55.06 | 73.98 | 18.92 | 174 | 290 | H | Mid | GMSK 1MB |
| 7434.740 | 56.51 | 73.98 | 17.47 | 144 | 3 | H | High | GMSK 1MB |
| 9912.678 | 53.43 | 73.98 | 20.55 | 151 | 9 | H | High | GMSK 1MB |
| 2403.462 | 99.95 | NA | NA | 110 | 197 | H | Low | GMSK 2MB |
| 2440.496 | 99.95 | NA | NA | 133 | 201 | H | Mid | GMSK 2MB |
| 2478.586 | 96.21 | NA | NA | 130 | 198 | H | High | GMSK 2MB |
| 7318.378 | 60.66 | 73.98 | 13.32 | 100 | 0 | V | Mid | GMSK 2MB |
| 9757.886 | 56.31 | 73.98 | 17.67 | 450 | 36 | V | Mid | GMSK 2MB |
| 7435.428 | 59.8 | 73.98 | 14.18 | 218 | 359 | V | High | GMSK 2MB |
| 9909.880 | 54.32 | 73.98 | 19.66 | 482 | 178 | V | High | GMSK 2MB |
| 2401.722 | 96.32 | NA | NA | 112 | 205 | H | Low | GFSK |
| 2440.392 | 99.47 | NA | NA | 110 | 208 | H | Mid | GFSK |
| 2480.424 | 95.77 | NA | NA | 130 | 203 | H | High | GFSK |

The EUT was maximized in all 3 orthogonal axes. The worst-case is shown in the plot and table above. All other emissions found to be at least 6dB below the limit line. System Noise floor was at least 6 dB below the limit line throughout the test range.



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

| Average Measurements, GMSK-GFSK | | | | | | | | |
|---------------------------------|--------------|--------------|--------|--------|-------|-----|---------|------------|
| Frequency | Level | Limit | Margin | Height | Angle | Pol | Channel | Modulation |
| MHz | dB μ V/m | dB μ V/m | dB | cm. | deg. | | | |
| 2402.276 | 88.21 | NA | NA | 259 | 226 | V | Low | GMSK 1MB |
| 2439.784 | 96.95 | NA | NA | 135 | 194 | H | Mid | GMSK 1MB |
| 2480.296 | 92.77 | NA | NA | 129 | 195 | H | High | GMSK 1MB |
| 7211.34 | 48.62 | 53.98 | 5.36 | 183 | 4 | H | Low | GMSK 1MB |
| 9614.912 | 44.21 | 53.98 | 9.77 | 349 | 290 | H | Low | GMSK 1MB |
| 7319.224 | 48.73 | 53.98 | 5.25 | 194 | 354 | H | Mid | GMSK 1MB |
| 9759.252 | 44.96 | 53.98 | 9.02 | 174 | 290 | H | Mid | GMSK 1MB |
| 7434.74 | 47.54 | 53.98 | 6.44 | 144 | 3 | H | High | GMSK 1MB |
| 9912.678 | 43.04 | 53.98 | 10.94 | 151 | 9 | H | High | GMSK 1MB |
| 2403.462 | 93.37 | NA | NA | 110 | 197 | H | Low | GMSK 2MB |
| 2440.496 | 93.85 | NA | NA | 133 | 201 | H | Mid | GMSK 2MB |
| 2478.586 | 89.33 | NA | NA | 130 | 198 | H | High | GMSK 2MB |
| 7318.378 | 52.17 | 53.98 | 1.81 | 100 | 0 | V | Mid | GMSK 2MB |
| 9757.886 | 46.42 | 53.98 | 7.56 | 450 | 36 | V | Mid | GMSK 2MB |
| 7435.428 | 52.66 | 53.98 | 1.32 | 218 | 359 | V | High | GMSK 2MB |
| 9909.88 | 43.64 | 53.98 | 10.34 | 482 | 178 | V | High | GMSK 2MB |
| 2401.722 | 93.08 | NA | NA | 112 | 205 | H | Low | GFSK |
| 2440.392 | 95.04 | NA | NA | 110 | 208 | H | Mid | GFSK |
| 2480.424 | 90.76 | NA | NA | 130 | 203 | H | High | GFSK |

The EUT was maximized in all 3 orthogonal axes. The worst-case is shown in the plot and table above. All other emissions found to be at least 6dB below the limit line. System Noise floor was at least 6 dB below the limit line throughout the test range.



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

4.4 BAND EDGES

Test Method: All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

Limits of band-edge measurements:

For FCC Part 15.247 Device:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

Test procedures:

The highest emissions level beyond the band-edge was measured and recorded. All band edge measurements were evaluated to the general limits in Part 15.209. More details can be found in section 3.4 of this report.

Deviations from test standard:

No deviation.

Test setup:

Test setup details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test results:

Pass

Comments:

1. All the band edge plots can be found in the Appendix C.
2. If the device falls under FCC Part 15.247 (Details can be found in summary of test results), compliance is shown in the unrestricted band edges by showing minimum delta of 20 dB between peak and the band edge.
3. The restricted band edge compliance is shown by comparing to the general limit defined in Part 15.209. The limit shown in the graph accounts for the antenna gain of the device.



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |

APPENDIX A: SAMPLE CALCULATION

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF - (-CF + AG) + AV$$

where FS = Field Strength

- RA = Receiver Amplitude
- AF = Antenna Factor
- CF = Cable Attenuation Factor
- AG = Amplifier Gain
- AV = Averaging Factor (if applicable)


Assume a receiver reading of 55 dB μ V is obtained. The Antenna Factor of 12 and a Cable Factor of 1.1 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.1 dB μ V/m.

$$FS = 55 + 12 - (-1.1 + 20) + 0 = 48.1 \text{ dB}\mu\text{V/m}$$

The 48.1 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(48.1 \text{ dB}\mu\text{V/m})/20] = 254.1 \mu\text{V/m}$$

AV is calculated by the taking the $20 \cdot \log(T_{on}/100)$ where T_{on} is the maximum transmission time in any 100ms window.

| | | | | |
|----------------------------------------------------------------------------------|----------------|----------------------------|-----|---|
|  | Report Number: | R20220122-21-E1 | Rev | 0 |
| | Prepared for: | Garmin International, Inc. | | |

EIRP Calculations

In cases where direct antenna port measurement is not possible or would be inaccurate, output power is measured in EIRP. The maximum field strength is measured at a specified distance and the EIRP is calculated using the following equation;

$$EIRP \text{ (Watts)} = [\text{Field Strength (V/m)} \times \text{antenna distance (m)}]^2 / 30$$

$$\text{Power (watts)} = 10^{[\text{Power (dBm)}/10]} / 1000$$

$$\text{Voltage (dB}\mu\text{V)} = \text{Power (dBm)} + 107 \text{ (for } 50\Omega \text{ measurement systems)}$$

$$\text{Field Strength (V/m)} = 10^{[\text{Field Strength (dB}\mu\text{V/m)} / 20]} / 10^6$$

$$\text{Gain} = 1 \text{ (numeric gain for isotropic radiator)}$$

Conversion from 3m field strength to EIRP (d=3):

$$EIRP = [\text{FS(V/m)} \times d^2]/30 = \text{FS} [0.3] \quad \text{for } d = 3$$

$$EIRP(\text{dBm}) = \text{FS}(\text{dB}\mu\text{V/m}) - 10(\log 10^9) + 10\log[0.3] = \text{FS}(\text{dB}\mu\text{V/m}) - 95.23$$

10log(10^9) is the conversion from micro to milli



| | | | |
|----------------|----------------------------|-----|---|
| Report Number: | R20220122-21-E1 | Rev | 0 |
| Prepared for: | Garmin International, Inc. | | |


APPENDIX B – MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been for tests performed in this test report:


| Test | Frequency Range | Uncertainty Value (dB) |
|-----------------------------|------------------------|-------------------------------|
| Radiated Emissions, 3m | 30MHz - 1GHz | ±4.31 |
| Radiated Emissions, 3m | 1GHz - 18GHz | ±5.08 |
| Emissions limits, conducted | 30MHz – 18GHz | ±3.03 |

Expanded uncertainty values are calculated to a confidence level of 95%.


APPENDIX C – GRAPHS AND TABLES




GFSK, High




GFSK, Low




GFSK, Mid




GMSK1MB, High




GMSK1MB, Low




GMSK1MB, Mid



GMSK2MB, High



GMSK2MB, Low



GMSK2MB, Mid



Report Number:


R20220122-21-E1

Rev

0

Prepared for:

Garmin International, Inc.



HBE Restricted, GFSK PRBS9



Report Number:


R20220122-21-E1

Rev

0

Prepared for:

Garmin International, Inc.



HBE Restricted, GMSK 1Mb



Report Number:


R20220122-21-E1

Rev

0

Prepared for:

Garmin International, Inc.



HBE Restricted, GMSK 2Mb



Report Number:


R20220122-21-E1

Rev

0

Prepared for:

Garmin International, Inc.



LBE Restricted, GFSK PRBS9



Report Number:


R20220122-21-E1

Rev

0

Prepared for:

Garmin International, Inc.



LBE Restricted, GMSK 1Mb



Report Number:


R20220122-21-E1

Rev

0

Prepared for:

Garmin International, Inc.



LBE Restricted, GMSK 2Mb



Report Number:

R20220122-21-E1

Rev

0

Prepared for:

Garmin International, Inc.

REPORT END