

Amended
FCC/ISED DXX Part 15.225
Test Report

Prepared for: Garmin International Inc.

Address: 1200 E. 151st Street
Olathe, Kansas, 66062, USA

Product: B03908

Test Report No: R20200110-20-E2B


Approved By: 
Nic S. Johnson, NCE
Technical Manager
iNARTE Certified EMC Engineer #EMC-003337-NE

DATE: 8 May 2020

Total Pages: 23



The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

Revision Page

Rev. No.	Date	Description
Original	21 April 2020	Original – Prepared by FLane Approved by NJohnson
A	29 April 2020	<ol style="list-style-type: none"> 1. Table in section 2.1 was updated to show the correct antenna type 2. Section 3.1.6 was updated with the statement regarding the harmonic measurements and the output power table was updated to show the 3m measurements. 3. Contains the report R20200110-20-E2 and its amendments in full. -KV
B	8 May 2020	<ol style="list-style-type: none"> 1. Radiated Emissions limit from RSS-Gen Issue 5 was added. 2. Output power table was updated. 3. Contains the report R20200110-20-E2A and its amendments in full. -KV



	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

TABLE OF CONTENTS

1	Summary of Test Results	4
1.1	Emissions Test Results	4
2	EUT Description	5
2.1	Equipment under Test (EUT)	5
2.2	Laboratory Description	5
2.3	EUT Setup	5
3	Test Results	6
3.1	Radiated Emissions, Band Width, Output Power and Band edge	6
3.2	Frequency Error	15
3.3	Conducted Emissions.....	17
Annex A: Measurement Uncertainty		20
Annex B: Sample Field Strength Calculation		21
REPORT END		23

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

1 Summary of Test Results

The EUT was tested for compliance to the following standards and/or regulations;

1.1 Emissions Test Results


The EUT was tested for compliance to:

US CFR Title 47 FCC Part 15.225
RSS-Gen Issue 5

Below is a summary of the test results. Complete results of testing can be found in Section 3.

Table 1 – Emissions Test Results

Emissions Tests	Test Method and Limits	Result
Radiated Emissions	FCC Part 15.225 (a), (b), (c), (d) RSS-Gen, Sec 8.9, B.6	Complies
Frequency Error	FCC Part 15.225 (e) RSS-Gen Sec 6.11, B.6	Complies
Conducted Emissions	FCC Part 15.207 RSS-Gen, Sec 8.8, B.6	Complies

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

2 EUT Description

2.1 Equipment under Test (EUT)

Table 2 – Equipment under Test (EUT)

Model	B03908
EUT Received	13 January 2020
EUT Tested	20 March 2020
Serial No.	3318005601 (Radiated Measurements) 3318005708 (Radiated Measurements)
Operating Band	13.56 MHz
Device Type	NFC
Power Supply	Internal Battery/ 5VDC Charger: Garmin (Phi Hong) MN: PSAF10R-050Q (Representative Power Supply)

2.2 Laboratory Description

All testing was performed at the following Facility:

The Nebraska Center for Excellence in Electronics (NCEE Labs)
4740 Discovery Drive
Lincoln, NE 68521


A2LA Certificate Number: 1953.01
FCC Accredited Test Site Designation No: US1060
Industry Canada Test Site Registration No: 4294A-1
NCC CAB Identification No: US0177

Environmental conditions varied slightly throughout the tests:

Relative humidity of $28 \pm 4\%$
Temperature of $22 \pm 3^\circ \text{C}$

2.3 EUT Setup

The EUT was powered by 120 VAC / 60Hz (5 VDC Output) for all tests.

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

3 Test Results

3.1 Radiated Emissions, Band Width, Output Power and Band edge

Test:	FCC Part 15.225 (a), (b), (c), (d) RSS-Gen Sec 8.9
Test Specifications:	Class A
Test Result:	Complies

3.1.1 Test Description

Radiated emissions measurements were made from 30MHz to 1GHz at a distance of 3m (Radiated Emissions) and 0.5m (Band width, Output Power and Band edges) inside a semi-anechoic chamber. The EUT was rotated 360°, the antenna height varied from 1-4 meters and both the vertical and horizontal antenna polarizations examined. For measurements below 30 MHz, the loop antenna was used to measure in all 3 axis. The results were compared against the limits. Measurements were made by first using a spectrum analyzer to acquire the signal spectrum; individual frequencies were then measured using a CISPR 16.1 compliant receiver with the following bandwidth setting:

- 30MHz – 1GHz:120kHz IF bandwidth, 60kHz steps
- 10 – 30MHz, 9kHz RBW, 5 kHz steps

Intermodulation products were investigated by measuring spurious emissions with each of the two 2.4 GHz radios running in parallel with the NFC radio. No intermodulation products were found above the labs system sensitivity.

3.1.2 Test Results

No radiated emissions measurements were found in excess of the limits. Test result data can be seen below.

3.1.3 Test Environment

Testing was performed at the NCEE Labs Lincoln facility in the 10m semi-anechoic chamber. Laboratory environmental conditions varied slightly throughout the test:

- Relative humidity of $30 \pm 5\%$
- Temperature of $23 \pm 2^\circ \text{C}$


3.1.4 Test Setup

See Section 2.3 for further details.

3.1.5 Test Equipment Used

Serial No.	Manufacturer	Model	Description	Last Cal.
A082918-1	SunAR RF Motion	JB1	Bicon Antenna	15 Oct 2018*
00024936	EMCO	6512	Loop Antenna	11 Feb 2019*
MY59050109	Keysight	N9038A	MXE Signal Analyzer	23 Apr 2019
700307	TDK	TDK Emissions lab	Software V.11.25	Not Required

*Two Year Calibration Cycle

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

3.1.6 Test Pictures and/or Figures




Figure 1 – Radiated Emissions Plot, Horizontal Polarization, 10 MHz- 30 MHz

*The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209. Note that the Harmonic measurements were investigated and found to be below the applicable limits by at least 6 dB so the tabular data was not provided.

FCC Limit: $30 \mu\text{V/m}$ at 30m = $29.54 \text{ dB}\mu\text{V/m}$ = $65.10 \text{ dB}\mu\text{V/m}$ at 0.5m

RSS-Gen Limit:

$0.08 \mu\text{A/m}$ at 30m = -1.938 dBuA/m = 33.625 dBuA/m at 0.5m = 67.60 dBuV/m at 0.5m
 ($\text{dBuV/m} = \text{dBuA/m} + 20\log(50 \text{ ohm})$ for 50 ohm measurement system)

Maximum Spurious = $107 - \text{FS (dBm)} + \text{CL} + \text{AF} = 107 - 84.16 + 0.9 + 34.4 = 58.14 \text{ dBuV/m}$ @ 0.5m

CL = cable loss = 0.90 dB

AF = antenna factor = 34.4 dB

107 = conversion from dBm to $\text{dB}\mu\text{V}$ on a 50Ω measurement system

A loop antenna was used to test all three axis, worst axis is reported. Note that the measurements were done at 100 kHz and compared to the limit at 10 kHz to show compliance.

Report Number:	R20200110-20-E2	Rev	B
Prepared for:	Garmin		





Figure 2 – Radiated Emissions Peak Plot, 30 MHz- 1 GHz
 All emissions were found to be at least 10dB below the limit.

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		





Figure 3 - 99% Occupied Bandwidth, NFC

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		




Figure 4 – Output Power

Raw band level dBm	Corrected band level @0.5m dBμV/m	Corrected band level @3m dBμV/m	Limit @ 0.5 m	Limit @ 3m	Margin	Result
-69.226	73.074	57.511	119.560	103.999	46.486	Pass

Maximum power = $107 - 69.226 + 0.9 + 34.4 = 73.074$ dBuV/m @ 0.5m=57.5109


CL = cable loss = 0.90 dB

AF = antenna factor = 34.4 dB

107 = conversion from dBm to dBμV on a 50Ω measurement system

* Extrapolated limit from 30 m to 0.5 m

Measurement performed at 0.5m distance.

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

Band Edge Measurements:

Band edge /Measurement Frequency (MHz)	Uncorrected band level dBm	Corrected band level dB μ V/m @ 0.5 m	Limit dB μ V	Margin	Result
13.11-13.41	-98.105	50.816	76.531	25.715	PASS
13.41-13.553	-75.505	73.416	86.041	12.625	PASS
13.71-14.01	-99.02	49.901	76.531	26.630	PASS
13.567-13.71	-70.698	78.223	86.041	7.818	PASS

* Extrapolated limit from 30 m to 0.5 m. Corrected band level = uncorrected band level + cable loss + antenna factor




Figure 5 – Lower Band-edge

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		




Figure 6 – Lower Band-edge





Figure 7 – Higher Band-edge

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		





Figure 8 – Higher Band-edge

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

3.2 Frequency Error

Test:	FCC Part 15.225 (e) RSS-Gen Sec 6.11
Test Result:	Complies

3.2.1 Test Description

Frequency error was determined using the build in frequency error function of the a spectrum analyzer. The analyzer finds the occupied bandwidth, calculates the center of the given band then returns the deviation with respect to the given transmit frequency. The temperature was varied from -20°C to -50°C. Limit: 100 PPM

3.2.2 Test Results

No results were found to be in excess of the limits. A plot of the results can be seen below.

3.2.3 Test Environment

Testing was performed at the NCEE Labs Lincoln facility on the 10-meter chamber ground plane. Laboratory environmental conditions varied slightly throughout the test:

Relative humidity of $30 \pm 5\%$
Temperature of $23 \pm 2^\circ \text{C}$


3.2.4 Test Setup

See Section 2.3 for further details.

3.2.5 Test Equipment Used

Serial No.	Manufacturer	Model	Description	Last Cal.
31373	Thermotron	SE1000-5-5	Temp chamber	NA
MY59050109	Keysight	N9038A	MXE Signal Analyzer	23 Apr 2019*
00024936	EMCO	6512	Loop Antenna	11 Feb 2019*
ID # 2130155	Omega	iTHX-SD	3m Temp. Humidity Meter	2018 Jan 31

*Two Year Calibration Cycle

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

3.2.6 Test results

Table 3 - Frequency Error Measurements in Hz


Temperature (°C)	Nominal Frequency 13.56000 MHz
	Frequency Error (Hz)
-20°C	18
-10°C	22
0°C	29
10°C	51
20°C	636
30°C	500
40°C	50
50°C	54

Limit: 100 PPM

Table 4 - Voltage Range Measurements

Temperature (°C)	Voltage (VDC)	Nominal Frequency 13.56000 MHz
		Frequency Error (Hz)
20°C	3.20	68
20°C	3.90	636
20°C	4.75	573

Voltage ranges provided by the manufacturer, Limit: 100 PPM

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

3.3 Conducted Emissions

Test Method:	ANSI C63.10-2013, Section(s) 6.2 RSS-Gen Sec 8.8
Test Result:	Complies

3.3.1 Test Description

Conducted emissions measurements were made from 150kHz to 30MHz via a 50µH Line Impedance Stabilization Network (LISN). The results were compared against the limits. Measurements were made on both the line and neutral conductors by first using a spectrum analyzer to acquire the signal spectrum; individual frequencies were then measured using a CISPR 16.1 compliant receiver with the following bandwidth setting:
150kHz – 30MHz: 9kHz IF bandwidth, 5kHz steps

3.3.2 Test Results

No results were found to be in excess of the limits. A plot of the results can be seen below.

3.3.3 Test Environment

Testing was performed at the NCEE Labs Lincoln facility. Laboratory environmental conditions varied slightly throughout the test:


Relative humidity of $30 \pm 5\%$
Temperature of $23 \pm 2^\circ \text{C}$

3.3.4 Test Setup

See Section 2.3 for further details.

3.3.5 Test Equipment Used

Serial No.	Manufacturer	Model	Description	Last Cal.
836679/010	Rohde & Schwarz	ESH3-Z5	Artificial Mains	25 Jul 2019
MY59050109	Keysight	N9038A	MXE Signal Analyzer	23 Apr 2019
700307	TDK	TDK Emissions lab	Software V.11.25	Not Required

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

3.3.6 Test Pictures and/or Figures




Figure 9 - Conducted Emissions, Line

All Measurements were found to be at least 10 dB below the limits.

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		





Figure 10 - Conducted Emissions, Neutral

All Measurements were found to be at least 10 dB below the limits.

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		


Annex A: Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been for tests performed in this test report:

Test	Frequency Range	Uncertainty Value (dB)
Radiated Emissions, 3m	30MHz - 1GHz	±3.82 dB
Radiated Emissions, 3m	1GHz - 18GHz	±4.44 dB
Emissions limits, conducted	30MHz – 18GHz	±3.30 dB
Antenna port conducted	9 kHz – 25 GHz	±0.50 dB

Values were calculated per CISPR 16-4-2:2011

Expanded uncertainty values are calculated to a confidence level of 95%.

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

Annex B: Sample Field Strength Calculation

Radiated Emissions

The field strength is calculated in decibels (dB) by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = R + AF - (-CF + AG)$$

where FS = Field Strength

R = Receiver Amplitude Receiver reading in dB μ V

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Preamplifier Amplifier Gain

Assume a receiver reading of 55.00 dB μ V is obtained. The Antenna Factor of 12.00 and a Cable Factor of 1.10 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.10 dB μ V/m.

$$FS = 55.00 + 12.00 - (-1.10 + 20.00) = 48.1 \text{ dB}\mu\text{V/m}$$

The 48.1 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(48.1 \text{ dB}\mu\text{V/m})/20] = 254.1 \mu\text{V/m}$$


Conducted Emissions

Receiver readings are compared directly to the conducted emissions limits in decibels (dB) by adding the cable loss and LISN insertion loss to the receiver reading. The basic equations with a sample calculation is as follows;

$$FS = R + IL - (-CF)$$

where V = Conducted Emissions Voltage Measurement

R = Receiver reading in dB μ V

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

IL = LISN Insertion Loss

CF = Cable Attenuation Factor

Assume a receiver reading of 52.00 dB μ V is obtained. The LISN insertion loss of 0.80 dB and a Cable Factor of 1.10 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.1 dB μ V/m.


$$V = 52.00 + 0.80 - (-1.10) = 53.90 \text{ dB}\mu\text{V/m}$$

The 53.90 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(48.1 \text{ dB}\mu\text{V/m})/20] = 495.45 \mu\text{V/m}$$

*Note: NCEE Labs uses the Rohde and Schwarz ES-K1 software package. In this software, all cable losses are listed as negative. This is why cable loss is subtracting in the preceding equations.

Margin is calculated by taking the limit and subtracting the Field

	Report Number:	R20200110-20-E2	Rev	B
	Prepared for:	Garmin		

REPORT END