

# Application For Grant of Certification

FOR

Model: CC3110  
2412-2462 MHz (DTS)  
Broadband Digital Transmission System  
FCC ID: IPH-C03110  
IC: 1792A-C03110

FOR


## Garmin International, Inc.

1200 East 151st Street  
Olathe, KS 66062

FCC Designation: US5305  
IC Test Site Registration: 3041A-1

Test Report Number: 190114

Authorized Signatory: *Scot D. Rogers*  
Scot D. Rogers



# **ROGERS LABS, INC.**

4405 West 259<sup>th</sup> Terrace  
Louisburg, KS 66053  
Phone / Fax (913) 837-3214

## Engineering Test Report For Grant of Certification Application

FOR  
47 CFR, PART 15C - Intentional Radiators  
47 CFR Paragraph 15.247 and  
Industry Canada RSS-GEN and RSS-247  
License Exempt Intentional Radiator

For  
**Garmin International, Inc.**

1200 East 151st Street  
Olathe, KS 66062

Digital Transmission System  
Model: CC3110

Frequency Range 2412-2462 MHz  
FCC ID: IPH-C03110  
IC: 1792A-C03110

Test Date: January 14, 2019

Certifying Engineer: *Scot D. Rogers*  
Scot D. Rogers  
Rogers Labs, Inc.  
4405 West 259<sup>th</sup> Terrace  
Louisburg, KS 66053  
Telephone/Facsimile: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory.  
This report must not be used by the client to claim product certification, approval, or  
endorsement by NVLAP, NIST, or any agency of the Federal Government.

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

Garmin International, Inc.  
Model: CC3110  
Test #: 190114  
Test to: 47 CFR 15C, RSS-Gen RSS-247  
File: CC3110 DTS TstRpt 190114

SN's: 4294967295 / B11  
FCC ID: IPH-C03110  
IC: 1792A-C03110  
Date: February 12, 2019  
Page 2 of 46

## Table of Contents

<b>TABLE OF CONTENTS.....</b>	<b>3</b>
<b>REVISIONS.....</b>	<b>5</b>
<b>FOREWORD.....</b>	<b>6</b>
<b>OPINION / INTERPRETATION OF RESULTS .....</b>	<b>6</b>
<b>EQUIPMENT TESTED.....</b>	<b>8</b>
<b>Equipment Function .....</b>	<b>9</b>
<b>Equipment Configuration.....</b>	<b>10</b>
<b>APPLICATION FOR CERTIFICATION.....</b>	<b>11</b>
<b>APPLICABLE STANDARDS &amp; TEST PROCEDURES .....</b>	<b>12</b>
<b>TESTING PROCEDURES .....</b>	<b>12</b>
<b>AC Line Conducted Emission Test Procedure .....</b>	<b>12</b>
<b>Radiated Emission Test Procedure.....</b>	<b>12</b>
<b>Antenna Port Conducted Emission Test Procedure.....</b>	<b>13</b>
Diagram 1 Test arrangement for AC Line Conducted emissions .....	14
Diagram 2 Test arrangement for radiated emissions of tabletop equipment.....	15
Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS).....	16
Diagram 4 Test arrangement for Antenna Port Conducted emissions .....	17
<b>TEST SITE LOCATIONS .....</b>	<b>17</b>
<b>LIST OF TEST EQUIPMENT .....</b>	<b>18</b>
<b>UNITS OF MEASUREMENTS .....</b>	<b>19</b>
<b>ENVIRONMENTAL CONDITIONS.....</b>	<b>19</b>
<b>STATEMENT OF MODIFICATIONS AND DEVIATIONS .....</b>	<b>19</b>
<b>INTENTIONAL RADIATORS.....</b>	<b>19</b>

**Antenna Requirements .....19**

**Restricted Bands of Operation.....20**

Table 1 Harmonic Radiated Emissions in Restricted Bands Data (802.11b, Worst-case).....20

Table 2 Harmonic Radiated Emissions in Restricted Bands Data (802.11g, Worst-case).....21

Table 3 Harmonic Radiated Emissions in Restricted Bands Data (802.11n, Worst-case).....22

**Summary of Results for Radiated Emissions in Restricted Bands .....22**

**AC Line Conducted EMI Procedure .....23**

Figure 1 AC Line Conducted emissions of EUT line 1 (#3, EUT – Computer).....24

Figure 2 AC Line Conducted emissions of EUT line 2 (#3, EUT – Computer).....24

Table 4 AC Line Conducted Emissions Data L1 (#3, EUT – Computer).....25

Table 5 AC Line Conducted Emissions Data L2 (#3, EUT – Computer).....25

**Summary of Results for AC Line Conducted Emissions .....25**

**General Radiated Emissions Procedure.....26**

Table 6 General Radiated Emissions Data .....27

**Summary of Results for General Radiated Emissions .....27**

**Operation in the Band 2400 – 2483.5 MHz .....28**

Figure 3 Plot of Transmitter Emissions in Operational Frequency (802.11 b-Mode) .....29

Figure 4 Plot of Transmitter Emissions in Operational Frequency (802.11 g-Mode) .....29

Figure 5 Plot of Transmitter Emissions in Operational Frequency (802.11 n-Mode) .....30

Figure 6 Plot of Lower Band Edge (802.11 b-mode) .....30

Figure 7 Plot of Lower Band Edge (802.11 g-mode) .....31

Figure 8 Plot of Lower Band Edge (802.11 n-mode) .....31

Figure 9 Plot of Upper Band Edge (802.11 b-mode).....32

Figure 10 Plot of Upper Band Edge (802.11 g-mode).....32

Figure 11 Plot of Upper Band Edge (802.11 n-mode).....33

Figure 12 Plot of Transmitter 6-dB Occupied Bandwidth (802.11 b-mode) .....33

Figure 13 Plot of Transmitter 99% Occupied Bandwidth (802.11 b-mode).....34

Figure 14 Plot of Transmitter 6-dB Occupied Bandwidth (802.11 g-mode) .....34

Figure 15 Plot of Transmitter 99% Occupied Bandwidth (802.11 g-mode).....35

Figure 16 Plot of Transmitter 6-dB Occupied Bandwidth (802.11 n-mode) .....35

Figure 17 Plot of Transmitter 99% Occupied Bandwidth (802.11 n-mode).....36

Figure 18 Plot of Transmitter Power Spectral Density (802.11 b-mode) .....36

Figure 19 Plot of Transmitter Power Spectral Density (802.11 g-mode) .....37  
 Figure 20 Plot of Transmitter Power Spectral Density (802.11 n-mode) .....37  
**Transmitter Emissions Data.....38**  
 Table 7 Transmitter Radiated Emission Worst-case Data 802.11b .....38  
 Table 8 Transmitter Radiated Emission Worst-case Data 802.11g .....39  
 Table 9 Transmitter Radiated Emission Worst-case Data 802.11n .....40  
 Table 10 Transmitter Antenna Port Data .....41  
**Summary of Results for Transmitter Radiated Emissions of Intentional Radiator.....41**  
**ANNEX..... 42**  
**Annex A Measurement Uncertainty Calculations .....43**  
**Annex B Additional Test Equipment List .....44**  
**Annex C Rogers Qualifications .....45**  
**Annex D Rogers Labs Certificate of Accreditation.....46**

## Revisions

Revision 1 Issued February 12, 2019

## Foreword

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under Code of Federal Regulations Title 47 (47 CFR) Paragraph 15.247 and Industry Canada RSS-GEN, Issue 5 and RSS-247 Issue 2, operation in the 2400 – 2483.5 MHz band.

Name of Applicant: Garmin International, Inc.  
1200 East 151st Street  
Olathe, KS 66062

M/N: CC3110

FCC ID: IPH-C03110

Industry Canada ID: 1792A-C03110

Frequency Range: 2412-2462 MHz

Power and OBW: 802.11b/g/n (Wi-Fi) mode,

802.11b Average output power 0.004, (99% Occupied 13,269 kHz)

802.11g Average output power 0.004, (99% Occupied 17,596 kHz)

802.11n Average output power 0.003, (99% Occupied 18,365 kHz)

## Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Emissions 15.205, RSS-GEN	-8.3	Complies
Emissions as per 47 CFR paragraphs 2 and 15.207	-11.6	Complies
Emissions as per 47 CFR paragraphs 2 and 15.209	-12.6	Complies
Harmonic Emissions per 47 CFR 15.247	-12.0	Complies
Power Spectral Density per 47 CFR 15.247	-26.4	Complies

Tests performed include

47CFR

15.247 (a) (2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g.,

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

Garmin International, Inc.  
Model: CC3110  
Test #: 190114  
Test to: 47 CFR 15C, RSS-Gen RSS-247  
File: CC3110 DTS TstRpt 190114

SN's: 4294967295 / B11  
FCC ID: IPH-C03110  
IC: 1792A-C03110  
Date: February 12, 2019  
Page 6 of 46

alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

RSS-247 Issue 2

### **5.2 Digital transmission systems**

DTSs include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to the bands 902-928 MHz and 2400-2483.5 MHz

a) The minimum 6 dB bandwidth shall be 500 kHz.

b) The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

### **5.4 Transmitter output power and equivalent isotropically radiated power (e.i.r.p.) requirements**

d) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

### **5.5 Unwanted emissions**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

## Equipment Tested

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT	CC3110	4294967295
EUT#2	CC3110	B11
1.5m micro B to USB A	320-01325-00	N/A
4m micro B to USB A	320-01325-10	N/A
Laptop Computer	Latitude E6320	FCN03Q1
USB Printer	Dell 0N5819	5D1SL61
Dual type-A Socket CLA	013-00797-00/01	N/A
DC Surveillance Mode Cable	320-01164-xx	N/A
DC Power Supply	BK 1745A	209C13

Test results in this report relate only to the items tested



## ***Equipment Function***

The EUT is a mobile mounted digital recording device incorporating wireless data transfer. The device incorporates camera sensor and associated circuitry to record images within the lens view angle. The design provides a single unique connection point for use of the USB interface cable options and slot for Micro SD memory card. The device offers no other interface options as presented below in the configuration diagrams. The transmitters provide communication capability across the 2402-2480 MHz frequency band. The design provides wireless communications with compatible Bluetooth® (BT) Low Energy (BLE), and 802.11b/g/n (Wi-Fi) equipment. The product operates from internal battery or external direct current power provided over the USB interface port for operation. Power is provided through compatible USB interface cable options and power source. The design utilizes internal fixed antenna system and offers no provision for antenna replacement or modification. Two samples were provided for testing, one representative of production design, and the other modified for testing purposes replacing the integral antenna with RF connection port. The test samples were provided with test software (version 0.07/1.33) providing test personnel the ability to enable transmitter functions on defined modulations and channels. The test software enabled near 100% transmit duty cycle for testing purposes. The antenna modification offered testing facility the ability to connect test equipment to the temporary antenna port for antenna port conducted emission testing. For testing purposes, the EUT received powered from internal battery as well as external direct current sources (CPU-USB port or DC power supply) and configured to operate in available modes. The EUT was arranged as described by the manufacturer emulating typical user configurations for testing purposes. As requested by the manufacturer and required by regulations, the equipment was tested for compliance using the available configurations with the worst-case data presented. This report documents the performed testing and results for applicable configurations and product modes of operation. Test results in this report relate only to the products described in this report.

## Equipment Configuration

- 1) Unit connected to (and powered by) CLA through 4-meter USB cable



- 2) Unit connected to (and powered by) CLA through 1.5-meter USB cable



- 3) Unit connected to (and powered by) Computer through 1.5-meter USB cable



- 4) Unit connected to (and powered by) Surveillance Mode Cable



## Application for Certification

- (1) Manufacturer: Garmin International, Inc.  
1200 East 151st Street  
Olathe, KS 66062
- (2) Identification: M/N: CC3110  
FCC ID: IPH-C03110 IC: 1792A-C03110
- (3) Instruction Book:  
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:  
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:  
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:  
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:  
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from external direct current power provided from compatible DC source. The EUT also provides communication options as documented and presented in this filing.
- (9) Transition Provisions of 47 CFR 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

## Applicable Standards & Test Procedures

The following information is submitted in accordance with the eCFR Federal Communications Code of Federal Regulations, dated January 14, 2019, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.247, KDB 558074 D01, v5, Industry Canada RSS-GEN Issue 5, and RSS-247 Issue 2. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013. This report documents compliance for the EUT operations in mode 2, 802.11b/g/n (Wi-Fi).

## Testing Procedures

### ***AC Line Conducted Emission Test Procedure***


The EUT operates on direct current power only provided by compatible DC source. Testing for the AC line-conducted emissions was performed as defined in ANSI C63.4-2014. The test setup, including the EUT, was arranged in the AC compatible test configuration as presented during testing. The test configuration was placed on a 1 x 1.5-meter bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- $\mu$ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram one showing typical test arrangement and photographs in exhibits for EUT placement used during testing.

### ***Radiated Emission Test Procedure***

Radiated emissions testing was performed as required in 47 CFR 15, RSS-247 and specified in ANSI C63.10-2013. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. The frequency spectrum from 9 kHz to 25,000 MHz was searched for during preliminary investigation. Refer to diagrams two and three showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.


### ***Antenna Port Conducted Emission Test Procedure***

The EUT was assembled as required for operation and placed on a benchtop located in a shielded enclosure. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed as presented in the regulations and specified in ANSI C63.10-2013. The active antenna port of the device was connected to appropriate attenuation and test equipment including spectrum analyzer and/or power meter. Refer to diagram four showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.



1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long see (see 6.2.3.1).
2. I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.2.2).
3. EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$  loads. LISN can be placed on top of, or immediately beneath, reference ground plane (see 6.2.2 and 6.2.3).
  - 3.1 All other equipment powered from additional LISN(s).
  - 3.2 Multiple-outlet strip can be used for multiple power cords of non-EUT equipment.
  - 3.3 LISN at least 80 cm from nearest part of EUT chassis.
4. Non-EUT components of EUT system being tested.
5. Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.3.1).
6. Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see 6.2.2 for options).
7. Antenna may be integral or detachable. If detachable, the antenna shall be attached for this test.

**Diagram 1 Test arrangement for AC Line Conducted emissions**



1—A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$  loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).


1.1—LISN spaced at least 80 cm from the nearest part of the EUT chassis.

2—Antenna can be integral or detachable, depending on the EUT (see 6.3.1).

3—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).

4—For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).


### Diagram 2 Test arrangement for radiated emissions of tabletop equipment



AC Line Conducted Emissions (0.150 -30 MHz)		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak / Quasi Peak
Emissions (30-1000 MHz)		
RBW	AVG. BW	Detector Function
120 kHz	300 kHz	Peak / Quasi Peak
Emissions (Above 1000 MHz)		
RBW	Video BW	Detector Function
100 kHz	100 kHz	Peak
1 MHz	1 MHz	Peak / Average

**Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)**





**Diagram 4 Test arrangement for Antenna Port Conducted emissions**

### Test Site Locations

Conducted EMI AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259<sup>th</sup> Terrace, Louisburg, KS

Radiated EMI The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259<sup>th</sup> Terrace, Louisburg, KS

Registered Site # FCC Site: US5305 and Industry Canada Registration: 3041A-1

NVLAP Accreditation Lab code 200087-0

Rogers Labs, Inc.  
 4405 W. 259th Terrace  
 Louisburg, KS 66053  
 Phone/Fax: (913) 837-3214  
 Revision 1

Garmin International, Inc.  
 Model: CC3110  
 Test #: 190114  
 Test to: 47 CFR 15C, RSS-Gen RSS-247  
 File: CC3110 DTS TstRpt 190114

SN's: 4294967295 / B11  
 FCC ID: IPH-C03110  
 IC: 1792A-C03110  
 Date: February 12, 2019  
 Page 17 of 46

## List of Test Equipment

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
<input checked="" type="checkbox"/> LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	5/2/2018	5/2/2019
<input checked="" type="checkbox"/> LISN	Compliance Design	FCC-LISN-2.Mod.cd,(126)	.15-30MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	10/16/2018	10/16/2019
<input type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303071)	9kHz-40 GHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/16/2018	10/16/2019
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/16/2018	10/16/2019
<input type="checkbox"/> Antenna	EMCO	3147 (40582)	200-1000MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	5/2/2018	5/2/2020
<input type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/16/2018	10/24/2019
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	5/15/2017	5/15/2019
<input checked="" type="checkbox"/> Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	5/2/2018	5/2/2019
<input type="checkbox"/> Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	12/22/2017	12/22/2018
<input type="checkbox"/> Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2019
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/16/2018	10/16/2019
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	10/16/2018	10/16/2019
<input type="checkbox"/> Power Meter	Agilent	N1911A with N1921A	0.05-40 GHz	5/2/2018	5/2/2019
<input type="checkbox"/> Generator	Rohde & Schwarz	SMB100A6 (100150)	20Hz-6 GHz	5/2/2018	5/2/2019
<input type="checkbox"/> Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50114 (017)1.5G HPF	30-18000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50105 (059) 6G HPF	30-18000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Fairview	SA6NFN100W-14 (1625)	30-1800 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1436)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (14362)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (14452)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1736)	30-6000 MHz	5/2/2018	5/2/2019
<input type="checkbox"/> Attenuator	JFW Industries	50FH-010-10 (1)	30-18000 MHz	5/2/2018	5/2/2019
<input checked="" type="checkbox"/> Weather station	Davis	6312 (A70927D44N)		10/16/2018	10/16/2019

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

Garmin International, Inc.  
Model: CC3110  
Test #: 190114  
Test to: 47 CFR 15C, RSS-Gen RSS-247  
File: CC3110 DTS TstRpt 190114

SN's: 4294967295 / B11  
FCC ID: IPH-C03110  
IC: 1792A-C03110  
Date: February 12, 2019  
Page 18 of 46

## Units of Measurements

Conducted EMI            Data is in dB $\mu$ V; dB referenced to one microvolt

Radiated EMI            Data is in dB $\mu$ V/m; dB/m referenced to one microvolt per meter

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Gain = amplification gains and/or cable losses

RFS (dB $\mu$ V/m @ 3m) = FSM (dB $\mu$ V) + A.F. (dB) - Gain (dB)

## Environmental Conditions

Ambient Temperature        20.6° C

Relative Humidity            35%

Atmospheric Pressure        1034.5 mb

## Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to demonstrate compliance with the 47 CFR Part 15C, RSS-Gen, and RSS-247 emission requirements. There were no deviations to the specifications.

## Intentional Radiators

The following information is submitted in support demonstration of compliance with the requirements of 47 CFR, Subpart C, paragraph 15.247 and Industry Canada RSS-247 and RSS-Gen the following information is submitted.

## Antenna Requirements

The EUT incorporates integral antenna system and offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

## Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

**Table 1 Harmonic Radiated Emissions in Restricted Bands Data (802.11b, Worst-case)**

Frequency in MHz	Horizontal Peak (dB $\mu$ V/m)	Horizontal Quasi-Peak (dB $\mu$ V/m)	Horizontal Average (dB $\mu$ V/m)	Vertical Peak (dB $\mu$ V/m)	Vertical Quasi-Peak (dB $\mu$ V/m)	Vertical Average (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)
2390.0	54.9	N/A	29.5	50.3	N/A	29.2	54.0
2483.5	53.7	N/A	29.6	49.7	N/A	29.3	54.0
4824.0	46.4	N/A	34.0	47.3	N/A	33.7	54.0
4884.0	47.2	N/A	35.3	47.3	N/A	34.7	54.0
4924.0	48.2	N/A	36.1	47.4	N/A	34.3	54.0
7236.0	47.9	N/A	34.8	48.1	N/A	34.8	54.0
7326.0	47.3	N/A	34.3	47.1	N/A	34.2	54.0
7386.0	46.7	N/A	34.1	46.8	N/A	34.0	54.0
12060.0	51.2	N/A	38.2	50.9	N/A	38.0	54.0
12210.0	50.2	N/A	37.5	50.3	N/A	37.7	54.0
12310.0	50.6	N/A	37.4	50.3	N/A	37.6	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 2 Harmonic Radiated Emissions in Restricted Bands Data (802.11g, Worst-case)**

Frequency in MHz	Horizontal Peak (dB $\mu$ V/m)	Horizontal Quasi-Peak (dB $\mu$ V/m)	Horizontal Average (dB $\mu$ V/m)	Vertical Peak (dB $\mu$ V/m)	Vertical Quasi-Peak (dB $\mu$ V/m)	Vertical Average (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)
2390.0	60.1	N/A	31.0	52.6	N/A	29.9	54.0
2483.5	60.3	N/A	33.4	55.1	N/A	31.0	54.0
4824.0	46.0	N/A	33.0	45.7	N/A	32.9	54.0
4884.0	47.1	N/A	33.5	46.5	N/A	33.2	54.0
4924.0	47.1	N/A	33.8	47.0	N/A	33.6	54.0
7236.0	47.3	N/A	34.8	47.5	N/A	34.7	54.0
7326.0	47.0	N/A	34.3	47.4	N/A	34.2	54.0
7386.0	47.3	N/A	34.0	48.1	N/A	34.0	54.0
12060.0	50.7	N/A	38.2	50.8	N/A	38.2	54.0
12210.0	51.0	N/A	37.6	50.1	N/A	37.6	54.0
12310.0	50.4	N/A	42.0	50.6	N/A	37.4	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 3 Harmonic Radiated Emissions in Restricted Bands Data (802.11n, Worst-case)**

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Quasi-Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Quasi-Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)
2390.0	59.4	N/A	30.6	56.0	N/A	29.8	54.0
2483.5	58.4	N/A	32.4	56.3	N/A	31.0	54.0
4824.0	46.1	N/A	33.0	45.7	N/A	32.8	54.0
4884.0	45.9	N/A	33.0	46.4	N/A	33.1	54.0
4924.0	46.6	N/A	33.7	46.7	N/A	33.6	54.0
7236.0	48.1	N/A	34.4	47.4	N/A	34.8	54.0
7326.0	47.0	N/A	34.3	47.2	N/A	34.2	54.0
7386.0	46.9	N/A	33.9	46.9	N/A	34.0	54.0
12060.0	50.5	N/A	38.2	50.8	N/A	38.2	54.0
12210.0	51.3	N/A	37.6	50.9	N/A	37.6	54.0
12310.0	50.1	N/A	37.4	50.5	N/A	37.4	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Summary of Results for Radiated Emissions in Restricted Bands**

The EUT demonstrated compliance with the radiated emissions requirements of 47 CFR Part 15C RSS-Gen, and RSS-247 Intentional Radiators. The EUT worst-case 802.11 mode demonstrated a minimum radiated emission margin of -12.0 dB below the requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

### **AC Line Conducted EMI Procedure**

The EUT was arranged in typical AC connected configuration as defined by manufacturer. AC Line Conducted emission testing was performed with the EUT placed on a 1 x 1.5-meter bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. Testing for the AC line-conducted emissions followed the procedures of ANSI C63.10-2013. The EUT was configured as presented in the AC Line conducted configuration as presented above in equipment configuration. The AC adapter for the CPU powering the EUT was connected to the LISN for AC line-conducted emissions testing. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the test configuration. All power cords except the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor, internal to the LISN. Power line conducted emissions testing was carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequencies of each of the emissions, which demonstrated the highest amplitudes. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz and data recorded.

Refer to figures one and two for plots of the EUT – USB Computer interface AC Line conducted emissions.




Figure 1 AC Line Conducted emissions of EUT line 1 (#3, EUT – Computer)




Figure 2 AC Line Conducted emissions of EUT line 2 (#3, EUT – Computer)



**Table 4 AC Line Conducted Emissions Data L1 (#3, EUT – Computer)**

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	158.000000000 kHz	43.95	Quasi Peak	-21.62
2	166.000000000 kHz	34.20	Average	-20.95
2	190.000000000 kHz	37.72	Average	-16.32
2	214.000000000 kHz	32.99	Average	-20.06
2	234.000000000 kHz	33.28	Average	-19.03
2	250.000000000 kHz	37.08	Average	-14.68
1	262.000000000 kHz	44.94	Quasi Peak	-16.42
2	398.000000000 kHz	25.44	Average	-22.46
1	618.000000000 kHz	40.59	Quasi Peak	-15.41
1	3.222000000 MHz	32.70	Quasi Peak	-23.30
1	17.540000000 MHz	34.98	Quasi Peak	-25.02
1	18.160000000 MHz	36.26	Quasi Peak	-23.74

Other emissions present had amplitudes at least 20 dB below the limit.

**Table 5 AC Line Conducted Emissions Data L2 (#3, EUT – Computer)**

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	190.000000000 kHz	42.46	Quasi Peak	-21.57
2	194.000000000 kHz	32.68	Average	-21.18
2	258.000000000 kHz	39.83	Average	-11.67
1	262.000000000 kHz	45.85	Quasi Peak	-15.51
2	390.000000000 kHz	32.67	Average	-15.40
1	14.856000000 MHz	36.23	Quasi Peak	-23.77
1	15.128000000 MHz	35.71	Quasi Peak	-24.29
2	16.424000000 MHz	27.61	Average	-22.39
1	16.604000000 MHz	36.65	Quasi Peak	-23.35
2	17.488000000 MHz	28.54	Average	-21.46
1	18.368000000 MHz	39.77	Quasi Peak	-20.23
2	18.548000000 MHz	29.61	Average	-20.39

Other emissions present had amplitudes at least 20 dB below the limit.

**Summary of Results for AC Line Conducted Emissions**

The EUT demonstrated compliance with the AC Line Conducted Emissions requirements of 47 CFR Part 15C, RSS-247 and RSS-Gen. The worst-case EUT AC conducted configuration demonstrated a minimum margin of -11.6 dB below the requirement. Other emissions were present with amplitudes at least 20 dB below the limit and worst-case amplitudes recorded.

## **General Radiated Emissions Procedure**

The EUT was arranged in a typical equipment configuration and operated through all available mode during testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated measurements were performed. Final data was taken with the EUT located on the OATS at 3 meters distance between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers above 1 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

**Table 6 General Radiated Emissions Data**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
134.9	27.8	21.2	N/A	31.3	22.5	N/A	40.0
179.8	32.1	27.4	N/A	32.0	22.7	N/A	40.0
224.8	23.5	15.7	N/A	27.4	20.7	N/A	40.0
269.9	32.0	27.6	N/A	37.0	31.3	N/A	47.0
315.0	24.0	18.5	N/A	26.3	17.8	N/A	47.0
359.8	29.9	26.4	N/A	32.2	29.1	N/A	47.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Summary of Results for General Radiated Emissions**

The EUT demonstrated compliance with the radiated emissions requirements of 47 CFR Part 15C paragraph 15.209, RSS-247 and RSS-GEN Intentional Radiators. The EUT demonstrated a minimum margin of -12.6 below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

### **Operation in the Band 2400 – 2483.5 MHz**

Test procedures of ANSI C63.10-2013 paragraph 6, and KDB 558074 D01 v5, were used during transmitter testing. Test sample #2 was provided for testing antenna port conducted emissions. This sample was modified by replacing the internal antenna with a 50-ohm antenna port connector and attenuator for testing purposes. The transmitter peak and average power was measured at the antenna port using a wideband RF power meter as described in KDB 558074 and ANSI C63.10-2013. Average power measured did not include any time intervals during which the transmitter was off or transmitting at a reduced power level. The peak Power Spectral Density (PKPSD) was measured as defined in KDB 558074 and ANSI C63.10-2013. DTS Emission bandwidth was measured as described in KDB 558074 and ANSI C63.10-2013. The amplitude of each harmonic and general radiated emission was measured on the OATS at distance of 3 meters from the FSM antenna (radiated emission testing was performed on sample #1 representative of production equipment with integral antenna). The EUT was positioned on supporting turntable elevated as required above the ground plane, at a distance of 3 meters from the FSM antenna. Radiated emission investigations were performed from 9 kHz to 25,000 MHz. Each radiated emission was maximized by varying the FSM antenna height and polarization, and by rotating the turntable. The worst-case amplitude of each emission was then recorded from the analyzer display. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Radiated Emissions were measured in dBµV/m @ 3 meters. Plots were taken of transmitter performance (using sample #2) for reference in this and other documentation.




Figure 3 Plot of Transmitter Emissions in Operational Frequency (802.11 b-Mode)






Figure 4 Plot of Transmitter Emissions in Operational Frequency (802.11 g-Mode)



**Figure 5 Plot of Transmitter Emissions in Operational Frequency (802.11 n-Mode)**



**Figure 6 Plot of Lower Band Edge (802.11 b-mode)**




Figure 7 Plot of Lower Band Edge (802.11 g-mode)






Figure 8 Plot of Lower Band Edge (802.11 n-mode)




**Figure 9 Plot of Upper Band Edge (802.11 b-mode)**




**Figure 10 Plot of Upper Band Edge (802.11 g-mode)**





**Figure 11 Plot of Upper Band Edge (802.11 n-mode)**



**Figure 12 Plot of Transmitter 6-dB Occupied Bandwidth (802.11 b-mode)**




Figure 13 Plot of Transmitter 99% Occupied Bandwidth (802.11 b-mode)






Figure 14 Plot of Transmitter 6-dB Occupied Bandwidth (802.11 g-mode)







**Figure 19 Plot of Transmitter Power Spectral Density (802.11 g-mode)**



**Figure 20 Plot of Transmitter Power Spectral Density (802.11 n-mode)**

**Transmitter Emissions Data**

**Table 7 Transmitter Radiated Emission Worst-case Data 802.11b**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
2412.0	--	--	--	--	--
4824.0	46.4	34.0	47.3	33.7	54.0
7236.0	47.9	34.8	48.1	34.8	54.0
9648.0	49.0	35.8	49.3	35.9	54.0
12060.0	51.2	38.2	50.9	38.0	54.0
14472.0	52.4	39.8	53.1	39.8	54.0
16884.0	57.1	44.4	57.3	44.6	54.0
2437.0	--	--	--	--	--
4874.0	47.2	35.3	47.3	34.7	54.0
7311.0	47.3	34.3	47.1	34.2	54.0
9748.0	49.5	36.1	49.2	36.0	54.0
12185.0	50.2	37.5	50.3	37.7	54.0
14622.0	53.1	40.2	53.3	40.3	54.0
17059.0	57.5	44.1	57.2	44.5	54.0
2462.0	--	--	--	--	--
4924.0	48.2	36.1	47.4	34.3	54.0
7386.0	46.7	34.1	46.8	34.0	54.0
9848.0	49.3	35.8	48.9	35.8	54.0
12310.0	50.6	37.4	50.3	37.6	54.0
14772.0	55.1	42.0	54.6	41.9	54.0
17234.0	56.4	43.3	56.1	43.2	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 8 Transmitter Radiated Emission Worst-case Data 802.11g**

Frequency in MHz	Horizontal Peak (dB $\mu$ V/m)	Horizontal Average (dB $\mu$ V/m)	Vertical Peak (dB $\mu$ V/m)	Vertical Average (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)
2412.0	--	--	--	--	--
4824.0	46.0	33.0	45.7	32.9	54.0
7236.0	47.3	34.8	47.5	34.7	54.0
9648.0	48.1	35.7	48.6	35.7	54.0
12060.0	50.7	38.2	50.8	38.2	54.0
14472.0	52.4	39.7	53.2	39.7	54.0
16884.0	57.6	44.4	58.0	44.7	54.0
2437.0	--	--	--	--	--
4874.0	47.1	33.5	46.5	33.2	54.0
7311.0	47.0	34.3	47.4	34.2	54.0
9748.0	49.1	36.1	49.2	36.1	54.0
12185.0	51.0	37.6	50.1	37.6	54.0
14622.0	53.4	40.4	53.1	40.3	54.0
17059.0	57.2	44.5	57.3	44.6	54.0
2462.0	--	--	--	--	--
4924.0	47.1	33.8	47.0	33.6	54.0
7386.0	47.3	34.0	48.1	34.0	54.0
9848.0	48.7	35.9	48.9	35.8	54.0
12310.0	50.4	42.0	50.6	37.4	54.0
14772.0	54.0	42.2	55.2	41.9	54.0
17234.0	56.6	43.4	56.3	43.2	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 9 Transmitter Radiated Emission Worst-case Data 802.11n**

Frequency in MHz	Horizontal Peak (dB $\mu$ V/m)	Horizontal Average (dB $\mu$ V/m)	Vertical Peak (dB $\mu$ V/m)	Vertical Average (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)
2412.0	--	--	--	--	--
4824.0	46.1	33.0	45.7	32.8	54.0
7236.0	48.1	34.4	47.4	34.8	54.0
9648.0	49.0	35.9	48.2	35.8	54.0
12060.0	50.5	38.2	50.8	38.2	54.0
14472.0	52.8	39.8	52.8	39.6	54.0
16884.0	57.4	44.7	57.3	44.5	54.0
2437.0	--	--	--	--	--
4874.0	45.9	33.0	46.4	33.1	54.0
7311.0	47.0	34.3	47.2	34.2	54.0
9748.0	49.6	36.1	49.4	36.1	54.0
12185.0	51.3	37.6	50.9	37.6	54.0
14622.0	53.3	40.4	53.0	40.2	54.0
17059.0	57.2	44.5	57.0	44.4	54.0
2462.0	--	--	--	--	--
4924.0	46.6	33.7	46.7	33.6	54.0
7386.0	46.9	33.9	46.9	34.0	54.0
9848.0	48.8	35.7	48.7	35.9	54.0
12310.0	50.1	37.4	50.5	37.4	54.0
14772.0	55.2	41.8	54.7	41.9	54.0
17234.0	56.0	43.2	56.7	43.2	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.



**Table 10 Transmitter Antenna Port Data**

Frequency MHz	Antenna Port Output Power Average (Watts)	99% Occupied Bandwidth (kHz)	6-dB Occupied Bandwidth (kHz)	Peak Power Spectral Density (dBm)
802.11b				
2412	0.004	13,269.2	8,413.5	-18.4
2437	0.004	13,173.1	7,884.6	-18.4
2462	0.004	13,269.2	8,028.8	-18.5
802.11g				
2412	0.004	17,596.2	16,442.3	-20.1
2437	0.004	17,596.2	16,442.3	-18.6
2462	0.004	17,500.0	16,346.2	-19.6
802.11n				
2412	0.003	18,365.4	17,092.3	-21.3
2437	0.003	18,269.2	16,538.5	-20.3
2462	0.003	18,173.1	17,307.7	-20.3

**Summary of Results for Transmitter Radiated Emissions of Intentional Radiator**

The EUT demonstrated compliance with the radiated and conducted emission requirements of 47CFR Part 15.247, RSS-GEN, and RSS-247 Digital Transmission Systems. Average output power of 0.004 Watts was measured at the antenna port. The peak power spectral density measured at the antenna port presented a minimum margin of -26.4 dB below the requirements. The EUT demonstrated a minimum margin of -12.0 dB below the harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements. There were no other deviations or exceptions to the requirements.

## Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Additional Test Equipment List
- Annex C Rogers Qualifications
- Annex D Rogers Labs Certificate of Accreditation

## Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16-4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.14
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

**Annex B Additional Test Equipment List**

List of Test Equipment	Calibration	Date (m/d/y)	Due
Antenna: Schwarzbeck Model: BBA 9106/VHBB 9124 (9124-627)		5/2/2018	5/2/2019
Antenna: Schwarzbeck Model: VULP 9118 A (VULP 9118 A-534)		5/2/2018	5/2/2019
Antenna: EMCO 6509		10/16/2018	10/16/2020
Antenna: EMCO 3143 (9607-1277) 20-1200 MHz		5/2/2018	5/2/2019
Antenna: EMCO Dipole Set 3121C		2/23/2018	2/23/2019
Antenna: C.D. B-101		2/23/2018	2/23/2019
Antenna: Solar 9229-1 & 9230-1		2/23/2018	2/23/2019
Cable: Belden 8268 (L3)		10/16/2018	10/16/2019
Cable: Time Microwave: 4M-750HF290-750		10/16/2018	10/16/2019
Frequency Counter: Leader LDC-825 (8060153)		5/2/2018	5/2/2019
Oscilloscope Scope: Tektronix 2230		2/23/2018	2/23/2019
Wattmeter: Bird 43 with Load Bird 8085		2/23/2018	2/23/2019
R.F. Generator: SMB100A6 s/n 100623		5/2/2018	5/2/2019
R.F. Generator: SBMBV100A s/n: 260771		5/2/2018	5/2/2019
R.F. Generators: HP 606A, HP 8614A, HP 8640B		2/23/2018	2/23/2019
R.F. Power Amp 65W Model: 470-A-1010		2/23/2018	2/23/2019
R.F. Power Amp 50W M185- 10-501		2/23/2018	2/23/2019
R.F. Power Amp A.R. Model: 10W 1010M7		2/23/2018	2/23/2019
R.F. Power Amp EIN Model: A301		2/23/2018	2/23/2019
LISN: Compliance Eng. Model 240/20		5/2/2018	5/2/2019
LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08		5/2/2018	5/2/2019
Audio Oscillator: H.P. 201CD		2/23/2018	2/23/2019
ESD Test Set 2010i		2/23/2018	2/23/2019
Oscilloscope Scope: Tektronix MDO 4104		2/23/2018	2/23/2019
EMC Transient Generator HVT TR 3000		2/23/2018	2/23/2019
AC Power Source (Ametech, California Instruments)		2/23/2018	2/23/2019
Fast Transient Burst Generator Model: EFT/B-101		2/23/2018	2/23/2019
Field Intensity Meter: EFM-018		2/23/2018	2/23/2019
KEYTEK Ecat Surge Generator		2/23/2018	2/23/2019
ESD Simulator: MZ-15		2/23/2018	2/23/2019
Shielded Room Calibration not required			

## **Annex C Rogers Qualifications**

***Scot D. Rogers, Engineer***

### **Rogers Labs, Inc.**

Mr. Rogers has approximately 30 years' experience in the field of electronics. Engineering experience includes six years in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

#### Positions Held


Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

#### Educational Background

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.



Scot D. Rogers

## Annex D Rogers Labs Certificate of Accreditation

<p>United States Department of Commerce National Institute of Standards and Technology</p> <p><b>NVLAP®</b></p> <hr/> <p><b>Certificate of Accreditation to ISO/IEC 17025:2005</b></p> <hr/> <p>NVLAP LAB CODE: 200087-0</p> <p><b>Rogers Labs, Inc.</b> Louisburg, KS</p> <p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p> <p><b>Electromagnetic Compatibility &amp; Telecommunications</b></p> <p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p> <hr/> <table border="0" style="width: 100%;"><tr><td style="width: 33%; text-align: center;"><p>2018-02-21 through 2019-03-31 <i>Effective Dates</i></p></td><td style="width: 33%; text-align: center;"></td><td style="width: 33%; text-align: center;"><p> <i>For the National Voluntary Laboratory Accreditation Program</i></p></td></tr></table>			<p>2018-02-21 through 2019-03-31 <i>Effective Dates</i></p>		<p> <i>For the National Voluntary Laboratory Accreditation Program</i></p>
<p>2018-02-21 through 2019-03-31 <i>Effective Dates</i></p>		<p> <i>For the National Voluntary Laboratory Accreditation Program</i></p>			

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

Garmin International, Inc.  
Model: CC3110  
Test #: 190114  
Test to: 47 CFR 15C, RSS-Gen RSS-247  
File: CC3110 DTS TstRpt 190114

SN's: 4294967295 / B11  
FCC ID: IPH-C03110  
IC: 1792A-C03110  
Date: February 12, 2019  
Page 46 of 46