



Date(s) of Evaluation  
Jun. 20, 2013

Test Report Serial No.  
061213IPH-1239S

Test Report Revision No.  
Rev. 1.1 (2nd Release)

Test Report Issue Date  
Jul. 3, 2013

Description of Test(s)  
Specific Absorption Rate

RF Exposure Category  
Gen. Pop. / Uncontrolled



DECLARATION OF COMPLIANCE		SAR RF EXPOSURE EVALUATION			FCC & IC					
Test Lab Information		CELLTECH LABS INC. 21-364 Lougheed Road, Kelowna, BC. V1X 7R8 Canada								
Test Lab Accreditation		A2LA - ISO/IEC 17025:2005 (A2LA TEST LAB CERTIFICATE NO. 2470.01)								
Applicant Information		GARMIN INTERNATIONAL INC. 1200, East 151 <sup>st</sup> Street, Olathe, KS, 66062 USA								
Application Type(s)	FCC	TCB Certification		IC	CB Certification					
Standard(s) Applied	FCC	47 CFR §2.1093		IC	Health Canada Safety Code 6					
Procedure(s) Applied	FCC	OET Bulletin 65, Supplement C (01-01) KDB 447498 D01v05 - General RF Exposure Procedures								
		KDB 248227 D01v01r02 - SAR Measurement Procedures for 802.11a/b/g Transmitters								
	IC	RSS-102 Issue 4								
	IEEE	1528-2003	IEC	62209-2:2010						
Device RF Exposure Category	FCC/IC	General Population / Uncontrolled Environment								
Device Classification(s)	FCC	DTS - Digital Transmission System (Part 15 Subpart C)								
	IC	Low Power License-Exempt Radio-communication Device (RSS-210)								
Device Identifier(s)	FCC ID:	IPH-F3ARGD00		IC:	1792A-F3ARGD00					
Device Model No.	F3ARGD00									
Test Sample Serial No.	n/a (Identical Prototype)									
Test Sample Hardware Rev. No.	v5		Test Sample Firmware Rev. No.		V0.20					
Measurement Date(s)	Jun. 20, 2013		Date of Sample Receipt		Jun. 12, 2013					
Device Description	Wrist-worn GPS Device									
Internal Transmitter(s) Type	802.11b/g									
Transmitter Type Tested	802.11b/g									
Transmitter Specifications	Frequency Range - 2412 - 2462 MHz 802.11b - Modulations [DSSS, CCK] - Data Rates [1, 2, 5.5, 11] 802.11g - Modulations [OFDM] - Data Rates [6, 9, 12, 24, 36, 48, 54] Maximum Rated Conducted Output Power = 10 mW Duty Cycle = 44%									
	802.15	2402 - 2480 MHZ	2 mW	No simultaneous tx						
Antenna Type(s) Tested	Internal (2.4 GHz)									
Battery Type(s) Tested	Internal Lithium-ion (150 mAh)				P/N: 361-00072-00					
Max. SAR Level(s) Evaluated	Extremity	802.11b	0.021 W/kg	10g average	FCC/IC SAR Limit	4.0 W/kg	10g average			
Celltech Labs Inc. declares under its sole responsibility that this wireless portable device was compliant with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093 and Health Canada's Safety Code 6 for the General Population / Uncontrolled Exposure environment. The device was tested in accordance with the measurement procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01), Industry Canada RSS-102 Issue 4, IEEE Standard 1528-2003 and IEC International Standard 62209-2:2010. All measurements were performed in accordance with the SAR system manufacturer recommendations.										
I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.										
The results and statements contained in this report pertain only to the device evaluated.										
This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc.										
Test Report Approved By			Mike Meaker	Engineering Technologist		Celltech Labs Inc.				

Applicant:	Garmin International Inc.	FCC ID:	IPH-F3ARGD00	IC:	1792A-F3ARGD00	
Model:	F3ARGD00	DUT Type:	Wrist-worn GPS Device			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 1 of 32

Date(s) of Evaluation

Jun. 20, 2013

Test Report Serial No.

061213IPH-1239S

Test Report Revision No.

Rev. 1.1 (2nd Release)

Test Report Issue Date

Jul. 3, 2013

Description of Test(s)

Specific Absorption Rate

RF Exposure Category

Gen. Pop. / Uncontrolled



Test Lab Certificate No. 2470.01

## TABLE OF CONTENTS

<b>1.0 INTRODUCTION</b>	<b>4</b>
<b>2.0 SAR MEASUREMENT SYSTEM</b>	<b>4</b>
<b>3.0 CONDUCTED OUTPUT POWER MEASUREMENTS</b>	<b>5</b>
<b>4.0 FLUID DIELECTRIC PARAMETERS</b>	<b>6</b>
<b>5.0 SAR MEASUREMENT SUMMARY</b>	<b>7</b>
<b>6.0 SAR SCALING FOR TUNE-UP TOLERANCE</b>	<b>8</b>
<b>7.0 SIMULTANEOUS TRANSMISSION ASSESSMENT</b>	<b>8</b>
<b>8.0 DETAILS OF SAR EVALUATION</b>	<b>9</b>
<b>9.0 SAR EVALUATION PROCEDURES</b>	<b>9</b>
<b>10.0 SYSTEM VERIFICATION</b>	<b>10</b>
<b>11.0 SIMULATED EQUIVALENT TISSUES</b>	<b>11</b>
<b>12.0 SAR LIMITS</b>	<b>11</b>
<b>13.0 ROBOT SYSTEM SPECIFICATIONS</b>	<b>12</b>
<b>14.0 PROBE SPECIFICATION (EX3DV4)</b>	<b>13</b>
<b>15.0 SAM TWIN PHANTOM V4.0C</b>	<b>13</b>
<b>16.0 DEVICE HOLDER</b>	<b>13</b>
<b>17.0 TEST EQUIPMENT LIST</b>	<b>14</b>
<b>18.0 MEASUREMENT UNCERTAINTY (IEC 62209-2)</b>	<b>15</b>
<b>19.0 REFERENCES</b>	<b>16</b>
<b>APPENDIX A - SAR MEASUREMENT PLOTS</b>	<b>17</b>
<b>APPENDIX B - SYSTEM PERFORMANCE CHECK PLOTS</b>	<b>22</b>
<b>APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS</b>	<b>25</b>
<b>APPENDIX D - SAR TEST SETUP &amp; DUT PHOTOGRAPHS</b>	<b>27</b>
<b>APPENDIX E - DIPOLE CALIBRATION</b>	<b>30</b>
<b>APPENDIX F - PROBE CALIBRATION</b>	<b>31</b>
<b>APPENDIX G - SAM PHANTOM CERTIFICATE OF CONFORMITY</b>	<b>32</b>

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>		
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 2 of 32			

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

REVISION HISTORY			
REVISION NO.	DESCRIPTION	IMPLEMENTED BY	RELEASE DATE
1.0	1st Release	Mike Meaker	Jul. 3, 2013
1.1	Minor fixes - model name and mode	Mike Meaker	Jul. 8, 2013

TEST REPORT SIGN-OFF			
DEVICE TESTED BY	REPORT PREPARED BY	QA REVIEW BY	REPORT APPROVED BY
Mike Meaker	Mike Meaker	Glen Westwell	Mike Meaker

<b>Applicant:</b>	Garmin International Inc.	<b>FCC ID:</b>	IPH-F3ARGD00	<b>IC:</b>	1792A-F3ARGD00	 <b>GARMIN</b>	
<b>Model:</b>	F3ARGD00	<b>DUT Type:</b>	Wrist-worn GPS Device				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 3 of 32		


	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## 1.0 INTRODUCTION

This measurement report demonstrates that the Garmin International Inc. Model: F3ARGD00 Wrist-worn GPS Device complies with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]) and Health Canada's Safety Code 6 (see reference [2]) for the General Population / Uncontrolled Exposure environment. The test procedures described in FCC OET Bulletin 65, Supplement C, Edition 01-01 (see reference [3]), IC RSS-102 Issue 4 (see reference [4]), IEEE Standard 1528-2003 (see reference [5]) and IEC International Standard 62209-2:2010 (see reference [7]) were employed. A description of the product, operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

## 2.0 SAR MEASUREMENT SYSTEM

Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for Head and/or Body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot utilizes a controller with built in VME-bus computer.



Applicant:	Garmin International Inc.		FCC ID:	IPH-F3ARGD00	IC:	1792A-F3ARGD00	
Model:	F3ARGD00		DUT Type:	Wrist-worn GPS Device			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 4 of 32



Date(s) of Evaluation  
Jun. 20, 2013

Test Report Serial No.  
061213IPH-1239S

Test Report Revision No.  
Rev. 1.1 (2nd Release)

Test Report Issue Date  
Jul. 3, 2013

Description of Test(s)  
Specific Absorption Rate

RF Exposure Category  
Gen. Pop. / Uncontrolled




Test Lab Certificate No. 2470.01

### 3.0 CONDUCTED OUTPUT POWER MEASUREMENTS

Freq. (MHz)	Channel	Peak Conducted Output Power (Watts)
<b>802.11b Mode</b>		<b>1 Mbps</b>
2412	1	0.008
2437	6	0.009
2462	11	0.009
<b>802.11g Mode</b>		<b>6 Mbps</b>
2412	1	0.006
2437	6	0.007
2462	11	0.007
<b>Notes</b>		
1. According to the manufacturer the conducted power levels of all higher data rates are <1/4 dB higher than the lowest data rates.		
2. The peak conducted power levels were provided by the EMC lab.		
3. The manufacturer confirmed that the SAR test sample met the output power specifications.		

#### Duty Cycle Measurement



The maximum transmit duty cycle was measured to be 44%.

Applicant:	Garmin International Inc.	FCC ID:	IPH-F3ARGD00	IC:	1792A-F3ARGD00						
Model:	F3ARGD00	DUT Type:	Wrist-worn GPS Device								
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.										
	Page 5 of 32										

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ilac-MRA</b>  <b>ACREDITED</b>
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## 4.0 FLUID DIELECTRIC PARAMETERS

FLUID DIELECTRIC PARAMETERS						
Date: 06/20/2013		Frequency: 2450 MHz			Tissue: Body	
Freq	Test_e	Test_s	Target_e	Target_s	Deviation Permittivity	Deviation Conductivity
2.350	53.04	1.8	52.7	1.95	0.65%	-7.69%
2.360	53.07	1.81	52.7	1.95	0.70%	-7.18%
2.370	52.99	1.81	52.7	1.95	0.55%	-7.18%
2.380	52.75	1.82	52.7	1.95	0.09%	-6.67%
2.390	52.83	1.86	52.7	1.95	0.25%	-4.62%
2.400	52.97	1.88	52.7	1.95	0.51%	-3.59%
2.410	52.84	1.89	52.7	1.95	0.27%	-3.08%
2.412*	52.8	1.89	52.7	1.95	0.19%	-3.08%
2.420	52.68	1.89	52.7	1.95	-0.04%	-3.08%
2.430	52.81	1.92	52.7	1.95	0.21%	-1.54%
2.440	52.87	1.95	52.7	1.95	0.32%	0.00%
2.442*	52.9	1.95	52.7	1.95	0.38%	0.00%
2.450	52.83	1.94	52.7	1.95	0.25%	-0.51%
2.460	52.84	1.95	52.7	1.95	0.27%	0.00%
2.462*	52.8	1.95	52.7	1.95	0.19%	0.00%
2.470	52.64	1.96	52.7	1.95	-0.11%	0.51%
2.480	52.69	1.98	52.7	1.95	-0.02%	1.54%
2.490	52.58	1.99	52.7	1.95	-0.23%	2.05%
2.500	52.52	2.01	52.7	1.95	-0.34%	3.08%
2.510	52.36	2.02	52.7	1.95	-0.65%	3.59%
2.520	52.41	2.06	52.7	1.95	-0.55%	5.64%
2.530	52.54	2.05	52.7	1.95	-0.30%	5.13%
2.540	52.4	2.08	52.7	1.95	-0.57%	6.67%
2.550	52.62	2.07	52.7	1.95	-0.15%	6.15%

\*interpolated using DASY4 software

Test Date	Fluid Type	Ambient Temperature	Fluid Temperature	Fluid Depth	Atmospheric Pressure	Relative Humidity	$\rho$ (Kg/m <sup>3</sup> )
Jun 20	2450 Body	24°C	23.8 °C	≥ 15 cm	100.6 kPa	43%	1000



Date(s) of Evaluation  
Jun. 20, 2013

Test Report Serial No.  
061213IPH-1239S

Test Report Revision No.  
Rev. 1.1 (2nd Release)

Test Report Issue Date  
Jul. 3, 2013

Description of Test(s)  
Specific Absorption Rate

RF Exposure Category  
Gen. Pop. / Uncontrolled



Test Lab Certificate No. 2470.01

## 5.0 SAR MEASUREMENT SUMMARY

### WRIST-WORN SAR EVALUATION RESULTS

WLAN Mode	Test Mode	Test Freq.	Test Chan.	Data Rate	Battery	DUT Position (Side facing phantom)	DUT Distance to Phantom	Conducted Power Before Test	SAR Drift During Test	Measured SAR (10g)														
								W	dB	W/kg														
802.11b	DSSS	2412	1	1	Li-ion	Back Touch	0mm	0.008	-0.788	0.017														
802.11b	DSSS	2442	6	1	Li-ion	Back Touch	0mm	0.009	-0.338	0.019														
802.11b	DSSS	2462	11	1	Li-ion	Back Touch	0mm	0.009	-0.353	0.018														
SAR SAFETY LIMIT(S)					BODY	SPATIAL PEAK		RF EXPOSURE CATEGORY																
FCC 47 CFR 2.1093		Health Canada Safety Code 6			4.0 W/kg	10g average		General Population / Uncontrolled																
Test Date(s):		Jun. 20, 2013																						
Notes																								
1.	Detailed measurement data and plots showing the maximum SAR location of the DUT are reported in Appendix A.																							
2.	The DUT was not required to be evaluated in 802.11g mode or higher data rates because the highest output power channel was < 1/4 dB higher than the corresponding 802.11b channel on the lowest data rate, in accordance with the procedures of FCC KDB 248227 (see reference [9]).																							
3.	The SAR drift of the DUT was measured by the DASY4 system for the duration of the SAR evaluation.																							
4.	The DUT battery was fully charged prior to each SAR evaluation.																							
5.	The fluid temperature remained within +/-2°C from the dielectric parameter measurement to the completion of the SAR test.																							
6.	The dielectric parameters of the simulated tissue mixture were measured prior to the SAR evaluations using a Dielectric Probe Kit and a Network Analyzer.																							

Applicant:	Garmin International Inc.	FCC ID:	IPH-F3ARGD00	IC:	1792A-F3ARGD00		
Model:	F3ARGD00	DUT Type:	Wrist-worn GPS Device				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 7 of 32		

 Celltech Testing and Engineering Services Lab	Date(s) of Evaluation Jun. 20, 2013	Test Report Serial No. 061213IPH-1239S	Test Report Revision No. Rev. 1.1 (2nd Release)	 ILAC-MRA ACCREDITED Test Lab Certificate No. 2470.01
	Test Report Issue Date Jul. 3, 2013	Description of Test(s) Specific Absorption Rate	RF Exposure Category Gen. Pop. / Uncontrolled	

## 6.0 SAR SCALING FOR TUNE-UP TOLERANCE

SCALED SAR							
Test Config.	Freq. (MHz)	Test Ch.	Data Rate	Measured Conducted Power (W)	Maximum Rated Conducted Power (W)	Measured SAR Level 10g (W/kg)	Scaled SAR 10g (W/kg)
WRIST	2442	6	1 Mbps	0.009	0.010	0.019	0.021

## 7.0 SIMULTANEOUS TRANSMISSION ASSESSMENT

802.11b/g + 802.15

These transmitters are not capable of simultaneous transmission. The 802.15 is rated at 2 mW and is below the threshold for standalone SAR evaluation.

Applicant:	Garmin International Inc.	FCC ID:	IPH-F3ARGD00	IC:	1792A-F3ARGD00	
Model:	F3ARGD00	DUT Type:	Wrist-worn GPS Device			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 8 of 32	

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## 8.0 DETAILS OF SAR EVALUATION

1. The DUT was evaluated for Wrist-worn extremity SAR in accordance with the test positions required by FCC KDB 447498 D01v05 (see reference [8]). Based on this the back side of the device at a distance of 0mm to the phantom surface was tested.
2. The DUT was supplied with test mode software that was able to transmit at any selected channel / data-rate required for SAR testing.
3. The DUT was tested with a modulated DSSS signal in 802.11b mode.
4. The battery was fully charged before each SAR evaluation.

## 9.0 SAR EVALUATION PROCEDURES

- a. (i) The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.  
(ii) For body-worn and face-held devices a planar phantom was used.
- b. The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 10mm x 10mm.  
An area scan was determined as follows:
- c. Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
- d. A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.  
A 1g and 10g spatial peak SAR was determined as follows:
- e. Extrapolation is used to determine the values between the dipole center of the probe and the surface of the phantom. This data cannot be measured because the center of the dipole sensors is 1.0 mm away from the probe tip and the distance between the probe and the boundary must be larger than 25% of the probe diameter. The probe diameter is 2.4 mm. In the DASY4 software, the distance between the sensor center and phantom surface is set to 2.0 mm. This provides a distance of 1.0 mm between the probe tip and the surface. The extrapolation of the values between the dipole center and the surface of the phantom was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
- f. Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).
- g. A zoom scan volume of 30 mm x 30 mm x 30 mm (5x5x7 points) centered at the peak SAR location determined from the area scan is used for all zoom scans for devices with a transmit frequency < 800 MHz. Zoom scans for frequencies ≥ 800 MHz are determined with a scan volume of 30 mm x 30 mm x 30 mm (7x7x7 points) to ensure complete capture of the peak spatial-average SAR. When the area scan estimated SAR is < 1.4W/kg, less points can be used for higher frequency zoom scans.

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 9 of 32			

## 10.0 SYSTEM VERIFICATION

Prior to the SAR evaluations, a system check was performed at the planar section of the SAM phantom with a 2450MHz SPEAG validation dipole (see Appendix B) in accordance with the procedures described in IEEE Standard 1528-2003 (see reference [5]) and IEC 62209-2:2010 (see reference [7]). A forward power of 250 mW was applied to the dipole and the system was verified to a tolerance of  $\pm 10\%$  from the system manufacturer's dipole calibration target SAR value (see Appendix E).

### SYSTEM PERFORMANCE CHECK EVALUATION

Test Date	Equiv. Tissue	SAR 10g (W/kg)			Dielectric Constant $\epsilon_r$			Conductivity $\sigma$ (mho/m)			$\rho$ (Kg/m <sup>3</sup> )	Amb. Temp. (°C)	Fluid Temp. (°C)	Fluid Depth (cm)	Humid. (%)	Barom. Press. (kPa)
		Freq. (MHz)	Target	Meas.	Dev.	Target	Meas.	Dev.	Target	Meas.	Dev.					
Jun 20	BODY 2450	5.91 $\pm 10\%$	6.49	+9.8%	52.7 $\pm 5\%$	52.8	+0.2%	1.95 $\pm 5\%$	1.94	-0.5%	1000	24.0	23.8	$\geq 15$	43	100.6
Notes																

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## 11.0 SIMULATED EQUIVALENT TISSUES

The simulated equivalent tissue recipe listed in the table below is derived from the SAR system manufacturer's suggested recipe in the DASY4 manual (see reference [11]). The ingredient percentage may have been adjusted minimally in order to achieve the appropriate target dielectric parameters within the specified tolerance.

2450 MHz SIMULATED TISSUE MIXTURES	
INGREDIENT	2450 MHz Body
Water	69%
Glycol Monobutyl	31%

## 12.0 SAR LIMITS

SAR RF EXPOSURE LIMITS			
FCC 47 CFR 2.1093	Health Canada Safety Code 6	(General Population / Uncontrolled Exposure)	(Occupational / Controlled Exposure)
Spatial Average (averaged over the whole body)		0.08 W/kg	0.4 W/kg
Spatial Peak (averaged over any 1 g of tissue)		1.6 W/kg	8.0 W/kg
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)		4.0 W/kg	20.0 W/kg
The Spatial Average value of the SAR averaged over the whole body.			
The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.			
The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.			
Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.			
Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.			

<b>Applicant:</b>	Garmin International Inc.	<b>FCC ID:</b>	IPH-F3ARGD00	<b>IC:</b>	1792A-F3ARGD00	 <b>GARMIN</b>
<b>Model:</b>	F3ARGD00	<b>DUT Type:</b>	Wrist-worn GPS Device			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 11 of 32

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## 13.0 ROBOT SYSTEM SPECIFICATIONS

<u>Specifications</u>	
<b>Positioner</b>	Stäubli Unimation Corp. Robot Model: RX60L
<b>Repeatability</b>	0.02 mm
<b>No. of axis</b>	6
<u>Data Acquisition Electronic (DAE) System</u>	
<u>Cell Controller</u>	
<b>Processor</b>	AMD Athlon XP 2400+
<b>Clock Speed</b>	2.0 GHz
<b>Operating System</b>	Windows XP Professional
<u>Data Converter</u>	
<b>Features</b>	Signal Amplifier, multiplexer, A/D converter, and control logic
<b>Software</b>	Measurement Software: DASY4, V4.7 Build 80
	Postprocessing Software: SEMCAD, V1.8 Build 186
<b>Connecting Lines</b>	Optical downlink for data and status info.; Optical uplink for commands and clock
<u>DASY4 Measurement Server</u>	
<b>Function</b>	Real-time data evaluation for field measurements and surface detection
<b>Hardware</b>	PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
<b>Connections</b>	COM1, COM2, DAE, Robot, Ethernet, Service Interface
<u>E-Field Probe</u>	
<b>Model</b>	EX3DV4
<b>Serial No.</b>	3600
<b>Construction</b>	Symmetrical design with triangular core
<b>Frequency</b>	10 MHz to 6 GHz
<b>Linearity</b>	$\pm 0.2$ dB (30 MHz to 3 GHz)
<u>Phantom(s)</u>	
<b>Type</b>	SAM V4.0C
<b>Shell Material</b>	Fiberglass
<b>Thickness</b>	$2.0 \pm 0.1$ mm
<b>Volume</b>	Approx. 25 liters

<b>Applicant:</b>	Garmin International Inc.		<b>FCC ID:</b>	IPH-F3ARGD00	<b>IC:</b>	1792A-F3ARGD00	 <b>GARMIN</b>
<b>Model:</b>	F3ARGD00		<b>DUT Type:</b>	Wrist-worn GPS Device			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.		Page 12 of 32				

 Testing and Engineering Services Lab	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 ILAC-MRA ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## 14.0 PROBE SPECIFICATION (EX3DV4)

**Construction:** Symmetrical design with triangular core  
 Built-in shielding against static charges  
 PEEK enclosure material (resistant to organic solvents, e.g. DGBE)

**Calibration:** Basic Broadband Calibration in air: 10-3000 MHz  
 Conversion Factors (CF) for HSL 900 and HSL 1750

**Frequency:** 10 MHz to >6 GHz; Linearity:  $\pm 0.2$  dB (30 MHz to 3 GHz)  
**Directivity:**  $\pm 0.3$  dB in HSL (rotation around probe axis)  
 $\pm 0.5$  dB in tissue material (rotation normal to probe axis)

**Dynamic Range:** 10  $\mu$ W/g to >100 mW/g; Linearity:  $\pm 0.2$  dB  
 (noise: typically < 1  $\mu$ W/g)

**Dimensions:** Overall length: 330 mm (Tip: 20 mm)  
 Tip diameter: 2.5 mm (Body: 12 mm)

**Application:** High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better than 30%.



EX3DV4 E-Field Probe

## 15.0 SAM TWIN PHANTOM V4.0C

The SAM Twin Phantom V4.0C is a fiberglass shell phantom with a 2.0 mm (+/-0.2 mm) shell thickness for left and right head and flat planar area integrated in a wooden table. The shape of the fiberglass shell corresponds to the phantom defined by SCC34-SC2. The device holder positions are adjusted to the standard measurement positions in the three sections (see Appendix G for specifications of the SAM Twin Phantom V4.0C).



SAM Twin Phantom V4.0C

## 16.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. For evaluations of larger devices a Plexiglas platform is attached to the device holder.



Device Holder

<b>Applicant:</b>	Garmin International Inc.		<b>FCC ID:</b>	IPH-F3ARGD00	<b>IC:</b>	1792A-F3ARGD00	
<b>Model:</b>	F3ARGD00		<b>DUT Type:</b>	Wrist-worn GPS Device			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 13 of 32

 Testing and Engineering Services Lab	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## 17.0 TEST EQUIPMENT LIST

TEST EQUIPMENT	ASSET NO.	SERIAL NO.	DATE CALIBRATED	CALIBRATION INTERVAL
DESCRIPTION				
Schmid & Partner DASY4 System	-	-	-	-
-DASY4 Measurement Server	00158	1078	CNR	CNR
-Robot	00046	599396-01	CNR	CNR
-DAE4	00019	353	19-Apr-12	Biennial
-EX3DV4 E-Field Probe	00213	3600	27-Apr-13	Annual
-D2450V2 Validation Dipole	00219	825	25-Apr-12	Triennial
-SAM Twin Phantom V4.0C	00154	1033	CNR	CNR
HP 85070C Dielectric Probe Kit	00033	None	CNR	CNR
Gigatronics 8652A Power Meter	00007	1835272	03-May-12	Biennial
Gigatronics 80701A Power Sensor	00014	1833542	03-May-12	Biennial
Gigatronics 80334A Power Sensor	-	1837001	03-May-12	Biennial
HP 8753ET Network Analyzer	00134	US39170292	26-Apr-12	Biennial
Rohde & Schwarz SMR20 Signal Generator	00006	100104	02-May-12	Biennial
Amplifier Research 5S1G4 Power Amplifier	00106	26235	CNR	CNR
CNR = Calibration Not Required				

Applicant:	Garmin International Inc.	FCC ID:	IPH-F3ARGD00	IC:	1792A-F3ARGD00						
Model:	F3ARGD00	DUT Type:	Wrist-worn GPS Device								
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.										
	Page 14 of 32										



Date(s) of Evaluation  
Jun. 20, 2013

Test Report Serial No.  
061213IPH-1239S

Test Report Revision No.  
Rev. 1.1 (2nd Release)

Test Report Issue Date  
Jul. 3, 2013

Description of Test(s)  
Specific Absorption Rate

RF Exposure Category  
Gen. Pop. / Uncontrolled



## 18.0 MEASUREMENT UNCERTAINTY (IEC 62209-2)

### UNCERTAINTY BUDGET FOR DEVICE EVALUATION (IEC 62209-2:2010)

Source of Uncertainty	IEC 62209-2 Section	Tolerance / Uncertainty ±%	Probability Distribution	Divisor	ci 1g	ci 10g	Standard Uncertainty ±% (1g)	Standard Uncertainty ±% (10g)	$V_i$ or $V_{eff}$
<b>Measurement System</b>									
Probe Calibration (2450 MHz)	7.2.2.1	6.0	Normal	1	1	1	6.0	6.0	∞
Isotropy	7.2.2.2	4.7	Rectangular	1.732050808	1	1	2.7	2.7	∞
Boundary Effect	7.2.2.6	1	Rectangular	1.732050808	1	1	0.6	0.6	∞
Linearity	7.2.2.3	4.7	Rectangular	1.732050808	1	1	2.7	2.7	∞
Detection Limits	7.2.2.5	1	Rectangular	1.732050808	1	1	0.6	0.6	∞
Readout Electronics	7.2.2.7	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	7.2.2.8	0.8	Rectangular	1.732050808	1	1	0.5	0.5	∞
Integration Time	7.2.2.9	2.6	Rectangular	1.732050808	1	1	1.5	1.5	∞
RF Ambient Conditions	7.2.4.5	3	Rectangular	1.732050808	1	1	1.7	1.7	∞
Probe Positioner Mechanical Restrictions	7.2.3.1	0.4	Rectangular	1.732050808	1	1	0.2	0.2	∞
Probe Positioning wrt Phantom Shell	7.2.3.3	2.9	Rectangular	1.732050808	1	1	1.7	1.7	∞
Post-processing	7.2.5	1	Rectangular	1.732050808	1	1	0.6	0.6	∞
<b>Test Sample Related</b>									
Test Sample Positioning	7.2.3.4.3	2.9	Normal	1	1	1	2.9	2.9	12
Device Holder Uncertainty	7.2.3.4.2	3.6	Normal	1	1	1	3.6	3.6	8
Drift of Output Power (meas. SAR drift)	7.2.2.10	5	Rectangular	1.732050808	1	1	2.9	2.9	∞
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty	7.2.3.2	4	Rectangular	1.732050808	1	1	2.3	2.3	∞
SAR Correction Algorithm for deviations in permittivity and conductivity	7.2.4.3	0.97	Normal	1	1	0.81	1.0	0.79	∞
Liquid Conductivity (measured)	7.2.4.3	3.08	Normal	1	0.78	0.71	2.4	2.2	∞
Liquid Permittivity (measured)	7.2.4.3	0.38	Normal	1	0.23	0.26	0.1	0.1	∞
Liquid Permittivity - temp. uncertainty	7.2.4.4	1.23	Rectangular	1.732050808	0.78	0.71	0.6	0.5	∞
Liquid Conductivity - temp. uncertainty	7.2.4.4	0.93	Rectangular	1.732050808	0.23	0.26	0.1	0.1	∞
<b>Combined Standard Uncertainty</b>		7.3.1		RSS			10.11	10.04	
<b>Expanded Uncertainty (95% Confidence Interval)</b>		7.3.2		k=2			20.22	20.09	

Measurement Uncertainty Table in accordance with International Standard IEC 62209-2:2010

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2

Applicant:	Garmin International Inc.	FCC ID:	IPH-F3ARGD00	IC:	1792A-F3ARGD00						
Model:	F3ARGD00	DUT Type:	Wrist-worn GPS Device								
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.										
	Page 15 of 32										

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## 19.0 REFERENCES

- [1] Federal Communications Commission - "Radiofrequency radiation exposure evaluation: portable devices", Rule Part 47 CFR §2.1093.
- [2] Health Canada - "Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz", Safety Code 6: 1999.
- [3] Federal Communications Commission - "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- [4] Industry Canada - "Radio Frequency Exposure Compliance of Radio Communication Apparatus (All Frequency Bands)", Radio Standards Specification RSS-102 Issue 4: March 2010.
- [5] IEEE Standard 1528-2003 - "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques": December 2003.
- [6] International Standard IEC 62209-1:2005 - "Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures."
- [7] International Standard IEC 62209-2 Edition 1.0 2010-03 - "Human exposure to radio frequency fields from hand-held & body-mounted wireless communication devices - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)".
- [8] Federal Communications Commission, Office of Engineering and Technology - "Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies", KDB 447498 D01v05r01: May 2013.
- [9] Federal Communications Commission, Office of Engineering and Technology - "SAR Measurement Procedures for 802.11a/b/g Transmitters"; KDB 248227 D01 v01r02: May 2007.
- [10] Federal Communications Commission, Office of Engineering and Technology - "SAR Measurement Requirements for 100MHz to 6GHz"; KDB 865664 D01v01r01: May 2013.
- [11] Schmid & Partner Engineering AG - DASY4 Manual V4.6, Chapter 17 Application Note, Body Tissue Recipe: Sept. 2005.
- [12] International Standard ISO/IEC 17025:2005 - "General requirements for the competence of testing and calibration laboratories".
- [13] Federal Communications Commission - "Measurements Required: RF Power Output"; Rule Part 47 CFR §2.1046.
- [14] Industry Canada - "General Requirements and Information for the Certification of Radiocommunication Equipment", Radio Standards Specification RSS-Gen Issue 2: June 2007.

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.							

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX A - SAR MEASUREMENT PLOTS

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 17 of 32			

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Date: 06/20/2013

## Extremity - 802.11b - Ch. 1 - 2412 MHz - 1Mbps

**DUT: F3ARGD00; Type: Wrist-worn GPS; Serial: Not Specified**

Program Notes: Ambient Temp: 24C; Fluid Temp: 23.8C; Barometric Pressure: 100.6 kPa; Humidity: 43%

Procedure Notes:

Communication System: WLAN

Frequency: 2412 MHz; Duty Cycle: 1:2.3

Medium: M2450 Medium parameters used (interpolated):  $f = 2412$  MHz;  $\sigma = 1.89$  mho/m;  $\epsilon_r = 52.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

- Probe: EX3DV4 - SN3600; ConvF(6.61, 6.61, 6.61); Calibrated: 26/04/2013
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 19/04/2012
- Phantom: SAM 4.0; Type: Fiberglass; Serial: 1033
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**802.11b - 2412 - 1Mbps/Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.042 mW/g

**802.11b - 2412 - 1Mbps/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 3.76 V/m; Power Drift = -0.788 dB

Peak SAR (extrapolated) = 0.066 W/kg

**SAR(1 g) = 0.036 mW/g; SAR(10 g) = 0.017 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.048 mW/g



DUT orientation: Top edge to the left.

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 18 of 32			

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Date: 06/20/2013

## Extremity - 802.11b - Ch. 6 - 2442 MHz - 1Mbps

**DUT: F3ARGD00; Type: Wrist-worn GPS; Serial: Not Specified**

Program Notes: Ambient Temp: 24C; Fluid Temp: 23.8C; Barometric Pressure: 100.6 kPa; Humidity: 43%

Procedure Notes:

Communication System: WLAN

Frequency: 2442 MHz; Duty Cycle: 1:2.3

Medium: M2450 Medium parameters used (interpolated):  $f = 2442$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 52.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

- Probe: EX3DV4 - SN3600; ConvF(6.61, 6.61, 6.61); Calibrated: 26/04/2013
- Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 19/04/2012
- Phantom: SAM 4.0; Type: Fiberglass; Serial: 1033
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**802.11b - 2442 - 1Mbps/Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.052 mW/g

**802.11b - 2442 - 1Mbps/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 4.24 V/m; Power Drift = -0.338 dB

Peak SAR (extrapolated) = 0.078 W/kg

**SAR(1 g) = 0.042 mW/g; SAR(10 g) = 0.019 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.058 mW/g



DUT orientation: Top edge to the left.

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 19 of 32		



Date(s) of Evaluation  
Jun. 20, 2013

Test Report Serial No.  
061213IPH-1239S

Test Report Revision No.  
Rev. 1.1 (2nd Release)

Test Report Issue Date  
Jul. 3, 2013


Description of Test(s)  
Specific Absorption Rate

RF Exposure Category  
Gen. Pop. / Uncontrolled



Test Lab Certificate No. 2470.01

## Z-axis Scan



Applicant:	Garmin International Inc.		FCC ID:	IPH-F3ARGD00	IC:	1792A-F3ARGD00	
Model:	F3ARGD00		DUT Type:	Wrist-worn GPS Device			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 20 of 32		

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Date: 06/20/2013

## Extremity - 802.11b - Ch. 11 - 2462 MHz - 1Mbps

**DUT: F3ARGD00; Type: Wrist-worn GPS; Serial: Not Specified**

Program Notes: Ambient Temp: 24C; Fluid Temp: 23.8C; Barometric Pressure: 100.6 kPa; Humidity: 43%

Procedure Notes:

Communication System: WLAN

Frequency: 2462 MHz; Duty Cycle: 1:2.3

Medium: M2450 Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 52.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

- Probe: EX3DV4 - SN3600; ConvF(6.61, 6.61, 6.61); Calibrated: 26/04/2013
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 19/04/2012
- Phantom: SAM 4.0; Type: Fiberglass; Serial: 1033
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**802.11b - 2462 - 1Mbps/Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.059 mW/g

**802.11b - 2462 - 1Mbps/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 4.50 V/m; Power Drift = -0.353 dB

Peak SAR (extrapolated) = 0.079 W/kg

**SAR(1 g) = 0.041 mW/g; SAR(10 g) = 0.018 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.054 mW/g



DUT orientation: Top edge to the left.

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 21 of 32		

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## APPENDIX B - SYSTEM PERFORMANCE CHECK PLOTS

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 22 of 32			

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Date: 06/20/2013

## System Performance Check - 2450 MHz Dipole - Body

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 825; Calibrated: 25/04/2012**

Program Notes: Ambient Temp: 24C; Fluid Temp: 23.8C; Barometric Pressure: 100.6 kPa; Humidity: 43%

Procedure Notes:

Communication System: CW

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: M2450 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.94$  mho/m;  $\epsilon_r = 52.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

- Probe: EX3DV4 - SN3600; ConvF(6.61, 6.61, 6.61); Calibrated: 26/04/2013
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 19/04/2012
- Phantom: SAM 4.0; Type: Fiberglass; Serial: 1033
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


**2450 MHz Dipole d=10mm P=250mW/Area Scan (6x10x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (measured) = 15.5 mW/g

**2450 MHz Dipole d=10mm P=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 96.1 V/m; Power Drift = -0.027 dB

Peak SAR (extrapolated) = 27.9 W/kg

**SAR(1 g) = 13.9 mW/g; SAR(10 g) = 6.49 mW/g**

Maximum value of SAR (measured) = 18.3 mW/g




<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>			
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 23 of 32		

 Testing and Engineering Services Lab	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 ILAC-MRA ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## Z-axis Scan



<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>		
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 24 of 32			

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 25 of 32			

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## 2450 MHz Body

Celltech Labs Inc.

Test Result for UIM Dielectric Parameter

20/Jun/2013

Freq Frequency(GHz)

FCC\_eB FCC Limits for Body Epsilon

FCC\_sB FCC Limits for Body Sigma

Test\_e Epsilon of UIM

Test\_s Sigma of UIM

Freq	FCC_eB	FCC_sB	Test_e	Test_s
2.3500	52.83	1.85	53.04	1.80
2.3600	52.82	1.86	53.07	1.81
2.3700	52.81	1.87	52.99	1.81
2.3800	52.79	1.88	52.75	1.82
2.3900	52.78	1.89	52.83	1.86
2.4000	52.77	1.90	52.97	1.88
2.4100	52.75	1.91	52.84	1.89
2.4200	52.74	1.92	52.68	1.89
2.4300	52.73	1.93	52.81	1.92
2.4400	52.71	1.94	52.87	1.95
2.4500	52.70	1.95	52.83	1.94
2.4600	52.69	1.96	52.84	1.95
2.4700	52.67	1.98	52.64	1.96
2.4800	52.66	1.99	52.69	1.98
2.4900	52.65	2.01	52.58	1.99
2.5000	52.64	2.02	52.52	2.01
2.5100	52.62	2.04	52.36	2.02
2.5200	52.61	2.05	52.41	2.06
2.5300	52.60	2.06	52.54	2.05
2.5400	52.59	2.08	52.40	2.08
2.5500	52.57	2.09	52.62	2.07

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 26 of 32			

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX E - DIPOLE CALIBRATION

<b>Applicant:</b>	<b>Garmin International Inc.</b>			<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>			<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.			Page 30 of 32					



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Celltech**

Certificate No: **D2450V2-825\_Apr12**

## CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 825**

Calibration procedure(s) **QA CAL-05.v8**  
 Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **April 25, 2012**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	05-Oct-11 (No. 217-01451)	Oct-12
Power sensor HP 8481A	US37292783	05-Oct-11 (No. 217-01451)	Oct-12
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.2 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ES3DV3	SN: 3205	30-Dec-11 (No. ES3-3205_Dec11)	Dec-12
DAE4	SN: 601	04-Jul-11 (No. DAE4-601_Jul11)	Jul-12
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-11)	In house check: Oct-12

Calibrated by: Name **Jeton Kastrati** Function **Laboratory Technician**

Approved by: Name **Katja Pokovic** Function **Technical Manager**

Issued: April 25, 2012

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

<b>DASY Version</b>	DASY5	V52.8.1
<b>Extrapolation</b>	Advanced Extrapolation	
<b>Phantom</b>	Modular Flat Phantom	
<b>Distance Dipole Center - TSL</b>	10 mm	with Spacer
<b>Zoom Scan Resolution</b>	dx, dy, dz = 5 mm	
<b>Frequency</b>	2450 MHz ± 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
<b>Nominal Head TSL parameters</b>	22.0 °C	39.2	1.80 mho/m
<b>Measured Head TSL parameters</b>	(22.0 ± 0.2) °C	39.6 ± 6 %	1.81 mho/m ± 6 %
<b>Head TSL temperature change during test</b>	< 0.5 °C	----	----

## SAR result with Head TSL

<b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b>	Condition	
SAR measured	250 mW input power	12.7 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	50.8 mW / g ± 17.0 % (k=2)

<b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b>	Condition	
SAR measured	250 mW input power	5.90 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	23.6 mW / g ± 16.5 % (k=2)

## Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
<b>Nominal Body TSL parameters</b>	22.0 °C	52.7	1.95 mho/m
<b>Measured Body TSL parameters</b>	(22.0 ± 0.2) °C	52.4 ± 6 %	1.98 mho/m ± 6 %
<b>Body TSL temperature change during test</b>	< 0.5 °C	----	----

## SAR result with Body TSL

<b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b>	Condition	
SAR measured	250 mW input power	12.7 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	50.4 mW / g ± 17.0 % (k=2)

<b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b>	Condition	
SAR measured	250 mW input power	5.91 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	23.5 mW / g ± 16.5 % (k=2)

## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	$53.0 \Omega + 5.5 \text{ j} \Omega$
Return Loss	- 24.3 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	$50.4 \Omega + 6.1 \text{ j} \Omega$
Return Loss	- 24.3 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.159 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	December 11, 2008

# DASY5 Validation Report for Head TSL

Date: 25.04.2012

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 825**

Communication System: CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.81$  mho/m;  $\epsilon_r = 39.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.45, 4.45, 4.45); Calibrated: 30.12.2011;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.07.2011
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

## Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid:  $dx=5$  mm,  $dy=5$  mm,  $dz=5$  mm

Reference Value = 99.271 V/m; Power Drift = 0.05 dB


Peak SAR (extrapolated) = 26.216 mW/g

**SAR(1 g) = 12.7 mW/g; SAR(10 g) = 5.9 mW/g**

Maximum value of SAR (measured) = 16.5 mW/g



## Impedance Measurement Plot for Head TSL



# DASY5 Validation Report for Body TSL

Date: 25.04.2012

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 825**

Communication System: CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 52.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.26, 4.26, 4.26); Calibrated: 30.12.2011;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.07.2011
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

## Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.157 V/m; Power Drift = -0.00 dB


Peak SAR (extrapolated) = 25.807 mW/g

**SAR(1 g) = 12.7 mW/g; SAR(10 g) = 5.91 mW/g**

Maximum value of SAR (measured) = 16.7 mW/g



## Impedance Measurement Plot for Body TSL



 Testing and Engineering Services Lab	<u>Date:</u> Jun 17, 2013	<u>Revision No.</u> Rev. 1.0
	<b>2450 MHz Dipole Extended Calibration</b>	

Dipole: D2450V2  
 Serial Number: 825  
 Last Calibrated: Apr. 25, 2012



<b>Antenna Parameters with Head TSL</b>						
	Impedance Real (ohms)	Deviation from cal	Impedance Imaginary (ohms)	Deviation from cal	Return Loss (dB)	Deviation from Cal
<b>Last Calibration</b>	53.0	-	+5.5	-	-24.3	-
<b>Extended Cal</b>						

<b>Antenna Parameters with Body TSL</b>						
	Impedance Real (ohms)	Deviation from cal (ohms)	Impedance Imaginary (ohms)	Deviation from cal (ohms)	Return Loss (dB)	Deviation from Cal (%)
<b>Last Calibration</b>	50.4	-	+6.1	-	-24.3	-
<b>Extended Cal</b> <b>Jun 17, 2013</b>	49.0	1.4	+7.9	1.8	-21.3	12.3%

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## APPENDIX F - PROBE CALIBRATION

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 31 of 32			

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Celltech**

Certificate No: **EX3-3600\_Apr13**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3600**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-14.v3, QA CAL-23.v4, QA CAL-25.v4**  
Calibration procedure for dosimetric E-field probes

Calibration date: **April 26, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	31-Jan-13 (No. DAE4-660_Jan13)	Jan-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Calibrated by:	Name <b>Claudio Leubler</b>	Function <b>Laboratory Technician</b>	Signature 
Approved by:	Name <b>Katja Pokovic</b>	Function <b>Technical Manager</b>	Signature 

Issued: April 27, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

TS	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\theta$	$\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\theta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)x,y,z = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCPx,y,z**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to  $NORM<sub>x,y,z</sub> * ConvF$  whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe EX3DV4

**SN:3600**

Manufactured: January 10, 2007  
Calibrated: April 26, 2013

**Calibrated for DASY/EASY Systems**  
(Note: non-compatible with DASY2 system!)

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3600

### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	0.48	0.49	0.40	$\pm 10.1\%$
DCP (mV) <sup>B</sup>	99.8	97.4	99.2	

### Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc <sup>E</sup> (k=2)
0	CW	X	0.0	0.0	1.0	0.00	127.7	$\pm 3.5\%$
		Y	0.0	0.0	1.0		153.3	
		Z	0.0	0.0	1.0		154.7	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3600

### Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>c</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
1810	40.0	1.40	6.98	6.98	6.98	0.56	0.72	± 12.0 %
1950	40.0	1.40	6.75	6.75	6.75	0.75	0.63	± 12.0 %
2450	39.2	1.80	6.25	6.25	6.25	0.34	0.89	± 12.0 %

<sup>c</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3600

### Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) <sup>c</sup>	Relative Permittivity <sup>f</sup>	Conductivity (S/m) <sup>f</sup>	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
1810	53.3	1.52	7.02	7.02	7.02	0.52	0.75	± 12.0 %
1950	53.3	1.52	7.07	7.07	7.07	0.36	0.88	± 12.0 %
2450	52.7	1.95	6.61	6.61	6.61	0.73	0.57	± 12.0 %
5200	49.0	5.30	4.00	4.00	4.00	0.45	1.90	± 13.1 %
5500	48.6	5.65	3.58	3.58	3.58	0.45	1.90	± 13.1 %
5800	48.2	6.00	3.64	3.64	3.64	0.50	1.90	± 13.1 %

<sup>c</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>f</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$

$f=600$  MHz, TEM





$f=1800$  MHz, R22




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

## Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f = 900 \text{ MHz}$ )




Uncertainty of Linearity Assessment:  $\pm 0.6\% (k=2)$

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900 \text{ MHz}$



## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3600

### Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	34.7
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	2 mm

 <b>Celltech</b> <small>Testing and Engineering Services Lab</small>	<u>Date(s) of Evaluation</u> Jun. 20, 2013	<u>Test Report Serial No.</u> 061213IPH-1239S	<u>Test Report Revision No.</u> Rev. 1.1 (2nd Release)	 <b>ILAC-MRA</b> ACCREDITED
	<u>Test Report Issue Date</u> Jul. 3, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## APPENDIX G - SAM PHANTOM CERTIFICATE OF CONFORMITY

<b>Applicant:</b>	<b>Garmin International Inc.</b>		<b>FCC ID:</b>	<b>IPH-F3ARGD00</b>	<b>IC:</b>	<b>1792A-F3ARGD00</b>	 <b>GARMIN</b>	
<b>Model:</b>	<b>F3ARGD00</b>		<b>DUT Type:</b>	<b>Wrist-worn GPS Device</b>				
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 32 of 32			

# Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

## Certificate of conformity / First Article Inspection

Item	SAM Twin Phantom V4.0
Type No	QD 000 P40 BA
Series No	TP-1002 and higher
Manufacturer / Origin	Untersee Composites Hauptstr. 69 CH-8559 Fruthwilen Switzerland

### Tests

The series production process used allows the limitation to test of first articles.

Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 BA, Serial No. TP-1006. Certain parameters have been retested using further series units (called samples).

Test	Requirement	Details	Units tested
Shape	Compliance with the geometry according to the CAD model.	IT'IS CAD File (*)	First article, Samples
Material thickness	Compliant with the requirements according to the standards	2mm +/- 0.2mm in specific areas	First article, Samples
Material parameters	Dielectric parameters for required frequencies	200 MHz – 3 GHz Relative permittivity < 5 Loss tangent < 0.05	Material sample TP 104-5
Material resistivity	The material has been tested to be compatible with the liquids defined in the standards	Liquid type HSL 1800 and others according to the standard.	Pre-series, First article

### Standards

- [1] CENELEC EN 50361
- [2] IEEE P1528-200x draft 6.5
- [3] IEC PT 62209 draft 0.9

(\*) The IT'IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of [1] and [3].

### Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standard [1] and draft standards [2] and [3].

Date

18.11.2001

Signature / Stamp

  
Schmid & Partner  
Engineering AG

Zeughausstrasse 43, CH-8004 Zurich  
Tel. +41 1 245 97 00, Fax +41 1 245 97 79