



FCC / ISED Test Report

FOR:

Garmin International, Inc.

Model Name:

GMN-02245

Product Description:

LTE/Wi-Fi Datalink and Data Storage System

FCC ID: IPH-03788

IC ID: 1792A-03788

Applied Rules and Standards:

47 CFR Part 15.247 (DTS)

RSS-247 Issue 2 (DTS) & RSS-Gen Issue 5

REPORT #: EMC_GARMI-094-21001_15.247_BT_DTS_R1

DATE: 2021-11-12



A2LA Accredited

IC recognized #
3462B-1

CABID: US0187

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: contact@cetecom.com • <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571



TABLE OF CONTENTS

1 ASSESSMENT 3

2 ADMINISTRATIVE DATA..... 4

2.1 IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT..... 4

2.2 IDENTIFICATION OF THE CLIENT 4

2.3 IDENTIFICATION OF THE MANUFACTURER 4

3 EQUIPMENT UNDER TEST (EUT) 5

3.1 EUT SPECIFICATIONS 5

3.2 EUT SAMPLE DETAILS 6

3.3 TEST SAMPLE CONFIGURATION 6

3.4 JUSTIFICATION FOR WORST CASE MODE OF OPERATION 6

4 SUBJECT OF INVESTIGATION 6

5 MEASUREMENT RESULTS SUMMARY 7

6 MEASUREMENT UNCERTAINTY 8

6.1 ENVIRONMENTAL CONDITIONS DURING TESTING: 8

6.2 DATES OF TESTING: 8

7 MEASUREMENT PROCEDURES..... 9

7.1 RADIATED MEASUREMENT 9

8 TEST RESULT DATA..... 12

8.1 RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS 12

9 CONDUCTED OUTPUT POWER VERIFICATION 26

10 TEST SETUP PHOTOS..... 27

11 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING 27

12 REVISION HISTORY 28



1 Assessment

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and the relevant ISED Canada standard RSS-247.

No deviations were ascertained.

Company	Description	Model #
Garmin International, Inc.	LTE/Wi-Fi Datalink and Data Storage System	GMN-02245

Responsible for Testing Laboratory:

2021-11-12	Compliance	Kevin Wang (EMC Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2021-11-12	Compliance	Yuchan Lu (Test Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Kevin Wang
Responsible Project Leader:	Sangeetha Sivaraman

2.2 Identification of the Client

Client's Name:	Garmin International, Inc.
Street Address:	1200 East 151st Street
City/Zip Code:	Olathe, KS 66062
Country:	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	Same as Client
Manufacturers Address:	-----
City/Zip Code	-----
Country	-----

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Model No:	GMN-02245
HW Version :	Ver 11
SW Version :	1.40
FCC-ID:	IPH-03788
IC-ID:	1792A-03788
HVIN:	GMN-02245
PMN:	GDL 60
Product Description:	LTE/Wi-Fi Datalink and Data Storage System
Frequency Range / number of channels:	<u>BLE:</u> Module Name: Texas Instruments Module Number: WiLink WL1835MOD FCC ID: Z64-WL18SBMOD IC ID: 4511-WL18SBMOD Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels
Type(s) of Modulation:	Bluetooth Low Energy, using Dynamic Sequence Spread Spectrum with GFSK modulation.
Modes of Operation:	Bluetooth LE in both advertising and connected mode of operation
Antenna Information as declared:	<ul style="list-style-type: none"> • 5 dBi
Max. Peak Output Power:	Conducted Power 9.99 dBm
Power Supply/ Rated Operating Voltage Range:	Vmin: 9 VDC/ Vnom: 24 VDC / Vmax: 32 VDC
Operating Temperature Range:	-40°C to 70 °C
Other Radios included in the device:	<ul style="list-style-type: none"> ❖ <u>WLAN</u> <ul style="list-style-type: none"> • Manufacture: Texas Instruments • Module name/number: WiLink WL1807MOD • FCC ID: Z64-WL18DBMOD • IC ID: 4511-WL18DBMOD ❖ <u>LTE</u> <ul style="list-style-type: none"> • Manufacture: Quectel • Module name/number: EG25-G

	<ul style="list-style-type: none"> • FCC ID: XMR201903EG25G • IC ID: 10224A-201903EG25G ❖ <u>Bluetooth, WLAN</u> <ul style="list-style-type: none"> • Manufacture: Texas Instruments • Module name/number: WiLink 1835
Sample Revision:	<input type="checkbox"/> Prototype Unit; <input type="checkbox"/> Production Unit; <input checked="" type="checkbox"/> Pre-Production

3.2 EUT Sample details

EUT #	Sample Number	HW Version	SW Version	Notes/Comments
1	67H000367	Ver 11	1.40	Radiated Emissions

3.3 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT#1	Special commands through command window used to configure the Bluetooth LE radio to low, mid and high channels and co-transmitting with LTE Band 4 mid Channel (1732.5 MHz) provided by the client that will not be available to the end user. For radiated measurements, the external antenna was connected.

3.4 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on low, mid and high channels, and co-transmitting with LTE Band 4 mid Channel (1732.5 MHz). Based on client declaration, the EUT was configured to the highest duty cycle and maximum output power.

For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 of ISED Canada.

Testing procedures are based on 558074 D01 DTS Meas Guidance v05r02 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.247(a)(1) RSS-247 5.2(1)	Emission Bandwidth	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Complies Note1
§15.247(e) RSS-247 5.2(2)	Power Spectral Density	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Complies Note1
§15.247(b)(1) RSS-247 5.4(4)	Maximum Conducted Output Power and EIRP	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Complies Note1
§15.247(d) RSS-247 5.5	Band edge compliance Unrestricted Band Edges	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Complies Note1
§15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band edge compliance Restricted Band Edges	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Complies Note1
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions- Radiated	Nominal	BTLE	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Complies Note1
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Complies

Note: NA= Not Applicable; NP= Not Performed.

Note1: Leveraged from module certification Texas Instruments WiLink WL1835MOD (FCC ID: Z64-WL18SBMOD, IC ID: 4511-WL18SBMOD)

6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=1.

Radiated measurement

9 kHz to 30 MHz	±2.5 dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	±2.0 dB (Biconilog Antenna)
1 GHz to 40 GHz	±2.3 dB (Horn Antenna)

Conducted measurement

150 kHz to 30 MHz	±0.7 dB (LISN)
-------------------	----------------

RF conducted measurement	±0.5 dB
--------------------------	---------

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3 dB to the limit.

6.1 Environmental Conditions during Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

6.2 Dates of Testing:


9/9/2021-9/15/2020

7 Measurement Procedures


7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



Radiated Emissions Test Setup 30MHz-1GHz Measurements



Radiated Emissions Test Setup above 1GHz Measurements



7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB μ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:

Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

8 Test Result Data

8.1 Radiated Transmitter Spurious Emissions and Restricted Bands

8.1.1 Measurement according to ANSI C63.10 (2013)

Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak

- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)

- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz

- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing at distance other than the specified in the standard, the limit conversion is calculated by using 40 dB/decade extrapolation factor as follow: Conversion factor (CF) = $40 \log (D/d) = 40 \log (300m / 3m) = 80dB$

8.1.2 Limits:

FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



FCC §15.209 & RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (µV/m)	Measurement Distance (m)	Field strength @ 3m (dBµV/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dBµV/m
88–216	150	3	43.5 dBµV/m
216–960	200	3	46 dBµV/m
Above 960	500	3	54 dBµV/m

FCC §15.205 & RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

*PEAK LIMIT= 74 dBµV/m

*AVG. LIMIT= 54 dBµV/m


8.1.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
23° C	1	GFSK continuous fixed channel	24 VDC

8.1.4 Measurement result:

Plot #	Channel #	Scan Frequency	Limit	Result
1-3	Low	30 MHz – 18 GHz	See section 8.1.2	Pass
4-8	Mid	9 kHz – 26 GHz	See section 8.1.2	Pass
9-11	High	30 MHz – 18 GHz	See section 8.1.2	Pass

8.1.5 Measurement Plots:









Plot #3 Radiated Emissions: 3-18 GHz

Modulation: BT LE

Channel: Low



- Preview Result 2-AVG
- Preview Result 1-PK+
- Critical_Freqs AVG
- Critical_Freqs PK+
- FCC 15.209 PK at 3m
- FCC 15.209 AVG at 3m
- Final_Result PK+
- Final_Result CAV




Plot #5 Radiated Emissions: 30 MHz – 1GHz

Modulation: BT LE


Channel: Mid


Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
149.957	30.84	43.50	12.66	500.0	120.000	117.0	V	221.0	18.2
174.983	32.49	43.50	11.01	500.0	120.000	221.0	H	288.0	15.1
224.970	31.37	46.02	14.65	500.0	120.000	117.0	H	86.0	12.9
249.964	25.31	46.02	20.71	500.0	120.000	125.0	H	27.0	17.9



— Preview Result 2-AVG
 — Preview Result 1-PK+
 — FCC 15.209 QP at 3m
 ◆ Final_Result C










Plot #9 Radiated Emissions: 30 MHz – 1GHz

Modulation: BT LE


Channel: High


Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
149.957	30.57	43.50	12.93	500.0	120.000	117.0	V	220.0	18.2
174.983	32.33	43.50	11.17	500.0	120.000	165.0	H	278.0	15.1
224.970	31.49	46.02	14.53	500.0	120.000	134.0	H	88.0	12.9
249.964	22.91	46.02	23.11	500.0	120.000	134.0	H	16.0	17.9
919.102	28.43	46.02	17.59	500.0	120.000	117.0	V	175.0	25.2




Preview Result 2-AVG Preview Result 1-PK+ FCC 15.209 QP at 3m Final_Result C







9 Conducted output power verification



low

Date: 11.NOV.2021 12:31:55

10 Test setup photos

Setup photos are included in supporting file name: "EMC_GARMI_094_21001_Setup_Photos_R1.pdf"

11 Test Equipment And Ancillaries Used For Testing

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
ACTIVE LOOP ANTENNA	ETS LINDGREN	6507	00161344	2 YEARS	10/30/2020
BILOG ANTENNA	ETS.LINDGREN	3142E	00166067	2 YEARS	03/12/2020
HORN ANTENNA	EMCO	3115	00035114	2 YEARS	08/10/2020
HORN ANTENNA	ETS.LINDGREN	3117	00215984	2 YEARS	01/31/2021
HORN ANTENNA	ETS.LINDGREN	3116	00070497	2 YEARS	11/23/2020
TEST RECEIVER	R&S	ESU40	100251	2 YEARS	09/13/2021
COMPACT DIGITAL BAROMETER	CONTROL COMPANY	10510-922	200236891	2 YEARS	04/13/2020
DIGITAL THRMOMETER	CONTROL COMPANY	36934-164	181230565	3 YEARS	01/10/2019

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.



12 Revision History

Date	Report Name	Changes to report	Report prepared by
2021-11-12	EMC_GARMI_094_21001_15.247_BT_DTS	Initial version	Yuchan Lu
2021-11-12	EMC_GARMI_094_21001_15.247_BT_DTS_R1	Added conducted output power verification	Yuchan Lu

<<The End>>