



FCC / ISED Test Report

FOR:

Garmin International, Inc.

Model Name:

A03949

Product Description:

Digital transmission system transceiver

FCC ID: IPH-03949

IC ID: 1792A-03949

Per:

47 CFR: Part 24, Part 27

RSS-130 Issue 2; RSS-133 Issue 6; RSS-139 Issue 3

REPORT #: EMC_GARMI-077-20001_FCC_24_27_ISED_R1

DATE: 2020-11-19



A2LA Accredited

IC recognized #
3462B-2
CABID: US0187

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	ASSESSMENT	3
2	ADMINISTRATIVE DATA	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER	4
3	EQUIPMENT UNDER TEST (EUT).....	5
3.1	EUT SPECIFICATIONS	5
3.2	EUT SAMPLE DETAILS	6
3.3	ACCESSORY EQUIPMENT DETAILS.....	6
3.4	SUPPORT EQUIPMENT.....	6
3.5	TEST SAMPLE CONFIGURATION	6
3.6	MODE OF OPERATION DETAILS	7
3.7	JUSTIFICATION FOR WORST CASE MODE OF OPERATION	7
4	SUBJECT OF INVESTIGATION	8
4.1	DATES OF TESTING:.....	8
4.2	MEASUREMENT UNCERTAINTY.....	8
4.3	ENVIRONMENTAL CONDITIONS DURING TESTING:.....	8
5	MEASUREMENT PROCEDURES	9
5.1	RADIATED MEASUREMENT	9
5.2	SAMPLE CALCULATIONS FOR FIELD STRENGTH MEASUREMENTS.....	11
6	MEASUREMENT RESULTS SUMMARY	12
6.1	FCC 24, RSS-133:.....	12
6.2	FCC 27, RSS-130, RSS-139:	13
7	TEST RESULT DATA	14
7.1	E(I)RP.....	14
7.2	RADIATED SPURIOUS EMISSIONS.....	15
8	TEST SETUP PHOTO.....	47
9	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING	47
10	REVISION HISTORY	48

1 Assessment

The following device as further described in section 3 of this report was evaluated for radiated spurious emissions in simultaneous transmission of cellular and unlicensed radios according to criteria specified in the Code of Federal Regulations Title 47 parts 24, 27 and Industry Canada Radio Standard Specifications RSS: 130 Issue 2, 133 Issue 6 and 139 Issue 3.

Company	Description	Model #
Garmin International, Inc.	Digital transmission system transceiver	A03949

No deficiencies were ascertained.

Responsible for Testing Laboratory:

2020-11-19	Compliance	Cindy Li (Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2020-11-19	Compliance	Yuchan Lu (Test Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Lab Manager:	Cindy Li
Responsible Project Leader:	Sangeetha Sivaraman

2.2 Identification of the Client

Client's Name:	Garmin International, Inc.
Street Address:	1200 East 151st Street
City/Zip Code	Olathe, KS 66062
Country	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	Garmin Corporation
Manufacturers Address:	No. 68, Zhangshu 2nd Rd., Xizhi Dist.,
City/Zip Code	New Taipei City 221,
Country	TAIWAN, R.O.C.

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Hardware Version Identification Number (HVIN):	A03949
Product Marketing Name (PMN):	N/A
Antenna Information as declared:	Monopole antenna Antenna gains: • LTE Band 2: -1.5 dBi • LTE Band 4: -0.6 dBi • LTE Band 12: -10.3 dBi
Other Radios included in the device:	❖ <u>WLAN</u> • Manufacture: Microchip • Module name/number: ATWILC1000 ❖ <u>Classic BT, BLE, ANT</u> • Manufacture: Cypress • Module name/number: BCM20719 ❖ <u>NFC</u> • Manufacture: NXP • Module name/number: SN100T ❖ <u>GNSS/GPS</u> • Manufacture: Garmin proprietary
Power Supply/ Rated Operating Voltage Range:	Vmin: 3.5 VDC/ Vnom: 3.9 VDC / Vmax: 4.35 VDC
Operating Temperature Range:	Low -20°C, Nominal 25°C, High 60°C
Sample Revision	☐ Prototype Unit; ☐ Production Unit; ☒ Pre-Production
EUT Dimensions(mm):	253 x 45 x 15
Weight(grams):	49
EUT Diameter	☒ < 60 cm ☐ Other _____

Module Information	
Module Name:	Murata
Model Number:	LBAD0XX1SC
FCC ID:	HSW-TY1SC
IC ID:	4492A-TY1SC

3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	3340894753	1	1.13	Radiated Measurement

3.3 Accessory Equipment details

AE #	Type	Manufacture	Model	P/N
1	DC Charging Cable	-	-	-

3.4 Support Equipment

SE #	Description
1	AC/DC Converter, Manufacture: PHIHONG, Model: PSAI05R-050Q
2	Laptop, Dell Latitude 7490

3.5 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT# 1 +AE# 1	Worst Case

3.6 Mode of Operation details

Mode of Operation	Description of Operating modes	Additional Information
Op. 1	Cellular Transmission	Cellular was tested on CAT M1 Low, Mid, High Channels at the maximum power, and co-transmitting with WLAN mid channel. For radiated measurements, the internal antenna was connected.

3.7 Justification for Worst Case Mode of Operation

During the testing process the EUT was tested with transmitter sets on CAT M1 low, mid and high channels and co-transmitting with WLAN mid channel at the maximum power transmission.

For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the evaluation conducted by CETECOM Inc. is to support a request for new equipment authorization under **FCC ID: IPH-03949/ IC ID: 1792A-03949**.

The pre-certified module to be integrated (LBAD0XX1SC) as described in Section 3, Radiated Spurious Emissions test was performed. Results have been checked to meet limits per Code of Federal Regulations Title 47 parts 24, 27 and Industry Canada Radio Standard Specifications RSS: 130 Issue 2, 133 Issue 6 and 139 Issue 3.

The conducted module test data that can be obtained under the **FCC Filing ID: HSW-TY1SC; IC Filing ID: 4492A-TY1SC** is applicable for the host described in section 3.

4.1 Dates of Testing:

09/02/2020 – 09/04/2020

4.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=1.

Radiated measurement

9 kHz to 30MHz	±2.5 dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	±2.0 dB (Biconilog Antenna)
1 GHz to 40 GHz	±2.3 dB (Horn Antenna)

4.3 Environmental Conditions during Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25°C
- Relative humidity: 40-60%


Deviating test conditions are indicated at individual test description where applicable.



5 Measurement Procedures

Testing is performed according to the guidelines provided in FCC publication (KDB) 971168 D01 v03 – “Measurement Guidance for Certification of Licensed Digital Transmitters” and according to ANSI C63.26 as detailed below.

5.1 Radiated Measurement

- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.





5.2 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

- Measured reading in dB μ V
- Cable Loss between the receiving antenna and SA in dB and
- Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$\text{FS (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:

Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

6 Measurement Results Summary

6.1 FCC 24, RSS-133:

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	Fail	NA	NP	Result
§2.1046; §24.232 (a)	RF Output Power	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1055; §24.235	Frequency Stability	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1049; §24.238	Occupied Bandwidth	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1051; §24.238	Band Edge Compliance	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1051; §24.238	Conducted Spurious Emissions	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1053; §24.238(a); RSS-133 Issue 6-6.5.1;	Radiated Spurious Emissions	Nominal	Op.1	■	☐	☐	☐	Complies

Note 1: NA= Not Applicable; NP= Not Performed.

Note 2: Leveraged from module certification FCC ID: HSW-TY1SC

6.2 FCC 27, RSS-130, RSS-139:

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	Fail	NA	NP	Result
§2.1046; §27.50 (d)	RF Output Power	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1055; §27.54	Frequency Stability	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1049; §27.53	Occupied Bandwidth	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1051; §27.53	Band Edge Compliance	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1051; §27.53	Conducted Spurious Emissions	Nominal	-	☐	☐	☐	■	Note 1 Note 2
§2.1053; §27.53(g); §27.53(h); RSS-130 Issue 2-4.6; RSS-139 Issue 3-6.6;	Radiated Spurious Emissions	Nominal	Op.1	■	☐	☐	☐	Complies

Note 1: NA= Not Applicable; NP= Not Performed.

Note 2: Leveraged from module certification FCC ID: HSW-TY1SC

7 Test Result Data

7.1 E(I)RP

Band	Frequency Range (MHz)	Power conducted (W)	Emission Designator	Antenna Gain + Cable loss (dBi)	gain linear	EIRP ¹ (W)	ERP ¹ (W)	Frequency deviation (ppm)	Limit ERP (W)
LTE 2	1850.0 – 1910.0	0.191	1M12G7D	-1.5	0.708	0.135	-	2.5	2
LTE 2	1850.0 – 1910.0	0.191	990KW7D	-1.5	0.708	0.135	-	2.5	2
LTE 4	1710.0 – 1755.0	0.198	1M12G7D	-0.6	0.871	0.172	-	2.5	1
LTE 4	1710.0 – 1755.0	0.188	960KW7D	-0.6	0.871	0.164	-	2.5	1
LTE 12	699.0 – 716.0	0.122	1M12G7D	-10.3	0.093	0.011	0.007	2.5	3
LTE 12	699.0 – 716.0	0.094	960KW7D	-10.3	0.093	0.009	0.005	2.5	3

Note 1: E(I)RP are calculated from maximum power in grant of cellular module LBAD0XX1SC adding the maximum gain of the utilized cellular antenna per operational description.

7.2 Radiated Spurious Emissions

7.2.1 Measurement according to FCC: CFR 47 Part 2.1053; CFR Part 24.238 and Part 27.53 utilizing KDB 971168 D01 Power Meas License Digital Systems v03, and according to ANSI C63.26 2017

Spectrum Analyzer Settings for FCC 24 and 27

Frequency Range	30MHz – 1 GHz	1 – 2.7 GHz	2.7 – 18 GHz	18 – 19.1 GHz
Resolution Bandwidth	100 kHz	1 MHz	1 MHz	1 MHz
Video Bandwidth	100 kHz	1 MHz	1 MHz	1 MHz
Detector	Peak	Peak	Peak	Peak
Trace Mode	Max Hold	Max Hold	Max Hold	Max Hold
Sweep Time	Auto	Auto	Auto	Auto

7.2.2 Limits:

- FCC Part 24.238(a), Part 27.53 (g) and Part 27.53 (h)
- RSS-130 Issue 2-4.6, RSS-133 Issue 6 6.5.1, RSS-139 Issue 3 6.6

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB = (-13dBm)

7.2.3 Test conditions and setup:


Ambient Temperature (C)	EUT operating mode	Power Input
22	Op. 1	110 VAC

7.2.4 Measurement Plots:

LTE Band 2

Plot # 1 Radiated Emissions: 30 MHz - 1 GHz


Channel: Low



— Preview Result 1-PK+ * Critical_Freqs PK+ — FCC Licensed -13dBm ◆ Final_Result RM

Plot # 2 Radiated Emissions: 1 GHz - 3 GHz

Channel: Low




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM

Plot # 3 Radiated Emissions: 3 GHz - 18 GHz

Channel: Low

Final Result


Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Comment
3702.500	-48.19	-13.00	35.19	500.0	1000.000	164.0	H	189.0	-101.7	
5553.500	-60.23	-13.00	47.23	500.0	1000.000	227.0	H	1.0	-99.7	
7405.000	-59.53	-13.00	46.53	500.0	1000.000	249.0	V	314.0	-95.5	





Plot # 4 Radiated Emissions: 9 kHz - 30 MHz


Channel: Mid





Plot # 5 Radiated Emissions: 30 MHz – 1GHz

Channel: Mid




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM



Plot # 6 Radiated Emissions: 1 GHz - 3 GHz

Channel: Mid




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM

Plot # 7 Radiated Emissions: 3 GHz – 18 GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Comment
3761.000	-45.65	-13.00	32.65	500.0	1000.000	185.0	H	187.0	-101.8	
5641.500	-57.67	-13.00	44.67	500.0	1000.000	196.0	V	217.0	-99.5	
7522.000	-57.71	-13.00	44.71	500.0	1000.000	140.0	H	206.0	-95.3	
9402.000	-58.10	-13.00	45.10	500.0	1000.000	195.0	V	238.0	-93.4	




Preview Result 1-PK+ FCC Licensed -13dBm Final_Result RMS



Plot # 8 Radiated Emissions: 18 GHz – 22 GHz

Channel: Mid




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm
Final_Result RMS Final_Result PK+



Plot # 9 Radiated Emissions: 30 MHz - 1 GHz


Channel: High



Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM

Plot # 10 Radiated Emissions: 1 GHz - 3 GHz

Channel: High




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM

Plot # 11 Radiated Emissions: 3 GHz - 18 GHz


Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Comment
3819.000	-42.53	-13.00	29.53	500.0	1000.000	206.0	H	220.0	-101.7	
5728.500	-54.44	-13.00	41.44	500.0	1000.000	162.0	V	246.0	-98.6	
7637.500	-58.27	-13.00	45.27	500.0	1000.000	140.0	H	2.0	-95.7	
9547.500	-60.06	-13.00	47.06	500.0	1000.000	153.0	V	151.0	-93.5	




Preview Result 1-PK+ FCC Licensed -13dBm Final Result RMS

LTE Band 4**Plot # 12 Radiated Emissions: 30 MHz - 1 GHz****Channel: Low**

— Preview Result 1-PK+ * Critical_Freqs PK+ — FCC Licensed -13dBm ◆ Final_Result RM

Plot # 13 Radiated Emissions: 1 GHz - 3 GHz

Channel: Low




Preview Result 1-PK+ FCC Licensed -13dBm Final_Result RMS

Plot # 14 Radiated Emissions: 3 GHz - 18 GHz

Channel: Low

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Comment
3430.750	-50.74	-13.00	37.74	500.0	1000.000	125.0	V	170.0	-105.1	
5146.000	-50.70	-13.00	37.70	500.0	1000.000	132.0	V	52.0	-101.5	
6861.500	-57.21	-13.00	44.21	500.0	1000.000	228.0	H	328.0	-98.2	




Preview Result 1-PK+ FCC Licensed -13dBm Final_Result RMS



Plot # 15 Radiated Emissions: 9 kHz - 30 MHz

Channel: Mid




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm
Final_Result RMS Final_Result PK+



Plot # 16 Radiated Emissions: 30 MHz – 1 GHz


Channel: Mid



Preview Result1-PK+ Final_Result RMS Critical_Freqs PK+ Final_Result PK+ FCC Licensed -13dBm

Plot # 17 Radiated Emissions: 1 GHz - 3 GHz

Channel: Mid




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm ◆ Final_Result RM

Plot # 18 Radiated Emissions: 3 GHz – 18GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Comment
3465.000	-51.53	-13.00	38.53	500.0	1000.000	175.0	H	168.0	-103.1	
5198.500	-51.14	-13.00	38.14	500.0	1000.000	140.0	H	37.0	-99.2	
6932.000	-51.49	-13.00	38.49	500.0	1000.000	152.0	H	99.0	-95.6	




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS



Plot # 19 Radiated Emissions: 30 MHz - 1 GHz


Channel: High



Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM

Plot # 20 Radiated Emissions: 1 GHz - 3 GHz

Channel: High




Preview Result 1-PK+ FCC Licensed -13dBm Final_Result RMS

Plot # 21 Radiated Emissions: 3 GHz - 18 GHz

Channel: High

Final Result


Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Comment
3506.500	-55.33	-13.00	42.33	500.0	1000.000	160.0	V	166.0	-104.8	
5260.000	-53.28	-13.00	40.28	500.0	1000.000	184.0	V	50.0	-101.0	
7013.750	-56.12	-13.00	43.12	500.0	1000.000	202.0	V	250.0	-98.3	
8766.750	-62.45	-13.00	49.45	500.0	1000.000	244.0	V	284.0	-97.3	



Preview Result 1-PK+ FCC Licensed -13dBm Final_Result RMS

LTE Band 12**Plot # 22 Radiated Emissions: 30 MHz – 1GHz****Channel: Low****Final Result**


Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Comment
213.694	-61.15	-13.00	48.15	500.0	100.000	100.0	H	72.0	-81.5	
486.240	-57.53	-13.00	44.53	500.0	100.000	265.0	H	61.0	-75.6	
914.252	-48.16	-13.00	35.16	500.0	100.000	100.0	H	196.0	-69.4	





Plot # 23 Radiated Emissions: 1 GHz - 3 GHz

Channel: Low




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM



Plot # 24 Radiated Emissions: 3 GHz – 9 GHz

Channel: Low




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM



Plot # 25 Radiated Emissions: 9 kHz - 30 MHz

Channel: Mid




Preview Result 1-PK+ Final_Result RMS
Critical_Freqs PK+ Final_Result PK+
FCC Licensed -13dBm

Plot # 26 Radiated Emissions: 30 MHz – 1GHz

Channel: Mid


Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Comment
213.282	-82.82	-13.00	69.82	500.0	100.000	141.0	H	235.0	-81.6	
494.776	-78.47	-13.00	65.47	500.0	100.000	275.0	H	350.0	-75.4	
921.600	-68.63	-13.00	55.63	500.0	100.000	107.0	H	345.0	-69.1	



Plot # 27 Radiated Emissions: 1 GHz - 3 GHz

Channel: Mid




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM



Plot # 28 Radiated Emissions: 3 GHz – 9 GHz

Channel: Mid




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM



Plot # 29 Radiated Emissions: 30 MHz – 1GHz


Channel: High



Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm ◆ Final_Result RM

Plot # 30 Radiated Emissions: 1 GHz - 3 GHz

Channel: High




Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM



Plot # 31 Radiated Emissions: 3 GHz – 9 GHz

Channel: High



Preview Result 1-PK+ * Critical_Freqs PK+ FCC Licensed -13dBm Final_Result RM

8 Test setup photo

Setup photos are included in supporting file name: "EMC_GARMI-077-20001_ISED_Setup_Photos_R1.pdf"

9 Test Equipment And Ancillaries Used For Testing

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
ACTIVE LOOP ANTENNA	ETS LINDGREN	6507	00161344	3 YEARS	10/26/2017
BILOG ANTENNA	TESEO	CBL 6141B	41106	3 YEARS	11/01/2017
HORN ANTENNA	ETS.LINDGREN	3115	00035111	3 YEARS	04/17/2019
HORN ANTENNA	ETS LINDGREN	3117	00169547	3 YEARS	09/01/2020
HORN ANTENNA	ETS LINDGREN	3116C	00169535	3 YEARS	09/24/2017
WIDEBAND RADIO COMMUNICATION	R&S	CMW500	109825	3 YEARS	02/12/2018
SIGNAL ANALYZER	R&S	FSV 40	101022	2 YEARS	07/15/2019
COMPACT DIGITAL BAROMETER	CONTROL COMPANY	10510-922	200236891	3 YEARS	04/13/2020
DIGITAL THRMOMETER	CONTROL COMPANY	36934-164	191871994	2 YEARS	01/10/2019

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels.

Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

10 Revision History

Date	Report Name	Changes to report	Report prepared by
2020-10-20	EMC_GARMI-077-20001_FCC_24_27_ISED	Initial version	Yuchan Lu
2020-11-19	EMC_GARMI-077-20001_FCC_24_27_ISED_R1	Changed Marketing name to "N/A"; Changed the client's and manufacture's addresses; Removed the WLAN FCC and IC IDs; Removed FVIN	Yuchan Lu

<<The End>>