

FCC ID : IPUWAMPLIFIER

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Antenna gain: 2.0dBi

802.11b:

Channel	Channel Frequency (MHz)	Output power (dBm)	Output power (mW)	Antenna Gain Numeric	Power density at 20cm(mW/cm2)	Power density Limits (mW/cm2)
1	2412	19.63	91.83	1.5849	0.0290	1
6	2437	20.08	101.86	1.5849	0.0321	1
11	2462	20.55	113.50	1.5849	0.0358	1

802.11g:

Channel	Channel Frequency (MHz)	Output power (dBm)	Output power (mW)	Antenna Gain Numeric	Power density at 20cm(mW/cm ²)	Power density Limits (mW/cm ²)
1	2412	22.00	158.49	1.5849	0.0500	1
6	2437	21.99	158.12	1.5849	0.0499	1
11	2462	22.48	177.01	1.5849	0.0558	1

802.11n HT20

Channel	Channel Frequency (MHz)	Output power (dBm)	Output power (mW)	Antenna Gain Numeric	Power density at 20cm(mW/cm ²)	Power density Limits (mW/cm ²)
1	2412	21.88	154.17	1.5849	0.0486	1
6	2437	21.12	129.42	1.5849	0.0408	1
11	2462	22.17	164.82	1.5849	0.0520	1

802.11n HT40

Channel	Channel Frequency (MHz)	Output power (dBm)	Output power (mW)	Antenna Gain Numeric	Power density at 20cm(mW/cm ²)	Power density Limits (mW/cm ²)
3	2422	21.90	154.88	1.5849	0.0488	1
6	2437	21.63	145.55	1.5849	0.0459	1
9	2452	21.40	138.04	1.5849	0.0435	1

802.11a

Channel	Channel Frequency (MHz)	Output power (dBm)	Output power (mW)	Antenna Gain Numeric	Power density at 20cm(mW/cm ²)	Power density Limits (mW/cm ²)
36	5180	14.46	27.93	1.5849	0.0088	1
42	5210	14.43	27.73	1.5849	0.0087	1
48	5240	15.09	32.28	1.5849	0.0102	1

802.11n HT20

Channel	Channel Frequency (MHz)	Output power (dBm)	Output power (mW)	Antenna Gain Numeric	Power density at 20cm(mW/cm ²)	Power density Limits (mW/cm ²)
36	5180	14.12	25.82	1.5849	0.0081	1
42	5210	14.5	28.18	1.5849	0.0089	1
48	5240	14.32	27.04	1.5849	0.0085	1

802.11n HT40

Channel	Channel Frequency (MHz)	Output power (dBm)	Output power (mW)	Antenna Gain Numeric	Power density at 20cm(mW/cm ²)	Power density Limits (mW/cm ²)
38	5190	13.16	20.70	1.5849	0.0065	1
46	5230	13.31	21.43	1.5849	0.0068	1